



## MATERIAL SAFETY DATA SHEET

<b>Supplier:</b>	ValvTect Petroleum Products A Division of Kop-Coat, Inc. 3400 Dundee Road Northbrook, IL 60062	<b>EMERGENCIES:</b> Health/spills:.....: Chemtrec Assistance.....: Chemtrec Outside USA.....:	800-548-0489 800-424-9300 703-527-3887
		<b>ValvTect Petroleum Products</b> Product Information.....: Outside USA.....:	847-272-2278 847-272-2278

### 1. Product Information

<b>Product name</b>	ValvTect Ethanol Gasoline Treatment 12 oz.
<b>Product code</b>	VEGA12BK\1

**Issuing date:** 07/08/2010

**Contact person:**

Environmental Health and Safety  
Manager

### 2. Hazards identification

#### Emergency Overview

**Appearance:**

Clear liquid, which may contain a colorant

**Odor:**

Hydrocarbon

**Hazards:**

WARNING!

Harmful if swallowed or inhaled. Causes eye and skin irritation. May be harmful if absorbed through skin.

#### Potential health effects

**Primary Routes of Entry:**

Eye contact, ingestion, skin contact, inhalation, and absorption.

**Eye contact:**

May cause moderate to severe eye irritation. Symptoms may include stinging, tearing, redness and swelling of eyes. Not expected to cause permanent damage if promptly rinsed from eyes.

**Ingestion:**

May cause gastrointestinal distress. Symptoms may include irritation to the mouth, throat and stomach and gastrointestinal disturbances such as nausea, vomiting or diarrhea and effects similar to those described in the Inhalation section. Aspiration of this product into the lungs during ingestion, gagging or vomiting may cause lung damage, which can be fatal.

**Skin contact:**

May cause skin irritation. Symptoms may include dryness, itching, burning sensation, redness, cracking and swelling depending on the extent of exposure. May be harmful if absorbed through the skin in toxic amounts and cause systemic effects.

**Inhalation:**

May cause irritation to the nose, throat and respiratory tract. Inhalation of high concentrations of vapors may cause respiratory tract irritation and central nervous system depression. Symptoms may include headache, nausea, dizziness and drowsiness. Continued inhalation may result in unconsciousness or death.

**Chronic effects:**

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Prolonged or repeated dermal exposure to this product can cause skin dermatitis characterized by red, dry, scaly skin.

**Target Organs:** Not Determined

**This product does not contain carcinogens or potential carcinogens as listed by IARC or NTP.**

### 3. Composition/information on ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Weight %</u>	<u>Carc</u>
Petroleum distillates, light aromatic	64742-95-6	30 - 50	
1,2,4-Trimethylbenzene	95-63-6	20 - 30	
Ethylene glycol monobutyl ether	111-76-2	10 - 20	
Petroleum Distillates, hydrotreated (middle)	64742-46-7	1 - 10	
Xylene	1330-20-7	1 - 10	
Alkylamines	Proprietary	1 - 10	
Tertiary Butylated Phenol	68610-06-0	1 - 10	
solvent naphtha (petroleum), heavy aromatic	64742-94-5	1 - 10	
Cumene	98-82-8	1 - 10	

### 4. FIRST AID MEASURES

**Eye contact:**

Quickly and gently blot or brush chemical off the face. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into unaffected eye or onto the face. Call poison control center, hospital emergency room, or physician immediately.

**Ingestion:**

NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 2 to 8 oz. (60 to 240 mL) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water again. Immediately obtain medical advice.

**Skin contact:**

As quickly as possible, remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Immediately wash with lukewarm, gently flowing water and non-abrasive soap for 15-20 minutes. Immediately obtain medical advice. Completely decontaminate clothing, shoes and leather goods before reuse or discard.

**Inhalation:**

Remove to fresh air. If not breathing, administer CPR until help arrives or the victim starts to breathe on his own. If breathing is difficult, give oxygen. Call poison control center, hospital emergency room, or physician immediately. Keep victim quiet and warm until emergency help arrives.

**Note to Physician :**

There is no specific antidote for effects from overexposure to this material. Treatment should be directed at the control of symptoms and the clinical condition.

## 5. FIRE-FIGHTING MEASURES

**Flash point** 106 deg F

**Extinguishing media:**

Use alcohol foam, dry chemical, carbon dioxide or any Class B fire extinguishing agent. Water may be unsuitable for extinguishing fires. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

**Hazardous combustion products:**

See Section 10 for potential decomposition products.

**Protective equipment and precautions for firefighters:**

Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal & Environmental Precautions:**

Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal using non-sparking tools. Follow personal protective equipment recommendations found in Section 8. Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

**Methods of Containment & Clean-up and Other Information:**

This product, if released in large enough quantities, may need to be reported to the US Coast Guard National Response Center at 1-800-424-8802. Contain spills with dikes and absorbents (sand, earth, dry chemical absorbent) to prevent migration and entry into waterways.

## 7. HANDLING AND STORAGE

**Handling:**

Keep container closed and upright when not in use. To prevent generation of static discharges, use bonding/grounding connection when transferring material. Vapors may accumulate and travel to distant ignition sources and flashback. Extinguish all sources of ignition including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Since empty containers may retain product residue and flammable vapors, observe precautions even after container is emptied. Do not cut, puncture, or weld on or near empty containers. Do not smoke where product is used or stored. Avoid contact with eyes, skin or clothing. Avoid inhalation (vapor, mist, dust or fume, as applicable). Use only with adequate ventilation. Observe good personal hygiene practices and recommended procedures. Wash thoroughly after handling.

**Storage:**

Store in areas/buildings designed to comply with OSHA 1910.106. Store away from sources of ignition and heat. Keep containers closed when not in use. Store in cool, well ventilated space away from incompatible materials.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Z-1 PEL</u>	<u>Z-2 PEL</u>	<u>ACGIH TLV</u>
Petroleum distillates, light aromatic	64742-95-6			
1,2,4-Trimethylbenzene	95-63-6			25 PPM
Ethylene glycol monobutyl ether	111-76-2	240 MGM3 (50 PPM)		20 PPM
Petroleum Distillates, hydrotreated (middle)	64742-46-7			
Xylene	1330-20-7	435 MGM3 (100 PPM)		100 PPM
Alkylamines	Proprietary			
Tertiary Butylated Phenol	68610-06-0			
solvent naphtha (petroleum), heavy aromatic	64742-94-5			
Cumene	98-82-8	245 MGM3 (50 PPM)		50 PPM

**Engineering measures:**

Use adequate ventilation to maintain airborne concentrations at levels below permissible or recommended occupational exposure limits. Supplementary local exhaust ventilation may be necessary in poorly ventilated spaces, during spraying, heating or other non-routine activities.

**Eye/face protection:**

Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.

**Skin protection:**

Chemical-resistant, flexible-type gloves (neoprene, nitrile or equal) to prevent contact. Gloves should be rinsed and removed immediately after use. Wash hands after removing gloves. Wear chemical-resistant clothing (e.g. apron, pants, coveralls) and safety footwear as appropriate.

**Respiratory protection:**

Respiratory protection may be necessary under certain use conditions. Under such conditions, an appropriate, properly fitted NIOSH-approved respirator must be worn. If respirators are used, a program should be instituted to assure compliance with 29 CFR 1910.34 and 42 CFR 84.

**General hygiene considerations:**

Facilities utilizing this material should be equipped with an eyewash station and safety shower. Thoroughly clean shoes and wash contaminated clothes before reuse.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical state</b>	Liquid
<b>Appearance:</b>	Clear liquid, which may contain a colorant
<b>Odor</b>	Hydrocarbon
<b>pH</b>	Not applicable.
<b>Boiling point</b>	Not applicable.
<b>Flash point</b>	106 deg F
<b>Solubility in water:</b>	Insoluble
<b>Specific Gravity:</b>	0.872
<b>Weight per gallon (LB/GAL) :</b>	7.27
<b>Evaporation rate (n-Butyl acetate = 1):</b>	not determined
<b>Volatile by Weight (including water and exempt compounds) (%):</b>	not determined
<b>Volatile Organic Content (VOC):</b>	not determined

## 10. STABILITY AND REACTIVITY

**Stability:**

Stable under normal conditions.

**Incompatibility:**

Oxidizing and reducing agents. Keep away from heat, sparks and open flames.

**Hazardous decomposition products:**

Carbon monoxide, carbon dioxide, oxides of nitrogen and other toxic organic compounds.

## 11. TOXICOLOGICAL INFORMATION

Ethylene glycol monobutyl ether (CAS#111-76-2): Laboratory studies on experimental animals indicate that exposure may cause red blood cell damage and damage to the kidney and liver. These effects have not been observed in humans. Laboratory animal studies have reported adverse reproductive and developmental effects from overexposure.

Xylene: Laboratory animals exposed to high levels of xylene showed evidence of effects on the liver, kidneys, lungs, spleen, and caused hearing loss. Rats exposed during pregnancy to xylene showed fetotoxic effects.

Tertiary butylated phenol (CAS# 68610-06-0): Higher or repeated exposures may cause abnormal blood clotting system function with easy bruising or bleeding.

## 12. ECOLOGICAL INFORMATION

This product contains a component that is toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

## 13. DISPOSAL CONSIDERATIONS

Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

## 14. TRANSPORT INFORMATION

**Transportation:**

This product is not regulated by the U.S. DOT when shipped by ground in containers < 119 gallons.

**By Ground:****DOT Hazard Class:**

3

**DOT Proper Shipping Name:**

Combustible liquid, n.o.s. (petroleum distillates, 1,2,4-trimethylbenzene) for containers > 119 gal.

**DOT Packing Group:**

III

**DOT UN Number:**

NA1993

**By Air:**

**IATA Hazard Class:** 3

**IATA Proper Shipping Name:** Flammable liquid, n.os. (petroleum distillates, 1,2,4-trimethylbenzene)

**IATA Packing Group:** III

**IATA UN Number:** UN1993

**By Sea:**

**IMDG Hazard Class:** 3

**IMDG Proper Shipping Name:** Flammable liquid, n.os. (petroleum distillates, 1,2,4-trimethylbenzene)

**IMDG Packing Group:** III

**IMDG UN Number:** UN1993

15. REGULATORY INFORMATION

**EPA registration number:** Not applicable.

**Pest Registration Act number:** Not applicable.

**Other:**  
Not applicable.

Chemical Name	CAS-No.	TSCA 12B	SARA 313	TSCA	DSL	EINECS	Prop 65	Whmis
Petroleum distillates, light aromatic	64742-95-6			*	*	*		*
1,2,4-Trimethylbenzene	95-63-6		*	*	*	*		*
Ethylene glycol monobutyl ether	111-76-2		*	*	*	*		*
Petroleum Distillates, hydrotreated (middle)	64742-46-7			*	*	*		
Xylene	1330-20-7		*	*	*	*		*
Alkylamines	Proprietary							
Tertiary Butylated Phenol	68610-06-0			*	*	*		
solvent naphtha (petroleum), heavy aromatic	64742-94-5			*	*	*		*
Cumene	98-82-8		*	*	*	*	*	*

16. OTHER INFORMATION

**HMIS Health: 2\***      **HMIS Flammability: 2**      **HMIS Physical Hazard: 0**

**NFPA Health: 2**      **NFPA Flammability: 2**      **NFPA Instability/Reactivity: 0**

**NOTICE:** This document is generated for the purpose of distributing health, safety, and environmental data. The information on this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed, or implied, regarding correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. Kop-Coat makes no warranty with respect thereto and disclaims all liability from reliance thereon.

**Key:**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS	Chemical Abstract Service Registry Number
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act
CERCLA RQ	CERCLA Reportable Quantity
CFR	Code of Federal Regulations
CPR	Cardiopulmonary resuscitation

<b>DSL</b>	<b>Domestic Substances List of Canada</b>
<b>EINECS</b>	<b>European Inventory of Existing Chemical Substances</b>
<b>EPCRA</b>	<b>Emergency Planning and Community Right-to-know Act</b>
<b>EPCRA EHS</b>	<b>EPCRA Extremely Hazardous Substance</b>
<b>EPCRA TPQ</b>	<b>EPCRA Threshold Planning Quantity</b>
<b>oF</b>	<b>Fahrenheit degrees</b>
<b>g/l</b>	<b>Grams per liter</b>
<b>gal</b>	<b>Gallons</b>
<b>Group A3</b>	<b>Carcinogen Category - Confirmed Animal Carcinogen with Unknown Relevance to Humans</b>
<b>Group A4</b>	<b>Carcinogen Category - Not Classifiable as a Human Carcinogen</b>
<b>HMIS</b>	<b>Hazardous Materials Identification System - Chemical Rating</b>
<b>IARC</b>	<b>International Agency for Research on Cancer</b>
<b>lbs or LBS</b>	<b>Pounds</b>
<b>MGM3</b>	<b>Milligrams per cubic meter</b>
<b>MIR</b>	<b>Maximum Incremental Reactivity</b>
<b>MSDS</b>	<b>Material Safety Data Sheet</b>
<b>NFPA</b>	<b>National Fire Protection Association</b>
<b>NIOSH</b>	<b>National Institute for Occupational Safety and Health</b>
<b>NTP</b>	<b>National Toxicology Program</b>
<b>OSHA</b>	<b>Occupational Safety and Health Administration</b>
<b>PEL</b>	<b>Permissible Exposure Limit</b>
<b>PPM</b>	<b>Parts per million</b>
<b>Proposition 65</b>	<b>California's Safe Drinking Water and Toxic Enforcement Act</b>
<b>SARA</b>	<b>Superfund Amendments and Reauthorization Act</b>
<b>TLV</b>	<b>Threshold Limit Value</b>
<b>TSCA</b>	<b>Toxic Substances Control Act</b>
<b>USEPA</b>	<b>United States Environmental Protection Agency</b>
<b>VOC</b>	<b>Volatile Organic Compound</b>
<b>VOL</b>	<b>Volume</b>
<b>WT</b>	<b>Weight</b>
<b>WHMIS</b>	<b>Canadian Workplace Hazardous Materials Information System</b>
<b>UN</b>	<b>United Nations</b>

ANSI KC 1.74