■ NetApp

Release notes

e-series

NetApp May 03, 2022

This PDF was generated from https://docs.netapp.com/us-en/e-series/whats-new.html on May 03, 2022. Always check docs.netapp.com for the latest.

Table of Contents

| Release notes | | |
 | 1 |
|---------------|--------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|---|
| What's new i | n SANtricity | / OS |
 | 1 |
| Release note | s | |
 | 6 |

Release notes

What's new in SANtricity OS

The following table describes new features in SANtricity OS.



The Resource Provisioning capability, which is available only on EF300 and EF600 systems with specific NVMe SSDs, has been disabled in Versions 11.71 and 11.72 so that outstanding issues can be resolved. Note that in some System Manager views, components might be reported as resource-provisioning (or DULBE) capable, but the ability to create resource- provisioned volumes is not available.

New features in Version 11.72

New feature	Description
SNMPv3 support	SNMPv3 is now supported for alert notifications, configurable in Settings > Alerts . SNMPv3 provides security through strong authentication and data encryption.
Support replicating keys to multiple key servers	For external key management for self-encrypting drives, the Create External Key Management dialog includes a new option for adding multiple key servers.
Updated browser versions	System Manager minimum browser versions have been updated.

New feature	Description
EF300 expansion	This release provides support for expansion to SAS-3 enclosures for the EF300 storage system. With this expansion, the 4KiB-block NVMe SSDs can coexist with 512e SAS SSDs and HDDs. However, drives with different block sizes cannot be configured in the same pool or volume group.
FEC mode option in iSCSI configuration	For storage arrays using the 25Gb iSCSI host interface card, a new option is available for setting the Forward Error Correction (FEC) mode when you configure iSCSI ports.
Remote Storage Volumes	The optional Remote Storage Volumes feature allows you to import volumes from a remote storage system to a local E- Series storage system using an iSCSI connection. The remote storage may be the same brand as your E-Series system or from a different storage vendor, as long as it is accessible via iSCSI.

New feature	Description
Sanitize (erase) capability added for non-FDE drives	The drive sanitize feature now includes non-FDE drives in the procedure. From the Hardware page, you can open the Drive's context menu and select "Erase" (previously, this selection was "Secure Erase").
Secure connection for email alerts	To enable encrypted email notifications, you can optionally configure outgoing emails (alerts, ASUP dispatches) to supply authentication credentials. Encryption types include SMTPS and STARTTLS.
AutoSupport additions	An alert now appears in the Notifications area when AutoSupport is not enabled.
Syslog alert format change	The Syslog alert format now supports RFC 5424.

New feature	Description
New storage system model – EF300	This release introduces the EF300 low-cost all-NVMe-flash storage system. The EF300 includes 24 NVME SSD drives and a single host interface card (HIC) per controller. The supported NVMe over Fabrics host interfaces include NVMe over IB, NVMe over RoCE, and NVMe over FC. The supported SCSI interfaces include FC, IB over iSER, and IB over SRP. Multiple EF300 storage systems and other E- Series storage systems can be viewed and managed in Unified Manager.
New Resource Provisioning feature (EF300 and EF600 only)	The Resource Provisioning feature is new for the EF300 and EF600 storage systems. Resource-provisioned volumes can be put in use immediately with no background initialization process.
Add 512e block size option (EF300 and EF600 only)	For EF300 and EF600 storage systems, a volume can be set to support a 512-byte or a 4KiB block size. The 512e capability has been added to allow support of the iSCSI host interface and the VMware OS. If possible, System Manager suggests the appropriate default value.
New option for sending AutoSupport dispatches on demand	A new Send AutoSupport Dispatch feature allows you to send data to technical support without waiting for a scheduled dispatch. This option is available in the AutoSupport tab of the Support Center.

New feature	Description
External Key Management Server enhancements	The feature for connecting to an external key management server includes the following enhancements: • Bypass the function for creating a backup key. • Choose an intermediate certificate for the key management server, in addition to the client and server certificates.
Certificate enhancements	This release allows for using an external tool such as OpenSSL to generate a Certificate Signing Request (CSR), which also requires you to import a private key file along with the signed certificate.
New Offline Initialization feature for Volume Groups	For volume creation, System Manager provides a method for skipping the host assignment step so that newly created volumes are initialized offline. This capability is applicable only to RAID volume groups on SAS drives (i.e., not to dynamic disk pools or to the NVMe SSDs included in the EF300 and EF600 storage systems). This feature is for workloads that need to have the volumes at full performance when usage begins, rather than having initialization run in the background.
New Collect Configuration Data feature	This new feature saves RAID configuration data from the controller, which includes all data for volume groups and disk pools (the same information as the CLI command for save storageArray dbmDatabase). This capability has been added to aid technical support and is located in the Diagnostics tab of the Support Center.
Change default preservation capacity for disk pools in 12 drive case	Previously, a 12-drive disk pool was created with enough preservation (spare) capacity to cover two drives. The default is now changed to handle a single drive failure to offer a more cost-effective small pool default.

New feature	Description
Downloadable CLI	System Manager for the E5700, EF570, E2800, and EF280 arrays now includes the ability to download and install the SANtricity command line interface (CLI) via a link in the Settings > System > Add-ons page. This is the https-based version of the CLI (also referred to as "Secure CLI"). This capability was previously released with the EF600 array.

New feature	Description
Mirroring configuration changes in System Manager and Unified Manager	The tasks for configuring synchronous and asynchronous mirrored pairs have moved from System Manager to Unified Manager. All other tasks for managing mirrored pairs remain in System Manager.
New 200Gb-capable HIC (EF600 arrays only)	This release adds a new 200Gb-capable HIC for EF600 storage arrays. Interfaces supported are NVMe/IB, NVMe/RoCE, and iSER/IB. Additionally, 100Gb SRP/IB is supported.
Additional options on 100Gb HIC (EF600 arrays only)	On the existing 100Gb HIC, iSER/IB and SRP/IB interfaces are now supported for EF600 storage arrays. (These interfaces are already supported for EF570 and E5700 arrays.)
Delete mail server in System Manager	System Manager allowed a mail server to be configured, but did not have an easy mechanism to remove it. With this release, the mail server configuration in System Manager can now be removed from Alerts, so that alerts are no longer sent to the email addresses associated with this mail server.
Optimization capacity adjustments for pools and volume groups (SSD drives only) in System Manager	For SSD drives, a new optimization capacity slider is available in System Manager for the Pool settings and Volume Group settings. The slider enables you to adjust the balance of available capacity versus SSD write performance and drive wear life.
New host types in System Manager	When you create new hosts in System Manager, the presented host options are now organized into three categories to provide better guidance: Common, Uncommon, and Use only if directed.

New feature	Description
Fibre Channel support for the EF600	This release adds Fibre Channel host support for the EF600 storage system. This is the first SCSI host supported by the EF600, which initially released with all NVMe over Fabrics host protocols. A single controller for the EF600 can be viewed and managed in System Manager. Multiple EF600 storage systems can be viewed and managed in Unified Manager.
Password requirements for admin user	For first-time login in Unified Manager, you must now enter a password for the administrator user. There is no longer a default "admin" password.

New feature	Description
New storage system model – EF600	This release offers a new EF600 all-flash storage system. The EF600 includes NVMe-oF host interfaces and NVMe SSDs.
	The EF600 significantly increases throughput and reduces latency. The supported host interfaces include NVMe over IB, NVMe over RoCE, and NVMe over FC, which can be configured in System Manager. Multiple EF600 storage systems can be viewed and managed in Unified Manager.
Downloadable CLI	System Manager now includes the ability to download and install the SANtricity command line interface (CLI) via a link in the Settings > System > Add-ons page. This is the https- based version of the CLI. The legacy SANtricity Storage Manager package continues to include the CLI as well.

This version includes only minor enhancements and fixes.

New features in Version 11.52

New feature	Description
NVMe over FC host interface	An NVMe over Fibre Channel host connection can now be ordered for EF570 or E5700 E-Series controllers, in addition to the existing support for NVMe over RoCE and NVMe over InfiniBand. System Manager includes statistics for this new connection type in Settings > System under "NVMe over Fibre Channel details."

New features in Version 11.51

This version includes only minor enhancements and fixes.

New feature	Description
NVMe over RoCE interface	An NVMe over RoCE host connection can now be ordered for EF570 or E5700 E-Series controllers. System Manager includes new functions for configuring the network connection to the host (available from the Hardware page or from Settings > System), and functions for viewing data about the NVMe over RoCE connections to the storage array (available from Support > Support Center or from Settings > System).
Manual drive selection for volume groups	In addition to convenient automatic selection, a new option is available for selecting individual drives when you create a volume group. In general, automatic drive selection is recommended, but the individual drive selection option is available for environments with special drive location requirements.
SANtricity Unified Manager	Unified Manager is a separately installed, browser-based application that discovers and manages E2800 series controllers and E5700 series controllers. While this new application is not a new feature of System Manager, it does provide a new browser-based enterprise framework from which System Manager can be launched for discovered storage arrays. The new Unified Manager can be downloaded from the Support software downloads area.

Release notes

Release Notes are available outside this site. You will be prompted to log in using your NetApp Support Site credentials.

- 11.70 Release notes
- 11.60 Release notes
- 11.50 Release notes

Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.