COMPACT SPEAKER CHEAT SHEET · SHORT EDITION (EN)

Speaker Cheat Sheet (Short Edition · English) — Louis Renner Masterclass

Presenter: Clemens Kunert · Louis Renner GmbH (Meuselwitz Headquarters, Germany)
Scope: 33 Slides (72 Sub-Sheets) across 5 Chapters · Lectern Quick-Reference with Exact Metrics, Interactions & Video Cues

LOUIS RENNER GMBH
Since 1882 · Meuselwitz Headquarters

Live Stage Controls: → / Space = next step / next slide · ← = back · Click any chapter card on **Slide 02** to jump directly · ▸ = live interaction · ▶ = video auto-plays.

Chapter 1: Introduction, Heritage & Meuselwitz Plant (Slides 01–04)

SLIDE 01 LOUIS RENNER

- **Core Message:** *Over 140 Years of Tradition (Since 1882)* — action and hammerhead precision from one source, fully united since 2025/2026 at our modernized **Meuselwitz** headquarters.
- **Opening Line:** *"Welcome everyone — today we will travel from uncompressed Merino wool in Wurzen through our unified hammerhead manufacturing in Meuselwitz and the drop-in Yamaha Kit all the way to the physics and master craft of concert voicing."*

SLIDE 02 Structure and Chapters at a Glance

- ▸ Interaction: Click any of the **5 chapter cards** to jump straight into that module:
  1. **History & Meuselwitz (Slides 3–4):** 9 milestones since 1882, 14 construction phases & interior drone flight in Meuselwitz.
  2. **Wurzen Felt Production (Slides 5–10):** FFW since 1783, wool blend, carding, 4 fulling pillars, `56%` density, unsanded felt sheets.
  3. **Hammerhead Production (Slides 11–18):** Felt storage, Weickert Special SEM, cutting & underfelt, 4 moulding woods & mass curve, kettle & side jaws, CNC & robotic calibration, riveting & boring.
  4. **Yamaha Kit C1–C3 (Slides 19–24):** Ready-to-mount set in `4–5 h` on site, India field proof & spectral analysis (H_1–H_{12} up to C_8).
  5. **Voicing & Open Q&A (Slides 25–33):** A_1 partial buildup, complex spring, clock model, 3-string plane, fine & una corda voicing, lacquer/ironing (`max. 135 °C`) & open Q&A.

SLIDE 03 140+ Years of Tradition & Perfection (1882 – Today)

- ▸ Interaction: Step through all **9 milestones** with → / Space (▶ video on Milestones 8 & 9):
  1. **1882 Founded in Stuttgart:** Louis Renner opens his workshop on Heusteigstrasse — specialized precision piano actions forming the historic root of Meuselwitz.
  2. **1906 In-House Hammerheads:** Actions and hammerheads engineered together under one roof using proprietary presses (from Cristofori's 1700 leather-capped roll to the tensioned felt hammer).
  3. **1911 Grand Actions & Electric Drives:** Building on Érard's double escapement; Oscar Renner converts belt shafts to hundreds of low-vibration individual electric motors.
  4. **1944 Wartime Destruction & Rebuilding:** Complete loss of the Stuttgart plant on July 24/25, 1944 — immediate reconstruction led by the skilled workforce (*"Renner will be rebuilt"*).
  5. **1951–1955 Dr. Manfred Renner (3rd Generation):** Assumes leadership in **1951**, completes Stuttgart rebuilding in **1955**, and expands global exports to premier piano makers.
  6. **1990 Reunification & Zeitz:** Acquisition of Piano Union's action plant in Zeitz — retains skilled specialists, safeguards major customers (e.g., Schimmel `> 40 pianos/day`), and establishes our Central German base.
  7. **2011 Two Core Sites:** Relocation from Zeitz into a modern **`6,800 m²`** **Meuselwitz hall** (actions & hammerheads) + new **Gärtringen facility** (specialized woodworking & administration).
  8. **2019 Steinway & Sons (▶ Video):** Entrusted by Clemens von Arnim (`† 2024` , honored in grateful memory) to Steinway & Sons with **full operational autonomy** — continuing open supply to **all** piano makers worldwide.
  9. **Today — Unified Meuselwitz Headquarters (▶ Drone Video):** Complete consolidation of wood, action, and hammerhead production under one roof with a new central filtration plant; warm gratitude to the Gärtringen workforce.

SLIDE 04 Construction Documentary: Building the Unified Meuselwitz Plant

- ▸ Interaction: **14 flipbook phases (`11.2025 – 09.2026`)** + ▶ **Interior Drone Flight** finale (`04.15`).
- **Key Facts to Cite:** Conversion completed **with zero production downtime** · automated vertical **shuttle storage lifts** · **40-ton, 12 m central filter tower (`120,000 m³/h` airflow)** lifted by 70-ton crane · rooftop HVAC maintaining **`45–50% RH`** year-round · relocation of hammerhead production (Phase 9) & molding shop (Phase 14).

Chapter 2: The Art of Felt Manufacturing – FFW Wurzen (Slides 05–10)

SLIDE 05 Filzfabrik Wurzen (FFW) – The Birthplace of Piano Hammer Felt

- ▸ Interaction: **6 historical era tabs** on the left + `⌕ Fiber Lens` on the right:
  1. **1783 Origin Wurzen:** Johann Dankegott Weickert founds the world's oldest industrial felt manufactory in Saxony's Mulde valley.
  2. **1847 1st Piano Hammer Felt:** Patzschke & Weickert replace uneven leather coverings with homogeneous hammer felt (aided by soft, low-mineral Mulde river water).
  3. **1850/51/67 World Expo Gold:** Gold medals in Leipzig (1850), London (1851) & Paris (1867) — Vienna, Paris, and London makers adopt Weickert felt.
  4. **1861 Mühlgraben Scale-Up:** Steam-powered precision fulling mills & gentle wool scouring in mineral-poor river water.
  5. **1906 Global Market Leader:** Up to `200,000` **pianos/year** equipped worldwide (Director Patzschke & 350 specialists; benchmark for Steinway NY).
  6. **Today — Weickert Spezial & Renner: 2010** revival of the 1903 original formula by the Brand family; **only** `~65 km` **proximity** between Wurzen and Meuselwitz enables face-to-face master calibration.

SLIDE 06 Pure Merino Wool & the Secret of Fiber Blending

- **Stage 01 (Raw Wool Selection): Uncompressed overseas bale delivery** (Argentina, South Africa, New Zealand/Australia) keeps microscopic keratin scales intact; strong natural crimp acts like millions of micro-springs; gentle scouring preserves natural **lanolin**.
- **Stage 02 (Fiber Formula):** Multi-stage pneumatic opening & climate conditioning in the FFW blending chamber; calibrated balance of **long tensile fibers** (crown tension) and **fine filler wool** (core support).

SLIDE 07 Carding: Parallel Fiber Alignment into Fine Fleece Webs

- **Process:** Fine **drum cards** gently comb the wool and impart a defined primary fiber course to the gossamer web; **cross-layered stacking** builds thickness, tensile strength, and wedge taper.
- **Voicing Link: Prerequisite for voicing** — only parallel-aligned fibers part cleanly when needled instead of being severed!

SLIDE 08 The 4 Pillars of Fulling: Steam, Pressure, Motion & Experience

- **The 4 Slide Cards: 1. Live Steam** (opens cuticle scales, softens keratin) · **2. Mechanical Pressure** (compresses fleece layers) · **3. Oscillating Motion** (interlocks barbed scales like burrs) · **4. Master Experience** (exact stopping point for natural springback).
- **Purity Rule:** Solely soft Muldental water and heat — **100% chemical-free, zero damping resins or glues**.

SLIDE 09 56% Fulling Density (0.56 g/cm³): The Natural Limit of Mechanical Fulling

- **Key Metric:** `56%` **(** `0.56 g/cm³` **)** is the physical ceiling of purely mechanical fiber compaction without synthetic resins.
- **Boundary:** Under-fulled felt stays spongy; forcing compaction past `56%` crushes keratin fibers (**felt breakage**, dead rebound).

SLIDE 10 Final Compaction & Tapered 36-Layer Anatomy

- ▸ Interaction: Toggle `Unsanded • Shape-Stable` ↔ `Sanded • Deformation`.
- **Left (Hammer & Stone):** Mechanical hammering with felt hammers and polished natural stones consolidates sheets to exact size (`56–68 Shore-A`) with **zero sanding removal**.
- **Right (36-Layer Wedge):** Staggered **shortened core webs** build the thick bass on the right while keeping treble thin on the left — enclosed by `2 × 6` **continuous outer tension webs**. Sanding severs those outer cords so fibers slip apart when pressed around the **hammer moulding**!

Chapter 3: Hammerhead Production in Meuselwitz (Slides 11–18)

SLIDE 11 Climate-Controlled Felt Storage & Assortment Diversity

- ▶ Video: Drone flight through the climate-controlled felt sheet inventory in Meuselwitz.
- **Top-Felt Inventory (** `30+ Grades` **):** Tapered FFW & Weickert sheets · regulated humidity, pheromone monitoring, and resting period relieve internal fulling stresses.
- **Underfelt Stock (** `6 Standard + Custom Colors` **): Red & Wine Red** (European concert grands) · **Orange** (concert & heritage restorations) · **Yellow** (Saxon/Viennese makers) · **Blue** (e.g., C. Bechstein), **Black** + bespoke dyeings.

SLIDE 12 "Weickert Special" – Exclusive to Renner

- ▸ Interaction: **SEM Zoom Viewer** (`1× Overview 1 mm` · `10× Fiber Detail 100 µm` · `22× Cuticle Zoom` · `⌕ Live Loupe` · `Felt Strip W 1512 K`).
- **Accredited STFI Test Report P2024 0903 (M. Kermer, ISO 3074 & Climate Cycle):**
  - `56%` **max. fulling density** (`0.56 g/cm³`) — peak purely mechanical density, zero chemical hardeners.
  - `0.36%` **residual wool grease (ISO 3074)** — `+38%` higher natural lanolin vs. `0.26%` comparison sample.
  - `−65%` **less swelling** in 48h climate cycling (only `4.81%` vs. `13.69%` thickness change) + intact epicuticle scales under SEM.

SLIDE 13 Felt Preparation: Top-Felt Cutting & Underfelt Profiling

- ▶ 2 Simultaneous Videos: Top-felt robotic cutting (top) · underfelt profile milling (bottom).
- **01 · Top-Felt Cutting (`≤ 1 mm Tolerance`):** 6-axis robot performs **crush-free cold cutting** without thermal glazing + **inline batch coding** on every strip.
- **02 · Underfelt Milling (`± 0.1 mm Tolerance`):** Elastic coupling bridge between rigid **hammer moulding** and top felt; feathered tails milled to `± 0.1 mm` guarantee balanced jaw load and a seamlessly closed contour right into the high treble.

SLIDE 14 The Hammer Moulding: Tonewoods, Properties & Profiles

- ▸ Interaction: Right media toggle `Profiles` (`Form A, B, US, CSB`) ↔ `Timber Stock`.
- **The 4 Moulding Tonewoods:**
  1. **Hornbeam (`Heavy • Stable`):** Very demanding to season — yet once properly dried, an **ideal, uniform moulding wood**.
  2. **Maple (`Heavy • Elastic`):** Often more elastic hardwood — though **irregular sugar deposits** carry a higher risk of variance.
  3. **American Walnut (`Very Light • Fine-Grained`): Highest-grade wood** — tight growth rings, long-fibered, and very light, **ideal for a brilliant treble**.
  4. **Kotibé / Mahogany (`Heavy • Oil-Rich`):** Comparatively heavy due to high natural oil content — reserved for specific applications.
- **Profiles: Symmetrical (`Form B · US · CSB`)** for Steinway, Bösendorfer, Bechstein, Yamaha, Kawai, Schimmel, Blüthner, Förster, Sauter · **Asymmetrical (`Form A`)** with offset moulding shoulder for vintage Bechstein grands & slender treble scales.

SLIDE 15 Optimal Hammerhead Weight Relative to String Weight

- ▸ Interaction: Zone buttons (`① Bass`, `② Break −1 g`, `③ Treble`), click keys `A₀–C₈`, simulator (`Too Light` / `Equilibrium` / `Too Heavy`) + `Test Strike`.
- **Mass Equilibrium (`Contact Time τc ↔ String Deflection`):**
  1. **Bass (`Keys 1–23`, copper-wound `90–210 g`):** The hammerhead (`~15.0 → 13.0 g`) is **always comparatively light relative to the heavy bass string** → bass hammer weight is **held high as long as possible**.
  2. **Break (`Key 23 → 24`, plain steel `3 strings/note ≈ 31 g`):** Sharp drop in choir mass requires a deliberate `−1.0 g` **step** (`13.0 → 12.0 g`).
  3. **Treble (`last 2 octaves to C₈`):** Trichord mass drops from `2.7 g` (`C₆`) to `~0.6 g` (`C₈`, `~0.2 g`/wire, `½ T < 0.5 ms`) → smooth taper to `5.0 g` (lightweight American walnut moulding) to prevent self-damping!

SLIDE 16 Pressing & Gluing to 0.1 mm

- ▶ Factory Video: Glue-press loading and closing in Meuselwitz (`0.1 mm` tolerance).
- **2-Stage Press Sequence: 1.** Felt is pressed downward into the **kettle** (`Pressgesenk`) · **2.** Heated **side jaws** (`Gegenlagen`) close in from both sides and press the felt onto the glue surface of the **hammer moulding**.
- **Effect:** High outer tensile tautness over a compressed, resilient inner cushion (foundation for `pp` to `ff`).

SLIDE 17 CNC Milling & Robotic Calibration

- ▶ 2 Sequential Factory Videos: CNC milling center first (`17.1`), followed by single-head robotic cell (`17.2`).
- **3 Steps: 1.** CNC-machine the **hammer mouldings** to `0.1 mm` · **2.** Trim and finish-mill felt overhang after pressing & gluing · **3.** Precisely calibrate **each individual hammerhead** on the **robotic cell**.

SLIDE 18 Automated Riveting & Boring

- ▶ Factory Video: Automated shank boring and brass rivet insertion.
- **3 Features: 1. Precision Boring Angle** (exact depth, e.g., `ø 5.4 mm`, individual boring angle per note) · **2. Brass Riveting** (permanently locks bonded felt tails under concert play) · **3. Radiused Hammer Tail** (contoured tail radii for reliable checking on the backcheck felt).

Chapter 4: The Louis Renner Yamaha Kit C1–C3 (Slides 19–24)

SLIDE 19 Louis Renner Yamaha Kit (C1–C3) – Seamless Drop-In

- ▸ Interaction: **5 Topic Tabs** + `⌕ Macro Zoom` on the right:
  1. **SYSTEM:** 5 years of R&D, proprietary measurement & production system → full concert sound **with zero manual pre-voicing** (complete reliability even without daily concert-voicing routine).
  2. **TOUCH:** Calibrated **walnut moulding**, quarter-sawn **hornbeam shanks**, pre-tensioned knuckles → reduced inertia, rapid repetition.
  3. **DROP-IN:** Pre-bored at the exact angle and factory-bonded onto shanks with flanges using rock-hard **natural hide glue** → **1-screw mounting** directly into the original Yamaha rail (`0 h` boring labor, zero drilling risk).
  4. **TONE:** Pressed from a **single homogeneous felt strip** → seamless transitions across all 88 keys, articulated bass, bell-clear treble.
  5. **TIME SAVED:** `4–5 hours` **on site** instead of `3–7 workshop days` → zero transport risk, direct tailoring to the venue's room acoustics and pianist.

SLIDE 20 Time-Lapse Installation: Complete Conversion in One Day

- ▶ Video: On-site time-lapse from India (10:00 – 18:00).
- **Field Proof:** Complete upgrade in **1 workday on site** — old set removal, 1-screw mounting onto the original rail, fine regulation (blow distance, let-off, checking), tuning & concert test.

SLIDE 21 Pianist Feedback: Pianist Raaga in Action

- ▶ Video with Audio: Immediate artist verdict right after installation.
- **Raaga's Verdict:** Immediately audible transformation from hard attack to warm, singing European concert tone, blooming treble, effortless pp–ff shading, and crisper repetition.

SLIDE 22 Sound Spectrum Comparison: Original vs. Renner Yamaha Kit

- ▸ Interaction: Click keyboard / 2-octave window (11:42 min recording: 0:00–5:17 Original vs. 5:18–11:42 Renner Kit).
- **5 Spectral Bands:** Bass (50–250 Hz : **−3.28 dB** less mud) · Body (250–800 Hz : −0.07 dB, 100% intact warmth) · Singing Presence (0.8–2.5 kHz : **+2.53 dB**) · Brilliance (2.5–6 kHz : **+1.87 dB**) · Air (6–12 kHz : +0.31 dB, zero metallic glare).

SLIDE 23 Partial Distribution (H_1–H_{12}) & 24-Semitone Comparison

- ▸ Interaction: Register buttons (Bass to Brilliance) & mode (Relative H_1 / Δ Gain / Absolute dB).
- **Harmonic Architecture: Even partials (H_2, H_4, H_6, H_8)** create **warmth & body**; **odd partials (H_3, H_5, H_7)** deliver **brilliance & singing core** — uniform across all 24 chromatic semitones on the right.

SLIDE 24 4 Tonal Gains & Overtone Retention up to C_8

- ▸ Interaction: Test the live pitch gain calculator on the right up to C_8 (4,186 Hz / slider up to 4,300 Hz).
- **4 Headline Metrics to Cite:**
  1. **Cantabile (0.8–2.5 kHz):** **+2.53 dB** (**+79%** **energy)**, peaking at **+3.4 dB** **at** **1.45 kHz**.
  2. **Treble Brilliance (2.5–6.0 kHz):** **+1.87 dB** (**+54%** **energy)** without harshness.
  3. **Bass Clarity (20–250 Hz):** **−3.28 dB** (**−53%** **boom)** → clean bass chord separation.
  4. **Overtone Retention (pp–ff):** **12.6%** **flatter roll-off** (−6.45 vs. −7.38 dB/kHz = net **+0.93 dB/kHz**) + **+0.42 dB** attack crest.

Chapter 5: The Art of Concert Voicing & Finale (Slides 25–33)

SLIDE 25 Partial Structure on A_1 (55 Hz): Felt Hardness & Strike Point

- ▸ Interaction: Hardness presets (Soft / Concert Ideal / Hard), strike point (x_0 / L on L = 1,560 mm) + Play A_1 (55 Hz).
- **2 Physical Levers:**
  1. **Felt Hardness & Contact Time τc :** Soft/needled (**$\tau c \approx 2.85$ ms**) lowers H_6–H_{12} by **−4.6 dB** · Concert Ideal (**$\tau c \approx 1.95$ ms**) blends H_1–H_4 warmth with singing H_5/H_6 · Hard (**$\tau c \approx 1.25$ ms**) boosts H_6–H_{12} by **+4.8 dB** (H_{12} +6.4 dB).
  2. **Young-Helmholtz Law (x_0 / L):** **1/8 L** **(195 mm , standard)** puts a node on H_8 (−22 dB) and tames rough H_7 & H_9; **1/7 L** **(223 mm)** cancels the natural 7th H_7 (−22 dB) while preserving the singing major third H_5.

SLIDE 26 The Hammerhead as a Complex Spring: From Cristofori to Zone Balance

- ▸ Interaction: Switch **1. Cristofori Roll (1700)** ↔ **2. Renner Tension Spring** + four 3-step controls.
- **Physics:** Cristofori's deer-leathered parchment roll used pure circumferential tension (88% bounce, $\tau c \approx 1.85$ ms) with zero dead core mass. The Renner head works as a **graded tension spring**: **100%** **compaction at the crown →** **½** **(50%) at the widest flank**, anchored to the **hammer moulding** by glue & rivet ($\tau c \approx 1.80$ ms).
- **Diagnostics:** Crown/transition too hard (125%) → **no** **pp** · Sluggish felt (54% bounce, $\tau c \approx 2.95$ ms) → **no** **ff** · Locked shoulder (18% flank active) → **double lock (neither** **pp** **nor** **ff** **)**!

SLIDE 27 Voicing Zones & Needling Effect: The Renner Clock Model

- ▸ Interaction: Click all 6 zones on the cross-section + toggle ✓ ⊥ to Fiber vs. × Cross / Chop + Needle & Play.
- **Golden Rule:** Always follow the wrapped wool fiber course and press **perpendicular to the fiber (⊥ 90°)** across 9:00–3:00 — parting fibers cleanly, never chopping across them!
- **All 6 Zones:**
  - **Blue (9–10 / 2–3h , ff -wedge):** 7–9 mm deep stopping short of underfelt → opens ff , H_1–H_4 +3.2 dB.
  - **Green (10–11 / 1–2h , f -wedge):** 4–6 mm deep → opens shoulder for cantabile core (+2.4 dB , glare −2.5 dB).
  - **Orange (11–12 / 12–1h , p -wedge):** 2.5–4 mm → cushions H_8–H_{12} (−3.8 dB) for warm piano.
  - **Purple (Crown, pp -wedge):** ≤ 2.0 mm , short single needle **strictly between string grooves** (H_9–H_{12} −5.1 dB).
  - **Yellow (Above Rivet → Toward Flank): Few, deep stitches (10–14 mm)** angled upward → tightens spring ($\tau c \approx 1.58$ ms) & boosts upper partials (H_7–H_{12} +3.1 dB).
  - **Red (12:00 Deep Core): Strict Taboo (> 2 mm)** — severs tension arch ($\tau c \to 3.15$ ms , hollow & dead tone)!

SLIDE 28 Crown & String Plane in 3-String Choirs: Phase & Cancellation

- ▸ Interaction: Toggle all **4 alignment states** (`✓ Flat & Parallel` · `∠ Tilted Crown` · `↕ Uneven String Plane` · `⌒ Hollow Crown`) + `Play A₃ Choir` (`220 Hz`).
- **Workshop Rule:** Just `0.2–0.3 mm` string offset or a tilted crown creates arrival delay `Δt` → upper partials shift **`120°–180°` out of phase** (comb-filter cancellation & metallic buzz). **No needle can fix phase cancellation — square and level the trichord first!**

SLIDE 29 String Preparation: Hitch Pins, Bridge Pins & Agraffes

- **4 Mandatory Steps Before Needling: 1.** Clean bearing surfaces & check hitch-pin seating · **2.** Tap strings solidly onto bridge pins with a brass drift punch · **3.** Space and level the 3-string plane behind the agraffes · **4.** Verify damper seating, beatless unison tuning & simultaneous hammer contact.

SLIDE 30 Intermediate, Fine & Una Corda Voicing

- **5 Concert-Finish Steps: 1.** Short single needle in the **BDK Fine Holder (** `43–0003269` **)** · **2. Mid-voicing** of shoulder wedges on a firm support pad · **3. Fine crown needling** in the grand with **Chop-Stick (** `43–0003271` **) max.** `2 mm` strictly **between string grooves** · **4.** Smooth crown with `320–400 grit` sanding paddle · **5. Shift-pedal voicing (*Una Corda*):** Depress soft pedal, voice only contacted string zones & lightly chamfer left crown edge.

SLIDE 31 Lacquer Dosing, Heat Ironing (max. 135 °C), Crown Finish & Weight

- ▸ Interaction: Click all **4 lacquer zones** + toggle time compaction (`Freshly Applied` ↔ Aged) + mass buttons (`+m` / `−m`).
- **01 · Lacquer Dosing & Mass Control:**
  - **Rivet Zone (below moulding):** Stiffens lower foundation (`H₁–H₄ +3.4 dB`) & can lift felt tension — upper elastic arch stays protected.
  - **Lateral Above Moulding:** Light side dosing boosts high partials (`H₉–H₁₂ +3.8 dB`), **but compacts further over playing time!** Excess lacquer wicks into the flank and locks up the spring (`H₁–H₄ −3.8 dB`).
  - **Direct on Crown (** `12:00` **): Strictly avoid!** (Glassy, nasal hardness `+6.0 dB`, permanent damage).
  - **Fundamental Fullness & Projection via Mass (instead of over-hardening):** Middle to bass **increase weight (** `+m ↑` **)** · Toward treble **reduce weight (** `−m ↓` **)**.
- **02 · Heat Ironing:** Thermostat-controlled **strictly max.** `135 °C` (protects keratin & lanolin from scorching/brittleness).
- **03 · Ultra-Fine Crown Finish:** Micro-abrasive down to `≤ 15 µm` **(** `15 my` **)** or **Braun Series 1** foil shaver (trims stray fuzz fibers with `0%` felt removal).

SLIDE 32 The Renner Academy & Technical Master Dialogue

- **Invitation:** Hands-on masterclasses (*By Masters for Masters* on action geometry, hammerhead installation, Yamaha Kit & concert voicing), **factory tours at our unified Meuselwitz plant**, and direct technical support.

SLIDE 33 Let the Perfect Hammer Sound!

- **Closing Line:** *“Meuselwitz precision and finest Wurzen Merino felt — Let the Perfect Hammer Sound! Thank you very much — I now look forward to your questions and your experiences from the workshop.”*