

Exploration in Reinforcement Learning (theory)

Lecturers: *M. Pirotta*(*December 12, 2022*)Solution by **FILL** fullname command at the beginning of latex document**Instructions**

- The deadline is **January 20, 2023. 23h59**
- By doing this homework you agree to the *late day policy, collaboration and misconduct rules* reported on Piazza.
- **Mysterious or unsupported answers will not receive full credit.** A correct answer, unsupported by calculations, explanation, or algebraic work will receive no credit; an incorrect answer supported by substantially correct calculations and explanations might still receive partial credit.
- Answers should be provided in **English**.

1 Best Arm Identification

In best arm identification (BAI), the goal is to identify the best arm in as few samples as possible. We will focus on the fixed-confidence setting where the goal is to identify the best arm with high probability $1 - \delta$ in as few samples as possible. A player is given k arms with expected reward μ_i . At each timestep t , the player selects an arm to pull (I_t), and they observe some reward ($X_{I_t,t}$) for that sample. At any timestep, once the player is confident that they have identified the best arm, they may decide to stop.

δ -correctness and fixed-confidence objective. Denote by τ_δ the stopping time associated to the stopping rule, by i^* the best arm and by \hat{i} an estimate of the best arm. An algorithm is δ -correct if it predicts the correct answer with probability at least $1 - \delta$. Formally, if $\mathbb{P}_{\mu_1, \dots, \mu_k}(\hat{i} \neq i^*) \leq \delta$ and $\tau_\delta < \infty$ almost surely for any μ_1, \dots, μ_k . Our goal is to find a δ -correct algorithm that minimizes the sample complexity, that is, $\mathbb{E}[\tau_\delta]$ the expected number of sample needed to predict an answer. Assume that the best arm i^* is *unique* (i.e., there exists only one arm with maximum mean reward).

Notation

- I_t : the arm chosen at round t .
- $X_{i,t} \in [0, 1]$: reward observed for arm i at round t .
- μ_i : the expected reward of arm i .
- $\mu^* = \max_i \mu_i$.
- $\Delta_i = \mu^* - \mu_i$: suboptimality gap.

Consider the following algorithm

The algorithm maintains an active set S and an estimate of the empirical reward of each arm $\hat{\mu}_{i,t} = \frac{1}{t} \sum_{j=1}^t X_{i,j}$.

- Compute the function $U(t, \delta)$ that satisfy the any-time confidence bound. Let

$$\mathcal{E} = \bigcup_{i=1}^k \bigcup_{t=1}^{\infty} \{|\hat{\mu}_{i,t} - \mu_i| > U(t, \delta')\}.$$

```

Input:  $k$  arms, confidence  $\delta$ 
 $S = \{1, \dots, k\}$ 
for  $t = 1, \dots$  do
    Pull all arms in  $S$ 
     $S = S \setminus \left\{ i \in S : \exists j \in S, \hat{\mu}_{j,t} - U(t, \delta') \geq \hat{\mu}_{i,t} + U(t, \delta') \right\}$ 
    if  $|S| = 1$  then
        STOP
        return  $S$ 
    end
end

```

Using Hoeffding's inequality and union bounds, shows that $\mathbb{P}(\mathcal{E}) \leq \delta$ for a particular choice of δ' . This is called “bad event” since it means that the confidence intervals do not hold.

- Show that with probability at least $1 - \delta$, the optimal arm $i^* = \arg \max_i \{\mu_i\}$ remains in the active set S . Use your definition of δ' and start from the condition for arm elimination. From this, use the definition of $\neg \mathcal{E}$.
- Under event $\neg \mathcal{E}$, show that an arm $i \neq i^*$ will be removed from the active set when $\Delta_i \geq C_1 U(t, \delta')$ for some constant $C_1 \in \mathbb{N}$. Compute the time required to have such condition for each non-optimal arm. Use the condition of arm elimination applied to arm i^* .¹
- Compute a bound on the sample complexity (after how many *pulls* the algorithm stops) for identifying the optimal arm w.p. $1 - \delta$.
- We assumed that the optimal arm i^* is unique. Would the algorithm still work if there exist multiple best arms? Why?

Note that also a variations of UCB are effective in pure exploration.

2 Regret Minimization in RL

Consider a finite-horizon MDP $M^* = (S, A, p_h, r_h)$ with stage-dependent transitions and rewards. Assume rewards are bounded in $[0, 1]$. We want to prove a regret upper-bound for UCBVI. We will aim for the suboptimal regret bound ($T = KH$)

$$R(T) = \sum_{k=1}^K V_1^*(s_{1,k}) - V_1^{\pi_k}(s_{1,k}) = \tilde{O}(H^2 S \sqrt{AK})$$

Define the set of plausible MDPs as

$$\mathcal{M}_k = \{M = (S, A, p_{h,k}, r_{h,k}) : r_{h,k}(s, a) \in \beta_{h,k}^r(s, a), p_{h,k}(\cdot | s, a) \in \beta_{h,k}^p(s, a)\}$$

Confidence intervals can be anytime or not.

- Define the event $\mathcal{E} = \{\forall k, M^* \in \mathcal{M}_k\}$. Prove that $\mathbb{P}(\neg \mathcal{E}) \leq \delta/2$. First step, construct a confidence interval for rewards and transitions for each (s, a) using Hoeffding and Weissmain inequality (see appendix), respectively. So, we want that

$$\mathbb{P}\left(\forall k, h, s, a : \hat{r}_{hk}(s, a) - r_h(s, a) \leq \beta_{hk}^r(s, a) \wedge \|\hat{p}_{hk}(\cdot | s, a) - p_h(\cdot | s, a)\|_1 \leq \beta_{hk}^p(s, a)\right) \geq 1 - \delta/2$$

¹Note that $at \geq \log(bt)$ can be solved using Lambert W function. We thus have $t \geq \frac{-W_{-1}(-a/b)}{a}$ since, given $a = \Delta_i^2$ and $b = 2k/\delta$, $-a/b \in (-1/e, 0)$. We can make the bound more explicit by noticing that $-1 - \sqrt{2u} - u \leq W_{-1}(-e^{-u-1}) \leq -1 - \sqrt{2u} - 2u/3$ for $u > 0$ [Chatzigeorgiou, 2016]. Then $t \geq \frac{1+\sqrt{2u}+u}{a}$ with $u = \log(b/a) - 1$.

- Define the bonus function and consider the Q-function computed at episode k

$$Q_{h,k}(s, a) = \hat{r}_{h,k}(s, a) + b_{h,k}(s, a) + \sum_{s'} \hat{p}_{h,k}(s'|s, a) V_{h+1,k}(s')$$

with $V_{h,k}(s) = \min\{H, \max_a Q_{h,k}(s, a)\}$. Recall that $V_{H+1,k}(s) = V_{H+1}^*(s) = 0$. Prove that under event \mathcal{E} , Q_k is optimistic, i.e.,

$$Q_{h,k}(s, a) \geq Q_h^*(s, a), \forall s, a$$

where Q^* is the optimal Q-function of the unknown MDP M^* . Note that $\hat{r}_{H,k}(s, a) + b_{H,k}(s, a) \geq r_{H,k}(s, a)$ and thus $Q_{H,k}(s, a) \geq Q_H^*(s, a)$ (for a properly defined bonus). Then use induction to prove that this holds for all the stages h .

- In class we have seen that

$$\delta_{1k}(s_{1,k}) \leq \sum_{h=1}^H Q_{hk}(s_{hk}, a_{hk}) - r(s_{hk}, a_{hk}) - \mathbb{E}_{Y \sim p(\cdot|s_{hk}, a_{hk})}[V_{h+1,k}(Y)] + m_{hk} \quad (1)$$

where $\delta_{hk}(s) = V_{hk}(s) - V_h^{\pi_k}(s)$ and $m_{hk} = \mathbb{E}_{Y \sim p(\cdot|s_{hk}, a_{hk})}[\delta_{h+1,k}(Y)] - \delta_{h+1,k}(s_{h+1,k})$. We now want to prove this result. Denote by a_{hk} the action played by the algorithm (you will have to use the greedy property).

1. Show that $V_h^{\pi_k}(s_{hk}) = r(s_{hk}, a_{hk}) + \mathbb{E}_p[V_{h+1,k}(s')] - \delta_{h+1,k}(s_{h+1,k}) - m_{hk}$
2. Show that $V_{h,k}(s_{hk}) \leq Q_{h,k}(s_{hk}, a_{hk})$.
3. Putting everything together prove Eq. 1.

- Since $(m_{hk})_{hk}$ is an MDS, using Azuma-Hoeffding we show that with probability at least $1 - \delta/2$

$$\sum_{k,h} m_{hk} \leq 2H\sqrt{KH \log(2/\delta)}$$

Show that the regret is upper bounded with probability $1 - \delta$ by

$$R(T) \leq 2 \sum_{kh} b_{hk}(s_{hk}, a_{hk}) + 2H\sqrt{KH \log(2/\delta)}$$

- Finally, we have that [Domingues et al., 2021]

$$\sum_{h,k} \frac{1}{\sqrt{N_{hk}(s_{hk}, a_{hk})}} \lesssim H^2 S^2 A + 2 \sum_{h=1}^H \sum_{s,a} \sqrt{N_{hk}(s, a)}$$

Complete this by showing an upper-bound of $H\sqrt{SAK}$, which leads to $R(T) \lesssim H^2 S \sqrt{AK}$

A Weissmain inequality

Denote by $\hat{p}(\cdot|s, a)$ the estimated transition probability build using n samples drawn from $p(\cdot|s, a)$. Then we have that

$$\mathbb{P}(\|\hat{p}_h(\cdot|s, a) - p_h(\cdot|s, a)\|_1 \geq \epsilon) \leq (2^S - 2) \exp\left(-\frac{n\epsilon^2}{2}\right)$$

References

- Ioannis Chatzigeorgiou. Bounds on the lambert function and their application to the outage analysis of user cooperation. *CoRR*, abs/1601.04895, 2016.
- Omar Darwiche Domingues, Pierre Ménard, Matteo Pirotta, Emilie Kaufmann, and Michal Valko. Kernel-based reinforcement learning: A finite-time analysis. In *ICML*, volume 139 of *Proceedings of Machine Learning Research*, pages 2783–2792. PMLR, 2021.

```

Initialize  $Q_{h1}(s, a) = 0$  for all  $(s, a) \in S \times A$  and  $h = 1, \dots, H$ 
for  $k = 1, \dots, K$  do
    Observe initial state  $s_{1k}$  (arbitrary)
    Estimate empirical MDP  $\widehat{M}_k = (S, A, \widehat{p}_{hk}, \widehat{r}_{hk}, H)$  from  $\mathcal{D}_k$ 

    
$$\widehat{p}_{hk}(s'|s, a) = \frac{\sum_{i=1}^{k-1} \mathbf{1}\{(s_{hi}, a_{hi}, s_{h+1,i}) = (s, a, s')\}}{N_{hk}(s, a)}, \quad \widehat{r}_{hk}(s, a) = \frac{\sum_{i=1}^{k-1} r_{hi} \cdot \mathbf{1}\{(s_{hi}, a_{hi}) = (s, a)\}}{N_{hk}(s, a)}$$


    Planning (by backward induction) for  $\pi_{hk}$  using  $\widehat{M}_k$ 
    for  $h = H, \dots, 1$  do
         $Q_{h,k}(s, a) = \widehat{r}_{h,k}(s, a) + b_{h,k}(s, a) + \sum_{s'} \widehat{p}_{h,k}(s'|s, a) V_{h+1,k}(s')$ 
         $V_{h,k}(s) = \min\{H, \max_a Q_{h,k}(s, a)\}$ 
    end
    Define  $\pi_{h,k}(s) = \arg \max_a Q_{h,k}(s, a), \forall s, h$ 
    for  $h = 1, \dots, H$  do
        Execute  $a_{hk} = \pi_{hk}(s_{hk})$ 
        Observe  $r_{hk}$  and  $s_{h+1,k}$ 
         $N_{h,k+1}(s_{hk}, a_{hk}) = N_{h,k}(s_{hk}, a_{hk}) + 1$ 
    end
end

```

Algorithm 1: UCBVI