AgCalculator

agcalculator.com · do the farm math

Fence Energizer Sizing Worksheet

Printable field reference

Fill this in at the calculator online, or work it by hand with the formulas below. These are conservative planning values — verify with your supplier for local conditions.

1. Your inputs

Length input (circle one): _____

☐ Total length ☐ Rectangle (L × W)

Total length, if known (ft) _____

Rectangle length (ft) _____

Rectangle width (ft) _____

Fence type (circle one): _____

☐ High-tensile ☐ Barbed ☐ Woven/mesh

Hot strands _____

Vegetation load (circle one): _____

☐ Low ☐ Medium ☐ High

2. Formulas

`Effective wire miles = physical miles × hot strands` (mesh counts as 1)

Base output J/mi: Low **0.6** · Medium **1.0** · High **2.0**

Fence type factor: High-tensile **×1.0** · Barbed **×1.1** · Mesh **×1.2**

`Recommended output J = effective miles × base J/mi × type factor` (min 1.0 J)

Good/Robust band = ±25% of recommendation Marketing “range” ≈ J ÷ 0.6 (mi)

3. Worked example

Rectangle 660×330 ft, high-tensile, 5 hot strands, medium vegetation:
Perimeter = 2×(660+330) = 1,980 ft = **0.375 mi** · Effective wire = 0.375×5 = **1.875 mi**
J = 1.875×1.0×1.0 = **1.88 J** · Good/Robust ≈ 1.41–2.34 J · Range ≈ **3.13 mi**

4. Your numbers

Effective wire distance (mi)	miles × strands	
Recommended output joules	eff × base × factor	
Good / Robust range (J)	±25%	
Suggested “range” rating (mi)	J ÷ 0.6	

Notes