

STATE OF UTAH DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING										FORM 8
WELL COMPLETION OR RECOMPLETION REPORT AND LOG										1. WELL NAME RD TRIBAL 17S-31E-H4UB
2. TYPE OF WELL Oil Well			3. TYPE OF WORK DRILL NEW ☒ REENTER P&A ☐ DEEPEN ☐ RECOMP ☐				4. API NUMBER 4304757497			
5. NAME OF OPERATOR Uinta Wax Operating, LLC					6. OPERATOR PHONE 817-402-0861			7. FIELD NAME INDEPENDENCE		
8. ADDRESS OF OPERATOR 6000 Western Plaza, Suite 1000, Fort Worth, TX, 76107					9. OPERATOR E-MAIL zachary.archer@uintawax.com			10. UNIT NAME		
11. MINERAL LEASE NUMBER MULTIPLE LEASES			12. MINERAL OWNERSHIP INDIAN,FEE			13. SURFACE OWNERSHIP FEE		14. COUNTY UINTAH		
15. DATE SPUDDED (SPUD RIG) 04/03/2024		16. DATE SPUDDED (ROTARY RIG) 04/17/2024		17. DATE TOTAL DEPTH REACHED 08/06/2024		18. DATE COMPLETED/ABANDONED 09/30/2024		19. DATE OF FIRST PROD. / INJ. PROD:10/01/2024 INJ:		
20. DEPTH REFERENCE GROUND LEVEL ☒ KELLY BUSHING ☐ DERRICK FLOOR ☐					21. DEPTH REFERENCE ELEVATION 5013 (US Feet)			22. GRADED GROUND LEVEL ELEVATION 5013 (US Feet)		
23. WELLBORE DEVIATION PROFILE VERTICAL ☐ DIRECTIONAL ☐ HORIZONTAL ☒					24. TOTAL DEPTH MD 18667 TVD 8127			25. PLUGGED BACK TOTAL DEPTH MD 18607 TVD 8130		
26. CURRENT WELL STATUS Producing										

27. LOCATION OF WELL									
WELL POSITION	FOOTAGES		QTR-QTR	SECTION	TOWNSHIP	RANGE	MERIDIAN	UTM EASTING	UTM NORTHING
Surface	649 FSL	1737 FEL	SWSE	8	3.0 S	1.0 E	U	593272	4453994
Producing Interval Top	100 FNL	2563 FWL	NENW	17	3.0 S	1.0 E	U		
Producing Interval Bottom	953 FSL	2611 FWL	SESW	20	3.0 S	1.0 E	U		
Total Depth	879 FSL	2611 FWL	SESW	20	3.0 S	1.0 E	U		

28. HOLE, CASING AND CEMENT INFORMATION															
STRING	HOLE SIZE	CASING O.D.	WEIGHT	GRADE	THREAD	TOP (MD)	BOTTOM (MD)	DV TOOL DEPTH	LEAD TAIL	CEMENT TYPE	SACKS	YIELD	WEIGHT	CEMENT TOP	BASIS FOR TOP
SURF	13.5	10.75	45.5	J-55	BTC	0	2020		L	Class G Cement	340	2.84	11.5	0	Circulate
									T	Class G Cement	280	1.17	15.8		
INT	9.875	7.625	29.7	P-110	BTB	0	8003		L	Class G Cement	900	2.91	11.5	0	Circulate
									T	Class G Cement	210	1.15	15.8		
PROD	6.75	5.5	23.0	P-110	BTB	0	7921		L	Class G Cement	200	2.92	11.5	0	Circulate
P2	6.75	5.0	18.0	P-110	BTB	7921	18627		T	Class G Cement	1180	1.2	14.5		

29. TUBING RECORD			
TUBING SIZE	TOP (MD)	BOT (MD)	PACKER DEPTH

30. RETRIEVABLE / TEMPORARY PLUGS		
PLUG	DEPTH (MD)	TYPE

31. PERMANENT / ABANDONMENT PLUGS		
PLUG	TOP (MD)	BOTTOM (MD)
1	18607	18608

32. FORMATION DETAILS and STRATIGRAPHIC MARKERS				
FR	FORMATION NAME	TOP (MD)	TOP (TVD)	DESCRIPTION, CONTENTS, ETC.
1	BIRDS NEST	4648	4611	
	OIL SHOW? ☐ GAS SHOW? ☐ WATER FLOW? ☐ DRILL STEM TESTED? ☐ CORED? ☐ COMPLETED OR TESTED? ☐ COMMINGLED? ☐			
2	MAHOGANY BENCH	5542	5482	
	OIL SHOW? ☐ GAS SHOW? ☐ WATER FLOW? ☐ DRILL STEM TESTED? ☐ CORED? ☐ COMPLETED OR TESTED? ☐ COMMINGLED? ☐			
3	GARDEN GULCH	6610	6529	
	OIL SHOW? ☐ GAS SHOW? ☐ WATER FLOW? ☐ DRILL STEM TESTED? ☐ CORED? ☐ COMPLETED OR TESTED? ☐ COMMINGLED? ☐			
4	DOUGLAS CREEK	7601	7513	
	OIL SHOW? ☐ GAS SHOW? ☐ WATER FLOW? ☐ DRILL STEM TESTED? ☐ CORED? ☐ COMPLETED OR TESTED? ☐ COMMINGLED? ☐			
5	BLACK SHALE	8086	7988	
	OIL SHOW? ☐ GAS SHOW? ☐ WATER FLOW? ☐ DRILL STEM TESTED? ☐ CORED? ☐ COMPLETED OR TESTED? ☐ COMMINGLED? ☐			
6	GREEN RIVER - LOWER	8231	8116	
	OIL SHOW? ☐ GAS SHOW? ☐ WATER FLOW? ☐ DRILL STEM TESTED? ☐ CORED? ☐ COMPLETED OR TESTED? ☐ COMMINGLED? ☐			
	CASTLE PEAK	8259	8138	

7	OIL SHOW? ☐ GAS SHOW? ☐ WATER FLOW? ☐ DRILL STEM TESTED? ☐ CORED? ☐ COMPLETED OR TESTED? ☐ COMMINGLED? ☐					
8	UTELAND BUTTE		8636	8368		
	OIL SHOW? ☒ GAS SHOW? ☒ WATER FLOW? ☐ DRILL STEM TESTED? ☐ CORED? ☐ COMPLETED OR TESTED? ☒ COMMINGLED? ☐					

33. COMPLETED and TESTED INTERVALS (Formation Reference (FR) 1, 2, 3, ..., etc. as in Section 32.)						
FR	TOP (MD)	BOTTOM (MD)	TOP (TVD)	BOTTOM (TVD)	STIMULATION TREATMENT	INTERVAL STATUS
8	9017	18594	8433	8130	Fracture Stimulated	PRODUCING

34A. PRODUCTION INFORMATION (Formation Reference (FR) 1, 2, 3, ..., etc. as in Section 32.)									
FR	TOP (MD)	BOTTOM (MD)	DATE FIRST PROD.	TEST DATE	HRS. TESTED	TBG. PRESSURE	CSG. PRESSURE	PROD. METHOD	
8	9017	18594	10/01/2024	10/05/2024	24			Flowing	
	TEST PRODUCTION VOLUMES			24-HOUR PRODUCTION RATES			GAS-OIL RATIO	OIL API	GAS BTU
	OIL (BBL)	GAS (MSCF)	WATER (BBL)	OIL (BBL)	GAS (MSCF)	WATER (BBL)	450	40.0	
	349	157	1774	349	157	1774			

35. WELL TREATMENTS (Formation Reference (FR) 1, 2, 3, ..., etc. as in Section 32.)						
FR	TREATMENT TYPE	TOP (MD)	BOTTOM (MD)	START DATE	END DATE	AMOUNT AND TYPE OF MATERIAL
8	Fracture Stimulation	9017	18594	08/26/2024	09/24/2024	23,585,500 #100 Mesh Sand, 379,281 bbls water

36. LOGS, SURVEYS, AND REPORTS (PDF file of each and LAS file of logs if available are to be submitted.)							
REPORTS AND OTHER INFORMATION.							
Dx Survey ☒		DST Report ☐		Core Analysis ☐		DOGM Form 7 ☐	
				Geologic Report ☐		Wellbore Diagram ☐	
						Other ☒	
SUBMITTED PDF LOGS				SUBMITTED LAS LOGS			
CEMENT BOND, TEMPERATURE							

OGM Official Use Only

37. I hereby certify that the foregoing and attached information is complete as determined from all available records.		
NAME	TITLE	DATE
Heather Pearson	GIS	11/21/2024
SIGNATURE	PHONE	EMAIL
N/A	817-442-7260	heather.pearson@uintawax.com

Uinta Wax

UINTAH COUNTY, UT (NAD 83) UTCZ GRID
S8-T3S-R1E (Sand View)
RD TRIBAL 17S-31E-H4UB

OH (240896)

SURVEYS



Standard Survey Report

06 August, 2024

Total Report Version 1.70

COMPASS 5000.16 Build 97



Survey Report

Company:	Uinta Wax	Local Co-ordinate Reference:	Well RD TRIBAL 17S-31E-H4UB
Project:	UINTAH COUNTY, UT (NAD 83) UTCZ GRID	TVD Reference:	23' KB @ 5036.00usft
Site:	S8-T3S-R1E (Sand View)	MD Reference:	23' KB @ 5036.00usft
Well:	RD TRIBAL 17S-31E-H4UB	North Reference:	Grid
Wellbore:	OH (240896)	Survey Calculation Method:	Minimum Curvature
Design:	SURVEYS	Database:	.Total Directional Production DB

Project	UINTAH COUNTY, UT (NAD 83) UTCZ GRID		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Utah Central Zone		

Site	S8-T3S-R1E (Sand View)		
Site Position:		Northing:	7,256,865.66 usft
From:	Lat/Long	Easting:	2,086,010.85 usft
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "
		Latitude:	40.231060
		Longitude:	-109.903918

Well	RD TRIBAL 17S-31E-H4UB		
Well Position	+N/-S	0.00 usft	Northing:
	+E/-W	0.00 usft	Easting:
Position Uncertainty	0.00 usft	Wellhead Elevation:	
Grid Convergence:	1.02 °		
		Latitude:	40.231194
		Longitude:	-109.903606
		Ground Level:	5,013.00 usft

Wellbore	OH (240896)		
Magnetics	Model Name	Sample Date	Declination
	HDGM2024	7/30/2024	(°)
			9.93
		Dip Angle	(°)
		65.70	
		Field Strength	(nT)
			51,053.10000000

Design	SURVEYS		
Audit Notes:			
Version:	1.0	Phase:	ACTUAL
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W
	(usft)	(usft)	(usft)
	0.00	0.00	0.00
			Direction
			(°)
			179.11

Survey Program	Date	8/6/2024		
From	To	Survey (Wellbore)	Tool Name	Description
(usft)	(usft)			
151.00	18,667.00	Survey #1 (OH (240896))	OWSG (Rev2) MWD	OWSG MWD - Standard

Survey													
Measured			Vertical	Local Coordinates		Map Coordinates		Geo Coordinates		Vertical	Dogleg	Build	Turn
Depth	INC	AZI	Depth	+N/-S	+E/-W	Northing	Easting	Latitude	Longituge	Section	Rate	Rate	Rate
(usft)	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)	(°)	(°)	(usft)	(°/100usft)	(°/100usft)	(°/100usft)
0.00	0.00	0.00	0.00	0.00	0.00	7,256,916.11	2,086,097.25	40.231194	-109.903606	0.00	0.00	0.00	0.00
151.00	0.18	169.69	151.00	-0.23	0.04	7,256,915.87	2,086,097.29	40.231194	-109.903606	0.23	0.12	0.12	0.00
241.00	0.48	144.20	241.00	-0.68	0.29	7,256,915.43	2,086,097.54	40.231192	-109.903605	0.68	0.36	0.33	-28.32
331.00	0.92	161.34	330.99	-1.67	0.74	7,256,914.44	2,086,097.99	40.231190	-109.903603	1.68	0.54	0.49	19.04
423.00	0.44	154.75	422.98	-2.69	1.13	7,256,913.42	2,086,098.37	40.231187	-109.903602	2.70	0.53	-0.52	-7.16
513.00	0.66	317.35	512.98	-2.62	0.92	7,256,913.49	2,086,098.17	40.231187	-109.903603	2.63	1.21	0.24	180.67



Survey Report

Company:	Uinta Wax	Local Co-ordinate Reference:	Well RD TRIBAL 17S-31E-H4UB
Project:	UINTAH COUNTY, UT (NAD 83) UTCZ GRID	TVD Reference:	23' KB @ 5036.00usft
Site:	S8-T3S-R1E (Sand View)	MD Reference:	23' KB @ 5036.00usft
Well:	RD TRIBAL 17S-31E-H4UB	North Reference:	Grid
Wellbore:	OH (240896)	Survey Calculation Method:	Minimum Curvature
Design:	SURVEYS	Database:	.Total Directional Production DB

Survey

Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	+E/-W (usft)	Map Coordinates Northing (usft)	Easting (usft)	Geo Coordinates Latitude (°)	Longitude (°)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
603.00	0.70	324.29	602.98	-1.79	0.25	7,256,914.31	2,086,097.50	40.231189	-109.903605	1.80	0.10	0.04	7.71
691.00	0.97	329.48	690.97	-0.71	-0.44	7,256,915.39	2,086,096.81	40.231192	-109.903607	0.71	0.32	0.31	5.90
782.00	1.10	340.02	781.95	0.77	-1.13	7,256,916.88	2,086,096.12	40.231196	-109.903610	-0.79	0.25	0.14	11.58
874.00	1.05	330.88	873.94	2.34	-1.84	7,256,918.44	2,086,095.41	40.231201	-109.903612	-2.37	0.19	-0.05	-9.93
989.00	0.44	27.48	988.93	3.65	-2.15	7,256,919.76	2,086,095.10	40.231204	-109.903613	-3.68	0.77	-0.53	49.22
1,074.00	0.48	41.02	1,073.92	4.21	-1.77	7,256,920.31	2,086,095.48	40.231206	-109.903612	-4.23	0.14	0.05	15.93
1,160.00	0.48	83.91	1,159.92	4.52	-1.17	7,256,920.62	2,086,096.08	40.231207	-109.903610	-4.54	0.41	0.00	49.87
1,246.00	0.40	111.16	1,245.92	4.45	-0.53	7,256,920.55	2,086,096.71	40.231207	-109.903607	-4.46	0.26	-0.09	31.69
1,332.00	0.48	115.20	1,331.92	4.19	0.07	7,256,920.29	2,086,097.32	40.231206	-109.903605	-4.18	0.10	0.09	4.70
1,418.00	0.75	101.14	1,417.91	3.92	0.95	7,256,920.03	2,086,098.20	40.231205	-109.903602	-3.91	0.36	0.31	-16.35
1,504.00	0.79	109.57	1,503.90	3.62	2.06	7,256,919.72	2,086,099.31	40.231204	-109.903598	-3.58	0.14	0.05	9.80
1,589.00	1.14	101.31	1,588.89	3.25	3.44	7,256,919.36	2,086,100.69	40.231203	-109.903593	-3.20	0.44	0.41	-9.72
1,677.00	1.05	107.55	1,676.88	2.84	5.07	7,256,918.95	2,086,102.32	40.231202	-109.903587	-2.76	0.17	-0.10	7.09
1,763.00	1.14	174.79	1,762.86	1.75	5.90	7,256,917.86	2,086,103.15	40.231199	-109.903584	-1.66	1.41	0.10	78.19
1,848.00	1.32	176.64	1,847.84	-0.07	6.03	7,256,916.04	2,086,103.28	40.231194	-109.903584	0.16	0.22	0.21	2.18
1,934.00	1.54	182.17	1,933.82	-2.21	6.05	7,256,913.89	2,086,103.29	40.231188	-109.903584	2.31	0.30	0.26	6.43
1,963.00	1.98	183.58	1,962.80	-3.10	6.00	7,256,913.00	2,086,103.25	40.231186	-109.903584	3.20	1.52	1.52	4.86
2,118.00	1.50	197.20	2,117.73	-7.71	5.23	7,256,908.39	2,086,102.48	40.231173	-109.903587	7.79	0.41	-0.31	8.79
2,212.00	0.30	36.70	2,211.72	-8.69	5.02	7,256,907.42	2,086,102.26	40.231170	-109.903588	8.77	1.90	-1.28	-170.74
2,305.00	2.60	3.50	2,304.69	-6.39	5.29	7,256,909.72	2,086,102.54	40.231177	-109.903587	6.47	2.53	2.47	-35.70
2,398.00	3.40	351.40	2,397.56	-1.56	5.01	7,256,914.55	2,086,102.26	40.231190	-109.903588	1.64	1.09	0.86	-13.01
2,491.00	4.70	323.80	2,490.33	4.24	2.34	7,256,920.35	2,086,099.59	40.231206	-109.903597	-4.21	2.48	1.40	-29.68
2,584.00	6.20	296.50	2,582.93	9.56	-4.40	7,256,925.67	2,086,092.85	40.231221	-109.903621	-9.63	3.18	1.61	-29.35
2,677.00	8.30	270.10	2,675.20	11.81	-15.61	7,256,927.92	2,086,081.63	40.231228	-109.903661	-12.06	4.18	2.26	-28.39
2,771.00	8.60	267.20	2,768.18	11.48	-29.42	7,256,927.59	2,086,067.83	40.231227	-109.903710	-11.94	0.55	0.32	-3.09
2,864.00	8.60	266.30	2,860.14	10.69	-43.30	7,256,926.80	2,086,053.95	40.231226	-109.903760	-11.37	0.14	0.00	-0.97
2,956.00	8.40	266.00	2,951.13	9.78	-56.87	7,256,925.89	2,086,040.38	40.231224	-109.903809	-10.66	0.22	-0.22	-0.33
3,049.00	8.80	275.90	3,043.09	10.04	-70.72	7,256,926.15	2,086,026.53	40.231225	-109.903858	-11.14	1.65	0.43	10.65
3,143.00	9.00	277.60	3,135.95	11.75	-85.16	7,256,927.86	2,086,012.09	40.231231	-109.903910	-13.07	0.35	0.21	1.81
3,235.00	9.00	277.20	3,226.82	13.60	-99.43	7,256,929.71	2,085,997.81	40.231237	-109.903961	-15.15	0.07	0.00	-0.43
3,328.00	8.70	277.70	3,318.71	15.46	-113.62	7,256,931.57	2,085,983.63	40.231242	-109.904012	-17.22	0.33	-0.32	0.54
3,422.00	9.40	277.30	3,411.54	17.39	-128.28	7,256,933.49	2,085,968.97	40.231248	-109.904064	-19.38	0.75	0.74	-0.43
3,515.00	11.20	280.40	3,503.04	19.98	-144.70	7,256,936.09	2,085,952.55	40.231256	-109.904123	-22.23	2.02	1.94	3.33
3,609.00	10.70	278.00	3,595.33	22.84	-162.32	7,256,938.95	2,085,934.93	40.231265	-109.904186	-25.36	0.72	-0.53	-2.55
3,702.00	12.00	279.20	3,686.51	25.59	-180.41	7,256,941.70	2,085,916.83	40.231273	-109.904250	-28.39	1.42	1.40	1.29
3,795.00	13.00	277.70	3,777.30	28.54	-200.32	7,256,944.65	2,085,896.92	40.231282	-109.904321	-31.65	1.13	1.08	-1.61
3,889.00	12.50	274.20	3,868.99	30.70	-220.95	7,256,946.81	2,085,876.30	40.231289	-109.904395	-34.13	0.98	-0.53	-3.72
3,982.00	12.10	270.30	3,959.85	31.49	-240.73	7,256,947.60	2,085,856.52	40.231293	-109.904466	-35.22	0.99	-0.43	-4.19



Survey Report

Company:	Uinta Wax	Local Co-ordinate Reference:	Well RD TRIBAL 17S-31E-H4UB
Project:	UINTAH COUNTY, UT (NAD 83) UTCZ GRID	TVD Reference:	23' KB @ 5036.00usft
Site:	S8-T3S-R1E (Sand View)	MD Reference:	23' KB @ 5036.00usft
Well:	RD TRIBAL 17S-31E-H4UB	North Reference:	Grid
Wellbore:	OH (240896)	Survey Calculation Method:	Minimum Curvature
Design:	SURVEYS	Database:	.Total Directional Production DB

Survey

Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	+E/-W (usft)	Map Coordinates Northing (usft)	Easting (usft)	Geo Coordinates Latitude (°)	Longitude (°)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
4,076.00	11.70	270.20	4,051.83	31.57	-260.12	7,256,947.68	2,085,837.13	40.231294	-109.904535	-35.61	0.43	-0.43	-0.11
4,168.00	12.60	273.70	4,141.77	32.25	-279.46	7,256,948.36	2,085,817.79	40.231297	-109.904604	-36.59	1.26	0.98	3.80
4,261.00	12.30	273.00	4,232.59	33.43	-299.47	7,256,949.53	2,085,797.78	40.231301	-109.904676	-38.07	0.36	-0.32	-0.75
4,355.00	12.40	275.70	4,324.41	34.95	-319.51	7,256,951.06	2,085,777.73	40.231306	-109.904748	-39.91	0.62	0.11	2.87
4,448.00	12.00	273.20	4,415.31	36.49	-339.10	7,256,952.59	2,085,758.15	40.231311	-109.904818	-41.75	0.71	-0.43	-2.69
4,541.00	12.80	275.60	4,506.14	38.03	-359.01	7,256,954.14	2,085,738.24	40.231316	-109.904889	-43.60	1.02	0.86	2.58
4,634.00	12.60	276.40	4,596.87	40.17	-379.34	7,256,956.27	2,085,717.91	40.231323	-109.904962	-46.05	0.29	-0.22	0.86
4,727.00	12.70	275.50	4,687.61	42.28	-399.60	7,256,958.38	2,085,697.65	40.231330	-109.905034	-48.48	0.24	0.11	-0.97
4,819.00	12.50	275.20	4,777.39	44.15	-419.58	7,256,960.25	2,085,677.67	40.231336	-109.905105	-50.66	0.23	-0.22	-0.33
4,913.00	12.20	272.80	4,869.22	45.56	-439.63	7,256,961.66	2,085,657.62	40.231341	-109.905177	-52.38	0.63	-0.32	-2.55
5,006.00	13.40	275.20	4,959.91	47.01	-460.18	7,256,963.12	2,085,637.07	40.231346	-109.905251	-54.15	1.41	1.29	2.58
5,100.00	14.00	274.20	5,051.23	48.83	-482.37	7,256,964.94	2,085,614.88	40.231352	-109.905330	-56.32	0.69	0.64	-1.06
5,194.00	13.70	273.40	5,142.50	50.33	-504.82	7,256,966.43	2,085,592.43	40.231357	-109.905410	-58.16	0.38	-0.32	-0.85
5,286.00	12.70	268.90	5,232.07	50.78	-525.81	7,256,966.88	2,085,571.44	40.231359	-109.905485	-58.94	1.56	-1.09	-4.89
5,379.00	12.00	262.10	5,322.92	49.25	-545.60	7,256,965.36	2,085,551.64	40.231356	-109.905556	-57.72	1.73	-0.75	-7.31
5,473.00	12.10	265.50	5,414.85	47.14	-565.11	7,256,963.24	2,085,532.14	40.231351	-109.905626	-55.91	0.76	0.11	3.62
5,566.00	12.20	269.70	5,505.77	46.32	-584.65	7,256,962.43	2,085,512.60	40.231350	-109.905696	-55.40	0.96	0.11	4.52
5,659.00	12.50	274.40	5,596.62	47.04	-604.51	7,256,963.15	2,085,492.74	40.231353	-109.905768	-56.42	1.13	0.32	5.05
5,753.00	13.80	279.50	5,688.16	49.67	-625.71	7,256,965.78	2,085,471.54	40.231361	-109.905843	-59.38	1.85	1.38	5.43
5,847.00	12.80	277.00	5,779.64	52.79	-647.11	7,256,968.90	2,085,450.14	40.231371	-109.905920	-62.84	1.23	-1.06	-2.66
5,940.00	12.00	271.30	5,870.47	54.27	-667.00	7,256,970.37	2,085,430.25	40.231376	-109.905991	-64.62	1.57	-0.86	-6.13
6,033.00	10.60	266.80	5,961.67	54.01	-685.20	7,256,970.11	2,085,412.04	40.231376	-109.906056	-64.64	1.78	-1.51	-4.84
6,126.00	10.80	272.60	6,053.05	53.93	-702.45	7,256,970.03	2,085,394.80	40.231377	-109.906118	-64.83	1.18	0.22	6.24
6,218.00	11.70	276.30	6,143.28	55.34	-720.33	7,256,971.45	2,085,376.91	40.231381	-109.906182	-66.52	1.25	0.98	4.02
6,311.00	10.40	274.30	6,234.56	57.00	-738.08	7,256,973.11	2,085,359.17	40.231387	-109.906245	-68.46	1.46	-1.40	-2.15
6,404.00	9.90	273.00	6,326.10	58.05	-754.43	7,256,974.16	2,085,342.82	40.231391	-109.906304	-69.76	0.59	-0.54	-1.40
6,497.00	10.30	270.80	6,417.66	58.59	-770.73	7,256,974.69	2,085,326.52	40.231393	-109.906362	-70.55	0.60	0.43	-2.37
6,589.00	9.70	266.70	6,508.26	58.26	-786.69	7,256,974.36	2,085,310.56	40.231393	-109.906419	-70.47	1.01	-0.65	-4.46
6,683.00	8.70	265.50	6,601.05	57.24	-801.68	7,256,973.35	2,085,295.56	40.231391	-109.906473	-69.69	1.08	-1.06	-1.28
6,776.00	8.70	274.50	6,692.99	57.24	-815.71	7,256,973.35	2,085,281.54	40.231391	-109.906523	-69.90	1.46	0.00	9.68
6,870.00	7.70	270.10	6,786.03	57.81	-829.09	7,256,973.92	2,085,268.15	40.231394	-109.906571	-70.68	1.26	-1.06	-4.68
6,962.00	8.10	268.50	6,877.15	57.65	-841.74	7,256,973.76	2,085,255.51	40.231394	-109.906616	-70.72	0.50	0.43	-1.74
7,057.00	7.90	268.40	6,971.23	57.29	-854.95	7,256,973.40	2,085,242.29	40.231393	-109.906664	-70.57	0.21	-0.21	-0.11
7,149.00	6.30	267.40	7,062.52	56.89	-866.32	7,256,972.99	2,085,230.93	40.231393	-109.906704	-70.34	1.74	-1.74	-1.09
7,242.00	3.70	283.90	7,155.16	57.38	-874.33	7,256,973.48	2,085,222.92	40.231395	-109.906733	-70.95	3.17	-2.80	17.74
7,335.00	3.90	291.60	7,247.96	59.26	-880.18	7,256,975.37	2,085,217.07	40.231400	-109.906754	-72.93	0.59	0.22	8.28
7,429.00	1.80	273.80	7,341.84	60.54	-884.63	7,256,976.64	2,085,212.62	40.231404	-109.906770	-74.27	2.40	-2.23	-18.94



Survey Report

Company:	Uinta Wax	Local Co-ordinate Reference:	Well RD TRIBAL 17S-31E-H4UB
Project:	UINTAH COUNTY, UT (NAD 83) UTCZ GRID	TVD Reference:	23' KB @ 5036.00usft
Site:	S8-T3S-R1E (Sand View)	MD Reference:	23' KB @ 5036.00usft
Well:	RD TRIBAL 17S-31E-H4UB	North Reference:	Grid
Wellbore:	OH (240896)	Survey Calculation Method:	Minimum Curvature
Design:	SURVEYS	Database:	.Total Directional Production DB

Survey

Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	+E/-W (usft)	Map Coordinates Northing (usft)	Easting (usft)	Geo Coordinates Latitude (°)	Longitude (°)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
7,523.00	2.00	232.40	7,435.79	59.63	-887.40	7,256,975.74	2,085,209.85	40.231401	-109.906780	-73.41	1.44	0.21	-44.04
7,616.00	3.30	211.30	7,528.69	56.36	-890.08	7,256,972.46	2,085,207.17	40.231393	-109.906790	-70.18	1.73	1.40	-22.69
7,709.00	3.10	210.20	7,621.55	51.90	-892.73	7,256,968.00	2,085,204.51	40.231380	-109.906799	-65.76	0.22	-0.22	-1.18
7,802.00	4.30	215.30	7,714.35	46.88	-896.01	7,256,962.98	2,085,201.24	40.231367	-109.906811	-60.79	1.34	1.29	5.48
7,895.00	11.40	217.90	7,806.42	36.77	-903.68	7,256,952.87	2,085,193.56	40.231339	-109.906840	-50.80	7.64	7.63	2.80
7,950.00	15.10	220.00	7,859.95	26.99	-911.63	7,256,943.09	2,085,185.62	40.231313	-109.906869	-41.14	6.78	6.73	3.82
8,063.00	21.60	194.90	7,967.31	-4.47	-926.48	7,256,911.64	2,085,170.77	40.231227	-109.906924	-9.92	8.93	5.75	-22.21
8,156.00	28.70	184.40	8,051.48	-43.35	-932.60	7,256,872.76	2,085,164.64	40.231121	-109.906948	28.85	8.99	7.63	-11.29
8,249.00	34.50	183.10	8,130.66	-91.95	-935.74	7,256,824.15	2,085,161.50	40.230988	-109.906963	77.41	6.28	6.24	-1.40
8,342.00	47.10	182.80	8,200.92	-152.52	-938.84	7,256,763.59	2,085,158.40	40.230822	-109.906978	137.92	13.55	13.55	-0.32
8,435.00	53.10	181.50	8,260.55	-223.78	-941.48	7,256,692.33	2,085,155.76	40.230626	-109.906992	209.13	6.54	6.45	-1.40
8,528.00	58.90	182.90	8,312.53	-300.79	-944.47	7,256,615.32	2,085,152.77	40.230415	-109.907007	286.08	6.36	6.24	1.51
8,621.00	59.40	182.30	8,360.22	-380.55	-948.10	7,256,535.56	2,085,149.15	40.230196	-109.907025	365.77	0.77	0.54	-0.65
8,715.00	68.90	181.80	8,401.16	-464.99	-951.10	7,256,451.12	2,085,146.15	40.229965	-109.907041	450.16	10.12	10.11	-0.53
8,808.00	82.00	182.20	8,424.47	-554.75	-954.25	7,256,361.35	2,085,143.00	40.229718	-109.907058	539.87	14.09	14.09	0.43
8,900.00	87.30	181.30	8,433.05	-646.28	-957.04	7,256,269.83	2,085,140.21	40.229467	-109.907074	631.33	5.84	5.76	-0.98
8,966.18	90.68	179.05	8,434.21	-712.43	-957.24	7,256,203.67	2,085,140.01	40.229286	-109.907079	697.48	6.14	5.11	-3.40
LP - RDT 17S H4UB (50 FNL, 2634 FEL)													
8,994.00	92.10	178.10	8,433.54	-740.24	-956.55	7,256,175.87	2,085,140.70	40.229209	-109.907078	725.29	6.14	5.11	-3.40
9,016.69	92.25	178.49	8,432.68	-762.90	-955.87	7,256,153.21	2,085,141.37	40.229147	-109.907077	747.96	1.84	0.65	1.72
FTP - 9016.69' MD													
9,017.64	92.25	178.51	8,432.64	-763.85	-955.85	7,256,152.26	2,085,141.40	40.229145	-109.907077	748.91	1.84	0.65	1.72
FTP - RDT 17S H4UB (100 FNL, 2634 FEL)													
9,087.00	92.70	179.70	8,429.65	-833.13	-954.76	7,256,082.97	2,085,142.48	40.228954	-109.907078	818.20	1.84	0.64	1.72
9,181.00	92.20	181.40	8,425.63	-927.04	-955.67	7,255,989.07	2,085,141.58	40.228697	-109.907087	912.08	1.88	-0.53	1.81
9,274.00	91.30	178.30	8,422.79	-1,019.98	-955.42	7,255,896.12	2,085,141.83	40.228441	-109.907092	1,005.02	3.47	-0.97	-3.33
9,367.00	93.10	179.80	8,419.22	-1,112.90	-953.88	7,255,803.21	2,085,143.37	40.228186	-109.907093	1,097.94	2.52	1.94	1.61
9,459.00	90.00	175.40	8,416.73	-1,204.75	-950.03	7,255,711.36	2,085,147.22	40.227934	-109.907085	1,189.85	5.85	-3.37	-4.78
9,552.00	92.00	177.00	8,415.10	-1,297.52	-943.87	7,255,618.59	2,085,153.38	40.227679	-109.907069	1,282.70	2.75	2.15	1.72
9,645.00	93.70	177.30	8,410.48	-1,390.29	-939.25	7,255,525.82	2,085,158.00	40.227424	-109.907058	1,375.53	1.86	1.83	0.32
9,739.00	92.50	176.50	8,405.40	-1,484.01	-934.17	7,255,432.10	2,085,163.08	40.227167	-109.907046	1,469.32	1.53	-1.28	-0.85
9,832.00	92.40	175.90	8,401.42	-1,576.72	-928.01	7,255,339.39	2,085,169.24	40.226912	-109.907030	1,562.12	0.65	-0.11	-0.65
9,925.00	90.70	172.80	8,398.90	-1,669.22	-918.86	7,255,246.89	2,085,178.39	40.226658	-109.907003	1,654.75	3.80	-1.83	-3.33
10,018.00	92.40	173.70	8,396.39	-1,761.54	-907.93	7,255,154.57	2,085,189.31	40.226404	-109.906970	1,747.22	2.07	1.83	0.97
10,112.00	93.70	174.80	8,391.39	-1,854.93	-898.53	7,255,061.18	2,085,198.72	40.226147	-109.906942	1,840.75	1.81	1.38	1.17
10,205.00	90.90	175.90	8,387.66	-1,947.54	-891.00	7,254,968.57	2,085,206.25	40.225892	-109.906921	1,933.46	3.23	-3.01	1.18
10,272.22	92.71	177.13	8,385.54	-2,014.60	-886.91	7,254,901.51	2,085,210.34	40.225708	-109.906910	2,000.58	3.25	2.69	1.83
RD TRIBAL 17S-31E-H4UB - 2000' VS													



Survey Report

Company:	Uinta Wax	Local Co-ordinate Reference:	Well RD TRIBAL 17S-31E-H4UB
Project:	UINTAH COUNTY, UT (NAD 83) UTCZ GRID	TVD Reference:	23' KB @ 5036.00usft
Site:	S8-T3S-R1E (Sand View)	MD Reference:	23' KB @ 5036.00usft
Well:	RD TRIBAL 17S-31E-H4UB	North Reference:	Grid
Wellbore:	OH (240896)	Survey Calculation Method:	Minimum Curvature
Design:	SURVEYS	Database:	.Total Directional Production DB

Survey													
Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	Local Coordinates +E/-W (usft)	Map Coordinates Northing (usft)	Map Coordinates Easting (usft)	Geo Coordinates Latitude (°)	Geo Coordinates Longitude (°)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,298.00	93.40	177.60	8,384.17	-2,040.31	-885.73	7,254,875.80	2,085,211.52	40.225638	-109.906908	2,026.31	3.25	2.69	1.83
10,391.00	93.10	176.20	8,378.89	-2,133.02	-880.71	7,254,783.08	2,085,216.54	40.225383	-109.906896	2,119.09	1.54	-0.32	-1.51
10,484.00	88.00	177.80	8,378.00	-2,225.86	-875.84	7,254,690.25	2,085,221.41	40.225128	-109.906884	2,211.99	5.75	-5.48	1.72
10,577.00	92.00	178.40	8,378.00	-2,318.79	-872.76	7,254,597.32	2,085,224.49	40.224873	-109.906879	2,304.95	4.35	4.30	0.65
10,670.00	93.60	179.20	8,373.46	-2,411.65	-870.81	7,254,504.45	2,085,226.43	40.224618	-109.906878	2,397.84	1.92	1.72	0.86
10,763.00	91.30	179.40	8,369.48	-2,504.55	-869.68	7,254,411.55	2,085,227.57	40.224362	-109.906880	2,490.74	2.48	-2.47	0.22
10,857.00	92.00	177.90	8,366.78	-2,598.49	-867.47	7,254,317.62	2,085,229.78	40.224105	-109.906878	2,584.70	1.76	0.74	-1.60
10,950.00	92.80	176.70	8,362.88	-2,691.30	-863.09	7,254,224.81	2,085,234.16	40.223850	-109.906868	2,677.57	1.55	0.86	-1.29
11,043.00	92.10	174.10	8,358.91	-2,783.91	-855.64	7,254,132.20	2,085,241.61	40.223595	-109.906847	2,770.28	2.89	-0.75	-2.80
11,136.00	91.60	178.50	8,355.90	-2,876.64	-849.64	7,254,039.47	2,085,247.61	40.223340	-109.906832	2,863.10	4.76	-0.54	4.73
11,230.00	92.70	179.70	8,352.37	-2,970.56	-848.17	7,253,945.55	2,085,249.08	40.223082	-109.906833	2,957.03	1.73	1.17	1.28
11,323.00	92.70	179.50	8,347.99	-3,063.45	-847.52	7,253,852.65	2,085,249.73	40.222827	-109.906836	3,049.92	0.21	0.00	-0.22
11,416.00	92.10	179.50	8,344.10	-3,156.37	-846.71	7,253,759.74	2,085,250.54	40.222572	-109.906839	3,142.84	0.65	-0.65	0.00
11,510.00	91.80	176.80	8,340.90	-3,250.26	-843.67	7,253,665.85	2,085,253.57	40.222314	-109.906834	3,236.76	2.89	-0.32	-2.87
11,603.00	92.00	180.00	8,337.82	-3,343.16	-841.08	7,253,572.95	2,085,256.17	40.222059	-109.906831	3,329.69	3.45	0.22	3.44
11,696.00	93.00	180.10	8,333.76	-3,436.07	-841.16	7,253,480.04	2,085,256.09	40.221804	-109.906837	3,422.59	1.08	1.08	0.11
11,789.00	91.30	178.10	8,330.27	-3,528.98	-839.70	7,253,387.12	2,085,257.55	40.221549	-109.906838	3,515.51	2.82	-1.83	-2.15
11,882.00	91.20	177.80	8,328.24	-3,621.90	-836.37	7,253,294.21	2,085,260.88	40.221294	-109.906832	3,608.47	0.34	-0.11	-0.32
11,975.00	92.20	177.70	8,325.48	-3,714.79	-832.72	7,253,201.32	2,085,264.52	40.221039	-109.906825	3,701.40	1.08	1.08	-0.11
12,068.00	92.30	175.90	8,321.83	-3,807.57	-827.54	7,253,108.54	2,085,269.71	40.220784	-109.906812	3,794.25	1.94	0.11	-1.94
12,161.00	90.90	178.80	8,319.23	-3,900.42	-823.24	7,253,015.69	2,085,274.01	40.220529	-109.906803	3,887.16	3.46	-1.51	3.12
12,254.00	91.80	178.80	8,317.04	-3,993.37	-821.29	7,252,922.74	2,085,275.96	40.220274	-109.906802	3,980.13	0.97	0.97	0.00
12,348.00	93.30	179.50	8,312.86	-4,087.26	-819.90	7,252,828.84	2,085,277.35	40.220016	-109.906803	4,074.04	1.76	1.60	0.74
12,441.00	92.10	177.70	8,308.48	-4,180.13	-817.63	7,252,735.98	2,085,279.62	40.219761	-109.906800	4,166.92	2.32	-1.29	-1.94
12,534.00	91.30	178.30	8,305.72	-4,273.03	-814.38	7,252,643.08	2,085,282.86	40.219506	-109.906795	4,259.86	1.08	-0.86	0.65
12,627.00	93.50	179.30	8,301.83	-4,365.92	-812.44	7,252,550.19	2,085,284.81	40.219251	-109.906794	4,352.77	2.60	2.37	1.08
12,719.00	92.70	178.20	8,296.85	-4,457.76	-810.43	7,252,458.35	2,085,286.81	40.218998	-109.906792	4,444.64	1.48	-0.87	-1.20
12,813.00	88.80	177.90	8,295.62	-4,551.68	-807.24	7,252,364.43	2,085,290.01	40.218741	-109.906787	4,538.59	4.16	-4.15	-0.32
12,906.00	91.60	180.10	8,295.30	-4,644.65	-805.61	7,252,271.46	2,085,291.63	40.218485	-109.906787	4,631.58	3.83	3.01	2.37
13,000.00	91.30	180.40	8,292.92	-4,738.62	-806.02	7,252,177.49	2,085,291.22	40.218227	-109.906794	4,725.53	0.45	-0.32	0.32
13,093.00	92.30	178.90	8,290.00	-4,831.57	-805.46	7,252,084.54	2,085,291.79	40.217972	-109.906798	4,818.47	1.94	1.08	-1.61
13,186.00	96.90	176.80	8,282.54	-4,924.17	-801.98	7,251,991.93	2,085,295.26	40.217718	-109.906792	4,911.12	5.43	4.95	-2.26
13,274.77	91.80	182.28	8,275.80	-5,012.62	-801.29	7,251,903.48	2,085,295.96	40.217475	-109.906795	4,999.57	8.42	-5.74	6.17
RD TRIBAL 17S-31E-H4UB - 5000' VS													
13,280.00	91.50	182.60	8,275.65	-5,017.84	-801.51	7,251,898.26	2,085,295.74	40.217461	-109.906796	5,004.79	8.42	-5.76	6.14
13,373.00	90.80	182.20	8,273.78	-5,110.74	-805.40	7,251,805.36	2,085,291.84	40.217206	-109.906816	5,097.62	0.87	-0.75	-0.43
13,466.00	94.00	184.40	8,269.89	-5,203.49	-810.75	7,251,712.62	2,085,286.50	40.216952	-109.906841	5,190.27	4.17	3.44	2.37
13,559.00	91.50	182.40	8,265.43	-5,296.21	-816.26	7,251,619.90	2,085,280.99	40.216697	-109.906867	5,282.89	3.44	-2.69	-2.15



Survey Report

Company:	Uinta Wax	Local Co-ordinate Reference:	Well RD TRIBAL 17S-31E-H4UB
Project:	UINTAH COUNTY, UT (NAD 83) UTCZ GRID	TVD Reference:	23' KB @ 5036.00usft
Site:	S8-T3S-R1E (Sand View)	MD Reference:	23' KB @ 5036.00usft
Well:	RD TRIBAL 17S-31E-H4UB	North Reference:	Grid
Wellbore:	OH (240896)	Survey Calculation Method:	Minimum Curvature
Design:	SURVEYS	Database:	.Total Directional Production DB

Survey

Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	+E/-W (usft)	Map Coordinates Northing (usft)	Easting (usft)	Geo Coordinates Latitude (°)	Longitude (°)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
13,652.00	91.80	181.00	8,262.75	-5,389.13	-819.01	7,251,526.98	2,085,278.23	40.216443	-109.906882	5,375.75	1.54	0.32	-1.51
13,745.00	91.60	179.30	8,259.99	-5,482.08	-819.26	7,251,434.03	2,085,277.99	40.216187	-109.906889	5,468.69	1.84	-0.22	-1.83
13,838.00	91.60	178.00	8,257.39	-5,575.02	-817.07	7,251,341.09	2,085,280.18	40.215932	-109.906887	5,561.65	1.40	0.00	-1.40
13,931.00	90.80	177.90	8,255.45	-5,667.94	-813.74	7,251,248.17	2,085,283.51	40.215677	-109.906881	5,654.61	0.87	-0.86	-0.11
14,024.00	92.20	178.60	8,253.01	-5,760.86	-810.90	7,251,155.25	2,085,286.35	40.215422	-109.906877	5,747.57	1.68	1.51	0.75
14,117.00	92.80	179.40	8,248.96	-5,853.75	-809.28	7,251,062.35	2,085,287.97	40.215167	-109.906877	5,840.48	1.07	0.65	0.86
14,211.00	91.60	178.70	8,245.35	-5,947.67	-807.72	7,250,968.44	2,085,289.53	40.214909	-109.906878	5,934.41	1.48	-1.28	-0.74
14,304.00	92.40	181.70	8,242.10	-6,040.60	-808.05	7,250,875.51	2,085,289.20	40.214654	-109.906885	6,027.32	3.34	0.86	3.23
14,397.00	93.00	182.40	8,237.72	-6,133.44	-811.37	7,250,782.67	2,085,285.88	40.214399	-109.906903	6,120.09	0.99	0.65	0.75
14,490.00	92.40	180.90	8,233.34	-6,226.29	-814.04	7,250,689.81	2,085,283.20	40.214144	-109.906918	6,212.90	1.74	-0.65	-1.61
14,583.00	90.30	178.20	8,231.15	-6,319.25	-813.31	7,250,596.86	2,085,283.93	40.213889	-109.906921	6,305.85	3.68	-2.26	-2.90
14,676.00	89.50	177.00	8,231.31	-6,412.17	-809.42	7,250,503.94	2,085,287.83	40.213634	-109.906913	6,398.82	1.55	-0.86	-1.29
14,769.00	92.40	178.50	8,229.77	-6,505.07	-805.77	7,250,411.04	2,085,291.48	40.213379	-109.906906	6,491.77	3.51	3.12	1.61
14,863.00	92.50	179.30	8,225.75	-6,598.97	-803.97	7,250,317.14	2,085,293.28	40.213121	-109.906906	6,585.68	0.86	0.11	0.85
14,957.00	92.20	177.90	8,221.90	-6,692.86	-801.67	7,250,223.25	2,085,295.58	40.212863	-109.906904	6,679.60	1.52	-0.32	-1.49
15,049.00	90.70	177.20	8,219.57	-6,784.74	-797.74	7,250,131.37	2,085,299.51	40.212611	-109.906895	6,771.53	1.80	-1.63	-0.76
15,142.00	90.70	180.80	8,218.43	-6,877.70	-796.12	7,250,038.40	2,085,301.13	40.212356	-109.906895	6,864.51	3.87	0.00	3.87
15,235.00	93.60	182.60	8,214.94	-6,970.58	-798.87	7,249,945.52	2,085,298.38	40.212101	-109.906911	6,957.33	3.67	3.12	1.94
15,277.38	92.78	181.73	8,212.58	-7,012.87	-800.47	7,249,903.24	2,085,296.78	40.211985	-109.906920	6,999.59	2.81	-1.93	-2.04
RD TRIBAL 17S-31E-H4UB - 7000' VS													
15,328.00	91.80	180.70	8,210.56	-7,063.43	-801.54	7,249,852.67	2,085,295.70	40.211846	-109.906927	7,050.13	2.81	-1.94	-2.04
15,422.00	90.30	179.50	8,208.84	-7,157.41	-801.71	7,249,758.69	2,085,295.54	40.211588	-109.906933	7,144.10	2.04	-1.60	-1.28
15,515.00	92.10	180.80	8,206.89	-7,250.39	-801.95	7,249,665.72	2,085,295.30	40.211333	-109.906940	7,237.05	2.39	1.94	1.40
15,607.00	92.40	180.80	8,203.28	-7,342.31	-803.24	7,249,573.80	2,085,294.01	40.211081	-109.906951	7,328.94	0.33	0.33	0.00
15,700.00	92.20	180.40	8,199.55	-7,435.23	-804.21	7,249,480.88	2,085,293.04	40.210826	-109.906960	7,421.84	0.48	-0.22	-0.43
15,793.00	90.60	177.90	8,197.27	-7,528.18	-802.83	7,249,387.93	2,085,294.42	40.210571	-109.906961	7,514.80	3.19	-1.72	-2.69
15,885.00	90.20	176.80	8,196.63	-7,620.07	-798.58	7,249,296.03	2,085,298.67	40.210318	-109.906952	7,606.75	1.27	-0.43	-1.20
15,978.00	91.50	182.60	8,195.25	-7,713.02	-798.09	7,249,203.09	2,085,299.16	40.210063	-109.906956	7,699.69	6.39	1.40	6.24
16,071.00	92.60	184.70	8,191.92	-7,805.77	-804.00	7,249,110.34	2,085,293.24	40.209809	-109.906983	7,792.34	2.55	1.18	2.26
16,163.00	92.40	183.20	8,187.91	-7,897.46	-810.33	7,249,018.65	2,085,286.91	40.209557	-109.907011	7,883.92	1.64	-0.22	-1.63
16,257.00	90.30	180.80	8,185.70	-7,991.36	-813.61	7,248,924.74	2,085,283.64	40.209300	-109.907029	7,977.76	3.39	-2.23	-2.55
16,350.00	93.10	182.40	8,182.94	-8,084.27	-816.21	7,248,831.83	2,085,281.04	40.209045	-109.907044	8,070.62	3.47	3.01	1.72
16,443.00	92.10	179.70	8,178.72	-8,177.15	-817.91	7,248,738.95	2,085,279.34	40.208790	-109.907056	8,163.46	3.09	-1.08	-2.90
16,535.00	90.90	177.40	8,176.31	-8,269.08	-815.58	7,248,647.02	2,085,281.67	40.208538	-109.907054	8,255.42	2.82	-1.30	-2.50
16,628.00	92.20	179.10	8,173.79	-8,362.00	-812.74	7,248,554.11	2,085,284.51	40.208282	-109.907050	8,348.37	2.30	1.40	1.83
16,721.00	92.30	178.70	8,170.14	-8,454.91	-810.96	7,248,461.19	2,085,286.29	40.208027	-109.907049	8,441.30	0.44	0.11	-0.43
16,814.00	91.90	177.50	8,166.73	-8,547.80	-807.88	7,248,368.31	2,085,289.37	40.207772	-109.907044	8,534.22	1.36	-0.43	-1.29
16,907.00	92.10	177.40	8,163.49	-8,640.65	-803.74	7,248,275.46	2,085,293.51	40.207517	-109.907035	8,627.12	0.24	0.22	-0.11



Survey Report

Company:	Uinta Wax	Local Co-ordinate Reference:	Well RD TRIBAL 17S-31E-H4UB
Project:	UINTAH COUNTY, UT (NAD 83) UTCZ GRID	TVD Reference:	23' KB @ 5036.00usft
Site:	S8-T3S-R1E (Sand View)	MD Reference:	23' KB @ 5036.00usft
Well:	RD TRIBAL 17S-31E-H4UB	North Reference:	Grid
Wellbore:	OH (240896)	Survey Calculation Method:	Minimum Curvature
Design:	SURVEYS	Database:	.Total Directional Production DB

Survey													
Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Geo Coordinates Latitude (°)	Longituge (°)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
17,000.00	88.80	175.60	8,162.76	-8,733.45	-798.06	7,248,182.65	2,085,299.18	40.207262	-109.907021	8,720.00	4.04	-3.55	-1.94
17,093.00	92.50	177.10	8,161.70	-8,826.24	-792.15	7,248,089.87	2,085,305.10	40.207007	-109.907005	8,812.87	4.29	3.98	1.61
17,186.00	92.20	176.90	8,157.89	-8,919.04	-787.28	7,247,997.07	2,085,309.97	40.206752	-109.906994	8,905.73	0.39	-0.32	-0.22
17,279.00	92.30	177.20	8,154.24	-9,011.84	-782.50	7,247,904.27	2,085,314.75	40.206497	-109.906983	8,998.60	0.34	0.11	0.32
17,371.00	91.30	177.30	8,151.35	-9,103.69	-778.09	7,247,812.42	2,085,319.16	40.206245	-109.906973	9,090.50	1.09	-1.09	0.11
17,465.00	89.10	176.00	8,151.02	-9,197.52	-772.60	7,247,718.59	2,085,324.65	40.205987	-109.906959	9,184.41	2.72	-2.34	-1.38
17,558.00	92.30	178.50	8,149.88	-9,290.39	-768.13	7,247,625.72	2,085,329.11	40.205732	-109.906949	9,277.33	4.37	3.44	2.69
17,651.00	91.10	177.30	8,147.13	-9,383.28	-764.73	7,247,532.83	2,085,332.52	40.205477	-109.906943	9,370.27	1.82	-1.29	-1.29
17,744.00	90.60	177.00	8,145.75	-9,476.15	-760.10	7,247,439.95	2,085,337.14	40.205222	-109.906932	9,463.20	0.63	-0.54	-0.32
17,781.31	90.04	176.44	8,145.54	-9,513.40	-757.97	7,247,402.71	2,085,339.28	40.205119	-109.906927	9,500.48	2.13	-1.51	-1.51
RD TRIBAL 17S-31E-H4UB - 9500' VS													
17,837.00	89.20	175.60	8,145.91	-9,568.95	-754.10	7,247,347.15	2,085,343.15	40.204967	-109.906917	9,556.09	2.13	-1.51	-1.51
17,930.00	92.80	177.80	8,144.28	-9,661.77	-748.75	7,247,254.34	2,085,348.50	40.204712	-109.906903	9,648.97	4.54	3.87	2.37
18,023.00	92.40	177.20	8,140.07	-9,754.58	-744.70	7,247,161.53	2,085,352.55	40.204457	-109.906895	9,741.84	0.77	-0.43	-0.65
18,117.00	92.40	176.40	8,136.13	-9,848.35	-739.46	7,247,067.76	2,085,357.79	40.204199	-109.906882	9,835.68	0.85	0.00	-0.85
18,210.00	92.00	177.40	8,132.56	-9,941.14	-734.43	7,246,974.96	2,085,362.82	40.203944	-109.906870	9,928.54	1.16	-0.43	1.08
18,302.00	90.70	180.70	8,130.39	-10,033.09	-732.91	7,246,883.01	2,085,364.34	40.203692	-109.906870	10,020.50	3.85	-1.41	3.59
18,395.00	88.20	180.70	8,131.28	-10,126.07	-734.04	7,246,790.03	2,085,363.21	40.203436	-109.906880	10,113.45	2.69	-2.69	0.00
18,488.00	89.80	181.20	8,132.91	-10,219.04	-735.58	7,246,697.06	2,085,361.66	40.203181	-109.906892	10,206.38	1.80	1.72	0.54
18,580.00	92.70	181.90	8,130.90	-10,310.98	-738.07	7,246,605.13	2,085,359.18	40.202929	-109.906907	10,298.27	3.24	3.15	0.76
18,616.00	92.20	182.10	8,129.36	-10,346.92	-739.33	7,246,569.18	2,085,357.92	40.202831	-109.906913	10,334.19	1.50	-1.39	0.56
LAST SURVEY - 18616.00' MD													
18,667.00	92.20	182.10	8,127.40	-10,397.85	-741.19	7,246,518.26	2,085,356.05	40.202691	-109.906923	10,385.08	0.00	0.00	0.00
PTB - 18667.00' MD (885 FSL, 2622 FEL) - BHL - RDT 17S H4UB (50 FSL, 2614 FEL) - LTP - RDT 17S H4UB (100 FSL, 2615 FEL)													

Design Annotations					
Measured Depth (usft)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Comment	
9,016.69	8,432.68	-762.90	-955.87	FTP - 9016.69' MD	
18,616.00	8,129.36	-10,346.92	-739.33	LAST SURVEY - 18616.00' MD	
18,667.00	8,127.40	-10,397.85	-741.19	PTB - 18667.00' MD (885 FSL, 2622 FEL)	

Checked By: _____

Approved By: _____

Date: _____