JETZ SPORTS ACADEMY

Trainer Attendance & Password Management API Specification

System: JETZ ERP Core • **Version:** 1.0 • **Auth:** JWT Bearer • **Base URL:** /api

1. API Overview & Endpoint Index

This specification covers two critical administrative and operational workflows in the JETZ ERP backend: **Password Management** (self-service password rotation and administrative one-time temporary resets) and **Trainer Attendance** (coach session check-ins, automated missed-deadline absence handling, correction request workflows, and approval mechanisms).

Method	Endpoint	Permission	Domain
POST	/api/auth/change-password/	Authenticated	Password: Self-service change
POST	/api/users/{id}/reset_password/	Super / Admin	Password: Admin temp reset
GET	/api/coaches/checkins/	coach.view / self	Trainer: List check-in records
POST	/api/coaches/checkins/	IsAuthenticated	Trainer: Check in to own session
PATCH	/api/coaches/checkins/{id}/	IsAuthenticated	Trainer: Correct manual check-in
GET	/api/coaches/corrections/	coach.view / self	Trainer: List correction requests
POST	/api/coaches/corrections/	IsAuthenticated	Trainer: Request absence fix
POST	/api/coaches/corrections/{id}/approve/	attendance.correct	Trainer: Approve correction
POST	/api/coaches/corrections/{id}/reject/	attendance.correct	Trainer: Reject correction
GET	/api/coaches/attendance-config/	settings.view	Trainer: Automation settings
GET	/api/coaches/leaves/	IsAuthenticated	Trainer: Leave management

2. Authentication & Postman Environment Variables

All authenticated endpoints require the standard header: Authorization: Bearer <token>.
The collection includes pre-configured variables for automated testing:

Variable	Default Value	Description
baseUrl	http://localhost:8000/api	Base URL for all backend endpoints
token	Auto-populated	JWT Bearer access token set automatically by login script
coachId	1	Primary key of coach profile
sessionId	1	Primary key of scheduled session
checkinId	1	Primary key of TrainerCheckIn record
correctionId	1	Primary key of TrainerAttendanceCorrection request

targetUserId	2	Primary key of User targeted for password reset

3. Password Management Endpoints

A. Self-Service Password Change

Permission: IsAuthenticated

Path: **POST** /api/auth/change-password/

Description: Enables any logged-in user (admin, coach, or parent) to set a new password. Immediately clears the must_change_password flag so new users can enter the main portal.

Parameters / Headers:
Headers: Content-Type: application/json, Authorization: Bearer <token>

Request Body:
```
{ "old_password": "CurrentPassword@123", "new_password": "NewSecurePass@2026" }
```

Sample Response:
```
{ "detail": "Password changed." }
```

B. Administrative Password Reset

Permission: Super Admin / User Manager

Path: **POST** /api/users/{id}/reset_password/

Description: Issues a cryptographic 12-character one-time temporary password for any managed account. Sets must_change_password = True. Plaintext password is returned exactly once in the response.

Parameters / Headers:
Path: id (User primary key)
Body: {} (Empty JSON object)

Request Body:
```
{}
```

Sample Response:
```
{ "detail": "Temporary password set. Share it securely - it is shown only once.", "temporary_password":
"Xk9#mQ2$vL8!" }
```

4. Trainer Attendance & Check-In Endpoints

C. Record Trainer Check-In

Permission: IsAuthenticated

Path: **POST** /api/coaches/checkins/

Description: Records the trainer's attendance for their assigned session. Enforces database uniqueness on (session, coach). Status choices: present, late, absent, leave.

Parameters / Headers:
Headers: Content-Type: application/json

Request Body:
```
{ "session": 1, "status": "present", "notes": "Checked in on court" }
```

Sample Response:
```
{ "id": 14, "coach": 1, "session": 1, "status": "present", "notes": "Checked in on court",
"auto_marked": false, "marked_at": "2026-10-22T08:00:15Z" }
```

D. List & Filter Trainer Check-Ins

Permission: IsAuthenticated

Path: GET /api/coaches/checkins/

Description: Returns paginated check-in records. Coaches see their own logs; academy managers see all trainers within their school scope.

Parameters / Headers:
Query params: ?coach=, ?session=, ?status=, ?date_from=, ?date_to=, ?page=

Sample Response:

```
{ "count": 1, "results": [ { "id": 14, "coach": 1, "coach_name": "John Doe", "session": 1, "session_date": "2026-10-22", "batch_name": "Elite Badminton U14", "status": "present", "auto_marked": false } ] }
```


E. Update Manual Check-In

Permission: IsAuthenticated (Self)

Path: PATCH /api/coaches/checkins/{id}/

Description: Trainers can update the status or notes of their own manually marked check-in. Auto-marked absences cannot be edited here—they require a formal correction request.

Parameters / Headers:
Path: id (Check-in primary key)

Request Body:

```
{ "status": "late", "notes": "Delayed 10m by traffic" }
```


Sample Response:

```
{ "id": 14, "status": "late", "notes": "Delayed 10m by traffic" }
```


5. Trainer Absence Corrections & Approval Workflow

When a trainer misses the check-in deadline (e.g. 30 mins after session start), the background task marks them absent with auto_marked = True. The coach cannot silently override this; they submit a correction request which must be reviewed and approved by an authorized administrator.

F. Submit Attendance Correction Request

Permission: IsAuthenticated (Coach)

Path: POST /api/coaches/corrections/

Description: Coach submits a claim to fix an automatically-marked absence within the open window (default 7 days). Original status is snapshotted.

Parameters / Headers:
Headers: Content-Type: application/json

Request Body:

```
{ "checkin": 14, "requested_status": "present", "reason": "Phone died before practice; coached full drills", "evidence_note": "Photos taken on court" }
```


Sample Response:

```
{ "id": 8, "checkin": 14, "requested_status": "present", "original_status": "absent", "status": "pending", "requested_at": "2026-10-22T10:15:00Z" }
```

G. Approve / Reject Correction Request

Permission: attendance.correct / Super

Path: POST /api/coaches/corrections/{id}/approve/ (or /reject/)

Description: Admin reviews and approves or rejects the request. Approval mutates the underlying check-in status, clears auto_marked, and writes an audit log.

Parameters / Headers:
POST /approve/ Payload: { "requested_status": "present", "note": "Verified with head coach" } POST /reject/ Payload: { "note": "No confirmation of attendance on court" }

Sample Response:
{ "id": 8, "status": "approved", "reviewed_by": 1, "reviewed_at": "2026-10-22T11:00:00Z", "review_note": "Verified with head coach" }

6. Automation Configuration & Trainer Leaves

H. Automatic Absence Settings

Permission: settings.view / settings.edit

Path: GET / POST /api/coaches/attendance-config/

Description: Configure automated absence sweeps: deadline minutes after session start, correction submission window in days, and enabled flags.

Parameters / Headers:
POST Payload: { "settings": [{ "key": "trainer.auto_absence_enabled", "value": true }, { "key": "trainer.checkin_deadline_minutes", "value": 30 }, { "key": "trainer.correction_deadline_days", "value": 7 }] }

Sample Response:
{ "status": "saved", "count": 3 }

I. Trainer Leave Requests

Permission: IsAuthenticated

Path: GET / POST /api/coaches/leaves/

Description: Coaches submit scheduled leaves. An approved leave exempts the coach from automated absence recording for those sessions.

Parameters / Headers:
POST Payload: { "date": "2026-10-25", "session": 1, "reason": "Medical appointment" }

Sample Response:
{ "id": 3, "coach": 1, "date": "2026-10-25", "status": "pending", "reason": "Medical appointment" }