


---

# Data Structure: Stack

Yongjun Park  
Hanyang University

# Stack ADT

- An ordered list in which insertions and deletions can be performed **at one end of the list**
- operations
  - **push(X, S)**: insert X in the list S
  - **pop(S)**: deletes the most recently inserted element from S




$\text{push}(1, S) \rightarrow \text{push}(2, S) \rightarrow \text{push}(3, S) \rightarrow \text{push}(X, S)$

# Stack ADT: array implementation

```
typedef struct StackRecord *Stack;
```

```
struct StackRecord  
{  
    int Capacity;  
    int TopOfStack;  
    ElementType *Array;  
};
```




# Stack ADT: array implementation

```
#define EmptyTOS ( -1 )
```


```
Stack CreateStack( int MaxElements )
```

```
{  
    Stack S;  
  
    S = malloc( sizeof( struct StackRecord ) );  
    if( S == NULL )  
        FatalError( "Out of space!!!" );  
  
    S->Array = malloc( sizeof( ElementType ) * MaxElements );  
    if( S->Array == NULL )  
        FatalError( "Out of space!!!" );  
  
    S->Capacity = MaxElements;  
    S->TopOfStack = EmptyTOS;  
  
    return S;  
}
```




# Stack ADT: array implementation

```
void Push( ElementType X, Stack S )
{
    if( IsFull( S ) )
        Error( "Full stack" );
    else
        S->Array[ ++S->TopOfStack ] = X;
}
```



# Stack ADT: array implementation


```
void Pop( Stack S )
{
    if( IsEmpty( S ) )
        Error( "Empty stack" );
    else
        S->TopOfStack--;
}
```





# Stack ADT: array implementation

```
ElementType Top( Stack S)
{
    if( !IsEmpty( S ) )
        return S->Array[ S->TopOfStack ];

    Error( "Empty stack" );
    return 0;
}
```



# Stack ADT: linked list implementation




```
struct Node;  
typedef struct Node *PtrToNode;  
typedef PtrToNode Stack;  
  
struct Node{  
    ElementType Element;  
    PtrToNode Next;  
};
```



# Stack ADT: linked list implementation

```
Stack CreateStack (){  
  
    Stack S;  
    S = malloc(sizeof (struct Node));  
  
    if (S==NULL)  
        FatalError("Out of space !!!");  
  
    S -> Next = NULL;  
    return S;  
}
```




# Stack ADT: linked list implementation

```
void MakeEmpty(Stack S) {  
    if (S == NULL)  
        Error ("No stack exists");  
    else  
        while( !IsEmpty(S))  
            Pop(S);  
}
```




# Stack ADT: linked list implementation

Push (ElementType X, Stack S)




# Stack ADT: linked list implementation



```
void Push (ElementType X, Stack S) {  
  
    PtrToNode TmpCell;  
    TmpCell = malloc (sizeof (struct Node));  
  
    if (TmpCell == NULL) {  
        FatalError("Out of space !!!");  
    } else {  
        TmpCell -> Element = X;  
        TmpCell -> Next = S -> Next;  
        S -> Next = TmpCell;  
    }  
}
```




# Stack ADT: linked list implementation

```
ElementType Top (Stack S) {  
    if (!IsEmpty(S))  
        return S->Next->Element;  
  
    Error ("Empty stack");  
    return 0;  
}
```




# Stack ADT: linked list implementation

Pop (Stack S)




# Stack ADT: linked list implementation

```
void Pop (Stack S) {  
  
    PtrToNode FirstCell;  
  
    if (IsEmpty(S))  
        Error("Empty stack");  
    else{  
        FirstCell = S->Next;  
        S->Next = S->Next->Next;  
        free(FirstCell);  
    }  
}
```



# infix, prefix, and postfix notation


infix





# infix, prefix, and postfix notation

infix



prefix

$$(3 + 4) * 6 \longrightarrow * + 3 4 6$$

$$3 + (4 * 6) \longrightarrow + 3 * 4 6$$

postfix

$$(3 + 4) * 6 \longrightarrow 3 4 + 6 *$$

$$3 + (4 * 6) \longrightarrow 3 4 6 * +$$



$$\overbrace{2 * 3 = 6}$$
$$\overbrace{7-6} = 1$$
$$\boxed{1^4 = 1}$$
$$\overbrace{9 / 3 = 3}$$
$$\overbrace{1 + 3} = 4$$


---

# Stack ADT: postfix evaluation


- ▶ scan left-to-right
- ▶ place the operands on a stack until an operator is found
- ▶ perform operations by popping two elements in the stack when an operator is found



# Stack ADT: postfix evaluation

6 5 2 3 + 8 \* + 3 + \*

→ TopOfStack



---

# Stack ADT: prefix evaluation

how can we evaluate prefix expression?

- + \* 2 3 + 5 4 9



# Stack ADT: translation of infix to postfix

$$3 + 4 * 6 \longrightarrow 3 4 6 * +$$

$$(3 + 4) * 6 \longrightarrow 3 4 + 6 *$$

$$3 + (4 * 6) \longrightarrow 3 4 6 * +$$



# Stack ADT: translation of infix to postfix

When you meet an **operand**, print it.

$$3 + 4 * 6 \longrightarrow 3 \ 4 \ 6 \ * \ +$$

$$(3 + 4) * 6 \longrightarrow 3 \ 4 \ + \ 6 \ *$$

$$3 + (4 * 6) \longrightarrow 3 \ 4 \ 6 \ * \ +$$



# Stack ADT: translation of infix to postfix

When you meet an **operand**, print it.

When you meet an **operator**, push it as long as the precedence of the **operator at the top of the stack is less** than the precedence of the incoming operator. Otherwise, pop the top in the stack and print it.

$$3 + 4 * 6 \longrightarrow 3 \ 4 \ 6 \ * \ +$$
$$3 + 4 * 6 + 5 \longrightarrow 3 \ 4 \ 6 \ * \ + \ 5 \ +$$




# Stack ADT: translation of infix to postfix

When you meet an **operand**, print it.

When you meet an **operator**, push it as long as the precedence of the **operator at the top of the stack is less** than the precedence of the incoming operator. Otherwise, pop the top in the stack and print it.

When you meet the **left parenthesis**, push it in the stack.

When you meet the **right parenthesis**, pop all the operators until we reach the corresponding left parenthesis.

$$(3 + 4) * 6 \longrightarrow 3 4 + 6 *$$



---

# Stack ADT: translation of infix to postfix

When you meet an **operand**, print it.

When you meet an **operator**, push it as long as the precedence of the **operator at the top of the stack is less** than the precedence of the incoming operator. Otherwise, pop the top in the stack and print it.

When you meet the **left parenthesis**, push it in the stack.


When you meet the **right parenthesis**, pop all the operators until we reach the corresponding left parenthesis.

When you reach the **end of expression**, pop all the operators from the stack.




# Stack ADT: translation of infix to postfix

$$(3 + 4) * 6 \longrightarrow 3 4 + 6 *$$




# Stack ADT: translation of infix to postfix

$$(3 + 4) * 6 \longrightarrow 3\ 4\ +\ 6\ *$$




$$3 + (4 * 6) \longrightarrow 3\ 4\ 6\ *\ +$$



# Stack ADT: translation of infix to postfix

$a + b * c + (d * e + f) * g \rightarrow a b c * + d e * f + g * +$




# Stack ADT: translation of infix to postfix

infix	postfix
$2 + 3 * 4$	$2\ 3\ 4\ *\ +$
$a * b + 5$	$a\ b\ *\ 5\ +$
$(1 + 2) * 7$	$1\ 2\ +\ 7\ *$
$a * b / c$	$a\ b\ *\ c\ /$
$((a / (b - c + d)) * (e - a) * c$	$a\ b\ c\ -\ d\ +\ /\ e\ a\ -\ *\ c\ *$
$a/b - c + d * e - a * c$	$a\ b\ /\ c\ -\ d\ e\ *\ +\ a\ c\ *\ -$


# Queue ADT

- a list that insertion is done at one end, whereas deletion is performed at the other end
- operations
  - enqueue: inserts an element at the end of the list
  - dequeue: deletes the element at the start of the list



# Queue ADT

```
#define MAX_QUEUE_SIZE 100
typedef struct {
    int key;
} element;
element queue[MAX_QUEUE_SIZE];
int rear = -1;
int front = 0;
```





# Queue ADT

```
void Enqueue(element item, element* queue) {  
  
    if (rear == MAX_QUEUE_SIZE - 1)  
        queue_full();          /* error */  
    queue[++rear] = item;  
}
```

0 1 2 3



0 1 2 3




↑ front

↑ rear



# Queue ADT

```
void Enqueue(element item, element* queue) {  
  
    if (rear == MAX_QUEUE_SIZE - 1)  
        queue_full();        /* error */  
    queue[++rear] = item;  
}
```



0    1    2    3





↑ front  
↑ rear

# Queue ADT




```
element Dequeue(element* queue) {  
    if (front > rear)          /* empty */  
        queue_empty();        /* error */  
    return queue[front++];  
}
```

↑ front  
↑ rear



# Queue ADT

↑ front  
↑ rear




What is the condition for empty state?

# Queue ADT

↑ front

↑ rear



# Queue ADT

## Example [job scheduling]

- ▶ in the operating system which does not use priorities, jobs are processed in the order they enter the system
- ▶ insertion and deletion from a sequential queue

front	rear	Q[0]	Q[1]	Q[2]	Q[3]	comments
0	-1					queue is empty
0	0	Job1				Job1 is added
0	1	Job1	Job2			Job2 is added
0	2	Job1	Job2	Job3		Job3 is added
1	2		Job2	Job3		Job1 is deleted
2	2			Job3		Job2 is deleted

# Queue ADT



## Example [job scheduling]

- ▶ in the operating system which does not use priorities, jobs are processed in the order they enter the system
- ▶ insertion and deletion from a sequential queue

front	rear	Q[0]	Q[1]	Q[2]	Q[3]	comments
-1	-1					queue is empty
-1	0	Job1				Job1 is added
-1	1	Job1	Job2			Job2 is added
-1	2	Job1	Job2	Job3		Job3 is added
0	2		Job2	Job3		Job1 is deleted
1	2			Job3		Job2 is deleted

# Queue ADT: circular queue





- when front or rear gets to the end of the array, it is wrapped around to the beginning







# Queue ADT: circular queue

- when front or rear gets to the end of the array, it is wrapped around to the beginning




# Queue ADT: circular queue

- when circular queue is full






```
struct QueueRecord{  
  
    int Capacity;  
    int Front;  
    int Rear;  
    int Size;  
    ElementType *Array;  
};
```



# Queue ADT: circular queue


- dequeue()



# Queue ADT: array implementation

- when front or rear gets to the end of the array, it is wrapped around to the beginning

↑ front      ↑ rear



↓ enqueue(1)



↓ enqueue(3)



↓ dequeue()



→ dequeue()



↑ enqueue(9)




↑ enqueue(7)



↑ dequeue()



↑ dequeue()



---

# Queue ADT: array implementation


```
struct QueueRecord;  
typedef struct QueueRecord *Queue;
```

```
struct QueueRecord{  
  
    int Capacity;  
    int Front;  
    int Rear;  
    int Size;  
    ElementType *Array;  
};
```




# Queue ADT: array implementation

```
void MakeEmpty (Queue Q){  
    Q -> Size = 0;  
    Q -> Front = 1;  
    Q -> Rear = 0;  
}
```



# Queue ADT: array implementation

```
static int Succ(int Value, Queue Q){  
    if (++Value == Q->Capacity)  
        Value = 0;  
    return Value;  
}  
  
void Enqueue (ElementType X, Queue Q){  
    if (IsFull(Q))  
        Error("Full queue");  
    else {  
        Q -> Size ++;  
        Q -> Rear = Succ(Q->Rear, Q);  
        Q -> Array[Q->Rear] = X;  
    }  
}
```



# Queue ADT: array implementation

```
void Enqueue (ElementType X, Queue Q){  
    if (IsFull(Q))  
        Error("Full queue");  
    else {  
        Q -> Size ++;  
        Q -> Rear = (Q->Rear + 1) % Q ->Capacity;  
        Q -> Array[Q->Rear] = X;  
    }  
}
```

