



University of
Nottingham
UK | CHINA | MALAYSIA

COMP3055


Machine Learning

Topic 11 – SVM

Dr. Zheng LU
2018 Autumn


Perceptron Revisited: Linear Separators

Binary classification can be viewed as the task of separating two classes in feature space:




Linear Separator

Which of the linear separators is optimal?




Classification Margin

- Distance from example x_i to the separator is $r = \frac{w^T x_i + b}{\|w\|}$.
- Examples closest to the hyperplane are **support vectors**.
- **Margin** ρ of the separator is the distance between support vectors.



Maximum Margin Classification

- Maximizing the margin is good according to intuition.
- Implying that only support vectors matter; other training examples are ignorable.



Linear SVM Mathematically

- Let training set $\{(x_i, y_i)\}_{i=1..w}$, $x_i \in R^d$, $y_i \in \{-1, 1\}$ be separated by a hyperplane with margin ρ . Then for each training example (\mathbf{x}_i, y_i) :

$$\begin{array}{ll} \mathbf{w}^T \mathbf{x}_i + b \leq -\rho/2 & \text{if } y_i = -1 \\ \mathbf{w}^T \mathbf{x}_i + b \geq \rho/2 & \text{if } y_i = 1 \end{array} \quad \Leftrightarrow \quad y_i(\mathbf{w}^T \mathbf{x}_i + b) \geq \rho/2$$

- For every support vector \mathbf{x}_s the above inequality is an equality. After rescaling \mathbf{w} and b by $\rho/2$ in the equality, we obtain that distance between each \mathbf{x}_s and the hyperplane is

$$r = \frac{y_s(\mathbf{w}^T \mathbf{x}_s + b)}{\|\mathbf{w}\|} = \frac{1}{\|\mathbf{w}\|}$$

- Then the margin can be expressed through (rescaled) \mathbf{w} and b as:

$$\rho = 2r = \frac{2}{\|\mathbf{w}\|}$$

Linear SVM Mathematically

- Then we can formulate the quadratic optimization problem:

Find \mathbf{w} and b such that

$\rho = \frac{2}{\|\mathbf{w}\|}$ is maximized,

and for all $(\mathbf{x}_i, y_i), i = 1..n$: $y_i(\mathbf{w}^T \mathbf{x}_i + b) \geq 1$

Which can be reformulated as:

Find \mathbf{w} and b such that

$\Phi(\mathbf{w}) = \|\mathbf{w}\|^2 = \mathbf{w}^T \mathbf{w}$ is minimized,

and for all $(\mathbf{x}_i, y_i), i = 1..n$: $y_i(\mathbf{w}^T \mathbf{x}_i + b) \geq 1$

Solving the Optimization Problem

Find \mathbf{w} and b such that

$\Phi(\mathbf{w}) = \|\mathbf{w}\|^2 = \mathbf{w}^T \mathbf{w}$ is minimized,

and for all $(\mathbf{x}_i, y_i), i = 1..n$: $y_i(\mathbf{w}^T \mathbf{x}_i + b) \geq 1$

- Need to optimize a **quadratic function subject to linear constraints**.
- Quadratic optimization problems are a well-known class of mathematical programming problems for which several (non-trivial) algorithms exist.
- The solution involves constructing a **dual problem** where a **Lagrange multiplier** α_i is associated with every inequality constraint in the primal (original) problem:

Find $\alpha_1 \dots \alpha_n$ such that

$Q(\alpha) = \sum \alpha_i - \frac{1}{2} \sum \sum \alpha_i \alpha_j y_i y_j \mathbf{x}_i^T \mathbf{x}_j$ is maximized and

(1) $\sum \alpha_i y_i = 0$

(2) $\alpha_i \geq 0$ for all α_i

The Optimization Problem Solution

- Given a solution $\alpha_1 \dots \alpha_n$ to the dual problem, solution to the primal is:

$$\mathbf{w} = \sum \alpha_i y_i \mathbf{x}_i, \quad b = y_k - \sum \alpha_i y_i \mathbf{x}_i^T \mathbf{x}_k, \quad \text{for any } \alpha_k > 0$$


- Each non-zero α_i indicates that corresponding \mathbf{x}_i is a support vector.
- Then the classifying function is (note that we don't need \mathbf{w} explicitly):

$$f(\mathbf{x}) = \sum \alpha_i y_i \mathbf{x}_i^T \mathbf{x} + b$$

- Notice that it relies on an *inner product* between the test point \mathbf{x} and the support vectors \mathbf{x}_i – we will return to this later.
- Also keep in mind that solving the optimization problem involved computing the inner products $\mathbf{x}_i^T \mathbf{x}_j$ between all training points.


Soft Margin Classification

- What if the training set is not linearly separable?




Soft Margin Classification

- What if the training set is not linearly separable?
- **Slack variables** ξ_i can be added to allow misclassification of difficult or noisy examples, resulting margin called **soft**.




Soft Margin Classification

- What if the training set is not linearly separable?
- **Slack variables** ξ_i can be added to allow misclassification of difficult or noisy examples, resulting margin called **soft**.



Soft Margin Classification

- What if the training set is not linearly separable?
- **Slack variables** ξ_i can be added to allow misclassification of difficult or noisy examples, resulting margin called **soft**.



Soft Margin Classification Mathematically

- The old formulation:

Find \mathbf{w} and b such that
 $\Phi(\mathbf{w}) = \mathbf{w}^T \mathbf{w}$ is minimized,
and for all $(\mathbf{x}_i, y_i), i = 1..n$: $y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1$

- Modified formulation incorporates slack variables:

Find \mathbf{w} and b such that
 $\Phi(\mathbf{w}) = \mathbf{w}^T \mathbf{w} + C \sum \xi_i$ is minimized,
and for all $(\mathbf{x}_i, y_i), i = 1..n$: $y_i (\mathbf{w}^T \mathbf{x}_i + b) \geq 1 - \xi_i, \quad \xi_i > 0$

- Parameter C can be viewed as a way to control overfitting: it “trades off” the relative importance of maximizing the margin and fitting the training data.

Soft Margin Classification Solution

- Dual problem:

Find $\alpha_1 \dots \alpha_n$ such that

$Q(\alpha) = \sum \alpha_i - \frac{1}{2} \sum \sum \alpha_i \alpha_j y_i y_j \mathbf{x}_i^T \mathbf{x}_j$ is maximized and

(1) $\sum \alpha_i y_i = 0$

(2) $0 \leq \alpha_i \leq C$ for all α_i

- Again, \mathbf{x}_i with non-zero α_i will be support vectors.
- Solution to the dual problem is:

$$\mathbf{w} = \sum \alpha_i y_i \mathbf{x}_i, \quad b = y_k (1 - \xi_k) - \sum \alpha_i y_i \mathbf{x}_i^T \mathbf{x}_k, \quad \text{for any } \alpha_k > 0$$

- Again, we do not need to compute \mathbf{w} explicitly for classification:

$$f(\mathbf{x}) = \sum \alpha_i y_i \mathbf{x}_i^T \mathbf{x} + b$$

Linear SVM - Overview

- The classifier is a *separating hyperplane*.
- Most “important” training points are support vectors; they define the hyperplane.
- Quadratic optimization algorithms can identify which training points \mathbf{x}_i are support vectors with non-zero Lagrangian multipliers α_i .
- Both in the dual formulation of the problem and in the solution training points appear only inside inner products:

Find $\alpha_1 \dots \alpha_n$ such that

$Q(\alpha) = \sum \alpha_i - \frac{1}{2} \sum \sum \alpha_i \alpha_j y_i y_j \mathbf{x}_i^T \mathbf{x}_j$ is maximized and


(1) $\sum \alpha_i y_i = 0$

(2) $0 \leq \alpha_i \leq C$ for all α_i

$$f(\mathbf{x}) = \sum \alpha_i y_i \mathbf{x}_i^T \mathbf{x} + b$$


Non-Linear SVM

- Datasets that are linearly separable with some noise work out great:




Non-Linear SVM

- Datasets that are linearly separable with some noise work out great:



Non-Linear SVM

- Datasets that are linearly separable with some noise work out great:




- But what are we going to do if the dataset is just too hard?



Non-Linear SVM


- Datasets that are linearly separable with some noise work out great:



- But what are we going to do if the dataset is just too hard?




- How about... mapping data to a higher-dimensional space:



Non-Linear SVM


- Datasets that are linearly separable with some noise work out great:



- But what are we going to do if the dataset is just too hard?




- How about... mapping data to a higher-dimensional space:



Non-Linear SVM: Feature Spaces

- **General idea:** the original feature space can always be mapped to some higher-dimensional feature space where the training set is separable:



The “Kernel Trick”

- The linear classifier relies on inner product between vectors $K(\mathbf{x}_i, \mathbf{x}_j) = \mathbf{x}_i^T \mathbf{x}_j$
- If every data point is mapped into high-dimensional space via some transformation $\Phi: \mathbf{x} \rightarrow \phi(\mathbf{x})$, the inner product becomes:

$$K(\mathbf{x}_i, \mathbf{x}_j) = \phi(\mathbf{x}_i)^T \phi(\mathbf{x}_j)$$

- A **kernel function** is a function that is equivalent to an inner product in some feature space.
- Example: 2-dimensional vectors $\mathbf{x} = [x_1 \ x_2]$; let $K(\mathbf{x}_i, \mathbf{x}_j) = (1 + \mathbf{x}_i^T \mathbf{x}_j)^2$, we need to show that $K(\mathbf{x}_i, \mathbf{x}_j) = \phi(\mathbf{x}_i)^T \phi(\mathbf{x}_j)$:

$$\begin{aligned} K(\mathbf{x}_i, \mathbf{x}_j) &= (1 + \mathbf{x}_i^T \mathbf{x}_j)^2 = 1 + x_{i1}^2 x_{j1}^2 + 2 x_{i1} x_{j1} x_{i2} x_{j2} + x_{i2}^2 x_{j2}^2 + 2 x_{i1} x_{j1} + 2 x_{i2} x_{j2} \\ &= [1 \ x_{i1}^2 \ \sqrt{2} x_{i1} x_{i2} \ x_{i2}^2 \ \sqrt{2} x_{i1} \ \sqrt{2} x_{i2}]^T [1 \ x_{j1}^2 \ \sqrt{2} x_{j1} x_{j2} \ x_{j2}^2 \ \sqrt{2} x_{j1} \ \sqrt{2} x_{j2}] \\ &= \phi(\mathbf{x}_i)^T \phi(\mathbf{x}_j), \end{aligned}$$

$$\text{where } \phi(\mathbf{x}) = [1 \ x_1^2 \ \sqrt{2} x_1 x_2 \ x_2^2 \ \sqrt{2} x_1 \ \sqrt{2} x_2]$$

- Thus, a kernel function **implicitly** maps data to a high-dimensional space (without the need to compute each $\phi(\mathbf{x})$ explicitly).

Kernel Functions

- What functions are kernel functions?
 - For some functions $K(\mathbf{x}_i, \mathbf{x}_j)$ checking that $K(\mathbf{x}_i, \mathbf{x}_j) = \varphi(\mathbf{x}_i)^T \varphi(\mathbf{x}_j)$ can be cumbersome.

Kernel Functions

- What functions are kernel functions?
 - For some functions $K(\mathbf{x}_i, \mathbf{x}_j)$ checking that $K(\mathbf{x}_i, \mathbf{x}_j) = \varphi(\mathbf{x}_i)^T \varphi(\mathbf{x}_j)$ can be cumbersome.
- Mercer's theorem
 - *Every semi-positive definite symmetric function is a kernel.*



Examples of Kernel Function

- Linear: $K(\mathbf{x}_i, \mathbf{x}_j) = \mathbf{x}_i^T \mathbf{x}_j$
 - Mapping $\Phi: \mathbf{x} \rightarrow \varphi(\mathbf{x})$, where $\varphi(\mathbf{x})$ is \mathbf{x} itself.
- Polynomial of power p : $K(\mathbf{x}_i, \mathbf{x}_j) = (1 + \mathbf{x}_i^T \mathbf{x}_j)^p$
 - Mapping $\Phi: \mathbf{x} \rightarrow \varphi(\mathbf{x})$, where $\varphi(\mathbf{x})$ has $\binom{d+p}{p}$ dimensions
- Gaussian (radial-basis function): $K(\mathbf{x}_i, \mathbf{x}_j) = e^{-\frac{\|\mathbf{x}_i - \mathbf{x}_j\|^2}{2\sigma^2}}$
 - Mapping $\Phi: \mathbf{x} \rightarrow \varphi(\mathbf{x})$, where $\varphi(\mathbf{x})$ is *infinite-dimensional*: every point is mapped to *a function* (a Gaussian); combination of functions for support vectors is the separator.
- Higher-dimensional space still has *intrinsic* dimensionality d , but linear separators in it correspond to *non-linear* separators in original space.

Non-Linear SVM Mathematically

- Dual problem formulation:

Find $\alpha_1 \dots \alpha_n$ such that

$Q(\alpha) = \sum \alpha_i - \frac{1}{2} \sum \sum \alpha_i \alpha_j y_i y_j K(\mathbf{x}_i, \mathbf{x}_j)$ is maximized and

(1) $\sum \alpha_i y_i = 0$

(2) $\alpha_i \geq 0$ for all α_i

- The solution is:

$$f(x) = \sum \alpha_i y_i K(\mathbf{x}_i, \mathbf{x}) + b$$

- Optimization for finding α_i remains the same!

SVM and Kernel Methods

- Are explicitly based on a theoretical model of learning.
- Come with theoretical guarantees about their performance.
- Have a modular design that allows one to separately implement and design their components.
- Are not affected by local minima.
- Do not suffer from the curse of dimensionality.

SVM Software and Resources

- <http://www.svms.org/tutorials/>
- <http://www.csie.ntu.edu.tw/~cjlin/libsvm/>
 - LIBSVM -- A Library for Support Vector Machines by Chih-Chung Chang and Chih-Jen Lin