



legoESM: A Differentiable Earth System Model in JAX

Technical Documentation of Equations and Implementations

legoESM Development Team

March 2026

Contents

1	Introduction	6
2	Grid Systems	6
2.1	Cubed-Sphere Grid	6
2.1.1	Face-to-Cartesian mapping	6
2.1.2	Cell area	7
2.1.3	Grid spacing	7
2.1.4	Grid angle and wind rotation	7
2.1.5	Halo exchange	7
2.2	Gaussian Grid and Spectral Transforms	7
2.2.1	Grid dimensions	7
2.2.2	Associated Legendre polynomials	8
2.2.3	Spherical harmonic transforms	8
2.2.4	Spectral operators	8
2.2.5	Velocity from vorticity and divergence	8
2.3	Sigma Vertical Coordinate	8
2.3.1	Simmons–Burridge geopotential	8
2.3.2	Sigma-dot	9
2.3.3	Pressure velocity	9
2.4	Height and z^* Coordinates	9
3	Core Operators	9
3.1	Gradient	9
3.2	Divergence (flux form)	9
3.3	Vorticity	10
3.4	C-D Grid Operators (FV3-style, <code>operators_cdgrid.py</code>)	10
3.5	Laplacian and Hyperdiffusion	11
4	Finite-Volume Transport	11
4.1	MUSCL Reconstruction (2nd order, $\text{halo} = 1$)	11
4.2	PPM Reconstruction (4th order, $\text{halo} = 2$)	11
4.2.1	Fourth-order edge values	11
4.2.2	Monotonicity constraint	11
4.2.3	Colella–Woodward limiting	11
4.3	WENO5 Reconstruction (5th order, $\text{halo} = 2$)	12
4.3.1	Left-biased reconstruction at $i + \frac{1}{2}$	12

4.3.2	Smoothness indicators	12
4.3.3	Nonlinear weights	12
4.3.4	Right-biased reconstruction	12
4.4	Rusanov Flux	12
4.5	Well-balanced scheme	12
5	FC-Gram Spectral Operators	12
5.1	Extension operator	13
5.2	Spectral differentiation	13
5.3	C-grid-style divergence damping	13
6	Atmospheric Dynamics	13
6.1	Shallow Water Equations	13
6.2	Hydrostatic Primitive Equations (σ -coordinates)	13
6.3	Spectral Primitive Equations (Vorticity–Divergence)	14
6.4	Non-Hydrostatic Compressible Euler Equations	14
6.4.1	Split-explicit time integration	15
6.4.2	Sponge layer	15
7	Atmospheric Physics	15
7.1	Gray Radiation (Frierson 2006)	15
7.1.1	Longwave optical depth	15
7.1.2	Two-stream LW fluxes	15
7.1.3	Shortwave (Beer–Lambert)	16
7.1.4	Heating rate	16
7.2	RRTMGP Correlated- k Radiation	16
7.3	SBM Convection (Frierson 2007)	16
7.3.1	Moist adiabatic lapse rate	16
7.3.2	Saturation mixing ratio (Tetens)	16
7.3.3	CAPE and trigger	16
7.3.4	Enthalpy-conserving relaxation	16
7.3.5	Precipitation	17
7.4	Held–Suarez Forcing	17
7.4.1	Equilibrium temperature	17
7.4.2	Newtonian relaxation	17
7.4.3	Rayleigh friction	17
7.5	Louis (1979) Turbulence	17
7.5.1	Mixing length	17
7.5.2	Richardson number	17
7.5.3	Stability functions	17
7.6	Vertical Diffusion (Implicit Thomas Algorithm)	17
7.7	Surface Fluxes	18
7.7.1	Constant coefficients (default)	18
7.7.2	Monin–Obukhov Similarity Theory (MOST)	18
7.7.3	COARE 3.0 roughness (Fairall et al. 2003)	19
7.7.4	Large & Yeager (2004) roughness	19
8	Ocean Dynamics	19
8.1	Boussinesq Hydrostatic Primitive Equations	19
8.1.1	Tracer equations (skew-symmetric)	19
8.1.2	Free-surface equation	19
8.2	Barotropic Solver (Forward–Backward, Semi-Implicit Coriolis)	19

8.3	Equation of State (Wright 1997)	20
8.4	Hydrostatic Pressure and Vertical Velocity	20
9	Time Integration	20
9.1	SSP-RK3 (Shu–Osher 1988)	20
9.2	Robert-Asselin-Williams (RAW) Time Filter (v3.7)	20
9.3	Adaptive Hyperdiffusion (v3.7)	21
9.4	Split-Explicit Methods	21
10	Land, Ice, and Coupler	21
10.1	Slab Land Model	21
10.1.1	Energy balance	21
10.1.2	Bucket hydrology	21
10.2	Sea-Ice Model	21
10.2.1	Surface temperature	21
10.2.2	Growth and melt	21
10.2.3	Concentration	21
10.2.4	EVP Rheology (Hunke & Dukowicz 1997)	22
10.2.5	Multi-category ice	22
10.3	Land Carbon Cycle and Stomatal Conductance	22
10.3.1	DALEC-990 Carbon Pools	22
10.3.2	Farquhar (1980) Photosynthesis	22
10.3.3	Stomatal conductance	22
10.4	Tile Coupler	22
11	Machine Learning: Spherical Fourier Neural Operator	23
11.1	Architecture	23
11.2	Spectral convolution	23
12	Conservation Corrections	23
12.1	Atmosphere	23
12.2	Ocean	24
13	Physical Constants	24
14	Ocean Biogeochemistry	24
14.1	Carbonate Chemistry and Air-Sea CO ₂ Exchange	24
14.2	NPZD Ecosystem Model	25
15	CMIP Infrastructure	25
15.1	CF/CMOR-Compliant Output	25
15.2	Experiment Templates	25
15.3	Restart and Reproducibility	25
15.4	Tuning Guide	25
16	4D-Var Data Assimilation (v3.9)	26
16.1	Cost Function	26
16.2	Control Vector	26
16.3	Background Error Covariance	26
16.4	Observation Operators	26
16.5	Minimiser	26
16.6	DA Cycling and Incremental Analysis	27

17 References**27**

Introduction

legoESM is a modular Earth System Model written entirely in JAX, supporting automatic differentiation through all components. The model couples atmospheric, oceanic, land, sea-ice, and biogeochemical components on the sphere, with 25+ dynamical cores spanning five discretisation families (C-D grid FV3, finite-volume PPM, pseudospectral, FC-Gram, C-grid) and 35+ physics parameterisations. The cubed-sphere implementation is unified around a single FV3-style C-D grid discretisation (Lin 2004, Putman & Lin 2007) shared by atmosphere (shallow water, hydrostatic PE, non-hydrostatic CE) and ocean, eliminating the Hollingsworth–Kallberg instability. The cubed-sphere transport uses an FV3-faithful PPM reconstruction with monotonicity limiters and flux-form mass transport on staggered grids, complemented by an FV3-exact forward–backward shallow-water core (`fv3_sw_core.py`) implementing the full `c_sw/d_sw` stepping and `d2a2c_vect` (D-grid $\rightarrow$ A-grid $\rightarrow$ C-grid) vector conversion with duo-grid sub-grid metrics ($\sin \alpha_{sg}$, $\cos \alpha_{sg}$) following Mouallem et al. (2023). The model includes a land carbon cycle with Farquhar photosynthesis and stomatal conductance, ocean biogeochemistry (abiotic carbon + NPZD ecosystem), sea-ice dynamics with EVP rheology and multi-category ice, CMIP6-class infrastructure (CF/CMOR output across four tables, experiment templates, restart reproducibility, documented tuning), and a fully differentiable 4D-Var data assimilation system leveraging JAX autodiff for adjoint-free gradient computation. The MPI-distributed runtime supports native 4D halo exchange (one message per neighbour for all vertical levels), reverse-mode AD through MPI via a custom `sendrecv` VJP wrapper, and AD-safe `allreduce(SUM)` for gradient-compatible global reductions. The codebase comprises approximately 385 source modules ($\sim 102,000$ lines of code) validated by 3489 tests across 216 test files.

Design principles.

- Pure-JAX implementation: all components are compatible with `jit`, `grad`, and `vmap`.
- Modular physics: each parameterisation follows a factory pattern returning a callable `physics_fn(state, grid, coord)  $\rightarrow$  Tendencities`.
- Multiple dynamical cores share the same physics interface, enabling interchangeable experiments.
- Neural-network components (SFNO) integrate seamlessly via the same JAX computational graph.

Grid Systems

Cubed-Sphere Grid

Six faces of a cube are mapped to the sphere via **gnomonic (central) projection**. Let $(\alpha_x, \alpha_y) \in [-\pi/4, \pi/4]^2$ be gnomonic coordinates on a face.

Face-to-Cartesian mapping

For face 0 (+x face):

$$(x, y, z) = (1, \tan \alpha_x, \tan \alpha_y), \quad (1)$$

with analogous expressions for the remaining five faces. Points are normalised to the unit sphere: $\hat{\mathbf{r}} = \mathbf{r}/|\mathbf{r}|$, and geographic coordinates follow as $\lambda = \text{atan2}(\hat{y}, \hat{x})$, $\phi = \arcsin(\hat{z})$.

Cell area

The area element on the gnomonic equidistant grid is

$$\Delta A = \frac{R^2 \Delta \alpha^2}{\cos^2 \alpha_x \cos^2 \alpha_y D^3}, \quad D = \sqrt{1 + \tan^2 \alpha_x + \tan^2 \alpha_y}, \quad \Delta \alpha = \frac{\pi}{2n}. \quad (2)$$

Grid spacing

Great-circle distances use the chord-to-arc formula:

$$d = R \cdot 2 \arcsin\left(\frac{|\mathbf{r}_1 - \mathbf{r}_2|}{2}\right). \quad (3)$$

Metric factors $\Delta x_{i,j}$ and $\Delta y_{i,j}$ are computed as two-cell spans for second-order centred differences.

Grid angle and wind rotation

The angle θ between the grid x -axis and geographic east is

$$\theta = \text{atan2}\left(\frac{\partial \phi}{\partial i}, \frac{\partial \lambda}{\partial i} \cos \phi\right). \quad (4)$$

Wind rotation between geographic (u_E, v_N) and grid-aligned (u_g, v_g) :

$$\begin{pmatrix} u_E \\ v_N \end{pmatrix} = \begin{pmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{pmatrix} \begin{pmatrix} u_g \\ v_g \end{pmatrix}. \quad (5)$$

Halo exchange

Scalar fields are exchanged directly across the six-face connectivity table. Vector fields are first rotated to geographic components, padded as scalars, then rotated back using the padded grid angle.

Two halo widths are supported. **Halo = 1** (one ghost cell per side) suffices for second-order centred differences and MUSCL reconstruction. **Halo = 2** (two ghost cells per side) is required by higher-order reconstruction stencils (PPM, WENO5). The halo exchange interpolates neighbour-face strips to the correct gnomonic position at each depth, removing the $O(\Delta \alpha)$ mismatch near cube corners.

Under MPI, the native **4D halo exchange** path (`pad_halo_4d`, `pad_halo_vector_4d`) exchanges all vertical levels in a single MPI message per neighbour, replacing the earlier per-level `vmap(pad_halo)` path. All `sendrecv` calls go through a `@jax.custom_vjp` wrapper that swaps source/dest in the backward pass, enabling `jax.grad` through distributed halo exchange for differentiable MPI simulations.

Gaussian Grid and Spectral Transforms

The spectral dynamical cores use a Gaussian grid with triangular truncation at total wavenumber $n_{\max}$.

Grid dimensions

$$n_{\text{lat}} = \lceil \frac{3}{2}(n_{\max} + 1) \rceil_{\text{even}}, \quad n_{\text{lon}} = 2 n_{\text{lat}}, \quad n_{\text{sh}} = \frac{(n_{\max} + 1)(n_{\max} + 2)}{2}. \quad (6)$$

Latitudes are Gaussian quadrature points $\mu_k = \sin \phi_k$ with weights w_k ; longitudes are equispaced.

Associated Legendre polynomials

Fully normalised (4π) polynomials $P_n^m(\mu)$ satisfy $\int |Y_n^m|^2 dA = 1$. They are computed via the recursion

$$P_m^m = -\sqrt{\frac{2m+1}{2m}} \sqrt{1-\mu^2} P_{m-1}^{m-1}, \quad (7)$$

$$P_n^m = \sqrt{\frac{4n^2-1}{n^2-m^2}} \left(\mu P_{n-1}^m - \sqrt{\frac{(n-1)^2-m^2}{4(n-1)^2-1}} P_{n-2}^m \right). \quad (8)$$

The derivative operator $H_n^m = -(1-\mu^2) dP_n^m/d\mu$ is used for meridional gradients.

Spherical harmonic transforms

Analysis (grid $\rightarrow$ spectral).

$$\hat{f}_{nm} = 2\pi \sum_k w_k P_n^m(\mu_k) \tilde{f}_m(\mu_k), \quad \tilde{f}_m = \frac{1}{n_{\text{lon}}} \text{FFT}[f]_m. \quad (9)$$

Synthesis (spectral $\rightarrow$ grid).

$$f(\phi, \lambda) = \text{iFFT} \left[\sum_{n=m}^{n_{\text{max}}} \hat{f}_{nm} P_n^m(\mu) \right]. \quad (10)$$

Spectral operators

Laplacian eigenvalue: $\nabla^2 \hat{f}_{nm} = -n(n+1)/a^2 \cdot \hat{f}_{nm}$. Inverse Laplacian: $\nabla^{-2} \hat{f}_{nm} = -a^2/[n(n+1)]$ for $n > 0$. Hyperdiffusion: $-\nu[n(n+1)/a^2]^p \hat{f}_{nm}$.

Velocity from vorticity and divergence

Streamfunction $\psi = \nabla^{-2} \zeta$, velocity potential $\chi = \nabla^{-2} \delta$. Velocity reconstruction:

$$u \cos \phi = \frac{\partial \psi}{\partial \theta} + \frac{\partial \chi}{\partial \lambda}, \quad v \cos \phi = \frac{\partial \psi}{\partial \lambda} - \frac{\partial \chi}{\partial \theta}, \quad (11)$$

where θ is colatitude.

Sigma Vertical Coordinate

$$\sigma = p/p_s, \quad \sigma \in [\sigma_{\text{top}}, 1]. \quad (12)$$

Half-level interfaces $\sigma_{k+1/2}$ are uniformly spaced; full levels $\sigma_k = (\sigma_{k-1/2} + \sigma_{k+1/2})/2$. Layer thickness $\Delta\sigma_k = \sigma_{k+1/2} - \sigma_{k-1/2}$.

Simmons–Burridge geopotential

The geopotential at full level k is

$$\Phi_k = \Phi_s + R_d \sum_{k'=k+1}^{N-1} T_{k'} \ln \frac{\sigma_{k'+1/2}}{\sigma_{k'-1/2}} + \alpha_k R_d T_k, \quad (13)$$

where the Simmons–Burridge coefficient is

$$\alpha_k = 1 - \frac{\sigma_{k-1/2}}{\Delta\sigma_k} \ln \frac{\sigma_{k+1/2}}{\sigma_{k-1/2}}. \quad (14)$$

Sigma-dot

The vertical velocity in σ -space is obtained by integrating the continuity equation from the model top ($\dot{\sigma} = 0$):

$$\dot{\sigma}_{k+1/2} = \frac{\sigma_{k+1/2} - \sigma_{\text{top}}}{1 - \sigma_{\text{top}}} D_{\text{tot}} - \sum_{k'=0}^k \nabla \cdot \mathbf{v}_{k'} \Delta \sigma_{k'}, \quad D_{\text{tot}} = \sum_{k'=0}^{N-1} \nabla \cdot \mathbf{v}_{k'} \Delta \sigma_{k'}. \quad (15)$$

Pressure velocity

Since $p = \sigma p_s$, the material pressure tendency is

$$\omega \equiv \frac{dp}{dt} = \sigma \frac{dp_s}{dt} + p_s \dot{\sigma}, \quad (16)$$

where dp_s/dt is the *material* derivative of surface pressure (Eulerian tendency plus advection by the horizontal wind).

Height and z^* Coordinates

The terrain-following z^* coordinate:

$$z^* = H \frac{z - z_s}{H - z_s}, \quad J = \frac{\partial z}{\partial z^*} = \frac{H - z_s}{H}. \quad (17)$$

Physical height: $z(z^*, x, y) = z_s + z^* (H - z_s)/H$.

For the **ocean**, the z^* coordinate has a dynamic Jacobian:

$$J(\eta) = \frac{\eta + H}{H_{\text{max}}}, \quad (18)$$

where η is the free-surface elevation and H the resting depth.

Core Operators

All finite-difference operators use second-order centred differences on the A-grid (collocated) with halo padding on the cubed sphere. The discrete difference operators δ_i and δ_j are defined as centred differences of *cell-centre* values on the padded grid:

$$\delta_i[q]_{i,j} = q_{i+1,j} - q_{i-1,j}, \quad \delta_j[q]_{i,j} = q_{i,j+1} - q_{i,j-1}. \quad (19)$$

All metric-weighted fluxes ($u h_y$, $v h_x$) are evaluated at cell centres before differencing, consistent with the A-grid stencil.

Gradient

$$\left. \frac{\partial f}{\partial x} \right|_{i,j} = \frac{f_{i+1,j} - f_{i-1,j}}{2 \Delta x_{i,j}}, \quad \left. \frac{\partial f}{\partial y} \right|_{i,j} = \frac{f_{i,j+1} - f_{i,j-1}}{2 \Delta y_{i,j}}. \quad (20)$$

Divergence (flux form)

$$\nabla \cdot (u, v) = \frac{1}{2 A_{i,j}} \left[\delta_i(u h_y) + \delta_j(v h_x) \right], \quad (21)$$

where $h_x = \Delta x/2$, $h_y = \Delta y/2$ are half-edge lengths and A is the cell area.

Vorticity

$$\zeta = \frac{1}{2A_{i,j}} \left[\delta_i(v h_y) - \delta_j(u h_x) \right]. \quad (22)$$

C-D Grid Operators (FV3-style, operators_cdgrid.py)

The canonical cubed-sphere operator module uses FV3-style C-D grid staggering (Lin 2004, Putman & Lin 2007), shared by all atmosphere (SW, PE, CE) and ocean dynamical cores. D-grid winds at cell corners $(6, n+1, n+1)$ are prognostic; C-grid velocities at cell edges are diagnosed for mass/scalar transport.

FV3-faithful PPM transport (v3.9). The operator module was rewritten (~ 740 lines) with proper PPM reconstruction, Colella–Woodward monotonicity limiters, and flux-form mass transport on staggered grids, faithfully following the FV3 algorithm of Putman & Lin (2007). This replaces the earlier simplified A-grid transport with a fully staggered C-D grid transport that correctly handles cross-face halo exchange, geographic-to-grid wind rotation, and corner interpolation for the cubed sphere.

D-grid vorticity. Vorticity at each cell corner is the discrete circulation integral divided by the corner dual-cell area A_c :

$$\zeta_{\text{corner}} = \frac{1}{A_c} \oint \mathbf{u} \cdot d\mathbf{l} \approx \frac{1}{A_c} [u_{i,j}^D \Delta x - u_{i+1,j}^D \Delta x + v_{i,j+1}^D \Delta y - v_{i,j}^D \Delta y]. \quad (23)$$

This circulation-based discretisation is exact on the D-grid and eliminates the Hollingsworth–Kallberg instability that plagues A-grid vorticity operators.

Arakawa–Lamb gradient. The Bernoulli (or Exner) gradient at D-grid corners is a 4-point Arakawa–Lamb average:

$$\left. \frac{\partial B}{\partial x} \right|_{i+\frac{1}{2}, j+\frac{1}{2}} = \frac{B_{i+1,j} + B_{i+1,j+1} - B_{i,j} - B_{i,j+1}}{2\Delta x}, \quad (24)$$

and analogously for $\partial B/\partial y$.

C-grid mass-flux divergence. Scalar transport uses upwind C-grid mass fluxes:

$$\frac{dh}{dt} = -\frac{1}{A} [(hu_c)_{i+\frac{1}{2},j} - (hu_c)_{i-\frac{1}{2},j} + (hv_c)_{i,j+\frac{1}{2}} - (hv_c)_{i,j-\frac{1}{2}}], \quad (25)$$

where u_c, v_c are diagnosed from u_d, v_d by face-edge averaging.

FV3 forward–backward shallow-water core (fv3_sw_core.py). An FV3-exact implementation of the complete c_sw/d_sw forward–backward stepping algorithm (Lin 2004). The forward step (c_sw) computes C-grid mass fluxes and height tendencies; the backward step (d_sw) updates D-grid winds using the vorticity flux and pressure gradient. Key components:

- **d2a2c_vect:** D-grid $\rightarrow$ A-grid $\rightarrow$ C-grid vector conversion, faithfully porting the GFDL FV3 algorithm including edge-boundary stencils, one-sided interpolation near cube edges, and non-orthogonality corrections via $\cos \alpha / \sin^{-2} \alpha$ metrics.
- **PPM wind advection:** Piecewise Parabolic Method reconstruction for C-grid wind tendencies (xtp_u, ytp_v), with FV3-specific interpolation coefficients (A_1, A_2, C_1-C_3).
- **PPM vorticity transport:** Monotonic PPM reconstruction for the absolute vorticity flux, stabilising the D-grid wind update.
- **Kinetic energy:** Cell-centred kinetic energy computed from A-grid velocities with optional 4th-order averaging via a2b_ord4.

Duo-grid sub-grid metrics (Mouallem et al. 2023). The cubed-sphere C-D grid includes 9-point sub-grid angle metrics per cell, stored as $\sin \alpha_{\text{sg}}$ and $\cos \alpha_{\text{sg}}$ arrays of shape $(6, n, n, 9)$. These encode the local deviation from orthogonality at cell centres, edge midpoints, and corners, enabling FV3-faithful flux scaling at cube-face boundaries where the gnomonic projection introduces non-orthogonality. Additional C-D grid metrics include centre-to-centre distances Δx_c , Δy_c , and non-orthogonality factors $\cos \alpha_{\text{corner}}$, $(\sin^2 \alpha_{\text{corner}})^{-1}$ at D-grid corners.

Laplacian and Hyperdiffusion

$$\nabla^2 f = \nabla \cdot (\nabla f), \quad \text{Hyperdiffusion:} \quad -\nu \nabla^4 f = -\nu \nabla^2 (\nabla^2 f). \quad (26)$$

Finite-Volume Transport

The finite-volume dynamical cores use upwind reconstruction at cell edges coupled with a Rusanov approximate Riemann solver. Three reconstruction methods are available, selected via the `limiter` parameter.

MUSCL Reconstruction (2nd order, halo = 1)

Piecewise-linear reconstruction with slope limiting (van Leer, 1979). At the interface between cells i and $i+1$:

$$q_L = q_i + \frac{1}{2} \phi_i, \quad q_R = q_{i+1} - \frac{1}{2} \phi_{i+1}, \quad (27)$$

where ϕ_i is the limited slope. Two limiters are provided:

- **Minmod:** $\phi = \text{minmod}(\Delta q_+, \Delta q_-)$,
- **MC** (monotonised central): $\phi = \text{minmod}(\text{minmod}(2\Delta q_+, 2\Delta q_-), \frac{1}{2}(\Delta q_+ + \Delta q_-))$.

PPM Reconstruction (4th order, halo = 2)

The Piecewise Parabolic Method (Colella & Woodward, 1984) constructs a monotone parabola in each cell from two edge values and the cell average.

Fourth-order edge values

At the interface $i + \frac{1}{2}$:

$$\hat{q}_{i+1/2} = \frac{7}{12}(q_i + q_{i+1}) - \frac{1}{12}(q_{i-1} + q_{i+2}). \quad (28)$$

Monotonicity constraint

The edge value is clamped to lie between its two adjacent cell averages:

$$\hat{q}_{i+1/2} \leftarrow \text{median}(\hat{q}_{i+1/2}, q_i, q_{i+1}). \quad (29)$$

Colella–Woodward limiting

For each cell i with left edge value $a_L = \hat{q}_{i-1/2}$ and right edge value $a_R = \hat{q}_{i+1/2}$:

1. If $(a_R - q_i)(q_i - a_L) \leq 0$ (local extremum): set $a_L = a_R = q_i$.
2. Define $\delta_m = a_R - a_L$ and $\delta_6 = 6(q_i - \frac{1}{2}(a_L + a_R))$.
 - If $\delta_m \delta_6 > \delta_m^2$: set $a_L = 3q_i - 2a_R$.
 - If $\delta_m \delta_6 < -\delta_m^2$: set $a_R = 3q_i - 2a_L$.

The left and right states at each edge are then $q_L = a_R$ of the cell to the left and $q_R = a_L$ of the cell to the right.

WENO5 Reconstruction (5th order, halo = 2)

The 5th-order Weighted Essentially Non-Oscillatory scheme (Jiang & Shu, 1996) combines three 3rd-order sub-stencil polynomials with nonlinear weights that adapt to local smoothness.

Left-biased reconstruction at $i + \frac{1}{2}$

Using cells $q_{i-2}, \dots, q_{i+2}$:

$$q^{(0)} = \frac{1}{6}(2q_{i-2} - 7q_{i-1} + 11q_i), \quad d_0 = \frac{1}{10}, \quad (30)$$

$$q^{(1)} = \frac{1}{6}(-q_{i-1} + 5q_i + 2q_{i+1}), \quad d_1 = \frac{6}{10}, \quad (31)$$

$$q^{(2)} = \frac{1}{6}(2q_i + 5q_{i+1} - q_{i+2}), \quad d_2 = \frac{3}{10}. \quad (32)$$

Smoothness indicators

$$\beta_0 = \frac{13}{12}(q_{i-2} - 2q_{i-1} + q_i)^2 + \frac{1}{4}(q_{i-2} - 4q_{i-1} + 3q_i)^2, \quad (33)$$

$$\beta_1 = \frac{13}{12}(q_{i-1} - 2q_i + q_{i+1})^2 + \frac{1}{4}(q_{i-1} - q_{i+1})^2, \quad (34)$$

$$\beta_2 = \frac{13}{12}(q_i - 2q_{i+1} + q_{i+2})^2 + \frac{1}{4}(3q_i - 4q_{i+1} + q_{i+2})^2. \quad (35)$$

Nonlinear weights

$$\alpha_k = \frac{d_k}{(\varepsilon + \beta_k)^2}, \quad \omega_k = \frac{\alpha_k}{\sum_j \alpha_j}, \quad q_L = \sum_k \omega_k q^{(k)}, \quad \varepsilon = 10^{-6}. \quad (36)$$

Right-biased reconstruction

The right state q_R at $i + \frac{1}{2}$ is obtained by mirroring the stencil around the interface, using cells $q_{i-1}, \dots, q_{i+3}$ with ideal weights $d_0 = \frac{1}{10}$, $d_1 = \frac{6}{10}$, $d_2 = \frac{3}{10}$ applied to the reversed sub-stencils.

Rusanov Flux

At each edge, the mass flux is

$$F = \frac{1}{2}(h_L u_L + h_R u_R) - \frac{1}{2} \alpha (h_R - h_L), \quad \alpha = \max(|u_L| + c_L, |u_R| + c_R), \quad (37)$$

where $c = \sqrt{g h}$ is the gravity-wave speed (set to zero for pure transport without wave-speed dissipation). The net flux divergence for cell i is

$$-(\nabla \cdot \mathbf{F})_i = -\frac{1}{A_i} \left[(F_x h_y)_{i+1/2} - (F_x h_y)_{i-1/2} + (G_y h_x)_{j+1/2} - (G_y h_x)_{j-1/2} \right], \quad (38)$$

where h_x, h_y are the edge metric factors.

Well-balanced scheme

When topography h_s is present, the scheme reconstructs the free surface $\eta = h + h_s$ instead of h . The fluid depth at each edge is recovered as $h_L = \max(\eta_L - h_{s,\text{edge}}, 0)$, ensuring zero spurious flux for a lake-at-rest state (Audusse et al., 2004).

FC-Gram Spectral Operators

The Fourier Continuation (FC-Gram) method extends periodic Fourier spectral methods to non-periodic domains by appending a smooth continuation interval. On each cubed-sphere face, the 1D function $f(x)$ on $[0, 1]$ is extended to a periodic function on $[0, 1 + d]$ via a Gram polynomial basis in the continuation region.

Extension operator

Given f sampled at n equispaced points, the extension f_{ext} is constructed as

$$f_{\text{ext}}(x) = \sum_{k=0}^{K-1} \alpha_k G_k(x), \quad x \in [1, 1+d], \quad (39)$$

where G_k are orthogonal Gram polynomials and the coefficients α_k are chosen so that f_{ext} smoothly matches f at both endpoints, yielding a globally smooth periodic extension.

Spectral differentiation

On the extended periodic domain of length $L_{\text{ext}} = 1 + d$, differentiation is performed via FFT:

$$f'_j = \text{IFFT} \left[i k \text{FFT}[f_{\text{ext}}] \right] \Big|_{x_j \in [0,1]}, \quad (40)$$

where k are the Fourier wavenumbers on the extended domain. This achieves spectral accuracy in the interior with controlled Gibbs artifacts at face boundaries.

C-grid-style divergence damping

The FC-Gram variants with divergence damping add 2nd and 4th order selective dissipation of divergent modes:

$$D_{\text{div}} = -\nu_2 \nabla(\nabla \cdot \mathbf{v}) - \nu_4 \nabla(\nabla^2(\nabla \cdot \mathbf{v})), \quad (41)$$

applied to the momentum equations. This selectively damps gravity-wave modes while preserving rotational (balanced) flow, mirroring the divergence damping strategy used in FV3 on its C-D grid.

Atmospheric Dynamics

Shallow Water Equations

In **vector-invariant form** on the cubed sphere:

$$\frac{\partial h}{\partial t} = -\nabla \cdot (h \mathbf{v}), \quad (42)$$

$$\frac{\partial u}{\partial t} = (\zeta + f) v - \frac{\partial B}{\partial x} + D_u, \quad (43)$$

$$\frac{\partial v}{\partial t} = -(\zeta + f) u - \frac{\partial B}{\partial y} + D_v, \quad (44)$$

where the Bernoulli function is $B = \frac{1}{2}(u^2 + v^2) + g(h + h_s)$ and D_u, D_v represent hyperdiffusion.

The mass equation (42) is discretised using the finite-volume Rusanov flux (Section 5) with a configurable reconstruction method: MUSCL (2nd order), PPM (4th order), or WENO5 (5th order), selected via `ShallowWaterConfig.fv_limiter`. Momentum uses centred differences with velocity-only biharmonic hyperdiffusion.

Hydrostatic Primitive Equations (σ -coordinates)

Prognostic variables: u, v (winds), T (temperature), p_s (surface pressure).

$$\frac{\partial p_s}{\partial t} = - \int_0^1 \nabla \cdot (p_s \mathbf{v}) d\sigma, \quad (45)$$

$$\frac{\partial u}{\partial t} = (\zeta + f) v - \frac{\partial B}{\partial x} - R_d T \frac{\partial \ln p_s}{\partial x} + D_u, \quad (46)$$

$$\frac{\partial v}{\partial t} = -(\zeta + f) u - \frac{\partial B}{\partial y} - R_d T \frac{\partial \ln p_s}{\partial y} + D_v, \quad (47)$$

$$\frac{\partial T}{\partial t} = -\nabla \cdot (T \mathbf{v}) + T \nabla \cdot \mathbf{v} - \dot{\sigma} \frac{\partial T}{\partial \sigma} + \kappa T \frac{\omega}{p} + Q, \quad (48)$$

where $B = K + \Phi$, $K = \frac{1}{2}(u^2 + v^2)$, and $\kappa = R_d/c_p$.

Spectral Primitive Equations (Vorticity–Divergence)

On the Gaussian grid, the momentum equations are recast in the vorticity–divergence form (Bourke, 1972):

$$\frac{\partial \hat{\zeta}}{\partial t} = \nabla \times [\widehat{(\zeta + f)} \mathbf{v}] + \widehat{\text{vert. adv.}} - \nu \nabla^{2p} \hat{\zeta}, \quad (49)$$

$$\frac{\partial \hat{\delta}}{\partial t} = \nabla \cdot [\widehat{(\zeta + f)} \mathbf{v}] - \nabla^2 (K + \Phi + R_d T \ln p_s) + \widehat{\text{vert. adv.}} - \nu \nabla^{2p} \hat{\delta}, \quad (50)$$

$$\frac{\partial \hat{T}}{\partial t} = -\nabla \cdot (\widehat{T \mathbf{v}}) + T \nabla \cdot \mathbf{v} - \dot{\sigma} \widehat{\partial T / \partial \sigma} + \widehat{\kappa T \omega / p}, \quad (51)$$

$$\frac{\partial \widehat{\ln p_s}}{\partial t} = - \int_0^1 \hat{\delta} d\sigma. \quad (52)$$

The spectral curl and divergence of flux vectors $(U, V) = (F_u \cos \phi, F_v \cos \phi)$ are

$$\widehat{\text{curl}} = \frac{im}{a} \mathcal{S}[V / \cos^2 \phi] + \frac{1}{a} \mathcal{S}_\mu[U], \quad \widehat{\text{div}} = \frac{im}{a} \mathcal{S}[U / \cos^2 \phi] - \frac{1}{a} \mathcal{S}_\mu[V], \quad (53)$$

where $\mathcal{S}$ and $\mathcal{S}_\mu$ denote the SH analysis with standard and $dP_n^m/d\mu$ Legendre matrices.

Non-Hydrostatic Compressible Euler Equations

In the z^* terrain-following coordinate, the prognostic variables are u, v, w, θ', ρ' (perturbations from a reference state ρ_0, θ_0, π_0).

$$\frac{\partial u}{\partial t} = (\zeta + f) v - \frac{\partial K}{\partial x} - c_p \theta \frac{\partial \pi'}{\partial x} + D_u - r u, \quad (54)$$

$$\frac{\partial v}{\partial t} = -(\zeta + f) u - \frac{\partial K}{\partial y} - c_p \theta \frac{\partial \pi'}{\partial y} + D_v - r v, \quad (55)$$

$$\frac{\partial w}{\partial t} = -\frac{c_p \theta}{J} \frac{\partial \pi'}{\partial z^*} - g \frac{\theta'}{\theta_0} - r w, \quad (56)$$

$$\frac{\partial \theta'}{\partial t} = -\nabla \cdot (\theta \mathbf{v}_h) - \frac{w}{J} \frac{\partial \theta}{\partial z^*} + D_\theta, \quad (57)$$

$$\frac{\partial \rho'}{\partial t} = -\frac{1}{J} \left[\nabla_h \cdot (J \rho \mathbf{v}_h) + \frac{\partial (\rho w)}{\partial z^*} \right], \quad (58)$$

where $r(z)$ is the sponge-layer Rayleigh damping coefficient and the Exner function perturbation is

$$\pi' = \pi_0 \left[\left(1 + \frac{\rho'}{\rho_0} \right) \left(1 + \frac{\theta'}{\theta_0} \right) \right]^{R_d/c_v} - \pi_0. \quad (59)$$

Split-explicit time integration

The equations are integrated with an outer SSP-RK3 scheme for the slow tendencies (advection, Coriolis, horizontal pressure gradient, diffusion) and inner forward–backward acoustic substeps for the fast variables (w, θ', ρ') .

Forward step (w).

$$w^{n+1} = w^n + \Delta t_s \left[-\frac{c_p \theta}{J} \frac{\partial \pi'}{\partial z^*} - g \frac{\theta'}{\theta_0} \right]. \quad (60)$$

Backward step (ρ', θ').

$$\rho'^{n+1} = \rho'^n - \Delta t_s \frac{\partial(\rho w^{n+1})}{\partial z^*}, \quad \theta'^{n+1} = \theta'^n - \Delta t_s \frac{w^{n+1}}{J} \frac{\partial \theta}{\partial z^*}. \quad (61)$$

An optional **semi-implicit acoustic** solve replaces the forward Euler for w with a tridiagonal system to remove the vertical acoustic CFL constraint.

Acoustic off-centering (v3.7). To damp vertically propagating acoustic/gravity wave noise in long integrations, the density update can be off-centred (Skamarock & Klemp 2008):

$$\rho'_\beta^{n+1} = (1 + \beta) \rho'^{n+1} - \beta \rho'^n, \quad (62)$$

where $\beta \geq 0$ is the off-centering parameter (`acoustic_off_centering` in the config). For $\beta = 0$ the scheme is centred (neutral); $\beta = 0.1$ is recommended for AMIP/CMIP runs. This adds a small amount of temporal diffusion to the fast modes without tightening the horizontal CFL constraint.

Sponge layer

$$r(z) = r_{\max} \sin^2 \left(\frac{\pi}{2} \frac{\max(0, z - z_{\text{bot}})}{z_{\text{top}} - z_{\text{bot}}} \right). \quad (63)$$

Atmospheric Physics

Gray Radiation (Frierson 2006)

Longwave optical depth

$$\tau(\sigma, \phi) = [f_l \sigma + (1 - f_l) \sigma^4] [\tau_e + (\tau_p - \tau_e) \sin^2 \phi] + \sum_k \tau_{\text{moist}} q_{v,k} \frac{\Delta p_k}{g}, \quad (64)$$

where the moisture optical depth per layer is $\Delta \tau_{\text{moist},k} = \tau_{\text{moist}} q_{v,k} \Delta p_k / g$, with $\tau_e = 7.2$, $\tau_p = 1.8$, $f_l = 0.2$, $\tau_{\text{moist}} = 0.0115 \text{ m}^2 \text{ kg}^{-1}$.

Two-stream LW fluxes

Layer transmittance and emissivity:

$$\mathcal{T}_k = e^{-D \Delta \tau_k}, \quad \varepsilon_k = 1 - \mathcal{T}_k, \quad D = 1.66. \quad (65)$$

Upward sweep from surface ($F_{\text{sfc}}^\uparrow = \varepsilon_s \sigma_{\text{SB}} T_s^4$):

$$F_k^\uparrow = \mathcal{T}_k F_{k+1}^\uparrow + \varepsilon_k \sigma_{\text{SB}} T_k^4. \quad (66)$$

Downward sweep from TOA ($F_0^\downarrow = 0$):

$$F_k^\downarrow = \mathcal{T}_k F_{k-1}^\downarrow + \varepsilon_k \sigma_{\text{SB}} T_k^4. \quad (67)$$

Shortwave (Beer–Lambert)

$$F_{\text{SW}}^{\downarrow}(k) = \frac{S_0}{4} e^{-\tau_{\text{SW},0} \sigma_k}, \quad F_{\text{SW}}^{\uparrow}(k) = \alpha_s F_{\text{SW}}^{\downarrow}(\text{sfc}), \quad (68)$$

with $\tau_{\text{SW},0} = 0.22$, $S_0 = 1360 \text{ W m}^{-2}$, $\alpha_s = 0.31$. This follows the Frierson/Isca convention used in the code: only the downward SW beam is absorbed by the atmosphere, while reflected upward SW escapes directly to space.

Heating rate

Defining $F_{\text{net}}^{\uparrow} = F^{\uparrow} - F^{\downarrow}$ (upward positive) at each interface, the heating rate for layer k is

$$\left. \frac{dT}{dt} \right|_{\text{rad},k} = \frac{g}{c_p} \frac{F_{\text{net},k+1/2}^{\uparrow} - F_{\text{net},k-1/2}^{\uparrow}}{p_{k+1/2} - p_{k-1/2}}, \quad (69)$$

where $k + \frac{1}{2}$ is the bottom interface and $k - \frac{1}{2}$ the top (pressure increasing downward). Positive divergence of upward flux warms the layer.

RRTMGP Correlated- k Radiation

The RRTMGP backend calls JAX-RRTMGP with correlated- k gaseous optics (128 LW and 112 SW g -points), a two-stream RTE solver, and optional cloud optics. Default trace-gas concentrations: $\text{CO}_2=415 \text{ ppmv}$, $\text{CH}_4=1900 \text{ ppbv}$, $\text{N}_2\text{O}=332 \text{ ppbv}$.

SBM Convection (Frierson 2007)

Moist adiabatic lapse rate

$$\Gamma_m = \frac{R_d T}{c_p p} \frac{1 + L_v q_s / (R_d T)}{1 + L_v^2 q_s / (c_p R_v T^2)}, \quad (70)$$

integrated upward via a trapezoidal predictor–corrector.

Saturation mixing ratio (Tetens)

$$e_s = 611.2 \exp\left(\frac{17.67 T_c}{T_c + 243.5}\right), \quad q_s = \frac{\varepsilon e_s}{p - e_s}, \quad \varepsilon = R_d / R_v \approx 0.622. \quad (71)$$

CAPE and trigger

$$\text{CAPE} = R_d \sum_k \max(0, T_{\text{parcel},k} - T_{\text{env},k}) \frac{\Delta p_k}{p_k}. \quad (72)$$

A smooth sigmoid trigger activates convection:

$$\mathcal{F} = \sigma(\kappa_s (\text{CAPE} - \text{CAPE}_c)), \quad \kappa_s = 0.01 \text{ (J/kg)}^{-1}. \quad (73)$$

Enthalpy-conserving relaxation

The reference profile T_{ref} is obtained by adjusting the moist adiabat so that column-integrated moist enthalpy is conserved:

$$\sum_k [c_p (T_{\text{ref},k} - T_k) + L_v (q_{\text{ref},k} - q_{v,k})] \Delta p_k = 0. \quad (74)$$

Newton iteration (2 steps) solves for the temperature offset. Tendencies:

$$\frac{dT}{dt} = \mathcal{F} \frac{T_{\text{ref}} - T}{\tau_c}, \quad \frac{dq_v}{dt} = \mathcal{F} \frac{q_{\text{ref}} - q_v}{\tau_c}, \quad \tau_c = 7200 \text{ s}. \quad (75)$$

Precipitation

$$P = -\frac{1}{g} \sum_k \frac{dq_v}{dt} \Delta p_k. \quad (76)$$

Held–Suarez Forcing

Equilibrium temperature

$$T_{\text{eq}} = \max\left(200, \left[315 - \Delta T_y \sin^2 \phi - \Delta \theta_z \ln(p/p_0) \cos^2 \phi\right] (p/p_0)^\kappa\right), \quad (77)$$

with $\Delta T_y = 60$ K, $\Delta \theta_z = 10$ K.

Newtonian relaxation

$$\frac{dT}{dt} = -k_T(\sigma, \phi) (T - T_{\text{eq}}), \quad k_T = k_a + (k_s - k_a) \max\left(0, \frac{\sigma - \sigma_b}{1 - \sigma_b}\right) \cos^4 \phi, \quad (78)$$

with $k_a = 1/(40 \text{ day})$, $k_s = 1/(4 \text{ day})$, $\sigma_b = 0.7$.

Rayleigh friction

$$\frac{d\mathbf{v}}{dt} = -k_v(\sigma) \mathbf{v}, \quad k_v = k_f \max\left(0, \frac{\sigma - \sigma_b}{1 - \sigma_b}\right), \quad k_f = 1/(1 \text{ day}). \quad (79)$$

Louis (1979) Turbulence

Mixing length

$$l = \frac{\kappa_{\text{vK}} z}{1 + \kappa_{\text{vK}} z/l_{\text{max}}}, \quad \kappa_{\text{vK}} = 0.4, \quad l_{\text{max}} = 100 \text{ m}. \quad (80)$$

Richardson number

$$\text{Ri} = \frac{N^2}{S^2}, \quad N^2 = \frac{g}{\theta_v} \frac{\partial \theta_v}{\partial z}, \quad S^2 = \left(\frac{\partial u}{\partial z}\right)^2 + \left(\frac{\partial v}{\partial z}\right)^2. \quad (81)$$

Stability functions

$$f_m(\text{Ri}) = \begin{cases} 1 - \frac{2b \text{Ri}}{1 + 3bc l^2 |\text{Ri}|^{1/2} / \Delta z^2} & \text{Ri} < 0, \\ \frac{1}{1 + 2b \text{Ri} / \sqrt{1 + d \text{Ri}}} & \text{Ri} \geq 0, \end{cases} \quad (82)$$

with $b = c = d = 5$. Eddy diffusivities: $K_m = l^2 S f_m$, $K_h = K_m$.

Vertical Diffusion (Implicit Thomas Algorithm)

The backward-Euler system $-a_k \varphi_{k-1} + b_k \varphi_k - c_k \varphi_{k+1} = d_k$ is solved with the Thomas algorithm.

Tridiagonal coefficients.

$$a_k = \frac{\Delta t K_{k-1/2}}{\rho_k \Delta z_k \Delta z_{k-1/2}}, \quad c_k = \frac{\Delta t K_{k+1/2}}{\rho_k \Delta z_k \Delta z_{k+1/2}}, \quad b_k = 1 + a_k + c_k. \quad (83)$$

Forward sweep.

$$w_k = \frac{a_k}{b'_{k-1}}, \quad b'_k = b_k - w_k c_{k-1}, \quad d'_k = d_k + w_k d'_{k-1}. \quad (84)$$

Back substitution.

$$\varphi_k = \frac{d'_k + c_k \varphi_{k+1}}{b'_k}. \quad (85)$$

Surface Fluxes

Three bulk flux schemes are available, selected per tile.

Constant coefficients (default)

$$\tau_x = -\rho C_D |\mathbf{V}| u, \quad \tau_y = -\rho C_D |\mathbf{V}| v, \quad (86)$$

$$\text{SH} = \rho c_p C_H |\mathbf{V}| (T_s - T_a), \quad (87)$$

$$\text{LH} = \rho L_v C_E |\mathbf{V}| (q_s - q_a), \quad (88)$$

with $C_D = C_H = C_E = 1.5 \times 10^{-3}$ and $|\mathbf{V}| = \sqrt{u^2 + v^2 + 10^{-4}}$.

Monin–Obukhov Similarity Theory (MOST)

Stability-dependent transfer coefficients via iterative Obukhov length computation (Businger–Dyer profiles).

Obukhov length.

$$L = -\frac{u_*^3 T_v}{\kappa_{\text{vK}} g (\theta_* + 0.61 T_a q_*)}, \quad (89)$$

where u_* , θ_* , q_* are friction velocity, temperature scale, and moisture scale.

Stability parameter. $\zeta = z_{\text{ref}}/L$.

Businger–Dyer stability functions.

$$\psi_m(\zeta) = \begin{cases} 2 \ln\left(\frac{1+x}{2}\right) + \ln\left(\frac{1+x^2}{2}\right) - 2 \arctan x + \frac{\pi}{2}, & \zeta < 0, \quad x = (1 - 16\zeta)^{1/4}, \\ -5\zeta, & \zeta \geq 0, \end{cases} \quad (90)$$

$$\psi_h(\zeta) = \begin{cases} 2 \ln\left(\frac{1+y}{2}\right), & \zeta < 0, \quad y = (1 - 16\zeta)^{1/2}, \\ -5\zeta, & \zeta \geq 0. \end{cases} \quad (91)$$

Transfer coefficients.

$$C_D = \left[\frac{\kappa_{\text{vK}}}{\ln(z/z_0) - \psi_m(\zeta)} \right]^2, \quad C_H = \frac{\kappa_{\text{vK}}^2}{[\ln(z/z_0) - \psi_m(\zeta)][\ln(z/z_{0t}) - \psi_h(\zeta)]}. \quad (92)$$

Iterative solver. The system u_* , θ_* , q_* , z_0 , z_{0t} , z_{0q} , L is solved iteratively (default 5 iterations) using `jax.lax.fori_loop` for full JAX differentiability.

COARE 3.0 roughness (Fairall et al. 2003)

Over ocean, roughness lengths are updated each iteration:

$$z_0 = \alpha_c \frac{u_*^2}{g} + 0.11 \frac{\nu}{u_*}, \quad z_{0t} = \min(1.15 \times 10^{-4}, 5.5 \times 10^{-5} \text{Re}_*^{-0.6}), \quad (93)$$

where $\alpha_c = 0.011$ is the Charnock parameter and $\text{Re}_* = u_* z_0 / \nu$.

Large & Yeager (2004) roughness

Empirical neutral drag coefficient as a function of neutral 10-m wind speed U_{10N} :

$$C_{DN} \times 10^3 = \frac{2.7}{U_{10N}} + 0.142 + 0.0764 U_{10N}, \quad (94)$$

with roughness recovered as $z_0 = 10 / \exp(\kappa_{vK} / \sqrt{C_{DN}})$. Stanton and Dalton numbers follow the stability-corrected LY04 parameterisation.

Ocean Dynamics

Boussinesq Hydrostatic Primitive Equations

In vector-invariant form on the cubed sphere:

$$\frac{\partial u}{\partial t} = (\zeta + f) v - \frac{\partial K}{\partial x} - \frac{1}{\rho_0} \frac{\partial p'}{\partial x} + A_h \nabla^2 u + \frac{\partial}{\partial z} \left(A_v \frac{\partial u}{\partial z} \right) - w \frac{\partial u}{\partial z}, \quad (95)$$

$$\frac{\partial v}{\partial t} = -(\zeta + f) u - \frac{\partial K}{\partial y} - \frac{1}{\rho_0} \frac{\partial p'}{\partial y} + A_h \nabla^2 v + \frac{\partial}{\partial z} \left(A_v \frac{\partial v}{\partial z} \right) - w \frac{\partial v}{\partial z}. \quad (96)$$

The Coriolis force is split: depth-mean $f\mathbf{v}$ in the barotropic substeps, baroclinic shear $f\mathbf{v}'$ in the slow tendencies.

Tracer equations (skew-symmetric)

$$\frac{\partial \phi}{\partial t} = \frac{1}{2} \left[-\mathbf{v} \cdot \nabla \phi - \nabla \cdot (\phi \mathbf{v}) \right] - w \frac{\partial \phi}{\partial z} + K_h \nabla^2 \phi + \frac{\partial}{\partial z} \left(K_v \frac{\partial \phi}{\partial z} \right). \quad (97)$$

Free-surface equation

$$\frac{\partial \eta}{\partial t} = - \sum_k \nabla \cdot (h_k \mathbf{v}_k). \quad (98)$$

Barotropic Solver (Forward–Backward, Semi-Implicit Coriolis)

The barotropic system is solved with split-explicit forward–backward substeps:

$$\frac{\partial \eta}{\partial t} = -\nabla \cdot (H \bar{\mathbf{V}}), \quad \frac{\partial \bar{\mathbf{V}}}{\partial t} = f \hat{\mathbf{k}} \times \bar{\mathbf{V}} - g \nabla \eta + \mathbf{F}_{\text{slow}}. \quad (99)$$

Semi-implicit Coriolis. With $\alpha = \frac{1}{2} f \Delta t_s$:

$$\bar{U}^{n+1} = \frac{R_u + \alpha R_v}{1 + \alpha^2}, \quad \bar{V}^{n+1} = \frac{R_v - \alpha R_u}{1 + \alpha^2}, \quad (100)$$

where $R_u = \bar{U}^n + \alpha \bar{V}^n - \Delta t_s g \partial \eta / \partial x$ and $R_v = \bar{V}^n - \alpha \bar{U}^n - \Delta t_s g \partial \eta / \partial y$.

Equation of State (Wright 1997)

The ocean prognostic temperature variable T is **potential temperature** [degC]. The Wright (1997) EOS computes in-situ density directly from potential temperature θ , salinity S [PSU], and pressure p [Pa]:

$$\rho = \frac{p + p_0(\theta, S)}{\lambda(\theta, S) + \alpha_0(\theta, S)(p + p_0)}, \quad (101)$$

where

$$\alpha_0 = a_0 + a_1\theta + a_2S, \quad (102)$$

$$p_0 = (b_0 + b_4S) + \theta(b_1 + \theta(b_2 + b_3\theta) + b_5S), \quad (103)$$

$$\lambda = (c_0 + c_4S) + \theta(c_1 + \theta(c_2 + c_3\theta) + c_5S). \quad (104)$$

Coefficients follow the MOM6 implementation. The density perturbation is $\rho' = \rho(\theta, S, p) - \rho_0$.

Hydrostatic Pressure and Vertical Velocity

Baroclinic pressure by downward integration:

$$p'_k = \rho_0 g \eta + \sum_{k'=0}^{k-1} \rho'_{k'} g \Delta z_{k'} + \frac{1}{2} \rho'_k g \Delta z_k. \quad (105)$$

Vertical velocity diagnosed bottom-up from $w(\text{floor}) = 0$:

$$w_{k-1/2} = - \sum_{k'=k}^{N-1} \nabla \cdot (h_{k'} \mathbf{v}_{k'}). \quad (106)$$

Time Integration

SSP-RK3 (Shu–Osher 1988)

The three-stage strong-stability-preserving Runge–Kutta method:

$$\mathbf{u}^{(1)} = \mathbf{u}^n + \Delta t F(\mathbf{u}^n), \quad (107)$$

$$\mathbf{u}^{(2)} = \frac{3}{4}\mathbf{u}^n + \frac{1}{4}\mathbf{u}^{(1)} + \frac{1}{4}\Delta t F(\mathbf{u}^{(1)}), \quad (108)$$

$$\mathbf{u}^{n+1} = \frac{1}{3}\mathbf{u}^n + \frac{2}{3}\mathbf{u}^{(2)} + \frac{2}{3}\Delta t F(\mathbf{u}^{(2)}). \quad (109)$$

SSP-RK(4,3) and SSP-RK(5,4) variants are also available.

Robert–Asselin–Williams (RAW) Time Filter (v3.7)

The leapfrog scheme used by the semi-implicit spectral PE solver requires a time filter to damp the computational mode. The Williams (2009) modification of the Robert–Asselin filter splits the correction between the current and next time levels, restoring second-order accuracy:

$$d^n = \frac{\gamma}{2}(X^{n-1} - 2X^n + X^{n+1}), \quad (110)$$

$$X_{\text{filt}}^n = X^n + (1 - \alpha) d^n, \quad (111)$$

$$X_{\text{filt}}^{n+1} = X^{n+1} + \alpha d^n. \quad (112)$$

With $\alpha = 0.5$ (default), this is the RAW filter; $\alpha = 0$ recovers the original Robert–Asselin filter. The original RA filter introduces a first-order phase error that causes slow energy drift over climate-length integrations; the RAW modification eliminates this while preserving the same damping rate for the computational mode.

Adaptive Hyperdiffusion (v3.7)

The maximum stable coefficient for n -th order hyperdiffusion under forward Euler is

$$\nu_n = S \cdot \frac{C(n) \Delta x^n}{\Delta t}, \quad C(2) = \frac{1}{2}, C(4) = \frac{1}{8}, C(6) = \frac{1}{48}, \quad (113)$$

where $S \in (0, 1]$ is a safety factor (default 0.5). The function `adaptive_hyperdiff_coeff(dx_min, dt, order, safety)` eliminates manual tuning of the hyperdiffusion coefficient for each resolution and timestep.

Split-Explicit Methods

Each outer RK stage computes slow tendencies once, updates u, v and tracers, then runs N_s forward-backward acoustic substeps on the fast variables (w, θ', ρ') with substep size $\Delta t_s = \Delta t / N_s$.

Land, Ice, and Coupler

Slab Land Model

Energy balance

$$C_s d_s \frac{dT_s}{dt} = (1 - \alpha_l) SW^\downarrow + \varepsilon_l (LW^\downarrow - \sigma_{SB} T_s^4) - SH - LH. \quad (114)$$

Bucket hydrology

$$\frac{dW}{dt} = P - E, \quad W \in [0, W_{\max}]. \quad (115)$$

Moisture availability $\beta = \beta_{\min} + (1 - \beta_{\min}) W / W_{\max}$ modulates evaporation via $q_{\text{sfc}} = \beta q_s(T_s)$.

Surface humidity consistency. All slab surface tiles (land, sea ice, lake) recompute q_{sfc} from the *updated* surface temperature T_s^{n+1} (and updated W^{n+1} for land) before constructing the `TileResponse`. This ensures that the returned q_{sfc} and T_{surface} are thermodynamically consistent at the end of the timestep.

Sea-Ice Model

Surface temperature

$$\rho_i c_i \frac{h_{\text{eff}}}{2} \frac{dT_i}{dt} = Q_{\text{sfc}} - \frac{k_i (T_f - T_i)}{h_{\text{eff}}}, \quad h_{\text{eff}} = \max(h_i, h_{\min}). \quad (116)$$

Growth and melt

$$\frac{dh_i}{dt} = \frac{F_{\text{cond}} - F_{\text{ocean}}}{\rho_i L_f}. \quad (117)$$

Concentration

$$\frac{dc}{dt} = \begin{cases} (dh/dt)(1 - c)/h_{\text{new}} & \text{growing,} \\ (dh/dt) c / h_{\text{eff}} & \text{melting.} \end{cases} \quad (118)$$

EVP Rheology (Hunke & Dukowicz 1997)

When `dynamics="evp"`, the ice momentum equation is

$$m \frac{\partial \mathbf{u}_i}{\partial t} = \boldsymbol{\tau}_a + \boldsymbol{\tau}_w - m f \hat{\mathbf{k}} \times \mathbf{u}_i - mg \nabla \eta + \nabla \cdot \boldsymbol{\sigma}, \quad (119)$$

where $\boldsymbol{\tau}_a, \boldsymbol{\tau}_w$ are air and ocean drag, and $\boldsymbol{\sigma}$ is the internal stress tensor from an elliptic yield curve with eccentricity $e = 2$. Ice strength:

$$P = P^* h \exp(-C(1 - c)), \quad P^* = 27.5 \text{ kPa}, \quad C = 20. \quad (120)$$

The elastic term provides subcycling stability ($N_{\text{evp}} = 120$ substeps).

Multi-category ice

For $N_{\text{cat}} > 1$, per-category state (h_k, T_k, c_k) evolves independently under thermodynamics, then Lipscomb (2001) linear remapping redistributes ice across thickness categories.

Land Carbon Cycle and Stomatal Conductance

DALEC-990 Carbon Pools

Six prognostic pools: labile C_{lab} , foliage C_f , root C_r , wood C_w , litter C_{lit} , soil organic matter C_{SOM} . GPP via light-use efficiency; decomposition via Q_{10} temperature sensitivity with moisture limitation.

Farquhar (1980) Photosynthesis

Assimilation rate:

$$A = \min(W_c, W_j) - R_d, \quad W_c = V_{c,\max} \frac{C_i - \Gamma^*}{C_i + K_c(1 + O/K_o)}, \quad W_j = \frac{J(C_i - \Gamma^*)}{4(C_i + 2\Gamma^*)}, \quad (121)$$

where the minimum is a smooth (differentiable) function. $V_{c,\max}$ and $J_{\max}$ follow peaked Arrhenius temperature responses (Bernacchi et al. 2001). Soil moisture stress: $V_{c,\max} \leftarrow V_{c,\max} \beta_{\text{soil}}$.

Stomatal conductance

Ball–Berry (1987): $g_s = g_0 + g_1 \text{ARH}/C_s$.

Medlyn (2011): $g_s = g_0 + 1.6(1 + g_1/\sqrt{\text{VPD}}) A/C_s$.

Jarvis (1976): $g_s = g_{s,\max} f(\text{PAR}) f(T) f(\text{VPD}) f(\theta)$ (CO₂-independent; used when carbon cycle is inactive).

The coupled A – g_s – C_i system is solved by 5 fixed-point iterations (unrolled for JAX JIT).

Tile Coupler

Surface fluxes are area-weighted blends over ocean, land, sea-ice, and lake tiles:

$$X_{\text{blend}} = f_{\text{ocn}} X_{\text{ocn}} + f_{\text{land}} X_{\text{land}} + f_{\text{ice}} X_{\text{ice}} + f_{\text{lake}} X_{\text{lake}}. \quad (122)$$

Fluxes are time-averaged over each coupling window before being passed to the atmosphere.

Ocean albedo. The constant ocean albedo α_{ocn} is controlled by `CouplerConfig.ocean_albedo` (default 0.06). When `ocean_albedo_config.method="zenith"`, the Briegleb (1992) zenith-angle formula is used:

$$\alpha_{\text{ocn}} = \frac{0.026}{1.1 \mu_0^{1.7} + 0.065} + 0.15 (\mu_0 - 0.1)(\mu_0 - 0.5)(\mu_0 - 1.0), \quad (123)$$

where $\mu_0 = \cos \theta_z$ is the cosine of the solar zenith angle.

External forcing. Time-varying greenhouse gases (CO_2 , CH_4 , N_2O), total solar irradiance, and monthly zonal-mean ozone and aerosol climatologies can be read from NetCDF files and linearly interpolated in time via the `ExternalForcingConfig` interface. Ozone and aerosol data are loaded but not yet connected to the radiation solver.

Machine Learning: Spherical Fourier Neural Operator

The SFNO (ACE/FourCastNet v2 style) operates on the Gaussian grid.

Architecture

1. **Encoder:** Pointwise linear $n_{\text{in}} \rightarrow n_{\text{emb}}$.
2. **N processor blocks**, each containing:
 - Layer normalisation,
 - SH analysis $\rightarrow$ learned spectral convolution $\rightarrow$ SH synthesis,
 - GELU activation,
 - Pointwise MLP (two layers with expansion factor),
 - Skip connection.
3. **Decoder:** Pointwise linear $n_{\text{emb}} \rightarrow n_{\text{out}}$.
4. **Big-skip residual:** $\text{output} = \text{input} + \text{decoder}(\dots)$.

Spectral convolution

In the SH coefficient space:

$$\hat{f}_{nm}^{\text{out}} = W_{nm} \hat{f}_{nm}^{\text{in}}, \quad (124)$$

where $W_{nm} \in \mathbb{R}^{n_{\text{emb}} \times n_{\text{emb}}}$ is a learnable weight matrix per wavenumber pair.

Conservation Corrections

Atmosphere

Dry-air mass is corrected by a uniform adjustment to p_s that restores the area-weighted global integral:

$$\Delta \bar{p} = \frac{\sum_i A_i p_{s,i}^{\text{new}} - \sum_i A_i p_{s,i}^{\text{old}}}{\sum_i A_i}, \quad p_{s,i}^{\text{corr}} = p_{s,i}^{\text{new}} - \Delta \bar{p}, \quad (125)$$

so that $\sum_i A_i p_{s,i}^{\text{corr}} = \sum_i A_i p_{s,i}^{\text{old}}$ (global dry mass conserved exactly). Column moisture is rescaled: $q^{\text{corr}} = q^{\text{new}} \cdot Q_{\text{old}}/Q_{\text{new}}$.

Initial-mass anchoring (v3.7). For long AMIP/CMIP integrations, the fixer can anchor to the *initial* mass $M_0 = \sum_i A_i p_{s,i}^{\text{init}}$ rather than the previous step’s mass, preventing cumulative $O(\varepsilon)$ drift over millions of timesteps. The correction becomes

$$\Delta \bar{p} = \frac{\sum_i A_i p_{s,i}^{\text{new}} - M_0}{\sum_i A_i}. \quad (126)$$

Set via `model.set_initial_mass(state)` or `anchor_mass_to_initial=True` in the config. All accumulations use float64 regardless of the state precision.

Ocean

Volume conservation: $\eta^{\text{corr}} = \eta^{\text{new}} + (\sum \eta_{\text{old}} A - \sum \eta_{\text{new}} A) / \sum A$.

Heat and salt conservation: uniform additive correction per unit volume.

Physical Constants

Symbol	Name	Value	Unit
g	Gravitational acceleration	9.80616	m s^{-2}
R_d	Dry-air gas constant	287.04	$\text{J kg}^{-1} \text{K}^{-1}$
c_p	Dry-air heat capacity	1005.0	$\text{J kg}^{-1} \text{K}^{-1}$
R_v	Water-vapour gas constant	461.5	$\text{J kg}^{-1} \text{K}^{-1}$
L_v	Latent heat of vapourisation	2.501×10^6	J kg^{-1}
κ	R_d/c_p	0.285	—
p_0	Reference pressure	10^5	Pa
σ_{SB}	Stefan–Boltzmann constant	5.67×10^{-8}	$\text{W m}^{-2} \text{K}^{-4}$
κ_{vK}	von Kármán constant	0.4	—
Ω	Earth rotation rate	7.292×10^{-5}	rad s^{-1}
$R_{\oplus}$	Earth radius	6.371×10^6	m
ρ_0	Ocean reference density	1025	kg m^{-3}

Ocean Biogeochemistry

Two schemes: abiotic (DIC + ALK only) and NPZD ecosystem.

Carbonate Chemistry and Air-Sea CO_2 Exchange

The ocean surface $p\text{CO}_2$ is computed from DIC, ALK, T , S via carbonate equilibria. Air-sea flux (Wanninkhof 2014):

$$F_{\text{CO}_2} = k_w K_0 (p\text{CO}_{2,\text{ocean}} - p\text{CO}_{2,\text{atm}}), \quad (127)$$

where $k_w = 0.251 U_{10}^2 (\text{Sc}/660)^{-1/2}$ is the gas transfer velocity [cm/hr] and K_0 is Henry’s law solubility.

NPZD Ecosystem Model

Four biological tracers: NO_3 , phytoplankton P , zooplankton Z , detritus D (Fasham et al. 1990).

$$\frac{\partial P}{\partial t} = \mu_P P - G - m_P P, \quad (128)$$

$$\frac{\partial Z}{\partial t} = \gamma_Z G - m_Z Z^2, \quad (129)$$

$$\frac{\partial D}{\partial t} = (1 - \gamma_Z)G + m_P P + m_Z Z^2 - r_D D + w_s \frac{\partial D}{\partial z}, \quad (130)$$

$$\frac{\partial \text{NO}_3}{\partial t} = -\mu_P P + r_D D, \quad (131)$$

where $\mu_P = \mu_{\max} f(T) \min(L_N, L_I)$ with Michaelis-Menten nutrient limitation $L_N = \text{NO}_3/(k_N + \text{NO}_3)$ and Beer-Lambert light limitation with chlorophyll self-shading. Grazing G follows Holling-III. Redfield stoichiometry ($R_{C:N} = 6.625$) couples biology to DIC/ALK.

CMIP Infrastructure

CF/CMOR-Compliant Output

The `CFWriter` class produces CF-1.8 NetCDF4 files with CMIP6 Data Reference Syntax (DRS) filenames: `<var>_<table>_<model>_<expt>_<variant>_<grid>.nc`. Four CMOR tables are provided: `Amon` (33 atmospheric variables including clear-sky radiative fluxes, cloud condensate, and relative humidity), `Lmon` (6 land variables), `Omon` (2 ocean variables: SST and sea-ice fraction), and `Aday` (5 daily atmospheric variables). 3-D fields are interpolated to a standard CMIP6 19-level pressure grid.

Experiment Templates

Six CMIP6-style experiments with built-in GHG time series:

Template	Period	Forcing	CO ₂ range
<code>piControl</code>	1850– ∞	Fixed 1850	284.3 ppmv
<code>historical</code>	1850–2014	Transient	284→397 ppmv
<code>ssp245</code>	2015–2100	SSP2-4.5	397→600 ppmv
<code>ssp585</code>	2015–2100	SSP5-8.5	397→1135 ppmv
<code>amip</code>	1979–2014	Prescribed SST	Transient
<code>1pctCO2</code>	1–150	1%/yr increase	284→1277 ppmv

Restart and Reproducibility

Each restart file is accompanied by a `.meta.json` sidecar containing: SHA-256 state digest (sorted, concatenated array bytes), SHA-256 config hash, platform identifier, JAX version, x64 mode, and git hash. The function `verify_reproducibility()` compares two restart files and reports any discrepancies.

Tuning Guide

A registry of 16 tunable parameters across five categories (dynamics, radiation, convection, diffusion, surface) with valid ranges, default values, sensitivity ratings, and physical notes. `validate_tuning(config)` checks CFL consistency, range violations, and conflicting options. `recommended_params(resolution, nlev)` provides resolution-appropriate defaults.

4D-Var Data Assimilation (v3.9)

The model includes a fully differentiable 4D-Var data assimilation system that exploits JAX's automatic differentiation to compute exact gradients of the cost function without hand-coded adjoints.

Cost Function

The 4D-Var cost function minimised over the assimilation window $[t_0, t_N]$ is

$$J(\mathbf{x}_0) = \frac{1}{2}(\mathbf{x}_0 - \mathbf{x}_b)^T \mathbf{B}^{-1}(\mathbf{x}_0 - \mathbf{x}_b) + \frac{1}{2} \sum_{i=1}^N (\mathcal{H}_i[\mathcal{M}_{0 \rightarrow i}(\mathbf{x}_0)] - \mathbf{y}_i)^T \mathbf{R}_i^{-1}(\mathcal{H}_i[\mathcal{M}_{0 \rightarrow i}(\mathbf{x}_0)] - \mathbf{y}_i), \quad (132)$$

where $\mathbf{x}_b$ is the background state, $\mathbf{B}$ the background error covariance, $\mathcal{M}_{0 \rightarrow i}$ the nonlinear model propagator, $\mathcal{H}_i$ the observation operator at time t_i , $\mathbf{y}_i$ the observations, and $\mathbf{R}_i$ the observation error covariance. Gradients $\nabla_{\mathbf{x}_0} J$ are computed via `jax.grad` through the full forward model trajectory.

Control Vector

The control vector comprises perturbations to:

- Horizontal wind components (u , v),
- Temperature (T),
- Specific humidity (q_v),
- Surface pressure (p_s).

Increments are applied in model space and can optionally be preconditioned by the square root of $\mathbf{B}$ (i.e. $\mathbf{x}_0 = \mathbf{x}_b + \mathbf{B}^{1/2} \boldsymbol{\chi}$ with minimisation in $\boldsymbol{\chi}$ -space).

Background Error Covariance

Four background error covariance formulations are implemented:

1. **Diagonal:** $\mathbf{B} = \text{diag}(\sigma_b^2)$, the simplest variance-only model.
2. **Diffusion:** $\mathbf{B} = \boldsymbol{\Sigma} \mathbf{C} \boldsymbol{\Sigma}$ where $\mathbf{C}$ is a correlation matrix defined implicitly via iterated Laplacian diffusion on the model grid.
3. **Spectral:** $\mathbf{B}$ is diagonal in spectral space, with variance specified per total wavenumber; correlations arise naturally from the spectral truncation.
4. **Hybrid:** $\mathbf{B} = \beta_1 \mathbf{B}_{\text{static}} + \beta_2 \mathbf{B}_{\text{ensemble}}$, blending a static covariance with flow-dependent ensemble covariance.

Observation Operators

Three observation operator types are provided:

- **Direct:** identity mapping from model grid points to observed quantities.
- **Interpolating:** bilinear (horizontal) and linear (vertical) interpolation from the model grid to observation locations.
- **Composite:** chains multiple operators (e.g. interpolation followed by a forward radiative transfer calculation).

Minimiser

The cost function is minimised using preconditioned gradient descent. The preconditioner is the square root of $\mathbf{B}$, transforming the problem to $\boldsymbol{\chi}$ -space where the background term becomes isotropic. The minimiser supports configurable iteration counts and convergence tolerances, and all operations are JIT-compiled.

DA Cycling and Incremental Analysis

For operational-style cycling, the analysis from each window serves as the background for the next. An incremental analysis update (IAU) option distributes the analysis increment gradually over the subsequent forecast window rather than inserting it as an instantaneous shock, reducing initialisation imbalance and gravity-wave noise.

References

- Audusse, E., F. Bouchut, M.-O. Bristeau, R. Klein, and B. Perthame (2004)
A fast and stable well-balanced scheme with hydrostatic reconstruction for shallow water flows. *SIAM J. Sci. Comput.*, **25**, 2050–2065.
- Ball, J.T., I.E. Woodrow, and J.A. Berry (1987)
A model predicting stomatal conductance and its contribution to the control of photosynthesis under different environmental conditions. *Prog. in Photosynthesis Res.*, **4**, 221–224.
- Bernacchi, C.J., E.L. Singsaas, C. Pimentel, A.R. Portis, and S.P. Long (2001)
Improved temperature response functions for models of Rubisco-limited photosynthesis. *Plant Cell Environ.*, **24**, 253–259.
- Bourke, W. (1972)
An efficient, one-level, primitive-equation spectral model. *Mon. Wea. Rev.*, **100**, 683–689.
- Businger, J.A., J.C. Wyngaard, Y. Izumi, and E.F. Bradley (1971)
Flux-profile relationships in the atmospheric surface layer. *J. Atmos. Sci.*, **28**, 181–189.
- Colella, P. and P.R. Woodward (1984)
The Piecewise Parabolic Method (PPM) for gas-dynamical simulations. *J. Comput. Phys.*, **54**, 174–201.
- Farquhar, G.D., S. von Caemmerer, and J.A. Berry (1980)
A biochemical model of photosynthetic CO₂ assimilation in leaves of C₃ species. *Planta*, **149**, 78–90.
- Fasham, M.J.R., H.W. Ducklow, and S.M. McKelvie (1990)
A nitrogen-based model of plankton dynamics in the oceanic mixed layer. *J. Mar. Res.*, **48**, 591–639.
- Fairall, C.W., E.F. Bradley, J.E. Hare, A.A. Grachev, and J.B. Edson (2003)
Bulk parameterization of air–sea fluxes: Updates and verification for the COARE algorithm. *J. Climate*, **16**, 571–591.
- Frierson, D.M.W., I.M. Held, and P. Zurita-Gotor (2006)
A gray-radiation aquaplanet moist GCM. Part I: Static stability and eddy scale. *J. Atmos. Sci.*, **63**, 2548–2566.
- Frierson, D.M.W. (2007)
The dynamics of idealized convection schemes and their effect on the zonally averaged tropical circulation. *J. Atmos. Sci.*, **64**, 1959–1976.
- Jiang, G.-S. and C.-W. Shu (1996)
Efficient implementation of weighted ENO schemes. *J. Comput. Phys.*, **126**, 202–228.
- Hunke, E.C. and J.K. Dukowicz (1997)
An elastic-viscous-plastic model for sea ice dynamics. *J. Phys. Oceanogr.*, **27**, 1849–1867.

- Held, I.M. and M.J. Suarez (1994)
A proposal for the intercomparison of the dynamical cores of atmospheric general circulation models. *Bull. Amer. Meteor. Soc.*, **75**, 1825–1830.
- Large, W.G. and S.G. Yeager (2004)
Diurnal to decadal global forcing for ocean and sea-ice models: The data sets and flux climatologies. *NCAR Technical Note*, NCAR/TN-460+STR.
- Lin, S.-J. (2004)
A “vertically Lagrangian” finite-volume dynamical core for global models. *Mon. Wea. Rev.*, **132**, 2293–2307.
- Lipscomb, W.H. (2001)
Remapping the thickness distribution in sea ice models. *J. Geophys. Res.*, **106**(C7), 13989–14000.
- Louis, J.-F. (1979)
A parametric model of vertical eddy fluxes in the atmosphere. *Bound.-Layer Meteor.*, **17**, 187–202.
- Medlyn, B.E. et al. (2011)
Reconciling the optimal and empirical approaches to modelling stomatal conductance. *Global Change Biol.*, **17**, 2134–2144.
- Mouallem, J., L.M. Harris, and R. Benson (2023)
A duo-grid methodology for cubed-sphere shallow water models. *J. Comput. Phys.*, **485**, 112097.
- Putman, W.M. and S.-J. Lin (2007)
Finite-volume transport on various cubed-sphere grids. *J. Comput. Phys.*, **227**, 55–78.
- Shu, C.-W. and S. Osher (1988)
Efficient implementation of essentially non-oscillatory shock-capturing schemes. *J. Comput. Phys.*, **77**, 439–471.
- Simmons, A.J. and D.M. Burridge (1981)
An energy and angular-momentum conserving vertical finite-difference scheme and hybrid vertical coordinates. *Mon. Wea. Rev.*, **109**, 758–766.
- Skamarock, W.C. and J.B. Klemp (2008)
A time-split nonhydrostatic atmospheric model for weather research and forecasting applications. *J. Comput. Phys.*, **227**, 3465–3485.
- van Leer, B. (1979)
Towards the ultimate conservative difference scheme. V. A second-order sequel to Godunov’s method. *J. Comput. Phys.*, **32**, 101–136.
- Wanninkhof, R. (2014)
Relationship between wind speed and gas exchange over the ocean revisited. *Limnol. Oceanogr. Methods*, **12**, 351–362.
- Wright, D.G. (1997)
An equation of state for use in ocean models: Eckart’s formula revisited. *J. Atmos. Ocean. Tech.*, **14**, 735–740.