

MoMo Ledger: Database Design Document

- **Project:** MoMo SMS Ledger
- **Author:** Clive Mushipe
- **Database:** MySQL 8.0+ (tested on MySQL 9.7.1)
- **Files:** database/database_setup.sql, database/crud_tests.sql, database/crud_test_results.txt, examples/json_schemas.json, docs/erd.drawio, docs/erd.dbml


1. Introduction

MoMo Ledger turns MTN Mobile Money SMS messages into a ledger that a user can search, edit and chart. A user uploads an XML backup of their phone's messages; the app reads each MoMo message, works out what kind of transaction it is, how much moved and who was on the other side, and stores it.

This document describes the relational database behind that: the ERD, why I designed it this way, a data dictionary, sample queries with their real output, the CRUD tests I ran, the security rules, and how the tables map to the JSON the API returns.

2. Entity Relationship Diagram

MoMo SMS Ledger – Entity Relationship Diagram



Drawn in Draw.io. The editable source is [erd.drawio](https://erd.drawio.com/): open it at app.diagrams.net to change it or export it again. [erd.dbml](#) holds the same model for dbdiagram.io.

Relationships and cardinality

Relationship	Cardinality	How it is enforced
users → transactions	1 : N (a user has zero or more transactions; each transaction has exactly one owner)	transactions.user_id NOT NULL FK, ON DELETE CASCADE
transaction_categories → transactions	1 : N (each transaction has exactly one category)	transactions.category_id NOT NULL FK, ON DELETE RESTRICT
transactions ↔ parties	M : N , resolved by transaction_parties	Composite PK (transaction_id, party_id, party_role), two FKs
users → sessions	1 : N	sessions.user_id NOT NULL FK, ON DELETE CASCADE
users → unmatched_sms	1 : N	unmatched_sms.user_id NOT NULL FK, ON DELETE CASCADE
users → system_logs	0..1 : N (a log may have no user, e.g. a failed login for an unknown name)	nullable FK, ON DELETE SET NULL
transactions → system_logs	0..1 : N	nullable FK, ON DELETE SET NULL

From the XML to the tables

The design comes from the MoMo SMS export in `data/`. Each `<sms>` element carries these attributes:

XML	Example	Where it goes
transaction_type	payment	transaction_categories.category_code, referenced by transactions.category_id
amount	2000	transactions.amount
currency	RWF	transactions.currency
date	2024-01-04 10:30:00	transactions.transaction_date
status	completed	transactions.status
sender	0781234567	parties (matched on phone_number), linked by transaction_parties with role sender
receiver	MTN:MoMoPay:Kigali_Mart	parties (matched on merchant_code), linked by transaction_parties with role receiver
body	Your payment of 2000 RWF to Kigali Mart was successful. TxnId: TXN002	transactions.raw_sms; the TxnId inside it becomes transactions.sms_ref

A real phone backup has only `body` and `date`, so the parser reads the rest out of the message text. Any MoMo message no rule understands is kept in `unmatched_sms` instead of being dropped, and the import itself is recorded in `system_logs`.

3. Design rationale

Every SMS describes one movement of money in one person's wallet, so **transactions** is the central table and everything else hangs off it. A transaction belongs to exactly one **user**, the wallet owner who uploaded the backup, so that is 1:N with a NOT NULL foreign key and `ON DELETE CASCADE`: a ledger with no owner means nothing.

The kind of transaction lives in a **transaction_categories** lookup table rather than a free-text column. That stops typos ("payement"), lets a category such as bank deposits be added without changing code, and records the `direction` (in or out) once, which the monthly totals rely on. Its foreign key uses `ON DELETE RESTRICT`, so a category still in use cannot be deleted.

The other side of a transaction is its own entity, **parties**: people, merchants, agents, banks and MTN services. As plain text, "Kigali Mart" and "Kigali mart" would be two merchants, and nothing could total what one person had been paid. A party appears in many transactions, and a transaction can involve more than one party, because a transfer made at an agent has both a receiver and an agent. That many-to-many relationship is resolved by the junction table **transaction_parties**, whose composite primary key includes `party_role`, so a party cannot be linked twice in the same role.

system_logs records imports, failed logins and errors. Its foreign keys are nullable and use `ON DELETE SET NULL`, because a log must outlive the rows it mentions.

Money is `DECIMAL(12,2)`, since floating point cannot hold amounts exactly; `ENUM` covers small fixed sets, and `CHAR` the fixed lengths (a bcrypt hash is 60 characters, a session token 43). `UNIQUE (sms_ref, user_id)` means the same SMS is never counted twice, and `CHECK` constraints reject impossible values in the database itself, not only in the app.

4. Data dictionary

Abbreviations: **PK** primary key, **FK** foreign key, **UQ** unique, **NN** not null.

users: wallet owners who use the ledger

Column	Type	Keys / constraints	Description
user_id	INT UNSIGNED	PK, auto-increment	Identifier
username	VARCHAR(30)	UQ, NN, CHECK <code>^[A-Za-z0-9_]{3,30}\$</code>	Login name
full_name	VARCHAR(100)	NN	Name shown on the dashboard
phone_number	VARCHAR(10)	UQ, NN, CHECK <code>^07[2389][0-9]{7}\$</code>	MTN number the SMS backups come from
password_hash	CHAR(60)	NN, CHECK bcrypt format and length 60	bcrypt hash; the password is never stored
created_at	DATETIME	NN, default now	When the account was created

transaction_categories: kinds of transaction

Column	Type	Keys / constraints	Description
category_id	TINYINT UNSIGNED	PK, auto-increment	Identifier
category_code	VARCHAR(30)	UQ, NN, CHECK <code>^[a-z_]+\$</code>	Stable code used by the parser and API
category_name	VARCHAR(60)	NN	Human-readable name
direction	ENUM('in','out')	NN	Whether money enters or leaves the wallet
description	VARCHAR(255)	nullable	Which SMS fall in this category

transactions: one row per MoMo transaction

Column	Type	Keys / constraints	Description
transaction_id	BIGINT UNSIGNED	PK, auto-increment	Identifier
user_id	INT UNSIGNED	FK → users, NN, CASCADE	Wallet owner
category_id	TINYINT UNSIGNED	FK → transaction_categories, NN, RESTRICT	Kind of transaction
sms_ref	VARCHAR(30)	nullable; UQ with user_id	TxnId from the SMS; NULL for manual entries
amount	DECIMAL(12,2)	NN, CHECK > 0	Amount moved
fee	DECIMAL(10,2)	NN, default 0, CHECK ≥ 0	MTN fee
balance_after	DECIMAL(12,2)	nullable, CHECK ≥ 0	Balance after, only when the SMS states it
currency	CHAR(3)	NN, default 'RWF', CHECK <code>^[A-Z]{3}\$</code>	ISO 4217 code
transaction_date	DATETIME	NN	When it happened
status	ENUM('completed','pending','failed','reversed')	NN, default 'completed'	Outcome
raw_sms	TEXT	nullable	Original message, so it can be parsed again
created_at	DATETIME	NN, default now	Row inserted
updated_at	DATETIME	NN, auto-updates	Row last changed

Indexes: `idx_transactions_user_date` (user_id, transaction_date), `uq_transactions_sms` (sms_ref, user_id), `idx_transactions_category`, `idx_transactions_status`.

parties: the other side of a transaction

Column	Type	Keys / constraints	Description
party_id	INT UNSIGNED	PK, auto-increment	Identifier
party_name	VARCHAR(100)	NN, indexed	Name as it appears in the SMS
party_type	ENUM('person','merchant','agent','bank','service')	NN	Kind of party
phone_number	VARCHAR(10)	UQ, nullable, CHECK phone format	For people and agents
merchant_code	VARCHAR(60)	UQ, nullable	MoMoPay or service code
created_at	DATETIME	NN, default now	First seen

Table CHECK `chk_parties_identified`: at least one of `phone_number` and `merchant_code` must be set.

transaction_parties: junction table (transactions M:N parties)

Column	Type	Keys / constraints	Description
transaction_id	BIGINT UNSIGNED	PK part, FK → transactions, CASCADE	The transaction
party_id	INT UNSIGNED	PK part, FK → parties, RESTRICT, indexed	The party
party_role	ENUM('sender','receiver','agent')	PK part	Role in this transaction

system_logs: processing and audit log

Column	Type	Keys / constraints	Description
log_id	BIGINT UNSIGNED	PK, auto-increment	Identifier
user_id	INT UNSIGNED	FK → users, nullable, SET NULL	User involved, if known
transaction_id	BIGINT UNSIGNED	FK → transactions, nullable, SET NULL	Transaction involved, if any
log_level	ENUM('DEBUG','INFO','WARNING','ERROR')	NN, default 'INFO'	Severity
event_type	VARCHAR(40)	NN, CHECK <code>^[a-z_]+\$</code>	Short code, e.g. <code>sms_import</code>
message	VARCHAR(500)	NN	What happened
created_at	DATETIME(3)	NN, default now, indexed	When, to the millisecond

sessions: logged-in browsers

Column	Type	Keys / constraints	Description
token	CHAR(43)	PK	Random URL-safe token (also in an HttpOnly cookie)
user_id	INT UNSIGNED	FK → users, NN, CASCADE, indexed	Who is logged in
created_at	DATETIME	NN	Login time
expires_at	DATETIME	NN, CHECK <code>> created_at</code>	When the token stops working

unmatched_sms: MoMo messages the parser could not read

Column	Type	Keys / constraints	Description
unmatched_id	INT UNSIGNED	PK, auto-increment	Identifier
user_id	INT UNSIGNED	FK → users, NN, CASCADE	Whose backup it came from
body	TEXT	NN	Full SMS text
body_hash	CHAR(64)	NN; UQ with user_id	SHA-256 of body, used to block duplicates
received_at	DATETIME	nullable	When the phone received it

Views

View	Purpose
v_monthly_flow	Money in and money out (amount + fee) per user per month, completed transactions only
v_merchant_spend	Number of payments and total spent at each merchant

Sample data loaded

Table	Rows
users	5
transaction_categories	6
parties	13
transactions	14
transaction_parties	15
system_logs	8
sessions	5
unmatched_sms	5

Transactions 1–8 come from the real sample file `data/modified_sms_v2.xml`.

5. Sample queries

All results below are real output from `database/crud_tests.sql` (full output in `database/crud_test_results.txt`).

5.1 A user's transactions with category and all parties (4-table join)

```
SELECT t.transaction_id, t.transaction_date, c.category_name, c.direction,
       t.amount, t.fee, t.status,
       GROUP_CONCAT(CONCAT(p.party_name, ' (' , tp.party_role, ')')
                     ORDER BY tp.party_role SEPARATOR ', ') AS parties
FROM transactions t
JOIN transaction_categories c  ON c.category_id = t.category_id
LEFT JOIN transaction_parties tp ON tp.transaction_id = t.transaction_id
LEFT JOIN parties p           ON p.party_id = tp.party_id
WHERE t.user_id = 1
GROUP BY t.transaction_id
ORDER BY t.transaction_date DESC;
```

```
| 15 | 2024-01-11 17:00:00 | Payment to merchant | out | 1200.00 | 0.00 | completed |
Supermarket A (receiver) |
| 8 | 2024-01-10 13:15:00 | Transfer to number | out | 7500.00 | 100.00 | completed | Eve
(receiver) |
| 7 | 2024-01-09 08:30:00 | Incoming money | in | 20000.00 | 0.00 | completed | David
(sender) |
...

```

```

Problems Output Debug Console Terminal Ports
mac@Clives-MacBook-Air momo % mysql -u root < database/database_setup.sql && mysql -u root --table --force momo_ledger < database/crud_tests.sql 2>&1 | awk '/2a\. READ: one user's transactions with category and parties /'
+-----+
| transaction_id | transaction_date | category_name | direction | amount | fee | status | parties |
+-----+
| 15 | 2024-01-11 17:00:00 | Payment to merchant | out | 1200.00 | 0.00 | completed | Supermarket A (receiver) |
| 8 | 2024-01-10 13:15:00 | Transfer to number | out | 7500.00 | 100.00 | completed | Eve (receiver) |
| 7 | 2024-01-09 08:30:00 | Incoming money | in | 20000.00 | 0.00 | completed | David (sender) |
| 6 | 2024-01-08 16:45:00 | Payment to merchant | out | 3500.00 | 0.00 | completed | Pharmacy Plus (receiver) |
| 5 | 2024-01-07 11:00:00 | Airtime purchase | out | 500.00 | 0.00 | completed | MTN Airtime (receiver) |
| 4 | 2024-01-06 09:05:00 | Incoming money | in | 15000.00 | 0.00 | completed | Carol (sender) |
| 3 | 2024-01-05 14:22:00 | Transfer to number | out | 10000.00 | 100.00 | completed | Bob (receiver) |
| 2 | 2024-01-04 10:30:00 | Payment to merchant | out | 2000.00 | 0.00 | completed | Kigali Mart (receiver) |
| 1 | 2024-01-03 08:12:00 | Incoming money | in | 5000.00 | 0.00 | completed | Alice (sender) |
+-----+

test

mac@Clives-MacBook-Air momo %

```

5.2 Money in vs out per month (view with a conditional aggregate)

```
SELECT * FROM v_monthly_flow ORDER BY user_id, month;
```

user_id	month	money_in	money_out
1	2024-01	40000.00	24900.00
2	2024-02	0.00	30700.00
3	2024-02	50000.00	0.00
4	2024-02	0.00	12250.00
5	2024-02	0.00	1000.00

```

mac@Clives-MacBook-Air momo % mysql -u root < database/database_setup.sql && mysql -u root --table --force momo_ledger < database/crud_tests.sql 2>&1 | awk '/2b\. READ: money in vs out per month (view) /'
+-----+
| user_id | month | money_in | money_out |
+-----+
| 1 | 2024-01 | 40000.00 | 24900.00 |
| 2 | 2024-02 | 0.00 | 30700.00 |
| 3 | 2024-02 | 50000.00 | 0.00 |
| 4 | 2024-02 | 0.00 | 12250.00 |
| 5 | 2024-02 | 0.00 | 1000.00 |
+-----+

test

2c. READ: spend per merchant (view)
+-----+
| user_id | merchant | payments | total |
+-----+
| 1 | Pharmacy Plus | 1 | 3500.00 |
| 1 | Kigali Mart | 1 | 2000.00 |
| 1 | Supermarket A | 1 | 1200.00 |
+-----+

test

2d. READ: transactions with more than one party (uses the junction table)
+-----+
| transaction_id | sms_ref | party_count | parties |
+-----+
| 13 | TXN4001 | 2 | Frank (receiver), Kimironko Agent 045 (agent) |
+-----+

test

2e. READ: top counterparties across all users
+-----+
| party_name | party_type | times_seen | total_amount |
+-----+
| Bank of Kigali | bank | 1 | 50000.00 |
| Kimironko Agent 045 | agent | 2 | 42000.00 |
| David | person | 1 | 20000.00 |
| Carol | person | 1 | 15000.00 |
| Frank | person | 1 | 12000.00 |
+-----+

test

mac@Clives-MacBook-Air momo %

```

5.3 Transactions with more than one party (uses the M:N junction table)

```

SELECT t.transaction_id, t.sms_ref, COUNT(*) AS party_count,
       GROUP_CONCAT(CONCAT(p.party_name, ' (', tp.party_role, ')') SEPARATOR ', ') AS parties
FROM transactions t
JOIN transaction_parties tp ON tp.transaction_id = t.transaction_id
JOIN parties p ON p.party_id = tp.party_id
GROUP BY t.transaction_id, t.sms_ref
HAVING COUNT(*) > 1;

```

```
| 13 | TXN4001 | 2 | Frank (receiver), Kimironko Agent 045 (agent) |
```


5.4 Top counterparties across all users

```
SELECT p.party_name, p.party_type, COUNT(*) AS times_seen, SUM(t.amount) AS total_amount
FROM parties p
JOIN transaction_parties tp ON tp.party_id = p.party_id
JOIN transactions t          ON t.transaction_id = tp.transaction_id
WHERE t.status = 'completed'
GROUP BY p.party_id, p.party_name, p.party_type
ORDER BY total_amount DESC
LIMIT 5;
```

Bank of Kigali	bank	1	50000.00	
Kimironko Agent 045	agent	2	42000.00	
David	person	1	20000.00	
Carol	person	1	15000.00	
Frank	person	1	12000.00	

5.5 The index is used

```
EXPLAIN SELECT transaction_id, amount FROM transactions
WHERE user_id = 1 AND transaction_date BETWEEN '2024-01-01' AND '2024-01-31';
```

-> Index range scan on transactions using idx_transactions_user_date
over (user_id = 1 AND '2024-01-01 00:00:00' <= transaction_date <= '2024-01-31 00:00:00')

MySQL reads only the matching slice of idx_transactions_user_date instead of scanning the whole table.

6. CRUD tests

#	Operation	What I did	Result
1	CREATE	Inserted payment TXN009, its party link and a log row inside one <code>START TRANSACTION ... COMMIT</code>	New row 15 joined to "Supermarket A (receiver)" ✓
2	READ	Queries 5.1–5.5 above	Correct rows returned ✓
3	UPDATE	Changed TXN2001 from failed to reversed	Status changed; updated_at moved from 13:13:56 to 13:13:57 ✓
4	DELETE	Deleted transaction 13	Its 2 junction rows were removed (CASCADE); its log row was kept with transaction_id = NULL (SET NULL) ✓

Constraint tests (each statement must be rejected)

#	Attempt	MySQL response
5a	Amount of -500	ERROR 3819: Check constraint 'chk_transactions_amount' is violated ✓
5b	Import TXN001 twice	ERROR 1062: Duplicate entry 'TXN001-1' for key 'uq_transactions_sms' ✓
5c	Transaction for user 999 (does not exist)	ERROR 1452: ... foreign key constraint fails (fk_transactions_user) ✓
5d	Delete the "payment" category while in use	ERROR 1451: Cannot delete or update a parent row (fk_transactions_category) ✓
5e	Phone number "12345"	ERROR 3819: Check constraint 'chk_users_phone' is violated ✓
5f	Plain-text password	ERROR 3819: Check constraint 'chk_users_hash' is violated ✓
5g	Party with no phone and no code	ERROR 3819: Check constraint 'chk_parties_identified' is violated ✓
5h	Session that expires before it starts	ERROR 3819: Check constraint 'chk_sessions_expiry' is violated ✓

```

mac@Clives-MacBook-Air momo % clear
mac@Clives-MacBook-Air momo % mysql -u root < database/database_setup.sql && mysql -u root --table --force momo_ledger < database/crud_tests.sql >&61 | awk '/1\./ CREATE/{f=1} /2a\./ READ/{f=0} /3\./ UPDATE/{f=1} /5a\./{f=0} f'
1. CREATE
+-----+-----+-----+-----+-----+-----+
| transaction_id | sms_ref | category_code | amount | party_name | party_role |
+-----+-----+-----+-----+-----+-----+
| 15 | TXN009 | payment | 1200.00 | Supermarket A | receiver |
+-----+-----+-----+-----+-----+-----+
| test |
+-----+-----+-----+-----+-----+-----+
3. UPDATE
+-----+-----+-----+-----+
| transaction_id | sms_ref | status | updated_at |
+-----+-----+-----+-----+
| 10 | TXN2001 | failed | 2026-09-24 15:14:23 |
+-----+-----+-----+-----+
| transaction_id | sms_ref | status | updated_at |
+-----+-----+-----+-----+
| 10 | TXN2001 | reversed | 2026-09-24 15:14:24 |
+-----+-----+-----+-----+
| test |
+-----+-----+-----+-----+
4. DELETE
+-----+-----+-----+
| party_links_before | logs_linked_before |
+-----+-----+-----+
| 2 | 1 |
+-----+-----+-----+
| transaction_after | party_links_after | logs_linked_after | log_kept_unlinked |
+-----+-----+-----+-----+
| 0 | 0 | 0 | 1 |
+-----+-----+-----+-----+
| test |
+-----+-----+-----+-----+
mac@Clives-MacBook-Air momo %

```

```

mac@Clives-MacBook-Air momo % mysql -u root < database/database_setup.sql && mysql -u root --table --force momo_ledger < database/crud_tests.sql >&61 | awk '/5a\./{f=1} f'
5a. negative amount -> CHECK chk_transactions_amount
ERROR 3819 (HY000) at line 113: Check constraint 'chk_transactions_amount' is violated.
| test |
+-----+-----+-----+-----+
5b. same SMS Imported twice -> UNIQUE uq_transactions_sms
ERROR 1062 (23000) at line 117: Duplicate entry 'TXN001-1' for key 'transactions-uq_transactions_sms'
| test |
+-----+-----+-----+-----+
5c. user that does not exist -> FOREIGN KEY fk_transactions_user
ERROR 1452 (23000) at line 121: Cannot add or update a child row: a foreign key constraint fails ('momo_ledger','transactions', CONSTRAINT 'fk_transactions_user' FOREIGN KEY ('user_id') REFERENCES 'users' ('user_id') ON DELETE CASCADE ON UPDATE CASCADE)
| test |
+-----+-----+-----+-----+
5d. delete a category still in use -> FOREIGN KEY ON DELETE RESTRICT
ERROR 1451 (23000) at line 125: Cannot delete or update a parent row: a foreign key constraint fails ('momo_ledger','transactions', CONSTRAINT 'fk_transactions_category' FOREIGN KEY ('category_id') REFERENCES 'transaction_categories' ('category_id') ON DELETE RESTRICT ON UPDATE CASCADE)
| test |
+-----+-----+-----+-----+
5e. badly formed phone number -> CHECK chk_users_phone
ERROR 3819 (HY000) at line 128: Check constraint 'chk_users_phone' is violated.
| test |
+-----+-----+-----+-----+
5f. plain-text password -> CHECK chk_users_hash
ERROR 3819 (HY000) at line 132: Check constraint 'chk_users_hash' is violated.
| test |
+-----+-----+-----+-----+
5g. party with no phone and no code -> CHECK chk_parties_identified
ERROR 3819 (HY000) at line 136: Check constraint 'chk_parties_identified' is violated.
| test |
+-----+-----+-----+-----+
5h. session that expires before it starts -> CHECK chk_sessions_expiry
ERROR 3819 (HY000) at line 139: Check constraint 'chk_sessions_expiry' is violated.
| test |
+-----+-----+-----+-----+
Row counts after the tests
+-----+-----+-----+-----+
| transactions | transaction_parties | users | parties | system_logs |
+-----+-----+-----+-----+
| 14 | 14 | 5 | 13 | 10 |
+-----+-----+-----+-----+
mac@Clives-MacBook-Air momo %

```

A problem I found while testing: at first I had `UNIQUE (user_id, sms_ref)`. On MySQL 9.7.1, test 5c was *accepted*: a transaction for a user that does not exist was inserted. I narrowed it down to this: when a new row has NULL in a composite UNIQUE key that begins with the foreign-key column, MySQL 9.7.1 did not check that foreign key. Manual entries always have `sms_ref = NULL`, so this would have let orphan rows in. Reordering the key to `UNIQUE (sms_ref, user_id)` keeps the same rule and fixed it; test 5c now fails as it should.

7. Security rules

1. **Passwords are never stored.** Only bcrypt hashes (cost 12) are saved, and `chk_users_hash` rejects anything that is not a 60-character bcrypt string, so a plain-text password cannot be saved even by mistake.
2. **Every user sees only their own data.** Every query in the app filters on `user_id` from the logged-in session, for example `WHERE id = ? AND user_id = ?`, so guessing another transaction's id returns 404.
3. **No SQL injection.** All values are passed as bound parameters (`?`), never pasted into the SQL string.
4. **Sessions.** Tokens are 32 random bytes (`secrets.token_urlsafe`), stored in an `HttpOnly`, `SameSite=Lax` cookie that JavaScript cannot read, and expire after one day (`chk_sessions_expiry`). The cookie's `secure` flag is currently off because the app runs over plain HTTP locally; it must be turned on before deployment over HTTPS.
5. **Least privilege.** The app should connect as a user that can read and write rows but cannot change the schema:

```
sql CREATE USER 'momo_app'@'localhost' IDENTIFIED BY '<strong password from an environment variable>'; GRANT SELECT, INSERT, UPDATE, DELETE ON momo_ledger.* TO 'momo_app'@'localhost';
```

6. **Integrity in the database, not only the app.** Foreign keys, CHECK constraints and UNIQUE keys reject bad data even if it comes from a script or a bug that bypasses the API.
 7. **Audit trail survives deletes.** `system_logs` uses `ON DELETE SET NULL`, so deleting a user or transaction does not erase the record of what happened.
 8. **Sensitive fields never leave the database.** `password_hash`, session tokens and `body_hash` are not part of any JSON response.
-

8. JSON data model

`examples/json_schemas.json` holds a JSON Schema (draft 2020-12) for every main entity, example objects, and the SQL-to-JSON mapping. I validated every example against its schema with the Python `jsonschema` library.

Serialization rules:

- Foreign keys become nested objects: `category_id` → `category { ... }`, `user_id` → `user { ... }`.
- The junction table becomes an array: `transaction_parties` → `parties: [ { role, party { ... } } ]`.

- Related logs become `logs: [ ... ]`.
- `DECIMAL` → string with two decimals (`"12000.00"`), so JavaScript clients don't introduce floating-point rounding.
- `DATETIME` → ISO 8601 with the Kigali offset (`2024-02-12T11:40:00+02:00`).
- `NULL` → `null`; the key is always present, so clients can rely on the shape.

A complete transaction (row 13, the transfer made through an agent):

```
{
  "transaction_id": 13,
  "sms_ref": "TXN4001",
  "amount": "12000.00",
  "fee": "250.00",
  "balance_after": null,
  "currency": "RWF",
  "transaction_date": "2024-02-12T11:40:00+02:00",
  "status": "completed",
  "category": { "category_id": 3, "category_code": "transfer", "category_name": "Transfer to number", "direction": "out", "description": "Money sent to another MoMo number" },
  "user": { "user_id": 4, "username": "eric_n", "full_name": "Eric Niyonzima" },
  "parties": [
    { "role": "receiver", "party": { "party_id": 6, "party_name": "Frank", "party_type": "person", "phone_number": "0786789012", "merchant_code": null } },
    { "role": "agent", "party": { "party_id": 12, "party_name": "Kimironko Agent 045", "party_type": "agent", "phone_number": "0788112233", "merchant_code": "AGT-045" } }
  ],
  "raw_sms": "You have transferred 12000 RWF to Frank (0786789012) via agent Kimironko Agent 045. TxnId: TXN4001",
  "logs": [
    { "log_id": 7, "log_level": "INFO", "event_type": "sms_import", "message": "Imported 1 new transaction with agent Kimironko Agent 045", "created_at": "2024-02-12T12:00:02.441+02:00" }
  ],
  "created_at": "2024-02-12T12:00:02+02:00",
  "updated_at": "2024-02-12T12:00:02+02:00"
}
```

9. How this relates to the running app

The FastAPI app in `app/` still runs on SQLite with a simpler schema (`app/schema.sql`: users, sessions, transactions, unmatched_sms, with the type and the other party stored as text columns). The MySQL design in this document is the full model the app is moving to: it adds the categories lookup table, parties and the junction table, and system logs. The app's current JSON responses are flatter than the nested format in section 8, which is the target API shape. Moving the app to this schema means changing `app/db.py` to MySQL and filling `parties` and `transaction_parties` from the parser.

10. Team and project management

- **Scrum board:** <https://github.com/users/clivetmushipe088/projects/2>
- **Repository:** <https://github.com/clivetmushipe088/momo-ledger>