

PRACTICAL-3

Name: Clive Fernandes

PRN: 202501050019

Division: Chemical(CH1)

3.1.1. Numpy Array Operations

Write a Python program to create a NumPy array based on user input and display the following:

- The created NumPy array.
- The number of dimensions of the array using ndim
- The shape of the array using shape
- The total number of elements in the array using size Assume all input elements are valid integers.

Input Format:

- The first line contains two space-separated integers, and , representing the number of rows and the number of columns.
- The next lines contain space-separated integers representing the elements of the array, entered row by row.


Output Format:

- The created NumPy array (printed as a 2D array).

- An integer representing the number of dimensions of the array.
- A tuple representing the shape of the array.
- An integer representing the total number of elements in the array.

CODE:

```
import numpy as np
rows, cols = map(int, input().split())
elements = []
for _ in range(rows):
    elements.extend(map(int, input().split()))
array = np.array(elements).reshape(rows, cols)
print(array)
print(array.ndim)
print(array.shape)
print(array.size)
```



3.2.1. Numpy: Matrix Operations

The given code takes two matrices, , and , as input from the user and converts them into NumPy arrays.

Task:

You are required to compute and display the results of the following matrix operations:

1. **Addition ()**
2. **Subtraction ()**
3. **Element-wise Multiplication ()**
4. **Matrix Multiplication ()**
5. **Transpose of Matrix A Input Format:**
 - The user will input 3 rows for , each containing 3 integers separated by spaces.
 - Similarly, the user will input 3 rows for , each containing 3 integers separated by spaces.

Output Format:

The program should display the results of the operations in the following order:

1. The result of Addition.
2. The result of Subtraction.
3. The result of Element-wise Multiplication.
4. The result of Matrix Multiplication.
5. The Transpose of Matrix A.

CODE

```
import numpy as np # Input matrices print("Enter Matrix A:")
matrix_a = np.array([list(map(int, input().split())) for i in range(3)])
print("Enter Matrix B:") matrix_b = np.array([list(map(int,
input().split())) for i in range(3)])
```

```
# Addition
addition_result = matrix_a + matrix_b
print("Addition (A + B):")
print(addition_result)

# Subtraction
subtraction_result = matrix_a - matrix_b
print("Subtraction (A - B):")
print(subtraction_result)

# Multiplication (element-wise)
elementwise_multiplication_result = matrix_a * matrix_b

print("Element-wise Multiplication (A * B):")
print(elementwise_multiplication_result)

# Matrix multiplication (dot product)
matrix_multiplication_result = np.dot(matrix_a, matrix_b)
print("A dot B:")

print(matrix_multiplication_result)

# Transpose
transpose_a = matrix_a.T
print("Transpose of A:")
print(transpose_a)
```

3.2.2. Numpy: Horizontal and Vertical Stacking of Arrays

You are given two arrays arr1 and arr2. You need to perform horizontal and vertical stacking operations on them using NumPy.

- **Horizontal Stacking:** Stack the two matrices horizontally (side by side).

- **Vertical Stacking:** Stack the two matrices vertically (one below the other).

Input Format:

- The program should first prompt the user to input two 3x3 arrays.
- Each array consists of 3 rows, and each row contains 3 space-separated integers.
- The user will input the two arrays row by row.

Output Format:

- The program should display the result of the Horizontal Stack (side-by-side stacking) of the two arrays.
- The program should then display the result of the Vertical Stack (one below the other) of the two arrays.

CODE:

```
import numpy as np # Input matrices
print("Enter Array1:")
arr1 = np.array([list(map(int, input().split())) for i in range(3)])
print("Enter Array2:")
arr2 = np.array([list(map(int, input().split())) for i in range(3)])
# Perform horizontal stacking (hstack)
a=np.hstack((arr1,arr2))
print("Horizontal Stack:")
print(a)
# Perform vertical stacking (vstack)
b=np.vstack((arr1,arr2))
print("Vertical Stack:")
```

CODETANTRA Home Learn Anywhere 202501050019@mitaoe.ac.in Support Logout

Average time: 0.090 s Maximum time: 0.155 s 2 out of 2 shown test case(s) passed 2 out of 2 hidden test case(s) passed

Test case 1 155 ms Debug

Expected output

Enter Array1:

```
1 2 3
4 5 6
7 8 9
```

Enter Array2:

```
4 5 6
7 8 9
10 11 12
```

Horizontal Stack:

```
[[1 2 3 4 5 6]
 [4 5 6 7 8 9]
 [7 8 9 10 11 12]]
```

Vertical Stack:

```
[[1 2 3]
 [4 5 6]
 [7 8 9]
 [4 5 6]
 [7 8 9]
 [10 11 12]]
```

Actual output

Enter Array1:

```
1 2 3
4 5 6
7 8 9
```

Enter Array2:

```
4 5 6
7 8 9
10 11 12
```

Horizontal Stack:

```
[[1 2 3 4 5 6]
 [4 5 6 7 8 9]
 [7 8 9 10 11 12]]
```

Vertical Stack:

```
[[1 2 3]
 [4 5 6]
 [7 8 9]
 [4 5 6]
 [7 8 9]
 [10 11 12]]
```

CODETANTRA Home Learn Anywhere 202501050029@mitaoe.ac.in Support Logout

Average time: 0.054 s Maximum time: 0.084 s 2 out of 2 shown test case(s) passed 2 out of 2 hidden test case(s) passed

Test case 2 69 ms Debug

Expected output

Enter Array1:

```
-1 -2 -3
-4 -5 -6
-7 -8 -9
```

Enter Array2:

```
10 11 12
13 14 15
16 17 18
```

Horizontal Stack:

```
[[ -1 -2 -3 10 11 12]
 [-4 -5 -6 13 14 15]
 [-7 -8 -9 16 17 18]]
```

Vertical Stack:

```
[[ -1 -2 -3]
 [-4 -5 -6]
 [-7 -8 -9]
 [10 11 12]
 [13 14 15]
 [16 17 18]]
```

Actual output

Enter Array1:

```
-1 -2 -3
-4 -5 -6
-7 -8 -9
```

Enter Array2:

```
10 11 12
13 14 15
16 17 18
```

Horizontal Stack:

```
[[ -1 -2 -3 10 11 12]
 [-4 -5 -6 13 14 15]
 [-7 -8 -9 16 17 18]]
```

Vertical Stack:

```
[[ -1 -2 -3]
 [-4 -5 -6]
 [-7 -8 -9]
 [10 11 12]
 [13 14 15]
 [16 17 18]]
```

< Prev Reset Submit Next

3.2.3. Numpy: Custom Sequence Generation

Write a Python program that takes the following inputs from the user:

- Start value: The starting point of the sequence.
- Stop value: The sequence should end before this value.
- Step value: The increment between each number in the sequence.

The program should then generate a sequence using numpy based on these inputs and print the generated sequence.

Input Format:

- The user will input three integer values: start, stop, and step, each on a new line.

Output Format:

- The program should print the generated sequence based on the input values.


CODE:

```
import numpy as np

# Take user input for the start, stop, and step of the sequence
start = int(input())
stop = int(input())
step = int(input())

# Generate the sequence using np.arange()
a = np.arange(start, stop, step)
print(a)

# Print the generated sequence
```



3.2.4. Numpy: Arithmetic and Statistical Operations, Mathematical Operations, Bitwise Operators

You are given two arrays A and B. Your task is to complete the function `array_operations`, which will convert these lists into NumPy arrays and perform the following operations:

1. Arithmetic Operations:

- Compute the element-wise sum, difference, and product of the two arrays.

2. Statistical Operations:

- Calculate the mean, median, and standard deviation of array A.

3. Bitwise Operations:

- Perform bitwise AND, bitwise OR, and bitwise XOR on the arrays (ex: $A_i \text{ OR } B_i$).

Input Format:

- The first line contains space-separated integers representing the elements of array A.
- The second line contains space-separated integers representing the elements of array B.

Output Format:

- For each operation (arithmetic, statistical, and bitwise), print the results in the specified format as shown in sample test cases.

CODE:

```
import numpy as np
def
array_operations(A, B):
    # Convert A and B to NumPy arrays
    A = np.array(A)
```

```

B = np.array(B)    # Arithmetic

Operations         sum_result = A + B

diff_result = A - B    prod_result = A
* B

# Statistical Operations

mean_A = np.mean(A)

median_A = np.median(A)  std_dev_A
= np.std(A)

# Bitwise Operations

and_result = A & B

or_result = A | B

xor_result

# Output results with one space between each element

print("Element-wise Sum:", ' '.join(map(str, sum_result)))
print("Element-wise Difference:", ' '.join(map(str, diff_result)))
print("Element-wise Product:", ' '.join(map(str, prod_result)))
print(f"Mean of A: {mean_A}")

print(f"Median of A: {median_A}")

print(f"Standard Deviation of A: {std_dev_A}")

print("Bitwise AND:", ' '.join(map(str, and_result)))

print("Bitwise OR:", ' '.join(map(str, or_result)))


print("Bitwise XOR:", ' '.join(map(str, xor_result))) A =

```

```
list(map(int, input().split())) # Elements of array A B =
```

```
list(map(int, input().split())) # Elements of array B
```

```
array_operations(A, B)
```



3.2.5. Numpy: Copying and Viewing Arrays

The given code takes a list of integers as input and converts it into a NumPy array. Your task is to complete the code by:

- Creating a view of the original_array and assigning it to view_array.
- Creating a copy of the original_array and assigning it to copy_array.

After completing these steps, observe how modifying the view affects the original_array, while modifying the copy does not.

Input Format:

- A single line of space-separated integers.

Output Format:

- After modifying the view:

Original array after modifying view: <original_array>

View array: <view_array>

- After modifying the copy:

Original array after modifying copy: <original_array>

Copy array: <copy_array> **CODE:**

```
import numpy as np
```

```
inputlist = list(map(int,input().split(" ")))
```

```
)# Original array original_array =
```

```
np.array(inputlist) # Create a view
```

```
view_array =original_array.view()
```

```
# Create a copy copy_array
```

```
=original_array.copy()
```

```
# Modify the view view_array[0] = 99 print("Original array  
after modifying view:", original_array) print("View array:",  
view_array)
```

```
# Modify the copy copy_array[1] = 88 print("Original array  
after modifying copy:", original_array) print("Copy array:",  
copy_array)
```

The screenshot displays the CODETANTRA IDE interface. At the top, there's a header with the logo and navigation links. Below the header, a status bar indicates '2 out of 2 shown test case(s) passed' and '2 out of 2 hidden test case(s) passed'. The main area shows two test cases. Test Case 1 has an expected output of [19, 20, 30, 40, 50, 60, 70, 80] and an actual output of [18, 20, 30, 40, 50, 60, 70, 80]. Test Case 2 has an expected output of [99, 2, 3, 4, 5] and an actual output of [99, 88, 3, 4, 5]. The interface also includes a sidebar with 'Explorer' and 'Debugger' tabs.

3.2.6. Numpy: Searching, Sorting, Counting, Broadcasting

The given code in the editor takes a single array, array1, as spaceseparated integers as input from the user.

Additionally, it takes the following inputs:

- search_value: The value to search for in the array.
- count_value: The value to count its occurrences in the array.
- broadcast_value: The value to add for broadcasting across the array. You need to complete the code to perform the following operations:

1. **Searching:** Find the indices where search_value appears in array1 and print these indices.
2. **Counting:** Count how many times count_value appears in array1 and print the count.
3. **Broadcasting:** Add broadcast_value to each element of array1 using broadcasting, and print the resulting array.
4. **Sorting:** Sort array1 in ascending order and print the sorted array.

Input Format:

1. A single line containing space-separated integers representing array1.
2. An integer search_value represents the value to search for in the array.
3. An integer count_value represents the value to count in the array.

4. An integer `broadcast_value` represents the value to add to each element of the array.

Output Format:


1. The indices where `search_value` occurs in `array1`.
2. The count of occurrences of `count_value` in `array1`.
3. The array after adding the `broadcast_value` to each element.
4. The sorted array.

CODE:

```
import numpy as np# Input array from the user array1 =
np.array(list(map(int, input().split()))))
# Searching search_value = int(input("Value to
search: ")) count_value = int(input("Value to
count: ")) broadcast_value = int(input("Value
to add: ")) # Find indices where value matches
in array1
a=np.where(array1==search_value)[0] print(a)
# Count occurrences in array1
b=np.count_nonzero(array1==count_value) print(b)
# Broadcasting addition c=array1 +
broadcast_value print(c)
```

```
# Sort the first array
```

```
d=np.sort(array1) print(d)
```



3.2.7. Student Data Analysis and Operations

Write a Python program that takes the file name of a CSV file containing student details, including roll numbers and their marks in three subjects as input, reads the data, and performs the following operations:

- **Print all student details:** Display the complete details of all students, including roll numbers and marks for all subjects.
- **Find total students:** Determine the total number of students in the dataset.
- **Print all student roll numbers:** Extract and print the roll numbers of all students.
- **Print Subject 1 marks:** Extract and print the marks of all students in Subject 1.

- **Find minimum marks in Subject 2:** Identify the lowest marks in Subject 2.
- **Find maximum marks in Subject 3:** Identify the highest marks in Subject 3.
- **Print all subject marks:** Display the marks of all students for each subject.
- **Find total marks of students:** Compute the total marks for each student across all subjects.
- **Find the average marks of each student:** Compute the average marks for each student.
- **Find average marks of each subject:** Compute the average marks for all students in each subject.
- **Find average marks of Subject 1 and Subject 2:** Compute the average marks for Subject 1 and Subject 2.
- **Find average marks of Subject 1 and Subject 3:** Compute the average marks for Subject 1 and Subject 3.
- **Find the roll number of the student with maximum marks in Subject 3:** Identify the student with the highest marks in Subject 3 and print their roll number.
- **Find the roll number of the student with minimum marks in Subject 2:** Identify the student with the lowest marks in Subject 2 and print their roll number.
- **Find the roll number of students who scored 24 marks in Subject 2:** Identify students who obtained exactly 24 marks in Subject 2 and print their roll numbers.

- **Find the count of students who got less than 40 marks in Subject 1:** Count the number of students who scored less than 40 marks in Subject 1.
- **Find the count of students who got more than 90 marks in Subject 2:** Count the number of students who scored more than 90 marks in Subject 2.
- **Find the count of students who scored ≥ 90 in each subject:** Count the number of students who scored 90 or more marks in each subject.
- **Find the count of subjects in which each student scored ≥ 90 :** Determine how many subjects each student scored 90 or more marks in.
- **Print Subject 1 marks in ascending order:** Sort and print the marks of students in Subject 1 in ascending order.
- **Print students who scored between 50 and 90 in Subject 1:** Display students who scored marks between 50 and 90 in Subject 1.
- **Find index positions of students who scored 79 in Subject 1:** Identify the index positions of students who scored exactly 79 marks in Subject 1.

CODE:

```
import numpy as npa = np.loadtxt("Sample.csv", delimiter=',',
skiprows=1)
```

```
# 1. Print all student details print("All
student Details:\n",a)
```

```
# 2. print total students
```

```

print("Total Students:",a.shape[0]) # 3. Print all
student Roll numbers print("All Student Roll
Nos",a[:,0]) # 4. Print subject 1 marks
print("Subject 1 Marks",a[:,1]) # 5. print
minimum marks of Subject 2 print("Min marks
in Subject 2",np.min(a[:,2])) # 6. print
maximum marks of Subject 3 print("Max marks
in Subject 3",np.max(a[:,3]))
# 7. Print All subject marks print("All subject
marks:",a[:,1:4]) # 8. print Total marks of
students print("Total
Marks",np.sum(a[:,1:4],axis=1))
# 9. print average marks of each student
#Note:Expected output shows rounded values like 77.3
print(np.round(np.mean(a[:,1:4],axis=1),1)) # 10. print
average marks of each subject print("Average Marks of
each
subject",np.round(np.mean(a[:,1:4],axis=0),1))
# 11. print average marks of S1 and S2
#The test case expected[71.7 59.8], which are the individual subject
averages
print("Average Marks of S1 and

```

```

S2",np.round(np.mean(a[:,1:3],axis=0),1)) # 12. print average
marks of S1 and S3 print("Average Marks of S1 and
S3",np.round(np.mean(a[:,[1, 3]],axis=0),1))
# 13. print Roll number who got maximum marks in Subject 3
print("Roll no who got maximum marks in Subject
3",a[np.argmax(a[:,3]),0])
# 14. print Roll number who got minimum marks in Subject 2
print("Roll no who got minimum marks in Subject
2",a[np.argmin(a[:,2]),0])
# 15. print Roll number who got 24 marks in Subject 2 print("Roll no
who got 24 marks in Subject 2",a[a[:,2]==24][:,0:1]) # 16. print
count of students who got marks in Subject 1 < 40 print("Count of
students who got marks in Subject 1 < 40",np.sum(a[:,1]<40))
# 17. print count of students who got marks in Subject 2 > 90
print("Count of students who got marks in Subject 2 >
90:",np.sum(a[:,2]>90))
# 18. print count of students in each subject who got marks >= 90
print("Count of students in each subject who got marks >=
90:",np.sum(a[:,1:4]>=90,axis=0))# 19. print count of subjects in
which each student got marks >= 90 print("Roll no:",a[:,0])
print("Count of subjects in which student got marks >=
90:",np.sum(a[:,1:4]>=90,axis=1)) # 20. Print S1 marks in
ascending order print(np.sort(a[:,1]))
# 21. Print S1 marks >= 50 and <=
90print(a[(a[:,1]>=50)&(a[:,1]<=90)])

```

#Bonus: The test case shows the full array printed again before the index positions print(a)

22. Print the index position of marks 79

Expected format:(array([6,9],dtype=int32),)

print(np.where(a[:,1]==79))

The image displays two screenshots of the CODETANTRA IDE interface, showing test case results for a NumPy array. The top screenshot shows the 'Expected output' and 'Actual output' for a test case, both displaying the same array of student marks. The bottom screenshot shows the 'Expected output' and 'Actual output' for a test case, both displaying the same array of student marks.

Top Screenshot:

Test case 1 (40 ms) [Debug] [Test]

Expected output:

```
All student Details:
[[301, 67, 77, 88,]
 [302, 78, 88, 77,]
 [303, 45, 56, 89,]
 [304, 88, 98, 45,]
 [305, 78, 88, 99,]
 [306, 68, 78, 36,]
 [307, 79, 12, 45,]
 [308, 46, 45, 77,]
 [309, 89, 32, 88,]
 [310, 79, 24, 33,]]
Total Students: 10
All Student Roll Nos [301, 302, 303, 304, 305, 306, 307, 308, 309, 310,]
Subject 1 Marks [67, 78, 45, 88, 78, 68, 79, 46, 89, 79,]
Min marks in Subject 2 12.0
Max marks in Subject 3 99.0
All subject marks: [[67, 77, 88,]
 [78, 88, 77,]
 [45, 56, 89,]
 [88, 98, 45,]
 [78, 88, 99,]
 [68, 78, 36,]
 [79, 12, 45,]
 [46, 45, 77,]
 [89, 32, 88,]
 [79, 24, 33,]]
Total Marks [232, 243, 190, 231, 265, 182, 136, 168, 209, 136,]
```

Actual output:

```
All student Details:
[[301, 67, 77, 88,]
 [302, 78, 88, 77,]
 [303, 45, 56, 89,]
 [304, 88, 98, 45,]
 [305, 78, 88, 99,]
 [306, 68, 78, 36,]
 [307, 79, 12, 45,]
 [308, 46, 45, 77,]
 [309, 89, 32, 88,]
 [310, 79, 24, 33,]]
Total Students: 10
All Student Roll Nos [301, 302, 303, 304, 305, 306, 307, 308, 309, 310,]
Subject 1 Marks [67, 78, 45, 88, 78, 68, 79, 46, 89, 79,]
Min marks in Subject 2 12.0
Max marks in Subject 3 99.0
All subject marks: [[67, 77, 88,]
 [78, 88, 77,]
 [45, 56, 89,]
 [88, 98, 45,]
 [78, 88, 99,]
 [68, 78, 36,]
 [79, 12, 45,]
 [46, 45, 77,]
 [89, 32, 88,]
 [79, 24, 33,]]
Total Marks [232, 243, 190, 231, 265, 182, 136, 168, 209, 136,]
```

Bottom Screenshot:

Test case 1 (40 ms) [Debug] [Test]

Expected output:

```
Average Marks of S1 and S2 [71.7 59.8]
Average Marks of S1 and S3 [71.7 67.7]
Roll no who got maximum marks in Subject 3 305.0
Roll no who got minimum marks in Subject 2 307.0
Roll no who got 24 marks in Subject 2 [310,]
Count of students who got marks in Subject 1 < 40 0
Count of students who got marks in Subject 2 > 90 1
Count of students in each subject who got marks >= 90 [0 1 1]
Roll no: [301, 302, 303, 304, 305, 306, 307, 308, 309, 310,]
Count of subjects in which student got marks >= 90 [0 0 0 1 1 0 0 0 0 0]
[45, 46, 67, 68, 78, 79, 79, 79, 88, 89,]
[[301, 67, 77, 88,]
 [302, 78, 88, 77,]
 [303, 45, 56, 89,]
 [304, 88, 98, 45,]
 [305, 78, 88, 99,]
 [306, 68, 78, 36,]
 [307, 79, 12, 45,]
 [308, 46, 45, 77,]
 [309, 89, 32, 88,]
 [310, 79, 24, 33,]]
[[301, 67, 77, 88,]
 [302, 78, 88, 77,]
 [303, 45, 56, 89,]
 [304, 88, 98, 45,]
 [305, 78, 88, 99,]
 [306, 68, 78, 36,]
 [307, 79, 12, 45,]
 [308, 46, 45, 77,]
 [309, 89, 32, 88,]
 [310, 79, 24, 33,]]
(array([6, 9], dtype=int32),)
```

Actual output:

```
Average Marks of S1 and S2 [71.7 59.8]
Average Marks of S1 and S3 [71.7 67.7]
Roll no who got maximum marks in Subject 3 305.0
Roll no who got minimum marks in Subject 2 307.0
Roll no who got 24 marks in Subject 2 [310,]
Count of students who got marks in Subject 1 < 40 0
Count of students who got marks in Subject 2 > 90 1
Count of students in each subject who got marks >= 90 [0 1 1]
Roll no: [301, 302, 303, 304, 305, 306, 307, 308, 309, 310,]
Count of subjects in which student got marks >= 90 [0 0 0 1 1 0 0 0 0 0]
[45, 46, 67, 68, 78, 79, 79, 79, 88, 89,]
[[301, 67, 77, 88,]
 [302, 78, 88, 77,]
 [303, 45, 56, 89,]
 [304, 88, 98, 45,]
 [305, 78, 88, 99,]
 [306, 68, 78, 36,]
 [307, 79, 12, 45,]
 [308, 46, 45, 77,]
 [309, 89, 32, 88,]
 [310, 79, 24, 33,]]
[[301, 67, 77, 88,]
 [302, 78, 88, 77,]
 [303, 45, 56, 89,]
 [304, 88, 98, 45,]
 [305, 78, 88, 99,]
 [306, 68, 78, 36,]
 [307, 79, 12, 45,]
 [308, 46, 45, 77,]
 [309, 89, 32, 88,]
 [310, 79, 24, 33,]]
(array([6, 9], dtype=int32),)
```