



HSR
HOCHSCHULE FÜR TECHNIK
RAPPERSWIL

COMPUTER SCIENCE

Readiness for Tailored Attacks and Lateral Movement Detection

STUDY THESIS

Authors:

Claudio MATTES
claudio.mattes@hsr.ch

Lukas KELLENBERGER
lukas.kellenberger@hsr.ch

Supervisor:

Cyrill BRUNSCHWILER
Hochschule für Technik Rapperswil
cyrill.brunschwiler@hsr.ch

DEPARTEMENT COMPUTER SCIENCES
HSR UNIVERSITY OF APPLIED SCIENCES RAPPERSWIL
CH-8640 RAPPERSWIL, SWITZERLAND

December 9, 2018

Abstract

Introduction

The amount of cyber-attacks where malicious code is used, which not only settles on the infected system, but also infects other systems in the network, has massively increased recently. The outcome is often the complete infiltration of the organization due the use of lateral movements and advanced persistent threats (APT). In the analysis of such an event, information and time are key factors to success. Consequently, readiness for such an event is a decisive factor.

Procedure

The project was limited to Windows machines running on the operating system Windows 10 Pro or Windows Server 16. In the elaboration phase, research was done into how the goal of determining readiness could be implemented. The decision was made to implement the tool on the basis of the Paper "Detecting Lateral Movement through Tracking Event Logs" of the "Japan Computer Emergency Response Team Coordination Center". Existing tools / products were searched for, on which can be built on. Unfortunately, no corresponding products were found and so decided that such a tool should be redesigned. As technology served PowerShell because it is close to the Microsoft operating system and that it has a detailed documentation at its disposal.

Result

During the construction phase the "System Readiness Inspector - SRI", a PowerShell script, was developed. This phase was completed using the Scrum method. The SRI has four different modes: Online, Offline, GroupPolicy, AllGroupPolicies. The online mode is limited to the current system and thus determines readiness. The offline mode is used to be able to make a statement about any system by means of exports. The GroupPolicy mode is limited to a specific Group Policy, which is checked for its audit settings. In the AllGroupPolicies mode, all group policies of the current domain are examined.

Management Summary

Initial Situation

The amount of cyber-attacks where malicious code is used, which not only settles on the infected system, but also infects other systems in the network, has massively increased recently. The outcome is often the complete infiltration of the organization. In the analysis of such an event, information and time are key factors to success. Consequently, readiness for such an event is a decisive factor.

The Japan Computer Emergency Response Team Coordination Center has analysed the procedure and the used tools of such attacks. In their most recent publication on this topic, they give hints which events indicate a possible contamination. The aim of this study thesis is to use this published paper and write a tool that helps to identify the readiness of a system.

Procedure

The project was initially limited to Windows machines running on the operating system Windows 10 Pro or Windows Server 16. The project was divided into four phases, one week inception, five weeks for the elaboration of the project, six weeks for construction and two weeks for the final phase, the transition. During the elaboration phase we did some research on the topic and we tested different tools which could be interesting for our project. At the end of the elaboration we had decided to realise the project using PowerShell. In the following six weeks we wrote the "System Readiness Inspector - SRI", a PowerShell script.

The SRI reads information about the system on which it is running and evaluates which attack categories can or cannot be detected with these settings. This information obtained is then visualized into a PDF document and output by the script.

Results

The SRI runs successfully and outputs important system settings about the readiness. Illustrated in a PDF, the analyst can see at a glance which of his audit settings are missing or incorrect. The script also evaluates which attacks might be missed due to incorrectly configured settings. SRI helps an analyst to check a system for its readiness and saves him the tedious task of collecting and evaluating the data.

Outlook

SRI is still at an early stage of its development. The further development of the visualization is conceivable. The extension to an entire fleet will also be an approach that will certainly be pursued further. Although SRI is a useful helper when it comes to get a quick overview about the audit settings and the readiness in general.

Contents

Abstract	I
Introduction	I
Procedure	I
Result	I
 Management Summary	 II
Initial Situation	II
Procedure	II
Results	II
Outlook	II
 Table of Contents	 VI
 I Technical Report	 VII
1 Introduction and Overview	1
2 Test environment	2
2.1 User	3
2.2 Difficulties	3
3 Analysis	4
3.1 BloodHound / SharpHound	4
3.1.1 Description	4
3.1.2 Difficulties	4
3.1.3 Conclusion	4
3.2 Windows Event Logging Forensic Logging Enhancement Services	4
3.2.1 Description	4
3.2.2 Conclusion	5
3.3 Microsoft Security Compliance Toolkit	5
3.3.1 Description	5
3.3.2 Difficulties	5
3.3.3 Conclusion	5
3.4 LogonTracer	6
3.4.1 Description	6
3.4.2 Difficulties	8
3.4.3 Conclusion	8
3.5 Microsoft Monitoring Active Directory for Signs of Compromise	9
3.5.1 Description	9
3.5.2 Conclusion	9

3.6	MITRE Adversarial Tactics, Techniques and Common Knowledge (ATT&CK) .	9
3.6.1	Description	9
3.6.2	Conclusion	9
3.7	Sysmon	10
3.7.1	Description	10
3.7.2	Conclusion	10
3.8	Sysmon Tools	10
3.8.1	Description	10
3.8.2	Conclusion	10
3.9	sysmon-modular	11
3.9.1	Description	11
3.9.2	Conclusion	11
3.10	CryptoAPI 2.0	12
3.10.1	Description	12
3.10.2	Conclusion	12
3.11	JPCERT/CC - Detecting Lateral Movement in APTs	13
3.11.1	Description	13
3.11.2	Conclusion	13
3.12	JPCERT/CC - Detecting Lateral Movement through Tracking Event Logs . . .	13
3.12.1	Description	13
3.12.2	Conclusion	13
4	Design	14
4.1	Decision for a new Tool	14
4.2	Mandatory Event Logs	14
4.3	Correlation: Advanced Audit Policy Setting and Event Log IDs	17
4.4	Attack Categories	19
4.5	Audit Priority	21
4.6	Domain Analysis	23
4.6.1	Network	24
4.6.2	Computer	24
4.6.3	Event	24
4.6.4	AuditPolicy	24
4.6.5	Reference	24
5	System Architecture	25
5.1	Use Cases (UC)	25
5.1.1	UC01 - Read Resultant Set of Policies	25
5.1.2	UC02 - Analyse Audit Policies	25
5.1.3	UC03 - Find Event Logs	26
5.1.4	UC04 - Analyse Found Event Logs	26
5.1.5	UC05 - Display missing or wrong system configuration	26
5.1.6	UC06 - Save Result to specific path	27
5.1.7	UC07 - Main Script	27
5.1.8	UC08 - Get Domain Information	27
5.2	Non Functional Requirements	28
5.3	Technologies	29
5.3.1	Chosen Technologies	29
5.3.2	Rejected Technologies	29
5.4	Sequence Diagram	30
5.4.1	GetAuditPolicy()	30

5.4.2	AnalyseAuditPolicy()	30
5.4.3	GetEventLog()	30
5.4.4	AnalyseEvents()	30
5.5	VisualiseResults()	31
6	Implementation	32
6.1	Module: GetAndAnalyseAuditPolicies	32
6.1.1	Result	32
6.1.2	Approach	33
6.1.3	Implementation	35
6.2	Module: GetAndCompareLogs	41
6.2.1	Result	41
6.2.2	Approach	42
6.2.3	Implementation	43
6.3	Module: Visualize	45
6.3.1	Result	45
6.3.2	Approach	45
6.3.3	Implementation	46
6.4	Main Script: SRI	49
6.4.1	Result	49
6.4.2	Approach	51
6.4.3	Implementation	51
7	Conclusion and Outlook	55
Glossary		VI
Listings		IX
List of Figures		X
List of Tables		XI
Bibliography		XIII
II Appendix		XIV
Einführung		XV
Aufgabe		XV
Abgrenzung		XV
Tätigkeiten		XV
Vorgehen		XVI
Anforderungen		XVI
Technologien		XVI
Infrastruktur		XVII
Erwartete Resultate		XVII
In elektronischer Form		XVII

Auf Papier	XVII
Termine	XVII
Zeitplan und Meilensteine	XVIII
Betreuung	XVIII
Kontakt	XVIII
Unterschriften	XVIII

Part I

Technical Report

1 Introduction and Overview

As described in the abstract, the key for a successful analysis in case of an advanced persistence threat (APT) or lateral movement in a network, is to have a solid event logging of all systems participating in the network.

Shusei Tomonaga at the Japan Computer Emergency Response Team Coordination Center (JPCERT/CC) has shown with the study "Detecting Lateral Movement through Tracking Event Logs" [1] how important it is to configure solid event logging to analyse attacks. JPCERT/CC found in their study that APT and lateral movements could be detected with the correct settings in the audit policy and with the help of Sysmon 37 of 44 attacks.

Hence, it was decided to implement the project on the basis of this study. This study offers an extensive set of analysed tools from bad guys and what effects these tools have on the event log. Thus, the readiness of a system can be concluded from this study.

This technical report contains the research part in which tools were searched for on which can be built on. Then, based on the research, the design decision and the resulting architecture follows. The implementation will then be discussed in detail and, finally, a conclusion and outlook will be drawn on the basis of this work.

2 Test environment

This chapter of the report describes the setup of the testing environment in which not only the tools during the research were tested, but also was used to test the System Readiness Inspector itself.

A virtual network was set up on the Microsoft Azure Cloud as a test environment. The test network was set up in the cloud so that the development team can access the network regardless of its location. The test network consists of a Windows server and two Windows clients. Active Directory service was configured on the server to manage the client computer and to have the possibilities to create group policies. Group policies are used in almost every corporate environment to build rule sets for configurations. These configurations are a core element to check the readiness of a system. The following operating systems were installed in this test network:

Server:

- Windows Server 2016

Clients:

- Windows 10 Pro, Version 1709

The network is structured as followed:




Figure 2.1: Test Environment

2.1 User

Three users were configured for the logfarm-network:

Name	Privileges
alice	Domain administrator
bob	User
charlie	User

Table 2.1: Test Environment User

2.2 Difficulties

Various difficulties occurred which are presented in this subsection.

Connect to the virtual machines via Remote Desktop Protocol (RDP)

After setting up the virtual machines on Azure, the developers tried to connect to the devices via the Remote Desktop Protocol but failed. First, the developers suspected the issue was the incoming port rules, so the machines were reinstalled. However, this did not fix the issue. It became apparent that the problem were not the virtual machines (VM), but with the network used to connect to the Microsoft Azure Cloud. Some firewall rules blocked the RDP-connection. In order to avoid this, the developers used a Virtual Private Network (VPN) connection in which these rules did not apply.

Firewall setting for Internet Control Message Protocol (ICMP)

After the virtual network had been set up, the developers tested the connections in the virtual network. The configured Domain Name System (DNS) ran without any problem and could translate all hostnames. Testing the network using Pings showed that almost all clients were receiving pings, but the ping-requests by one client remained unanswered. It transpired that, for some inexplicable reason, the incoming ICMP-firewall-settings were different on this client. After adjusting the setting, the ping-requests were answered positively.

RDP connection for Bob and Charlie

Due to the fact that the user `alice` owns domain administrator privileges, this user was able to connect over RDP without an error. Bob and Charlie on the other hand did not have this permission. The developers had to create a group for them, the RDP-Group. This group was then allowed to login over RDP on the clients Win10-Client and Win10-Admin.

3 Analysis

This chapter describes the first step of this project, the research of published technical reports and tools which are considered interesting for this project. The individual sections are again divided into a short description and a conclusion of how valuable this will be for the project. In the case of tested tools, the difficulties during the tests are also discussed.

3.1 BloodHound / SharpHound

3.1.1 Description

BloodHound describes itself on its wiki page on GitHub as follows:

"BloodHound is a single page Javascript web application, built on top of Linkurious, compiled with Electron, with a Neo4j database fed by a PowerShell/C# ingestor. BloodHound uses graph theory to reveal the hidden and often unintended relationships within an Active Directory environment. Attacks can use BloodHound to easily identify highly complex attack paths that would otherwise be impossible to quickly identify. Defenders can use BloodHound to identify and eliminate those same attack paths. Both blue and red teams can use BloodHound to easily gain a deeper understanding of privilege relationships in an Active Directory environment." [2]

3.1.2 Difficulties

BloodHound was tested in the test environment which is described later in this chapter. Both the C# and Python ingestors were successfully installed and tested. The only problem which occurred was that the Python-ingestor does not yet run on the latest Python release. One must have a Python 2.7.x version installed to run the scripts successfully.

3.1.3 Conclusion

The most interesting aspect of BloodHound for our project is the way it retrieves its data. Due to the decision that the application, in a first step, only reads the data of the local computer and not the whole domain, BloodHound will only be important in a later part of the project. Their so called ingestor will be used to retrieve the data of a whole network instead of only a local computer.

3.2 Windows Event Logging Forensic Logging Enhancement Services

3.2.1 Description

Windows Event Logging Forensic Logging Enhancement Services (WEFFLES) is a Threat Hunting/Incident Response Console with Windows Event Forwarding and PowerBI, coded and published by Microsoft-Security-Employee Jessica Payne. It is built to help set up the Windows Event Forwarding, so that all the collected logs of a system are stored on one centralised server, and afterwards to analyse the collected data. Jessica Payne wrote an installation instruction on the Microsoft TechNet blog <https://blogs.technet.microsoft.com/jepayne/2017/12/08/weffles/>. Once the data is collected the generated weffles.csv file can simply be imported into Excel and start filtering the logs to gain the needed. Jessica Payne recommends to use PowerBI, a business analytics tool designed by Microsoft. In her published blog she also gives a short introduction on what to look out for, which event ids are important and other useful tips and tricks for detecting suspicious activities in the network.

3.2.2 Conclusion

WEFFELS will not be the product on which this project is based, but could become an important point of reference. The installation guide and other WEFFELS-related documents collected by Jessica Payne provide a lot of information for reading and understanding logs, which will be very helpful for this project. Also an interesting aspect of WEFFLES and the Jessica Payne article is how she visualised the logs, using Microsoft PowerBI.

3.3 Microsoft Security Compliance Toolkit

3.3.1 Description

The Microsoft Security Compliance Toolkit (SCT) [3] allows security administrators to analyse their configured enterprise Group Policy Objects (GPO) in comparison to the Microsoft-recommended GPO baselines. The toolkit comes with several baseline GPO's for different versions of Microsoft Windows Client and Servers:

- Windows 10 security baselines
 - Windows 10 Version 1803 (April 2018 Update), 1709 (Fall Creators Update), 1703 (Creators Update), 1607 (Anniversary Update), 1511 (November Update), 1507
- Windows Server security baselines
 - Windows Server 2016
 - Windows Server 2012 R2
- Microsoft Office security baseline
 - Office 2016

3.3.2 Difficulties

The toolkit is very simple and could be understood and used without any difficulties. The handling is very intuitive and does not require much training. Please note, however, that the toolkit cannot be used with Windows 10 Home, since active directory support is not provided with this version.

3.3.3 Conclusion

This toolkit can be used for a very baseline GPO in enterprise environment. With the delivered baselines it is easy to compare the configured GPO and to see the readiness of the enterprise GPO. The toolkit enables the comparison of different local GPO's installed on different Clients or Servers to check their consistency. In addition, the provided baselines can be used for building new GPO's. Furthermore, Microsoft delivers with the SCT a Local Group Policy Object Utility (LGPO.exe) to:

- Import and apply policy settings
- Export local policy to a GPO backup
- Parse a registry.pol file to "LGPO text" format
- Build a registry.pol file from "LGPO text"

This toolkit is very interesting, but cannot be used to build on it. The reason for this is that the source code of the complete toolkit is not available. However, it can be used as additional help for checking the readiness of a system and comparing the local policies against templates or other local policies.

3.4 LogonTracer

3.4.1 Description

JPCERT/CCs LogonTracer is a tool built to investigate malicious logons on a system based on the research described in section "3.11 JPCERT/CC - Detecting Lateral Movement in APTs". The tool links hostnames or Internet-Protocol (IP) addresses with the "[...] *account name found in logon-related events and displays it as a graph*". [4] The following event ids are checked with the tool:

- 4624: Successful logon
- 4625: Logon failure
- 4768: Kerberos Authentication
- 4769: Kerberos Service Ticket
- 4776: NTLM Authentication
- 4672: Assign special privileges

The following figure depicts a sample graph of logins from different users in the test environment:




Figure 2.2: LogonTracer: Sample Graph from Test Environment

To use the LogonTracer, only a .evtx-File (Windows Extensible Markup Language (XML) Event Log: export of Windows event logs) is necessary to be uploaded. To get the best result out of LogonTracer an export of the security event log from the domain controller should be used - to get as much information of the network as possible. With the built-in analysis of logins, by using machine learning models and statistical analysis, LogonTracer is able to provide a ranking of the most malicious users which tried to log in. [5]

In addition, LogonTracer provides a timeline for all or selected users to show when each user logged in. The timeline can also be displayed as a graph with the LogonTracer, allowing anomalies to be detected more quickly.

The test environment showed that this graph can quickly become confusing - especially in a larger corporate environment as depicted in figure 2.3 LogonTracer: Confusing Graph from Test Environment. Although only a small environment as described in the section 2 "Test environment" was used, it turned out that various users wanted to log on to the virtual machines. The reason for this is that the test environment was built in the Microsoft Azure Cloud and is accessible via public IP addresses in the cloud.




Figure 2.3: LogonTracer: Confusing Graph from Test Environment

Nevertheless, with meaningful filters the search can be restricted and the graph can be used efficiently, as shown in figure 2.2 LogonTracer: Sample Graph from Test Environment

3.4.2 Difficulties

During the test phase of LogonTracer some difficulties were faced. It is pretty easy to get the docker container, but starting LogonTracer was a bit of a challenge. JPCERT/CC gives the following instructions for starting the docker container:

Listing 2.1: LogonTracer: given docker run command

```

1  $ docker run --detach \
2  --publish=7474:7474 --publish=7687:7687 --publish=8080:8080 \
3  -e LTHOSTNAME=[IP_Address] jpcertcc/docker-logontracer

```

The problem was that the parameter `[IP_Address]` was not described well. If the command `docker ps` was executed it always showed the following **PORTS**:

Listing 2.2: LogonTracer: docker ps (PORTS)

```

1  PORTS
2  0.0.0.0:7474->7474/tcp, 0.0.0.0:7687->7687/tcp, 7473/tcp, 0.0.0.0:8080->8080/tcp

```

After some time of investigation and further tests, it turned out that under **PORTS** the ports respectively ip addresses of the container can be bound to the host. But these are not relevant for the LogonTracer, because it provides a web application under the defined parameter `[IP_Address]` and it can eventually be reached via `localhost:8080`. If this parameter was set to `127.0.0.1`, the database containing the imported `.evtx` file could not be accessed. Thus the graph was never displayed. The parameter `[IP_Address]` set to `localhost` solved this problem.

Listing 2.3: LogonTracer: recommended docker run command

```

1  $ docker run --detach \
2  --publish=7474:7474 --publish=7687:7687 --publish=8080:8080 \
3  -e LTHOSTNAME=localhost jpcertcc/docker-logontracer

```

3.4.3 Conclusion

The LogonTracer is unique in its form and should not be underestimated for the detection of lateral movements. This is because user access to various components available in the network can be visualised simply and graphically, hence conclusions can be drawn about what has happened.

However, the LogonTracer is not suitable for detection readiness and cannot be used to build on it. Nonetheless, approaches for reading the event log for further work could be used. This tool is also extremely interesting and recommendable for a further detection of lateral movements.

3.5 Microsoft Monitoring Active Directory for Signs of Compromise

3.5.1 Description

This article "Microsoft Monitoring Active Directory for Signs of Compromise" [6] is about configuration of a solid event log monitoring for Microsoft servers. The article gives a quite a good overview about the audit policy in Microsoft systems and what each policy stands for. The article gives information about the most important audit policies and how noisy (if a lot of data is produced by them) they are. This study does not go into the details of the audit policies in detail. Furthermore, the article describes how the policies can be read with powershell.

In this article Microsoft compiles in Appendix L [7] all important event ids which are necessary for a successful detection of APTs and lateral movements.

3.5.2 Conclusion

Due to the fact that audit policies are an important setting for solid event logging, this article and Appendix L will be a central part of the toolkit to be built. As a next step and part of this study, these event ids have to be correlated with the event ids found in the JPCERT/CC's study "Detecting Lateral Movement through Tracking Event Logs" [1] to make a clear statement which event ids have to be logged.

3.6 MITRE Adversarial Tactics, Techniques and Common Knowledge (ATT&CK)

3.6.1 Description

MITRE ATT&CK introduces itself on its website as follows:

"MITRE ATT&CKTM is a globally-accessible knowledge base of adversary tactics and techniques based on real-world observations. The ATT&CK knowledge base is used as a foundation for the development of specific threat models and methodologies in the private sector, in government, and in the cybersecurity product and service community." [8]

The portal offers a variety of attacks and their patterns, which are currently known in different operating systems. MITRE ATT&CK describes the attack in short words and then lists possibilities for detection and mitigation. The portal also describes various attack tools, their targets and effects on the system. In addition, the corresponding attacks are always cross-referenced. This is a great advantage for a quick search, especially when time is of the essence.

3.6.2 Conclusion

Although many attacks are described and how they can be detected and fended off, MITRE ATT&CK is not quite suitable for our task. The readiness of a system to detect tailored attacks and lateral movements is only roughly described and would be associated with a time-consuming analysis in order to draw exact conclusions.

3.7 Sysmon

3.7.1 Description

System Monitor (Sysmon) is a Windows system service and device driver that, once installed on a system, remains resident across system reboots to monitor and log system activity to the Windows event log. It provides detailed information about process creations, network connections, and changes to file creation time.[9]

Sysmon logs several events on the system which are partly logged by default too. For example, the event "A new process has been created" with the identifier (ID) 4688 is logged by Sysmon with the ID 1 "Process Creation". The problem is that the default logged event with the ID 4688 logs only the executable file (EXE) name as well as the including path. But bad guys want to stay below the radar, so they might replace the original EXE with a malicious one and rename it like the original. Hence, there is no way to determine with the system based event log entry 4688 if the original EXE was executed. Sysmon eliminates exactly this gap by logging not only the name and path of the EXE but also the hash value of the EXE. Ergo Sysmon brings a big advantage to detect if a malicious EXE was executed or not. therefore a reference hash value of the executed EXE is required to compare the hash values on its correctness. [10]

3.7.2 Conclusion

As mentioned in the description, Sysmon is an important tool to be enabled for solid detection of attacks. So Sysmon has to be detected if it is running or not to prepare an environment for a good readiness. In order to not create duplicated events, the events similar logged by default and Sysmon must be examined by their differences. Very likely Sysmon is the better choice.

3.8 Sysmon Tools

3.8.1 Description

Sysmon Tools [11] contains some useful functions to make better use of Sysmon. Among other things there are different views for the representation of the single entries which were recorded by Sysmon. A Process View is provided which can be used to examine a process in more detail. Related processes are taken into account and represented in a simple data-flow-like view, sorted by chronological order. With the Map View you can include geo-locate IP addresses during the import phase and Map View tries to geo-map the network destinations with ipstack [12]. The All Events View represents a full search by Sysmon and can be filtered and grouped accordingly. Furthermore, Sysmon Tools offers a Sysmon Shell, which can be used to create a customized XML configuration for Sysmon using a graphical user interface (GUI). Templates are also provided for further building.

3.8.2 Conclusion

This tool can also be a great help for detecting attacks and, with the Sysmon Shell, a robust configuration for Sysmon can be created. However, Sysmon Tool will have no basis for this project.

3. Analysis

3.9 sysmon-modular

3.9.1 Description

With sysmon-modular [13] a clean configuration of the Windows system service System Monitor (Sysmon), an xml-file which is loaded by Sysmon, is provided. Noisy process creations, which are made by legitimate programs, are suppressed as far as possible by Sysmon. The tool offers the possibility and it is expressly recommended by the developer to adapt the configuration to the respective organisation. Furthermore, sysmon-modular implements various attacks in MITRE ATT&CK for detection with Sysmon. It offers the possibility to detect the attacks shown in the figure 2.4 with Sysmon.

Execution 25 Items	Persistence 41 Items	Privilege Escalation 21 Items	Defense Evasion 49 Items	Credential Access 16 Items	Discovery 19 Items	Lateral Movement 15 Items	Collection 13 Items	Exfiltration 9 Items	Command And Control 20 Items
CMSTP	Accessibility Features	Access Token Manipulation	Access Token Manipulation	Account Manipulation	Account Discovery	Application Deployment Software	Audio Capture	Automated Exfiltration	Commonly Used Port
Command-Line Interface	AppCert DLLs	AppCert DLLs	Binary Padding	Brute Force	Application Window Discovery	Automated Collection	Automated Collection	Data Compressed	Communication Through Removable Media
Control Panel Items	Appoint DLLs	Appoint DLLs	BITS Jobs	Credential Dumping	Discovery	Distributed Component Object Model	Clipboard Data	Data Encrypted	Connection Proxy
Dynamic Data Exchange	Application Shimming	AppCert DLLs	Bypass User Account Control	Credentials in Files	Browser Bookmark Discovery	Exploitation of Remote Services	Data from Information Repositories	Data Transfer Size Limits	Custom Command and Control Protocol
Execution through API	Authentication Package	Appoint DLLs	CMSTP	Credentials in Registry	File and Directory Discovery	Logon Scripts	Data from Local System	Exfiltration Over Alternative Protocol	Custom Cryptographic Protocol
Execution through Module Load	BITS Jobs	Application Shimming	Code Signing	Exploitation for Credential Access	Network Service Scanning	Pass the Hash	Data from Network Shared Drive	Exfiltration Over Command and Control Channel	Data Encoding
Exploitation for Client Execution	Bootkit	Bypass User Account Control	Component Firmware	Forced Authentication	Hooking	Pass the Ticket	Data from Removable Media	Exfiltration Over Other Network Medium	Domain Fronting
Graphical User Interface	Browser Extensions	DLL Search Order Hijacking	Component Object Model Hijacking	Input Capture	Network Share Discovery	Remote Desktop Protocol	Data Staged	Exfiltration Over Physical Medium	Fallback Channels
InstallUtil	Change Default File Association	Exploitation for Privilege Escalation	Control Panel Items	Kerberoasting	DCShadow	Remote File Copy	Email Collection	Scheduled Transfer	Multi-hop Proxy
LSASS Driver	Component Firmware	Extra Window Memory Injection	Deobfuscate/Decode Files or Information	LLMNR/NBT-NS Poisoning	Peripheral Device Discovery	Remote Services	Input Capture	Man in the Browser	Multi-Stage Channels
Mshta	Component Object Model Hijacking	File System Permissions Weakness	Disabling Security Tools	Password Filter DLL	Permission Groups Discovery	Replication Through Removable Media	Screen Capture	Screen Capture	Multiband Communication
PowerShell	Create Account	DLL Search Order Hijacking	DLL Search Order Hijacking	Private Keys	Process Discovery	Shared Webroot	Taint Shared Content	Video Capture	Multilayer Encryption
Regsvcs/Regasm	DLL Search Order Hijacking	Hooking	DLL Side-Loading	Replication Through Removable Media	Query Registry	Third-party Software	Windows Admin Shares	Remote Access Tools	Remote File Copy
Regsvr32	External Remote Services	Image File Execution Options Injection	Exploitation for Defense Evasion	Two-Factor Authentication Interception	Remote System Discovery	Security Software Discovery	Windows Remote Management	Standard Application Layer Protocol	Standard Cryptographic Protocol
Rundl32	File System Permissions Weakness	New Service	Extra Window Memory Injection	File Deletion	System Information Discovery	System Network Configuration Discovery	System Network Connections Discovery	System Owner/User Discovery	System Service Discovery
Scheduled Task	Hidden Files and Directories	Path Interception	File System Logical Offsets	Port Monitors	System Information Discovery	System Network Configuration Discovery	System Network Connections Discovery	System Owner/User Discovery	System Service Discovery
Scripting	Hooking	Process Injection	Hidden Files and Directories	Image File Execution Options Injection	System Network Configuration Discovery	System Network Connections Discovery	System Owner/User Discovery	System Service Discovery	System Time Discovery
Service Execution	Hypervisor	Scheduled Task	Image File Execution Options Injection	Indicator Blocking	System Network Configuration Discovery	System Network Connections Discovery	System Owner/User Discovery	System Service Discovery	System Time Discovery
Signed Binary Proxy Execution	Image File Execution Options Injection	Service Registry Permissions Weakness	Indicator Blocking	SID-History Injection	Indicator Removal from Tools	Indicator Removal on Host	Indirect Command Execution	Install Root Certificate	InstallUtil
Signed Script Proxy Execution	Logon Scripts	SID-History Injection	Indicator Removal from Tools	Indicator Removal on Host	Indirect Command Execution	Install Root Certificate	InstallUtil	Masquerading	Modify Registry
Third-party Software	LSASS Driver	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
Trusted Developer Utilities	Modify Existing Service	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
User Execution	Netsh Helper DLL	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
Windows Management Instrumentation	New Service	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
Windows Remote Management	Office Application Startup	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Path Interception	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Port Monitors	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Redundant Access	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Registry Run Keys / Start Folder	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Scheduled Task	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Screensaver	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Security Support Provider	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Service Registry Permissions Weakness	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Shortcut Modification	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	SIP and Trust Provider Hijacking	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	System Firmware	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Time Providers	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Valid Accounts	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Web Shell	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Windows Management Instrumentation Event Subscription	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access
	Winlogon Helper DLL	Valid Accounts	Web Shell	NTFS File Attributes	Obfuscated Files or Information	Process Doppelgänger	Process Hollowing	Process Injection	Redundant Access

Figure 2.4: Detectable attacks with sysmon-modular

3.9.2 Conclusion

Sysmon-modular offers a very good basic configuration for Sysmon based on the platform MITRE ATT&CK which is widely used in the security scene. Unfortunately, sysmon-modular was discovered when decisions were made to develop a tool based on the study "Detecting Lateral Movement through Tracking Event Logs" by JPCERT/CC. The readiness of a system with the basis of MITRE ATT&CK patterns would probably have had an even greater impact. However, Sysmon-modular will most likely not be included in the tool during this study, unless there are still enough time reserves for such an

integration. This tool would better fit the goal to realise a "Readiness Optimizer" as initially mentioned in the task definition.

3.10 CryptoAPI 2.0

3.10.1 Description

The Microsoft feature CryptoAPI 2.0 (CAPI2) Diagnostics provides the ability to collect detailed information about certificate chain validation, certificate store operations and signature verification. CAPI2 is doubt extremely important for any Public Key Infrastructure (PKI) to perform several security based tasks, such as

- Build and verify certificate chains
- Manage per-user and per-computer certificate stores
- Encrypt/decrypt, encode/decode and sign/verify messages

Hence, CAPI2 enables an organisation to secure its communications and business transactions. Identification of users, devices or organisation as well as signed e-mail, code signing and secure web browsing is made possible with today's standards of hash-functions and encryption due to CAPI2. PKI problems are not always easy to troubleshoot and therefore it is necessary to have good diagnostic capabilities in such cases.

CAPI2 Diagnostics in Windows Vista¹ provides logging of detailed information about certificate validation, network retrievals, revocation, and other low-level API results and errors. [...] utilizes the event logging and Event Viewer to provide better logging and troubleshooting capabilities for PKI applications based on the CAPI2 API set. [14]

3.10.2 Conclusion

To detect whether a system is ready for a good detection of lateral movements and APTs, CAPI2 is a core component to be logged in every system and CAPI2 Diagnostics must be enabled on a system. Hence, it is necessary to detect if CAPI2 is enabled on the system. On the other hand, CAPI2 Diagnostics produces a lot of events and therefore the log size should be chosen wisely. For this reason the recommendation of 4 Megabyte (MB) from Microsoft shall be applied. [14]

¹Windows Vista and above

3.11 JPCERT/CC - Detecting Lateral Movement in APTs

3.11.1 Description

This document [15] is from a presentation by Shingo Abe, a JPCERT/CC employee. In it he describes how to find system intruders more effectively using Windows Event Logs. The collected data is used to detect inconsistencies more effectively, such as when an administrator logs on to another machine or when an administrator logs on suspiciously often.

3.11.2 Conclusion

This presentation contains interesting information which could be built into the project at a later point. The information this document contains is more suitable for monitoring purposes than for checking the readiness of a system.

3.12 JPCERT/CC - Detecting Lateral Movement through Tracking Event Logs

3.12.1 Description

This is a document [1] JPCERT/CC published in the year 2017. It describes how, in their experience, attackers proceed with lateral movement. In a very detailed 81-page report they describe the procedure step-by-step, the tools used and, what is most interesting for the project, the logs generated while doing so.

3.12.2 Conclusion

This report will have the biggest impact on this project, it shows which logs have to be read in any case. In addition, JPCERT/CC describes in this report which configurations are necessary for solid logging. The appendix not only describes the individual event log IDs, but also the audit policy that can be used to achieve them. For this reason, the checklist to be used will mainly be based on this report. With the provided information we see the greatest potential to develop a suitable tool for the accomplishment of the task in the given time. The given information of the configuration settings in JPCERT/CCs study appendix must be correlated with the "Advanced security auditing Frequently Asked Questions (FAQ)" [16] in order to define the right auditing settings so that the right events are captured.

4 Design

4.1 Decision for a new Tool

At the beginning it was not clear how the tool should be built exactly and what the functionality and scope should be based on. After a detailed analysis of different tools, reports and studies, it was possible to better estimate how an efficient detection of the readiness of a system can be implemented. It would have been desirable to be able to build on an existing tool, but as shown in a five-week analysis, there is no such tool. For this reason it was decided to develop a tool based on JPCERT/CCs study. The configurations in the Advanced Audit Settings of the GPOs are to be checked accordingly and in a second step the event logs are to be searched for the EventIDs.

4.2 Mandatory Event Logs

The following tables lists the event logs which are mandatory and must be logged based on the study "JPCERT/CC - Detecting Lateral Movement through Tracking Event Logs":

System	
EventID	Description
8222 ²	Shadow copy has been created
20001 ²	Driver Management concluded the process to install driver

Table 2.2: Mandatory System Event Logs

Applications & Service > Microsoft > Windows > TaskScheduler > Operational	
EventID	Description
102 ²	Task completed
106 ²	A task has been registered
129 ²	A task process has been created
200 ²	The operation that has been started
201 ²	The operation has been completed

Table 2.3: Mandatory TaskScheduler Event Logs

Applications & Service > Microsoft > Windows > Windows Remote Management > Operational	
EventID	Description
6 ²	Creating WSMAN Session
169 ²	User authentication authenticated successfully

Table 2.4: Mandatory Windows Remote Management Event Logs

²Recorded by default Windows settings

Applications & Service > Microsoft > Windows > TerminalServices-LocalSessionManager > Operational	
EventID	Description
21 ²	Remote Desktop Services: Session logon succeeded
24 ²	Remote Desktop Services: Session has been disconnected

Table 2.5: Mandatory TerminalServices-LocalSessionManager Event Logs

Applications & Service > Microsoft > Windows > Sysmon > Operational	
EventID	Description
1 ³	Process create
2 ³	A process changed a file creation time
5 ³	Process terminated
8 ³	CreateRemoteThread
9 ³	RawAccessRead: detects when the process is using "\\.\\"

Table 2.6: Mandatory Sysmon Event Logs

Applications & Service > Microsoft > Windows > TaskScheduler > Operational	
EventID	Description
102 ²	Task completed
106 ²	Task registered
129 ²	Created Task Process
200 ²	Action started
201 ²	Action completed

Table 2.7: Mandatory TaskScheduler Event Logs

Applications & Service > Microsoft > Windows > WinRM > Operational	
EventID	Description
6 ²	Creating WSMAN Session
169 ²	User authentication: authenticated successfully

Table 2.8: Mandatory Windows Remote Management Event Logs

Applications & Service > Microsoft > Windows > TerminalServices > LocalSessionManager > Operational	
EventID	Description
21 ²	Remote Desktop Services: Session logon succeeded
24 ²	Remote Desktop Services: Session has been disconnected

Table 2.9: Mandatory Windows Local Session Manager Event Logs

²Recorded by default Windows settings³Recorded by default Sysmon settings

Security	
EventID	Description
104 ²	The System log file was cleared
4624	An account was successfully logged on
4634	An account was logged off
4648	A logon was attempted using explicit credentials
4656	A handle to an object was requested
4658	The handle to an object was closed
4660	An object was deleted
4661	A handle to an object was requested
4663	An attempt was made to access an object
4672	Special privileges assigned to new logon
4673	A privileged service was called
4688	A new process has been created
4689	A process has exited
4690	An attempt was made to duplicate a handle to an object
4720	A user account was created
4726	A user account was deleted
4728	A member was added to a security enabled global group
4729	A member was removed from a security enabled global group
4768	A Kerberos authentication ticket (TGT) was requested
4769	A Kerberos service ticket was requested
4946	A change has been made to Windows Firewall exception list. A rule was added
5140	A network share object was accessed
5142	A network share object was added
5144	A network share object was deleted
5145	A network share object was accessed
5154	WFP has permitted an application or service to listen on a port for incoming connections
5156	WFP has allowed a connection
7036 ²	The service state has changed
7045 ²	A service was installed in the system

Table 2.10: Mandatory Security Event Logs

²Recorded by default Windows settings

4.3 Correlation: Advanced Audit Policy Setting and Event Log IDs

In this section, the "Advanced Audit Policies" required to trigger the corresponding event logs are shown in tables. Based on these tables, the "Advanced Audit Policies" are checked for correctness with the tool. There are several combinations of settings which can be configured:

Not Configured:

Nothing selected

No Auditing:

"Configure the following audit events:"

Success (S):

"Success"

Failure (F):

"Failure"

Success and Failure (S, F):

"Success" and "Failure"




Figure 2.5: Advanced Audit Policy - Logon/Logoff - Audit Special Logon

Account Logon	
Subcategory	EventIDs
Audit Kerberos Authentication Service	4768(S, F)
Audit Kerberos Service Ticket Operations	4769(S, F)

Table 2.11: Advanced Audit Policy Setting Account Logon

Account Management	
Subcategory	EventIDs
Audit User Account Management	4720(S), 4726(S), 4738(S), 4724(S), 4722(S)
Audit Security Group Management	4728(S, F), 4729(S, F), 4737 (S, F)

Table 2.12: Advanced Audit Policy Setting Account Management

Detailed Tracking	
Subcategory	EventIDs
Audit Process Creation	4688(S)
Audit Process Termination	4689(S)

Table 2.13: Advanced Audit Policy Setting Logon/Logoff

Logon/Logoff	
Subcategory	EventIDs
Audit Logon	4624(S), 4648(S)
Audit Logoff	4634(S)
Audit Special Logon	4672(S)

Table 2.14: Advanced Audit Policy Setting Logon/Logoff

Object Access	
Subcategory	EventIDs
Audit Detailed File Share	5145(S, F)
Audit File Share	5140(S, F), 5142(S), 5144(S)
Audit File System	4656(S, F), 4658(S), 4660(S), 4663(S), 4670(S)
Audit Filtering Platform Connection	5154(S), 5156(S), 5447(S, F)
Audit Handle Manipulation	4658(S), 4690(S)
Audit Kernel Object	4656(S, F), 4658(S), 4660(S), 4663(S)
Audit Other Object Access Events	4698(S, F)
Audit Registry	4656(S, F), 4658(S), 4660(S), 4663(S)
Audit SAM	4661(S, F)

Table 2.15: Advanced Audit Policy Setting Object Access

Policy Change	
Subcategory	EventIDs
Audit MPSSVC Rule-Level Policy Change	4946(S)

Table 2.16: Advanced Audit Policy Setting Policy Change

Privilege Use	
Subcategory	EventIDs
Audit Non Sensitive Privilege Use	4673(S, F)
Audit Sensitive Privilege Use	4673(S, F)

Table 2.17: Advanced Audit Policy Setting Privilege Use

4.4 Attack Categories

JPCERT/CC has divided the attack tool examined in their report into several attack categories. When developing the tool, the developers relied on this list:

Attack category	Tools
Command Execution	PsExec WMIC PowerShell Remote Command Execution wmiexec.vbs BeginX WinRM WinRS AT Command BITS
Password Hash Acquisition	PWDump7 PWDumpX Quarks PwDump Mimikatz (Obtaining Password Hash) Mimikatz (Obtaining Ticket) WCE (Windows Credentials Editor) gsecdump lsisass Find-GPOPasswords.ps1 Mail PassView WebBrowserPassView Remote Desktop PassView
Malicious Communication Relay (Packet Tunneling)	Htran Fake wpad
Remote Login	RDP
Pass-the-ticket, Pass-the-hash	WCE (Remote Login) Mimikatz (Remote Login)
Escalation to SYSTEM Privileges	MS14-058 Exploit MS15-078 Exploit
Privilege Escalation	SDB UAC Bypass
Capturing the DomainAdministrator and AccountCredentials	ntdsutil vssadmin
Adding or Deleting a Local User/Group	net user
File Sharing	netuse net share icacls

Capturing Active Directory Database (Creation of Domain Administrator or Addition of a User to Administrator Group)	ntdsutil vssadmin
Deleting Evidence	sdelete timestomp
Deleting Eventlog	wevutil
Acquisition of Account Information	csde ldifde dsquery

Table 2.18: Attack Categories [1]

4.5 Audit Priority

Audit	Prio	Explanation
Audit File System	High	Is needed to be able to detect many attack categories, events are logged when users attempt to access file system objects
Audit Kernel Object	High	Is needed to be able to detect many attack categories, events are logged when a process has exited
Audit Process Creation	High	Is needed to be able to detect many attack categories, events are logged when a process is created (starts)
Audit Process Termination	High	Is needed to be able to detect almost all attack categories, events are logged when users attempt to access the system kernel
Audit Registry	High	Is needed to be able to detect many attack categories, events are logged when attempt was made to access registry objects
Audit Special Logon	High	Events are logged when a member of a "Special Group", that has administrator-equivalent privileges, logs on
Force Audit Policy Subcategory	High	Force audit policy subcategory settings to override audit policy category settings
Sysmon	High	Logs detailed information about process creations, network connections, and changes to file creation time
Audit Detailed File Share	Medium	Events are logged when users attempt to access files and folders on a shared folder
Audit Logon	Medium	Is needed to be able to detect many attack categories, events are logged when a user is logging on to a device
Audit MPSSVCRule-LevelPolicyChange	Medium	Events are logged when changes are made to policy rules for the Microsoft Protection Service
Audit Security Group Management	Medium	Microsoft prioritises this audit setting as "Medium", Events are logged when specific security group management tasks are performed
Audit Sensitive Privilege Use	Medium	Logs events that show the usage of sensitive privileges, for example "Act as part of the operating system"
Audit User Account Management	Medium	Microsoft prioritises this audit setting as "Medium", when specific user account management tasks are performed
Audit File Share	Low	Logs events related to file shares: creation, deletion, modification, and access attempts
Audit Filtering Platform Connection	Low	Events are logged when connections are allowed or blocked by the Windows Filtering Platform
Audit Handle Manipulation	Low	Creates the event " 4658: The handle to an object was closed" in various subcategories and shows duplication and close actions
Audit Kerberos Authentication Service	Low	Logs events for Kerberos authentication ticket-granting ticket requests

Audit Kerberos Service Ticket Operations	Low	Logs security audit events for Kerberos service ticket requests
Audit Logoff	Low	Events are logged when a user is logging off a device
Audit Non Sensitive Privilege Use	Low	Logs events that show usage of non-sensitive privileges, for example "Add workstations to domain"
Audit Other Object Access Events	Low	Monitor operations with scheduled tasks
Audit SAM	Low	Logs events when user attempts to access Security Account Manager objects
CAPI2	Low	Not essential
CAPI2LogSize	Low	Not essential

Table 2.19: Audit Policy Priority [18]

4.6 Domain Analysis

The following section describes the problem domain which is faced during this project. Despite the decision to not programme an object orientated solution, there are several things to be aware of and to think through carefully. For this reason, building a domain model is a simple and suitable technique to use. The following figure 2.6 shows the domain model and will be explained in some details afterwards.




Figure 2.6: Domain Model

4.6.1 Network

The class network depicts the organizations wide network which is used to connect all clients and servers together. In this project the main goal is to locally detect the readiness of the system and not to extend the detection for a system-wide infrastructure. For further development on this project and a system-wide extension, the network is already considered in this domain model.

4.6.2 Computer

A computer illustrates either a client like a Windows 10 machine or a server, in particular, a domain controller running on a Windows Server 2016. In principle, however, every Windows computer is represented. A computer is a core component in our project, because the detection is done on a single client or server.

4.6.3 Event

An event represents a single event log entry in simplified form.

4.6.4 AuditPolicy

AuditPolicy displays the individual settings of the audit policies of the group policy, which can be found via `gpedit.msc` under "Computer Configuration > Windows Settings". However, only the settings under "Security Settings > Advanced Audit Policy Configuration" are considered and not the settings under "Security Settings > Local Policies > Audit Policy". The reason for this is that Microsoft recommends that only one of the two policies is used:

[...] do not use both the basic audit policy settings under Local Policies\Audit Policy and the advanced settings under Security Settings\Advanced Audit Policy Configuration. Using both basic and advanced audit policy settings can cause unexpected results in audit reporting. [16]

A single audit policy setting represents one or more event IDs logged by this configuration.

4.6.5 Reference

ActualList The ActualList represents the current state of the system. It reflects the event log IDs that have occurred and the audit policies that have been set.

TargetList The TargetList represents either the list of event logs or configured audit policies which must be present for a solid detection of attacks.

DeltaList Based on the required lists (audit policies, event logs) as well as the current state of the computer, the DeltaList shows which settings are missing in the audit policies.

5 System Architecture

In this section the following main question is answered:

”What would a system architecture look like to fulfill the described problem domain?”

This includes the coverage of use cases, non-functional requirements, technologies used and how the tool will be designed.

5.1 Use Cases (UC)

A visual representation of the use cases with a use case diagram was deliberately omitted, because there is only one actor involved - the security advisor. The actor is not specifically mentioned in the use cases every time, because it is always the same. During the elaboration phase, it was decided in consultation with the client that the project would be limited to a Readiness Analyser only.

5.1.1 UC01 - Read Resultant Set of Policies

Description

The specified audit policies are read and saved in a temporary file.

Precondition

The system is running and the tool must possess administrator permissions.

Main Success Scenario

1. Read the specified audit policies from the system
2. Save the needed information from the audit policies in a temporary file for analysis purposes.

5.1.2 UC02 - Analyse Audit Policies

Description

The list which was created in UC01 is compared to a ”perfect settings”-list. Missing or wrong settings are going to be exported into a separate file.

Precondition

UC01 is fulfilled: the temporary file is available.

Main Success Scenario

1. The temporary files can be read
2. Creates a list of incorrect settings

5.1.3 UC03 - Find Event Logs

Description

Event logs are searched by ID and marked in an external file as found or missing.

Precondition

The system is running and must have valid event logs. The tool must possess administrator permissions.

Main Success Scenario

1. Search for the specified event logs from the local system
2. Save the result from the search in a temporary file for analysis purposes.

5.1.4 UC04 - Analyse Found Event Logs

Description

The implemented logic analyses, by defined event ids, which events occurred or are missing. Then creates a list of events that did not occur or are not logged yet.

Precondition

UC03 is fulfilled: the temporary file is available.

Main Success Scenario

1. The temporary file can be read
2. The list with the defined event ids is available
3. Create a list of events which occurred and which are missing

5.1.5 UC05 - Display missing or wrong system configuration

Description

Based on the list created in UC02 and UC04 the user gets an overview of missing configurations (the result) which would improve the readiness of the system for a good attack detection.

Precondition

The lists from UC02 and UC04 are available.

Main Success Scenario

1. Displays a visual output of missing or wrong system configurations

5.1.6 UC06 - Save Result to specific path

Description

The actor has the possibility to save the overview from UC05 to a file in a specific path defined by the actor himself. This file contains the result from UC05 in a descriptive way.

Precondition

UC05 is fulfilled: the result, respectively the overview is available

Main Success Scenario

1. A file is saved to a specific path with the result from UC05
2. The path can be defined by the actor

5.1.7 UC07 - Main Script

Description

The actor is able to use the implemented functionalities in an easy way. Therefore the actor requires the script to be used with simple arguments to run the script in its different given modes. More specifically the actor should be faced with the possibility to run the script online (check the current system) and offline (check any system with provided exports). In addition, the actor is able to call a help function of the script to get more information about the script itself and how to use it.

Precondition

All functions and process flows have to be implemented and defined.

Main Success Scenario

1. The actor can call all functionalities just through the main script with appropriate arguments
2. The actor can call a helper function to get information how the script is supposed to use

5.1.8 UC08 - Get Domain Information

Description

The actor has the possibility to gather information about single or all domain group policies. This information should be processed and analyzed in the same way as the local gathered data.

Precondition

Access to SYSVOL is possible.

Main Success Scenario

1. The actor gets a result about the readiness of domain group policies which are of interest.

5.2 Non Functional Requirements

NFR-No.	Description
NRF01	After using the Toolkit the system must remain in the status quo. More specifically, the system shall not deliberately alter any existing entry in the event logs and registry. However, the tool may produce new event logs.
NFR02	The user shall not notice significant performance degradation from the system when using the Toolkit.
NFR03	The Toolkit must be portable with no installation procedure before use.
NFR04	The minimal target version of the system for the Toolkit to run must be Microsoft Windows 10 Professional or Microsoft Server 2016.
NFR05	The Toolkit runs in one go, but can also be executed in single steps with the possibility to skip single steps (pause/abort in case of performance problems)

Table 2.20: Non Functional Requirements

5.3 Technologies

5.3.1 Chosen Technologies

PowerShell & Visual Studio Code

The decision as to which technology to use, was made in favour of PowerShell. The reason why PowerShell was used, was that it is close to the Microsoft Operating System and that it has a large and detailed documentation at its disposal.

The scripts are written in Visual Studio Code with the extension packet "PowerShell". Visual Studio code is preferred to PowerShell Integrated Scripting Environment (PowerShell ISE) because it only requires working in one Integrated Development Environment (IDE) for implementation and documentation.

LaTeX & Visual Studio Code

The documentation is written with LaTeX in Visual Studio Code with the LaTeX Workshop extension. The main reason for LaTeX was that the developers are already familiar with it. Furthermore, LaTeX offers a very simple way for referencing sources. On the other hand, we made the experience that with LaTeX the formatting is more reliable than for example when Microsoft Word is used.

Azure Cloud

The test environment is set up, as described in section 2 "Test environment", in the azure cloud. One server and two clients form a virtual network, this enables developers to access it from anywhere to any given time. A disadvantage is the changing public IP-addresses to access the VMs. In the end, the advantages outweigh the disadvantages.

GitHub

GitHub is used as a version control tool for source code and documentation. GitHub has been elected because of its good reputation and the experience the developers already gained with.

Continuous Integration

Continuous Integration (CI) for Powershell is unfortunately not very widespread as has been shown after some time of research. Fortunately, the article "Converting a PowerShell Project to use Azure DevOps Pipelines" [19] by Daniel Scott-Raynsford was found, which describes in detail how a CI environment can be set up in Microsoft Azure DevOps. Due to the fact that Azure DevOps offers a very simple and clear handling, as well as supports all common operating systems (Linux, Windows and MacOS), it was decided to set up the CI environment in Azure DevOps. The structure and the important findings are described in the Continuous Integration manual.

5.3.2 Rejected Technologies

Python

The decision to use PowerShell and maybe C# for a GUI instead of Python was made because the developers do not have much experience with Python. Also PowerShell is closer to the Microsoft operating system. With Python there is no guarantee that the libraries which would be used are as powerful to solve the requirements.

5.4 Sequence Diagram

This section describes the process of the toolkit and explain the individual steps in detail. As mentioned in the Use Cases, the actor of this toolkit will be a security advisor, who will execute the toolkit.




Figure 2.7: Sequence Diagram SystemReadinessInspector - SRI

5.4.1 GetAuditPolicy()

This task is responsible to get all Audit Policies, which are relevant for logging the right events according to JPCERT/CCs study. To gather all information about the Audit Policies and the current state of its configuration the Resultant Set of Policies (RSoP) must be read. [20] RSoP is a Microsoft snap-in to create a detailed report about the applied policy settings.

5.4.2 AnalyseAuditPolicy()

In this task the RSoP from the task GetAuditPolicy(), which is represented as a XML-File, is going to be analysed and all values of the defined audit settings are gathered and written as a result of this analysis, stored in a XML-based format in a temporary file.

5.4.3 GetEventLog()

This task is responsible for getting the event logs from the system. Therefore the command **Get-EventLogs** [21] retrieves all logs from 'System' and 'Security'. With the command **wevutil** the 'Application and Service'-Logs are read out. These logs are, to be analysed later, saved as a 'CSV' file to the current path where the PowerShell is running.

5.4.4 AnalyseEvents()

In this task the created command-separated values file (CSV) from GetEventLog() is used to analyse the collected logs. They are compared to a list provided by JPCERT/CC to find out if these events already occurred. The result of this comparison will be stored as a 'XML' file in order to visualise it.

5.5 VisualiseResults()

The resulting XML-files from `AnalyseEvents()` and `AnalyseAuditPolicy()` are gathered and compared with a checklist, which is based on the recommendation from JPCERT/CCs study (see 3.12 JPCERT/CC - Detecting Lateral Movement through Tracking Event Logs). Incorrect or missing configuration is highlighted in red, correct configurations in green. The event logs are listed as missing or present.

6 Implementation

This sections shows the implementation of the logic. Divided according to the script and its activities, the results of the script are shown first. The second part describes the approach which was taken, which ideas were not implemented and why not. In the third part, the implementation part, the used code is described and explained.

6.1 Module: GetAndAnalyseAuditPolicies

The basic idea was to implement the use case "UC01 - Read Resultant Set of Policies" separately from the use case "UC02 - Analyse Audit Policies". However, during the implementation it quickly became clear that these two use cases could be merged and did not have to be implemented separately. Therefore, both use cases were integrated into one script module. The following, describes how the two use cases were implemented.

6.1.1 Result

The script follows the following schedule in the probably most often used **-Online Mode**:

- Reading and caching of the RSoP which includes the audit settings
- Compare the audit settings from the RSoP with the target list so that all defined audit policies are in place
- Get all value of the defined audit policies for further analysis
- Check if "Audit: Force audit policy subcategory settings (Windows Vista or later) to override audit policy category settings" is enabled in registry to prevent conflicts between security settings
- Check if Sysmon is installed and running as a service
- Check whether CAPI2 is enabled and its log size is appropriate (> 4MB)

Each result of the individual steps is collected in hashtables and merged together to be exported to a XML file. Finally, the environment and files that are no longer needed are deleted, so that only the result XML is available for further processing. A result could possibly look like the following listing:

Listing 2.4: Example Result Audit Policy Analysis

```

1 <?xml version="1.0" encoding="utf-8"?>
2 <AuditPolicies>
3   <AuditNonSensitivePrivilegeUse>NotConfigured</AuditNonSensitivePrivilegeUse>
4   <AuditOtherObjectAccessEvents>NotConfigured</AuditOtherObjectAccessEvents>
5   <AuditUserAccountManagement>NotConfigured</AuditUserAccountManagement>
6   <AuditKernelObject>NotConfigured</AuditKernelObject>
7   <AuditSAM>NotConfigured</AuditSAM>
8   <AuditKerberosAuthenticationService>NotConfigured</AuditKerberosAuthenticationService>
9   <AuditHandleManipulation>NotConfigured</AuditHandleManipulation>
10  <AuditRegistry>NotConfigured</AuditRegistry>
11  <AuditProcessTermination>NotConfigured</AuditProcessTermination>
12  <AuditFileSystem>NotConfigured</AuditFileSystem>
13  <AuditMPSSVCRule-LevelPolicyChange>NotConfigured</AuditMPSSVCRule-LevelPolicyChange>
14  <AuditSpecialLogon>NotConfigured</AuditSpecialLogon>
15  <AuditFileShare>NotConfigured</AuditFileShare>
16  <AuditLogoff>NotConfigured</AuditLogoff>
17  <AuditDetailedFileShare>NotConfigured</AuditDetailedFileShare>
18  <AuditSensitivePrivilegeUse>NotConfigured</AuditSensitivePrivilegeUse>

```


6. Implementation

```

19 <AuditLogon>NotConfigured</AuditLogon>
20 <AuditFilteringPlatformConnection>NotConfigured</AuditFilteringPlatformConnection>
21 <AuditProcessCreation>NotConfigured</AuditProcessCreation>
22 <ForceAuditPolicySubcategory>Enabled</ForceAuditPolicySubcategory>
23 <Sysmon>InstalledAndRunning</Sysmon>
24 <CAPI2LogSize>4194304</CAPI2LogSize>
25 <CAPI2>EnabledGoodLogSize</CAPI2>
26 </AuditPolicies>

```

6.1.2 Approach

Read Resultant Set of Policies

Research was carried out to read the corresponding audit policy configurations from the system. At the beginning, the approach was to read the required configurations using the command `auditpol`. [22] This command can be used to read out and manipulate the currently valid information on the audit policies. However, the manipulation of the audit policies is not necessary within the tool and can be ignored. The command provides exactly the information needed to fulfill this use case:

Listing 2.5: auditpol

```

1 PS C:\Windows\system32> auditpol /get /category:Logon/Logoff
2 System audit policy
3 Category/Subcategory          Setting
4 Logon/Logoff
5   Logon                       Success and Failure
6   Logoff                      Success and Failure
7   Account Lockout             No Auditing
8   IPsec Main Mode             No Auditing
9   IPsec Quick Mode            No Auditing
10  IPsec Extended Mode          No Auditing
11  Special Logon                Success and Failure
12  Other Logon/Logoff Events    No Auditing
13  Network Policy Server        No Auditing
14  User / Device Claims         No Auditing
15  Group Membership             No Auditing

```

Unfortunately, this output is not very ideal for a suitable further processing and analysis of the current configuration. The return value of the command is an ordinary array filled with corresponding strings and, therefore, the complete array should have been checked for correct content by string comparisons. Furthermore, the command `auditpol` does not offer the possibility of remote configuration with regard to an extension of the tool to a whole fleet of computers. For this reason, the idea of building the tool on the basis of this command was rejected.

Further research has shown that Microsoft provides a RSoP [20] for reading audit policies. This can also be accessed via a PowerShell command. Microsoft offers the command `Get-GPResultantSetOfPolicy` [23] for this purpose. This command can be used to generate an XML-based report of the currently valid GPOs. Since traversing an XML-based file via PowerShell proves to be very simple, this variant is preferable to the `auditpol` command. After a short test, it quickly became clear that the generated XML provides all necessary information for the further analysis. Unfortunately, the `Get-GPResultantSetOfPolicy` command is not available by default on all systems. However, this command is used and the missing Module: "GroupPolicy", which is used to activate the command, will be prerequisite for the script. [24] [25]

Analyse Audit Policies

The current configuration of the system's audit policies is then to be evaluated from the temporarily

cached file. The basis for this provides section "4.3 Correlation: Advanced Audit Policy Setting and Event Log IDs" based on "3.12 JPCERT/CC - Detecting Lateral Movement through Tracking Event Logs".

6. Implementation

6.1.3 Implementation

This section describes the implementation of **GetAndCheckAuditPolicies** in detail. For this purpose, the following is referred to in section 6.1.1 Result described schedule. This section is focusing on the **-Online** mode but will also cover the other functions which are implemented for a domain based system check.

To read the RSoP from the local/current system the command **Get-GPResultantSetOfPolicy** is used. The XML that is retrieved is then temporarily cached in the execution path of the script and read in again for further processing. The temporarily cached XML will then be removed.

Listing 2.6: Get-GPResultantSetOfPolicy

```

1 try {
2     Get-GPResultantSetOfPolicy -ReportType Xml -Path $PathRSoPXML | Out-Null
3 }
4 catch {
5     Write-Host "Necessary Module: ''GroupPolicy'' is not provided
6         within this system" -ForegroundColor Red
7     return
8 }
9
10 if ([System.IO.File]::Exists($PathRSoPXML)) {
11     [xml]$RSoPResult = Get-Content $PathRSoPXML
12 }

```

The generated XML (RSoP) is an extraction of the GPOs and contains only the configurations set from them. Afterwards the analysis begins and the entries are searched in the XML file, in which the required configurations for the "Advanced Audit Policies" are stored (see figure 2.8).




Figure 2.8: GPO - Advanced Audit Policies

The function **CompareToTargetList** searches for missing audit settings. It iterates over the queried **AuditSettings** and searches for missing configurations. Any missing setting will be written in a hashtable **result** for further processing.

Listing 2.7: CompareToTargetList: Search missing configurations

```

1 Function CompareToTargetList ([Hashtable] $AuditSettings, [Array] $TargetAuditSettings) {
2     $Result = @{}
3     foreach ($TargetAuditSetting in $TargetAuditSettings) {
4         if ($AuditSettings.keys -notcontains $TargetAuditSetting) {
5             $Result.Add(($TargetAuditSetting -replace (" ")), "NotConfigured")
6         }
7     }
8     return $Result
9 }

```

After checking for missing configurations, all values of the set settings are gathered for further processing.

Listing 2.8: GetAuditSettingValues: Get configured audit settings from RSoP

```

1 foreach ($AuditSetting in $AuditSettings.GetEnumerator()) {
2     if ($TargetAuditSettings -notcontains $AuditSetting.Name) {
3         continue
4     }
5     if ($AuditSetting.Value -and $AuditSetting.Name) {
6         try {
7             $AuditSettingValue = $AuditSetting.Value
8         }
9         catch {
10            $AuditSettingValue = 0
11        }
12        $AuditSubcategoryName = $AuditSetting.Name
13        switch ($AuditSettingValue) {
14            NoAuditing {
15                $AuditSettingValueString = "NoAuditing"
16                continue
17            }
18            Success {
19                $AuditSettingValueString = "Success"
20                continue
21            }
22            Failure {
23                $AuditSettingValueString = "Failure"
24                continue
25            }
26            SuccessAndFailure {
27                $AuditSettingValueString = "SuccessAndFailure"
28                continue
29            }
30            Default { continue }
31        }
32        $Result.Add(($AuditSubcategoryName -replace (" ")), $AuditSettingValueString)
33    }
34 }

```

After gathering of the values, the next step is to verify if the setting "Audit: Force audit policy subcategory settings (Windows Vista or later) to override audit policy category settings" is enabled as considered in section "4.6.4 AuditPolicy". This had to be solved via the registry, because this information is not available in the RSoP.

Listing 2.9: GetRegistryValue

```

1 Function GetRegistryValue([String] $Path, [String] $Name) {
2     return Get-ItemProperty -Path $Path -Name $Name -ErrorAction Stop
3 }

```

The registry entry is captured in a separate function to provide the possibility for tests. This function is called with the following parameter [26] to get the searched registry entry:

```

1 $Path = "HKLM:\System\CurrentControlSet\Control\Lsa"
2 $Name = "SCENoApplyLegacyAuditPolicy"

```

Listing 2.10: Function IsForceAuditPolicyEnabled

```

1 Function IsForceAuditPolicyEnabled ([Object] $AuditPolicySubcategoryKey) {
2     $result = @{}
3
4     if ($auditPolicySubcategoryKey) {
5         if ($auditPolicySubcategoryKey.SCENoApplyLegacyAuditPolicy -eq 1) {
6             $result.Add("ForceAuditPolicySubcategory", "Enabled")
7             return $result
8         }
9         else {
10            $result.Add("ForceAuditPolicySubcategory", "Disabled")
11            return $result
12        }
13    }
14    else {
15        $result.Add("ForceAuditPolicySubcategory", "NotDefined")
16        return $result
17    }
18 }

```

The next step is to check if Sysmon as a service is installed (also not contained in the RSOP) and, if so, is it running or not. Since a service can be renamed to hide it from the bad guys, the **Get-Service** command cannot make a 100% statement about whether the service is actually installed. For this reason the description of the service is queried, which does not change while renaming. [10]

Listing 2.11: Function IsSysmonInstalled

```

1 Function IsSysmonInstalled {
2     $Service = Get-WmiObject win32_service -Filter "Description = 'System Monitor
3         service'"
4     $Result = @{}
5
6     if ($Service) {
7         if ($Service.State -ne "Running") {
8             $Result.Add("Sysmon", "InstalledNotRunning")
9             return $Result
10        }
11        else {
12            $Result.Add("Sysmon", "InstalledAndRunning")
13            return $Result
14        }
15    }
16    else {
17        $Result.Add("Sysmon", "NotInstalled")
18        return $Result
19    }
20 }

```

6. Implementation

As a last step, the online mode is checking whether CAPI2 is enabled and has the right minimum log size of 4MB. The decision for 4MB is mentioned in the section "3.10 CryptoAPI 2.0". Unfortunately, this information is also not available via the RSoP. Therefore, the command `wevtutil` is used to query CAPI2 in the event log. The reason for this is that CAPI2 can only be enabled via the Event Viewer. [14] In order to enable testing here as well, a Get function for the event log entry has been created.

Listing 2.12: Function GetCAPI2

```

1 Function GetCAPI2 {
2     return [xml](wevtutil gl Microsoft-Windows-CAPI2/Operational /f:xml)
3 }

```

The log size is stored in the Windows system as mebibyte (MiB). This is the reason for defining the initial log size to **4194304**. The following conversion from 4 MB to mebibyte should make it clear:

$$4 \text{ MB} = 4 \cdot 1024 \cdot 1024 \text{ BYTES} = 4194304 \text{ BYTES}$$

Listing 2.13: Function IsCAPI2Enabled

```

1 Function IsCAPI2Enabled([xml] $capi2, [uint32] $requiredLogSize) {
2     $capi2Enabled = $capi2.channel.enabled
3     $currentLogSize = $capi2.channel.logging.maxsize -as [uint32]
4     $result = @{}
5
6     if ($requiredLogSize -lt 4194304) {
7         $requiredLogSize = 4194304
8     }
9
10    if ($capi2Enabled -eq "true" -and $currentLogSize -ge $requiredLogSize) {
11        $result.Add("CAPI2", "EnabledGoodLogSize")
12        $result.Add("CAPI2LogSize", "$currentLogSize")
13    }
14    elseif ($capi2Enabled -eq "true" -and $currentLogSize -lt $requiredLogSize) {
15        $result.Add("CAPI2", "EnabledBadLogSize")
16        $result.Add("CAPI2LogSize", "$currentLogSize")
17    }
18    else {
19        $result.Add("CAPI2", "Disabled")
20    }
21    return $result
22 }

```

All temporary files are removed at the end of this script.

6. Implementation

To fulfill UC08 - Get Domain Information (see section 5.1.8) two functions were created to gather the advanced audit settings from group policies. One for gathering information about a specific group policy (**GetDomainAuditPolicy**) and the other for all group policies (**GetAllDomainAuditPolicies**). To achieve this, the information is gathered from the System Volume (SYSVOL) where all group policies remain in an active directory network. The audit settings of each group policy, remaining in SYSVOL, are stored as a CSV. This CSV is imported and each setting is gathered for further analysis. Like within the online mode, after doing so the hashtable is returned and filled with the missing audit settings.

Listing 2.14: Function GetDomainAuditPolicy

```

1 Function GetDomainAuditPolicy ([String] $PolicyName) {
2     $PolicyCSV = CheckDomainAndPolicy $PolicyName
3
4     if ([System.IO.File]::Exists($PolicyCSV)) {
5         Write-Host "Get audit settings from group policy: '$PolicyName'"
6         $AuditSettings = @{}
7         $Policy = Import-Csv $PolicyCSV -Encoding UTF8
8
9         foreach ($Element in $Policy) {
10             $AuditSettings.Add(($Element.Subcategory -replace (" ")), $Element."Setting
              Value")
11         }
12         return $AuditSettings
13     } else {
14         Write-Host "For this Group Policy exist no auditing definition"
15         return
16     }
17 }
```

To analyse all group policies the function **GetDomainAuditPolicy** is called for each group policy and a hashtable, with the name of the group policy as the key and the settings as the value, is filled and returned.

Listing 2.15: Function GetAllDomainAuditPolicies

```

1 Function GetAllDomainAuditPolicies {
2     try {
3         $GPOs = Get-GPO -all | Select-Object DisplayName, Id
4     }
5     catch {
6         Write-Host "Your system is not associated with an Active Directory domain or
              forest"
7         return
8     }
9
10    $AuditSettingsPerPolicy = @{}
11    $AuditSettings = @{}
12
13    foreach ($GPO in $GPOs) {
14        $AuditSettings = GetDomainAuditPolicy $GPO.DisplayName
15        $AuditSettingsPerPolicy.Add($GPO.DisplayName, $AuditSettings)
16    }
17
18    return $AuditSettingsPerPolicy
19 }
```

6. Implementation

In addition to capture all audit settings of the group policies, the setting "Audit: Force audit policy subcategory settings (Windows Vista or later) to override audit policy category settings" is captured as well. If this setting is enabled in the group policy, it will remain in `GptTmpl.inf` in `SecEdit` in the `SYSVOL`-path of each policy.

Listing 2.16: Function `IsForceAuditPolicyDomainEnabled`

```

1 Function IsForceAuditPolicyDomainEnabled ([String] $PolicyName) {
2     $Domain = Get-WmiObject Win32_ComputerSystem -ComputerName "localhost"
3         | Select-Object -ExpandProperty Domain
4
5     $PolicyId = Get-GPO -Name $PolicyName | Select-Object -ExpandProperty id
6
7     $SecEditPath = "\\$Domain\SYSVOL\$Domain\...\Windows NT\SecEdit\GptTmpl.inf"
8     $ForceAuditPolicyEnabled = "MACHINE\...\SCENoApplyLegacyAuditPolicy=4,1"
9     $ForceAuditPolicyDisabled = "MACHINE\...\SCENoApplyLegacyAuditPolicy=4,0"
10    $AuditSettings = @{}
11
12    if (Test-Path $SecEditPath) {
13        $RegistryKeyValue = Get-Content $SecEditPath
14
15        if ($RegistryKeyValue -contains $ForceAuditPolicyEnabled) {
16            $AuditSettings.Add("ForceAuditPolicySubcategory", "Enabled")
17        } elseif ($RegistryKeyValue -contains $ForceAuditPolicyDisabled) {
18            $AuditSettings.Add("ForceAuditPolicySubcategory", "Disabled")
19        } else {
20            $AuditSettings.Add("ForceAuditPolicySubcategory", "NotDefined")
21        }
22    }
23    return $AuditSettings
24 }

```

6. Implementation

6.2 Module: GetAndCompareLogs

This section describes the implementation of the "UC03 - Find Event Logs" as well as "UC04 - Analyse Found Event Logs". Both use cases were fulfilled in the PowerShell script "GetAndCompareLogs". Here is a description how the use cases were implemented.

6.2.1 Result

The script "GetAndCompareLogs", where both use cases were implemented, runs as follows:

- Reading and caching the Event Logs "System" & "Security"
- Filter cached Logs by EventID, group EventIDs that occur more than once. Found EventIDs are exported as "CSV"
- Checking and caching whether a list of EventIDs from "Application and Service" Logs can be read out
- Export result set of found EventIDs as "CSV"
- Import list of found Event Logs and compare it with the predefined checklist
- Result of the comparison is written into an "XML" file
- Import and compare found Application and Service Logs with predefined checklist
- Result of the comparison is written into the same "XML" as before

The now no longer needed CSV files are deleted. The XML with the result set is now available for any further processing. A result could possibly look like the following listing:

Listing 2.17: Example Result Audit Policy Analysis

```

1  <?xml version="1.0"?>
2  <Logs>
3    <EventLogsID>
4      <6>present</6>
5      <21>missing</21>
6      <24>missing</24>
7      <102>missing</102>
8      <104>missing</104>
9      <106>missing</106>
10     <201>missing</201>
11     <4624>present</4624>
12     <4634>present</4634>
13     <4648>present</4648>
14     <4656>present</4656>
15     ...
16   </EventLogsID>
17   <AppAndServID>
18     <106>present</106>
19     <200>present</200>
20     <129>present</129>
21     <201>present</201>
22     <102>present</102>
23     <6>missing</6>
24     <169>missing</169>
25     <21>present</21>
26     <24>present</24>
27   </AppAndServID>
28 </Logs>

```

6.2.2 Approach

Get Event Logs

After research was done on how to read out the Event Logs "System" and "Security" the decision was made to use the PowerShell command `Get-EventLog` [21]. This command allows to read out the whole EventLog by the LogName or also to search after a specific EventID. The first approach was to search for each EventID individually. The EventIDs to search for were taken from the JPCERT/CC Appendix B in the "Detecting Lateral Movement through Tracking Event Logs" report. [1]. The script ran successfully, but the runtime was not practicable. It took over 5 minutes to search for all EventIDs in an Event Log of the size of about 37 000 Logs, or in other words 300 Kilobyte (KB). The developers then started to calculate the worst case scenario, in this case the worst case scenario is that none of the searched EventIDs is found in the EventLog. There are n EventIDs in the checklist and m entries in the EventLogs, if no EventID is found, every entry is called m times. That results in $O(n*m)$. The developers decided to cache the Event Logs, reducing the runtime to $O(m)$. The cached Logs are then grouped into EventIDs and export into a "CSV" file.

To read out the "Application and Service" Logs we can not use `Get-EventLog`. The first approach used the `Get-WinEvent` [27] command. The logic stayed the same, read out all events, group and export them into a 'CSV' file. Unfortunately the `Get-WinEvent` is very slow, it took over 10 minutes to read out just under 6000 logs. The developers found an other, much quicker command called `wevtutil` [28]. Unfortunately it is not quite simple to read out all Logs, for that reason each EventID will be searched if it appeared. Unlike `Get-EventLog`, this is not a problem because the command is faster, the EventIDs are more likely to occur and the amount of Logs is smaller. On the testing environment with a machine with 4 Gigabyte (GB) Ram and an Intel Xeon E5 with 2 cores it took about 10 seconds to check for 9 EventIDs in 15 000 Log entries. If an EventID was found it was added to an `ArrayList`, after all IDs are checked the file is exported as a 'CSV'.

Analyse Found Event Logs

To analyse the occurred EventIDs the two generated "CSV" files are imported into the PowerShell script. The respective checklists, which are based on the JPCERT/CC - Detecting Lateral Movement through Tracking Event Logs, are embedded in the script. Each id from the checklist is checked if it is present in the respective CSV file. If this is the case, the id is added to the XML-file and marked as present. If the id did not occur in the it will be added and marked as missing. The file looks like the example in "Result" shown.

6.2.3 Implementation

This section describes the implementation of **GetAndCompareLogs** in detail. For this purpose, the following is referred to in the section "6.2.1 Result" described schedule.

The first step is to read out the "System" and "Security" Logs. To achieve this goal the command **Get-EventLog** is used in the first part of the function **GetEventLogsAndExport**.

Note The code has been adapted for better readability and easier understanding

Listing 2.18: Function GetEventLogsAndExport Part 1

```

1  $logNames = @("System", "Security")
2  $eventLogs = New-Object System.Collections.ArrayList
3
4  Function GetEventLogsAndExport{
5      foreach($log in $logNames){
6          $eventLogs += Get-EventLog -LogName $log
7      }
8      ...

```

The second part of the function filters the EventIDs from the chaced logs. Subsequently, multiple EventIDs are grouped together.

Listing 2.19: Function GetEventLogsAndExport Part 2

```

1  $currentFolder = (Resolve-Path .\).Path
2  $exportEventLogsIntoCSV=$currentFolder + "\myeventlogs.csv"
3
4  $eventLogs| Select EventID -Unique |Export-CSV $exportEventLogsIntoCSV -NoTypeInfo
   -Encoding UTF8
5  }

```

After the export the function **GetApplicationAndServiceLogs** is called. As before, the function is divided into two parts, first how to get the data. The same procedure is used three times, for the "TaskScheduler", "WindowsRemoteManagement" and "LocalSessionManager". Due to the fact that the code is very similarly it is only shown once. To search for the EventIDs **wevtutil** is used.

Listing 2.20: Function GetApplicationAndServiceLogs Part 1

```

1  $appAndServLogs = New-Object System.Collections.ArrayList
2  $idsForTaskScheduler = ("106", "200", "129", "201", ...)
3
4  $appAndServLogs += "EventID"
5
6  Function GetApplicationAndServiceLogs{
7
8      foreach($id in $idsForTaskScheduler){
9          if(wevtutil qe Microsoft-Windows-TaskScheduler/Operational
              /q:"*[System[(EventID="$id" )]]" /uni:false /f:text){
10             $appAndServLogs += $id
11             }
12         }
13     ...

```

6. Implementation

After all three Logs were checked and all found EventIDs were added, the information is exported into a "CSV"-file.

Listing 2.21: Function GetApplicationAndServiceLogs Part 2

```

1  $exportApplicationAndServiceLogsIntoCSV = $currentFolder +
    "\myapplicationandservicelogs.csv"
2
3  $appAndServLogs | Out-File -FilePath $exportApplicationAndServiceLogsIntoCSV
4  }
```

The next point on the list is importing the found "EventLogs" and "Service And Application" Logs. Due to the similarity we only show one code.

Listing 2.22: Function ImportCompareExport

```

1  $eventLogIdsToCheck = (6, 21, 24, 102, 104, 106, 129, ...
2
3  # Create XML "resultOfEventLogs.xml"
4
5
6  $importEventLogs = $exportEventLogsIntoCSV
7  $myEventLogs = Import-Csv $importEventLogs -Encoding UTF8
8
9  Function ImportCompareExport{
10     foreach($id in $eventLogIdsToCheck){
11         if($myEventLogs | where {$_.EventID -eq $id}){
12             # Write to XML with value "present"
13         }
14         else{
15             # Write to XML with value "missing"
16         }
17     }
18 }
19 # Close XML
```

The same happens with the "App and Service" Logs in the `GetApplicationAndServiceLogs` function. All temporary files are removed at the end of this script.

6. Implementation

6.3 Module: Visualize

In this script the "UC05 - Display missing or wrong system configuration" is implemented here the description how it was done.

6.3.1 Result

The script "UC05 - Display missing or wrong system configuration" runs as follows:

- Create Portable Document Format (PDF) at given folder and "open" it
- Import audit policies and compare them to a given checklist, result is written and visualized in a table
- Check which attack tool categories can be detected with the current audit guidelines and which cannot
- Import the found EventLogs and check if the important EventIDs, according to JPCERT/CC, are found
- "Close" PDF-document

The resulting PDF looks something like this:

AuditPolicies

Audit Name	Target	Actual	Prio
AuditNonSensitivePrivilege	SuccessAndFailure	SuccessAndFailure	High
AuditProcessTermination	Success	SuccessAndFailure	Medium
AuditSAM	SuccessAndFailure	Not Configured	Low
...	

With this policies it is possible to detect X out of 14 attack categories

The following attack categories cannot be detected with certainty:

...

WindowsLogs

EventID6	present
EventID104	missing
...	...

6.3.2 Approach

At first, the developers considered using "PowerBI" [29], like Jessica Payne uses it in "WEFFELS". But after a short trial they decided that the tool was too overpowered for their purpose. Also, they did not like that the user would have to install a third-party tool to analyse his data. The Dynamic Link Library (DLL) "iTextSharp", originally a C# library, allows to generate a PDF directly from the code, which can also be used in PowerShell. This variant is not very versatile and it is difficult to create an appealing design, but it is enough for now.

6.3.3 Implementation

This section describes the implementation of **Display missing or wrong system configuration** in detail. For this purpose, the following is referred to in section "6.3.1 Result" described schedule.

The iTextSharp.dll and the functions from **PowerShell-PDF** [30] were imported. The first step is to create a PDF-document and "open" it. For this purpose the function **OpenPDF** was created:

Listing 2.23: Function OpenPDF

```

1 function OpenPDF{
2     $pdf = New-Object iTextSharp.text.Document
3     New-PDF -Document $pdf -File #export path
4     $pdf.Open()
5 }

```

The function **WriteAuditPolicies** then compares the found audit policies and display the ones who are incorrectly. It will call two other functions, **CreateAddCellWithColor** and **CreateAddCell**.

Listing 2.24: Functions WriteAuditPolicies & CreateAddCellWithColor & CreateAddCell

```

1 function WriteAuditPolicies{
2     $auditChecklist = @({AuditLogon = @("Success", "Medium"; ...)})
3     $incorrectAudits = @() # will be returned for later use
4     [xml] auditXml = Get-Content $auditPath
5     $myAudits = $auditXml.AuditPolicies.ChildNodes
6     foreach ($audit in $myAudits) {
7         $localName = $audit.LocalName
8         CreateAddCell $localName # Display auditname into cell
9
10        $checkaudit = $auditChecklist[$localName]
11        $checkauditvalue = $checkaudit[0] # Correct setting
12        $checkauditprio = $checkaudit[1] # Priority of audit
13
14        if ($audit.InnerXml -eq $checkauditvalue) { # Checks if audit values are equal
15            CreateAddCell $checkauditvalue # Displays correct audit value
16            CreateAddCellWithColor $audit.InnerXml 0 255 0
17            # Displays actual audit value into cell, color green
18        }
19        elseif ($audit.InnerXml.startswith("Succ") #checks if audit is ''overpowered''
20        -and $checkauditvalue -eq "Success") {
21            CreateAddCell $checkauditvalue # Displays correct audit value
22            CreateAddCellWithColor $audit.InnerXml 0 106 0
23            # Displays actual audit value into cell, color darkgreen
24        }
25        else { #audit is wrong
26            CreateAddCell $checkauditvalue # Displays correct audit value
27            CreateAddCellWithColor $audit.InnerXml 255 0 0
28            #Displays actual audit value into cell, color red
29            $incorrectAudits += $audit.LocalName
30        }
31        CreateAddCell $checkauditprio # Displays audit priority into cell
32    }
33    return $incorrectAudits
34 }
35
36
37
38
39
40

```

```

41 function CreateAddCellWithColor($content, $R, $G, $B) {
42     # Create iTextSharp.text.Paragraph and add content
43     # Create iTextSharp.text.pdf.PdfPCell with paragraph and set backgroundcolor $R $G $B
44     # Add Cell to Table
45 }
46
47 function CreateAddCell($content) {
48     # Create iTextSharp.text.Paragraph and add content
49     # Create iTextSharp.text.pdf.PdfPCell with paragraph
50     # Add Cell to Table
51 }

```

Now that the "Import audit policies and compare them to a given checklist, result is written and visualized in a table" is done, it is possible to check which attack tool categories can be detected with the current audit settings. For that purpose, the function **ToolsCanBeDetected** was created. This function relies on the return of the **\$incorrectAudits**.

Listing 2.25: Function ToolsCanBeDetected

```

1  function ToolsCanBeDetected($incorrectAudits){
2      [xml] $auditsByCategorie = Get-Content "$PSScriptRoot\AuditByCategorie.xml"
3      $notDetectableCategories = @()
4      $causingAudit = @()
5
6      $Categories = $auditsByCategorie.Category.ChildNodes
7      foreach ($Category in $Categories) {
8          [int]$checknr = 0
9          foreach ($incorrectAudit in $incorrectAudits) {
10             if ($Category.ChildNodes.InnerXml -contains $incorrectAudit) {
11                 $checknr += 1
12                 $causingAudit += $incorrectAudit
13             }
14         }
15
16         if ($checknr -gt 0) {
17             $notDetectableCategories += $Category.LocalName + "(" + $causingAudit + ")"
18         }
19
20         # Output of the not detectable categories and the causing audits
21     }

```

The next step is to display the found EventLogs and if they are missing or present. Therefore two tables, one for the WindowsLogs and one for the Application And Service Logs, are created. Because these two tables are created the same way, only one case is shown. Hence, the function **WriteEventLogs** was created.

Listing 2.26: Function WriteEventLogs

```

1  function WriteEventLogs {
2      [xml] $eventxml = Get-Content # importPath
3      # Add Title
4      $eventsWindows = $eventxml.Logs.EventLogsID.ChildNodes
5      $result = @()
6      foreach ($event in $eventsWindows) {
7          $result += $event.LocalName
8          $result += $event.InnerXml
9      }
10     #Add result to table
11 }

```

6. Implementation

As a final task, all these function have to be called in the right order, and the opened PDF has to be closed. For this case, the simple function **VisualizeAll** was created:

Listing 2.27: Function VisualizeAll

```
1  function WriteEventLogs {  
2      $pdf = OpenPDF $exportFolder  
3      $incorrectAudits = WriteAuditPolicies $exportFolder  
4      ToolCanBeDetected $incorrectAudits  
5      WriteEventLogs $exportFolder  
6      $pdf.Close()  
7  }
```

6.4 Main Script: SRI

The aim of the main script is to supply the user with various procedures to evaluate the readiness of audit policies and/or event logs. However, the user is not meant to use single functions provided by the modules because most function provide just a metaset of data in order to make a statement of the readiness. For this reason, the main script is able to be called with various parameter for the different procedures. Moreover, the user gets a help functionality (via PowerShell's common **Get-Help**) to provide an overview of parameter combinations.

6.4.1 Result

The various procedures/modes provided by the main script, with eventual additional parameter, are:

- *-Online, -Offline, -GroupPolicy and -AllGroupPolicies*

```

1 PS C:\>./sri.ps1 [-Online] [-OnlineExportPath <String>] [-CAPI2LogSize <Int32>]
2
3 PS C:\>./sri.ps1 [-Offline] [[-AuditPolicies]] [[-EventLogs]] [-ImportPath] <String>
4                      [-ExportPath] <String> [-CAPI2LogSize <Int32>]
5
6 PS C:\>./sri.ps1 [-GroupPolicy] [-GroupPolicyName] <String>
7
8 PS C:\>./sri.ps1 [-AllGroupPolicies]
```

NOTE: *Mandatory parameter are underlined.*

-Online

The current system which is calling the script will be checked on its readiness.

PARAMETER

No parameter	The result PDF will be saved to the current path
-OnlineExportPath	The result PDF will be saved to this path
-CAPI2LogSize	Definition of the CAPI2 log size suitable for the environment. By default this value is set to 4MB as recommended from Microsoft [14]

-Offline

Some system will be checked on its readiness - by default audit policies and event log are analysed. Export files of this system are required.

PARAMETER

<u>-ImportPath</u>	Defines where the required files rsop.xml ^a , windowslogs.csv ^b , appandservlogs.csv ^c remain for analysis.
	The result PDF will be saved to the current path
-AuditPolicies	Checks only the audit policies.
	The result PDF will be saved to the current path
	<u>-ImportPath</u> requires rsop.xml
-EventLogs	Checks only the event logs
	The result PDF will be saved to the current path
	<u>-ImportPath</u> requires windowslogs.csv and appandservlogs.csv
-ExportPath	The result PDF will be saved to this path
-CAPI2LogSize	Definition of the CAPI2 log size suitable for the environment. By default this value is set to 4MB as recommended from Microsoft [14]

^aXML-Export of Resultant Set of Policy [20]

^bExport of

^cExport of

-GroupPolicy

Audit policies from a specific group policy are analysed.

PARAMETER

<u>-GroupPolicyName</u>	The name of the group policy to be analysed
--------------------------------	---

-AllGroupPolicies

All audit policies from every group policy in the current domain are analysed.
The result PDF will be saved to the current path

6.4.2 Approach

Users should not have to call the individual functions from the PowerShell modules. For this reason, the idea was to provide a main script which defines several modes to call with appropriate parameter. Each mode has a predefined procedure of function calls which will create a result PDF. In addition, the script should be delivered with a integrated help functionality to supply a on-demand overview of all possible script modes and its parameter.

6.4.3 Implementation

To get a better understanding how each mode proceeds, this section describes the source code in form of activity diagrams. The activity diagrams are an overview and contain the core of each mode.




Figure 2.9: Online Mode

1. Get the audit policies from RSoP
2. Analyse the audit policies
3. Get the registry value of the audit setting "Audit: Force audit policy subcategory settings (Windows Vista or later) to override audit policy category settings" and check if it is enabled
4. Check if sysmon is installed and running
5. Check if CAPI2 is enabled and has a minimum log size of 4MB
6. Merge all returned hashtables from step 2-5 to one hashtable
7. Write the "result_audit_policy.xml" for further processing to PDF
8. Get all events from "System" and "Security" event logs and write it uniquely to a temporary CSV
9. Get all events from "Application and Service" event log and write it uniquely to a temporary CSV
10. Compare the gathered events with the target lists of events (see "4.2 Mandatory Event Logs")
11. Create the result PDF




Figure 2.10: Offline Mode

1. The offline mode without parameter will check the audit policies and event logs with the supplied export files⁴
 - (a) Get the audit policies from the supplied rsop.xml
 - (b) Analyse the audit policies
 - (c) Write the "result_audit_policy.xml" for further processing to PDF
 - (d) Compare the events form the supplied windowslogs.csv and appandservlogs.csv with the target lists of events
 - (e) Create the result PDF
2. The offline mode with the parameter **-AuditPolicies** will check the audit policies with the supplied export file
 - (a) Get the audit policies from the supplied rsop.xml
 - (b) Analyse the audit policies
 - (c) Write the "result_audit_policy.xml" for further processing to PDF
 - (d) Create the result PDF
3. The offline mode with the parameter **-EventLogs** will check the event logs with the supplied files
 - (a) Compare the events form the supplied windowslogs.csv and appandservlogs.csv with the target lists of events
 - (b) Create the result PDF

⁴All export files required must remain at the **-ImportPath**




Figure 2.11: GroupPolicy Mode

1. Get the audit policies from defined group policy which is stored in SYSVOL
2. Analyse the audit policies
3. Check if the audit setting "Audit: Force audit policy subcategory settings (Windows Vista or later) to override audit policy category settings" is enabled
4. Merge the returned hashtables from step 2 and 3 to one hashtable
5. Write the "result_audit_policy.xml" for further processing to PDF
6. Create the result PDF and store it in the current path




Figure 2.12: AllGroupPolicies Mode

1. Get all audit policies from all group policies, which are stored in SYSVOL, and loop for each through the following procedure:
 - (a) Analyse the audit policies
 - (b) Check if the audit setting "Audit: Force audit policy subcategory settings (Windows Vista or later) to override audit policy category settings" is enabled
 - (c) Merge the returned hashtables from step 2 and 3 to one hashtable
 - (d) Write the "result_audit_policy.xml" for further processing to PDF
 - (e) Create the result PDF and store it in the current path
 - (f) Rename the created PDF- and XML-Files to its group policy name (e.g. `results_TestPolicy.pdf` and `result_audit_policies_TestPolicy.xml`)

7 Conclusion and Outlook

Glossary

APT	Advanced Persistent Threat, a stealthy computer network attack in which the attacker gains unauthorized access to a network and remains undetected for an extended period
CAPI2	CryptoAPI2, a Microsoft Windows platform specific Cryptographic Application Programming Interface from Windows Vista or newer, offers function for encrypting and decrypting data and strong authentication with digital certificates and secure generation of random numbers
CI	Continuous Integration, continuous assembly of components into an application, mostly on a server with automatic builds and tests
CSV	Comma-separated values, a delimited text file that uses a comma to separate values
DLL	Dynamic Link Library, is Microsoft's implementation of the shared library concept in the Microsoft Windows
DNS	Domain Name System, name resolution on the internet, dns is a directory service responsible for converting alphanumeric domain names into numeric IP addresses
EXE	Executable File for different OS
FAQ	Frequently Asked Questions, listed questions and answers, all supposed to be commonly asked in some context, and pertaining to a particular topic
GB	Gigabyte, is a unit of measurement for digital technology and computer science, 1 GB is 10^9 Byte
GPO	Group Policy Objects, is a digital policy for various settings under Microsoft Windows 2000 and its successors
GUI	Graphic User Interface, a form of user interface of a computer, make application software operable for humans on a computer by means of graphic symbols and control elements
ICMP	Internet Control Message Protocol, is used in computer networks to exchange information and error messages via the internet protocol
ID	Identifier, is a characteristic linked to a particular identity for the unique identification of the load-bearing object

IDE	Integrated development environment, is a software application that provides comprehensive facilities to computer programmers for software development
IP	Internet-Protocol, widely used network protocol, represents the basis of the internet
JPCERT/CC	Japan Computer Emergency Response Team Coordination Center, a Computer Security Incident Response Team established in Japan
KB	Kilobyte, is a unit of measurement for digital technology and computer science, 1 KB is 10^3 Byte
LaTeX	Lamport TeX, is a software package that simplifies the use of the TeX typesetting system with the help of macros
LGPO	Local Group Policy Object, is a Local GPO
LGPO.exe	Local Group Policy Object Utility, a command-line utility to automate the management of local group policy
MB	Megabyte, is a unit of measurement for digital technology and computer science, 1 MB is 10^6 Byte
MiB	Mebibyte is a power of two, appropriate for binary machines Many operating systems calculate the file size in mebibyte, but specify the number as MB (megabyte)
MITRE ATT&CK	MITRE Adversarial Tactics, Techniques, and Common Knowledge, a globally-accessible knowledge base of adversary tactics and techniques based on real-world observations by MITRE, a non-profit organisation which manages federally funded research and development centers supporting several U.S. government agencies
MPSSVC	Is part of Windows Firewall, which protects computers by preventing unauthorized users from gaining access through the Internet or a network
PKI	Public Key Infrastructure, a system capable of issuing, distributing and verifying digital certificates
PowerBI	Is a business analytics service delivered by Microsoft with self-service business intelligence capabilities
PowerShell ISE	PowerShell Integrated Scripting Environment, a Windows-based graphic user interface for PowerShell
RDP	Remote Desktop Protocol, is a Microsoft network protocol for remote access to Windows computers
RSoP	Resultant Set of Policies, is an overview of all group policy settings within the Active Directory structure
SAM	Security Accounts Manager, is a Microsoft Windows service that stores user information such as logon name and password as hash values in a database

SCT	Microsoft Security Compliance Toolkit, this set of tools allows enterprise security administrators analyze, test, edit and store Microsoft-recommended security configuration baselines for Windows and other Microsoft products, while comparing them against other security configurations
SYSVOL	System Volume, a shared directory that stores the server copy of the domain's public files that must be shared for common access and replication throughout a domain
TGT	Ticket Granting Ticket, is a small file that, similar to a password, but more secure, allows access to a data exchange
UC	Use Case, the externally visible behavior of a system is described from the user's point of view
VPN	Virtual Private Network, a private network that enables users to send and receive data securely and encrypted over public or shared networks
WEFFLES	Windows Event Logging Forensic Logging Enhancement Services, a Threat Hunting/Incident Response Console with Windows Event Forwarding and visualized with PowerBI
wevtutil	Windows Event Log Tools Utility, enables to get information about event logs and publishers
WFP	Windows Filtering Platform, set of API and system services that provide a platform for creating network filtering applications
XML	Extensible Markup Language, a markup language for the representation of hierarchically structured data in the format of a text file, which is readable both by humans and by machines

Listings

2.1	LogonTracer: given docker run command	8
2.2	LogonTracer: docker ps (PORTS)	8
2.3	LogonTracer: recommended docker run command	8
2.4	Example Result Audit Policy Analysis	32
2.5	auditpol	33
2.6	Get-GPResultantSetOfPolicy	35
2.7	CompareToTargetList: Search missing configurations	35
2.8	GetAuditSettingValues: Get configured audit settings from RSoP	36
2.9	GetRegistryValue	36
2.10	Function IsForceAuditPolicyEnabeled	37
2.11	Function IsSysmonInstalled	37
2.12	Function GetCAPI2	38
2.13	Function IsCAPI2Enabled	38
2.14	Function GetDomainAuditPolicy	39
2.15	Function GetAllDomainAuditPolicies	39
2.16	Function IsForceAuditPolicyDomainEnabeled	40
2.17	Example Result Audit Policy Analysis	41
2.18	Function GetEventLogsAndExport Part 1	43
2.19	Function GetEventLogsAndExport Part 2	43
2.20	Function GetApplicationAndServiceLogs Part 1	43
2.21	Function GetApplicationAndServiceLogs Part 2	44
2.22	Function ImportCompareExport	44
2.23	Function OpenPDF	46
2.24	Functions WriteAuditPolicies & CreateAddCellWithColor & CreateAddCell	46
2.25	Function ToolsCanBeDetected	47
2.26	Function ToolsCanBeDetected	47
2.27	Function VisualizeAll	48

List of Figures

2.1	Test Environment	2
2.2	LogonTracer: Sample Graph from Test Environment	6
2.3	LogonTracer: Confusing Graph from Test Environment	7
2.4	Detectable attacks with sysmon-modular	11
2.5	Advanced Audit Policy - Logon/Logoff - Audit Special Logon	17
2.6	Domain Model	23
2.7	Sequence Diagram SystemReadinessInspector - SRI	30
2.8	GPO - Advanced Audit Policies	35
2.9	Online Mode	51
2.10	Offline Mode	52
2.11	GroupPolicy Mode	53
2.12	AllGroupPolicies Mode	54

List of Tables

2.1	Test Environment User	3
2.2	Mandatory System Event Logs	14
2.3	Mandatory TaskScheduler Event Logs	14
2.4	Mandatory Windows Remote Management Event Logs	14
2.5	Mandatory TerminalServices-LocalSessionManager Event Logs	15
2.6	Mandatory Sysmon Event Logs	15
2.7	Mandatory TaskScheduler Event Logs	15
2.8	Mandatory Windows Remote Management Event Logs	15
2.9	Mandatory Windows Local Session Manager Event Logs	15
2.10	Mandatory Security Event Logs	16
2.11	Advanced Audit Policy Setting Account Logon	17
2.12	Advanced Audit Policy Setting Account Management	17
2.13	Advanced Audit Policy Setting Logon/Logoff	17
2.14	Advanced Audit Policy Setting Logon/Logoff	18
2.15	Advanced Audit Policy Setting Object Access	18
2.16	Advanced Audit Policy Setting Policy Change	18
2.17	Advanced Audit Policy Setting Privilege Use	18
2.18	Attack Categories [1]	20
2.19	Audit Policy Priority [18]	22
2.20	Non Functional Requirements	28

Bibliography

- [1] JPCERT/CC. Detecting Lateral Movement through Tracking Event Logs. , June 2017.
- [2] harmj0y Andrew Robbins, Rohan Vazarkar. BloodHound - Wiki. <https://github.com/BloodHoundAD/BloodHound/wiki>, September 2018.
- [3] Microsoft. Microsoft Security Compliance Toolkit. <https://docs.microsoft.com/en-us/windows/security/threat-protection/security-compliance-toolkit-10>, June 2018.
- [4] JPCERT/CC. LogonTracer. <https://github.com/JPCERTCC/LogonTracer>, September 2018.
- [5] Shusei Tomonaga. Visualise Event Logs to Identify Compromised Accounts - LogonTracer -. <https://blog.jpcert.or.jp/2017/11/visualise-event-logs-to-identify-compromised-accounts—logontracer-.html> , November 2017.
- [6] Microsoft. Monitoring Active Directory for Signs of Compromise | Microsoft Docs. <https://docs.microsoft.com/en-us/windows-server/identity/ad-ds/plan/security-best-practices/monitoring-active-directory-for-signs-of-compromise>, May 2017.
- [7] Microsoft. Appendix L: Events. <https://docs.microsoft.com/en-us/windows-server/identity/ad-ds/plan/appendix-l-events-to-monitor>, July 2018.
- [8] MITRE ATT&CK. MITRE ATT&CK Website. <https://attack.mitre.org/>, September 2018.
- [9] Mark Russinovich, Thomas Garnier. Sysmon - System Monitor. <https://docs.microsoft.com/en-us/sysinternals/downloads/sysmon>, July 2018.
- [10] Carlos Perez. Operating Offensively Against Sysmon. <https://www.darkoperator.com/blog/2018/10/5/operating-offensively-against-sysmon>, October 2018.
- [11] Nader Shalabi. Sysmon Tools. <https://github.com/olafhartong/sysmon-modular>, October 2018.
- [12] ipstack. Locate and identify website visitors by IP address. <https://ipstack.com/>, October 2018.
- [13] Olaf Hartong. sysmon-modular. <https://attack.mitre.org/>, October 2018.
- [14] Microsoft. Troubleshooting PKI Problems on Windows Vista - CAPI2 Diagnostics in Windows Vista. [https://docs.microsoft.com/en-us/previous-versions/windows/it-pro/windows-vista/cc749296\(v=ws.10\)#capi2-diagnostics-in-windows-vista](https://docs.microsoft.com/en-us/previous-versions/windows/it-pro/windows-vista/cc749296(v=ws.10)#capi2-diagnostics-in-windows-vista), July 2008.
- [15] Abe, Shingo. Detecting Lateral Movement in APTs - Analysis Approach on Windows Event Logs Introduction to JPCERT / CC. June 2016.
- [16] Microsoft. Advanced security auditing FAQ. <https://docs.microsoft.com/en-us/windows/security/threat-protection/auditing/advanced-security-auditing-faq>, April 2017.

- [17] Peter Morin. Extending Your Incident Response Capabilities with Sysmon. https://sector.ca/wp-content/uploads/presentations18/Morin_Sysmon_2019-16-9.pdf, September 2018.
- [18] Microsoft. Advanced security auditing FAQ. <https://docs.microsoft.com/en-us/windows/security/threat-protection/auditing/advanced-security-auditing-faq>, April 2017.
- [19] Daniel Scott-Raynsford. Converting a PowerShell Project to use Azure DevOps Pipelines. <https://www.powershellmagazine.com/2018/09/20/converting-a-powershell-project-to-use-azure-devops-pipelines/>, September 2018.
- [20] Microsoft. RSoP - Resultant Set of Policy. [https://docs.microsoft.com/en-us/previous-versions/windows/it-pro/windows-server-2008-R2-and-2008/cc772175\(v=ws.11\)](https://docs.microsoft.com/en-us/previous-versions/windows/it-pro/windows-server-2008-R2-and-2008/cc772175(v=ws.11)), February 2017.
- [21] Microsoft. Get-EventLog. <https://docs.microsoft.com/en-us/powershell/module/microsoft.powershell.management/get-eventlog?view=powershell-5.1>, October 2018.
- [22] Microsoft. auditpol. <https://docs.microsoft.com/en-us/windows-server/administration/windows-commands/auditpol>, September 2017.
- [23] Microsoft. Get-GPResultantSetOfPolicy. <https://docs.microsoft.com/en-us/powershell/module/grouppolicy/get-gpresultantsetofpolicy?view=win10-ps>, October 2018.
- [24] Microsoft. GroupPolicy. <https://docs.microsoft.com/en-us/powershell/module/grouppolicy/?view=win10-ps>, October 2018.
- [25] Microsoft. Remote Server Administration Tools for Windows 10. <https://www.microsoft.com/en-us/download/details.aspx?id=45520>, October 2018.
- [26] Microsoft. Audit: Force audit policy subcategory settings (Windows Vista or later) to override audit policy category settings. <https://docs.microsoft.com/en-us/windows/security/threat-protection/security-policy-settings/audit-force-audit-policy-subcategory-settings-to-override>, April 2017.
- [27] Microsoft. Get-WinEvent. <https://docs.microsoft.com/en-us/powershell/module/microsoft.powershell.diagnostics/get-winevent?view=powershell-6>, October 2018.
- [28] Microsoft. wevtutil. <https://docs.microsoft.com/en-us/windows-server/administration/windows-commands/wevtutil>, October 2017.
- [29] Microsoft. PowerBI. <https://powerbi.microsoft.com>, November 2018.
- [30] Patrick Lambert. PowerShell-PDF. <https://github.com/dendory/PowerShell-PDF>, March 2015.

Part II

Appendix

Task Definition

Einführung

Es werden vermehrt Cyberangriffe publik, wo Schadcode im Einsatz ist, welcher sich nicht nur auf einem infizierten System niederlässt, sondern weitere Systeme im Netz befällt. Das Ziel oder Resultat ist dabei oft die komplette Infiltrierung einer Organisation. In der Analyse solcher Fälle sind Information und Zeit ein Schlüssel zum Erfolg. Folglich ist die Bereitschaft "Readiness" für ein solches Ereignis ein entscheidender Faktor.

Aufgabe

Ziel dieser Arbeit ist es, ein Tool zu erstellen, welches die Bewertung der eigene Readiness erlaubt aber auch im Analysefall eine Unterstützung bietet. Readiness betrifft viele Aspekte und einfache Dinge wie korrekte Zeitstempel in Logs, deren Vollständigkeit oder die Bereitstellung von Backups. In der konkreten Aufgabenstellung soll die Readiness-Analyse primär für Windows-Infrastrukturen anhand von Logs und spezifischen Events erfolgen. Unter anderem soll auf den neusten Publikationen des japanischen Computer Emergency Response Teams (JPCERT/CC) und der öffentlichen Datenbank der MITRE Corporation, dem Adversarial Tactics, Techniques, and Common Knowledge (ATT&CKTM) Wissenspool, basiert werden. Das JPCERT und MITRE haben dabei die Werkzeuge und das generelle Vorgehen von Angreifern analysiert und geben Hinweise, welche Events auf eine mögliche Verseuchung hinweisen.

Abgrenzung

Es geht nicht darum neue Angriffsvektoren zu finden.

Tätigkeiten

- Projektmanagement und Dokumentation
- Einarbeitung in Incident Handling und Forensik
- Einarbeitung in Angriffstechniken und Werkzeuge
- Einarbeitung in Abwehrtechniken und Härtung von Systemen
- Studium öffentlicher Quellen und verfügbaren Tools
- Umsetzung eines Analyzers gemäss Anforderungen basierend auf etablierten Frameworks

Vorgehen

Im Rahmen der allgemeinen Richtlinien zur Durchführung von Studien- und Bachelorarbeiten gemäss eigenem Projektmanagementplan. Dieser Projektmanagementplan ist als Erstes zu erstellen und enthält insbesondere:

- Die Beschreibung des dem Projektcharakter angepassten Vorgehensmodells.
- Eine erste Aufteilung der Aufgabe in gemeinsam und einzeln zu bearbeitende Teile unter Berücksichtigung der vorgegebenen Teilaspekte. Die genaue Aufteilung muss spätestens nach der Technologiestudie (Elaboration) erfolgen.
- Den Projektplan (Zeitplan) und die Meilensteine.

Anforderungen

Es geht primär darum einen Analyzer zu erstellen um die "Readiness for Tailored Attacks and Lateral Movement Detection" beurteilen zu können. Idealerweise kann dieses Tool von einem IT Administrator ohne spezielle Kenntnisse und grossartige Installationsprozedur ausgeführt werden.

Schematisch aber nicht bindend werden folgende Schritte auszuführen sein

- Definition der Requirements für einen neuen/verbesserten Analyzer
- Design und Analyse basierend auf den Vorgaben
- Vorschläge für die Umsetzung oder Verbesserung eines
 - Readiness Analyzers
 - Readiness Optimizers
 - Compromise Analyzers
- Implementation der Funktionalität und Erstellung eines Benutzerhandbuch
- Erweiterung der Analyzer um neue Erkenntnisse, Werkzeuge und Indicators
- Dokumentation der Software und Skripte

Technologien

- Windows Workstations, Windows Server, Windows Security generell
- Windows Event Logs, Security und Audit Logs
- Windows On-Board Tools, Sysinternals Toolkit
- Active Directory Service (AD) Services
- Group Policy Objects (GPO)
- PowerShell, .NET, Python, Windows Batch

Infrastruktur

Die Arbeiten werden auf den Rechnern der Studenten durchgeführt. Zusätzlich benötigte Software oder Hardware wird bei Bedarf und nach Rücksprache mit Compass Security zur Verfügung gestellt.

Erwartete Resultate

In elektronischer Form

- lauffähiges Toolkit und kompletter Source Code
- komplette Software Dokumentation (Use Cases, Klassenmodell, Sequenzdiagramme usw. in UML)
- komplette Use Cases und Erfolgs-Szenarien resp. Musterlösungen
- alle Dokumente und Protokolle (vorzugsweise in englischer Sprache)

Auf Papier

Gemäss der Anleitung der HSR: \\hsr.ch\root\alg\skripte\Informatik\Fachbereich\Studienarbeit_Informatik Es muss aus den abgegebenen Dokumenten klar hervorgehen, wer für welchen Teil der Arbeit und der Dokumentation verantwortlich war (detaillierte Zeiterfassung).

Termine

Termine gemäss der HSR: \\hsr.ch\root\alg\skripte\Informatik\Fachbereich\Studienarbeit_Informatik\SAI\Termine

Datum	Task
17.09.2018	Beginn der Arbeit, Ausgabe der Aufgabenstellung durch den Betreuer.
18.12.2018	<p>Erfassung des Abstracts im Online-Tool https://abstract.hsr.ch/ Die Studierenden geben den Abstract für die Diplomarbeitbroschüre zur Kontrolle an ihren Betreuer/Examinator frei.</p> <p>Der Betreuer/Examinator gibt das Dokument mit dem korrekten und vollständigen Abstract zur Weiterverarbeitung an das Studiengangsekretariat frei</p> <p>Vorlagen sowie eine ausführliche Anleitung betreffend Dokumentation stehen auf dem Skripteserver zur Verfügung.</p>
21.12.2018	<p>Der Betreuer/Examinator gibt das Dokument mit dem korrekten und vollständigen Abstract der Broschüre zur Weiterverarbeitung an das Studiengangsekretariat frei.</p> <p>Hochladen aller verlangten Dokumente auf archiv-i.hsr.ch Abgabe des Berichts an den Betreuer bis 12.00 Uhr</p>

Zeitplan und Meilensteine

Zeitplan und Meilensteine für das Projekt sind von den Studenten selber zu erarbeiten und zusammen mit dem Projektmanagementplan abzuliefern. Die Meilensteine sind bindend. Der erste Meilenstein ist vorgegeben. Mit den Betreuern werden regelmässige Sitzungen zur Fortschrittskontrolle durchgeführt.

Betreuung

Die Arbeiten werden durch Cyrill Brunswiler betreut. Der Gegenleser ist noch nicht bestimmt.

Kontakt

Cyrill Brunswiler, Managing Director, Compass Security Schweiz AG
Weststrasse 50, 8003 Zürich, Switzerland
Werkstrasse 20, 8645 Jona, Switzerland

+41 55 214 41 73

cyrill.brunswiler@compass-security.com

cyrill.brunswiler@hsr.ch

Unterschriften

Jona, 28. September 2018



Cyrill Brunswiler



Claudio Mattes



Lukas Kellenberger