- Ultimate goal of (empirical) Analysis & (mathematical) Modeling of Social Networks in Computer Science: Constructing useful services for users; Establish & further develop Social Networking (Model of network + bundle of services that operate on that model) as Social Medium
- In Social Computing: Services are ultimately Communication Services: Information is transferred between individuals
- More fine grained subdivision: Awareness Services, Communication Services (per se), Information Services; (subdivision is only coarse: every communication act transfers information and requires awareness about state of receiver; every use of an information service is ultimately a communication act)


- Awareness-Services: Inform Users about the activities or general state of other users
- Communication-Service (per se): Establish channels for all kinds of communication acts: (synchronous vs. asynchronous, direct vs. indirect, 1:1 vs n:m, textual, audio-visual, symbolical etc.)
- Information Service: Allow users to manage information spaces and other users to access those information spaces

- Most basic Awareness-Service in Social Networking: Visualize the social network
- Purposes of social network visualizations:
 - Get an overview about a particular social network
 - Perceive structures (clusters etc.) in the SN via human visual system
 - Show dynamic changes in a network

We model SN as graphs → Investigate discipline of graph drawing

- (1) Theoretical Background; Drawing of static graphs
- (2) Drawing of dynamic graphs; SN visualization applications

What we saw so far: How to draw a graph so that certain "quality criteria" are met; Concentration on layout




Layout: Examples:


Kamada Kawai


Planar Graph drawing


Fruchterman Reingold





Symbols: Examples:











Color: Examples:

- (Continuous) Color Temperature: E.g. Use Hot Colors for active edges (that are often "instantiated"), edges with high weight, active actors etc. and cold colors for inactive edges or actors or low weight edges etc.
- Use a distinct set of n colors for different actor / relation types. Problem: Maximize color difference → In 3 valued color spaces (RGB etc.) or 4 valued color spaces (CMYK, RGBA etc.): Find n vectors on unit spheres of corresponding dimension so that angles are maximized → interesting combinatorial / abstract mathematical problem; very complex aspects (see [2]) → use numerical approach (→ e.g. charged particles)

Further possibilities:

- Interactive SN visualizations:
 - Zooming
 - Change Projection (3D)
 - Click on / Point to Actor / Relation to get further information
 - Click on / Point to Actor / Relation to invoke service (e.g. instantiate communication channel)
- SN visualizations with hierarchical graphs: E.g. for every clique introduce "supernode"
- SN visualizations with multigraphs: Two nodes can be connected by more than one edge (e.g. of different types)
- SN visualizations with hypergraphs: An edge can connect more than one node (e.g. have cliques connected by special "clique edge")

- Goal of dynamic social network visualization: Visualize not only structure of a SN "as it is" but: Visualize dynamics of a social network:
 - edges appear / disappear, change weights, change type;
 - nodes appear / disappear, change profile etc.
- Either animated / unanimated sequence of graphs (each graph corresponding to a time slice ti or a "stacked" view of the graph at the current time slice and the time slices before). (Examples later).
- Main goal / Quality criterion:
 Preserving the mental map ← → How long does it take to re-familiarize oneself with new graph layout by re-identifying important nodes and most important structural features of graph.

"Communicate the changes"[15]

Quality criteria: more detailed (see [15])

- Movements of nodes and edges should be easy to follow
- Movements of / in the graph should be structured (Uniform movement, symmetric movement, 2D Proj of 3D structure...)
- Smooth transitions
- No display of non-existing structures
- Individual frames should satisfy the classical criteria for good graph drawings (see chapter 3)
- Minimize temporary edge crossings.
- Minimize the length of the movement path of a node


Software Packages for Graph Drawing and Social Network Visualization

- We will investigate software packages for general visualization of SN in the context of the general discussion on general purpose software (tool sets) for social network analysis in a later chapter of the lecture
- We will now take a look at specific "solutions" (original papers) on dynamic social network visualization

Dynamic viz. of "activity" while using social media: Examples: Babble + PeopleGarden

Both not viz. of dynamic SN in the narrower sense but: Dynamic "Activity" may be an indirect hint for dynamic network centrality; also: two users being both active at a given time interval may also have a higher probability of interacting in that interval (→ indirect hint for dyn. SN edge)

Babble [3]: Viz. of activity in a chat: Distance to center → Activity; Compare Milgram's crowd metaphor [4] (center & fringe)



Dynamic viz. of "activity" while using social media:


Examples: Babble + PeopleGarden

- PeopleGarden [5]: Viz. of activity in communities (discussion boards etc.): Flower paradigm
- Height of flower: Time of first posting (→ how long "member")
- Bloom / blossom:
 - number of petals ←→ number of postings;
 - color saturation: age of postings;
 - color: post or reply




Dynamic SN viz. Examples

- PieSpy [6]: Viz. dyn SN inferred from IRC channels
- Series of SN drawings at given time interval; no animation → some aprupt changes (→ sometimes no preserving of mental map)
- Fruchterman-Reingold based drawing; disconnected components hindered of drifting too far away by repelling force cutoff
- Ability to suppress edges → better "readability" (only proximity of nodes)




Dynamic SN viz. Examples

- SoNIA [7,8,9] (Social Network Image Animator): General purpose dynamic SN visualizer
- In each time slice: relational events → aggregated into SN; smooth transition animation between slices
- Various options: Layout alg (FR, KK, etc.); initial node positioning (random, circular, previous slice etc.); centering of layout (canvas center, barycenter); max. number of iterations for layout alg. etc.; Works together with standard SN software (eg. Pajek)



Dynamic SN viz. Examples

SoNIA [7,8,9] (Social Network Image Animator): General purpose dynamic SN visualizer



Dynamic SN viz. Examples

SoNIA [7,8,9] (Social Network Image Animator): General purpose dynamic SN visualizer: Problem of chosing the right time slice





Figure 1. Interaction data from McFarland's classroom observations viewed at various levels of time aggregation from 35 minutes (one entire class period) to 1 minute (two to three turns of interaction).

Dynamic SN viz. Examples

Chen & Carr [10,11] Co-citation dynamic network visualization

 co-citation network with stacked bars that indicate frequency of co-citation


events



Dynamic SN viz. Examples

Forsighted layout [13] / Graphs they are changing [12]


- Visualize Dynamic graph where nodes and edges appear from slice to slice
- Idea: Draw Supergraph where all edges and nodes of all times are contained; In each slice: draw subgraph
- nodes and edges do not change positions / curvature between slices
- Nodes / Edges existing at disjoint slices only may be grouped and positioned at similar positions of subsequent time slices
- In [12] movement tolerance of nodes is introduced to make layout more compact; several other variations of static placement are introduced



Dynamic SN viz. Examples

Graph Drawing in Motion [15]: Preserving the Mental Map in Dyn. Graph Drawing by:


- minimize changes or animate transitions between time slices
- Further methods: avoid temporary edge crossings, maintain minimal dist. betw. nodes (if poss.); maintain symmetry of structures, move graphs "like rigid objects";



Dynamic Data Viz. Examples with Graphs

Fund Manager Flow Graph [16,17]


- "Movement" (B→A: Transaction: Buying shares of company A and Selling shares from B) of fund managers between company shares
- 2,5D: Time is z-axis; Movement: edge; Edge-weight (thickness): Value of transferred shares; Radius of company-cylinder: Value of current share (red: loss, green: gain)
- Graph layout: Force directed alg. (Frick)
- Click on edge: Information on fund manager that initiated the transaction



Dynamic SN Viz. Example:

GraphAEL [18,19]

- 2.5D co-citation network; Node weight (diameter): "Productivity" of author; Edge weight (thickness): "Intensity" of collaboration
- Intertemporal edges:Identify corresp. nodes
- Each time slice: force directed layout (modified KK)




Dynamic Temporal Data Viz. Example:

Research Area Evolution Network [20]

• 2.5D citation network
Nodes: All Papers of a
particular research area;
Edges: Citations; Node
weight (diameter): number
of citations or research
area; No Edge weight


Each time slice: Modified force directed layout: Hot research topics move to center


Intertemporal edges: "worm tubes"



Dynamic SN Viz. Example:


Dyson [1]





Dynamic SN Viz. Example:

Dyson [1]



Dynamic SN Viz. Example:

Dyson [1]





Figure 3.5: Tube-only model without and with mapping of degree centrality onto temporal axis.



Dynamic SN Viz. Example:

Dyson [1]

Each time-slice layout: modified FR algorithm: Attractive forces:

$$\frac{\delta^2}{k} \to \frac{\delta^2}{k} w(e_i)$$

- Gravitational force to center
- Preserving the Mental Map: Use final layout of slice ti as initial layout of slice ti+1; Introduce spring forces between node position and initial node position. (force is inverse proportional to degree change of node (compared to previous timeslice) → nodes with no changes in degree move less).

Dynamic SN Viz. Example:

Dyson [1]

Modify gravitational forces further: emphasize node (degree) centrality

$$F_{grav}(v) \rightarrow F_{grav}(v) (\deg(v) + c)$$

- → nodes with high centrality move to center
- depict node "activity" (number of social "events" in current slice) by color temperature: hot colors → high activity
- depict further node profile element (or also "activity") as node diameter
- interpolate node's layout locations & diameters in different time slices → tube metaphor

Recommended Readings

- Select two papers from the shown example systems;
- Especially Recommended are: [9] (Excellent overview), [6], [15]

Citations

- (1) Holger Hanstein: "Interactive visualization of dynamic social networks" Master's Thesis, TU-München, Falultät für Informatik, LS Prof. Schlichter, Betreuer: G.Groh, 2007
- (2) http://www.maths.unsw.edu.au/school/articles/me100.html (URL May 2008)
- (3) Erin Bradner, Wendy A. Kellogg, and Thomas Erickson. The adoption and use of BABBLE: a field study of chat in the workplace. In Proceedings of the Sixth European conference on Computer supported cooperative work, pages 139–158, Norwell, MA, USA, 1999. Kluwer Academic Publishers. www.research.ibm.com/SocialComputing/Papers/AdoptionOfBabble.htm (URL May 2008)
- (4) Stanley Milgram. The individual in a social world Essays and Experiments. Series in social psychology. Addison-Wesley, Reading, Massachusetts, 1977.
- (5) Rebecca Xiong and Judith Donath. Peoplegarden: creating data portraits for users. In UIST '99: Proceedings of the 12th annual ACM symposium on User interface software and technology, pages 37–44, New York, NY, USA, 1999. ACM Press. http://doi.acm.org/10.1145/320719.322581
- (6) Paul Mutton. Piespy social network bot inferring and visualizing social networks on irc, 2006. http://www.jibble.org/piespy/
- (7) Daniel A. McFarland and Skye Bender-deMoll. SoNIA (Social Network Image Animator), 2007. http://sonia.stanford.edu
- (8) Skye Bender-deMoll and Daniel A. McFarland. Interaction, time, and motion: Animating social networks with sonia, 2004. www.stanford.edu/group/sonia/papers/PiranVizTalk.pdf
- (9) Skye Bender-deMoll and Daniel A. McFarland. The art and science of dynamic network visualization. Journal of Social Structure, 7(2), 2006. www.cmu.edu/joss/content/articles/volume7/deMollMcFarland/

Citations

- (10) Chaomei Chen and Leslie Carr. Visualizing the evolution of a subject domain: a case study. In VIS '99: Proceedings of the conference on Visualization '99, pages 449–452, Los Alamitos, CA, USA, 1999. IEEE Computer Society Press.
- (11) Ed H. Chi. Web analysis visualization spreadsheet. Technical report, Xerox Palo Alto Research Center, Palo Alto, CA 94304, 1999. http://www2.parc.com/istl/groups/uir/publications/items/UIR-1999-08-Chi-WOWS99-WAVS.pdf (URL May 2008)
- (12) Stephan Diehl and Carsten Görg. Graphs, they are changing dynamic graph drawing for a sequence of graphs. In Graph Drawing: 10th International Symposium, GD 2002, Irvine, CA, USA, August 26-28, 2002. Revised Papers, volume 2528/2002 of Lecture Notes in Computer Science, pages 23–30. Springer-Link, 2002. www.springerlink.com/content/dklm0erkw0bftwh8 (URL May 2008)
- (13) Stephan Diehl, Carsten Görg, and Andreas Kerren. Preserving the mental map using foresighted layout. In Proceedings of the Joint Eurographics-IEEE TVCG Symposium on Visualization, VisSym, pages 175–184. Springer Verlag, Wien, New York, 2001. http://citeseer.ist.psu.edu/diehl01preserving.html (URL May 2008)
- (14) Jürgen Branke. Dynamic graph drawing. Lecture Notes In Computer Science, pages 228–246, 2001. http://portal.acm.org/citation.cfm?id=376953
- (15) Carsten Friedrich and Peter Eades. Graph drawing in motion. Journal of Graph Algorithms and Applications, 6(3):353–370, February 2002. http://jgaa.info/accepted/2002/FriedrichEades2002.6.3.pdf
- (16) Tim Dwyer. A scalable method for visualising changes in portfolio data. In APVis '03: Proceedings of the Asia-Pacific symposium on Information visualisation, pages 17–25, Darlinghurst, Australia, Australia, 2003. Australian Computer Society, Inc. http://portal.acm.org/citation.cfm?id=857083.
- (17) Tim Dwyer. Two and a Half Dimensional Visualisation of Relational Networks. PhD thesis, University of Sydney, 2005. www.cs.usyd.edu.au/dwyer/thesis-20050609.pdf

Citations

- (18) Cesim Erten, Philip J. Harding, Stephen G. Kobourov, Kevin Wampler, and Gary Yee. Exploring the computing literature using temporal graph visualization, 2003. http://citeseer.ist.psu.edu/erten03exploring.html
- (19) Cesim Erten, Philip J. Harding, Stephen G. Kobourov, Kevin Wampler, and Gary V. Yee. Graphael: Graph animations with evolving layouts. In Graph Drawing, volume 2912 of Lecture Notes in Computer Science, pages 98–110. Springer Verlag, 2004. www.springerlink.com/content/4pt8gbhu8eqyyk7e
- (20) Adel Ahmed, Tim Dwyer, Colin Murray, Le Song, and Ying Xin Wu. Wilmascope graph visualisation. In INFOVIS '04: Proceedings of the IEEE Symposium on Information Visualization (INFOVIS'04), page 216.4, Washington, DC, USA, 2004. IEEE Computer Society. http://dx.doi.org/10.1109/INFOVIS2004