

Learning R packages

Cristian Villegas

2023-05-15

Sumário

1	Intro	7
1.1	Carrega pacotes a serem usados	7
1.2	Alguns atalhos no Rstudio	7
2	dplyr (60 minutos)	9
2.1	Carrega pacotes a serem usados	9
2.2	Descrição dos dados mpg	9
2.3	Lista de funções do pacote dplyr	11
2.4	Operador Pipe	13
2.5	select() para colunas	13
2.6	rename()	17
2.7	mutate() para colunas	19
2.8	transmute()	20
2.9	filter() para linhas	21
2.10	slice() para linhas	26
2.11	arrange() para linhas	27
2.12	distinct() para linhas	30
2.13	summarise()	32
2.14	group_by()	33
2.15	count()	35
2.16	sample_n()	36
2.17	sample_frac()	37
3	ggplot2 (60 minutos)	39
3.1	Carrega pacotes a serem usados	39
3.2	Lista de funções do pacote ggplot2	40
3.3	Primeiros passos usando geom_point	40
3.4	smooth, boxplot, histogram	57
3.5	gridExtra e patchwork	61
3.6	bar, col, density, density2d	68
3.7	facet_grid, facet_wrap	75
3.8	stat_function	82
3.9	stat_summary	82

3.10	theme_*()	83
3.11	Gráfico de perfis (Spagueti plot)	84
3.12	plotly	86
3.13	esquisse	86
3.14	Exemplo esquisse	87
4	purrr	89
4.1	Apply a function to each element of a list or atomic vector	90
4.2	Examples	92
4.3	map functions	102
4.4	map2 functions	103
5	tidyr	105
5.1	nest()	105
5.2	unnest()	110
5.3	Exemplos da ajuda do R	110
5.4	Mais detalhes	115
6	broom and dplyr	117
6.1	Tidy bootstrapping	125
6.2	Mais detalhes (glance)	131
6.3	links	139
7	Extra	141
7.1	Introduction	141
7.2	Correlation	141
7.3	Correlation matrix	141
7.4	Testing a bivariate association	142
7.5	Visualizing the association	143
7.6	Testing the significance of all correlations in the matrix	143
7.7	Pretty output	144
7.8	Keeping the correlations for further analysis	145
7.9	Correlation method	146
7.10	Missing data	147
8	Single-predictor (simple) regression	149
8.1	Regression diagnostics	151
8.2	Bootstrap estimates and confidence intervals	152
9	Multiple regression	155
9.1	Visualizing regression data	156
9.2	Getting results into a tidy, useful format	156
9.3	Modeling interactions	157
9.4	Contrasts in regression	158
9.5	Expected means for protein source	159
9.6	Expected means for protein level	160
9.7	Means in each cell of the factorial design	160

9.8	Pairwise comparisons among protein sources	160
9.9	Pairwise differences and simple slopes in regression	162
9.10	A few other emmeans features	164

Capítulo 1

Intro

1.1 Carrega pacotes a serem usados

```
#install.packages("tidyverse")
#install.packages("dplyr")
#install.packages("tidyr")
#install.packages("ggplot2")

library(tidyverse)
# Manipulação de dados
#library(dplyr)

# Visualização de gráficos
library(ggplot2)
library(gridExtra)
library(patchwork)
library(plotly)
library(esquisse)

# Para dados gráfico de perfis
library(nlme)
```

1.2 Alguns atalhos no Rstudio

Para considerar

Operador Pipe ($\%>\%$): Ctrl + Shift + M (Windows) ou Cmd + Shift + M (Mac).

Criar novos chunks: Ctrl + Alt + I (Windows) ou Cmd + Option + I (Mac).

Capítulo 2

dplyr (60 minutos)

2.1 Carrega pacotes a serem usados

```
#install.packages("tidyverse")
#install.packages("dplyr")
#install.packages("tidyr")
#install.packages("ggplot2")

library(tidyverse)
# Manipulação de dados
#library(dplyr)

# Visualização de gráficos
library(ggplot2)
library(gridExtra)
library(patchwork)
library(plotly)
library(esquisse)

# Para dados gráfico de perfis
library(nlme)
```

2.2 Descrição dos dados mpg

Dados de economia de combustível de 1999 a 2008 para *38 modelos populares de carros*. Este conjunto de dados contém um subconjunto dos dados de economia de combustível que a EPA disponibiliza em <https://fuelconomy.gov/>. Ele contém apenas modelos que tiveram um novo lançamento a cada ano entre 1999 e 2008 - isso foi usado como um substituto para a popularidade do carro. Um

data frame com 234 linhas e 11 variáveis:

- *manufacturer* nome do fabricante
- *model* nome do modelo
- *displ* cilindrada do motor, em litros
- *year* ano de fabricação
- *cyl* número de cilindros
- *trans* tipo de transmissão
- *drv* o tipo de trem de força, onde **f** = **tração dianteira**, **r** = **tração traseira** e **4** = **4wd**
- *cty* milhas urbanas por galão
- *hwy* milhas rodoviárias por galão
- *fl* tipo de combustível
- *class* “tipo” de carro

```
#help("mpg")
```

```
library(tidyverse)
```

```
dados <- mpg
```

```
glimpse(dados)
```

```
## Rows: 234
```

```
## Columns: 11
```

```
## $ manufacturer <chr> "audi", "audi", "audi", "audi", "audi", "audi", "audi", "~
```

```
## $ model <chr> "a4", "a4", "a4", "a4", "a4", "a4", "a4", "a4 quattro", "~
```

```
## $ displ <dbl> 1.8, 1.8, 2.0, 2.0, 2.8, 2.8, 3.1, 1.8, 1.8, 2.0, 2.0, 2.~
```

```
## $ year <int> 1999, 1999, 2008, 2008, 1999, 1999, 2008, 1999, 1999, 200~
```

```
## $ cyl <int> 4, 4, 4, 4, 6, 6, 6, 4, 4, 4, 4, 6, 6, 6, 6, 6, 6, 8, 8, ~
```

```
## $ trans <chr> "auto(l5)", "manual(m5)", "manual(m6)", "auto(av)", "auto~
```

```
## $ drv <chr> "f", "f", "f", "f", "f", "f", "f", "4", "4", "4", "4", "4~
```

```
## $ cty <int> 18, 21, 20, 21, 16, 18, 18, 18, 16, 20, 19, 15, 17, 17, 1~
```

```
## $ hwy <int> 29, 29, 31, 30, 26, 26, 27, 26, 25, 28, 27, 25, 25, 25, 2~
```

```
## $ fl <chr> "p", "p", "p", "p", "p", "p", "p", "p", "p", "p", "p", "p", "p~
```

```
## $ class <chr> "compact", "compact", "compact", "compact", "compact", "c~
```

```
dados <- mutate(.data = dados,
```

```
  across(where(is.character),
```

```
    as.factor))
```

```
#View(df)
```

```
glimpse(dados)
```

```
## Rows: 234
```

```
## Columns: 11
```


## [88] "distinct_if"	"distinct_prepare"	"do"
## [91] "do_"	"dplyr_col_modify"	"dplyr_reconstruct"
## [94] "dplyr_row_slice"	"ends_with"	"enexpr"
## [97] "enexprs"	"enquo"	"enquos"
## [100] "ensym"	"ensyms"	"eval_tbls"
## [103] "eval_tbls2"	"everything"	"explain"
## [106] "expr"	"failwith"	"filter"
## [109] "filter_"	"filter_all"	"filter_at"
## [112] "filter_if"	"first"	"full_join"
## [115] "funs"	"funs_"	"glimpse"
## [118] "group_by"	"group_by_"	"group_by_all"
## [121] "group_by_at"	"group_by_drop_default"	"group_by_if"
## [124] "group_by_prepare"	"group_cols"	"group_data"
## [127] "group_indices"	"group_indices_"	"group_keys"
## [130] "group_map"	"group_modify"	"group_nest"
## [133] "group_rows"	"group_size"	"group_split"
## [136] "group_trim"	"group_vars"	"group_walk"
## [139] "grouped_df"	"groups"	"id"
## [142] "ident"	"if_all"	"if_any"
## [145] "if_else"	"inner_join"	"intersect"
## [148] "is_grouped_df"	"is.src"	"is.tbl"
## [151] "is_grouped_df"	"join_by"	"lag"
## [154] "last"	"last_col"	"last_dplyr_warnings"
## [157] "lead"	"left_join"	"location"
## [160] "lst"	"make_tbl"	"matches"
## [163] "min_rank"	"mutate"	"mutate_"
## [166] "mutate_all"	"mutate_at"	"mutate_each"
## [169] "mutate_each_"	"mutate_if"	"n"
## [172] "n_distinct"	"n_groups"	"na_if"
## [175] "near"	"nest_by"	"nest_join"
## [178] "new_grouped_df"	"new_rowwise_df"	"nth"
## [181] "ntile"	"num_range"	"one_of"
## [184] "order_by"	"percent_rank"	"pick"
## [187] "progress_estimated"	"pull"	"quo"
## [190] "quo_name"	"quos"	"recode"
## [193] "recode_factor"	"reframe"	"relocate"
## [196] "rename"	"rename_"	"rename_all"
## [199] "rename_at"	"rename_if"	"rename_vars"
## [202] "rename_vars_"	"rename_with"	"right_join"
## [205] "row_number"	"rows_append"	"rows_delete"
## [208] "rows_insert"	"rows_patch"	"rows_update"
## [211] "rows_upsert"	"rowwise"	"same_src"
## [214] "sample_frac"	"sample_n"	"select"
## [217] "select_"	"select_all"	"select_at"
## [220] "select_if"	"select_var"	"select_vars"
## [223] "select_vars_"	"semi_join"	"setdiff"

## [226] "setequal"	"show_query"	"slice"
## [229] "slice_"	"slice_head"	"slice_max"
## [232] "slice_min"	"slice_sample"	"slice_tail"
## [235] "sql"	"sql_escape_ident"	"sql_escape_string"
## [238] "sql_join"	"sql_select"	"sql_semi_join"
## [241] "sql_set_op"	"sql_subquery"	"sql_translate_env"
## [244] "src"	"src_df"	"src_local"
## [247] "src_mysql"	"src_postgres"	"src_sqlite"
## [250] "src_tbls"	"starts_with"	"starwars"
## [253] "storms"	"summarise"	"summarise_"
## [256] "summarise_all"	"summarise_at"	"summarise_each"
## [259] "summarise_each_"	"summarise_if"	"summarize"
## [262] "summarize_"	"summarize_all"	"summarize_at"
## [265] "summarize_each"	"summarize_each_"	"summarize_if"
## [268] "sym"	"syndiff"	"syms"
## [271] "tally"	"tally_"	"tbl"
## [274] "tbl_df"	"tbl_nongroup_vars"	"tbl_ptype"
## [277] "tbl_vars"	"tibble"	"top_frac"
## [280] "top_n"	"transmute"	"transmute_"
## [283] "transmute_all"	"transmute_at"	"transmute_if"
## [286] "tribble"	"type_sum"	"ungroup"
## [289] "union"	"union_all"	"validate_grouped_df"
## [292] "validate_rowwise_df"	"vars"	"where"
## [295] "with_groups"	"with_order"	"wrap_dbplyr_obj"

2.4 Operador Pipe

```
sqrt(log(44))
```

```
## [1] 1.945299
```

```
44 %>% log %>% sqrt
```

```
## [1] 1.945299
```

2.5 select() para columnas

```
select(dados, manufacturer, model, year)
```

```
## # A tibble: 234 x 3
```

##	manufacturer	model	year
##	<fct>	<fct>	<int>
##	1 audi	a4	1999
##	2 audi	a4	1999
##	3 audi	a4	2008

```
## 4 audi      a4      2008
## 5 audi      a4      1999
## 6 audi      a4      1999
## 7 audi      a4      2008
## 8 audi      a4 quattro 1999
## 9 audi      a4 quattro 1999
## 10 audi     a4 quattro 2008
## # ... with 224 more rows
```

```
select(dados, starts_with("m"))
```

```
## # A tibble: 234 x 2
##   manufacturer model
##   <fct>          <fct>
## 1 audi          a4
## 2 audi          a4
## 3 audi          a4
## 4 audi          a4
## 5 audi          a4
## 6 audi          a4
## 7 audi          a4
## 8 audi          a4 quattro
## 9 audi          a4 quattro
## 10 audi         a4 quattro
## # ... with 224 more rows
```

```
select(dados, contains("r"))
```

```
## # A tibble: 234 x 4
##   manufacturer year trans      drv
##   <fct>         <int> <fct>   <fct>
## 1 audi          1999 auto(l5)  f
## 2 audi          1999 manual(m5) f
## 3 audi          2008 manual(m6) f
## 4 audi          2008 auto(av)   f
## 5 audi          1999 auto(l5)  f
## 6 audi          1999 manual(m5) f
## 7 audi          2008 auto(av)   f
## 8 audi          1999 manual(m5) 4
## 9 audi          1999 auto(l5)  4
## 10 audi         2008 manual(m6) 4
## # ... with 224 more rows
```

```
select(dados, ends_with("y"))
```

```
## # A tibble: 234 x 2
##   cty    hwy
##   <int> <int>
```

```
## 1 18 29
## 2 21 29
## 3 20 31
## 4 21 30
## 5 16 26
## 6 18 26
## 7 18 27
## 8 18 26
## 9 16 25
## 10 20 28
## # ... with 224 more rows
```

```
select(dados, matches("[abc]"))
```

```
## # A tibble: 234 x 6
##   manufacturer year   cyl trans      cty class
##   <fct>         <int> <int> <fct>    <int> <fct>
## 1 audi         1999     4 auto(15)    18 compact
## 2 audi         1999     4 manual(m5)  21 compact
## 3 audi         2008     4 manual(m6)  20 compact
## 4 audi         2008     4 auto(av)    21 compact
## 5 audi         1999     6 auto(15)    16 compact
## 6 audi         1999     6 manual(m5)  18 compact
## 7 audi         2008     6 auto(av)    18 compact
## 8 audi         1999     4 manual(m5)  18 compact
## 9 audi         1999     4 auto(15)    16 compact
## 10 audi        2008     4 manual(m6)  20 compact
## # ... with 224 more rows
```

```
select(dados, starts_with("m"), starts_with("c"))
```

```
## # A tibble: 234 x 5
##   manufacturer model      cyl cty class
##   <fct>         <fct>    <int> <int> <fct>
## 1 audi         a4         4     18 compact
## 2 audi         a4         4     21 compact
## 3 audi         a4         4     20 compact
## 4 audi         a4         4     21 compact
## 5 audi         a4         6     16 compact
## 6 audi         a4         6     18 compact
## 7 audi         a4         6     18 compact
## 8 audi         a4 quattro  4     18 compact
## 9 audi         a4 quattro  4     16 compact
## 10 audi        a4 quattro  4     20 compact
## # ... with 224 more rows
```

```
select(dados, ends_with("l"), ends_with("s"))
```

```
## # A tibble: 234 x 6
##   model      displ  cyl fl   trans      class
##   <fct>      <dbl> <int> <fct> <fct>      <fct>
## 1 a4          1.8     4 p   auto(l5) compact
## 2 a4          1.8     4 p   manual(m5) compact
## 3 a4          2       4 p   manual(m6) compact
## 4 a4          2       4 p   auto(av) compact
## 5 a4          2.8     6 p   auto(l5) compact
## 6 a4          2.8     6 p   manual(m5) compact
## 7 a4          3.1     6 p   auto(av) compact
## 8 a4 quattro  1.8     4 p   manual(m5) compact
## 9 a4 quattro  1.8     4 p   auto(l5) compact
## 10 a4 quattro 2       4 p   manual(m6) compact
## # ... with 224 more rows
```

```
select(dados, 1:3)
```

```
## # A tibble: 234 x 3
##   manufacturer model      displ
##   <fct>          <fct>      <dbl>
## 1 audi          a4          1.8
## 2 audi          a4          1.8
## 3 audi          a4          2
## 4 audi          a4          2
## 5 audi          a4          2.8
## 6 audi          a4          2.8
## 7 audi          a4          3.1
## 8 audi          a4 quattro 1.8
## 9 audi          a4 quattro 1.8
## 10 audi          a4 quattro 2
## # ... with 224 more rows
```

```
select(dados, c(2,5,7))
```

```
## # A tibble: 234 x 3
##   model      cyl drv
##   <fct>      <int> <fct>
## 1 a4          4 f
## 2 a4          4 f
## 3 a4          4 f
## 4 a4          4 f
## 5 a4          6 f
## 6 a4          6 f
## 7 a4          6 f
## 8 a4 quattro  4 4
## 9 a4 quattro  4 4
## 10 a4 quattro  4 4
```



```
## # ... with 224 more rows
```

```
select(dados, manufacturer:cyl)
```

```
## # A tibble: 234 x 5
```

```
##   manufacturer model      displ  year  cyl
##   <fct>         <fct>    <dbl> <int> <int>
## 1 audi          a4        1.8  1999   4
## 2 audi          a4        1.8  1999   4
## 3 audi          a4         2   2008   4
## 4 audi          a4         2   2008   4
## 5 audi          a4        2.8  1999   6
## 6 audi          a4        2.8  1999   6
## 7 audi          a4        3.1  2008   6
## 8 audi          a4 quattro  1.8  1999   4
## 9 audi          a4 quattro  1.8  1999   4
## 10 audi         a4 quattro   2   2008   4
```

```
## # ... with 224 more rows
```

```
select(dados, -(manufacturer:cyl))
```

```
## # A tibble: 234 x 6
```

```
##   trans      drv   cty   hwy fl   class
##   <fct>     <fct> <int> <int> <fct> <fct>
## 1 auto(l5)  f      18    29 p    compact
## 2 manual(m5) f      21    29 p    compact
## 3 manual(m6) f      20    31 p    compact
## 4 auto(av)  f      21    30 p    compact
## 5 auto(l5)  f      16    26 p    compact
## 6 manual(m5) f      18    26 p    compact
## 7 auto(av)  f      18    27 p    compact
## 8 manual(m5) 4      18    26 p    compact
## 9 auto(l5)  4      16    25 p    compact
## 10 manual(m6) 4      20    28 p    compact
```

```
## # ... with 224 more rows
```

2.6 `rename()`

```
dados1 <- rename(dados,
                 mnfc = manufacturer,
                 mod = model)
```

```
dados1
```

```
## # A tibble: 234 x 11
```

```
##   mnfc mod      displ  year  cyl trans      drv   cty   hwy fl   class
##   <fct> <fct>    <dbl> <int> <int> <fct>    <fct> <int> <int> <fct> <fct>
```

```
## 1 audi a4 1.8 1999 4 auto(15) f 18 29 p compact
## 2 audi a4 1.8 1999 4 manual(m5) f 21 29 p compact
## 3 audi a4 2 2008 4 manual(m6) f 20 31 p compact
## 4 audi a4 2 2008 4 auto(av) f 21 30 p compact
## 5 audi a4 2.8 1999 6 auto(15) f 16 26 p compact
## 6 audi a4 2.8 1999 6 manual(m5) f 18 26 p compact
## 7 audi a4 3.1 2008 6 auto(av) f 18 27 p compact
## 8 audi a4 quattro 1.8 1999 4 manual(m5) 4 18 26 p compact
## 9 audi a4 quattro 1.8 1999 4 auto(15) 4 16 25 p compact
## 10 audi a4 quattro 2 2008 4 manual(m6) 4 20 28 p compact
## # ... with 224 more rows
```

```
select(dados,
       mnfc = manufacturer,
       mod = model)
```

```
## # A tibble: 234 x 2
##   mnfc mod
##   <fct> <fct>
## 1 audi a4
## 2 audi a4
## 3 audi a4
## 4 audi a4
## 5 audi a4
## 6 audi a4
## 7 audi a4
## 8 audi a4 quattro
## 9 audi a4 quattro
## 10 audi a4 quattro
## # ... with 224 more rows
```

```
select(dados,
       mnfc = manufacturer,
       mod = model,
       everything())
```

```
## # A tibble: 234 x 11
##   mnfc mod displ year cyl trans drv cty hwy fl class
##   <fct> <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct>
## 1 audi a4 1.8 1999 4 auto(15) f 18 29 p compact
## 2 audi a4 1.8 1999 4 manual(m5) f 21 29 p compact
## 3 audi a4 2 2008 4 manual(m6) f 20 31 p compact
## 4 audi a4 2 2008 4 auto(av) f 21 30 p compact
## 5 audi a4 2.8 1999 6 auto(15) f 16 26 p compact
## 6 audi a4 2.8 1999 6 manual(m5) f 18 26 p compact
## 7 audi a4 3.1 2008 6 auto(av) f 18 27 p compact
## 8 audi a4 quattro 1.8 1999 4 manual(m5) 4 18 26 p compact
```

```
## 9 audi a4 quattro 1.8 1999 4 auto(15) 4 16 25 p compact
## 10 audi a4 quattro 2 2008 4 manual(m6) 4 20 28 p compact
## # ... with 224 more rows
```

2.7 mutate() para colunas

```
mutate(dados, sqrt_cty = sqrt(cty))
```

```
## # A tibble: 234 x 12
##   manufac~1 model displ year   cyl trans drv   cty   hwy fl   class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct> <dbl>
## 1 audi      a4      1.8  1999   4 auto~ f    18   29 p    comp~ 4.24
## 2 audi      a4      1.8  1999   4 manu~ f    21   29 p    comp~ 4.58
## 3 audi      a4      2    2008   4 manu~ f    20   31 p    comp~ 4.47
## 4 audi      a4      2    2008   4 auto~ f    21   30 p    comp~ 4.58
## 5 audi      a4      2.8  1999   6 auto~ f    16   26 p    comp~ 4
## 6 audi      a4      2.8  1999   6 manu~ f    18   26 p    comp~ 4.24
## 7 audi      a4      3.1  2008   6 auto~ f    18   27 p    comp~ 4.24
## 8 audi      a4 q~    1.8  1999   4 manu~ 4    18   26 p    comp~ 4.24
## 9 audi      a4 q~    1.8  1999   4 auto~ 4    16   25 p    comp~ 4
## 10 audi     a4 q~    2    2008   4 manu~ 4    20   28 p    comp~ 4.47
## # ... with 224 more rows, and abbreviated variable names 1: manufacturer,
## # 2: sqrt_cty
```

```
names(dados)
```

```
## [1] "manufacturer" "model"      "displ"      "year"      "cyl"
## [6] "trans"        "drv"        "cty"        "hwy"       "fl"
## [11] "class"
```

```
dados<- mutate(dados, sqrt_cty = sqrt(cty))
names(dados)
```

```
## [1] "manufacturer" "model"      "displ"      "year"      "cyl"
## [6] "trans"        "drv"        "cty"        "hwy"       "fl"
## [11] "class"        "sqrt_cty"
```

```
dados <- mutate(dados,
`soma de variáveis` = (cty + hwy) / 2)
names(dados)
```

```
## [1] "manufacturer" "model"      "displ"
## [4] "year"         "cyl"        "trans"
## [7] "drv"         "cty"        "hwy"
## [10] "fl"          "class"      "sqrt_cty"
## [13] "soma de variáveis"
```

```
dados <- mutate(dados,
  car = paste(manufacturer, model, sep = " "),
  `cyl / trans` = paste(cyl, " cylinders", " / ", trans, " transmission", sep = " "),
  dados
```

```
## # A tibble: 234 x 15
##   manufac~1 model displ  year  cyl trans drv   cty  hwy fl   class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct> <dbl>
## 1 audi      a4      1.8  1999    4 auto~ f    18   29 p   comp~  4.24
## 2 audi      a4      1.8  1999    4 manu~ f    21   29 p   comp~  4.58
## 3 audi      a4      2    2008    4 manu~ f    20   31 p   comp~  4.47
## 4 audi      a4      2    2008    4 auto~ f    21   30 p   comp~  4.58
## 5 audi      a4      2.8  1999    6 auto~ f    16   26 p   comp~  4
## 6 audi      a4      2.8  1999    6 manu~ f    18   26 p   comp~  4.24
## 7 audi      a4      3.1  2008    6 auto~ f    18   27 p   comp~  4.24
## 8 audi      a4 q~    1.8  1999    4 manu~ 4    18   26 p   comp~  4.24
## 9 audi      a4 q~    1.8  1999    4 auto~ 4    16   25 p   comp~  4
## 10 audi     a4 q~    2    2008    4 manu~ 4    20   28 p   comp~  4.47
## # ... with 224 more rows, 3 more variables: `soma de variáveis` <dbl>,
## #   car <chr>, `cyl / trans` <chr>, and abbreviated variable names
## #   1: manufacturer, 2: sqrt_cty
```

2.8 transmute()

```
transmute(dados,
  `avg miles per gallon` = (cty + hwy) / 2)
```

```
## # A tibble: 234 x 1
##   `avg miles per gallon`
##   <dbl>
## 1          23.5
## 2          25
## 3          25.5
## 4          25.5
## 5          21
## 6          22
## 7          22.5
## 8          22
## 9          20.5
## 10         24
## # ... with 224 more rows
```

```
transmute(dados,
  car = paste(manufacturer, model, sep = " "),
  `cyl / trans` = paste(cyl, " cylinders", " / ", trans, " transmission", sep = " "),
  dados
```

```
## # A tibble: 234 x 2
##   car                `cyl / trans`
##   <chr>              <chr>
## 1 audi a4           4 cylinders / auto(l5) transmission
## 2 audi a4           4 cylinders / manual(m5) transmission
## 3 audi a4           4 cylinders / manual(m6) transmission
## 4 audi a4           4 cylinders / auto(av) transmission
## 5 audi a4           6 cylinders / auto(l5) transmission
## 6 audi a4           6 cylinders / manual(m5) transmission
## 7 audi a4           6 cylinders / auto(av) transmission
## 8 audi a4 quattro 4 cylinders / manual(m5) transmission
## 9 audi a4 quattro 4 cylinders / auto(l5) transmission
## 10 audi a4 quattro 4 cylinders / manual(m6) transmission
## # ... with 224 more rows
```

2.9 filter() para linhas

```
filter(dados, manufacturer == "audi")
```

```
## # A tibble: 18 x 15
##   manufac~1 model displ year   cyl trans drv   cty   hwy fl   class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct> <dbl>
## 1 audi      a4      1.8  1999     4 auto~ f     18    29 p   comp~  4.24
## 2 audi      a4      1.8  1999     4 manu~ f     21    29 p   comp~  4.58
## 3 audi      a4      2    2008     4 manu~ f     20    31 p   comp~  4.47
## 4 audi      a4      2    2008     4 auto~ f     21    30 p   comp~  4.58
## 5 audi      a4      2.8  1999     6 auto~ f     16    26 p   comp~  4
## 6 audi      a4      2.8  1999     6 manu~ f     18    26 p   comp~  4.24
## 7 audi      a4      3.1  2008     6 auto~ f     18    27 p   comp~  4.24
## 8 audi      a4 q~    1.8  1999     4 manu~ 4     18    26 p   comp~  4.24
## 9 audi      a4 q~    1.8  1999     4 auto~ 4     16    25 p   comp~  4
## 10 audi     a4 q~    2    2008     4 manu~ 4     20    28 p   comp~  4.47
## 11 audi     a4 q~    2    2008     4 auto~ 4     19    27 p   comp~  4.36
## 12 audi     a4 q~    2.8  1999     6 auto~ 4     15    25 p   comp~  3.87
## 13 audi     a4 q~    2.8  1999     6 manu~ 4     17    25 p   comp~  4.12
## 14 audi     a4 q~    3.1  2008     6 auto~ 4     17    25 p   comp~  4.12
## 15 audi     a4 q~    3.1  2008     6 manu~ 4     15    25 p   comp~  3.87
## 16 audi     a6 q~    2.8  1999     6 auto~ 4     15    24 p   mids~  3.87
## 17 audi     a6 q~    3.1  2008     6 auto~ 4     17    25 p   mids~  4.12
## 18 audi     a6 q~    4.2  2008     8 auto~ 4     16    23 p   mids~  4
## # ... with 3 more variables: `soma de variáveis` <dbl>, car <chr>,
## #   `cyl / trans` <chr>, and abbreviated variable names 1: manufacturer,
## #   2: sqrt_cty
```

```
filter(dados, manufacturer == "audi" & year == "1999")
```

```
## # A tibble: 9 x 15
##   manufact~1 model displ  year   cyl trans drv   cty   hwy fl   class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct>   <dbl>
## 1 audi      a4      1.8  1999    4 auto~ f    18    29 p    comp~  4.24
## 2 audi      a4      1.8  1999    4 manu~ f    21    29 p    comp~  4.58
## 3 audi      a4      2.8  1999    6 auto~ f    16    26 p    comp~  4
## 4 audi      a4      2.8  1999    6 manu~ f    18    26 p    comp~  4.24
## 5 audi      a4 q~    1.8  1999    4 manu~ 4    18    26 p    comp~  4.24
## 6 audi      a4 q~    1.8  1999    4 auto~ 4    16    25 p    comp~  4
## 7 audi      a4 q~    2.8  1999    6 auto~ 4    15    25 p    comp~  3.87
## 8 audi      a4 q~    2.8  1999    6 manu~ 4    17    25 p    comp~  4.12
## 9 audi      a6 q~    2.8  1999    6 auto~ 4    15    24 p    mids~  3.87
## # ... with 3 more variables: `soma de variáveis` <dbl>, car <chr>,
## #   `cyl / trans` <chr>, and abbreviated variable names 1: manufacturer,
## #   2: sqrt_cty
```

```
filter(dados, manufacturer == "audi", year == 1999)
```

```
## # A tibble: 9 x 15
##   manufact~1 model displ  year   cyl trans drv   cty   hwy fl   class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct>   <dbl>
## 1 audi      a4      1.8  1999    4 auto~ f    18    29 p    comp~  4.24
## 2 audi      a4      1.8  1999    4 manu~ f    21    29 p    comp~  4.58
## 3 audi      a4      2.8  1999    6 auto~ f    16    26 p    comp~  4
## 4 audi      a4      2.8  1999    6 manu~ f    18    26 p    comp~  4.24
## 5 audi      a4 q~    1.8  1999    4 manu~ 4    18    26 p    comp~  4.24
## 6 audi      a4 q~    1.8  1999    4 auto~ 4    16    25 p    comp~  4
## 7 audi      a4 q~    2.8  1999    6 auto~ 4    15    25 p    comp~  3.87
## 8 audi      a4 q~    2.8  1999    6 manu~ 4    17    25 p    comp~  4.12
## 9 audi      a6 q~    2.8  1999    6 auto~ 4    15    24 p    mids~  3.87
## # ... with 3 more variables: `soma de variáveis` <dbl>, car <chr>,
## #   `cyl / trans` <chr>, and abbreviated variable names 1: manufacturer,
## #   2: sqrt_cty
```

```
filter(dados, manufacturer == "audi" | manufacturer == "dodge") %>%
  print(n = 20)
```

```
## # A tibble: 55 x 15
##   manufac~1 model displ  year   cyl trans drv   cty   hwy fl   class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct>   <dbl>
## 1 audi      a4      1.8  1999    4 auto~ f    18    29 p    comp~  4.24
## 2 audi      a4      1.8  1999    4 manu~ f    21    29 p    comp~  4.58
## 3 audi      a4      2    2008    4 manu~ f    20    31 p    comp~  4.47
## 4 audi      a4      2    2008    4 auto~ f    21    30 p    comp~  4.58
## 5 audi      a4      2.8  1999    6 auto~ f    16    26 p    comp~  4
```

```
## 6 audi      a4      2.8 1999      6 manu~ f      18      26 p      comp~ 4.24
## 7 audi      a4      3.1 2008      6 auto~ f      18      27 p      comp~ 4.24
## 8 audi      a4 q~   1.8 1999      4 manu~ 4      18      26 p      comp~ 4.24
## 9 audi      a4 q~   1.8 1999      4 auto~ 4      16      25 p      comp~ 4
## 10 audi     a4 q~   2    2008      4 manu~ 4      20      28 p      comp~ 4.47
## 11 audi     a4 q~   2    2008      4 auto~ 4      19      27 p      comp~ 4.36
## 12 audi     a4 q~   2.8 1999      6 auto~ 4      15      25 p      comp~ 3.87
## 13 audi     a4 q~   2.8 1999      6 manu~ 4      17      25 p      comp~ 4.12
## 14 audi     a4 q~   3.1 2008      6 auto~ 4      17      25 p      comp~ 4.12
## 15 audi     a4 q~   3.1 2008      6 manu~ 4      15      25 p      comp~ 3.87
## 16 audi     a6 q~   2.8 1999      6 auto~ 4      15      24 p      mids~ 3.87
## 17 audi     a6 q~   3.1 2008      6 auto~ 4      17      25 p      mids~ 4.12
## 18 audi     a6 q~   4.2 2008      8 auto~ 4      16      23 p      mids~ 4
## 19 dodge    cara~   2.4 1999      4 auto~ f      18      24 r      mini~ 4.24
## 20 dodge    cara~   3    1999      6 auto~ f      17      24 r      mini~ 4.12
## # ... with 35 more rows, 3 more variables: `soma de variáveis` <dbl>,
## #   car <chr>, `cyl / trans` <chr>, and abbreviated variable names
## #   1: manufacturer, 2: sqrt_cty

filter(dados, manufacturer %in% c("audi", "dodge")) %>%
  print(n = 20)
```

```
## # A tibble: 55 x 15
##   manufac~1 model displ  year   cyl trans drv   cty   hwy fl   class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct> <dbl>
## 1 audi      a4      1.8 1999     4 auto~ f     18    29 p   comp~ 4.24
## 2 audi      a4      1.8 1999     4 manu~ f     21    29 p   comp~ 4.58
## 3 audi      a4      2    2008     4 manu~ f     20    31 p   comp~ 4.47
## 4 audi      a4      2    2008     4 auto~ f     21    30 p   comp~ 4.58
## 5 audi      a4      2.8 1999     6 auto~ f     16    26 p   comp~ 4
## 6 audi      a4      2.8 1999     6 manu~ f     18    26 p   comp~ 4.24
## 7 audi      a4      3.1 2008     6 auto~ f     18    27 p   comp~ 4.24
## 8 audi      a4 q~   1.8 1999     4 manu~ 4     18    26 p   comp~ 4.24
## 9 audi      a4 q~   1.8 1999     4 auto~ 4     16    25 p   comp~ 4
## 10 audi     a4 q~   2    2008     4 manu~ 4     20    28 p   comp~ 4.47
## 11 audi     a4 q~   2    2008     4 auto~ 4     19    27 p   comp~ 4.36
## 12 audi     a4 q~   2.8 1999     6 auto~ 4     15    25 p   comp~ 3.87
## 13 audi     a4 q~   2.8 1999     6 manu~ 4     17    25 p   comp~ 4.12
## 14 audi     a4 q~   3.1 2008     6 auto~ 4     17    25 p   comp~ 4.12
## 15 audi     a4 q~   3.1 2008     6 manu~ 4     15    25 p   comp~ 3.87
## 16 audi     a6 q~   2.8 1999     6 auto~ 4     15    24 p   mids~ 3.87
## 17 audi     a6 q~   3.1 2008     6 auto~ 4     17    25 p   mids~ 4.12
## 18 audi     a6 q~   4.2 2008     8 auto~ 4     16    23 p   mids~ 4
## 19 dodge    cara~   2.4 1999     4 auto~ f     18    24 r   mini~ 4.24
## 20 dodge    cara~   3    1999     6 auto~ f     17    24 r   mini~ 4.12
## # ... with 35 more rows, 3 more variables: `soma de variáveis` <dbl>,
```

```
## #   car <chr>, `cyl / trans` <chr>, and abbreviated variable names
## #   1: manufacturer, 2: sqrt_cty
```

```
filter(dados, hwy >= 30) %>%
  select(hwy) %>%
  print(n = 26)
```

```
## # A tibble: 26 x 1
```

```
##       hwy
```

```
##   <int>
```

```
## 1     31
```

```
## 2     30
```

```
## 3     30
```

```
## 4     33
```

```
## 5     32
```

```
## 6     32
```

```
## 7     32
```

```
## 8     34
```

```
## 9     36
```

```
## 10    36
```

```
## 11    30
```

```
## 12    31
```

```
## 13    31
```

```
## 14    32
```

```
## 15    31
```

```
## 16    31
```

```
## 17    31
```

```
## 18    31
```

```
## 19    30
```

```
## 20    33
```

```
## 21    35
```

```
## 22    37
```

```
## 23    35
```

```
## 24    44
```

```
## 25    44
```

```
## 26    41
```

```
filter(dados, year != 1999) %>%
  select(year) %>%
  print(n = 30)
```

```
## # A tibble: 117 x 1
```

```
##       year
```

```
##   <int>
```

```
## 1  2008
```

```
## 2  2008
```

```
## 3  2008
```



```
## 4 2008
## 5 2008
## 6 2008
## 7 2008
## 8 2008
## 9 2008
## 10 2008
## 11 2008
## 12 2008
## 13 2008
## 14 2008
## 15 2008
## 16 2008
## 17 2008
## 18 2008
## 19 2008
## 20 2008
## 21 2008
## 22 2008
## 23 2008
## 24 2008
## 25 2008
## 26 2008
## 27 2008
## 28 2008
## 29 2008
## 30 2008
## # ... with 87 more rows
filter(dados, between(cty, 15, 22))
```

```
## # A tibble: 143 x 15
##   manufac~1 model displ  year   cyl trans drv   cty   hwy fl   class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct> <dbl>
## 1 audi      a4      1.8  1999   4 auto~ f    18    29 p    comp~ 4.24
## 2 audi      a4      1.8  1999   4 manu~ f    21    29 p    comp~ 4.58
## 3 audi      a4      2    2008   4 manu~ f    20    31 p    comp~ 4.47
## 4 audi      a4      2    2008   4 auto~ f    21    30 p    comp~ 4.58
## 5 audi      a4      2.8  1999   6 auto~ f    16    26 p    comp~ 4
## 6 audi      a4      2.8  1999   6 manu~ f    18    26 p    comp~ 4.24
## 7 audi      a4      3.1  2008   6 auto~ f    18    27 p    comp~ 4.24
## 8 audi      a4 q~    1.8  1999   4 manu~ 4    18    26 p    comp~ 4.24
## 9 audi      a4 q~    1.8  1999   4 auto~ 4    16    25 p    comp~ 4
## 10 audi     a4 q~    2    2008   4 manu~ 4    20    28 p    comp~ 4.47
## # ... with 133 more rows, 3 more variables: `soma de variáveis` <dbl>,
## #   car <chr>, `cyl / trans` <chr>, and abbreviated variable names
```

```
## # 1: manufacturer, 2: sqrt_cty
```

2.10 slice() para linhas

```
slice(dados, 1:5)
```

```
## # A tibble: 5 x 15
##   manufact~1 model displ  year   cyl trans drv   cty   hwy fl   class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct> <dbl>
## 1 audi      a4      1.8  1999   4 auto~ f    18    29 p    comp~  4.24
## 2 audi      a4      1.8  1999   4 manu~ f    21    29 p    comp~  4.58
## 3 audi      a4      2    2008   4 manu~ f    20    31 p    comp~  4.47
## 4 audi      a4      2    2008   4 auto~ f    21    30 p    comp~  4.58
## 5 audi      a4      2.8  1999   6 auto~ f    16    26 p    comp~  4
## # ... with 3 more variables: `soma de variáveis` <dbl>, car <chr>,
## #   `cyl / trans` <chr>, and abbreviated variable names 1: manufacturer,
## #   2: sqrt_cty
```

```
# dados[1:5,]
```

```
slice(dados, 20:30)
```

```
## # A tibble: 11 x 15
##   manufac~1 model displ  year   cyl trans drv   cty   hwy fl   class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct> <dbl>
## 1 chevrolet c150~  5.3  2008   8 auto~ r    11    15 e    suv    3.32
## 2 chevrolet c150~  5.3  2008   8 auto~ r    14    20 r    suv    3.74
## 3 chevrolet c150~  5.7  1999   8 auto~ r    13    17 r    suv    3.61
## 4 chevrolet c150~  6    2008   8 auto~ r    12    17 r    suv    3.46
## 5 chevrolet corv~  5.7  1999   8 manu~ r    16    26 p    2sea~  4
## 6 chevrolet corv~  5.7  1999   8 auto~ r    15    23 p    2sea~  3.87
## 7 chevrolet corv~  6.2  2008   8 manu~ r    16    26 p    2sea~  4
## 8 chevrolet corv~  6.2  2008   8 auto~ r    15    25 p    2sea~  3.87
## 9 chevrolet corv~  7    2008   8 manu~ r    15    24 p    2sea~  3.87
## 10 chevrolet k150~  5.3  2008   8 auto~ 4    14    19 r    suv    3.74
## 11 chevrolet k150~  5.3  2008   8 auto~ 4    11    14 e    suv    3.32
## # ... with 3 more variables: `soma de variáveis` <dbl>, car <chr>,
## #   `cyl / trans` <chr>, and abbreviated variable names 1: manufacturer,
## #   2: sqrt_cty
```

```
# dados[20:30,]
```

2.11 arrange() para linhas

```
# ordenar "displ" de menor a maior
arrange(dados, displ)
```

```
## # A tibble: 234 x 15
##   manufac~1 model displ  year   cyl trans  drv      cty   hwy fl      class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct>    <dbl>
## 1 honda      civic  1.6  1999     4 manu~ f      28    33 r      subc~    5.29
## 2 honda      civic  1.6  1999     4 auto~ f      24    32 r      subc~    4.90
## 3 honda      civic  1.6  1999     4 manu~ f      25    32 r      subc~     5
## 4 honda      civic  1.6  1999     4 manu~ f      23    29 p      subc~    4.80
## 5 honda      civic  1.6  1999     4 auto~ f      24    32 r      subc~    4.90
## 6 audi       a4      1.8  1999     4 auto~ f      18    29 p      comp~    4.24
## 7 audi       a4      1.8  1999     4 manu~ f      21    29 p      comp~    4.58
## 8 audi       a4 q~   1.8  1999     4 manu~ 4      18    26 p      comp~    4.24
## 9 audi       a4 q~   1.8  1999     4 auto~ 4      16    25 p      comp~     4
## 10 honda     civic  1.8  2008     4 manu~ f      26    34 r      subc~    5.10
## # ... with 224 more rows, 3 more variables: `soma de variáveis` <dbl>,
## #   car <chr>, `cyl / trans` <chr>, and abbreviated variable names
## #   1: manufacturer, 2: sqrt_cty

arrange(dados, displ) %>%
  print(n=20)
```

```
## # A tibble: 234 x 15
##   manufac~1 model displ  year   cyl trans  drv      cty   hwy fl      class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct>    <dbl>
## 1 honda      civic  1.6  1999     4 manu~ f      28    33 r      subc~    5.29
## 2 honda      civic  1.6  1999     4 auto~ f      24    32 r      subc~    4.90
## 3 honda      civic  1.6  1999     4 manu~ f      25    32 r      subc~     5
## 4 honda      civic  1.6  1999     4 manu~ f      23    29 p      subc~    4.80
## 5 honda      civic  1.6  1999     4 auto~ f      24    32 r      subc~    4.90
## 6 audi       a4      1.8  1999     4 auto~ f      18    29 p      comp~    4.24
## 7 audi       a4      1.8  1999     4 manu~ f      21    29 p      comp~    4.58
## 8 audi       a4 q~   1.8  1999     4 manu~ 4      18    26 p      comp~    4.24
## 9 audi       a4 q~   1.8  1999     4 auto~ 4      16    25 p      comp~     4
## 10 honda     civic  1.8  2008     4 manu~ f      26    34 r      subc~    5.10
## 11 honda     civic  1.8  2008     4 auto~ f      25    36 r      subc~     5
## 12 honda     civic  1.8  2008     4 auto~ f      24    36 c      subc~    4.90
## 13 toyota    coro~   1.8  1999     4 auto~ f      24    30 r      comp~    4.90
## 14 toyota    coro~   1.8  1999     4 auto~ f      24    33 r      comp~    4.90
## 15 toyota    coro~   1.8  1999     4 manu~ f      26    35 r      comp~    5.10
## 16 toyota    coro~   1.8  2008     4 manu~ f      28    37 r      comp~    5.29
## 17 toyota    coro~   1.8  2008     4 auto~ f      26    35 r      comp~    5.10
## 18 volkswag~ pass~   1.8  1999     4 manu~ f      21    29 p      mids~    4.58
```

```
## 19 volkswag~ pass~ 1.8 1999 4 auto~ f 18 29 p mids~ 4.24
## 20 volkswag~ jetta 1.9 1999 4 manu~ f 33 44 d comp~ 5.74
## # ... with 214 more rows, 3 more variables: `soma de variáveis` <dbl>,
## # car <chr>, `cyl / trans` <chr>, and abbreviated variable names
## # 1: manufacturer, 2: sqrt_cty
```

```
# ordenar "displ" de maior a menor
arrange(dados, desc(displ))
```

```
## # A tibble: 234 x 15
##   manufac~1 model displ year cyl trans drv cty hwy fl class sqrt_~2
##   <fct> <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct> <dbl>
## 1 chevrolet corv~ 7 2008 8 manu~ r 15 24 p 2sea~ 3.87
## 2 chevrolet k150~ 6.5 1999 8 auto~ 4 14 17 d suv 3.74
## 3 chevrolet corv~ 6.2 2008 8 manu~ r 16 26 p 2sea~ 4
## 4 chevrolet corv~ 6.2 2008 8 auto~ r 15 25 p 2sea~ 3.87
## 5 jeep gran~ 6.1 2008 8 auto~ 4 11 14 p suv 3.32
## 6 chevrolet c150~ 6 2008 8 auto~ r 12 17 r suv 3.46
## 7 dodge dura~ 5.9 1999 8 auto~ 4 11 15 r suv 3.32
## 8 dodge ram ~ 5.9 1999 8 auto~ 4 11 15 r pick~ 3.32
## 9 chevrolet c150~ 5.7 1999 8 auto~ r 13 17 r suv 3.61
## 10 chevrolet corv~ 5.7 1999 8 manu~ r 16 26 p 2sea~ 4
## # ... with 224 more rows, 3 more variables: `soma de variáveis` <dbl>,
## # car <chr>, `cyl / trans` <chr>, and abbreviated variable names
## # 1: manufacturer, 2: sqrt_cty
```

```
arrange(dados, desc(displ)) %>%
  print(n=20)
```

```
## # A tibble: 234 x 15
##   manufac~1 model displ year cyl trans drv cty hwy fl class sqrt_~2
##   <fct> <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct> <dbl>
## 1 chevrolet corv~ 7 2008 8 manu~ r 15 24 p 2sea~ 3.87
## 2 chevrolet k150~ 6.5 1999 8 auto~ 4 14 17 d suv 3.74
## 3 chevrolet corv~ 6.2 2008 8 manu~ r 16 26 p 2sea~ 4
## 4 chevrolet corv~ 6.2 2008 8 auto~ r 15 25 p 2sea~ 3.87
## 5 jeep gran~ 6.1 2008 8 auto~ 4 11 14 p suv 3.32
## 6 chevrolet c150~ 6 2008 8 auto~ r 12 17 r suv 3.46
## 7 dodge dura~ 5.9 1999 8 auto~ 4 11 15 r suv 3.32
## 8 dodge ram ~ 5.9 1999 8 auto~ 4 11 15 r pick~ 3.32
## 9 chevrolet c150~ 5.7 1999 8 auto~ r 13 17 r suv 3.61
## 10 chevrolet corv~ 5.7 1999 8 manu~ r 16 26 p 2sea~ 4
## 11 chevrolet corv~ 5.7 1999 8 auto~ r 15 23 p 2sea~ 3.87
## 12 chevrolet k150~ 5.7 1999 8 auto~ 4 11 15 r suv 3.32
## 13 dodge dura~ 5.7 2008 8 auto~ 4 13 18 r suv 3.61
## 14 dodge ram ~ 5.7 2008 8 auto~ 4 13 17 r pick~ 3.61
## 15 jeep gran~ 5.7 2008 8 auto~ 4 13 18 r suv 3.61
```

```
## 16 toyota    land~  5.7  2008    8 auto~ 4      13    18 r    suv    3.61
## 17 nissan    path~  5.6  2008    8 auto~ 4      12    18 p    suv    3.46
## 18 ford     expe~  5.4  1999    8 auto~ r     11    17 r    suv    3.32
## 19 ford     expe~  5.4  2008    8 auto~ r     12    18 r    suv    3.46
## 20 ford     f150~  5.4  1999    8 auto~ 4      11    15 r    pick~  3.32
## # ... with 214 more rows, 3 more variables: `soma de variáveis` <dbl>,
## #   car <chr>, `cyl / trans` <chr>, and abbreviated variable names
## #   1: manufacturer, 2: sqrt_cty
```

```
select(dados, displ, cty) %>%
  arrange(displ, cty) %>%
  print(n = 20)
```

```
## # A tibble: 234 x 2
##   displ  cty
##   <dbl> <int>
## 1  1.6    23
## 2  1.6    24
## 3  1.6    24
## 4  1.6    25
## 5  1.6    28
## 6  1.8    16
## 7  1.8    18
## 8  1.8    18
## 9  1.8    18
## 10 1.8    21
## 11 1.8    21
## 12 1.8    24
## 13 1.8    24
## 14 1.8    24
## 15 1.8    25
## 16 1.8    26
## 17 1.8    26
## 18 1.8    26
## 19 1.8    28
## 20 1.9    29
## # ... with 214 more rows
```

```
select(dados, displ, cty) %>%
  arrange(displ, desc(cty)) %>%
  print(n = 20)
```

```
## # A tibble: 234 x 2
##   displ  cty
##   <dbl> <int>
## 1  1.6    28
## 2  1.6    25
```

```
## 3 1.6 24
## 4 1.6 24
## 5 1.6 23
## 6 1.8 28
## 7 1.8 26
## 8 1.8 26
## 9 1.8 26
## 10 1.8 25
## 11 1.8 24
## 12 1.8 24
## 13 1.8 24
## 14 1.8 21
## 15 1.8 21
## 16 1.8 18
## 17 1.8 18
## 18 1.8 18
## 19 1.8 16
## 20 1.9 35
## # ... with 214 more rows
```

2.12 distinct() para linhas

```
dados_exemplo <- data.frame(id = 1:3,
                             name = c("John", "Max", "Julia"))
dados_exemplo

##   id name
## 1  1 John
## 2  2  Max
## 3  3 Julia

# bind_rows == rbind()
dados_exemplo <- bind_rows(dados_exemplo, slice(dados_exemplo, 2))
dados_exemplo

##   id name
## 1  1 John
## 2  2  Max
## 3  3 Julia
## 4  2  Max

distinct(dados_exemplo)

##   id name
## 1  1 John
## 2  2  Max
```

```
## 3 3 Julia
dados_exemplo2 <- data.frame(id = c(1,1,2),
                             name = c("John", "Max", "Julia"))
dados_exemplo2
```

```
##   id  name
## 1  1  John
## 2  1   Max
## 3  2  Julia
distinct(dados_exemplo2)
```

```
##   id  name
## 1  1  John
## 2  1   Max
## 3  2  Julia
dados_duplicados <- select(dados, manufacturer, model)
dados_duplicados
```

```
## # A tibble: 234 x 2
##   manufacturer model
##   <fct>         <fct>
## 1 audi          a4
## 2 audi          a4
## 3 audi          a4
## 4 audi          a4
## 5 audi          a4
## 6 audi          a4
## 7 audi          a4
## 8 audi          a4 quattro
## 9 audi          a4 quattro
## 10 audi          a4 quattro
## # ... with 224 more rows
dados_ao_duplicados <- distinct(dados_duplicados)
dados_ao_duplicados
```

```
## # A tibble: 38 x 2
##   manufacturer model
##   <fct>         <fct>
## 1 audi          a4
## 2 audi          a4 quattro
## 3 audi          a6 quattro
## 4 chevrolet     c1500 suburban 2wd
## 5 chevrolet     corvette
## 6 chevrolet     k1500 tahoe 4wd
```

```
## 7 chevrolet    malibu
## 8 dodge        caravan 2wd
## 9 dodge        dakota pickup 4wd
## 10 dodge       durango 4wd
## # ... with 28 more rows
```

2.13 summarise()

```
summarise(dados, `média hwy` = mean(hwy))
```

```
## # A tibble: 1 x 1
##   `média hwy`
##         <dbl>
## 1         23.4
```

```
summarise(dados,
  `num. de dados` = n(),
  `num. modelos` = n_distinct(model))
```

```
## # A tibble: 1 x 2
##   `num. de dados` `num. modelos`
##         <int>         <int>
## 1           234             38
```

```
# levels(dados$model)
```

```
summarise(dados,
  `mín. hwy` = min(hwy, na.rm = TRUE),
  `mín. cty` = min(cty, na.rm = TRUE),
  `máx. hwy` = max(hwy, na.rm = TRUE),
  `máx. cty` = max(cty, na.rm = TRUE))
```

```
## # A tibble: 1 x 4
##   `mín. hwy` `mín. cty` `máx. hwy` `máx. cty`
##         <int>    <int>    <int>    <int>
## 1         12         9        44        35
```

```
dados %>%
```

```
  summarise_at(c("hwy", "cty"), list(min, max), na.rm = TRUE)
```

```
## # A tibble: 1 x 4
##   hwy_fn1 cty_fn1 hwy_fn2 cty_fn2
##     <int>  <int>  <int>  <int>
## 1      12     9      44     35
```

```
dados %>%
```

```
  summarise_if(is.numeric, list(min, max), na.rm = TRUE)
```

```
## # A tibble: 1 x 14
```



```
##   displ_fn1 year_fn1 cyl_fn1 cty_fn1 hwy_fn1 sqrt_cty_~1 soma ~2 displ~3 year_~4
##   <dbl>    <int>    <int>    <int>    <int>    <dbl>    <dbl>    <dbl>    <int>
## 1      1.6     1999      4      9      12      3     10.5      7     2008
## # ... with 5 more variables: cyl_fn2 <int>, cty_fn2 <int>, hwy_fn2 <int>,
## #   sqrt_cty_fn2 <dbl>, `soma de variáveis_fn2` <dbl>, and abbreviated variable
## #   names 1: sqrt_cty_fn1, 2: `soma de variáveis_fn1`, 3: displ_fn2,
## #   4: year_fn2
```

```
dados %>%
  summarise_if(is.numeric, min, na.rm = TRUE)
```

```
## # A tibble: 1 x 7
##   displ year   cyl   cty   hwy sqrt_cty `soma de variáveis`
##   <dbl> <int> <int> <int> <int>   <dbl>         <dbl>
## 1   1.6  1999     4     9    12     3         10.5
```

```
dados %>%
  summarise_if(is.numeric, max, na.rm = TRUE)
```

```
## # A tibble: 1 x 7
##   displ year   cyl   cty   hwy sqrt_cty `soma de variáveis`
##   <dbl> <int> <int> <int> <int>   <dbl>         <dbl>
## 1     7  2008     8    35    44    5.92         39.5
```

```
Tiago<- function(dados){
  sd(dados)/mean(dados)
}
```

```
dados %>%
  summarise_if(is.numeric, Tiago)
```

```
## # A tibble: 1 x 7
##   displ   year   cyl   cty   hwy sqrt_cty `soma de variáveis`
##   <dbl>   <dbl> <dbl> <dbl> <dbl>   <dbl>         <dbl>
## 1 0.372 0.00225 0.274 0.252 0.254    0.125         0.251
```

2.14 group_by()

```
group_by(dados, manufacturer)
```

```
## # A tibble: 234 x 15
## # Groups:   manufacturer [15]
##   manufac~1 model displ year   cyl trans drv   cty   hwy fl   class sqrt_~2
##   <fct>    <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct>    <dbl>
## 1 audi     a4      1.8  1999     4 auto~ f     18    29 p   comp~    4.24
## 2 audi     a4      1.8  1999     4 manu~ f     21    29 p   comp~    4.58
## 3 audi     a4      2    2008     4 manu~ f     20    31 p   comp~    4.47
```

```
## 4 audi      a4      2      2008      4 auto~ f      21      30 p      comp~      4.58
## 5 audi      a4      2.8    1999      6 auto~ f      16      26 p      comp~      4
## 6 audi      a4      2.8    1999      6 manu~ f      18      26 p      comp~      4.24
## 7 audi      a4      3.1    2008      6 auto~ f      18      27 p      comp~      4.24
## 8 audi      a4 q~    1.8    1999      4 manu~ 4      18      26 p      comp~      4.24
## 9 audi      a4 q~    1.8    1999      4 auto~ 4      16      25 p      comp~      4
## 10 audi     a4 q~    2      2008      4 manu~ 4      20      28 p      comp~      4.47
## # ... with 224 more rows, 3 more variables: `soma de variáveis` <dbl>,
## #   car <chr>, `cyl / trans` <chr>, and abbreviated variable names
## #   1: manufacturer, 2: sqrt_cty
```

```
dados %>%
  group_by(manufacturer) %>%
  summarise(`num. carros` = n())
```

```
## # A tibble: 15 x 2
##   manufacturer `num. carros`
##   <fct>         <int>
## 1 audi             18
## 2 chevrolet        19
## 3 dodge            37
## 4 ford             25
## 5 honda             9
## 6 hyundai          14
## 7 jeep             8
## 8 land rover        4
## 9 lincoln           3
## 10 mercury          4
## 11 nissan            13
## 12 pontiac           5
## 13 subaru            14
## 14 toyota            34
## 15 volkswagen       27
```

```
dados %>%
  group_by(model) %>%
  summarise(`média hwy` = mean(hwy),
            `min. hwy` = min(hwy),
            `max. hwy` = max(hwy))
```

```
## # A tibble: 38 x 4
##   model          `média hwy` `min. hwy` `max. hwy`
##   <fct>         <dbl>     <int>     <int>
## 1 4runner 4wd      18.8         17         20
## 2 a4              28.3         26         31
## 3 a4 quattro      25.8         25         28
## 4 a6 quattro      24          23         25
```

```
## 5 altima                28.7        26        32
## 6 c1500 suburban 2wd    17.8        15        20
## 7 camry                 28.3        26        31
## 8 camry solara          28.1        26        31
## 9 caravan 2wd          22.4        17        24
## 10 civic                32.6        29        36
## # ... with 28 more rows
```

2.15 count()

```
count(dados)
```

```
## # A tibble: 1 x 1
##       n
##   <int>
## 1   234
```

```
dados %>%
  group_by(manufacturer) %>%
  count()
```

```
## # A tibble: 15 x 2
## # Groups:   manufacturer [15]
##   manufacturer      n
##   <fct>          <int>
## 1 audi             18
## 2 chevrolet        19
## 3 dodge            37
## 4 ford             25
## 5 honda            9
## 6 hyundai          14
## 7 jeep             8
## 8 land rover        4
## 9 lincoln           3
## 10 mercury          4
## 11 nissan           13
## 12 pontiac          5
## 13 subaru           14
## 14 toyota           34
## 15 volkswagen       27
```

```
# Equivalente com o código anterior
```

```
dados %>%
  group_by(manufacturer) %>%
  summarise(cars = n())
```

```
## # A tibble: 15 x 2
```

```
##      manufacturer cars
##      <fct>          <int>
##  1 audi             18
##  2 chevrolet        19
##  3 dodge            37
##  4 ford             25
##  5 honda            9
##  6 hyundai          14
##  7 jeep             8
##  8 land rover       4
##  9 lincoln          3
## 10 mercury          4
## 11 nissan           13
## 12 pontiac          5
## 13 subaru           14
## 14 toyota           34
## 15 volkswagen       27
```

2.16 sample_n()

```
set.seed(567)
sample_n(dados, size = 10, replace = F)
```

```
## # A tibble: 10 x 15
##   manufac~1 model displ  year   cyl trans drv   cty   hwy fl   class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct> <dbl>
##  1 mercury  moun~    5   1999    8 auto~ 4     13    17 r    suv     3.61
##  2 chevrolet corv~    7   2008    8 manu~ r     15    24 p    2sea~  3.87
##  3 dodge    ram ~   4.7  2008    8 manu~ 4     12    16 r    pick~  3.46
##  4 toyota   land~   4.7  1999    8 auto~ 4     11    15 r    suv     3.32
##  5 volkswag~ jetta  2    1999    4 auto~ f     19    26 r    comp~  4.36
##  6 dodge    cara~   3.8  1999    6 auto~ f     15    21 r    mini~  3.87
##  7 honda    civic  1.8  2008    4 auto~ f     25    36 r    subc~    5
##  8 ford     must~   4.6  1999    8 auto~ r     15    21 r    subc~  3.87
##  9 chevrolet c150~   5.3  2008    8 auto~ r     14    20 r    suv     3.74
## 10 ford     expe~   5.4  1999    8 auto~ r     11    17 r    suv     3.32
## # ... with 3 more variables: `soma de variáveis` <dbl>, car <chr>,
## #   `cyl / trans` <chr>, and abbreviated variable names 1: manufacturer,
## #   2: sqrt_cty
```

```
sample_n(dados, size = 10, replace = T)
```

```
## # A tibble: 10 x 15
##   manufac~1 model displ  year   cyl trans drv   cty   hwy fl   class sqrt_~2
##   <fct>      <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct> <dbl>
```

```
## 1 chevrolet c150~ 5.3 2008 8 auto~ r 11 15 e suv 3.32
## 2 volkswag~ gti 2 2008 4 auto~ f 22 29 p comp~ 4.69
## 3 dodge dako~ 4.7 2008 8 auto~ 4 14 19 r pick~ 3.74
## 4 ford expl~ 4.6 2008 8 auto~ 4 13 19 r suv 3.61
## 5 dodge cara~ 3.8 2008 6 auto~ f 16 23 r mini~ 4
## 6 chevrolet k150~ 5.3 2008 8 auto~ 4 14 19 r suv 3.74
## 7 dodge dura~ 5.2 1999 8 auto~ 4 11 16 r suv 3.32
## 8 toyota camry 2.4 2008 4 manu~ f 21 31 r mids~ 4.58
## 9 toyota camry 3 1999 6 manu~ f 18 26 r mids~ 4.24
## 10 subaru impr~ 2.2 1999 4 auto~ 4 21 26 r subc~ 4.58
## # ... with 3 more variables: `soma de variáveis` <dbl>, car <chr>,
## # `cyl / trans` <chr>, and abbreviated variable names 1: manufacturer,
## # 2: sqrt_cty
```

2.17 sample_frac()

```
sample_frac(dados, size = 0.1, replace = F)
```

```
## # A tibble: 23 x 15
##   manufac~1 model displ year cyl trans drv cty hwy fl class sqrt_~2
##   <fct> <fct> <dbl> <int> <int> <fct> <fct> <int> <int> <fct> <fct> <dbl>
## 1 toyota coro~ 1.8 2008 4 manu~ f 28 37 r comp~ 5.29
## 2 lincoln navi~ 5.4 1999 8 auto~ r 11 17 r suv 3.32
## 3 honda civic 1.6 1999 4 auto~ f 24 32 r subc~ 4.90
## 4 audi a6 q~ 2.8 1999 6 auto~ 4 15 24 p mids~ 3.87
## 5 nissan path~ 4 2008 6 auto~ 4 14 20 p suv 3.74
## 6 toyota camry 3.5 2008 6 auto~ f 19 28 r mids~ 4.36
## 7 subaru impr~ 2.5 2008 4 auto~ 4 20 25 p comp~ 4.47
## 8 toyota toyo~ 3.4 1999 6 auto~ 4 15 19 r pick~ 3.87
## 9 audi a4 q~ 3.1 2008 6 manu~ 4 15 25 p comp~ 3.87
## 10 toyota coro~ 1.8 1999 4 manu~ f 26 35 r comp~ 5.10
## # ... with 13 more rows, 3 more variables: `soma de variáveis` <dbl>,
## # car <chr>, `cyl / trans` <chr>, and abbreviated variable names
## # 1: manufacturer, 2: sqrt_cty
```


Capítulo 3

ggplot2 (60 minutos)

3.1 Carrega pacotes a serem usados

```
#install.packages("tidyverse")
#install.packages("dplyr")
#install.packages("tidyr")
#install.packages("ggplot2")

library(tidyverse)
# Manipulação de dados
#library(dplyr)

# Visualização de gráficos
library(ggplot2)
library(gridExtra)
library(patchwork)
library(plotly)
library(esquisse)

# Para dados gráfico de perfis
library(nlme)
```

Alguns links

The R Graph Gallery

120 registered extensions available to explore

link 1: patchwork


link 2: patchwork

```
ls("package:ggplot2")
```


3.2 Lista de funções do pacote ggplot2

```
dados <- mpg  
ggplot(dados)
```


3.3 Primeiros passos usando geom_point




```
ggplot(dados, aes(x = cty, y = hwy))
```


```
# Alternativas  
ggplot(dados, aes(x = cty, y = hwy)) +  
  geom_point()
```




```
ggplot(dados) +  
  geom_point(aes(x = cty, y = hwy))
```




```
ggplot() +  
  geom_point(data = dados, aes(x = cty, y = hwy))
```




```
# Fim  
  
ggplot(dados, aes(x = cty, y = hwy)) +  
  geom_point(colour = "red")
```




```
ggplot(dados, aes(x = cty, y = hwy)) +  
  geom_point(colour = "red", size = 6)
```




```
ggplot(dados, aes(x = cty, y = hwy)) +  
  geom_point(colour = "red", size = 6, shape = 10)
```



```
# Alternativa  
ggplot(dados, aes(x = cty, y = hwy)) +  
  geom_point(colour = "red", size = 6, shape = "circle plus")
```



```
ggplot(dados, aes(x = cty, y = hwy)) +  
  geom_point(colour = "red", size = 6, shape = 10)+  
  labs(x = "cty (city miles per gallon hwy)",  
       y = "hwy (highway miles per gallon)",  
       title = "Pensar em algum título...",  
       subtitle = "Escrever alguma coisa")
```




3.3.1 Mais detalhes sobre `geom_point`


`geom_point()` understands the following aesthetics (required aesthetics are in bold):

- **x**
- **y**
- alpha
- colour
- fill
- group
- shape
- size
- stroke


```
ggplot(dados, aes(x = cty, y = hwy)) +  
  geom_point()
```




```
ggplot(dados, aes(x = cty, y = hwy, col = factor(year))) +  
  geom_point() +  
  labs(col = "year")
```




```
# Alternativa
ggplot(dados, aes(x = cty, y = hwy, col = factor(class))) +
  geom_point() +
  labs(col = "class")+
  scale_color_brewer(type = "qual")
```


```
ggplot(dados, aes(x = cty, y = hwy, col = factor(class))) +  
  geom_point() +  
  labs(col = "class") +  
  scale_color_brewer(type = "div")
```




```
ggplot(dados, aes(x = cty, y = hwy, col = factor(class))) +
  geom_point() +
  labs(col = "class")+
  scale_color_brewer(palette = "Set1", name = "Tipo de carro")+
  scale_y_continuous(breaks = seq(10,60,3))+
  scale_x_continuous(breaks = seq(10,40,3))+
  theme_minimal()
```




```
ggplot(dados, aes(x = cty, y = hwy, alpha = factor(year))) +
  geom_point() +
  labs(alpha = "year")
```




```
ggplot(dados, aes(x = cty, y = hwy, size = factor(year))) +  
  geom_point() +  
  labs(size = "year")
```




```
# Alternativa
ggplot(dados, aes(x = cty, y = hwy, col = cty <= 20)) +
  geom_point() +
  geom_vline(xintercept = 20)+
  labs(col = "year")
```



```
# Erro comum
ggplot(dados, aes(x = cty, y = hwy, col = "red")) +
  geom_point()+
  labs(col = "year")
```




```
ggplot(dados, aes(x = cty, y = hwy)) +  
  geom_point(col = "red")+  
  labs(col = "year")
```




```
# Fim Erro comum
```


```
ggplot(dados, aes(x = cty, y = hwy, shape = factor(year))) +  
  geom_point(col = "red") +  
  labs(shape = "year")
```




```
ggplot(dados, aes(x = cty, y = hwy, size = class)) +  
  geom_point() +  
  labs(size = "class")
```




```
ggplot(dados, aes(x = cty, y = hwy,  
                  size = class,  
                  col = class)) +  
  geom_point() +  
  guides(colour = guide_legend("Tipo de carro (color)"),  
         size = guide_legend("Tipo de carro (size)"))
```




```
ggplot(dados, aes(x = cty, y = hwy,
                  size = class,
                  col = class)) +
  geom_point() +
  labs(col = "Tipo de Carro", size = "Tipo de Carro")+
  guides(col = "legend")
```


```
v1<- ggplot(dados, aes(x = cty, y = hwy)) +  
  geom_point(col = "blue")+  
  geom_smooth(method = mgcv::gam,  
              formula = y ~ s(x, bs = "cs") ,  
              col = "red",  
              se = FALSE)  
v1
```




```
v2 <- ggplot(dados, aes(x = cty)) +  
  geom_boxplot(fill = "red")  
v2
```




```
v3 <- ggplot(dados, aes(x = cty)) +  
  geom_histogram(bins = 10, fill = "red", col = "blue", lwd=2)  
v3
```



```
v4<- ggplot(dados, aes(x = cty)) +  
  geom_histogram(aes(y = after_stat(density)),  
    bins = 10, fill = "yellow", col = "red") +  
  geom_density(col = "blue", lwd =3)  
v4
```



```
# Adicional (estadística experimental)
ggplot(dados, aes(x = drv, y = cty, col = drv)) +
  geom_boxplot()+
  theme_bw()+
  theme(legend.position = "none")
```




3.5 gridExtra e patchwork

Alguns links


link 1: patchwork

link 2: patchwork


```
# gridExtra
grid.arrange(v1, v2, v3, v4)
```




```
# patchwork
v1 + v2
```




v1 | v2




v1 / v2




```
v1 + v2 + v3
```




```
v1 + (v2 + v3)
```




v1 | (v2 / v3)




v1 / (v2 + v3)




v1 + v2 + v3 + v4




v1/(v2+v3+v4)




v1 + (v2 + v3 + v4)




v1 + v2 + (v3 + v4)




```
(v1 | v2 | v3) / v4
```



```
v5 <- ggplot(dados , aes(x = manufacturer)) +  
  geom_bar()+  
  theme(axis.text.x = element_text(angle = 45))  
v5
```




```
# Dúvidas no geom_col
v6 <- ggplot(dados , aes(x = manufacturer, y = cty)) +
  geom_col()+
  theme(axis.text.x = element_text(angle = 45))
v6
```




```
dados %>%
  select(manufacturer, cty) %>%
  group_by(manufacturer) %>%
  summarise(soma_total_cty = sum(cty),
            n = n())
```

```
## # A tibble: 15 x 3
##   manufacturer soma_total_cty     n
##   <chr>          <int> <int>
## 1 audi           317     18
## 2 chevrolet      285     19
## 3 dodge          486     37
## 4 ford           350     25
## 5 honda          220      9
## 6 hyundai        261     14
## 7 jeep           108      8
## 8 land rover      46      4
## 9 lincoln         34      3
## 10 mercury        53      4
## 11 nissan          235     13
## 12 pontiac         85      5
## 13 subaru          270     14
## 14 toyota          630     34
## 15 volkswagen      565     27
```





```
# dados %>%  
#   filter(manufacturer == "audi") %>%  
#   select(cty) %>%  
#   sum()  
v7 <- ggplot(dados , aes(x = cty)) +  
  geom_density()  
v7
```



```
v8 <- ggplot(dados, aes(x = cty, y = hwy)) +  
  geom_density2d()+  
  geom_point(colour = "red")  
v8
```



```
(v5+v6)/ (v7 + v8)
```



```
# Deixar pra depois...
```

```
dados %>%
```

```
  select(manufacturer, hwy, year) %>%
```



```
filter(manufacturer == "audi", year == "1999") %>%
summarise(media = max(hwy))
```

```
## # A tibble: 1 x 1
##   media
##   <int>
## 1     29

# plotly
ggplotly(
  ggplot(dados, aes(x = manufacturer, y = hwy, fill = factor(year))) +
    geom_col(position = "dodge") +
    labs(fill = "year") +
    theme(axis.text.x = element_text(angle = 45)))


dados %>% select(manufacturer, hwy, year) %>%
  group_by(manufacturer, year) %>%
  summarise(media = mean(hwy))

# Para pensar


(dados_trat <- data.frame(tratamento = LETTERS[1:3],
  resposta = c(2.3, 1.9, 3.2)))
```

```
##   tratamento resposta
## 1          A        2.3
## 2          B        1.9
## 3          C        3.2

ggplot(dados_trat, aes(tratamento, resposta)) +
  geom_col(fill = "red")
```




```
# Mais detalhes...
dados %>% select(manufacturer, hwy, year) %>%
  group_by(manufacturer, year) %>%
  summarise(media = mean(hwy), .groups = "drop") %>%
  ggplot(aes(x = manufacturer, y = media, fill = factor(year)))+
  geom_col(position = "dodge")+
  labs(fill = "year") +
  theme(axis.text.x = element_text(angle = 45))
```




```
p1<- ggplot(dados, aes(x = cty, y = hwy)) +  
  geom_point()  
p1
```


3.7 facet_grid, facet_wrap




```
p1 + facet_grid(rows = vars(cyl))
```




```
p1 + facet_grid(cols = vars(cyl))
```




```
p1 + facet_grid(~cyl)
```




```
p1 + facet_grid(rows = vars(year), cols =vars(cyl))
```




```
p1 + facet_grid(year~cyl)
```




```
p1 + facet_wrap(year ~ cyl)
```




```
p1 + facet_wrap(cyl ~ year)
```




```
p1 + facet_wrap(~cyl + year)
```




```
p1 + facet_wrap(~year + cyl)
```



```
p1 + facet_wrap(year ~ cyl, ncol = 4)
```


```
p1 + facet_wrap(cyl ~ year, ncol = 4)
```



```

a<- -3 # média
b<- 4 # desv. padrão
ggplot(data.frame(x = c(a - 3*b, a + 3*b)), aes(x)) +
  stat_function(fun = dnorm, args = list(mean = a, sd = b))+
  geom_vline(xintercept = c(a - 3*b, a, a + 3*b), col = "red", lty = 2)+
  theme_minimal()


```



```


ggplot(dados, aes(x = manufacturer, y = hwy)) +
  geom_boxplot()+
  geom_point(col = "red", size=0.8)+
  stat_summary(fun = mean, col = "blue")+
  theme_minimal()+
  theme(axis.text.x = element_text(angle = 45))

```



```
a1<- p1 + theme_bw() + labs(title = "theme_bw()")
a2<- p1 + theme_classic() + labs(title = "theme_classic()")
a3<- p1 + theme_light() + labs(title = "theme_light()")
a4<- p1 + theme_minimal() + labs(title = "theme_minimal()")


a1 + a2 + a3 + a4
```




```
## 11. Círculo de la vida (Orange)
glimpse(Orange)
```

```
## Rows: 35
## Columns: 3
## $ Tree      <ord> 1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2, 3, 3, 3, 3, 3, ~
## $ age       <dbl> 118, 484, 664, 1004, 1231, 1372, 1582, 118, 484, 664, 10~
## $ circumference <dbl> 30, 58, 87, 115, 120, 142, 145, 33, 69, 111, 156, 172, 2~

ggplot(Orange, aes(x = age, y = circumference, group = Tree,
                    col = Tree)) +
  geom_line()+
  stat_summary(aes(group = 1), fun = mean, col = "red",
               geom = "line", size = 1, show.legend = FALSE,
               linetype = 2)+
  xlim(0, 1600)+
  theme_minimal()
```



```
ggplot(Orange, aes(x = age, y = circumference, group = Tree)) +  
  geom_line()+  
  xlim(0, 1600)+  
  facet_wrap(~Tree)+  
  theme_minimal()+  
  theme(legend.position = "none")
```



3.12 plotly

plotly cran

Interactive web-based data visualization with R, plotly, and shiny

Plotly R Open Source Graphing Library

```
ggplotly(v1)
ggplotly(v2)
ggplotly(v4)
ggplotly(v5)
```

3.13 esquisse

Alguns links de interesse

esquisse

esquisse + shiny


```
esquisser(dados)
```

```

aes(x = displ, y = hwy, colour = drv) +
geom_point(shape = "circle", size = 1.85) +
scale_color_hue(direction = 1) +
theme_minimal() +
theme(legend.position = "top")

```


3.14 Exemplo esquisse



```

ggplot(dados) +
  aes(x = displ, y = cty, colour = class, size = cty) +
  geom_point(shape = "circle") +
  scale_color_hue(direction = 1) +
  theme(legend.position = "top") +
  facet_wrap(vars(drv))

```



Capítulo 4

purrr

```
library(tidyverse)
ls("package:purrr")
```

##	[1]	"%@"	"% %"	"%>%"
##	[4]	"accumulate"	"accumulate_right"	"accumulate2"
##	[7]	"array_branch"	"array_tree"	"as_mapper"
##	[10]	"as_vector"	"assign_in"	"at_depth"
##	[13]	"attr_getter"	"auto_browse"	"chuck"
##	[16]	"compact"	"compose"	"cross"
##	[19]	"cross_d"	"cross_df"	"cross_n"
##	[22]	"cross2"	"cross3"	"detect"
##	[25]	"detect_index"	"discard"	"discard_at"
##	[28]	"done"	"every"	"exec"
##	[31]	"flatten"	"flatten_chr"	"flatten_dbl"
##	[34]	"flatten_df"	"flatten_dfc"	"flatten_dfr"
##	[37]	"flatten_int"	"flatten_lgl"	"flatten_raw"
##	[40]	"has_element"	"head_while"	"imap"
##	[43]	"imap_chr"	"imap_dbl"	"imap_dfc"
##	[46]	"imap_dfr"	"imap_int"	"imap_lgl"
##	[49]	"imap_raw"	"imodify"	"insistently"
##	[52]	"invoke"	"invoke_map"	"invoke_map_chr"
##	[55]	"invoke_map_dbl"	"invoke_map_df"	"invoke_map_dfc"
##	[58]	"invoke_map_dfr"	"invoke_map_int"	"invoke_map_lgl"
##	[61]	"invoke_map_raw"	"is_atomic"	"is_bare_atomic"
##	[64]	"is_bare_character"	"is_bare_double"	"is_bare_integer"
##	[67]	"is_bare_list"	"is_bare_logical"	"is_bare_numeric"
##	[70]	"is_bare_vector"	"is_character"	"is_double"
##	[73]	"is_empty"	"is_formula"	"is_function"
##	[76]	"is_integer"	"is_list"	"is_logical"

## [79]	"is_null"	"is_rate"	"is_scalar_atomic"
## [82]	"is_scalar_character"	"is_scalar_double"	"is_scalar_integer"
## [85]	"is_scalar_list"	"is_scalar_logical"	"is_scalar_vector"
## [88]	"is_vector"	"iwalk"	"keep"
## [91]	"keep_at"	"lift"	"lift_dl"
## [94]	"lift_dv"	"lift_ld"	"lift_lv"
## [97]	"lift_vd"	"lift_vl"	"list_along"
## [100]	"list_assign"	"list_c"	"list_cbind"
## [103]	"list_flatten"	"list_merge"	"list_modify"
## [106]	"list_rbind"	"list_simplify"	"list_transpose"
## [109]	"lmap"	"lmap_at"	"lmap_if"
## [112]	"map"	"map_at"	"map_chr"
## [115]	"map_dbl"	"map_depth"	"map_df"
## [118]	"map_dfc"	"map_dfr"	"map_if"
## [121]	"map_int"	"map_lgl"	"map_raw"
## [124]	"map_vec"	"map2"	"map2_chr"
## [127]	"map2_dbl"	"map2_df"	"map2_dfc"
## [130]	"map2_dfr"	"map2_int"	"map2_lgl"
## [133]	"map2_raw"	"map2_vec"	"modify"
## [136]	"modify_at"	"modify_depth"	"modify_if"
## [139]	"modify_in"	"modify_tree"	"modify2"
## [142]	"negate"	"none"	"partial"
## [145]	"pluck"	"pluck_depth"	"pluck_exists"
## [148]	"pluck<-"	"pmap"	"pmap_chr"
## [151]	"pmap_dbl"	"pmap_df"	"pmap_dfc"
## [154]	"pmap_dfr"	"pmap_int"	"pmap_lgl"
## [157]	"pmap_raw"	"pmap_vec"	"possibly"
## [160]	"prepend"	"pwalk"	"quietly"
## [163]	"rate_backoff"	"rate_delay"	"rate_reset"
## [166]	"rate_sleep"	"rbernoulli"	"rdunif"
## [169]	"reduce"	"reduce_right"	"reduce2"
## [172]	"reduce2_right"	"rep_along"	"rerun"
## [175]	"safely"	"set_names"	"simplify"
## [178]	"simplify_all"	"slowly"	"some"
## [181]	"splice"	"tail_while"	"transpose"
## [184]	"update_list"	"vec_depth"	"walk"
## [187]	"walk2"	"when"	"zap"

4.1 Apply a function to each element of a list or atomic vector

The map functions transform their input by applying a function to each element of a list or atomic vector and returning an object of the same length as the input.

4.1. APPLY A FUNCTION TO EACH ELEMENT OF A LIST OR ATOMIC VECTOR⁹¹

- `map()` always returns a list. See the `modify()` family for versions that return an object of the same type as the input.
- `map_lgl()`, `map_int()`, `map_dbl()` and `map_chr()` return an atomic vector of the indicated type (or die trying).
- `map_dfr()` and `map_dfc()` return a data frame created by row-binding and column-binding respectively. They require `dplyr` to be installed.
- The returned values of `.f` must be of length one for each element of `.x`. If `.f` uses an extractor function shortcut, `.default` can be specified to handle values that are absent or empty. See `as_mapper()` for more on `.default`.
- `walk()` calls `.f` for its side-effect and returns the input `.x`.

4.1.1 Usage

- `map(.x, .f, ...)`
- `map_lgl(.x, .f, ...)`
- `map_chr(.x, .f, ...)`
- `map_int(.x, .f, ...)`
- `map_dbl(.x, .f, ...)`
- `map_raw(.x, .f, ...)`
- `map_dfr(.x, .f, ..., .id = NULL)`
- `map_dfc(.x, .f, ...)`
- `walk(.x, .f, ...)`

4.1.2 Arguments

- `.x` A list or atomic vector.
- `.f` A function, formula, or vector (not necessarily atomic).

If a function, it is used as is.

If a formula, e.g. `~ .x + 2`, it is converted to a function. There are three ways to refer to the arguments:

- For a single argument function, use `.`
- For a two argument function, use `.x` and `.y`
- For more arguments, use `..1`, `..2`, `..3` etc

This syntax allows you to create very compact anonymous functions.

If character vector, numeric vector, or list, it is converted to an extractor function. Character vectors index by name and numeric vectors index by position;

use a list to index by position and name at different levels. If a component is not present, the value of `.default` will be returned.

- ... Additional arguments passed on to the mapped function.
- `.id` Either a string or `NULL`. If a string, the output will contain a variable with that name, storing either the name (if `.x` is named) or the index (if `.x` is unnamed) of the input. If `NULL`, the default, no variable will be created.

Only applies to `_dfr` variant.

4.1.3 Value

- `map()` Returns a list the same length as `.x`.
- `map_lgl()` returns a logical vector, `map_int()` an integer vector, `map_dbl()` a double vector, and `map_chr()` a character vector.
- `map_df()`, `map_dfc()`, `map_dfr()` all return a data frame.
- If `.x` has `names()`, the return value preserves those names.
- The output of `.f` will be automatically typed upwards, e.g. logical \rightarrow integer \rightarrow double \rightarrow character.
- `walk()` returns the input `.x` (invisibly). This makes it easy to use in pipe.

4.1.4 See Also

`map_if()` for applying a function to only those elements of `.x` that meet a specified condition.

Other map variants: `imap()`, `invoke()`, `lmap()`, `map2()`, `map_if()`, `modify()`

4.2 Examples

```
# Compute normal distributions from an atomic vector
```

```
1:10 %>%
```

```
  map(rnorm, n = 10)
```

```
## [[1]]
```

```
## [1] 0.9606835 0.2558870 1.3668572 1.1732371 0.2350102 2.6521804
```

```
## [7] 0.8214040 1.9771913 -0.6155543 -0.9988018
```

```
##
```

```
## [[2]]
```

```
## [1] 0.9377754 0.9214704 2.8330264 3.0352480 0.5238653 2.5443251 2.2924893
```

```
## [8] 2.7829582 2.4419409 0.3743757
```

```
##
```

```
## [[3]]
```

```
## [1] 1.879637 3.818392 2.890525 3.872515 3.140802 2.768388 2.584703 2.922238
## [9] 2.616681 4.430572
##
## [[4]]
## [1] 3.567559 4.349109 3.615555 5.362684 2.652931 5.404148 3.194384 2.184058
## [9] 3.673871 5.500680
##
## [[5]]
## [1] 5.036916 4.557861 3.973224 6.193965 4.280406 5.230274 5.726284 5.856957
## [9] 5.082852 3.858142
##
## [[6]]
## [1] 4.656112 7.127457 7.521381 6.674265 6.095799 6.279487 6.779528 6.858636
## [9] 6.285432 8.188434
##
## [[7]]
## [1] 7.006924 7.218360 9.174065 7.025654 5.990612 7.551149 8.043741 7.910483
## [9] 8.426142 6.625891
##
## [[8]]
## [1] 8.002099 8.256513 6.616554 9.059241 7.288628 7.784038 10.333387
## [8] 7.588237 8.447337 7.238239
##
## [[9]]
## [1] 7.935737 8.246600 10.050744 7.661163 8.686803 6.817224 10.071338
## [8] 9.372334 7.385286 9.223673
##
## [[10]]
## [1] 9.330173 9.315890 11.722364 10.076962 8.569037 10.816171 9.890369
## [8] 10.161575 12.456419 9.847980

# You can also use an anonymous function
1:10 %>%
  map(function(x) rnorm(10, x))

## [[1]]
## [1] 2.4355148 1.3161904 -0.3844751 0.2743863 0.6748907 1.7813773
## [7] 2.4774534 0.9030152 2.0938987 0.7016563
##
## [[2]]
## [1] 4.134756 2.155219 2.612060 2.072941 2.212364 1.161664 3.075493 2.425679
## [9] 2.495402 1.971725
##
## [[3]]
## [1] 3.486822 2.451827 1.297666 2.291035 4.398815 3.260149 3.528562 1.261258
## [9] 4.190041 4.215717
```

```
##
## [[4]]
## [1] 5.009319 4.773983 4.106116 3.835846 3.576150 2.326984 5.184813 3.810730
## [9] 2.117968 3.568571
##
## [[5]]
## [1] 3.414407 4.265428 5.562993 5.277723 5.809059 4.492726 6.804638 3.683302
## [9] 6.856712 4.673499
##
## [[6]]
## [1] 6.501189 4.649399 3.941000 7.249335 6.460261 7.380625 6.432399 7.486122
## [9] 5.982924 7.892294
##
## [[7]]
## [1] 5.963699 7.444964 6.695306 6.825283 7.318234 4.847514 7.119791 7.097203
## [9] 7.174268 6.752557
##
## [[8]]
## [1] 7.624474 7.737118 7.432223 8.107198 6.294585 7.416914 8.153201 8.554924
## [9] 7.239460 7.551029
##
## [[9]]
## [1] 9.714895 8.727867 10.330333 10.059361 7.865472 8.657559 11.955671
## [8] 8.627070 9.512751 9.812425
##
## [[10]]
## [1] 9.475433 10.877835 9.728579 11.468436 11.286864 9.036773 9.359317
## [8] 8.569081 11.450863 9.169504

# Or a formula
1:10 %>%
  map(~ rnorm(10, .x))

## [[1]]
## [1] 3.0076519 1.3518697 0.7273344 0.3630838 0.5742323 0.1116815
## [7] -0.3309606 2.6579127 -0.6714084 -0.5835447
##
## [[2]]
## [1] 1.8177842 3.0601065 1.4946339 3.3512698 4.0715896 1.9266118 0.1991496
## [8] 1.2843011 3.1614962 2.6488691
##
## [[3]]
## [1] 2.0150944 3.3520639 4.3315523 0.8447573 3.3162547 4.2627852 2.7075133
## [8] 2.9769775 2.1460154 1.7398364
##
## [[4]]
```

```
## [1] 2.581916 4.808275 3.368369 4.329507 3.458508 4.789342 2.740603 3.141206
## [9] 3.398164 5.694223
##
## [[5]]
## [1] 7.134640 4.254732 5.143223 4.848392 6.329070 4.984556 6.355305 4.787746
## [9] 4.854475 3.621560
##
## [[6]]
## [1] 6.668563 6.849455 5.349847 6.371768 5.304878 8.179186 5.507334 4.445319
## [9] 7.270777 7.253198
##
## [[7]]
## [1] 6.663330 9.986253 6.115810 6.244033 5.867123 7.941277 7.945039 8.765729
## [9] 7.763603 7.744577
##
## [[8]]
## [1] 6.909167 7.448366 5.721610 8.387959 7.137138 7.407341 9.087489 8.648508
## [9] 6.143680 8.053039
##
## [[9]]
## [1] 5.729458 9.210299 7.224728 9.911272 8.154753 9.608185 8.063629 7.206674
## [9] 8.543258 9.196022
##
## [[10]]
## [1] 10.242230 9.523368 9.630883 9.686558 9.136119 11.507728 8.930809
## [8] 9.987174 10.816272 9.131987
```

Simplify output to a vector instead of a list by computing the mean of the distributions

```
1:10 %>%
  map(rnorm, n = 10) %>% # output a list
  map_dbl(mean)         # output an atomic vector
```

```
## [1] 0.6709021 2.2725584 3.0476521 3.9502926 4.3599626 6.3029332 7.4379788
## [8] 8.0346655 8.6689626 9.8911214
```

*# Using set_names() with character vectors is handy to keep track
of the original inputs:*

```
set_names(c("foo", "bar")) %>%
  map_chr(paste0, ":suffix")
```

```
##           foo           bar
## "foo:suffix" "bar:suffix"
```

Working with lists

```
favorite_desserts <- list(Sophia = "banana bread", Elliott = "pancakes", Karina = "chocolate cake")
favorite_desserts
```

```
## $Sophia
```

```
## [1] "banana bread"
##
## $Eliott
## [1] "pancakes"
##
## $Karina
## [1] "chocolate cake"
```

```
favorite_desserts %>%
  map_chr(~ paste(.x, "rocks!"))
```

```
##                Sophia                Eliott                Karina
## "banana bread rocks!" "pancakes rocks!" "chocolate cake rocks!"
```

```
# Extract by name or position
# .default specifies value for elements that are missing or NULL
l1 <- list(list(a = 1L),
           list(a = NULL, b = 2L),
           list(b = 3L))
l1
```

```
## [[1]]
## [[1]]$a
## [1] 1
##
##
## [[2]]
## [[2]]$a
## NULL
##
## [[2]]$b
## [1] 2
##
##
## [[3]]
## [[3]]$b
## [1] 3
```

```
l1 %>%
  map("a", .default = "???)")
```

```
## [[1]]
## [1] 1
##
## [[2]]
## [1] "???"
##
##
## [[3]]
```



```
## [1] "???"
l1 %>%
  map_int("b", .default = NA)

## [1] NA  2  3
l1 %>%
  map_int(2, .default = NA)

## [1] NA  2 NA
# Supply multiple values to index deeply into a list
l2 <- list(
  list(num = 1:3,      letters[1:3]),
  list(num = 101:103, letters[4:6]),
  list())
l2

## [[1]]
## [[1]]$num
## [1] 1 2 3
##
## [[1]][[2]]
## [1] "a" "b" "c"
##
##
## [[2]]
## [[2]]$num
## [1] 101 102 103
##
## [[2]][[2]]
## [1] "d" "e" "f"
##
##
## [[3]]
## list()

l2 %>%
  map(c(2, 2))

## [[1]]
## [1] "b"
##
## [[2]]
## [1] "e"
##
## [[3]]
## NULL
```

```
# Use a list to build an extractor that mixes numeric indices and names,
# and .default to provide a default value if the element does not exist
```

```
12 %>%
  map(list("num", 3))
```

```
## [[1]]
## [1] 3
##
## [[2]]
## [1] 103
##
## [[3]]
## NULL
```

```
12 %>%
  map_int(list("num", 3), .default = NA)
```

```
## [1] 3 103 NA
```

```
# Working with data frames
```

```
# Use map_lgl(), map_dbl(), etc to return a vector instead of a list:
```

```
mtcars %>%
  map_dbl(sum)
```

```
##      mpg      cyl      disp      hp      drat      wt      qsec      vs
## 642.900 198.000 7383.100 4694.000 115.090 102.952 571.160 14.000
##      am      gear      carb
## 13.000 118.000 90.000
```

```
# A more realistic example: split a data frame into pieces, fit a
# model to each piece, summarise and extract R^2
```

```
mtcars %>%
  split(.$cyl)
```

```
## $`4`
##      mpg cyl  disp  hp drat    wt  qsec vs am gear carb
## Datsun 710  22.8  4 108.0  93 3.85 2.320 18.61 1  1   4   1
## Merc 240D  24.4  4 146.7  62 3.69 3.190 20.00 1  0   4   2
## Merc 230   22.8  4 140.8  95 3.92 3.150 22.90 1  0   4   2
## Fiat 128   32.4  4  78.7  66 4.08 2.200 19.47 1  1   4   1
## Honda Civic 30.4  4  75.7  52 4.93 1.615 18.52 1  1   4   2
## Toyota Corolla 33.9  4  71.1  65 4.22 1.835 19.90 1  1   4   1
## Toyota Corona 21.5  4 120.1  97 3.70 2.465 20.01 1  0   3   1
## Fiat X1-9   27.3  4  79.0  66 4.08 1.935 18.90 1  1   4   1
## Porsche 914-2 26.0  4 120.3  91 4.43 2.140 16.70 0  1   5   2
## Lotus Europa 30.4  4  95.1 113 3.77 1.513 16.90 1  1   5   2
## Volvo 142E  21.4  4 121.0 109 4.11 2.780 18.60 1  1   4   2
##
```

```
## $`6`
##           mpg cyl  disp  hp drat   wt  qsec vs am gear carb
## Mazda RX4      21.0   6  160.0 110 3.90 2.620 16.46 0  1    4    4
## Mazda RX4 Wag  21.0   6  160.0 110 3.90 2.875 17.02 0  1    4    4
## Hornet 4 Drive  21.4   6  258.0 110 3.08 3.215 19.44 1  0    3    1
## Valiant        18.1   6  225.0 105 2.76 3.460 20.22 1  0    3    1
## Merc 280       19.2   6  167.6 123 3.92 3.440 18.30 1  0    4    4
## Merc 280C      17.8   6  167.6 123 3.92 3.440 18.90 1  0    4    4
## Ferrari Dino   19.7   6  145.0 175 3.62 2.770 15.50 0  1    5    6
##
## $`8`
##           mpg cyl  disp  hp drat   wt  qsec vs am gear carb
## Hornet Sportabout 18.7   8  360.0 175 3.15 3.440 17.02 0  0    3    2
## Duster 360       14.3   8  360.0 245 3.21 3.570 15.84 0  0    3    4
## Merc 450SE       16.4   8  275.8 180 3.07 4.070 17.40 0  0    3    3
## Merc 450SL       17.3   8  275.8 180 3.07 3.730 17.60 0  0    3    3
## Merc 450SLC      15.2   8  275.8 180 3.07 3.780 18.00 0  0    3    3
## Cadillac Fleetwood 10.4   8  472.0 205 2.93 5.250 17.98 0  0    3    4
## Lincoln Continental 10.4   8  460.0 215 3.00 5.424 17.82 0  0    3    4
## Chrysler Imperial 14.7   8  440.0 230 3.23 5.345 17.42 0  0    3    4
## Dodge Challenger 15.5   8  318.0 150 2.76 3.520 16.87 0  0    3    2
## AMC Javelin      15.2   8  304.0 150 3.15 3.435 17.30 0  0    3    2
## Camaro Z28       13.3   8  350.0 245 3.73 3.840 15.41 0  0    3    4
## Pontiac Firebird 19.2   8  400.0 175 3.08 3.845 17.05 0  0    3    2
## Ford Pantera L   15.8   8  351.0 264 4.22 3.170 14.50 0  1    5    4
## Maserati Bora    15.0   8  301.0 335 3.54 3.570 14.60 0  1    5    8

mtcars %>%
  split(.$cyl) %>%
  map(~ lm(mpg ~ wt, data = .x))

## $`4`
##
## Call:
## lm(formula = mpg ~ wt, data = .x)
##
## Coefficients:
## (Intercept)          wt
##      39.571      -5.647
##
## $`6`
##
## Call:
## lm(formula = mpg ~ wt, data = .x)
##
```

```
## Coefficients:
## (Intercept)          wt
##      28.41      -2.78
##
##
## $`8`
##
## Call:
## lm(formula = mpg ~ wt, data = .x)
##
## Coefficients:
## (Intercept)          wt
##      23.868      -2.192

mtcars %>%
  split(.$cyl) %>%
  map(~ lm(mpg ~ wt, data = .x)) %>%
  map(summary)

## $`4`
##
## Call:
## lm(formula = mpg ~ wt, data = .x)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.1513 -1.9795 -0.6272  1.9299  5.2523
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   39.571      4.347   9.104 7.77e-06 ***
## wt           -5.647      1.850  -3.052  0.0137 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 3.332 on 9 degrees of freedom
## Multiple R-squared:  0.5086, Adjusted R-squared:  0.454
## F-statistic: 9.316 on 1 and 9 DF,  p-value: 0.01374
##
##
## $`6`
##
## Call:
## lm(formula = mpg ~ wt, data = .x)
##
## Residuals:
```

```
##      Mazda RX4  Mazda RX4 Wag  Hornet 4 Drive      Valiant      Merc 280
##      -0.1250      0.5840      1.9292      -0.6897      0.3547
##      Merc 280C   Ferrari Dino
##      -1.0453      -1.0080
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  28.409      4.184    6.789 0.00105 **
## wt          -2.780      1.335   -2.083 0.09176 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.165 on 5 degrees of freedom
## Multiple R-squared:  0.4645, Adjusted R-squared:  0.3574
## F-statistic: 4.337 on 1 and 5 DF,  p-value: 0.09176
##
## $`8`
##
## Call:
## lm(formula = mpg ~ wt, data = .x)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -2.1491 -1.4664 -0.8458  1.5711  3.7619
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  23.8680      3.0055    7.942 4.05e-06 ***
## wt          -2.1924      0.7392   -2.966 0.0118 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.024 on 12 degrees of freedom
## Multiple R-squared:  0.423, Adjusted R-squared:  0.3749
## F-statistic: 8.796 on 1 and 12 DF,  p-value: 0.01179
# original
mtcars %>%
  split(.$cyl) %>%
  map(~ lm(mpg ~ wt, data = .x)) %>%
  map(summary) %>%
  map_dbl("r.squared")

##      4      6      8
## 0.5086326 0.4645102 0.4229655
```

```

# If each element of the output is a data frame, use
# map_dfr to row-bind them together:
mtcars %>%
  split(.$cyl) %>%
  map(~ lm(mpg ~ wt, data = .x)) %>%
  map_dfr(~ as.data.frame(t(as.matrix(coef(.))))))

##      (Intercept)          wt
## 1      39.57120 -5.647025
## 2      28.40884 -2.780106
## 3      23.86803 -2.192438

# (if you also want to preserve the variable names see
# the broom package)

#nest, unest() estudar!

mtcars %>%
  group_by(cyl) %>%
  nest()

## # A tibble: 3 x 2
## # Groups:   cyl [3]
##       cyl data
##   <dbl> <list>
## 1     6 <tibble [7 x 10]>
## 2     4 <tibble [11 x 10]>
## 3     8 <tibble [14 x 10]>

#mtcars %>%
#   group_by(cyl) %>%
#   nest() %>%
#   map(~ lm(mpg ~ wt, data = .x))

```

4.3 map functions

```

example("map")
example("map_at")
example("map_chr")
example("map_dbl")
example("map_df")
example("map_dfc")
example("map_dfr")

```

```
example("map_int")  
example("map_lgl")  
example("map_vec")
```

4.4 map2 functions

```
example("map2")  
example("map2_chr")  
example("map2_dbl")  
example("map2_df")  
example("map2_dfc")  
example("map2_dfr")  
example("map2_int")  
example("map2_lgl")  
example("map2_raw")  
example("map2_vec")
```


Capítulo 5

tidyr

More details in <https://tidyr.tidyverse.org/articles/nest.html>

5.1 nest()

```
library(tidyverse)

mtcars %>%
  group_by(cyl) %>%
  nest()

## # A tibble: 3 x 2
## # Groups:   cyl [3]
##   cyl data
##   <dbl> <list>
## 1     6 <tibble [7 x 10]>
## 2     4 <tibble [11 x 10]>
## 3     8 <tibble [14 x 10]>

um<- mtcars %>%
  group_by(cyl) %>%
  nest() %>%
  mutate(
    linMod = map(data, ~lm(mpg ~ wt, data = .)),
    coeffs = map(linMod, coefficients),
    slope = map_dbl(coeffs, 2))
um

## # A tibble: 3 x 5
## # Groups:   cyl [3]
```

```
##      cyl data          linMod coeffs      slope
##    <dbl> <list>          <list> <list>    <dbl>
## 1      6 <tibble [7 x 10]> <lm>    <dbl [2]> -2.78
## 2      4 <tibble [11 x 10]> <lm>    <dbl [2]> -5.65
## 3      8 <tibble [14 x 10]> <lm>    <dbl [2]> -2.19
```

```
um$linMod
```

```
## [[1]]
##
## Call:
## lm(formula = mpg ~ wt, data = .)
##
## Coefficients:
## (Intercept)          wt
##      28.41         -2.78
##
##
## [[2]]
##
## Call:
## lm(formula = mpg ~ wt, data = .)
##
## Coefficients:
## (Intercept)          wt
##      39.571         -5.647
##
##
## [[3]]
##
## Call:
## lm(formula = mpg ~ wt, data = .)
##
## Coefficients:
## (Intercept)          wt
##      23.868         -2.192
```

```
um$coeffs
```

```
## [[1]]
## (Intercept)          wt
##  28.408845    -2.780106
##
## [[2]]
## (Intercept)          wt
##  39.571196    -5.647025
##
```

```
## [[3]]
## (Intercept)          wt
## 23.868029    -2.192438
um$slope

## [1] -2.780106 -5.647025 -2.192438
um$linMod[[1]]

##
## Call:
## lm(formula = mpg ~ wt, data = .)
##
## Coefficients:
## (Intercept)          wt
##      28.41         -2.78
dois<- mtcars %>%
  group_by(cyl) %>%
  nest() %>%
  mutate(model = map(data, function(df) lm(mpg ~ wt, data = df)))
dois

## # A tibble: 3 x 3
## # Groups:   cyl [3]
##   cyl data          model
##   <dbl> <list>        <list>
## 1     6 <tibble [7 x 10]> <lm>
## 2     4 <tibble [11 x 10]> <lm>
## 3     8 <tibble [14 x 10]> <lm>
dois$cyl

## [1] 6 4 8
dois$data

## [[1]]
## # A tibble: 7 x 10
##   mpg  disp  hp  drat   wt  qsec   vs  am  gear  carb
##   <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1  21    160   110  3.9   2.62  16.5    0    1     4     4
## 2  21    160   110  3.9   2.88  17.0    0    1     4     4
## 3  21.4  258   110  3.08  3.22  19.4    1    0     3     1
## 4  18.1  225   105  2.76  3.46  20.2    1    0     3     1
## 5  19.2  168.   123  3.92  3.44  18.3    1    0     4     4
## 6  17.8  168.   123  3.92  3.44  18.9    1    0     4     4
## 7  19.7  145   175  3.62  2.77  15.5    0    1     5     6
##
```

```
## [[2]]
## # A tibble: 11 x 10
##   mpg   disp  hp  drat    wt  qsec    vs  am  gear carb
##   <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1  22.8  108    93  3.85  2.32  18.6    1    1    4    1
## 2  24.4  147    62  3.69  3.19  20      1    0    4    2
## 3  22.8  141    95  3.92  3.15  22.9    1    0    4    2
## 4  32.4   78.7   66  4.08  2.2   19.5    1    1    4    1
## 5  30.4   75.7   52  4.93  1.62  18.5    1    1    4    2
## 6  33.9   71.1   65  4.22  1.84  19.9    1    1    4    1
## 7  21.5  120    97  3.7   2.46  20.0    1    0    3    1
## 8  27.3   79    66  4.08  1.94  18.9    1    1    4    1
## 9   26   120    91  4.43  2.14  16.7    0    1    5    2
## 10  30.4  95.1   113  3.77  1.51  16.9    1    1    5    2
## 11  21.4  121   109  4.11  2.78  18.6    1    1    4    2
##
## [[3]]
## # A tibble: 14 x 10
##   mpg   disp  hp  drat    wt  qsec    vs  am  gear carb
##   <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1  18.7  360   175  3.15  3.44  17.0    0    0    3    2
## 2  14.3  360   245  3.21  3.57  15.8    0    0    3    4
## 3  16.4  276   180  3.07  4.07  17.4    0    0    3    3
## 4  17.3  276   180  3.07  3.73  17.6    0    0    3    3
## 5  15.2  276   180  3.07  3.78  18      0    0    3    3
## 6  10.4  472   205  2.93  5.25  18.0    0    0    3    4
## 7  10.4  460   215  3     5.42  17.8    0    0    3    4
## 8  14.7  440   230  3.23  5.34  17.4    0    0    3    4
## 9  15.5  318   150  2.76  3.52  16.9    0    0    3    2
## 10  15.2  304   150  3.15  3.44  17.3    0    0    3    2
## 11  13.3  350   245  3.73  3.84  15.4    0    0    3    4
## 12  19.2  400   175  3.08  3.84  17.0    0    0    3    2
## 13  15.8  351   264  4.22  3.17  14.5    0    1    5    4
## 14  15    301   335  3.54  3.57  14.6    0    1    5    8

dois$model

## [[1]]
##
## Call:
## lm(formula = mpg ~ wt, data = df)
##
## Coefficients:
## (Intercept)          wt
##      28.41       -2.78
##
```

```
##
## [[2]]
##
## Call:
## lm(formula = mpg ~ wt, data = df)
##
## Coefficients:
## (Intercept)          wt
##      39.571      -5.647
##
## [[3]]
##
## Call:
## lm(formula = mpg ~ wt, data = df)
##
## Coefficients:
## (Intercept)          wt
##      23.868      -2.192
dois$model[[3]]

##
## Call:
## lm(formula = mpg ~ wt, data = df)
##
## Coefficients:
## (Intercept)          wt
##      23.868      -2.192
tres<- dois %>%
  mutate(model = map(model, predict))
tres

## # A tibble: 3 x 3
## # Groups:   cyl [3]
##   cyl data          model
##   <dbl> <list>        <list>
## 1     6 <tibble [7 x 10]> <dbl [7]>
## 2     4 <tibble [11 x 10]> <dbl [11]>
## 3     8 <tibble [14 x 10]> <dbl [14]>
tres$model

## [[1]]
##      1      2      3      4      5      6      7
## 21.12497 20.41604 19.47080 18.78968 18.84528 18.84528 20.70795
```

```
##
## [[2]]
##      1      2      3      4      5      6      7      8
## 26.47010 21.55719 21.78307 27.14774 30.45125 29.20890 25.65128 28.64420
##      9     10     11
## 27.48656 31.02725 23.87247
##
## [[3]]
##      1      2      3      4      5      6      7      8
## 16.32604 16.04103 14.94481 15.69024 15.58061 12.35773 11.97625 12.14945
##      9     10     11     12     13     14
## 16.15065 16.33700 15.44907 15.43811 16.91800 16.04103
tres$model[[3]]

##      1      2      3      4      5      6      7      8
## 16.32604 16.04103 14.94481 15.69024 15.58061 12.35773 11.97625 12.14945
##      9     10     11     12     13     14
## 16.15065 16.33700 15.44907 15.43811 16.91800 16.04103
```

5.2 unnest()

```
um %>%
  unnest(data)

## # A tibble: 32 x 14
## # Groups:   cyl [3]
##      cyl  mpg  disp    hp  drat    wt  qsec    vs  am  gear  carb  linMod
##    <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <list>
## 1     6   21   160   110  3.9   2.62  16.5     0    1    4     4 <lm>
## 2     6   21   160   110  3.9   2.88  17.0     0    1    4     4 <lm>
## 3     6  21.4  258   110  3.08  3.22  19.4     1    0    3     1 <lm>
## 4     6  18.1  225   105  2.76  3.46  20.2     1    0    3     1 <lm>
## 5     6  19.2  168.   123  3.92  3.44  18.3     1    0    4     4 <lm>
## 6     6  17.8  168.   123  3.92  3.44  18.9     1    0    4     4 <lm>
## 7     6  19.7  145   175  3.62  2.77  15.5     0    1    5     6 <lm>
## 8     4  22.8  108    93  3.85  2.32  18.6     1    1    4     1 <lm>
## 9     4  24.4  147.    62  3.69  3.19  20      1    0    4     2 <lm>
## 10    4  22.8  141.    95  3.92  3.15  22.9     1    0    4     2 <lm>
## # ... with 22 more rows, and 2 more variables: coeffs <list>, slope <dbl>
```

5.3 Exemplos da ajuda do R

```
df <- tibble(x = c(1, 1, 1, 2, 2, 3),
             y = 1:6,
```

```

      z = 6:1)
df

## # A tibble: 6 x 3
##       x     y     z
##   <dbl> <int> <int>
## 1     1     1     6
## 2     1     2     5
## 3     1     3     4
## 4     2     4     3
## 5     2     5     2
## 6     3     6     1

# Note that we get one row of output for each unique combination of
# non-nested variables
df %>%
  nest(data = c(y, z))

## # A tibble: 3 x 2
##       x data
##   <dbl> <list>
## 1     1 <tibble [3 x 2]>
## 2     2 <tibble [2 x 2]>
## 3     3 <tibble [1 x 2]>

# chop does something similar, but retains individual columns
df %>%
  chop(c(y, z))

## # A tibble: 3 x 3
##       x     y     z
##   <dbl> <list<int>> <list<int>>
## 1     1         [3]         [3]
## 2     2         [2]         [2]
## 3     3         [1]         [1]

# use tidyselect syntax and helpers, just like in dplyr::select()
df %>%
  nest(data = any_of(c("y", "z")))

## # A tibble: 3 x 2
##       x data
##   <dbl> <list>
## 1     1 <tibble [3 x 2]>
## 2     2 <tibble [2 x 2]>
## 3     3 <tibble [1 x 2]>

```

```

iris %>%
  nest(data = !Species)

## # A tibble: 3 x 2
##   Species    data
##   <fct>      <list>
## 1 setosa    <tibble [50 x 4]>
## 2 versicolor <tibble [50 x 4]>
## 3 virginica <tibble [50 x 4]>

nest_vars <- names(iris)[1:4]
iris %>%
  nest(data = any_of(nest_vars))

## # A tibble: 3 x 2
##   Species    data
##   <fct>      <list>
## 1 setosa    <tibble [50 x 4]>
## 2 versicolor <tibble [50 x 4]>
## 3 virginica <tibble [50 x 4]>

iris %>%
  nest(petal = starts_with("Petal"), sepal = starts_with("Sepal"))

## # A tibble: 3 x 3
##   Species    petal          sepal
##   <fct>      <list>      <list>
## 1 setosa    <tibble [50 x 2]> <tibble [50 x 2]>
## 2 versicolor <tibble [50 x 2]> <tibble [50 x 2]>
## 3 virginica <tibble [50 x 2]> <tibble [50 x 2]>

iris %>%
  nest(width = contains("Width"), length = contains("Length"))

## # A tibble: 3 x 3
##   Species    width          length
##   <fct>      <list>      <list>
## 1 setosa    <tibble [50 x 2]> <tibble [50 x 2]>
## 2 versicolor <tibble [50 x 2]> <tibble [50 x 2]>
## 3 virginica <tibble [50 x 2]> <tibble [50 x 2]>

# Nesting a grouped data frame nests all variables apart from the group vars
fish_encounters %>%
  group_by(fish) %>%
  nest()

## # A tibble: 19 x 2
## # Groups:   fish [19]

```



```
##      fish  data
##      <fct> <list>
##  1 4842 <tibble [11 x 2]>
##  2 4843 <tibble [11 x 2]>
##  3 4844 <tibble [11 x 2]>
##  4 4845 <tibble [5 x 2]>
##  5 4847 <tibble [3 x 2]>
##  6 4848 <tibble [4 x 2]>
##  7 4849 <tibble [2 x 2]>
##  8 4850 <tibble [6 x 2]>
##  9 4851 <tibble [2 x 2]>
## 10 4854 <tibble [2 x 2]>
## 11 4855 <tibble [5 x 2]>
## 12 4857 <tibble [9 x 2]>
## 13 4858 <tibble [11 x 2]>
## 14 4859 <tibble [5 x 2]>
## 15 4861 <tibble [11 x 2]>
## 16 4862 <tibble [9 x 2]>
## 17 4863 <tibble [2 x 2]>
## 18 4864 <tibble [2 x 2]>
## 19 4865 <tibble [3 x 2]>

# Nesting is often useful for creating per group models
mtcars %>%
  group_by(cyl) %>%
  nest() %>%
  mutate(models = lapply(data, function(df) lm(mpg ~ wt, data = df)))

## # A tibble: 3 x 3
## # Groups:   cyl [3]
##      cyl data          models
##   <dbl> <list>         <list>
## 1     6 <tibble [7 x 10]> <lm>
## 2     4 <tibble [11 x 10]> <lm>
## 3     8 <tibble [14 x 10]> <lm>

# unnest() is primarily designed to work with lists of data frames
df <- tibble(
  x = 1:3,
  y = list(
    NULL,
    tibble(a = 1, b = 2),
    tibble(a = 1:3, b = 3:1)
  )
)

df %>%
```

```

unnest(y)

## # A tibble: 4 x 3
##       x     a     b
##   <int> <dbl> <dbl>
## 1     2     1     2
## 2     3     1     3
## 3     3     2     2
## 4     3     3     1

df %>%
  unnest(y, keep_empty = TRUE)

## # A tibble: 5 x 3
##       x     a     b
##   <int> <dbl> <dbl>
## 1     1    NA    NA
## 2     2     1     2
## 3     3     1     3
## 4     3     2     2
## 5     3     3     1

# If you have lists of lists, or lists of atomic vectors, instead
# see hoist(), unnest_wider(), and unnest_longer()

#' # You can unnest multiple columns simultaneously
df <- tibble(
  a = list(c("a", "b"), "c"),
  b = list(1:2, 3),
  c = c(11, 22)
)
df

## # A tibble: 2 x 3
##       a           b           c
##   <list>   <list>   <dbl>
## 1 <chr [2]> <int [2]>    11
## 2 <chr [1]> <dbl [1]>    22

df %>%
  unnest(c(a, b))

## # A tibble: 3 x 3
##       a           b           c
##   <chr> <dbl> <dbl>
## 1 a           1     11
## 2 b           2     11
## 3 c           3     22

```

```
# Compare with unnesting one column at a time, which generates  
# the Cartesian product
```

```
df %>%  
  unnest(a) %>%  
  unnest(b)
```

```
## # A tibble: 5 x 3  
##   a         b     c  
##   <chr> <dbl> <dbl>  
## 1 a         1     11  
## 2 a         2     11  
## 3 b         1     11  
## 4 b         2     11  
## 5 c         3     22
```

5.4 Mais detalhes

https://github.com/tidymodels/broom/blob/main/vignettes/broom_and_dplyr.Rmd

Capítulo 6

broom and dplyr

While broom is useful for summarizing the result of a single analysis in a consistent format, it is really designed for high-throughput applications, where you must combine results from multiple analyses. These could be subgroups of data, analyses using different models, bootstrap replicates, permutations, and so on. In particular, it plays well with the `nest/unnest` functions in `tidyr` and the `map` function in `purrr`. First, loading necessary packages and setting some defaults:

```
#ls("package:tidyr")
library(broom)
library(tibble)
library(ggplot2)
library(dplyr)
library(tidyr)
library(purrr)

theme_set(theme_minimal())
```

Let's try this on a simple dataset, the built-in `Orange`. We start by coercing `Orange` to a `tibble`. This gives a nicer print method that will especially be useful later on when we start working with list-columns.

```
data(Orange)

Orange <- as_tibble(Orange)
Orange

## # A tibble: 35 x 3
##   Tree   age circumference
##   <ord> <dbl>         <dbl>
## 1 1     118           30
## 2 1     484           58
```


```
## 3 1      664      87
## 4 1      1004     115
## 5 1      1231     120
## 6 1      1372     142
## 7 1      1582     145
## 8 2       118      33
## 9 2       484      69
## 10 2      664     111
## # ... with 25 more rows
```

This contains 35 observations of three variables: `Tree`, `age`, and `circumference`. `Tree` is a factor with five levels describing five trees. As might be expected, age and circumference are correlated:

```
cor(Orange$age, Orange$circumference)
```

```
## [1] 0.9135189
```

```
ggplot(Orange, aes(age, circumference, color = Tree)) +
  geom_line()
```



Suppose you want to test for correlations individually *within* each tree. You can do this with dplyr's `group_by`:

```
Orange %>%
  group_by(Tree) %>%
  summarize(correlation = cor(age, circumference))
```

```
## # A tibble: 5 x 2
##   Tree correlation
##   <ord>         <dbl>
## 1 3             0.988
## 2 1             0.985
## 3 5             0.988
## 4 2             0.987
## 5 4             0.984
```

(Note that the correlations are much higher than the aggregated one, and furthermore we can now see it is similar across trees).

Suppose that instead of simply estimating a correlation, we want to perform a hypothesis test with `cor.test`:

```
ct <- cor.test(Orange$age, Orange$circumference)
ct

##
## Pearson's product-moment correlation
##
## data: Orange$age and Orange$circumference
## t = 12.9, df = 33, p-value = 1.931e-14
## alternative hypothesis: true correlation is not equal to 0
## 95 percent confidence interval:
##  0.8342364 0.9557955
## sample estimates:
##          cor
## 0.9135189
```

This contains multiple values we could want in our output. Some are vectors of length 1, such as the p-value and the estimate, and some are longer, such as the confidence interval. We can get this into a nicely organized tibble using the `tidy` function:

```
tidy(ct)

## # A tibble: 1 x 8
##   estimate statistic p.value parameter conf.low conf.high method      alter~1
##   <dbl>      <dbl>   <dbl>    <int>    <dbl>    <dbl> <chr>      <chr>
## 1    0.914      12.9 1.93e-14      33    0.834    0.956 Pearson's pr~ two.si~
## # ... with abbreviated variable name 1: alternative
```

Often, we want to perform multiple tests or fit multiple models, each on a different part of the data. In this case, we recommend a `nest-map-unnest` workflow. For example, suppose we want to perform correlation tests for each different tree. We start by `nesting` our data based on the group of interest:

```
nested <- Orange %>%
  nest(data = ~Tree)
```

Then we run a correlation test for each nested tibble using `purrr::map`:

```
nested %>%
  mutate(test = map(data, ~ cor.test(.x$age, .x$circumference)))
```

```
## # A tibble: 5 x 3
##   Tree data          test
##   <ord> <list>        <list>
## 1 1    <tibble [7 x 2]> <htest>
## 2 2    <tibble [7 x 2]> <htest>
## 3 3    <tibble [7 x 2]> <htest>
## 4 4    <tibble [7 x 2]> <htest>
## 5 5    <tibble [7 x 2]> <htest>
```

This results in a list-column of S3 objects. We want to tidy each of the objects, which we can also do with `map`.

```
nested %>%
  mutate(
    test = map(data, ~ cor.test(.x$age, .x$circumference)), # S3 list-col
    tidied = map(test, tidy)
  )
```

```
## # A tibble: 5 x 4
##   Tree data          test  tidied
##   <ord> <list>        <list> <list>
## 1 1    <tibble [7 x 2]> <htest> <tibble [1 x 8]>
## 2 2    <tibble [7 x 2]> <htest> <tibble [1 x 8]>
## 3 3    <tibble [7 x 2]> <htest> <tibble [1 x 8]>
## 4 4    <tibble [7 x 2]> <htest> <tibble [1 x 8]>
## 5 5    <tibble [7 x 2]> <htest> <tibble [1 x 8]>
```

Finally, we want to unnest the tidied data frames so we can see the results in a flat tibble. All together, this looks like:

```
Orange %>%
  nest(data = ~Tree) %>%
  mutate(
    test = map(data, ~ cor.test(.x$age, .x$circumference)), # S3 list-col
    tidied = map(test, tidy)
  ) %>%
  unnest(tidied)
```

```
## # A tibble: 5 x 11
##   Tree data          test estimate stat~1 p.value param~2 conf.~3 conf.~4 method
##   <ord> <list>        <list>      <dbl>  <dbl>  <dbl>    <int>   <dbl>   <dbl> <chr>
```



```
## 1 1      <tibble> <htest>      0.985      13.0 4.85e-5      5      0.901      0.998 Pears~
## 2 2      <tibble> <htest>      0.987      13.9 3.43e-5      5      0.914      0.998 Pears~
## 3 3      <tibble> <htest>      0.988      14.4 2.90e-5      5      0.919      0.998 Pears~
## 4 4      <tibble> <htest>      0.984      12.5 5.73e-5      5      0.895      0.998 Pears~
## 5 5      <tibble> <htest>      0.988      14.1 3.18e-5      5      0.916      0.998 Pears~
## # ... with 1 more variable: alternative <chr>, and abbreviated variable names
## #   1: statistic, 2: parameter, 3: conf.low, 4: conf.high
```

This workflow becomes even more useful when applied to regressions. Untidy output for a regression looks like:

```
lm_fit <- lm(age ~ circumference, data = Orange)
summary(lm_fit)

##
## Call:
## lm(formula = age ~ circumference, data = Orange)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -317.88 -140.90  -17.20   96.54  471.16
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   16.6036    78.1406   0.212   0.833
## circumference   7.8160     0.6059  12.900 1.93e-14 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 203.1 on 33 degrees of freedom
## Multiple R-squared:  0.8345, Adjusted R-squared:  0.8295
## F-statistic: 166.4 on 1 and 33 DF,  p-value: 1.931e-14
```

where we tidy these results, we get multiple rows of output for each model:

```
tidy(lm_fit)

## # A tibble: 2 x 5
##   term          estimate std.error statistic  p.value
##   <chr>          <dbl>     <dbl>     <dbl>    <dbl>
## 1 (Intercept)    16.6      78.1       0.212 8.33e- 1
## 2 circumference   7.82      0.606     12.9  1.93e-14
```

Now we can handle multiple regressions at once using exactly the same workflow as before:

```
Orange %>%
  nest(data = -Tree) %>%
  mutate(
```

```
fit = map(data, ~ lm(age ~ circumference, data = .x)),
tidied = map(fit, tidy)
) %>%
unnest(tidied)
```

```
## # A tibble: 10 x 8
##   Tree data          fit term          estimate std.er~1 stati~2 p.value
##   <ord> <list>         <list> <chr>          <dbl>    <dbl>    <dbl>    <dbl>
## 1 1    <tibble [7 x 2]> <lm> (Intercept)    -265.    98.6     -2.68  4.36e-2
## 2 1    <tibble [7 x 2]> <lm> circumference    11.9     0.919    13.0  4.85e-5
## 3 2    <tibble [7 x 2]> <lm> (Intercept)   -132.    83.1     -1.59  1.72e-1
## 4 2    <tibble [7 x 2]> <lm> circumference     7.80     0.560    13.9  3.43e-5
## 5 3    <tibble [7 x 2]> <lm> (Intercept)   -210.    85.3     -2.46  5.74e-2
## 6 3    <tibble [7 x 2]> <lm> circumference    12.0     0.835    14.4  2.90e-5
## 7 4    <tibble [7 x 2]> <lm> (Intercept)   -76.5    88.3     -0.867 4.26e-1
## 8 4    <tibble [7 x 2]> <lm> circumference     7.17     0.572    12.5  5.73e-5
## 9 5    <tibble [7 x 2]> <lm> (Intercept)   -54.5    76.9     -0.709 5.10e-1
## 10 5   <tibble [7 x 2]> <lm> circumference     8.79     0.621    14.1  3.18e-5
## # ... with abbreviated variable names 1: std.error, 2: statistic
```

You can just as easily use multiple predictors in the regressions, as shown here on the `mtcars` dataset. We nest the data into automatic and manual cars (the `am` column), then perform the regression within each nested tibble.

```
data(mtcars)
mtcars <- as_tibble(mtcars) # to play nicely with list-cols
mtcars
```

```
## # A tibble: 32 x 11
##   mpg   cyl  disp    hp  drat    wt  qsec    vs  am  gear  carb
##   <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1  21     6  160   110  3.9   2.62  16.5     0     1     4     4
## 2  21     6  160   110  3.9   2.88  17.0     0     1     4     4
## 3 22.8     4  108    93  3.85  2.32  18.6     1     1     4     1
## 4 21.4     6  258   110  3.08  3.22  19.4     1     0     3     1
## 5 18.7     8  360   175  3.15  3.44  17.0     0     0     3     2
## 6 18.1     6  225   105  2.76  3.46  20.2     1     0     3     1
## 7 14.3     8  360   245  3.21  3.57  15.8     0     0     3     4
## 8 24.4     4  147    62  3.69  3.19  20      1     0     4     2
## 9 22.8     4  141    95  3.92  3.15  22.9     1     0     4     2
## 10 19.2     6  168   123  3.92  3.44  18.3     1     0     4     4
## # ... with 22 more rows
```

```
mtcars %>%
  nest(data = -am) %>%
  mutate(
    fit = map(data, ~ lm(wt ~ mpg + qsec + gear, data = .x)), # S3 list-col
```

```
tidied = map(fit, tidy)
) %>%
unnest(tidied)
```

```
## # A tibble: 8 x 8
##       am data      fit term      estimate std.error stati~1 p.value
##   <dbl> <list>    <list> <chr>      <dbl>      <dbl>    <dbl>    <dbl>
## 1     1 <tibble [13 x 10]> <lm> (Intercept)  4.28        3.46      1.24    2.47e-1
## 2     1 <tibble [13 x 10]> <lm> mpg      -0.101      0.0294   -3.43    7.50e-3
## 3     1 <tibble [13 x 10]> <lm> qsec       0.0398     0.151    0.264    7.98e-1
## 4     1 <tibble [13 x 10]> <lm> gear     -0.0229     0.349   -0.0656   9.49e-1
## 5     0 <tibble [19 x 10]> <lm> (Intercept)  4.92        1.40      3.52    3.09e-3
## 6     0 <tibble [19 x 10]> <lm> mpg      -0.192     0.0443   -4.33    5.91e-4
## 7     0 <tibble [19 x 10]> <lm> qsec       0.0919     0.0983    0.935    3.65e-1
## 8     0 <tibble [19 x 10]> <lm> gear       0.147     0.368    0.398    6.96e-1
## # ... with abbreviated variable name 1: statistic
```

What if you want not just the tidy output, but the `augment` and `glance` outputs as well, while still performing each regression only once? Since we're using list-columns, we can just fit the model once and use multiple list-columns to store the tidied, glanced and augmented outputs.

```
regressions <- mtcars %>%
  nest(data = -am) %>%
  mutate(
    fit = map(data, ~ lm(wt ~ mpg + qsec + gear, data = .x)),
    tidied = map(fit, tidy),
    glanced = map(fit, glance),
    augmented = map(fit, augment)
  )

regressions %>%
  unnest(tidied)
```

```
## # A tibble: 8 x 10
##       am data      fit term estim~1 std.e~2 stati~3 p.value glanced augmen~4
##   <dbl> <list>    <list> <chr>    <dbl>    <dbl>    <dbl>    <dbl>    <list>    <list>
## 1     1 <tibble> <lm> (Inte~  4.28     3.46     1.24    2.47e-1 <tibble> <tibble>
## 2     1 <tibble> <lm> mpg    -0.101    0.0294   -3.43    7.50e-3 <tibble> <tibble>
## 3     1 <tibble> <lm> qsec     0.0398    0.151    0.264    7.98e-1 <tibble> <tibble>
## 4     1 <tibble> <lm> gear   -0.0229    0.349   -0.0656   9.49e-1 <tibble> <tibble>
## 5     0 <tibble> <lm> (Inte~  4.92     1.40     3.52    3.09e-3 <tibble> <tibble>
## 6     0 <tibble> <lm> mpg    -0.192    0.0443   -4.33    5.91e-4 <tibble> <tibble>
## 7     0 <tibble> <lm> qsec     0.0919    0.0983    0.935    3.65e-1 <tibble> <tibble>
## 8     0 <tibble> <lm> gear     0.147    0.368    0.398    6.96e-1 <tibble> <tibble>
## # ... with abbreviated variable names 1: estimate, 2: std.error, 3: statistic,
## # 4: augmented
```

```
regressions %>%
  unnest(glanced)
```

```
## # A tibble: 2 x 17
##       am data      fit      tidied  r.squared adj.r.s~1 sigma stati~2 p.value    df
##   <dbl> <list>    <list> <list>      <dbl>      <dbl> <dbl>    <dbl>  <dbl> <dbl>
## 1     1 <tibble> <lm>    <tibble>    0.833      0.778 0.291    15.0  7.59e-4     3
## 2     0 <tibble> <lm>    <tibble>    0.625      0.550 0.522     8.32  1.70e-3     3
## # ... with 7 more variables: logLik <dbl>, AIC <dbl>, BIC <dbl>,
## #   deviance <dbl>, df.residual <int>, nobs <int>, augmented <list>, and
## #   abbreviated variable names 1: adj.r.squared, 2: statistic
```

```
regressions %>%
  unnest(augmented)
```

```
## # A tibble: 32 x 15
##       am data      fit      tidied  glanced      wt  mpg  qsec  gear .fitted
##   <dbl> <list>    <list> <list>      <list>    <dbl> <dbl> <dbl> <dbl>  <dbl>
## 1     1 <tibble> <lm>    <tibble> <tibble>    2.62  21   16.5    4    2.73
## 2     1 <tibble> <lm>    <tibble> <tibble>    2.88  21   17.0    4    2.75
## 3     1 <tibble> <lm>    <tibble> <tibble>    2.32  22.8  18.6    4    2.63
## 4     1 <tibble> <lm>    <tibble> <tibble>    2.2   32.4  19.5    4    1.70
## 5     1 <tibble> <lm>    <tibble> <tibble>    1.62  30.4  18.5    4    1.86
## 6     1 <tibble> <lm>    <tibble> <tibble>    1.84  33.9  19.9    4    1.56
## 7     1 <tibble> <lm>    <tibble> <tibble>    1.94  27.3  18.9    4    2.19
## 8     1 <tibble> <lm>    <tibble> <tibble>    2.14  26   16.7    5    2.21
## 9     1 <tibble> <lm>    <tibble> <tibble>    1.51  30.4  16.9    5    1.77
## 10    1 <tibble> <lm>    <tibble> <tibble>    3.17  15.8  14.5    5    3.15
## # ... with 22 more rows, and 5 more variables: .resid <dbl>, .hat <dbl>,
## #   .sigma <dbl>, .cooksd <dbl>, .std.resid <dbl>
```

By combining the estimates and p-values across all groups into the same tidy data frame (instead of a list of output model objects), a new class of analyses and visualizations becomes straightforward. This includes

- Sorting by p-value or estimate to find the most significant terms across all tests
- P-value histograms
- Volcano plots comparing p-values to effect size estimates

In each of these cases, we can easily filter, facet, or distinguish based on the `term` column. In short, this makes the tools of tidy data analysis available for the *results* of data analysis and models, not just the inputs.


6.1 Tidy bootstrapping

Another place where combining model fits in a tidy way becomes useful is when performing bootstrapping or permutation tests. These approaches have been explored before, for instance by Andrew MacDonald [here](#), and Hadley has explored efficient support for bootstrapping as a potential enhancement to dplyr. broom fits naturally with dplyr in performing these analyses.

Bootstrapping consists of randomly sampling a dataset with replacement, then performing the analysis individually on each bootstrapped replicate. The variation in the resulting estimate is then a reasonable approximation of the variance in our estimate.

Let's say we want to fit a nonlinear model to the weight/mileage relationship in the `mtcars` dataset.

```
library(ggplot2)
theme_set(theme_minimal())
ggplot(mtcars, aes(mpg, wt)) +
  geom_point()
```




We might use the method of nonlinear least squares (via the `nls` function) to fit a model.

```
nlsfit <- nls(mpg ~ k / wt + b, mtcars, start = list(k = 1, b = 0))
summary(nlsfit)
```

```
##
```

```
## Formula: mpg ~ k/wt + b
##
## Parameters:
##   Estimate Std. Error t value Pr(>|t|)
## k   45.829      4.249  10.786 7.64e-12 ***
## b    4.386      1.536   2.855 0.00774 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.774 on 30 degrees of freedom
##
## Number of iterations to convergence: 1
## Achieved convergence tolerance: 2.877e-08
```

```
ggplot(mtcars, aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = predict(nlsfit)))
```



While this does provide a p-value and confidence intervals for the parameters, these are based on model assumptions that may not hold in real data. Bootstrapping is a popular method for providing confidence intervals and predictions that are more robust to the nature of the data.

We can use the `bootstraps` function in the `rsample` package to sample bootstrap replications. First, we construct 100 bootstrap replications of the data, each of which has been randomly sampled with replacement. The resulting

object is an `rset`, which is a dataframe with a column of `rsplit` objects.

An `rsplit` object has two main components: an analysis dataset and an assessment dataset, accessible via `analysis(rsplit)` and `assessment(rsplit)` respectively. For bootstrap samples, the analysis dataset is the bootstrap sample itself, and the assessment dataset consists of all the out of bag samples.

```
library(dplyr)
library(rsample)
library(broom)
library(purrr)
library(tidyr)
set.seed(27)
boots <- bootstraps(mtcars, times = 100)
boots
```

```
## # Bootstrap sampling
## # A tibble: 100 x 2
##   splits      id
##   <list>    <chr>
## 1 <split [32/13]> Bootstrap001
## 2 <split [32/10]> Bootstrap002
## 3 <split [32/13]> Bootstrap003
## 4 <split [32/11]> Bootstrap004
## 5 <split [32/9]>  Bootstrap005
## 6 <split [32/10]> Bootstrap006
## 7 <split [32/11]> Bootstrap007
## 8 <split [32/13]> Bootstrap008
## 9 <split [32/11]> Bootstrap009
## 10 <split [32/11]> Bootstrap010
## # ... with 90 more rows
```

We create a helper function to fit an `nls` model on each bootstrap sample, and then use `purrr::map` to apply this function to all the bootstrap samples at once. Similarly, we create a column of tidy coefficient information by unnesting.

```
fit_nls_on_bootstrap <- function(split) {
  nls(mpg ~ k / wt + b, analysis(split), start = list(k = 1, b = 0))
}
boot_models <- boots %>%
  mutate(model = map(splits, fit_nls_on_bootstrap),
         coef_info = map(model, tidy))
boot_models
```

```
## # Bootstrap sampling
## # A tibble: 100 x 4
##   splits      id      model  coef_info
##   <list>    <chr>    <list> <list>
## 1 <split [32/13]> Bootstrap001 <list> <list>
```

```
## 1 <split [32/13]> Bootstrap001 <nls> <tibble [2 x 5]>
## 2 <split [32/10]> Bootstrap002 <nls> <tibble [2 x 5]>
## 3 <split [32/13]> Bootstrap003 <nls> <tibble [2 x 5]>
## 4 <split [32/11]> Bootstrap004 <nls> <tibble [2 x 5]>
## 5 <split [32/9]> Bootstrap005 <nls> <tibble [2 x 5]>
## 6 <split [32/10]> Bootstrap006 <nls> <tibble [2 x 5]>
## 7 <split [32/11]> Bootstrap007 <nls> <tibble [2 x 5]>
## 8 <split [32/13]> Bootstrap008 <nls> <tibble [2 x 5]>
## 9 <split [32/11]> Bootstrap009 <nls> <tibble [2 x 5]>
## 10 <split [32/11]> Bootstrap010 <nls> <tibble [2 x 5]>
## # ... with 90 more rows

boot_coefs <- boot_models %>%
  unnest(coef_info)
```

The unnested coefficient information contains a summary of each replication combined in a single data frame:

```
boot_coefs
```

```
## # A tibble: 200 x 8
##   splits      id      model term estimate std.error stati~1 p.value
##   <list>      <chr>    <list> <chr>    <dbl>      <dbl>    <dbl>    <dbl>
## 1 <split [32/13]> Bootstrap001 <nls> k      42.1      4.05    10.4  1.91e-11
## 2 <split [32/13]> Bootstrap001 <nls> b       5.39     1.43     3.78  6.93e- 4
## 3 <split [32/10]> Bootstrap002 <nls> k      49.9     5.66     8.82  7.82e-10
## 4 <split [32/10]> Bootstrap002 <nls> b       3.73     1.92     1.94  6.13e- 2
## 5 <split [32/13]> Bootstrap003 <nls> k      37.8     2.68    14.1  9.01e-15
## 6 <split [32/13]> Bootstrap003 <nls> b       6.73     1.17     5.75  2.78e- 6
## 7 <split [32/11]> Bootstrap004 <nls> k      45.6     4.45    10.2  2.70e-11
## 8 <split [32/11]> Bootstrap004 <nls> b       4.75     1.62     2.93  6.38e- 3
## 9 <split [32/9]> Bootstrap005 <nls> k      43.6     4.63     9.41  1.85e-10
## 10 <split [32/9]> Bootstrap005 <nls> b       5.89     1.68     3.51  1.44e- 3
## # ... with 190 more rows, and abbreviated variable name 1: statistic
```

We can then calculate confidence intervals (using what is called the percentile method):

```
alpha <- .05
boot_coefs %>%
  group_by(term) %>%
  summarize(low = quantile(estimate, alpha / 2),
            high = quantile(estimate, 1 - alpha / 2))


## # A tibble: 2 x 3
##   term      low high
##   <chr>    <dbl> <dbl>
## 1 b      0.283  6.74
```



```
## 2 k      38.5   57.6
```

Or we can use histograms to get a more detailed idea of the uncertainty in each estimate:

```
ggplot(boot_coefs, aes(estimate)) +
  geom_histogram(binwidth = 2) +
  facet_wrap(~ term, scales = "free")
```




Or we can use `augment` to visualize the uncertainty in the curve:

```
boot_aug <- boot_models %>%
  mutate(augmented = map(model, augment)) %>%
  unnest(augmented)
boot_aug
```

```
## # A tibble: 3,200 x 8
##   splits      id      model coef_info  mpg  wt .fitted .resid
##   <list>    <chr>    <list> <list>    <dbl> <dbl> <dbl> <dbl>
## 1 <split [32/13]> Bootstrap001 <nls> <tibble>  18.7  3.44   17.6  1.08
## 2 <split [32/13]> Bootstrap001 <nls> <tibble>  32.4  2.2    24.5  7.89
## 3 <split [32/13]> Bootstrap001 <nls> <tibble>  15.5  3.52   17.3 -1.84
## 4 <split [32/13]> Bootstrap001 <nls> <tibble>  22.8  3.15   18.7  4.05
## 5 <split [32/13]> Bootstrap001 <nls> <tibble>  24.4  3.19   18.6  5.82
## 6 <split [32/13]> Bootstrap001 <nls> <tibble>  30.4  1.62   31.4 -1.04
## 7 <split [32/13]> Bootstrap001 <nls> <tibble>  10.4  5.42   13.1 -2.75
## 8 <split [32/13]> Bootstrap001 <nls> <tibble>   21   2.62   21.4 -0.448
```


```
## 9 <split [32/13]> Bootstrap001 <nls> <tibble> 19.2 3.84 16.3 2.87
## 10 <split [32/13]> Bootstrap001 <nls> <tibble> 21 2.62 21.4 -0.448
## # ... with 3,190 more rows
```

```
ggplot(boot_aug, aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted, group = id), alpha=.2)
```



With only a few small changes, we could easily perform bootstrapping with other kinds of predictive or hypothesis testing models, since the `tidy` and `augment` functions work for many statistical outputs. As another example, we could use `smooth.spline`, which fits a cubic smoothing spline to data:

```
fit_spline_on_bootstrap <- function(split) {
  data <- analysis(split)
  smooth.spline(data$wt, data$mpg, df = 4)
}
boot_splines <- boots %>%
  mutate(spline = map(splits, fit_spline_on_bootstrap),
         aug_train = map(spline, augment))
splines_aug <- boot_splines %>%
  unnest(aug_train)
ggplot(splines_aug, aes(x, y)) +
  geom_point() +
  geom_line(aes(y = .fitted, group = id), alpha = 0.2)
```



6.2 Mais detalhes (glance)

6.2.1 lm()

```
fit <- lm(Volume ~ Girth + Height, trees)
tidy(fit)
```

```
## # A tibble: 3 x 5
##   term      estimate std.error statistic  p.value
##   <chr>      <dbl>    <dbl>    <dbl>    <dbl>
## 1 (Intercept) -58.0      8.64     -6.71 2.75e- 7
## 2 Girth        4.71     0.264     17.8 8.22e-17
## 3 Height       0.339    0.130      2.61 1.45e- 2
```

```
glance(fit)
```

```
## # A tibble: 1 x 12
##   r.squared adj.r.squa~1 sigma stati~2 p.value   df logLik   AIC   BIC devia~3
##   <dbl>      <dbl> <dbl>    <dbl>    <dbl> <dbl> <dbl> <dbl> <dbl>    <dbl>
## 1   0.948      0.944  3.88     255. 1.07e-18    2  -84.5  177.  183.   422.
## # ... with 2 more variables: df.residual <int>, nobs <int>, and abbreviated
## #   variable names 1: adj.r.squared, 2: statistic, 3: deviance
```

```
augment(fit, data = trees)
```

```
## # A tibble: 31 x 9
##   Girth Height Volume .fitted .resid   .hat .sigma   .cooksd .std.resid
##   <dbl>   <dbl>   <dbl>   <dbl> <dbl>   <dbl>   <dbl>   <dbl>   <dbl>
## 1  8.3     70    10.3    4.84  5.46  0.116   3.79  0.0978     1.50
## 2  8.6     65    10.3    4.55  5.75  0.147   3.77  0.148     1.60
## 3  8.8     63    10.2    4.82  5.38  0.177   3.78  0.167     1.53
## 4 10.5     72    16.4   15.9  0.526 0.0592   3.95  0.000409    0.140
## 5 10.7     81    18.8   19.9 -1.07  0.121   3.95  0.00394   -0.294
## 6 10.8     83    19.7   21.0 -1.32  0.156   3.94  0.00840   -0.370
## 7 11       66    15.6   16.2 -0.593 0.115   3.95  0.00114   -0.162
## 8 11       75    18.2   19.2 -1.05  0.0515  3.95  0.00138   -0.277
## 9 11.1     80    22.6   21.4  1.19  0.0920  3.95  0.00348    0.321
## 10 11.2     75    19.9   20.2 -0.288 0.0480   3.95  0.0000968  -0.0759
## # ... with 21 more rows
```

```
methods("tidy")
```

```
## [1] tidy.aareg*          tidy.acf*
## [3] tidy.anova*          tidy.aov*
## [5] tidy.aovlist*        tidy.Arima*
## [7] tidy.betamfx*        tidy.betareg*
## [9] tidy.biglm*          tidy.binDesign*
## [11] tidy.binWidth*       tidy.boot*
## [13] tidy.btergm*         tidy.cch*
## [15] tidy.character*      tidy.cld*
## [17] tidy.clm*            tidy.clmm*
## [19] tidy.coefest*        tidy.confint.glm*
## [21] tidy.confusionMatrix* tidy.coxph*
## [23] tidy.crr*            tidy.cv.glmnet*
## [25] tidy.data.frame*     tidy.default*
## [27] tidy.density*        tidy.dist*
## [29] tidy.drc*            tidy.durbinWatsonTest*
## [31] tidy.emmGrid*        tidy.epi.2by2*
## [33] tidy.ergm*           tidy.factanal*
## [35] tidy.felm*           tidy.fitdistr*
## [37] tidy.fixest*         tidy.ftable*
## [39] tidy.gam*            tidy.Gam*
## [41] tidy.garch*          tidy.geeglm*
## [43] tidy.glm*            tidy.glm*
## [45] tidy.glmnet*         tidy.glmrob*
## [47] tidy.glmRob*         tidy.gmm*
## [49] tidy.htest*          tidy.ivreg*
## [51] tidy.kappa*          tidy.kde*
## [53] tidy.Kendall*        tidy.kmeans*
## [55] tidy.lavaan*         tidy.leveneTest*
## [57] tidy.Line*           tidy.Lines*
```

```
## [59] tidy.list*                tidy.lm*
## [61] tidy.lm.beta*             tidy.lmodel2*
## [63] tidy.lmrob*               tidy.lmRob*
## [65] tidy.logical*             tidy.logitmfx*
## [67] tidy.lsmobj*              tidy.manova*
## [69] tidy.map*                 tidy.margins*
## [71] tidy.Mclust*              tidy.mediate*
## [73] tidy.mfx*                 tidy.mjoint*
## [75] tidy.mle2*                tidy.mlm*
## [77] tidy.mlogit*              tidy.muhaaz*
## [79] tidy.multinom*            tidy.negbin*
## [81] tidy.negbinmfx*           tidy.nested_cv*
## [83] tidy.nlrq*                 tidy.nls*
## [85] tidy.NULL*                tidy.numeric*
## [87] tidy.orcutt*              tidy.pairwise.htest*
## [89] tidy.pam*                 tidy.plm*
## [91] tidy.poissonmfx*          tidy.polCA*
## [93] tidy.polr*                tidy.Polygon*
## [95] tidy.Polygons*            tidy.power.htest*
## [97] tidy.prcomp*              tidy.probitmfx*
## [99] tidy.pyears*              tidy.rcorr*
## [101] tidy.ref.grid*            tidy.regsubsets*
## [103] tidy.ridgeglm*            tidy.rlm*
## [105] tidy.rma*                 tidy.roc*
## [107] tidy.rq*                  tidy.rqs*
## [109] tidy.rset*                tidy.rsplitt*
## [111] tidy.sarlm*               tidy.Sarlm*
## [113] tidy.SpatialLinesDataFrame* tidy.SpatialPolygons*
## [115] tidy.SpatialPolygonsDataFrame* tidy.spec*
## [117] tidy.speedglm*            tidy.speedlm*
## [119] tidy.summary.glm*         tidy.summary.lm*
## [121] tidy.summary.plm*         tidy.summary_emm*
## [123] tidy.summaryDefault*      tidy.survdiff*
## [125] tidy.survexp*             tidy.survfit*
## [127] tidy.survreg*             tidy.svyglm*
## [129] tidy.svyolr*              tidy.systemfit*
## [131] tidy.table*               tidy.tobit*
## [133] tidy.ts*                  tidy.TukeyHSD*
## [135] tidy.varest*              tidy.vfold_cv*
## [137] tidy.zoo*
## see '?methods' for accessing help and source code
methods("glance")
```

```
## [1] glance.aareg*           glance.anova*           glance.aov*
## [4] glance.Arima*           glance.betamfx*         glance.betareg*
```

```
## [7] glance.biglm*           glance.binDesign*      glance.cch*
## [10] glance.clm*             glance.clmm*           glance.coefTest*
## [13] glance.coxph*           glance.crr*            glance.cv.glmnet*
## [16] glance.data.frame*      glance.default*        glance.drc*
## [19] glance.durbinWatsonTest* glance.ergm*            glance.factanal*
## [22] glance.felm*            glance.fitdistr*       glance.fixest*
## [25] glance.gam*             glance.Gam*            glance.garch*
## [28] glance.geeglm*          glance.glm*            glance.glmnet*
## [31] glance.glmRob*          glance.gmm*            glance.htest*
## [34] glance.ivreg*           glance.kmeans*         glance.lavaan*
## [37] glance.list*            glance.lm*             glance.lmodel2*
## [40] glance.lmrob*           glance.lmRob*          glance.logitmfx*
## [43] glance.margins*         glance.Mclust*         glance.mfx*
## [46] glance.mjoint*          glance.mlogit*         glance.muhaz*
## [49] glance.multinom*        glance.negbin*         glance.negbinmfx*
## [52] glance.nlrq*            glance.nls*            glance.NULL*
## [55] glance.orcutt*          glance.pam*            glance.plm*
## [58] glance.poissonmfx*      glance.polCA*          glance.polr*
## [61] glance.probitmfx*       glance.pyears*         glance.ridgelm*
## [64] glance.rlm*             glance.rma*            glance.rq*
## [67] glance.rqs*             glance.sarlm*          glance.Sarlm*
## [70] glance.smooth.spline*   glance.speedglm*       glance.speedlm*
## [73] glance.summary.lm*      glance.summaryDefault* glance.survdiff*
## [76] glance.survexp*         glance.survfit*        glance.survreg*
## [79] glance.svyglm*          glance.svyolr*         glance.tbl_df*
## [82] glance.varest*
## see '?methods' for accessing help and source code
methods("augment")
```

```
## [1] augment.betamfx*      augment.betareg*      augment.clm*
## [4] augment.coxph*        augment.data.frame*   augment.decomposed.ts*
## [7] augment.default*      augment.drc*          augment.factanal*
## [10] augment.felm*         augment.fixest*       augment.gam*
## [13] augment.glm*          augment.glmRob*       augment.glmRob*
## [16] augment.htest*        augment.ivreg*        augment.kmeans*
## [19] augment.lm*           augment.lmrob*        augment.lmRob*
## [22] augment.loess*        augment.logitmfx*     augment.margins*
## [25] augment.Mclust*       augment.mfx*          augment.mjoint*
## [28] augment.mlogit*       augment.negbinmfx*    augment.nlrq*
## [31] augment.nls*          augment.NULL*         augment.pam*
## [34] augment.plm*          augment.poissonmfx*   augment.polCA*
## [37] augment.polr*         augment.prcomp*       augment.probitmfx*
## [40] augment.rlm*          augment.rma*          augment.rq*
## [43] augment.rqs*          augment.sarlm*        augment.Sarlm*
## [46] augment.smooth.spline* augment.speedglm*     augment.speedlm*
```

```
## [49] augment.stl*          augment.survreg*
## see '?methods' for accessing help and source code
```

```
#tirei da ajuda do R!
# fit models
a <- lm(mpg ~ wt + qsec + disp, mtcars)
b <- lm(mpg ~ wt + qsec, mtcars)

mod <- anova(a, b)

# summarize model fit with tidiers
tidy(mod)
```

```
## # A tibble: 2 x 7
##   term                df.residual  rss    df    sumsq statistic p.value
##   <chr>                <dbl> <dbl> <dbl>    <dbl>    <dbl>    <dbl>
## 1 mpg ~ wt + qsec + disp          28  195.   NA NA         NA         NA
## 2 mpg ~ wt + qsec                29  195.   -1 -0.00102  0.000147  0.990
glance(mod)
```

```
## # A tibble: 1 x 2
##   deviance df.residual
##   <dbl>    <dbl>
## 1    195.        29
# car::linearHypothesis() example
library(car)
mod_lht <- linearHypothesis(a, "wt - disp")
tidy(mod_lht)
```

```
## # A tibble: 1 x 10
##   term      null.value estim~1 std.e~2 stati~3 p.value df.re~4  rss    df sumsq
##   <chr>        <dbl>  <dbl>  <dbl>  <dbl>  <dbl>  <dbl> <dbl> <dbl> <dbl>
## 1 wt - disp          0   -5.03   1.23   16.6 3.39e-4    28  195.    1  116.
## # ... with abbreviated variable names 1: estimate, 2: std.error, 3: statistic,
## # 4: df.residual
glance(mod_lht)
```

```
## # A tibble: 1 x 2
##   deviance df.residual
##   <dbl>    <dbl>
## 1    195.        28
```

```
# fit model
nn <- nls(mpg ~ k * e^wt, data = mtcars, start = list(k = 1, e = 2))

# summarize model fit with tidiers + visualization
tidy(nn)
```

```
## # A tibble: 2 x 5
##   term estimate std.error statistic p.value
##   <chr>      <dbl>      <dbl>      <dbl>   <dbl>
## 1 k         49.7         3.79        13.1 5.96e-14
## 2 e          0.746        0.0199        37.5 8.86e-27


augment(nn)
```

```
## # A tibble: 32 x 4
##   mpg    wt .fitted .resid
##   <dbl> <dbl>   <dbl>   <dbl>
## 1  21    2.62    23.0   -2.01
## 2  21    2.88    21.4  -0.352
## 3  22.8  2.32    25.1  -2.33
## 4  21.4  3.22    19.3   2.08
## 5  18.7  3.44    18.1   0.611
## 6  18.1  3.46    18.0   0.117
## 7  14.3  3.57    17.4  -3.11
## 8  24.4  3.19    19.5   4.93
## 9  22.8  3.15    19.7   3.10
## 10 19.2  3.44    18.1   1.11
## # ... with 22 more rows

glance(nn)
```

```
## # A tibble: 1 x 9
##   sigma isConv   finTol logLik   AIC   BIC deviance df.residual nobs
##   <dbl> <lgl>      <dbl>   <dbl> <dbl> <dbl>   <dbl>      <int> <int>
## 1  2.67 TRUE    0.00000204 -75.8  158.  162.    214.        30    32

ggplot(augment(nn), aes(wt, mpg)) +
  geom_point() +
  geom_line(aes(y = .fitted))
```

```
newdata <- head(mtcars)
newdata$wt <- newdata$wt + 1

augment(nn, newdata = newdata)
```

```
## # A tibble: 6 x 12
##   mpg   cyl  disp    hp  drat    wt   qsec    vs  am  gear  carb .fitted
##   <dbl> <dbl> <dbl>   <dbl> <dbl>   <dbl> <dbl>   <dbl> <dbl> <dbl> <dbl> <dbl>
## 1  21     6   160   110   3.9    3.62  16.5     0     1     4     4   17.2
## 2  21     6   160   110   3.9    3.88  17.0     0     1     4     4   15.9
## 3  22.8   4   108    93   3.85    3.32  18.6     1     1     4     1   18.7
## 4  21.4   6   258   110   3.08    4.22  19.4     1     0     3     1   14.4
## 5  18.7   8   360   175   3.15    4.44  17.0     0     0     3     2   13.5
## 6  18.1   6   225   105   2.76    4.46  20.2     1     0     3     1   13.4
```

6.2.3 glm()

```
g <- glm(am ~ mpg, mtcars, family = "binomial")
g
```

```
##
## Call:  glm(formula = am ~ mpg, family = "binomial", data = mtcars)
##
## Coefficients:
## (Intercept)          mpg
```

```
##      -6.604      0.307
##
## Degrees of Freedom: 31 Total (i.e. Null);  30 Residual
## Null Deviance:      43.23
## Residual Deviance: 29.68      AIC: 33.68

glance(g)

## # A tibble: 1 x 8
##   null.deviance df.null logLik   AIC   BIC deviance df.residual  nobs
##   <dbl>    <int>  <dbl> <dbl> <dbl>   <dbl>      <int> <int>
## 1      43.2      31  -14.8  33.7  36.6    29.7        30    32
```

6.2.4 gam()

```
# load libraries for models and data
library(mgcv)

# fit model
g <- gam(mpg ~ s(hp) + am + qsec, data = mtcars)
g

##
## Family: gaussian
## Link function: identity
##
## Formula:
## mpg ~ s(hp) + am + qsec
##
## Estimated degrees of freedom:
## 2.36 total = 5.36
##
## GCV score: 8.837538

# summarize model fit with tidiers
tidy(g)

## # A tibble: 1 x 5
##   term      edf ref.df statistic p.value
##   <chr> <dbl>  <dbl>      <dbl>   <dbl>
## 1 s(hp)  2.36   3.02      6.34  0.00218

tidy(g, parametric = TRUE)

## # A tibble: 3 x 5
##   term      estimate std.error statistic p.value
##   <chr>      <dbl>      <dbl>      <dbl>   <dbl>
## 1 (Intercept) 16.7        9.83      1.70  0.101
```

```
## 2 am          4.37      1.56      2.81 0.00918
## 3 qsec        0.0904    0.525     0.172 0.865
glance(g)

## # A tibble: 1 x 7
##       df logLik   AIC   BIC deviance df.residual  nobs
##   <dbl> <dbl> <dbl> <dbl>   <dbl>      <dbl> <int>
## 1  5.36 -74.4  162.  171.    196.        26.6   32
augment(g)

## # A tibble: 32 x 10
##       mpg      am  qsec    hp .fitted .se.fit .resid  .hat .sigma .cooksd
##   <dbl> <dbl> <dbl> <dbl>   <dbl>   <dbl>   <dbl>   <dbl> <dbl>   <dbl>
## 1  21      1  16.5  110   24.3    1.03  -3.25  0.145 NA     0.0529
## 2  21      1  17.0  110   24.3    0.925 -3.30  0.116 NA     0.0411
## 3  22.8    1  18.6   93   26.0    0.894 -3.22  0.109 NA     0.0359
## 4  21.4    0  19.4  110   20.2    0.827  1.25  0.0930 NA     0.00448
## 5  18.7    0  17.0  175   15.7    0.815  3.02  0.0902 NA     0.0251
## 6  18.1    0  20.2  105   20.7    0.914 -2.56  0.113 NA     0.0240
## 7  14.3    0  15.8  245   12.7    1.11  1.63  0.167 NA     0.0162
## 8  24.4    0  20     62   25.0    1.45 -0.618 0.287 NA     0.00545
## 9  22.8    0  22.9   95   21.8    1.81  0.959 0.446 NA     0.0340
## 10 19.2    0  18.3  123   19.0    0.864  0.211 0.102 NA     0.000142
## # ... with 22 more rows
```

6.3 links

https://www.youtube.com/watch?v=1bnhT8tJCJQ&list=PLBnFxG6owe1F-3y0_aphRZ5YHH06Qr1Kj

https://bookdown.org/bruno_lucian_costa/CursoIntermediarioR/tidyr.html

<https://bookdown.org/Maxine/r4ds/nesting.html>

<https://livro.curso-r.com/7-3-tidyr.html>

<http://leg.ufpr.br/~walmes/cursoR/data-vis/slides/04-tidyr.pdf>

Ver como citar referências Wickham et al. [2019], Wickham [2023], Wickham et al. [2023c], Wickham et al. [2023a], Wickham and Henry [2023], Wickham et al. [2023b], Xie [2023b], Xie [2023a]

Capítulo 7

Extra

7.1 Introduction

The overall goal is to give you a very quick introduction to conducting correlation and regression analyses in R.

7.2 Correlation

The Pearson product moment correlation seeks to measure the linear association between two variables, x and y on a standardized scale ranging from $r = -1$ to 1 .

The correlation of x and y is a covariance that has been standardized by the standard deviations of x and y . This yields a scale-insensitive measure of the linear association of x and y . For much more conceptual detail, see this: https://psu-psychology.github.io/psy-597-SEM/01_correlation_regression/01_Correlation_and_Regression.html.

$$r_{XY} = \frac{s_{XY}}{s_X s_Y}$$

7.3 Correlation matrix

```
to_correlate <- mtcars %>% dplyr::select(qsec, cyl, disp, hp)
cor(to_correlate)
```

```
##           qsec           cyl           disp           hp
## qsec  1.0000000 -0.5912421 -0.4336979 -0.7082234
## cyl  -0.5912421  1.0000000  0.9020329  0.8324475
## disp -0.4336979  0.9020329  1.0000000  0.7909486
```

```
## hp    -0.7082234  0.8324475  0.7909486  1.0000000
```

7.4 Testing a bivariate association

Recall that the significance of correlations are computed on $n - 2$ degrees of freedom.

The t-test is:

$$t = \frac{r\sqrt{n-2}}{\sqrt{1-r^2}}$$

```
cor.test(mtcars$qsec, mtcars$cyl)
```

```
##
##  Pearson's product-moment correlation
##
## data:  mtcars$qsec and mtcars$cyl
## t = -4.0154, df = 30, p-value = 0.0003661
## alternative hypothesis: true correlation is not equal to 0
## 95 percent confidence interval:
##  -0.7792781 -0.3055388
## sample estimates:
##           cor
## -0.5912421
```


Note that we can use the `conf.int` argument to `cor.test` to get different levels of confidence.

```
cor.test(mtcars$qsec, mtcars$cyl, conf.level = 0.9)
```

```
##
##  Pearson's product-moment correlation
##
## data:  mtcars$qsec and mtcars$cyl
## t = -4.0154, df = 30, p-value = 0.0003661
## alternative hypothesis: true correlation is not equal to 0
## 90 percent confidence interval:
##  -0.7552287 -0.3576005
## sample estimates:
##           cor
## -0.5912421
```

7.5 Visualizing the association

```
ggplot(to_correlate, aes(x=cyl, y=qsec)) + geom_jitter(width=0.1) + stat_smooth(method="lm", se=F)
```



7.6 Testing the significance of all correlations in the matrix

```
Hmisc::rcorr(to_correlate %>% as.matrix())
```

```
##      qsec  cyl  disp  hp
## qsec  1.00 -0.59 -0.43 -0.71
## cyl  -0.59  1.00  0.90  0.83
## disp -0.43  0.90  1.00  0.79
## hp   -0.71  0.83  0.79  1.00
##
## n= 32
##
##
## P
##      qsec  cyl  disp  hp
## qsec      0.0004 0.0131 0.0000
## cyl  0.0004      0.0000 0.0000
## disp 0.0131 0.0000      0.0000
```

```
## hp    0.0000 0.0000 0.0000
```

Notice that we now get a matrix of p-values, too...

7.7 Pretty output

```
stargazer(cor(to_correlate), type = "html")
```

```
qsec
```

```
cyl
```

```
disp
```

```
hp
```

```
qsec
```

```
1
```

```
-0.591
```

```
-0.434
```

```
-0.708
```

```
cyl
```

```
-0.591
```

```
1
```

```
0.902
```

```
0.832
```

```
disp
```

```
-0.434
```

```
0.902
```

```
1
```

```
0.791
```

```
hp
```

```
-0.708
```

```
0.832
```

```
0.791
```

```
1
```


#you can use the filename argument to write out the table as a Word doc!
`apaTables::apa.cor.table(to_correlate)`

```
##
##
## Means, standard deviations, and correlations with confidence intervals
##
##
##   Variable M      SD    1          2          3
##   1. qsec  17.85  1.79
##
##   2. cyl    6.19   1.79  -.59**
##                               [-.78, -.31]
##
##   3. disp  230.72 123.94 -.43*      .90**
##                               [-.68, -.10] [.81, .95]
##
##   4. hp    146.69 68.56 -.71**      .83**      .79**
##                               [-.85, -.48] [.68, .92] [.61, .89]
##
##
## Note. M and SD are used to represent mean and standard deviation, respectively.
## Values in square brackets indicate the 95% confidence interval.
## The confidence interval is a plausible range of population correlations
## that could have caused the sample correlation (Cumming, 2014).
## * indicates p < .05. ** indicates p < .01.
##
```

7.8 Keeping the correlations for further analysis

Here, we store all details of the bivariate correlation test as an R object `ctest`.

```
ctest <- cor.test(mtcars$qsec, mtcars$cyl)
```

Let's poke under the hood:

```
str(ctest)
```

```
## List of 9
## $ statistic : Named num -4.02
##   ..- attr(*, "names")= chr "t"
## $ parameter : Named int 30
##   ..- attr(*, "names")= chr "df"
## $ p.value    : num 0.000366
## $ estimate   : Named num -0.591
##   ..- attr(*, "names")= chr "cor"
```

```
## $ null.value : Named num 0
##   .. attr(*, "names")= chr "correlation"
## $ alternative: chr "two.sided"
## $ method      : chr "Pearson's product-moment correlation"
## $ data.name    : chr "mtcars$qsec and mtcars$cyl"
## $ conf.int     : num [1:2] -0.779 -0.306
##   .. attr(*, "conf.level")= num 0.95
## - attr(*, "class")= chr "htest"
```

So, we can poke around and grab specific things:

```
ctest$p.value
```

```
## [1] 0.0003660533
```

```
ctest$estimate
```

```
##          cor
## -0.5912421
```

And there are useful helper packages, especially `broom`, that will help you work with statistics objects as `data.frame` objects.

```
broom::glance(ctest)
```

```
## # A tibble: 1 x 8
##   estimate statistic p.value parameter conf.low conf.high method      alter~1
##   <dbl>      <dbl>   <dbl>    <int>    <dbl>    <dbl> <chr>      <chr>
## 1   -0.591      -4.02 0.000366      30   -0.779    -0.306 Pearson's pr~ two.si~
## # ... with abbreviated variable name 1: alternative
```

7.9 Correlation method

You can use a different correlation method (e.g., Spearman) using the `method` argument:

```
cor.test(mtcars$qsec, mtcars$cyl, method = "spearman")
```

```
##
## Spearman's rank correlation rho
##
## data:  mtcars$qsec and mtcars$cyl
## S = 8578.7, p-value = 0.0006196
## alternative hypothesis: true rho is not equal to 0
## sample estimates:
##          rho
## -0.5723509
```

```
cor(to_correlate, method = "spearman")

##          qsec          cyl          disp          hp
## qsec  1.0000000 -0.5723509 -0.4597818 -0.6666060
## cyl  -0.5723509  1.0000000  0.9276516  0.9017909
## disp -0.4597818  0.9276516  1.0000000  0.8510426
## hp   -0.6666060  0.9017909  0.8510426  1.0000000
```

7.10 Missing data

By default, `cor` will return an NA (missing) for every pair in which at least one observation is missing. We can ask for correlations to be estimated on the complete cases for each pair. This is `use="pairwise.complete.obs"`.

Here's the difference (I introduced some missing data to make the point):

First, with 'everything' as the `use` argument (any missing on a variable drops it from the correlation table).

```
to_correlate_miss <- to_correlate
to_correlate_miss$qsec[c(1, 5)] <- NA
cor(to_correlate_miss) #implicitly use="everything"
```

```
##          qsec          cyl          disp          hp
## qsec      1          NA          NA          NA
## cyl    NA 1.0000000  0.9020329  0.8324475
## disp    NA 0.9020329  1.0000000  0.7909486
## hp      NA 0.8324475  0.7909486  1.0000000
```

Now with pairwise complete calculation:

```
cor(to_correlate_miss, use="pairwise.complete.obs")

##          qsec          cyl          disp          hp
## qsec  1.0000000 -0.5961232 -0.4483569 -0.7313008
## cyl  -0.5961232  1.0000000  0.9020329  0.8324475
## disp -0.4483569  0.9020329  1.0000000  0.7909486
## hp   -0.7313008  0.8324475  0.7909486  1.0000000
```


Capítulo 8

Single-predictor (simple) regression

Next, let's turn to 'simple' linear regression (one predictor, one outcome), then scale to multiple regression (many predictors, one outcome). The standard linear regression model is implemented by the `lm` function in R. The `lm` function uses ordinary least squares (OLS) which estimates the parameter by minimizing the squared residuals.


In simple regression, we are interested in a relationship of the form:

$$Y = B_0 + B_1X$$

where Y is the dependent variable (criterion) and X is the predictor (covariate). The intercept is represented by B_0 and the slope for the X predictor by B_1 .

Let's take a look at the simple case of stopping distance (braking) as a function of car speed.

```
ggplot(cars, aes(x=speed, y=dist)) +  
  geom_point(color='darkblue', size = 3) +  
  geom_smooth(method=lm, se=FALSE, fullrange=TRUE, color='black', size=1.2) +  
  labs(x="Speed (mph)", y="Stopping distance (ft)")
```



When conducting regression, we typically try to capture linear relationships among variables. We can introduce higher-order polynomial terms (e.g., quadratic models) or splines (more flexible shapes), but this is beyond the scope here.

Fortunately, this relationship looks quite linear! The faster the car, the longer it takes to brake.

In R regression models, we use the `~` operator to denote ‘regressed on’. It’s not especially intuitive, but we say the criterion is regressed on the predictor. Here, if we think speed is a key cause of stopping distance, we’d say ‘braking distance regressed on speed’ or ‘speed predicts braking distance.’

In formula terms, this is `dist ~ speed`, which we pass as the first argument to `lm()`.

```
lm_cars <- lm(dist ~ speed, data=cars)
summary(lm_cars)
```

```
##
## Call:
## lm(formula = dist ~ speed, data = cars)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -29.069  -9.525  -2.272   9.215  43.201
##
## Coefficients:
```


```
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) -17.5791      6.7584  -2.601   0.0123 *
## speed       3.9324       0.4155   9.464  1.49e-12 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 15.38 on 48 degrees of freedom
## Multiple R-squared:  0.6511, Adjusted R-squared:  0.6438
## F-statistic: 89.57 on 1 and 48 DF,  p-value: 1.49e-12
```

The output contains individual parameter estimates of the model (here, just the intercept and slope), their standard errors, significance tests, and p-values (one degree of freedom). We also get global information such as the sum of squared errors and the coefficient of determination (R^2).

8.1 Regression diagnostics


We can also get useful diagnostic plots for free using the `plot()` function:

```
par(mfrow=c(2,2))
plot(lm_cars)
```



The `ggfortify` package also provides an `autoplot` function that gives similar diagnostics within a handy ggplot-based graph.

```
autoplot(lm_cars)
```



8.2 Bootstrap estimates and confidence intervals

Using functionality from the `car` and `boot` packages, we can easily get estimates of the regression coefficients and standard errors using nonparametric bootstrapping, which relaxes the normal theory assumption on the standard errors and, therefore, the significance tests. Likewise, the model does not assume normally distributed error.

Nonparametric bootstrapping approximates the sampling distribution for a statistic of interest (e.g., a slope) by resampling the existing data with replacement many times and examining the resulting density.

```
system.time(lm_cars.boot <- Boot(lm_cars, R=2000))
```

```
##  usuário  sistema decorrido
##    2.29    0.05    2.37
```

```
summary(lm_cars.boot, high.moments=TRUE)
```

```
##
## Number of bootstrap replications R = 2000
##           original bootBias bootSE bootMed bootSkew bootKurtosis
```



```
## (Intercept) -17.5791  0.226401  5.79888 -16.9703 -0.30316      0.41996
## speed        3.9324 -0.023637  0.41637   3.9049  0.21044      0.14774
```


We can use the object to obtain 95% bootstrapped confidence intervals using the ‘bias corrected, accelerated’ method (aka bca).

```
confint(lm_cars.boot, level=.95, type="bca")
```

```
## Bootstrap bca confidence intervals
##
##              2.5 %    97.5 %
## (Intercept) -32.379303 -7.993205
## speed        3.241629  4.933584
```

And we can easily compare the bootstrapped and standard OLS models:

```
hist(lm_cars.boot, legend="separate")
```



Notice that the **speed** regression coefficient is slightly positively skewed. Additional details are provided in John Fox’s useful book “An R Companion to Applied Regression” (2nd edition): <https://socialsciences.mcmaster.ca/jfox/Books/Companion/appendix/Appendix-Bootstrapping.pdf>.

Capítulo 9

Multiple regression

We can easily extend to larger regression models by adding terms to the right side of the formula. For example, in the `mtcars` dataset (car performance statistics from 1974 Motor Trend), we could examine the extent to which the gas mileage (`mpg`) is a function of both gross horsepower (`hp`) and transmission (`am`, where 0 is 'automatic' and 1 is 'manual').

```
mpg_model <- lm(mpg ~ hp + am, mtcars)
summary(mpg_model)
```


```
##
## Call:
## lm(formula = mpg ~ hp + am, data = mtcars)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -4.3843 -2.2642  0.1366  1.6968  5.8657
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  26.584914   1.425094  18.655 < 2e-16 ***
## hp          -0.058888   0.007857  -7.495 2.92e-08 ***
## am           5.277085   1.079541   4.888 3.46e-05 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.909 on 29 degrees of freedom
## Multiple R-squared:  0.782, Adjusted R-squared:  0.767
## F-statistic: 52.02 on 2 and 29 DF, p-value: 2.55e-10
```

It appears that these are both influential predictors. We could examine the

relationship graphically.

9.1 Visualizing regression data

```
ggplot(mtcars, aes(x=hp, y=mpg, color=factor(am))) + geom_point() +
  stat_smooth(method=lm, se=FALSE)
```



There doesn't appear to be any meaningful interaction between horsepower and transmission type.

9.2 Getting results into a tidy, useful format

Note that the `broom` package is very useful for extracting global and specific statistics from many models in R, including regression models. The introductory vignette provides a number of useful examples: <https://cran.r-project.org/web/packages/broom/vignettes/broom.html>. Here, what if we want to save the global statistics and parameter estimates into data.frame objects?

We can use the `glance` function to get the global model statistics.

```
broom::glance(mpg_model)
```

```
## # A tibble: 1 x 12
##   r.squared adj.r.squa~1 sigma stati~2 p.value   df logLik   AIC   BIC devia~3
##   <dbl>         <dbl> <dbl>   <dbl>   <dbl> <dbl> <dbl> <dbl> <dbl>   <dbl>
```

```
## 1      0.782      0.767 2.91    52.0 2.55e-10    2 -78.0 164. 170.    245.
## # ... with 2 more variables: df.residual <int>, nobs <int>, and abbreviated
## #   variable names 1: adj.r.squared, 2: statistic, 3: deviance
```

And the `tidy` function yields the parameter table

```
broom::tidy(mpg_model)
```

```
## # A tibble: 3 x 5
##   term          estimate std.error statistic  p.value
##   <chr>          <dbl>     <dbl>     <dbl>   <dbl>
## 1 (Intercept)    26.6         1.43      18.7 1.07e-17
## 2 hp             -0.0589      0.00786   -7.50 2.92e- 8
## 3 am              5.28         1.08      4.89 3.46e- 5
```

As can imagine (and saw earlier in the functional programming overview), the ability to extract regression statistics into a tidy data.frame is a boon to scaling your analyses to multiple models and datasets.

9.3 Modeling interactions

We can use the `*` operator in R to ask that both the constituent variables and their interaction(s) are entered into the model. For example:

```
int_model <- lm(mpg ~ hp*wt + am, mtcars)
summary(int_model)
```

```
##
## Call:
## lm(formula = mpg ~ hp * wt + am, data = mtcars)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -2.9845 -1.6580 -0.7407  1.4362  4.5266
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  49.452241   5.280731   9.365 5.69e-10 ***
## hp           -0.119303   0.026550  -4.494 0.000119 ***
## wt           -8.100558   1.789325  -4.527 0.000108 ***
## am            0.125107   1.333431   0.094 0.925942
## hp:wt         0.027488   0.008473   3.244 0.003130 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 2.192 on 27 degrees of freedom
## Multiple R-squared:  0.8848, Adjusted R-squared:  0.8677
```

```
## F-statistic: 51.84 on 4 and 27 DF, p-value: 2.765e-12
```

This model includes individual effects of horsepower (**hp**) and weight (**wt**), as well as their interaction (**hp:wt**). This highlights that the asterisk operator ***** will compute all possible interactions among the specified predictors. For example, **a*b*c*d** will generate all effects up through and including the **a x b x c x d** interaction. By contrast, if you wish to specify a given interaction manually/directly, use the colon operator (e.g., **a:b**). The downside of the colon operator is that it doesn't guarantee that the corresponding lower-level effects are included, which is usually a sane default position. As a reminder, you should essentially never include an interaction without including the lower level effects, because this can misassign the variance.

Note that with weight (**wt**) in the model, as well the horsepower x weight interaction, the automatic/manual transmission distinction is no longer significant (not even close). Let's take a look at this interaction. For a two-way continuous x continuous interaction, we typically separate one predictor into low (-1SD), medium (mean), and high (+1SD) levels, and plot separate lines for each.

```
#handy 2-way interaction plotting function from jtools.
interact_plot(int_model, pred = "hp", modx = "wt")
```

What do we see? At higher horsepower, gas mileage suffers regardless of the weight of the car. At lower horsepower, car weight makes a big difference (lower weight, higher mpg).

9.4 Contrasts in regression

(Some of the code and text here has been adapted from Russell Lenth's excellent **emmeans** documentation: <https://cran.r-project.org/web/packages/emmeans/>)

One of the handiest packages in the R regression universe is **emmeans**, which can provide the 'expected marginal means' (em means), as well as a host of other contrasts and comparisons. In particular, it is very easy to test simple slopes and pairwise differences. Furthermore, the package works with **multcomp** to handle correction for multiple comparisons. See the longer documentation here.

Let's look at the concentration of leucine in a study of pigs who were fed differing levels of protein in the diet (9, 12, 15, and 18%) and different protein sources (fish, soybean, milk). The concentration has a long positive tail, so here we log transform it to normalize things somewhat.

```
data(pigs, package="emmeans")
pigs <- pigs %>% mutate(log_conc=log(conc), percent_fac=factor(percent))
pigs.lm <- lm(log_conc ~ source + percent_fac, data = pigs)
summary(pigs.lm)
```

```
##
```

```
## Call:
## lm(formula = log_conc ~ source + percent_fac, data = pigs)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.18858 -0.05980 -0.02158  0.08120  0.24601
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   3.22029    0.05361  60.067 < 2e-16 ***
## sourcesoy     0.27277    0.05293   5.153 3.19e-05 ***
## sourceskim    0.40228    0.05416   7.428 1.50e-07 ***
## percent_fac12 0.17955    0.05608   3.202 0.003960 **
## percent_fac15 0.21740    0.05973   3.640 0.001370 **
## percent_fac18 0.29985    0.06762   4.434 0.000191 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1151 on 23 degrees of freedom
## Multiple R-squared:  0.7566, Adjusted R-squared:  0.7037
## F-statistic: 14.3 on 5 and 23 DF,  p-value: 2.054e-06
```

This output is hard to look at because there are many dummy codes and we have to infer the reference condition for each factor (usually alphabetical). Also, we do not have an intuitive sense of the expected means in each condition because they depend on the sum of the intercept and the specific dummy code for the condition interest, averaging over the other factor.

We can obtain the expected means for each condition.

9.5 Expected means for protein source

```
pigs.emm.s <- emmeans(pigs.lm, "source")
print(pigs.emm.s)
```

```
## source emmean      SE df lower.CL upper.CL
## fish     3.39 0.0367 23      3.32      3.47
## soy      3.67 0.0374 23      3.59      3.74
## skim     3.80 0.0394 23      3.72      3.88
##
## Results are averaged over the levels of: percent_fac
## Confidence level used: 0.95
```

9.6 Expected means for protein level

```
pigs.emm.p <- emmeans(pigs.lm, "percent_fac")
print(pigs.emm.p)
```

```
## percent_fac emmean      SE df lower.CL upper.CL
## 9           3.45 0.0409 23      3.36      3.53
## 12          3.62 0.0384 23      3.55      3.70
## 15          3.66 0.0437 23      3.57      3.75
## 18          3.75 0.0530 23      3.64      3.85
##
## Results are averaged over the levels of: source
## Confidence level used: 0.95
```

9.7 Means in each cell of the factorial design

```
print(emmeans(pigs.lm, ~source*percent_fac))
```

```
## source percent_fac emmean      SE df lower.CL upper.CL
## fish 9           3.22 0.0536 23      3.11      3.33
## soy 9           3.49 0.0498 23      3.39      3.60
## skim 9          3.62 0.0501 23      3.52      3.73
## fish 12          3.40 0.0493 23      3.30      3.50
## soy 12          3.67 0.0489 23      3.57      3.77
## skim 12         3.80 0.0494 23      3.70      3.90
## fish 15          3.44 0.0548 23      3.32      3.55
## soy 15          3.71 0.0507 23      3.61      3.82
## skim 15         3.84 0.0549 23      3.73      3.95
## fish 18          3.52 0.0547 23      3.41      3.63
## soy 18          3.79 0.0640 23      3.66      3.93
## skim 18         3.92 0.0646 23      3.79      4.06
##
## Confidence level used: 0.95
```

9.8 Pairwise comparisons among protein sources

If we wanted to compare the pairwise differences in the effect of protein source on leucine concentration while controlling for protein percentage (and potentially other variables we add to the model), we could use the `pairs` function:

```
pig_pairs <- pairs(pigs.emm.s)
print(pig_pairs)
```

```
## contrast      estimate      SE df t.ratio p.value
## fish - soy    -0.273 0.0529 23  -5.153 0.0001
```



```
## fish - skim    -0.402 0.0542 23   -7.428 <.0001
## soy - skim     -0.130 0.0530 23   -2.442  0.0570
##
## Results are averaged over the levels of: percent_fac
## P value adjustment: tukey method for comparing a family of 3 estimates
```

Note that you can get a sense of the contrasts being tested by `emmeans` by examining the `@linfct` slot of the object. I've learned *a lot* by examining these contrast matrices and thinking about how to setup a (focal) contrast of interest. Also note that you get p-value adjustment for free (here, Tukey's HSD method).

Contrasts for the predicted mean level of leucine contrast for each protein source, controlling for protein percentage.

```
pigs.emm.s@linfct
```

```
##      (Intercept) sourcesoy sourceskim percent_fac12 percent_fac15 percent_fac18
## [1,]           1          0           0           0.25           0.25           0.25
## [2,]           1          1           0           0.25           0.25           0.25
## [3,]           1          0           1           0.25           0.25           0.25
```


What are the pairwise contrasts for the protein sources?

```
pig_pairs@linfct
```

```
##      (Intercept) sourcesoy sourceskim percent_fac12 percent_fac15 percent_fac18
## [1,]           0         -1           0           0           0           0
## [2,]           0          0          -1           0           0           0
## [3,]           0          1          -1           0           0           0
```

The `emmeans` package also provides useful plots to understand pairwise differences:

```
plot(pigs.emm.s, comparisons = TRUE)
```



The blue bars are confidence intervals for the EMMs, and the red arrows are for the comparisons among them. If an arrow from one mean overlaps an arrow from another group, the difference is not significant, based on the adjust setting (which defaults to “tukey”). (Note: Don’t ever use confidence intervals for EMMs to perform comparisons; they can be very misleading.)

9.9 Pairwise differences and simple slopes in regression

Returning to the iris dataset (from the parallel R examples), consider a model in which we examine the association between petal length and width across species. Here, we regress petal length on petal width, species (three levels), and their interaction.

```
fitiris <- lm(Petal.Length ~ Petal.Width * Species, data = iris)
summary(fitiris)
```

```
##
## Call:
## lm(formula = Petal.Length ~ Petal.Width * Species, data = iris)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.84099 -0.19343 -0.03686  0.16314  1.17065
##
```

9.9. PAIRWISE DIFFERENCES AND SIMPLE SLOPES IN REGRESSION 163

```
## Coefficients:
##               Estimate Std. Error t value Pr(>|t|)
## (Intercept)      1.3276      0.1309  10.139 < 2e-16 ***
## Petal.Width       0.5465      0.4900   1.115  0.2666
## Speciesversicolor 0.4537      0.3737   1.214  0.2267
## Speciesvirginica  2.9131      0.4060   7.175 3.53e-11 ***
## Petal.Width:Speciesversicolor 1.3228      0.5552   2.382  0.0185 *
## Petal.Width:Speciesvirginica  0.1008      0.5248   0.192  0.8480
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.3615 on 144 degrees of freedom
## Multiple R-squared:  0.9595, Adjusted R-squared:  0.9581
## F-statistic: 681.9 on 5 and 144 DF,  p-value: < 2.2e-16
```

```
car::Anova(fitiris, type="III") #overall effects of predictors in the model
```

```
## Anova Table (Type III tests)
##
## Response: Petal.Length
##               Sum Sq Df F value    Pr(>F)
## (Intercept)    13.4329  1 102.8050 < 2.2e-16 ***
## Petal.Width      0.1625  1   1.2438 0.2665889
## Species          6.7474  2  25.8196 2.614e-10 ***
## Petal.Width:Species 2.0178  2   7.7213 0.0006525 ***
## Residuals      18.8156 144
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Note that this yields a categorical (species) x continuous (petal width) interaction. The output from `car::Anova` indicates that the interaction is significant, but we need more detailed guidance on how the slope for petal width is moderated by species. We can visualize the interaction as follows:

```
interact_plot(fitiris, pred = "Petal.Width", modx = "Species")
```

In a simple slopes test, we might wish to know whether the slope for `Petal.Width` is non-zero in each species individually. Let's start by getting the estimated marginal means for each species.

```
emmeans(fitiris, ~Species)
```

```
## Species    emmean      SE df lower.CL upper.CL
## setosa      1.98 0.4699 144     1.05     2.91
## versicolor  4.02 0.0609 144     3.90     4.14
## virginica   5.02 0.1636 144     4.69     5.34
##
## Confidence level used: 0.95
```

And pairwise differences between species:

```
pairs(emmeans(fitiris, ~Species))

## contrast      estimate      SE  df t.ratio p.value
## setosa - versicolor    -2.040 0.474 144  -4.306  0.0001
## setosa - virginica     -3.034 0.498 144  -6.097  <.0001
## versicolor - virginica -0.994 0.175 144  -5.692  <.0001
##
## P value adjustment: tukey method for comparing a family of 3 estimates
```

Transitioning to petal width, because we are interested its linear effect (slope), we use the `emtrends` function to estimate the slope in each species individually. In terms of simple slopes, we test whether the `Petal.Width` slope is non-zero in each Species. The `infer` argument in the summary of `emtrends` requests t-tests and p-values for the slopes.

```
summary(emtrends(model = fitiris, ~Species, var="Petal.Width"), infer=TRUE)
```

Finally, we could examine pairwise differences between slopes among species.

```
pairs(emtrends(model = fitiris, ~Species, var="Petal.Width"))
```

9.10 A few other emmeans features

In the `pigs` dataset, we have treated protein percentage as a fact (9, 12, 15, or 18 percent). If we keep this representation (as opposed to entering percentage as continuous), we can easily get orthogonal polynomial contrasts in `emmeans`. For example, is the effect of protein percent linearly related to leucine, or might it be quadratic or cubic?

```
pigs.emm.p <- emmeans(pigs.lm, "percent_fac")
ply <- contrast(pigs.emm.p, "poly")
ply

## contrast estimate      SE df t.ratio p.value
## linear      0.9374 0.2106 23   4.452  0.0002
## quadratic  -0.0971 0.0883 23  -1.099  0.2830
## cubic       0.1863 0.1877 23   0.992  0.3313
##
## Results are averaged over the levels of: source
coef(ply) #show the contrast coefficients

##           percent_fac c.1 c.2 c.3
## percent_fac9          9  -3   1  -1
## percent_fac12         12  -1  -1   3
## percent_fac15         15   1  -1  -3
## percent_fac18         18   3   1   1
```

There is a lot more on probing interactions here: <https://cran.r-project.org/web/packages/emmeans/vignettes/interactions.html>.

Finally, we can examine effects in multivariate regression models (i.e., multiple DVs). Here, we can examine the sales of two varieties of oranges as a function of their prices, the day, and store. Sales for both oranges are modeled at once (`sales1` and `sales2`) to get a sense of price interdependence.

```
org.int <- lm(cbind(sales1, sales2) ~ price1 * price2 + day + store, data = oranges)
summary(org.int)
```

```
## Response sales1 :
##
## Call:
## lm(formula = sales1 ~ price1 * price2 + day + store, data = oranges)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -7.4646 -2.8230  0.4627  1.5425  6.8493
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   67.91880    30.97512   2.193  0.03920 *
## price1        -1.41364     0.60170  -2.349  0.02819 *
## price2        -0.52938     0.68462  -0.773  0.44760
## day2           0.19984     2.57232   0.078  0.93878
## day3           7.57474     2.52069   3.005  0.00652 **
## day4           2.90480     2.52012   1.153  0.26143
## day5           9.68284     2.56659   3.773  0.00105 **
## day6           5.51804     2.53842   2.174  0.04076 *
## store2         1.58480     2.91591   0.544  0.59225
## store3        -0.61385     3.01569  -0.204  0.84057
## store4         2.54945     3.03622   0.840  0.41012
## store5         1.83524     2.86046   0.642  0.52777
## store6         7.01866     2.76358   2.540  0.01867 *
## price1:price2  0.01369     0.01367   1.001  0.32755
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 4.213 on 22 degrees of freedom
## Multiple R-squared:  0.761, Adjusted R-squared:  0.6197
## F-statistic: 5.387 on 13 and 22 DF,  p-value: 0.0002804
##
##
## Response sales2 :
##
## Call:
```

```
## lm(formula = sales2 ~ price1 * price2 + day + store, data = oranges)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -8.5004 -1.8640 -0.1674  2.7834  9.9762
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  -47.88395    38.70597   -1.237  0.22909
## price1         1.69081     0.75187    2.249  0.03487 *
## price2         0.89372     0.85549    1.045  0.30751
## day2        -2.03219     3.21433   -0.632  0.53375
## day3         10.10986     3.14981    3.210  0.00404 **
## day4         3.96694     3.14910    1.260  0.22097
## day5         7.72972     3.20716    2.410  0.02475 *
## day6         5.06292     3.17196    1.596  0.12472
## store2        6.73894     3.64367    1.849  0.07787 .
## store3        2.05515     3.76835    0.545  0.59099
## store4        5.68186     3.79401    1.498  0.14845
## store5        6.40091     3.57438    1.791  0.08710 .
## store6        5.14117     3.45332    1.489  0.15075
## price1:price2 -0.03199     0.01708   -1.872  0.07450 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 5.265 on 22 degrees of freedom
## Multiple R-squared:  0.7783, Adjusted R-squared:  0.6473
## F-statistic:  5.94 on 13 and 22 DF,  p-value: 0.0001367
```

Using `emmeans`, we can test the difference in sales of the two orange varieties as a function of the price of the first type (`price1`).

```
#test the pairwise differences in price1 slopes between varieties.
emtrends(org.int, pairwise ~ variety, var = "price1", mult.name = "variety")
```

```
## $emtrends
##  variety price1.trend    SE df lower.CL upper.CL
##  sales1      -0.749 0.171 22   -1.104   -0.394
##  sales2       0.138 0.214 22   -0.306    0.582
##
## Results are averaged over the levels of: day, store
## Confidence level used: 0.95
##
## $contrasts
##  contrast      estimate    SE df t.ratio p.value
##  sales1 - sales2  -0.887 0.24 22   -3.690  0.0013
##
```

```
## Results are averaged over the levels of: day, store
```


Referências Bibliográficas

- Hadley Wickham. *tidyverse: Easily Install and Load the Tidyverse*, 2023. URL <https://CRAN.R-project.org/package=tidyverse>. R package version 2.0.0.
- Hadley Wickham and Lionel Henry. *purrr: Functional Programming Tools*, 2023. URL <https://CRAN.R-project.org/package=purrr>. R package version 1.0.1.
- Hadley Wickham, Mara Averick, Jennifer Bryan, Winston Chang, Lucy D’Agostino McGowan, Romain François, Garrett Golemund, Alex Hayes, Lionel Henry, Jim Hester, Max Kuhn, Thomas Lin Pedersen, Evan Miller, Stephan Milton Bache, Kirill Müller, Jeroen Ooms, David Robinson, Dana Paige Seidel, Vitalie Spinu, Kohske Takahashi, Davis Vaughan, Claus Wilke, Kara Woo, and Hiroaki Yutani. Welcome to the tidyverse. *Journal of Open Source Software*, 4(43):1686, 2019. doi: 10.21105/joss.01686.
- Hadley Wickham, Winston Chang, Lionel Henry, Thomas Lin Pedersen, Kohske Takahashi, Claus Wilke, Kara Woo, Hiroaki Yutani, and Dewey Dunnington. *ggplot2: Create Elegant Data Visualisations Using the Grammar of Graphics*, 2023a. URL <https://CRAN.R-project.org/package=ggplot2>. R package version 3.4.1.
- Hadley Wickham, Romain François, Lionel Henry, Kirill Müller, and Davis Vaughan. *dplyr: A Grammar of Data Manipulation*, 2023b. URL <https://CRAN.R-project.org/package=dplyr>. R package version 1.1.1.
- Hadley Wickham, Davis Vaughan, and Maximilian Girlich. *tidyr: Tidy Messy Data*, 2023c. URL <https://CRAN.R-project.org/package=tidyr>. R package version 1.3.0.
- Yihui Xie. *bookdown: Authoring Books and Technical Documents with R Markdown*, 2023a. URL <https://CRAN.R-project.org/package=bookdown>. R package version 0.33.
- Yihui Xie. *knitr: A General-Purpose Package for Dynamic Report Generation in R*, 2023b. URL <https://yihui.org/knitr/>. R package version 1.42.