

Chapter 1

Library c01_basics

Capítulo 1 - Functional Programming in Coq (Basics)

Booleano

Inductive *bool* : Type :=

| *true* : *bool*
| *false* : *bool*.

Negação

Definition *negb* (*x*: *bool*) : *bool* :=

match *x* **with**
| *true* \Rightarrow *false*
| *false* \Rightarrow *true*
end.

Notation " \sim *x*" := (*negb* *x*).

Tabela Verdade - Negação

Example *test_negb1* : (*negb true*) = *false*.

Example *test_negb2* : (*negb false*) = *true*.

Conjunção

Definition *andb* (*x y*: *bool*) : *bool* :=

match (*x, y*) **with**
| (*true, true*) \Rightarrow *true*
| _ \Rightarrow *false*
end.

Notation "*x* /\ *y*" := (*andb* *x y*).

Tabela Verdade - Conjunção

Example *test_andb1* : (*andb true true*) = *true*.

Example *test_andb2* : (*andb true false*) = *false*.

Example *test_andb3* : (*andb false true*) = *false*.

Example *test_andb4* : (*andb false false*) = *false*.

Disjunção

Definition *orb* (*x y*: *bool*) : *bool* :=
 match (*x, y*) with
 | (*false, false*) ⇒ *false*
 | _ ⇒ *true*
end.

Notation "*x \\/ y*" := (*orb x y*).

Tabela Verdade - Disjunção

Example *test_orb1* : (*orb true true*) = *true*.

Example *test_orb2* : (*orb true false*) = *true*.

Example *test_orb3* : (*orb false true*) = *true*.

Example *test_orb4* : (*orb false false*) = *false*.

Implicação

Definition *implb* (*x y*: *bool*) : *bool* :=
 match (*x, y*) with
 | (*true, false*) ⇒ *false*
 | _ ⇒ *true*
end.

Notation "*x -> y*" := (*implb x y*).

Tabela Verdade - Implicação

Example *test_implb1* : (*implb true true*) = *true*.

Example *test_implb2* : (*implb true false*) = *false*.

Example *test_implb3* : (*implb false true*) = *true*.

Example *test_implb4* : (*implb false false*) = *true*.

Bi-implicação

Definition *biimplb* (*x y*: *bool*) : *bool* :=
 match (*x, y*) with
 | (*true, true*) ⇒ *true*
 | (*false, false*) ⇒ *true*
 | _ ⇒ *false*
end.

Notation "*x <-> y*" := (*biimplb x y*).

Tabela Verdade - Bi-implicação

Example *test_biimplb1* : (*biimplb true true*) = *true*.

Example *test_biimplb2* : (*biimplb true false*) = *false*.

Example *test_biimplb3* : (*biimplb false true*) = *false*.

Example *test_biimplb4* : (*biimplb false false*) = *true*.

Exercise: 1 star, standard (*nandb*)

Definition *nandb* (*x y* : *bool*) : *bool* :=
 match (*x, y*) with
 | (*true, true*) ⇒ *false*
 | _ ⇒ *true*
end.

Example *test_nandb1*: (*nandb true false*) = *true*.

Example *test_nandb2*: (*nandb false false*) = *true*.

Example *test_nandb3*: (*nandb false true*) = *true*.

Example *test_nandb4*: (*nandb true true*) = *false*.

Exercise: 1 star, standard (*andb3*)

Definition *andb3* (*x y z* : *bool*) : *bool* :=
 match (*x, y, z*) with
 | (*true, true, true*) ⇒ *true*
 | _ ⇒ *false*
end.

Example *test_andb31*: (*andb3 true true true*) = *true*.

Example *test_andb32*: (*andb3 false true true*) = *false*.

Example *test_andb33*: (*andb3 true false true*) = *false*.

Example *test_andb34*: (*andb3 true true false*) = *false*.

Naturais

Definition *minustwo* (*x* : *nat*) : *nat* :=
 match *x* with
 | *O* ⇒ *O*
 | *S O* ⇒ *O*
 | *S (S n')* ⇒ *n'*
end.

Par

```

Fixpoint evenb (x: nat) : bool :=
  match x with
  | 0 => true
  | S 0 => false
  | S (S x') => evenb x'
  end.

```

Example *test_evenb1* : (evenb 2) = true.

Example *test_evenb2* : (evenb 3) = false.

Ímpar

```

Fixpoint oddb (x: nat) : bool :=
  match x with
  | 0 => false
  | S 0 => true
  | S (S x') => oddb x'
  end.

```

Example *test_oddb1* : (oddb 3) = true.

Example *test_oddb2* : (oddb 2) = false.

Adição

```

Fixpoint plus (x y : nat) : nat :=
  match x with
  | 0 => y
  | S x' => S (plus x' y)
  end.

```

Notation "x + y" := (plus x y) (at level 50, left associativity) : nat_scope.

Example *test_plus1* : (plus 2 3) = 5.

Subtração

```

Fixpoint minus (x y:nat) : nat :=
  match x, y with
  | 0, _ => 0
  | S _, 0 => x
  | S x', S y' => minus x' y'
  end.

```

Notation "x - y" := (minus x y) (at level 50, left associativity) : nat_scope.

Example *test_minus1* : (minus 5 2) = 3.

Multiplicação

```

Fixpoint mult (x y : nat) : nat :=

```

```

match x with
| O ⇒ O
| S x' ⇒ plus y (mult x' y)
end.

```

Notation "x * y" := (mult x y) (at level 40, left associativity) : nat_scope.

Example test_mult1: (mult 3 4) = 12.

Potenciação

```

Fixpoint exp (b p : nat) : nat :=
  match p with
  | O ⇒ S O
  | S p' ⇒ mult b (exp b p')
  end.

```

Notation "x ^ y" := (exp x y).

Example test_exp1 : (exp 3 2) = 9.

Exercise: 1 star, standard (factorial)

```

Fixpoint factorial (x: nat) : nat :=
  match x with
  | O ⇒ 1
  | S x' ⇒ x × (factorial x')
  end.

```

Example test_factorial1: (factorial 3) = 6.

Example test_factorial2: (factorial 5) = (mult 10 12).

Função 'igual que'

```

Fixpoint eqb (x y : nat) : bool :=
  match x with
  | O ⇒ match y with
        | O ⇒ true
        | S y' ⇒ false
      end
  | S x' ⇒ match y with
        | O ⇒ false
        | S y' ⇒ eqb x' y'
      end
  end.

```

Notation "x = y" := (eqb x y) (at level 70) : nat_scope.

Example test_eqb1 : (eqb 3 3) = true.

Example *test_eqb2* : (*eqb* 2 3) = *false*.

Função 'menor ou igual que'

```
Fixpoint leb (x y : nat) : bool :=  
  match x with  
  | O => true  
  | S x' => match y with  
    | O => false  
    | S y' => leb x' y'  
  end  
end.  
end.
```

Notation "x <= y" := (*leb* x y) (at level 70) : *nat_scope*.

Example *test_leb1* : (*leb* 2 2) = *true*.

Example *test_leb2* : (*leb* 2 4) = *true*.

Example *test_leb3* : (*leb* 4 2) = *false*.

Exercise: 1 star, standard (*ltb*) - Função 'menor que'

```
Definition ltb (x y : nat) : bool :=  
  (andb (leb x y) (negb (eqb x y))).
```

Notation "x < y" := (*ltb* x y) (at level 70) : *nat_scope*.

Example *test_ltb1* : (*ltb* 2 2) = *false*.

Example *test_ltb2* : (*ltb* 2 4) = *true*.

Example *test_ltb3* : (*ltb* 4 2) = *false*.

Exemplo rewrite

```
Theorem plus_id_example : ∀ x y : nat,  
  x = y →  
  x + x = y + y.
```

```
Theorem plus_id_example' : ∀ x y : nat,  
  x = y →  
  x + x = y + y.
```

Exercise: 1 star, standard (*plus_id_exercise*)

Theorem *plus_id_exercise* :

```
  ∀ x y z : nat,  
  x = y →  
  y = z →  
  x + y = y + z.
```

Exercise: 2 stars, standard (*mult_S_1*)

Theorem *mult_S_1* :

$\forall x y : nat,$
 $y = S\ x \rightarrow$
 $y \times (1 + x) = y \times y.$

Dupla Negação

Theorem *negb_involutive* :

$\forall x : bool,$
 $negb\ (negb\ x) = x.$

Theorem *negb_involutive'* :

$\forall x : bool,$
 $negb\ (negb\ x) = x.$

Theorem *negb_involutive''* :

$\forall x : bool,$
 $negb\ (negb\ x) = x.$

Comutação **Theorem** *andb_commutative* :

$\forall x y,$
 $andb\ x\ y = andb\ y\ x.$

Theorem *andb_commutative'* :

$\forall x y,$
 $andb\ x\ y = andb\ y\ x.$

Theorem *andb_commutative''* :

$\forall x y,$
 $andb\ x\ y = andb\ y\ x.$

Exercise: 2 stars, standard (*andb_true_elim2*) **Theorem** *andb_true_elim2* :

$\forall x y : bool,$
 $andb\ x\ y = true \rightarrow$
 $y = true.$

Theorem *andb_true_elim2'* :

$\forall x y : bool,$
 $andb\ x\ y = true \rightarrow$
 $y = true.$

Exercise: 1 star (*zero_nbeq_plus_1*)

Theorem *zero_nbeq_plus_1* :

$\forall x : nat,$
 $(0 = x + 1) = false.$

Theorem *zero_nbeq_plus_1'* :

$\forall x : nat,$
 $(0 = x + 1) = false.$

Exercise: 2 stars (*boolean_functions*) **Theorem** *identity_fn_applied_twice* :

$\forall (f : bool \rightarrow bool),$

$(\forall (x : \text{bool}), f\ x = x) \rightarrow$
 $\forall (b : \text{bool}), f\ (f\ b) = b.$

Exercise: 1 star, standard (negation_fn_applied_twice)

Theorem *negation_fn_applied_twice* :

$\forall (f : \text{bool} \rightarrow \text{bool}),$
 $(\forall (x : \text{bool}), f\ x = \text{negb}\ x) \rightarrow$
 $\forall (b : \text{bool}), f\ (f\ b) = b.$

Exercise: 2 stars (andb_eq_orb)

Theorem *andb_eq_orb* :

$\forall (x\ y : \text{bool}),$
 $(\text{andb}\ x\ y = \text{orb}\ x\ y) \rightarrow$
 $x = y.$

Exercise: 3 stars, standard (binary)

Inductive *bin* : Type :=

| *Z* : *bin*
| *A* : *bin* \rightarrow *bin*
| *B* : *bin* \rightarrow *bin*.

Fixpoint *incr* (*x* : *bin*) : *bin* :=

match *x* with
| *Z* \Rightarrow *B Z*
| *A x'* \Rightarrow *B x'*
| *B x'* \Rightarrow *A (incr x')*
end.

Fixpoint *bin_to_nat* (*x* : *bin*) : *nat* :=

match *x* with
| *Z* \Rightarrow *O*
| *A x'* \Rightarrow *mult* 2 (*bin_to_nat x'*)
| *B x'* \Rightarrow *S (mult 2 (bin_to_nat x'))*
end.

Example *inc_three_four*: (*bin_to_nat (incr (B (B Z)))*) = 4.

Example *inc_nine_ten*: (*bin_to_nat (incr (B (A (A (B Z))))*) = 10.

Example *zero_is_zero*: (*bin_to_nat Z*) = 0.

Example *five_is_five*: (*bin_to_nat (B (A (B Z)))*) = 5.

Fixpoint *incN* (*n*:*nat*) (*m*:*bin*) :=

match *n* with
| 0 \Rightarrow *m*
| *S n'* \Rightarrow *incN n' (incr m)*
end.

Example *SanityCheck*: *bin_to_nat (incN 15 Z)* = 15.