NAMESPACES AND PREFIXES

```
@prefix dbpedia: <a href="http://dbpedia.org/resource/">http://dbpedia.org/resource/</a>.

@prefix: <a href="http://dbpedia.org/ontology/">http://dbpedia.org/ontology/</a>.

Default namespace

rdf: is a shorthand for http://sa is shorthand for rdf:type:

a is shorthand for rdf:type:

Amsterdam al: Place

Non-abbreviated version:

<a href="http://dbpedia.org/resource/Amsterdam">http://dbpedia.org/resource/Amsterdam</a> rdf:type: <a href="http://dbpedia.org/ontology/Place">http://dbpedia.org/ontology/Place</a>>
```

SHORTHANDS

Default Abbreviations

```
dbpedia:Amsterdam rdf:type: :Place .

dbpedia:Amsterdam a :Place .
```

| Subject Sharing | dbpedia: Amsterdam | officialName "Amsterdam" | dbpedia: Amsterdam | areaTotal 219320000 | dbpedia: Amsterdam | officialName "Amsterdam" | isCapital true | dbpedia: Amsterdam | officialName "Amsterdam" | areaTotal 219320000 | isCapital true | isCapital true | | white | whit

```
"The Netherlands"@en ,
"Pays-Bas"@fr ;
capital dbpedia:Amsterdam .
```

dbpedia:Netherlands:rdfs:label "Nederland"@nl,

LITERALS

TAGS

```
dbpedia: Amsterdam rdfs: label "Amsterdam"@nl .

Specifies langua
```

BLANK NODES

Blank Node: An object that has no URI, and is used in a similar fashion to the connector element of UML schemas. It serves as a terminal or intermediary between two or more elements.

Normal Syntax