

2. THE FOLLOWING SYMBOLS DENOTE:-1. NOTES ON ALL DRAWINGS APPLY WHERE APPROPRIATE.

- COMBINED HEAT DETECTOR, SPEECH SOUNDER & STROBE
- COMBINED HEAT & CARBON MONOXIDE DETECTIOR

 SMOKE DETECTOR

 SMOKE DETECTOR LOCATED IN CEILING
 COMBINED SMOKE DETECTOR, SPEECH
 SOUNDER & STROBE

OPTICAL HEAT MULTISENSOR, SPEECH
SOUNDER, STROBE FIRE ALARM HEAD.

MANUAL CALL POINT (NUMBER BELOW DENOTES FIRE PANEL LOOP.

⊕

GREEN MANUAL CALL POINT FOR OVERRIDDING ELECTRONIC DOOR CONTROLS.

SPEECH SOUNDER STROBE.

NED MAIN FIRE ALARM PANEL

NED MOTORIZED FIRE DAMPER.

REFUGE INTERCOM.

MAIN REFUGE INTERCOM

DOOR HOLD OPEN DEVICES.

FLOOR MOUNTED DOOR HOLD OPEN

DEVICE.

ALL VOID DETECTION TO HAVE REMOTE VISIBLE INDICATORS

AUTOMATIC INTERFACE TO THE FIRE ALARM SYSTEM.

- THEAT DETECTOR

3682/E301

FIRE ALARM

BASEMENT

ELECTRICAL SERVICES INSTALLATION

ICA ARCHITECTS

Caldwell

DW MB
DW MB
DW MB
DW MB
CK

SOLE/FRANTDAT DATE DAWN CHEXED 1:125@A1 JAN'15 DW CHEXED UNT 6 FORESTIGRONE BUSINESS PARK TEL (028)90599720 FAX (028)90641625 NEWTOWNBREDA BTB 6AWN EDMAIL: odmin@coldwellconsulting.net 2