

NOTES

1. NOTES ON ALL DRAWINGS APPLY WHERE APPROPRIATE.
2. THE FOLLOWING SYMBOLS DENOTE:--

- ② HEAT DETECTOR
- ☼ COMBINED HEAT DETECTOR, SPEECH
SOUNDER & STROBE
- ☼ COMBINED HEAT & CARBON MONOXIDE
DETECTOR
- ☼ SMOKE DETECTOR
- ☼ SMOKE DETECTOR LOCATED IN CEILING
VOID
- ☼ COMBINED SMOKE DETECTOR, SPEECH
SOUNDER & STROBE
- ☼ OPTICAL, HEAT, ULTRASONIC, SPEECH
SOUNDER, STROBE FIRE ALARM HEAD,
MANUAL CALL POINT (NUMBER BELOW
DENOTES FIRE PANEL LOOP).
- ☼ GREEN MANUAL CALL POINT FOR
OVERRIDEING ELECTRONIC DOOR
CONTROLS.
- ☼ FIREMAN'S WINDOW CONTROL.
- ☼ SPEECH SOUNDER STROBE.
- ☼ MAIN FIRE ALARM PANEL.
- ☼ MOTORIZED FIRE DAMPER.
- ☼ REFUGE INTERCOM.
- ☼ MAIN REFUGE INTERCOM.
- ☼ DOOR HOLD OPEN DEVICES.
- ☼ FLOOR MOUNTED DOOR HOLD OPEN
DEVICE.
- ☼ AUTOMATIC INTERFACE TO THE FIRE
ALARM SYSTEM.
3. ALL VOID DETECTION TO HAVE REMOTE VISIBLE
INDICATORS

