

1. NOTES ON ALL DRAWINGS APPLY WHERE APPROPRIATE.

HEAT DETECTOR

COMBINED HEAT DETECTOR, SPEECH
SOUNDER & STROBE

COMBINED HEAT & CARBON MONOXIDE DETECTOR

ALL VOID DETECTION TO HAVE REMOTE VISIBLE INDICATORS

AUTOMATIC INTERFACE TO THE FIRE ALARM SYSTEM. FLOOR MOUNTED DOOR HOLD OPEN DEVICE. MAIN REFUGE INTERCOM
DOOR HOLD OPEN DEVICES. SPEECH SOUNDER STROBE.

IND MAIN FIRE ALARM PANEL

MED MOTORIZED FIRE DAMPER.

REFUGE INTERCOM.

OPTICAL HEAT MULTISENSOR, SPEECH SOUNDER, STROBE FIRE ALARM HEAD.

MANUAL CALL POINT (NUMBER BELOW DENOTES FIRE PANEL LOOP.

GREEN MANUAL CALL POINT FOR OVERRIDDING ELECTRONIC DOOR CONTROLS.

SMOKE DETECTOR

SMOKE DETECTOR

SMOKE DETECTOR LOCATED IN CELLING
WIDD

COMBINED SMOKE DETECTOR, SPEECH

SOUNDER & STROBE

2. THE FOLLOWING SYMBOLS DENOTE:-

DR MB

3682/E304

SCALE/PRINTEDÁT DATE TILL (125@AAT LAN'15 DW CHEXED

1:125@A1 JAN'15 DW CHEXED

UNIT 6 FORESTIGROE BUSINESS PARK TEL (028)90069720 FAX (028)90641625

NEWTOWNEREDA BT8 6AW EMAALL: odmin@coldwellconsulting.net