
apysheII

Release 1.0

Mark Anacker

Nov 21, 2023

CONTENTS

1 **apyshe ll package** 1

1.1 Subpackages 1

1.2 Submodules 1

1.2.1 apyshe ll.apyshe ll module 1

1.2.2 apyshe ll.extensionapi module 2

1.2.3 apyshe ll.extensionmgr module 3

1.2.4 apyshe ll.support module 6

1.3 Module contents 7

Python Module Index 9

Index 11

APYSHELL PACKAGE

1.1 Subpackages

1.2 Submodules

1.2.1 apyshell.apyshell module

apyshell - Python Embedded apy script runnner

This script creates a framework for running lightweight scripts under the apyengine interpreter. It demonstrates embedding and controlling the engine. It can be run either stand-alone, or itself embedded into an application.

Credits

- version: 1.0
- last update: 2023-Nov-17
- License: MIT
- Author: Mark Anacker <closecrowd@pm.me>
- Copyright (c) 2023 by Mark Anacker

apyshell (*script*, *basedir*='/opt/apyshell/scripts', *extensiondir*='/opt/apyshell/extensions', *extension_opts*=None, *args*=None, *initscript*=None, *globals*=False)
Execute a script file under anyengine.

This is the main entry point.

Args: script : The .apy script to execute.

Returns: The return value. True for success, False otherwise.

savepid (*pfile*)
Save our current PID if we can.

Note: this doesn't do any checking of the file path. Take care if running under root.

usage ()
Help message.

1.2.2 apysheIl.extensionapi module

extensionapi - The interface between extensions and the engine.

An instance of this class is passed to the extensions at load time to give them an API back into the engine via the ExtensionMgr

Credits

- version: 1.0
- last update: 2023-Nov-20
- License: MIT
- Author: Mark Anacker <closecrowd@pm.me>
- Copyright (c) 2023 by Mark Anacker

class ExtensionAPI (*eng, parent, internal=True*)

Bases: object

getSysvar_ (*name, default=None*)

Return the value of a system variable or a default

getVar_ (*vname, default=None*)

Return the value of a script variable or a default

handleEvents (*name, data*)

Handle callback events.

If an extension allows for handlers to receive events, each callback comes through here. This function passes the name and data object through to the ExtensionMgr to run in the engine.

Args:

name : The name of the handler func().

data : The object to pass as the **only** argument to the handler.

Returns:

ret : A string with the return from the handler()

None : Something failed

isDef_ (*name*)

Return True is the name is defined

listDefs_ (*exception_list=None*)

Return a list of script def procs

list_Modules_ ()

Return a list of install_()-ed modules

loadScript_ (*filename, persist=False*)

Load and execute a script file

logError (*modname="", *args*)

regcmd (*name, func=None*)

Add a new command callable by scripts

registerCmds (*mdict*)

Make an extension's functions available to scripts

Extensions call here through the api reference to install their commands into the engine.

Args:

mdict : A dict with the commands and function refs.

Returns

True [Commands are installed and the extension is] ready to use.

False [Commands are NOT installed, and the extension] is inactive.

setSysvar__ (*name, val*)

Set a system variable

setvar__ (*vname, val*)

Set a script variable

unregisterCmds (*mdict*)

Remove an extension's commands from the engine.

Extensions call here through the api reference to remove their commands from the engine.

Args:

mdict : A dict with the commands and function refs.

Returns

True : Commands have been removed.

False : Something failed.

debug (**args*)

1.2.3 apysheIl.extensionmgr module

extensionmgr - Handles extension load/unload for apysheIl.

This module supports the extension handling commands for apysheIl.

Credits

- version: 1.0
- last update: 2023-Nov-20
- License: MIT
- Author: Mark Anacker <closecrowd@pm.me>
- Copyright (c) 2023 by Mark Anacker

class ExtensionMgr (*eng, epath, options=None*)

Bases: object

handleEvents (*name, data*)

Handle callback events.

If an extension allows for handlers to receive events, each callback comes through here. This function makes sure the handler (a `def func()` in the script) is defined. It then executes the handler `func` **in the context of the thread that calls this method**. This may not be the thread that the majority of the script is running on.

Args:

name : The name of the handler `func()`.

data : The object to pass as the **only** argument to the handler.

Returns:

ret : A string with the return from the handler()

None : Something failed

isExtLoaded_(*ename*)

Handles the `isExtLoaded_()` function.

This function is used to test whether an extension is currently loaded or not.

Args:

ename : The name of the extension to check.

Returns:

True : The extension is loaded.

False : It's not loaded.

listExtensions_()

Handles the `listExtensions_()` function.

Return a `list[]` of currently-loaded extensions - those that a script has used `loadExtension_()` to install.

Args:

None

Returns:

A `list[]` of the loaded extension names.

None if there are no loaded extensions.

loadExtension_(*ename*)

Handles the `loadExtension_()` function.

This function loads an extension by name (no paths allowed), if it's in the `__availExtensions` list. If the list is empty, the extensions directories are scanned.

If the extension is available, it's loaded into the engine's symbol table and the `register()` function is called to add it's functions.

Args:

ename : The name of the extension to load.

Returns:

True : The extension loaded correctly.

False : It didn't load.

register()

Make this extension's functions available to scripts

This method installs our script API methods as functions in the engine symbol table, making them available to scripts.

Note:**Functions installed:**

- `scanExtensions_()` : Look through the extensions dir and return a list of available extensions.
- `listExtensions_()` : Return a list of loaded extensions.
- `isExtLoaded_()` : Return True if the extension is loaded.
- `loadExtension_()` : Load an extension into the engine.
- `unloadExtension_()` : Remove an extension from the engine.

Args:

None

Returns

True [Commands are installed and the extension is] ready to use.

False [Commands are NOT installed, and the extension] is inactive.

scanExtensions_()

Handles the `scanExtensions_()` function.

This function builds a list of the Python files in the extension director(ies) stored in `self.__expath`. This can be either a single directory, or a list of them. All `.py` files in these directories are presumed to be extensions, although there is a signature test performed at extension load time.

You can limit which extensions are available simply by limiting which files are placed into these directories.

Args:

None

Returns:

A list[] of the available extension names.

None if there are no extensions.

scanForExtensions (*dir, iflag*)**shutdown()**

Perform a graceful shutdown.

Calls the `shutdown()` method of each loaded extension, making sure they go cleanly.

This gets called by apyshell just before it exits.

unloadExtension_ (*ename*)

Handles the `unloadExtension_()` function.

This function removes a currently-loaded extension from the symbol table, making it unavailable to scripts. It calls the `shutdown()` and `unregister()` methods in the extension before removing it.

Args:

ename : The name of the extension to unload.

Returns:

True : The extension unloaded correctly.

False : There was an error.

quoteSpecial (*orig*)

1.2.4 apysheIl.support module

support - Various stand-alone support functions for apysheIl.

This file contains various utility functions used by apysheIl.

Credits

- version: 1.0
- last update: 2023-Nov-13
- License: MIT
- Author: Mark Anacker <closecrowd@pm.me>
- Copyright (c) 2023 by Mark Anacker

checkFileName (*fname*)

Check a file name

Checks the given filename for characters in the set of a-z, A-Z, _ or -

Args: fname : The name to check

Returns: True if the name is entirely in that set False if there were invalid char(s)

debugMsg (*source*=", *args)

enableDebug (*arg*)

errorMsg (*source*=", *args)

get_queue (*q, defvalue=None, timeout=0*)

getparam (*table, key, default, remove=False*)

retError (*api, module, msg, ret=False*)

sanitizePath (*path*)

Clean a path.

Remove dangerous characters from a path string.

Args: path : The strin with the path to clean

Returns: The cleaned path or None if there was a problem

setparam (*table, key, value, replace=False*)

swapparam (*table, oldkey, newkey, value=None*)

unlock__ (*lock*)

1.3 Module contents

ApyShell - Python Embedded apy script runnner

This package creates a framework for running lightweight scripts under the apyengine interpreter. It demonstrates embedding and controlling the engine. It can be run either stand-alone, or itself embedded into an application.

The companion project “apyengine” has documentation and examples of how to use the apyengine outside of this package. The entire apyengine package is included in this package for convenience. <<https://github.com/closecrowd/apyengine>>

Credits

- version: 1.0
- last update: 2023-Nov-17
- License: MIT
- Author: Mark Anacker <closecrowd@pm.me>
- Copyright (c) 2023 by Mark Anacker

PYTHON MODULE INDEX

a

- `apyshell`, [7](#)
- `apyshell.apyshell`, [1](#)
- `apyshell.extensionapi`, [2](#)
- `apyshell.extensionmgr`, [3](#)
- `apyshell.support`, [6](#)

A

apyshell
 module, 7
 apyshell() (in module *apyshell.apyshell*), 1
 apyshell.apyshell
 module, 1
 apyshell.extensionapi
 module, 2
 apyshell.extensionmgr
 module, 3
 apyshell.support
 module, 6

C

checkFileName() (in module *apyshell.support*), 6

D

debug() (in module *apyshell.extensionapi*), 3
 debugMsg() (in module *apyshell.support*), 6

E

enableDebug() (in module *apyshell.support*), 6
 errorMsg() (in module *apyshell.support*), 6
 ExtensionAPI (class in *apyshell.extensionapi*), 2
 ExtensionMgr (class in *apyshell.extensionmgr*), 3

G

get_queue() (in module *apyshell.support*), 6
 getparam() (in module *apyshell.support*), 6
 getSysvar_() (ExtensionAPI method), 2
 getvar_() (ExtensionAPI method), 2

H

handleEvents() (ExtensionAPI method), 2
 handleEvents() (ExtensionMgr method), 3

I

isDef_() (ExtensionAPI method), 2
 isExtLoaded_() (ExtensionMgr method), 4

L

list_Modules_() (ExtensionAPI method), 2

listDefs_() (ExtensionAPI method), 2
 listExtensions_() (ExtensionMgr method), 4
 loadExtension_() (ExtensionMgr method), 4
 loadScript_() (ExtensionAPI method), 2
 logError() (ExtensionAPI method), 2

M

module
 apyshell, 7
 apyshell.apyshell, 1
 apyshell.extensionapi, 2
 apyshell.extensionmgr, 3
 apyshell.support, 6

Q

quoteSpecial() (in module *apyshell.extensionmgr*), 6

R

regcmd() (ExtensionAPI method), 2
 register() (ExtensionMgr method), 4
 registerCmds() (ExtensionAPI method), 2
 retError() (in module *apyshell.support*), 6

S

sanitizePath() (in module *apyshell.support*), 6
 savepid() (in module *apyshell.apyshell*), 1
 scanExtensions_() (ExtensionMgr method), 5
 scanForExtensions() (ExtensionMgr method), 5
 setparam() (in module *apyshell.support*), 6
 setSysvar_() (ExtensionAPI method), 3
 setvar_() (ExtensionAPI method), 3
 shutdown() (ExtensionMgr method), 5
 swapparam() (in module *apyshell.support*), 6

U

unloadExtension_() (ExtensionMgr method), 5
 unlock__() (in module *apyshell.support*), 6
 unregisterCmds() (ExtensionAPI method), 3
 usage() (in module *apyshell.apyshell*), 1