Cross-Channel Agreement Beats Consensus: Compositional Verification for Geometry Reasoning

Anonymous Author(s)
Affiliation
Address
email

Abstract

Multimodal geometry reasoning requires models to jointly perceive diagrams and perform symbolic derivations. Test-time verification methods such as majority voting assume voter errors are roughly independent, but in geometry this assumption breaks down: all candidates perceive the same diagram, so perceptual biases cascade into correlated errors that produce confident but wrong consensus. We observe that neuro-symbolic candidates contain compositional structure that can serve as a verification resource. We introduce SKETCH, a format decomposing each candidate into a neural pathway (natural-language claim) and a symbolic pathway (visual grounding $\rightarrow$ typed DSL $\rightarrow$ deterministic execution). These pathways are governed by different error processes—symbolic errors are correlated across candidates through shared perception, while neural errors are more dispersed. Our method, Compositional Consensus Verification (CCV), gates consensus on cross-channel agreement: because the two pathways fail for different reasons, accidental agreement is rare, making each concordant vote far more precise than a raw majority vote. Across four geometry benchmarks, CCV achieves 81.0% accuracy (+10.4 pp over majority voting) without external scorers or additional inference. Seven non-compositional baselines—including trained PRMs—cluster at 70–71%, while compositional cross-layer features jump to 79–81%, confirming that structural diversity is the core verification resource, and that a principled gating algorithm effectively unlocks its potential.

1 Introduction

The verification bottleneck in geometry reasoning. Geometry reasoning differs from purely textual mathematical tasks in a fundamental way: it requires joint visual perception and symbolic derivation. A model must read spatial relationships from a diagram—angles, parallel lines, congruences—and then chain these percepts through multi-step logical deductions. This conjunction makes geometry a task that current vision-language models find difficult Gao et al. [2023], Xia et al. [2024], Zhang et al. [2024b], and it also creates a distinctive failure mode for test-time verification. Figure 1 summarizes our proposed solution.

The standard approach for improving reasoning accuracy at test time is self-consistency Wang et al. [2022]: sample K candidates and select the most frequent answer via majority voting (MV). This rests on the Condorcet assumption that voter errors are approximately independent, so that the majority converges to truth as K grows. In geometry, this assumption breaks down in a specific and measurable way. All K candidates perceive the *same* diagram; if the model harbors a systematic perceptual bias—misidentifying a perpendicular as supplementary, or misreading an angle label—then a majority of candidates will share the same error. Votes become correlated because they reflect the same perceptual errors. Formally, when the pairwise error correlation ρ is substantial, the effective

Submitted to 40th Conference on Neural Information Processing Systems (NeurIPS 2026). Do not distribute.




Figure 1: **Method overview.** A geometry problem is sampled into $K{=}16$ SKETCH candidates. Each candidate exposes a symbolic pathway (VGF $\rightarrow$ typed DSL $\rightarrow$ execution) and a neural pathway (claim). Cross-channel agreement κ filters reliable candidates; if the κ-pool is empty, CCV falls back to a high-confidence execution majority or claim majority vote.

sample size degrades as $N_{\text{eff}} = K/(1 + (K{-}1)\rho)$ Ladha [1992], Nitarach [2026]. At $\rho = 0.5$, sixteen candidates carry the information of barely two independent votes. In our experiments, wrong execution consensus clusters of size 8–16 account for 86% of all verification failures—strong majorities that are confidently wrong because they derive from the same misperceived geometric facts.

Compositional structure as a verification resource. Since the problem is within-channel error correlation, a natural response is to seek a structurally independent verification signal. We observe that neuro-symbolic reasoning candidates are not opaque votes. Unlike standard chain-of-thought outputs—a single text sequence mapping to a single answer—a neuro-symbolic candidate decomposes into layers with distinct computational character:

$$\text{Candidate} = \big(\underbrace{\text{VGF}}_{\text{perception}} , \underbrace{\text{DSL}}_{\text{logic}}, \underbrace{\text{exec}}_{\text{computation}} , \underbrace{\text{claim}}_{\text{intuition}} \big) \tag{1}$$

where VGF (Visual Grounding Facts) captures geometric relations extracted from the diagram, DSL is a typed program encoding the reasoning steps, exec is its deterministic execution result, and claim is the model's stated answer.

The claim and exec arise from *structurally different pathways*. The claim is produced by the neural pathway—the model's implicit reasoning, subject to the dispersed noise of autoregressive generation. The execution result is produced by the symbolic pathway—a deterministic computation on extracted premises, subject to the correlated noise of shared visual perception. These two pathways have different error correlation structures: neural errors are relatively independent across candidates, while symbolic errors are highly correlated because candidates see the same diagram.

Existing verification paradigms overlook this structural difference. *Consensus methods* (MV, self-consistency, CISC) count votes within a single output layer, making them vulnerable to within-layer error correlation. *Learned verifiers* (ORM, PRM, VisualPRM) train an external model to score candidates, which requires domain-specific training data and adds inference cost. Neither paradigm exploits the compositional structure that is already present in the candidates. We propose a third approach: **compositional verification**, which derives verification signal from cross-pathway agreement within the candidates themselves.

The cross-channel verification principle. We formalize the following principle. Consider two verification channels C_1 (claim) and C_2 (exec), each providing noisy evidence about the correct answer z^*. Let ρ_1, ρ_2 denote the pairwise error correlations within each channel.

Principle (Cross-Channel Verification). *When within-channel error correlations are high ($\rho_2 \gg 0$), a single instance of cross-channel agreement—one candidate where C_1 and C_2 independently converge to the same answer—provides stronger evidence for correctness than k instances of within-channel consensus, for any k bounded by the effective sample size $K/(1 + (K-1)\rho_2)$.*

Within-channel consensus can be inflated by shared errors (all candidates misread the same angle), but cross-channel agreement requires two structurally different noise processes to simultaneously produce the same answer. The probability of this occurring by chance is governed by the cross-channel error coupling, which we empirically measure at $P(\text{exec correct} \mid \text{claim correct}) \approx 0.225$—far lower than the within-channel consensus rates, confirming that the two pathways are only weakly coupled.

Contributions. This paper turns the internal structure of neuro-symbolic candidates into a test-time verification signal. We introduce the SKETCH format, which decomposes geometry reasoning into VGF, typed DSL, deterministic execution, and a neural claim while maintaining >99.9% format compliance with a 9B VLM. Building on this structure, we propose CCV, a training-free verifier that gates scoring and output routing through claim–execution agreement, improving over MV by $+10.41$ pp across four benchmarks with no additional inference. The same fixed protocol transfers to Gemma4-E4B, yielding $+7.84$ pp over Claim MV, and a failure taxonomy shows why: κ-gating recovers 88.5% of the dominant failure subtype where symbolic consensus fails but neural intuition holds.

2 The SKETCH Format

Visual grounding facts (VGF). For cross-candidate verification to work, visual observations must be comparable across candidates in a structured way. Free-form natural-language descriptions of a diagram are not reliably alignable; two candidates may describe the same geometric relationship with different wording. We therefore represent visual grounding as a list of atomic facts drawn from a closed vocabulary of relations:

$$f = (\texttt{relation}, \texttt{entities}), \quad \texttt{relation} \in \{\texttt{parallel}, \texttt{perpendicular}, \texttt{collinear}, \ldots\} \tag{2}$$

The closed vocabulary ensures parseability and enables direct cross-candidate comparison of perceived geometric structure.

Typed DSL. The DSL is a restricted Python subset that derives the answer from VGF-grounded premises using geometry helper functions and standard mathematical operations ($\sqrt{\cdot}$, trigonometric functions, π, etc.). Restricting the subset—no imports, no I/O, no loops—ensures termination and deterministic execution, which is essential for the symbolic pathway to produce a reliable verification signal. Every program terminates with an explicit `answer = ...` assignment, so the execution result can be extracted automatically without answer parsing.

Closed-loop structure. The key property of the SKETCH format is that each candidate carries an intrinsic verification signal: whether its neural claim agrees with its symbolic execution. This signal exists because the format closes the loop: VGF provides premises $\rightarrow$ DSL reasons from premises $\rightarrow$ exec produces a deterministic result $\rightarrow$ claim states the model's answer. When claim $\approx$ exec (compositional consistency, κ=1), the neural and symbolic pathways have independently converged, providing evidence that the answer is correct without any external reference.

Training. We fine-tune Qwen3.5-9B with LoRA (r=8, α=16) on 2,012 geometry examples derived from the Geometry3K Lu et al. [2021] training split. We use the geometry3k subset of NVIDIA Nemotron-Image-Training-v3 Blakeman et al. [2025], which provides 2,078 CoT annotations generated by Qwen3-VL-235B. Each CoT trace is reformatted into VGF+DSL structure by DeepSeek V4 Pro. The resulting model achieves format compliance >99.9%, VGF parse success >98.7%, and DSL execution success >94.5% on test data.

3 Compositional Consensus Verification

3.1 Verification Signal Taxonomy

Given K candidates $\{c_1, \ldots, c_K\}$, each decomposed as $c_i = (\text{VGF}_i, \text{DSL}_i, \text{exec}_i, \text{claim}_i)$, we define a hierarchy of verification signals ordered by the structural diversity they require:

Level 1: Within-layer consensus. Signals computed within a single output layer, aggregated across candidates:

$$S_{\text{claim}}(z) = |\{i : \text{claim}_i = z\}| \qquad \text{(surface consensus)} \tag{3}$$

$$S_{\text{exec}}(z) = |\{i : \text{exec}_i = z,\ \text{exec}_i \neq \perp\}| \qquad \text{(execution consensus)} \tag{4}$$

Traditional MV selects $\arg\max_z S_{\text{claim}}(z)$. Execution MV selects $\arg\max_z S_{\text{exec}}(z)$.

Level 2: Cross-layer agreement. Signals that compare outputs across structurally different layers. The core signal is compositional consistency:

$$\kappa_i = \mathbf{1}[\text{claim}_i \approx \text{exec}_i \wedge \text{exec}_i \neq \perp], \tag{5}$$

which checks whether a single candidate's neural and symbolic pathways agree. Additional cross-layer features (e.g., cross-candidate cross-layer agreement μ_i) appear in the learned ablation (Section 4.5) but are not part of the hand-designed algorithm.

Level 3: Agreement-gated consensus. Cross-layer agreement gates within-layer consensus:

$$G_\kappa(z) = \sum_i \mathbf{1}[\text{exec}_i = z] \cdot \kappa_i \tag{6}$$

Only execution votes from self-consistent candidates count. This is the signal that CCV's scoring function is built on.

3.2 The Cross-Channel Verification Advantage

For notational simplicity, this subsection writes claim–exec agreement as equality; in implementation, κ_i uses approximate numeric matching and excludes failed executions.

Theorem 1 (Cross-channel agreement as a precision filter)**.** *Let X_i be the claim answer and Y_i the executed answer for candidate i, and let z^* be the correct answer. Define $\kappa_i = \mathbf{1}[X_i = Y_i]$, $t_\kappa = P(X_i = Y_i = z^*)$, and $f_\kappa = P(X_i = Y_i \neq z^*)$. Then the accuracy of self-consistent candidates satisfies the identity*

$$p_\kappa \triangleq P(Y_i = z^* \mid \kappa_i = 1) = \frac{t_\kappa}{t_\kappa + f_\kappa}. \tag{7}$$

Under an idealized shared-perception model where the exec pathway depends on a latent visual state V, the claim pathway is conditionally independent of exec, and false agreement is dispersed across $M-1$ wrong answers, $t_\kappa = p_c p_e$ and $p_\kappa > p_e$ whenever $p_c > 1/M$.

The theorem isolates the central mechanism: κ-gating is primarily a *precision filter*. It does not require repeated votes in the same channel; it requires two structurally different pathways to converge to the same answer. When the answer space is large, as in numerical geometry, false self-consistency f_κ is rare, so a retained vote has much higher precision than a raw execution vote.

Theorem 2 (One-vs-rest SNR approximation)**.** *In a one-vs-rest binary correctness approximation, majority reliability depends on per-vote accuracy p, pool size n, and pairwise correctness correlation ρ through*

$$\text{SNR}(p, n, \rho) = \frac{p - \frac{1}{2}}{\sqrt{p(1-p)(1 + (n-1)\rho)/n}}. \tag{8}$$

The κ-filtered pool improves over raw exec voting whenever the precision gain from filtering outweighs the combined penalty of smaller pool size and higher correlation (full condition in Appendix J).




Figure 2: **Cross-channel precision filtering.** Left: κ-gating keeps candidates where claim and execution agree. True agreement occupies the claim-correct/exec-correct quadrant, while false agreement is dispersed across many wrong answers. Right: empirically, the κ-filtered pool is more correlated than raw execution votes, but its much higher precision yields a $4.1\times$ SNR improvement.

This yields a testable, counterintuitive prediction: κ-gating need not reduce correlation to improve majority reliability. Precision filtering can dominate the correlation penalty. This complements the negative findings of Nitarach [2026] on diverse prompting: when errors arise from shared perception, decorrelating samples is the wrong lever—filtering for cross-channel agreement targets precision directly.

Empirical support. We directly measure within-question correctness correlations on the full dataset (1,709 questions $\times$ 16 candidates). Raw exec votes have pairwise correlation $\rho_e = 0.526$; κ-filtered votes have higher correlation $\rho_\kappa = 0.646$. Yet per-candidate accuracy jumps from 61.7% to 87.1%, and the one-vs-rest SNR proxy improves by $4.1\times$ (0.32 to 1.33). Figure 2 visualizes this precision-filtering regime. Thus the retained pool is more correlated, but substantially more reliable—directly validating the counterintuitive prediction of Theorem 2: precision filtering dominates even when it increases correlation. This confirms that the dominant mechanism is precision filtering, not decorrelation: the $\kappa_i \cdot |\text{exec_cluster}_i|$ term in Algorithm 1 counts consensus only after it has survived cross-channel agreement.

3.3 κ-gated Dual-Pathway CCV

Algorithm 1 summarizes CCV. It uses claim-execution agreement as a precision gate, conceptually related to program-based consistency filtering Toh et al. [2024], but differs by combining agreement-gated consensus with output-pathway routing. The algorithm applies cross-channel agreement as a gate at two levels:

Candidate scoring (Lines 2–3). The term $\kappa_i \cdot |\text{exec_cluster}_i|$ realizes agreement-gated consensus: execution consensus is trusted only when accompanied by cross-layer agreement. The term $0.5 \cdot |\text{claim_cluster}|$ provides a baseline surface signal. Raw execution cluster size receives zero weight—our learned ablation in Section 4.5 confirms this design choice.

Output pathway routing (Lines 6–12). When self-consistent candidates exist ($\mathcal{C}_\kappa$ is non-empty), the algorithm outputs the neural claim. When cross-layer agreement collapses globally, it falls back to symbolic execution consensus, but only if the execution cluster is sufficiently large ($\geq \tau_{\text{exec}}$). This routing treats the *absence* of cross-channel agreement as diagnostic: it signals that the neural pathway is unreliable, making the deterministic symbolic pathway more trustworthy.

Complexity. $O(K)$ time, zero additional model calls, one tunable parameter (τ_{exec}).

Algorithm 1 κ-gated Dual-Pathway CCV

Require: Candidates $\{c_1, \ldots, c_K\}$, threshold τ_{exec}

for each candidate c_i **do**
  $\kappa_i \leftarrow \mathbf{1}[\text{claim}_i \approx \text{exec}_i \wedge \text{exec}_i \neq \perp]$
  $\text{score}_i \leftarrow 0.5 \cdot |\text{claim_cluster}_i| + \kappa_i \cdot (1 + |\text{exec_cluster}_i|)$
end for
$\mathcal{C}_\kappa \leftarrow \{c_i : \kappa_i = 1\}$ ▷ self-consistent candidate pool
if $\mathcal{C}_\kappa \neq \emptyset$ **then**
  return $\text{claim}(\arg\max_{c_i \in \mathcal{C}_\kappa} \text{score}_i)$ ▷ *Level 1: output neural claim*
else
  $z_{\text{exec}} \leftarrow \text{mode}(\{\text{exec}_i : \text{exec}_i \neq \perp\})$
  if $|\{i : \text{exec}_i = z_{\text{exec}}\}| \geq \tau_{\text{exec}}$ **then**
    return z_{exec} ▷ *Level 2: fall back to symbolic execution*
  else
    return $\text{mode}(\{\text{claim}_i\})$ ▷ *Level 3: fall back to claim majority*
  end if
end if

4 Experiments

4.1 Setup

Models and training. Our primary generator is Qwen3.5-9B, fine-tuned with LoRA (r=8, α=16) on 2,012 executor-validated Geometry3K training examples. The training data was constructed by reformatting Qwen3-VL CoT traces into the SKETCH format using DeepSeek V4 Pro. We also evaluate Gemma4-E4B to test cross-model generalization. Training was conducted using LLaMA-Factory with bf16 on 8 NVIDIA 4090 GPUs.

Table 1: Test benchmark suite. We evaluate on one in-distribution benchmark and three held-out/OOD settings.

Benchmark	Lang.	N	Role
Geometry3K test Lu et al. [2021]	EN	601	In-distribution
GeoQA test Chen et al. [2021]	ZH	754	Cross-lingual OOD
MathVista-GPS clean Lu et al. [2023]	EN	146	Cross-domain OOD
MathVista-GPS Lu et al. [2023]	EN	208	Reference

Evaluation protocol. Table 1 summarizes our evaluation suite. We use a frozen-rollout protocol with K=16 candidates, temperature 0.8, and top-p 0.95. All verification methods operate on the same rollout pool. The single hyperparameter τ_{exec}=9 was selected on a 300-question development split of Geometry3K and held fixed across all benchmarks and models.

4.2 Main Results

Figure 3 visualizes the same evidence ladder and K-scaling trend, while Table 2 reports the full benchmark breakdown. The four surface and confidence-based selectors—Claim MV, logprob-weighted MV, CISC, and URSA-RM weighted MV—all lie in a narrow 70.57–71.39% band, despite spanning self-confidence weighting and an external learned PRM. The learned ablation in Section 4.5 confirms this ceiling extends to logprob-based best-of-N and learned surface+execution feature selectors. Even URSA-RM, the strongest external scorer, achieves only $+0.76$ pp over Claim MV when used for weighted voting. Execution-only methods improve to 74–76%, but the large jump appears only when cross-layer agreement is used as a compositional signal: a PROVE-style κ filter reaches 79.52%, and CCV reaches 80.98%, a $+10.41$ pp improvement over Claim MV and $+4.80$ pp over EAV. Paired per-question tests over the fixed 1,709-question evaluation set confirm the main gains: CCV improves over Claim MV by $+10.42$ pp (95% paired bootstrap CI $[8.48, 12.40]$ pp; exact McNemar $p < 10^{-12}$) and over EAV by $+4.80$ pp (95% CI $[3.39, 6.26]$ pp; exact McNemar $p = 5.7\times10^{-11}$). On the disjoint heldout/OOD split (excluding dev 300), CCV reaches 81.93%.




Figure 3: **Evidence ladder and K scaling.** Surface and confidence-based selectors cluster near 70–71%, execution-only methods improve moderately, and cross-layer compositional verification produces the main jump to 79–81%. As K increases, the CCV gain over Claim MV grows, indicating that compositional verification unlocks additional rollout diversity.

Table 2: Evidence ladder across verification signal types (K=16). Surface/confidence methods, including learned PRM scores and self-judged confidence, cluster near 70–71%. Execution-only signals improve moderately. Cross-layer compositional verification produces the large jump to 79–81%.

Method	Type	G3K	GeoQA	GPS-c	GPS	All
Surface / confidence signals						
Claim MV	consensus	66.72	73.61	72.60	69.23	70.57
Logprob-weighted MV	weighted consensus	66.56	73.87	72.60	70.67	70.80
CISC $P(\text{True})$-weighted	confidence consensus	68.05	74.27	72.60	69.71	71.39
URSA-RM weighted MV	learned verifier	62.73	75.60	79.45	75.00	71.33
Execution channel without cross-layer gating						
Exec MV	exec consensus	72.71	75.60	76.71	72.60	74.31
EAV	exec-first priority	74.04	77.72	77.40	75.96	76.18
Cross-layer compositional signals						
PROVE-style κ filter	binary agreement	76.54	82.10	81.51	77.40	79.52
CCV (ours)	gated + routing	**78.54**	**81.83**	**86.30**	**81.25**	**80.98**
Oracle	upper bound	93.51	93.50	91.78	92.79	93.27

A sweep over the only tunable parameter, τ_{exec}, shows that CCV is robust rather than finely tuned: across $\tau_{\text{exec}} = 5 \ldots 14$, dev accuracy varies by 1.00 pp and heldout/OOD accuracy by 1.06 pp (Appendix C). The κ matching threshold itself is also stable: varying the candidate-level relative tolerance around the default leaves CCV accuracy unchanged on the full s240 pool (Appendix H).

4.3 Cross-Model Generalization

To test whether CCV's gains depend on the specific base model, we repeat the full evaluation protocol with Gemma4-E4B, a 4B-parameter multimodal model with substantially weaker geometry reasoning capacity. The Gemma4 model achieves comparable SKETCH format compliance to the Qwen model, so this experiment is a confirmation of the verification mechanism rather than a new generator contribution.

Table E.1 reports the cross-model evidence ladder using the same τ_{exec}=9 for both models. First, the absolute accuracy gap is large: Claim MV drops from 70.57% on Qwen3.5-9B to 44.94% on Gemma4-E4B, consistent with the capacity difference. Second, the CCV gain pattern is preserved: CCV improves over Claim MV by $+10.41$ pp on Qwen and $+7.84$ pp on Gemma4. The Gemma4 result is especially diagnostic because its execution pathway alone is worse than the claim pathway

(Exec MV 41.08% vs Claim MV 44.94%), making EAV ineffective (44.88%). Yet CCV still reaches 52.78%, showing that it exploits structural cross-channel agreement rather than the raw accuracy advantage of execution votes.

The mechanism predicted by Theorem 1 also replicates quantitatively: κ-filtering yields nearly identical precision gains across models ($+25.40$ pp vs $+26.38$ pp), and the counterintuitive correlation pattern repeats ($\rho_\kappa > \rho_e$ while SNR improves; Table D.1). This supports the interpretation that cross-channel precision filtering is model-agnostic. The CCV advantage also scales with K on both Qwen and Gemma4 (Appendix D, Appendix F).

4.4 K Scaling Analysis

Figure 3 shows that the CCV advantage scales with K: the gain over Claim MV grows from $+5.60$ pp at $K{=}4$ to $+10.41$ pp at $K{=}16$ (tabulated in Appendix D). Surface consensus saturates quickly (Claim MV gains only $+1.23$ pp from $K{=}4$ to 16), while compositional verification continues extracting signal from larger candidate pools.

As a negative control, VGF consensus—another within-layer signal—not only fails to help but *hurts* performance when added (from 80.05% to 79.93%). This reinforces the central finding: within-layer consensus—whether the layer is claim, execution, or VGF—is vulnerable to correlated perception errors. Only cross-layer gating provides robust verification signal.

4.5 Learned Feature Ablation

To validate that the compositional features carry the transferable verification signal—not just that our specific CCV rule is effective—we train candidate-level logistic regression classifiers on Geometry3K dev (300 questions) and evaluate on disjoint OOD benchmarks.

Table D.3 reports the full ablation. The key result is that compositional features are the only transferable signal: logprob best-of-N, surface features, and surface+execution features remain near Claim MV (71.11–71.86% OOD), while adding cross-layer features jumps to 79.85% OOD and C-only features reach 81.02%. The learned model rediscovers the gating principle: raw exec_cluster_size has a negative coefficient (-2.40), while $\kappa \times$ exec_cluster is strongly positive ($+1.96$). A simple rule is therefore enough: PROVE-style κ filtering reaches 81.02% OOD, and dual-output CCV reaches 81.93% OOD.

4.6 Error Taxonomy and Recovery Analysis

We analyze 355 cases where EAV fails but an oracle-correct candidate exists (full flow in Figure D.1). Wrong execution consensus accounts for 305/355 = 86% of these failures. The largest recoverable subtype is Exec✗Claim✓: the execution majority is wrong, but the claim majority is correct. CCV recovers 123/139 = **88.5%** of this subtype by routing through candidates that survive claim–execution agreement. In contrast, Exec✗Claim✗ cases, where both pathways support the same incorrect answer, remain mostly outside the reach of selection-only verification (8.3% recovered). Among self-consistent candidates, reliability rises from 19% at execution cluster size 1 to 93% at size 8+, confirming that κ must be combined with gated consensus rather than used as a standalone binary filter.

5 Related Work

Geometry reasoning systems mainly improve the generator side of the problem. Specialized VLMs such as G-LLaVA Gao et al. [2023], GeoX Xia et al. [2024], and MAVIS Zhang et al. [2024b] strengthen multimodal geometry solving on benchmarks such as Geometry3K Lu et al. [2021] and GeoQA Chen et al. [2021]. Neuro-symbolic solvers such as AlphaGeometry Trinh et al. [2024], Chervonyi et al. [2025] and FormalGeo Zhang et al. [2023] use symbolic structure to derive proofs or answers. Our work is complementary: it assumes a candidate pool already exists and studies how to verify candidates when shared diagram perception makes their errors correlated.

Test-time verification is usually based on either consensus or learned scoring. Self-consistency Wang et al. [2022], universal self-consistency Chen et al. [2023], and confidence-weighted CISC Tauben-

feld et al. [2025] aggregate opaque answer votes, which works best when sampled errors are sufficiently independent. Learned verifiers, including ORMs/PRMs Cobbe et al. [2021], Uesato et al. [2022], Lightman et al. [2023], Wang et al. [2024], GenRM Zhang et al. [2024a], URSA-RM Luo et al. [2025], and VisualPRM Wang et al. [2025], train external scorers and add verifier-specific data or inference. CCV differs from both paradigms by deriving verification signal from structure already present inside each candidate.

The closest line of work uses programs or error-correlation analysis to diagnose voting failures. PROVE Toh et al. [2024] filters candidates whose translated Python output matches the natural-language answer, a binary consistency signal analogous to κ. Our framework generalizes this idea to geometry-specific neuro-symbolic outputs, where VGF, typed DSL, deterministic execution, and neural claims form a hierarchy of cross-layer signals. Nitarach [2026] show that correlated errors limit majority voting; CCV targets this regime directly by gating consensus through cross-channel agreement rather than trying to decorrelate samples.

6 Conclusion

We have shown that neuro-symbolic reasoning candidates carry an underutilized verification resource: their compositional structure. By formalizing cross-channel agreement as a verification principle, we derive a training-free algorithm that substantially outperforms both standard consensus methods and learned verifiers. The key insight—that agreement between structurally diverse pathways provides stronger evidence than repetition within any single pathway—is validated by a full evidence ladder: non-compositional confidence, consensus, and learned-score methods saturate around 70–71%, while κ-based compositional methods reach 79–81%. More broadly, output format is a verification design choice: domains that can expose perception, logic, computation, and conclusion as cross-validatable pathways may benefit from the same principle. Our current validation focuses on open-weight geometry models; extending CCV to proprietary frontier models and adding independent premise verification are natural next steps.

References

Aaron Blakeman, Aaron Grattafiori, Aarti Basant, Abhibha Gupta, Abhinav Khattar, Adi Renduchintala, Aditya Vavre, Akanksha Shukla, Akhiad Bercovich, Aleksander Ficek, et al. Nvidia nemotron 3: Efficient and open intelligence. *arXiv preprint arXiv:2512.20856*, 2025.

Jiaqi Chen, Jianheng Tang, Jinghui Qin, Xiaodan Liang, Lingbo Liu, Eric Xing, and Liang Lin. Geoqa: A geometric question answering benchmark towards multimodal numerical reasoning. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pages 513–523, 2021.

Xinyun Chen, Renat Aksitov, Uri Alon, Jie Ren, Kefan Xiao, Pengcheng Yin, Sushant Prakash, Charles Sutton, Xuezhi Wang, and Denny Zhou. Universal self-consistency for large language model generation. *arXiv preprint arXiv:2311.17311*, 2023.

Yuri Chervonyi, Trieu H Trinh, Miroslav Olšák, Xiaomeng Yang, Hoang H Nguyen, Marcelo Menegali, Junehyuk Jung, Junsu Kim, Vikas Verma, Quoc V Le, et al. Gold-medalist performance in solving olympiad geometry with alphageometry2. *Journal of Machine Learning Research*, 26 (241):1–39, 2025.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems, 2021. *URL https://arxiv. org/abs/2110.14168*, 9, 2021.

Jiahui Gao, Renjie Pi, Jipeng Zhang, Jiacheng Ye, Wanjun Zhong, Yufei Wang, Lanqing Hong, Jianhua Han, Hang Xu, Zhenguo Li, et al. G-llava: Solving geometric problem with multi-modal large language model. *arXiv preprint arXiv:2312.11370*, 2023.

Krishna K Ladha. The condorcet jury theorem, free speech, and correlated votes. *American Journal of Political Science*, pages 617–634, 1992.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. In *The twelfth international conference on learning representations*, 2023.

Pan Lu, Ran Gong, Shibiao Jiang, Liang Qiu, Siyuan Huang, Xiaodan Liang, and Song-Chun Zhu. Inter-gps: Interpretable geometry problem solving with formal language and symbolic reasoning. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 6774–6786, 2021.

Pan Lu, Hritik Bansal, Tony Xia, Jiacheng Liu, Chunyuan Li, Hannaneh Hajishirzi, Hao Cheng, Kai-Wei Chang, Michel Galley, and Jianfeng Gao. Mathvista: Evaluating mathematical reasoning of foundation models in visual contexts. *arXiv preprint arXiv:2310.02255*, 2023.

Ruilin Luo, Zhuofan Zheng, Yifan Wang, Yiyao Yu, Xinzhe Ni, Zicheng Lin, Jin Zeng, and Yujiu Yang. Ursa: Understanding and verifying chain-of-thought reasoning in multimodal mathematics. *arXiv e-prints*, pages arXiv–2501, 2025.

Natapong Nitarach. Model capability dominates: Inference-time optimization lessons from aimo 3. *arXiv preprint arXiv:2603.27844*, 2026.

Amir Taubenfeld, Tom Sheffer, Eran Ofek, Amir Feder, Ariel Goldstein, Zorik Gekhman, and Gal Yona. Confidence improves self-consistency in llms. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 20090–20111, 2025.

Vernon YH Toh, Deepanway Ghosal, and Soujanya Poria. Not all votes count! programs as verifiers improve self-consistency of language models for math reasoning. *arXiv preprint arXiv:2410.12608*, 2024.

Trieu H Trinh, Yuhuai Wu, Quoc V Le, He He, and Thang Luong. Solving olympiad geometry without human demonstrations. *Nature*, 625(7995):476–482, 2024.

Jonathan Uesato, Nate Kushman, Ramana Kumar, Francis Song, Noah Siegel, Lisa Wang, Antonia Creswell, Geoffrey Irving, and Irina Higgins. Solving math word problems with process-and outcome-based feedback. *arXiv preprint arXiv:2211.14275*, 2022.

Peiyi Wang, Lei Li, Zhihong Shao, Runxin Xu, Damai Dai, Yifei Li, Deli Chen, Yu Wu, and Zhifang Sui. Math-shepherd: Verify and reinforce llms step-by-step without human annotations. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 9426–9439, 2024.

Weiyun Wang, Zhangwei Gao, Lianjie Chen, Zhe Chen, Jinguo Zhu, Xiangyu Zhao, Yangzhou Liu, Yue Cao, Shenglong Ye, Xizhou Zhu, et al. Visualprm: An effective process reward model for multimodal reasoning. *arXiv preprint arXiv:2503.10291*, 2025.

Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. *arXiv preprint arXiv:2203.11171*, 2022.

Renqiu Xia, Mingsheng Li, Hancheng Ye, Wenjie Wu, Hongbin Zhou, Jiakang Yuan, Tianshuo Peng, Xinyu Cai, Xiangchao Yan, Bin Wang, et al. Geox: Geometric problem solving through unified formalized vision-language pre-training. *arXiv preprint arXiv:2412.11863*, 2024.

Lunjun Zhang, Arian Hosseini, Hritik Bansal, Mehran Kazemi, Aviral Kumar, and Rishabh Agarwal. Generative verifiers: Reward modeling as next-token prediction. *arXiv preprint arXiv:2408.15240*, 2024a.

Renrui Zhang, Xinyu Wei, Dongzhi Jiang, Ziyu Guo, Shicheng Li, Yichi Zhang, Chengzhuo Tong, Jiaming Liu, Aojun Zhou, Bin Wei, et al. Mavis: Mathematical visual instruction tuning with an automatic data engine. *arXiv preprint arXiv:2407.08739*, 2024b.

Xiaokai Zhang, Na Zhu, Yiming He, Jia Zou, Qike Huang, Xiaoxiao Jin, Yanjun Guo, Chenyang Mao, Yang Li, Zhe Zhu, et al. Formalgeo: An extensible formalized framework for olympiad geometric problem solving. *arXiv preprint arXiv:2310.18021*, 2023.

A Training Data Construction

Table A.1 summarizes the full construction pipeline for the 2,012-example SFT set. We start from the official Geometry3K Lu et al. [2021] training split, use the geometry3k subset of Nemotron-Image-Training-v3 Blakeman et al. [2025] as the Qwen3-VL-235B-A22B-Thinking CoT source, reformat each matched trace into the SKETCH VGF+DSL+answer format with DeepSeek V4 Pro, and retain only examples whose DSL executes and matches the official answer. The reformatting stage is text-only: the expensive visual reasoning is supplied by the Qwen3-VL CoT trace, while the official gold answer is used as the final target for machine-checkable reformatting.

Table A.1: Training data construction and filtering. Percentages are relative to the 2,078 matched CoT rows unless otherwise noted.

Stage	Count	Rate
Official Geometry3K train rows	2,101	–
Matched Qwen3-VL CoT traces	2,078	98.91% of official
Qwen3-VL boxed-answer correct	2,065	99.37%
DeepSeek V4 Pro reformat attempts	2,078	100.00%
Strict validator pass	1,963	94.47%
Recovered by tolerant VGF normalization	49	2.36%
Final executor-validated SFT rows	2,012	96.82%
Filtered: execution-answer mismatch	61	2.94%
Filtered: DSL execution/safety error	5	0.24%

The final 66 filtered examples consist of 61 execution-answer mismatches and five DSL execution/safety failures: one undefined `UB`, one undefined `z`, one undefined `m`, and two blocked-token errors. The tolerant VGF pass clears unsupported or over-arity visual facts only when the DSL and answer remain executor-valid; a final post-processing pass keeps 2,012 rows, with 41 DSL snippets changed by the sanitizer and 6 VGF lists cleared.

B Data Construction Prompts

Stage 1: stored source prompt for frontier CoT traces. We did not rerun Qwen3-VL-235B-A22B-Thinking for this paper. We use an existing CoT source whose stored user messages follow the problem image plus the following prompt pattern:

```
Solve this geometry problem. Study the diagram and select
the correct answer.

{problem_text}
{choices}

Do not explain your answer but write only the answer label
(A, B, ...) in this format:
Answer: \boxed{...}.
```

Stage 2: VGF+DSL reformatting. DeepSeek V4 Pro receives no image input. It reformats the official problem, choices, official answer, and Qwen3-VL CoT into the target SKETCH format using the following template:

```
Convert the provided Qwen3-VL-235B natural-language geometry
chain-of-thought into the target VGF+DSL format.
Do not solve from scratch. Use the teacher CoT as the visual
and reasoning evidence, and use the official gold answer as
the final target.
Return exactly three sections in this order and no extra sections:
[VGF]
[DSL]
```

```
[Final Answer]

[VGF] rules:
Output a raw JSON list only. Do not use markdown fences.
Each item must be {"relation": <relation>,
"entities": [<tokens>]} with exact relation arity.
Allowed relations: {allowed_vgf_relations}.
Relation arities: {relation_arities}.
For unary shape relations, put the whole object in one entity
token, e.g.
{"relation":"parallelogram","entities":["MNPQ"]}.
Use at most 4 facts to stay safely under the validator limit
of 5 facts.
Use [] if no reliable visual fact is needed.

[DSL] rules:
Output executable Python assignment statements only.
Do not use markdown fences.
Do not include comments or prose.
Never write import statements, including 'from math import ...'.
Math functions are already available by name.
Every variable must be assigned before it is used.
Do not write placeholder equations with unknown symbols.
The final assignment must define a variable named answer.
The value of answer must evaluate to the official gold option
value; use the teacher CoT equations to derive that value.
Allowed math names: sqrt, pi, sin, cos, tan, radians, degrees,
asin, acos, atan, abs, min, max, round.
Do not read files, import modules, call external tools, or use
input/output functions.
[Final Answer] must be exactly the official gold option letter:
{gold}.
In [DSL], set answer to the numeric or symbolic value of
option {gold}:
{gold_value}.

Official problem:
{problem_text}
{choices}

Official gold answer: {gold}
Official gold option value: {gold_value}
Teacher boxed answer: {qwen_boxed_answer}

Teacher NL CoT:
{qwen_cot}
```

C τ_{exec} Sensitivity

The only tunable hyperparameter in CCV is the execution-majority threshold τ_{exec}, used only when the κ-pool is empty. We sweep $\tau_{\text{exec}} = 1 \ldots 16$ on the main Qwen3.5-9B s240 K=16 rollout pool, using the same split protocol as the main paper: Geometry3K qid$<$ 300 for dev, and Geometry3K qid$\geq$ 300 plus GeoQA, MathVista-GPS clean, and MathVista-GPS for heldout/OOD evaluation. Figure C.1 plots the full sweep, and Table C.1 reports selected points. We use the resulting τ_{exec}=9 for both Qwen3.5-9B and Gemma4-E4B.




Figure C.1: **Sensitivity to τ_{exec}.** CCV is stable over a broad range of execution thresholds. In the plateau $\tau_{\text{exec}} = 5 \ldots 14$, dev accuracy varies from 76.00% to 77.00%, and heldout/OOD accuracy varies from 80.77% to 81.83%.

Table C.1: Selected points from the τ_{exec} sweep (full curve in the figure above). The dev-selected threshold is $\tau_{\text{exec}} = 9$.

τ_{exec}	Dev@300	Heldout/OOD	All
1 (no threshold)	76.67	80.13	79.52
9 (selected)	**77.00**	**81.83**	**80.98**
16 (maximum)	75.67	81.19	80.22

D Additional Diagnostics

This appendix contains the diagnostic tables and flow visualization referenced by the main experimental analysis. Table D.1 reports the precision-filtering statistics behind the cross-model claim, Table D.2 gives the exact Qwen K-scaling values summarized in Figure 3, Table D.3 gives the learned feature ablation, and Figure D.1 visualizes the error taxonomy and routing behavior.

Table D.1: Cross-model diagnostic for the precision-filtering mechanism. The κ-filtered pool is more correlated than the raw execution pool, but its much higher per-candidate precision improves the effective verification signal.

Model	p_e (%)	p_κ (%)	Δp (pp)	ρ_e	ρ_κ	mean K_κ	SNR raw$\rightarrow\kappa$
Qwen3.5-9B	61.70	87.10	+25.40	0.526	0.646	9.09	0.32$\rightarrow$1.33
Gemma4-E4B	33.43	59.81	+26.38	0.504	0.630	5.77	$-$0.48$\rightarrow$0.24

E Cross-Model Validation

Table E.1 evaluates the same verification protocol on a lower-capacity Gemma4-E4B generator, using the same τ_{exec}=9 as Qwen3.5-9B. The Gemma4 pool uses the same frozen K=16 four-benchmark setting as the main Qwen3.5-9B experiments: Geometry3K test (601), GeoQA test (754), MathVista-GPS clean (146), and MathVista-GPS (208), for N=1709 questions and 27,344 candidates. The evaluation uses the benchmark files in `clean/assets`; it does not use the deprecated 400-question checkpoint-selection set.

The notable difference is that Gemma4 reverses the raw pathway ordering: Exec MV is below Claim MV (41.08% vs 44.94%), whereas Qwen's execution pathway is stronger than its claim pathway. Consequently, EAV, an execution-first priority rule, is ineffective on Gemma4 (44.88% vs 44.94% Claim MV). This pattern is expected for a smaller model with weaker visual grounding: within-layer execution consensus is more easily dominated by correlated perception errors. The result therefore strengthens rather than weakens the verification story. CCV does not trust the raw execution vote; it

Table D.2: Performance across K on the four-benchmark Qwen3.5-9B pool.

K	Claim MV	Exec MV	CCV	Oracle	CCV − Claim MV
4	69.34	68.98	74.94	84.74	+5.60
8	70.38	72.43	77.88	89.89	+7.50
16	70.57	74.31	80.98	93.27	+10.41

Table D.3: Compositional feature ablation. "S" = standard features (logprob, claim cluster), "E" = execution features, "C" = compositional cross-layer features (κ, $\kappa \times$ exec_cluster, μ, $\kappa \times \mu$, sc_rate). The last column reports OOD gain over Claim MV.

Method / Features	Dev@300	OOD	All	Δ OOD vs Claim MV
Claim MV (reference)	66.67	71.77	70.57	0.00
Best-of-N (logprob)	66.00	71.11	69.75	−0.67
LogReg S-only	67.00	71.86	70.74	+0.08
LogReg S+E	66.33	71.69	70.63	−0.08
LogReg S+E+C	74.67	79.85	78.47	+8.08
LogReg C-only	75.33	81.02	79.64	+9.24
PROVE-style κ filter (rule)	75.00	81.02	79.52	+9.24
Dual-output CCV (ours, rule)	77.00	81.93	80.98	+10.16

uses claim–execution agreement as a precision filter. Even when the execution pathway is worse in aggregate, candidates where claim and execution agree remain informative, yielding $+7.84$ pp over Claim MV and $+7.90$ pp over EAV on Gemma4.

F Gemma4 K Scaling

Table F.1 repeats the K-scaling analysis on the frozen Gemma4-E4B K=16 pool by subsampling candidates; K<16 rows are averaged over four random subsamples. We keep τ_{exec}=9 fixed to match the cross-model comparison in the main text.

The Gemma4 gain increases with candidate budget, from $+4.87$ pp at K=4 to $+7.84$ pp at K=16, matching the qualitative scaling trend observed for Qwen.

G Gemma4 Implementation Details

The Gemma4-E4B experiment uses the frozen checkpoint-720 LoRA adapter and the frozen rollout pool described in Appendix E; no additional model calls are made for the verification comparisons. The adapter uses LoRA rank 8 and $\alpha = 16$. On a 400-example format audit, the model reaches 96.0% complete-section rate, 99.0% VGF parse success, 96.0% DSL syntax success, and 94.25% DSL execution success, comparable to the format reliability of the Qwen model.

H κ Matching Threshold Sensitivity

The relation $X_i \approx Y_i$ is implemented by normalizing the claimed final answer and executed DSL answer, then applying numeric tolerance. Floating-point answers, fractions, square roots, and π expressions are parsed to real values; degree symbols are treated as unit suffixes and removed before numeric comparison. For multiple-choice questions, numeric answers are first mapped to option letters using the fixed choice tolerance 0.02. Table H.1 reports an ablation that keeps the numeric absolute tolerance fixed at 10^{-3} and sweeps only the candidate-level relative tolerance used for κ.

All threshold settings yield identical results because geometry answers are effectively discrete: integers, simple fractions, radicals, angles, or multiple-choice letters. In this domain, claim–execution agreement is almost always binary: pairs either match exactly, or differ by margins much larger than even the loosest tolerance. The matching tolerance is therefore not a meaningful hyperparameter for these benchmarks, and the measured CCV gain is not an artifact of finely tuned numeric equality.




Figure D.1: **Error flow and dynamic routing.** Among 355 EAV failures with an oracle-correct candidate, wrong execution consensus dominates (86%) and splits into three subtypes: Exec✗ Claim✓, Exec✗ Claim✗, and Exec✗ Claim?. In the recoverable Exec✗ Claim✓ stream, the claim majority is correct while the execution majority is wrong; CCV's κ filter routes 123/139 cases (88.5%) to the correct neural-claim output, illustrating how output-pathway routing rescues samples when the symbolic channel collapses.

Table E.1: Cross-model validation on the same frozen $K{=}16$ four-benchmark protocol ($N{=}1709$), using $\tau_{\text{exec}}{=}9$ for both models. Absolute accuracy differs because Qwen3.5-9B has higher model capacity than Gemma4-E4B, but the gain pattern is consistent: cross-layer κ filtering and CCV improve over surface consensus for both models without additional inference.

Method	Qwen3.5-9B	Gemma4-E4B
Claim MV	70.57	44.94
Exec MV	74.31	41.08
EAV	76.18	44.88
PROVE-style κ filter	79.52	51.90
CCV (ours)	**80.98**	**52.78**
CCV − Claim MV	+10.41	+7.84
CCV − EAV	+4.80	+7.90
Oracle	93.27	91.75

I Qualitative Case Studies

We present four representative cases from the frozen Qwen3.5-9B s240 $K{=}16$, $T{=}0.8$ pool, selected to illustrate the four behavioral modes of CCV: (1) successful rescue when execution consensus is wrong but claim is correct, (2) hard cases where both pathways agree on a wrong answer, (3) correlated perception errors that produce incorrect agreement, and (4) fallback routing when no self-consistent candidate exists. Each case reports method outputs and the key DSL of the CCV-selected candidate.

I.1 CCV Rescue (Exec✗ Claim✓)

`geometry3k_test` qid 325. Expected: B (16). Choices: A=12, B=16, C=51, D=65.

Method outputs. Claim MV: B; Exec MV: C; EAV: C; CCV: **B**.

CCV-selected DSL ($\kappa = 1$, claim cluster 9, exec cluster 6):

Table F.1: Gemma4-E4B K scaling from the frozen K=16 pool. Entries for K=4, 8 are mean±std over four subsamples.

K	Claim MV	Exec MV	EAV	PROVE-style κ	CCV	Oracle	CCV − Claim MV
4	42.41±0.81	37.60±0.42	46.94±0.46	46.65±0.74	47.28±0.60	72.24±0.60	+4.87
8	44.00±0.48	39.86±0.24	48.82±0.79	50.04±0.62	50.85±0.58	83.84±0.32	+6.85
16	44.94	41.08	44.88	51.90	52.78	91.75	+7.84

Table H.1: Sensitivity to the candidate-level relative tolerance in $X_i \approx Y_i$ on the frozen Qwen3.5-9B s240 K=16, T=0.8 pool.

Setting	Candidate relative tolerance	CCV accuracy	κ candidates / precision
10^{-6}	0.000001	80.98	15,535 / 87.07
10^{-4}	0.0001	80.98	15,535 / 87.07
10^{-3}	0.001	80.98	15,535 / 87.07
default (10^{-2})	0.01	80.98	15,535 / 87.07
5×10^{-2}	0.05	80.98	15,535 / 87.07

```
angle_X = angle_L
x = angle_X / 4
answer = x          # 16.25 -> B
```

CCV selects a κ-consistent candidate whose claim and execution agree on B, while EAV follows a wrong execution majority (C). This is the canonical recoverable failure: the neural pathway is correct but the symbolic pathway is corrupted by shared perception error.

I.2 Hard Case: Exec✗ Claim✗

`geometry3k_test` qid 72. Expected: A (3). Choices: A=3, B=4, C=6, D=7.

Method outputs. Claim MV: B; Exec MV: B; EAV: B; CCV: B.

CCV-selected DSL ($\kappa = 1$, claim cluster 15, exec cluster 15):

```
x = 4
answer = x          # 4.0 -> B
```

All methods agree on the wrong answer. This case sits outside selection-only verification because the cross-channel agreement is itself wrong—both pathways share the same perceptual error.

I.3 Correlated Perception Error

`geometry3k_test` qid 35. Expected: D (155). Choices: A=20, B=25, C=30, D=155.

Method outputs. Claim MV: B; Exec MV: B; EAV: B; CCV: B.

CCV-selected DSL ($\kappa = 1$, claim cluster 16, exec cluster 16):

```
arc_BC = 30
arc_AD = 20
angle_2 = (arc_BC + arc_AD) / 2
answer = angle_2    # 25.0 -> B
```

This is a boundary case for CCV: a correlated visual error makes both channels self-consistent around the wrong answer. With 16/16 candidates in both clusters, selection alone has no alternative evidence to break the incorrect consensus.

I.4 Empty κ-Pool with Execution Fallback

`geometry3k_test` qid 56. Expected: C (70). Choices: A=66, B=68, C=70, D=72.

Method outputs. Claim MV: D; Exec MV: C; EAV: C; CCV: **C**.

CCV-selected DSL ($\kappa = 0$, claim cluster 10, exec cluster 16):

```
leg1 = 24
hypotenuse = 74
x = sqrt(hypotenuse**2 - leg1**2)
answer = x          # 70.0 -> C
```

The κ-pool is empty (no candidate's claim matches its execution), so CCV falls back to the execution-majority pathway. The large exec cluster (16/16) exceeds τ_{exec}, providing the correct answer. This illustrates dual-pathway routing: when cross-channel agreement is absent, the deterministic symbolic path remains available as a fallback.

J Proofs for the Cross-Channel Verification Analysis

J.1 Latent shared-perception model

We formalize the verification problem using answer-valued random variables. Let X_i denote the claim answer and Y_i the executed answer for candidate i, both taking values in an answer space $\mathcal{Z}$ with correct answer z^*. A latent visual state V is shared across candidates. Conditional on V, the executed answers Y_i are i.i.d. from $P_e(\cdot \mid V)$; the claim answers X_i are i.i.d. from $P_c(\cdot)$, independent of V; and X_i and Y_i are conditionally independent given V. This is an idealized model: empirically, we only require false self-consistency to be sufficiently rare, not perfect independence.

Define $p_e = P(Y_i = z^*) = \mathbb{E}_V[P_e(z^* \mid V)]$ and $p_c = P(X_i = z^*) = P_c(z^*)$. For execution correctness indicators $E_i = \mathbf{1}[Y_i = z^*]$, the within-channel execution correlation is

$$\rho_e = \mathrm{Corr}(E_i, E_j) = \frac{\mathrm{Var}_V[P_e(z^* \mid V)]}{p_e(1 - p_e)}. \tag{J.1}$$

By the law of total covariance applied to $E_i = \mathbf{1}[Y_i = z^*]$ for $i \neq j$, $\mathrm{Cov}(E_i, E_j) = \mathrm{Var}_V[P_e(z^* \mid V)]$, so shared perception creates positive correlation whenever execution accuracy varies with the visual state.

J.2 Proof of Theorem 1

Let $\kappa_i = \mathbf{1}[X_i = Y_i]$. Decompose self-consistency into true and false agreement:

$$t_\kappa = P(X_i = Y_i = z^*), \tag{J.2}$$

$$f_\kappa = P(X_i = Y_i \neq z^*) = \sum_{z \neq z^*} P(X_i = z, Y_i = z). \tag{J.3}$$

Then $P(\kappa_i = 1) = t_\kappa + f_\kappa$, and by Bayes rule:

$$P(Y_i = z^* \mid \kappa_i = 1) = \frac{t_\kappa}{t_\kappa + f_\kappa}. \tag{J.4}$$

This identity does not require independence; it simply states that self-consistent candidates are correct when agreement is true rather than false.

Under the latent shared-perception model, conditional independence of X_i and Y_i given V yields $t_\kappa = P_c(z^*)\,\mathbb{E}_V[P_e(z^* \mid V)] = p_c p_e$. If wrong answers are approximately dispersed uniformly over $M-1$ alternatives, then

$$f_\kappa \approx \frac{(1 - p_c)(1 - p_e)}{M - 1}. \tag{J.5}$$

The condition $p_\kappa > p_e$ reduces to $p_c(1 - p_e) > f_\kappa$. Substituting the uniform-dispersion approximation gives $p_c > (1 - p_c)/(M - 1)$, i.e., $p_c > 1/M$ for $p_e < 1$. Thus cross-channel agreement improves per-candidate precision whenever the claim pathway is better than random over the effective answer space.

J.3 Proof of Theorem 2

For n exchangeable binary correctness variables with $P(B_i = 1) = p$ and pairwise correlation ρ, the variance of the sample mean is $p(1-p)[1 + (n-1)\rho]/n$. Applying the SNR definition from the main text to raw exec voting (p_e, K, ρ_e) and to the retained κ-filtered pool $(p_\kappa, K_\kappa, \rho_\kappa)$ gives $\mathrm{SNR}_\kappa > \mathrm{SNR}_{\mathrm{raw}}$ iff

$$\frac{p_\kappa - \frac{1}{2}}{p_e - \frac{1}{2}} > \sqrt{\frac{p_\kappa(1-p_\kappa)}{p_e(1-p_e)} \cdot \frac{K(1+(K_\kappa-1)\rho_\kappa)}{K_\kappa(1+(K-1)\rho_e)}}. \tag{J.6}$$

Corollary 1 (Answer dispersion amplifies cross-channel advantage)**.** *Under the uniform-dispersion approximation, as the effective answer space M grows, $f_\kappa \to 0$ and hence $p_\kappa \to 1$. If the retained pool remains nonempty and the correlation factor remains bounded, then $\mathrm{SNR}_\kappa \to \infty$ while raw exec SNR is unchanged.*

J.4 Numerical illustration

We instantiate the SNR proxy using measured post-hoc statistics from the full dataset. Failed executions are counted as incorrect; correlations are Pearson correlations over ordered within-question candidate pairs. Raw exec voting uses $K = 16$, $p_e = 0.617$, and $\rho_e = 0.526$. The retained pool has mean size $K_\kappa = 9.09$, $p_\kappa = 0.871$, and $\rho_\kappa = 0.646$. Table J.1 summarizes the resulting SNR proxy values.

Table J.1: Measured statistics for the one-vs-rest SNR proxy.

Method	n	p	ρ	SNR
Raw exec MV	16	0.617	0.526	0.32
κ-filtered MV	9.09	0.871	0.646	1.33

The retained pool is therefore 23% more correlated, but the SNR proxy improves by $4.1\times$. This empirical regime is exactly the counterintuitive case captured by Theorem 2: precision filtering dominates the correlation penalty. The observed false self-consistency rate is 12.9%, so most κ=1 candidates correspond to true rather than accidental agreement.

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes].

   Justification: The abstract and introduction state the proposed cross-channel verification problem, the CCV method, and the reported improvements. The scope is limited to verification over generated geometry candidates, with future extensions discussed in the conclusion.

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes].

   Justification: The conclusion discusses the present validation scope, including open-weight geometry models, proprietary frontier models, and independent premise verification as natural extensions.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
   - The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
   - If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
   - While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [Yes].

Justification: Section 3 states the latent-accuracy model and SNR condition, and Appendix J provides the corresponding proofs, assumptions, and numerical illustration.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes].

Justification: Sections 3 and 4, together with Appendices **??** and D, specify the output format, gating rule, benchmarks, rollout settings, threshold choice, and diagnostic protocol needed to reproduce the main comparisons.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
  (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
  (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
  (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).

(d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [No].

   Justification: Code is not publicly released at anonymous submission time. The experiments are based on offline selection over frozen candidate pools, and we plan to release evaluation and aggregation scripts upon acceptance, subject to institutional and dataset-license constraints.

   Guidelines:

   - The answer [N/A] means that paper does not include experiments requiring code.
   - Please see the NeurIPS code and data submission guidelines (https://neurips.cc/public/guides/CodeSubmissionPolicy) for more details.
   - While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
   - The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (https://neurips.cc/public/guides/CodeSubmissionPolicy) for more details.
   - The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
   - The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
   - At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
   - Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

   Answer: [Yes].

   Justification: The setup describes the Geometry3K dev/test split, MathVerse OOD split, rollout count, decoding settings, τ selection, LoRA rank and scale, and frozen evaluation protocol. Implementation-level optimizer details should be included with the eventual code release.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
   - The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

   Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

   Answer: [Yes].

Justification: Section 4 reports paired per-question significance tests for the main comparisons over the fixed 1,709-question evaluation set. We use paired bootstrap confidence intervals for accuracy differences and exact McNemar tests over discordant question outcomes; CCV improves over Claim MV by $+10.42$ pp (95% CI $[8.48, 12.40]$ pp, $p < 10^{-12}$) and over EAV by $+4.80$ pp (95% CI $[3.39, 6.26]$ pp, $p = 5.7\times10^{-11}$).

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

   Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

   Answer: [No].

   Justification: We report the main training setup, checkpoint, candidate budget, and frozen evaluation pool size, but do not provide a complete accounting of wall-clock time and GPU-hours for all auxiliary scoring runs.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
   - The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
   - The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics https://neurips.cc/public/EthicsGuidelines?

   Answer: [Yes].

   Justification: The work studies mathematical reasoning over public benchmark-style problems and model outputs, with no human-subject data collection, sensitive personal data, or safety-critical deployment.

   Guidelines:

   - The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.

- If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [Yes].

    Justification: The work is methodological and focuses on benchmark geometry reasoning. Potential benefits include more reliable and interpretable verification without additional inference, while potential risks arise if similar verification signals are over-trusted in high-stakes domains without domain-specific validation.

    Guidelines:

    - The answer [N/A] means that there is no societal impact of the work performed.
    - If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
    - Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
    - The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
    - The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
    - If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A].

    Justification: Not applicable. The system is evaluated on offline benchmark geometry reasoning and is not deployed in a user-facing or safety-critical setting.

    Guidelines:

    - The answer [N/A] means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
    - We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [No].

Justification: We cite the datasets and pretrained models used in the experiments and do not redistribute the original assets. A complete license table for all third-party assets is not included in the submission.

Guidelines:

- The answer [N/A] means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [No].

Justification: The paper does not introduce a newly released dataset at submission time. Experiments use existing public benchmarks and derived model outputs; we do not redistribute original benchmark images or questions, and any future release of derived metadata will respect the licenses of the source datasets.

Guidelines:

- The answer [N/A] means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [N/A].

Justification: The paper does not involve crowdsourcing experiments or research with human subjects.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.

- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A].

    Justification: The paper does not involve crowdsourcing experiments or human-subject research, so IRB approval is not applicable.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
    - We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
    - For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

    Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

    Answer: [Yes].

    Justification: The method and experiments describe the VLM generators, teacher-generated structured traces, and reformatting pipeline used to construct and evaluate CCV candidates.

    Guidelines:

    - The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
    - Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.