Hands-on: Break → Troubleshoot → Fix Git Issues

Objective: 🔗

Simulate common Git mistakes and issues, learn how to identify them, and fix them using appropriate commands and workflows.

✅ Pre-requisites: 🔗

- Local Git setup
- A test repository cloned from Bitbucket Enterprise
- Two team members (can be simulated by switching user identity locally)

🔧 Scenario 1: Uncommitted Work Lost During Checkout 🔗

Break:

1. Make changes to a file without committing:

```
echo "test change" >> index.html
```

2. Attempt to switch branches:

```
git checkout main
```

Troubleshoot:

- Git will refuse checkout with warning: "Your local changes to the following files would be overwritten..."

Fix:

- Option 1 (preserve changes):

```
git stash
git checkout main
git stash pop
```

- Option 2 (discard changes):

```
git checkout -- index.html
git checkout main
```

🔧 Scenario 2: Wrong Commit Message or File 🔗

Break:

1. Commit the wrong file or message:

```
git add config.js
git commit -m "Fix styling"
```

```
3
```

Troubleshoot:

- Realize `config.js` wasn't meant to be committed, and message is wrong.

Fix:

- Amend commit (if not pushed yet):

```
1  git reset --soft HEAD~1
2  git reset config.js
3  git commit -m "Correct: Fix styling for homepage"
4
```

🔧 Scenario 3: Merge Conflict 🔗

Break:

1. On `main`, update `README.md` and commit.
2. On `feature`, update the same line in `README.md` and commit.
3. Try to merge `main` into `feature`:

```
1  git checkout feature
2  git merge main
3
```

Troubleshoot:

- Git shows conflict in `README.md`.

Fix:

1. Open the file and resolve the conflict manually.
2. Mark it as resolved:

```
1  git add README.md
2  git commit
3
```

🔧 Scenario 4: Force Push Gone Wrong 🔗

Break:

1. Rebase and force push to remote:

```
1  git rebase main
2  git push --force
3
```

2. Collaborator's local branch is now out of sync.

Troubleshoot:

- Collaborator gets error: "Updates were rejected because the remote contains work…"

Fix (for collaborator):

- Sync with force-updated branch:

```
1  git fetch
2  git reset --hard origin/feature-branch
3
```

🔧 Scenario 5: Detached HEAD State 🔗

Break:

1. Checkout a commit hash:

```
1  git checkout <commit-hash>
```

Troubleshoot:

- Git shows: "You are in 'detached HEAD' state."

Fix:

- Create a new branch from detached state:

```
1  git checkout -b hotfix-temporary
```