SIVI-RC12M18001

TSMC 180nm-G (1P5M)

MAIN FEATURES

- Designed on TSMC 180nm Generic Process
- 12MHz nominal Oscillation Frequency
- Auto-calibration mode
- Accuracy after calibration is better than +/- 10%
- Power consumption at 12MHz is less than 60uA
- Operates from 1.8V supply



SiVi-RC12M18001 Symbol

IP DESCRIPTION

SiVi-RC12M18001 is a low power high resolution RC oscillator nominally operates at 12MHz output clock from a 1.8V supply. The IP consumes only 60uA as a worst case at the maximum oscillation frequency. It has an auto-calibration circuit with a bypass option. The IP is silicon verified on 180nm process.

ELECTRICAL SPECIFICATIONS

Spec / Result	Min	Typ	Max	Unit
Supply Voltage		1.8		V
Temperature Range	-40	27	125	°C
Output Frequency	11	12.2	13.8	MHz
Current Consumption			60	µA

PIN DESCRIPTION

Pin Name	Direction	Description
rcosc_vdd1p8v	Input	1.8V analog supply rail
rcosc_vss	Input	Analog ground rail
digctrl_startautocal_1p8v	Input	Digital signal used to start the calibration process
icnst_pwr_rcosc_i10u_p	Input	10µA constant bias current
digctrl_oscrescalfrc_1p8v<3:0>	Input	External calibration word
Digital_caloveride	Input	Calibration override mode (input will be 1'b1 in this mode)
clkgen_clk1mhz_1p8v	Input	1MHz clock used in calibration mode
bias_vbg1p2v_v	Input	1.2V reference voltage used for calibration
digctrl_oscrescalout_1p8v<3:0>	Output	Calibration word results from calibrator
rcosc_clk12mhz_1p8v	Output	Output 12MHz clock
digctrl_oscrescaldone_1p8v	Output	Calibration flag which is raised after the end of the calibration process
rcosc_testclk12mhz_1p8v	Output	Output clock to be tested

Silicon Vision
79 Almultaqa Alaraby,
Cairo, Egypt, P.O. Box 11361
Tel: +202-22669160
info@si-vision.com