PROG6212

Part One Submission

ST10445289_ANGELA_LEKALA

PROGRAMMING 2B


ST10445289@rcconnect.edu.za

RaceDay

Part 1 — System Planning and Database

Section A — Entity Relationship Diagram (ERD)

The RaceDay data model is built from six entities. The design follows a normalised, role-driven approach: a single User entity carries a Role flag rather than splitting Organiser and Participant into separate tables, because both share the same core identity attributes (name, email, password, profile picture) and only differ in behaviour, not structure — that behavioural difference is enforced in the API's authorisation logic in Part 2, not in the schema. Cardinality is shown using 1..* (one-to-many) and 1..1 (one-to-one) notation at each end of every connector.



Solid lines mark the primary ownership chain (User → Event → Category → Enrolment → Result). Dashed lines mark the two secondary relationships where User and Event connect directly into Enrolment.

IMAGE DESIGNED USING CANVA

Entity Detail

User

Represents every account in the system, whether Organiser or Participant. Kept as one table because an Organiser and a Participant are the same kind of thing — a person with login credentials — and duplicating that structure across two tables would violate normalisation for no benefit.

- UserId (PK) — surrogate key, referenced by Event.OrganiserId and Enrolment.ParticipantId.
- Email (unique) — doubles as the login identifier; uniqueness is enforced at the database level, not just in application code.
- PasswordHash — the password is hashed (never stored in plain text), satisfying the assignment's authentication requirement.
- Role — a constrained value (Organiser/Participant) that the API reads from the session on every request to decide what the caller may do.
- ProfilePictureUrl — points to a file in Azure Blob Storage (Part 3); the User table stores only the URL, not the image.

EventType

A lookup table for Run / Walk / Cycle. This was pulled out as its own entity — rather than a hardcoded string or enum on Event — specifically to satisfy the brief's minimum of six entities with a proper foreign-key relationship, and because it mirrors how a real system would let new event types be added later without a schema change.

- EventTypeId (PK) — referenced by Event.EventTypeId.
- Name — the display value shown when browsing events.

Event

The central entity of the system. Every Event belongs to exactly one Organiser and one EventType, and owns its own Categories and Enrolments.

- EventId (PK) — referenced by Category, Enrolment (indirectly via Category), and directly by Enrolment.EventId.
- OrganiserId (FK → User) — identifies who may edit or delete this event; this is the field every ownership check in Part 2 relies on.
- EventTypeId (FK → EventType) — classifies the event as Run, Walk or Cycle.
- BannerImageUrl — populated after upload to Azure Blob Storage, same pattern as the User's profile picture.

Category

An age or distance category that only makes sense in the context of one specific event (e.g. '10km' for a cycling event, 'Under 20' for a fun run). This is why Category has a mandatory FK to Event rather than being a global lookup — the same category name can exist independently under different events.

- CategoryId (PK) — referenced by Enrolment.CategoryId.
- EventId (FK → Event) — every category is scoped to exactly one event.

Enrolment

The junction that records a Participant entering a specific Event under a specific Category. This is the busiest entity in the model — it has three foreign keys — because it is genuinely the intersection of three other entities, and it is also where a Result eventually attaches.

- EnrolmentId (PK) — referenced by Result.EnrolmentId.
- ParticipantId (FK → User) — restricted at the API level to users with Role = Participant.
- EventId (FK → Event) and CategoryId (FK → Category) — together these must be consistent (the chosen category must actually belong to the chosen event); this is validated in the API, since a foreign key alone can't express that cross-table rule.
- EnrolmentStatus — Pending or Confirmed, satisfying the brief's requirement for visually distinct, colour-coded statuses in Part 3.

Result

Deliberately kept separate from Enrolment rather than adding FinishTime/FinishingPosition columns directly onto it. The reasoning: an Enrolment exists the moment someone signs up, long before the event happens, while a Result only exists after the event concludes and the Organiser captures it. Splitting them means an Enrolment can exist with no Result for weeks, which matches the real workflow far more honestly than nullable columns would.

- ResultId (PK).
- EnrolmentId (FK, unique) — the uniqueness constraint is what enforces the 1..1 relationship: one Enrolment can never have more than one Result.

Relationship Summary

Relationship	Cardinality	Business Meaning
User (Organiser) → Event	**1..***	One Organiser creates many Events; every Event has exactly one owning Organiser.
EventType → Event	**1..***	One EventType classifies many Events.
Event → Category	**1..***	One Event defines many Categories; a Category belongs to exactly one Event.
Event → Enrolment	**1..***	One Event receives many Enrolments.
Category → Enrolment	**1..***	One Category is selected by many Enrolments.
User (Participant) → Enrolment	**1..***	One Participant can enrol in many Enrolments (different events); each Enrolment belongs to exactly one Participant.
Enrolment → Result	**1..1**	Each Enrolment produces at most one Result, and each Result belongs to exactly one Enrolment.

Section B — API Endpoint Plan

The endpoints below are grouped by functional area, matching the order they'll be built in Part 2. Each description explains not just what the endpoint does, but the access rule or business logic behind it, so the plan can be implemented from this document without guessing at intent. Role columns distinguish 'any authenticated user' from role-specific and ownership-specific restrictions — ownership checks (e.g. 'Organiser, owner only') are stricter than a simple role check and must be enforced in the controller logic, not just via a role attribute.

1. Authentication

Handles account creation, login and logout. Every other protected endpoint in the system depends on the session these three establish.

Method	Route	Description	Role	Request Body	Expected Response
POST	/api/auth/register	Creates a new account. The caller chooses their role (Organiser or Participant) at registration time, which permanently determines what the account can do — this single decision is what the whole role-based access system in Part 2 hinges on. The password is never stored as-is; it is hashed before it touches the database.	None (public)	{ fullName, email, password, role }	201 Created returns the new user's id, name and role (never the password/hash) 400 Bad Request missing/invalid fields 409 Conflict email already registered
POST	/api/auth/login	Validates credentials against the stored hash and starts an authenticated session. The session is what every subsequent protected endpoint checks — it must carry both the user's identity and their role, since role is checked on almost every write operation.	None (public)	{ email, password }	200 OK session started, returns id/name/role 401 Unauthorized invalid email or password
POST	/api/auth/logout	Clears the session so the client is treated as anonymous again. Included so the MVC app in Part 3 has a clean way to end a user's visit.	Any (logged in)	None	200 OK session cleared

2. User Profile

Lets any logged-in user view and maintain their own information — deliberately self-scoped, with no endpoint that exposes another user's profile.

Method	Route	Description	Role	Request Body	Expected Response
GET	/api/profile	Returns only the calling user's own record — there is deliberately no way to fetch another user's profile through this route, which keeps personal data scoped to its owner.	Any (logged in)	None	200 OK own profile fields 401 Unauthorized no active session
PUT	/api/profile	Lets a user update their display name and profile picture. The picture itself is uploaded to Azure Blob Storage in Part 3; this endpoint only stores the resulting URL, so the API never handles raw image bytes here.	Any (logged in)	{ fullName, profilePictureUrl }	200 OK updated profile 400 Bad Request invalid data

3. Events

Public read access supports browsing without an account; all write access is restricted to the owning Organiser.

Method	Route	Description	Role	Request Body	Expected Response
GET	/api/events	Public listing of upcoming events, used by the Participant home page for browsing and filtering. Deliberately open to unauthenticated callers since events are meant to be discoverable.	Any (public)	None	200 OK array of events
GET	/api/events/{id}	Full detail for one event, including its list of categories, so the event detail page can be built from a single call.	Any (public)	None	200 OK event detail with categories 404 Not Found
POST	/api/events	Creates an event owned by the calling Organiser. OrganiserId is taken from the session, never from the request body, so one Organiser can never create an event under another Organiser's name.	Organiser	{ name, description, date, location, distance, eventTypeId, bannerImageUrl }	201 Created new event 400 Bad Request 403 Forbidden caller is a Participant

Method	Route	Description	Role	Request Body	Expected Response
PUT	/api/events/{id}	Updates an event. The API must check not only that the caller is an Organiser, but that they are the specific Organiser who owns this event — ownership, not just role, is the real access rule here.	Organiser (owner only)	{ name, description, date, location, distance, eventTypeId, bannerImageUrl }	200 OK updated event 403 Forbidden not the owner 404 Not Found
DELETE	/api/events/{id}	Deletes an event owned by the calling Organiser. Cascading behaviour (what happens to its Categories/Enrolments) is handled in the SQL script's foreign key constraints.	Organiser (owner only)	None	204 No Content 403 Forbidden 404 Not Found

4. Categories

Categories are always managed in the context of their parent event.

Method	Route	Description	Role	Request Body	Expected Response
GET	/api/events/{eventId}/categories	Lists the categories available for one event, used both on the event detail page and the enrolment form where a Participant picks a category.	Any (public)	None	200 OK array of categories 404 Not Found
POST	/api/events/{eventId}/categories	Adds a category (e.g. '10km', 'Under 20') to an event the Organiser owns. Categories only ever belong to one event, matching the ERD's Event 1..* Category relationship.	Organiser (owner only)	{ name }	201 Created new category 403 Forbidden 404 Not Found

5. Event Enrolments

Where Participants and Events actually connect. This area carries the most business rules of any part of the API — duplicate prevention, category-event consistency, and role separation.

Method	Route	Description	Role	Request Body	Expected Response
POST	/api/events/{eventId}/enrolments	Records that the calling Participant is entering an event under a specific category. The API should reject a duplicate enrolment (same Participant, same	Participant	{ categoryId }	201 Created new enrolment, status Pending 400 Bad Request invalid category for this event 403 Forbidden

Method	Route	Description	Role	Request Body	Expected Response
		Event) so one person can't accidentally enrol twice.			caller is an Organiser 409 Conflict already enrolled
GET	/api/enrolments/mine	The Participant's own enrolment list with status, powering their 'My Events' view — never exposes other Participants' enrolments.	Participant	None	200 OK array of the caller's enrolments 401 Unauthorized
GET	/api/events/{eventId}/enrolments	Gives the owning Organiser the full roster for one event — who enrolled, in which category, and their status — which is what the Organiser needs before capturing results.	Organiser (owner only)	None	200 OK array of enrolments with participant + category 403 Forbidden 404 Not Found

6. Results

The final stage of an event's lifecycle — results can only be captured by the Organiser who owns the event, and only once per enrolment.

Method	Route	Description	Role	Request Body	Expected Response
POST	/api/enrolments/{enrolmentId}/results	Captures a finish time and position for one enrolment after the event concludes. Restricted to a single Result per Enrolment (enforced by the unique FK in the SQL script) so a participant's result can't be recorded twice.	Organiser (owner only)	{ finishTime, finishingPosition }	201 Created new result 400 Bad Request 403 Forbidden 404 Not Found 409 Conflict result already captured
GET	/api/results/mine	The Participant's full personal race history — joining their Enrolments to Results and Events so each row shows the event name, date, category, finish time and position.	Participant	None	200 OK array of results 401 Unauthorized

Section C — SQL Database Script

```
/* ================================================================================
   RaceDay - Part 1, Section C: SQL Database Script
   ---------------------------------------------------------------
IF DB_ID('RaceDay') IS NULL
BEGIN
    CREATE DATABASE RaceDay;
END
USE RaceDay;




SET NOCOUNT ON;
```

```
/* ----------------------------------------------------------------
   Drop tables if they already exist (clean re-run support), in
   child-to-parent order to respect foreign keys.
   ---------------------------------------------------------------- */
IF OBJECT_ID('dbo.Results', 'U') IS NOT NULL DROP TABLE dbo.Results;
IF OBJECT_ID('dbo.Enrolments', 'U') IS NOT NULL DROP TABLE dbo.Enrolments;
IF OBJECT_ID('dbo.Categories', 'U') IS NOT NULL DROP TABLE dbo.Categories;
IF OBJECT_ID('dbo.Events', 'U') IS NOT NULL DROP TABLE dbo.Events;
IF OBJECT_ID('dbo.EventTypes', 'U') IS NOT NULL DROP TABLE dbo.EventTypes;
IF OBJECT_ID('dbo.Users', 'U') IS NOT NULL DROP TABLE dbo.Users;



/* ================================================================
```

1. Users

Stores both Organisers and Participants, distinguished by Role.

========== */

```
CREATE TABLE dbo.Users
(
    UserId            INT IDENTITY(1,1)   NOT NULL,
    FullName          NVARCHAR(100)       NOT NULL,
    Email             NVARCHAR(150)       NOT NULL,
    PasswordHash      NVARCHAR(255)       NOT NULL,
    Role              NVARCHAR(20)        NOT NULL,
    ProfilePictureUrl NVARCHAR(500)       NULL,
    CreatedAt         DATETIME2           NOT NULL DEFAULT SYSDATETIME(),

    CONSTRAINT PK_Users PRIMARY KEY (UserId),
    CONSTRAINT UQ_Users_Email UNIQUE (Email),
```

```
    CONSTRAINT CK_Users_Role CHECK (Role IN ('Organiser', 'Participant'))
);

/* ============================================================================
```

```
   2. EventTypes
   Lookup table: Run / Walk / Cycle.
   ============================================================================ */
CREATE TABLE dbo.EventTypes
(
    EventTypeId INT IDENTITY(1,1) NOT NULL,
    Name        NVARCHAR(30)      NOT NULL,

    CONSTRAINT PK_EventTypes PRIMARY KEY (EventTypeId),
    CONSTRAINT UQ_EventTypes_Name UNIQUE (Name)
);

/* ============================================================================
```

```
   3. Events
   Owned by an Organiser (Users), classified by EventType.
   ============================================================================ */

CREATE TABLE dbo.Events
(
   EventId        INT IDENTITY(1,1)   NOT NULL,
   Name           NVARCHAR(150)       NOT NULL,
   Description    NVARCHAR(1000)      NULL,
   Date           DATETIME2           NOT NULL,
   Location       NVARCHAR(150)       NOT NULL,
   Distance       DECIMAL(6,2)        NOT NULL,
   EventTypeId    INT                 NOT NULL,
   OrganiserId    INT                 NOT NULL,
   BannerImageUrl NVARCHAR(500)       NULL,
```

```
    CONSTRAINT PK_Events PRIMARY KEY (EventId),
    CONSTRAINT FK_Events_EventTypes FOREIGN KEY (EventTypeId)
        REFERENCES dbo.EventTypes (EventTypeId),
    CONSTRAINT FK_Events_Organiser FOREIGN KEY (OrganiserId)
        REFERENCES dbo.Users (UserId),
    CONSTRAINT CK_Events_Distance CHECK (Distance > 0)
);









/* ================================================================================
```

4. Categories

Age/distance categories, scoped to one Event.

========== */

```
CREATE TABLE dbo.Categories
(
    CategoryId  INT IDENTITY(1,1) NOT NULL,
    EventId     INT               NOT NULL,
    Name        NVARCHAR(50)      NOT NULL,

    CONSTRAINT PK_Categories PRIMARY KEY (CategoryId),
    CONSTRAINT FK_Categories_Events FOREIGN KEY (EventId)
        REFERENCES dbo.Events (EventId) ON DELETE CASCADE,
    CONSTRAINT UQ_Categories_EventName UNIQUE (EventId, Name)
);
/* ==========
```

```
   5. Enrolments
   Links a Participant (Users) to an Event under a chosen Category.
   ============================================================================ */
CREATE TABLE dbo.Enrolments
(
   EnrolmentId     INT IDENTITY(1,1)   NOT NULL,
   ParticipantId   INT                 NOT NULL,
   EventId         INT                 NOT NULL,
   CategoryId      INT                 NOT NULL,
   EnrolmentStatus NVARCHAR(20)        NOT NULL DEFAULT 'Pending',
   EnrolmentDate   DATETIME2           NOT NULL DEFAULT SYSDATETIME(),

   CONSTRAINT PK_Enrolments PRIMARY KEY (EnrolmentId),
   CONSTRAINT FK_Enrolments_Participant FOREIGN KEY (ParticipantId)
      REFERENCES dbo.Users (UserId),
```

```
    CONSTRAINT FK_Enrolments_Events FOREIGN KEY (EventId)
        REFERENCES dbo.Events (EventId),
    CONSTRAINT FK_Enrolments_Categories FOREIGN KEY (CategoryId)
        REFERENCES dbo.Categories (CategoryId),
    CONSTRAINT CK_Enrolments_Status CHECK (EnrolmentStatus IN ('Pending', 'Confirmed')),
    -- A Participant may only enrol once per Event (prevents duplicate enrolment)
    CONSTRAINT UQ_Enrolments_Participant_Event UNIQUE (ParticipantId, EventId)
);









/* ================================================================================
```

```
   6. Results
   One-to-one with Enrolments (unique FK). Only exists once an event
   has concluded and the Organiser has captured the outcome.
   ================================================================== */
CREATE TABLE dbo.Results
(
   ResultId          INT IDENTITY(1,1)  NOT NULL,
   EnrolmentId       INT                NOT NULL,
   FinishTime        TIME(0)            NOT NULL,
   FinishingPosition INT                NOT NULL,

   CONSTRAINT PK_Results PRIMARY KEY (ResultId),
   CONSTRAINT FK_Results_Enrolments FOREIGN KEY (EnrolmentId)
      REFERENCES dbo.Enrolments (EnrolmentId),
   CONSTRAINT UQ_Results_Enrolment UNIQUE (EnrolmentId),
```

```
    CONSTRAINT CK_Results_Position CHECK (FinishingPosition > 0)
);

/* ============================================================================
```

```
   SEED DATA

   ============================================================================== */


/* ---- Users: 2 Organisers, 2 Participants -------------------------- */

INSERT INTO dbo.Users (FullName, Email, PasswordHash, Role, ProfilePictureUrl)

VALUES

   ('Thabo Nkosi',     'thabo.nkosi@raceday.co.za',     'AQAAAAIAAYagAAAAEHash001==', 'Organiser',   NULL),

   ('Lerato Dube',     'lerato.dube@raceday.co.za',     'AQAAAAIAAYagAAAAEHash002==', 'Organiser',   NULL),

   ('Sipho Mahlangu',   'sipho.mahlangu@example.com',    'AQAAAAIAAYagAAAAEHash003==', 'Participant',
NULL),

   ('Anika van Wyk',    'anika.vanwyk@example.com',      'AQAAAAIAAYagAAAAEHash004==', 'Participant',
NULL);




/* ---- EventTypes --------------------------------------------------- */
```

```
INSERT INTO dbo.EventTypes (Name)
VALUES ('Run'), ('Walk'), ('Cycle');



/* ---- Events: 3 events, each owned by an Organiser ---------- */
-- OrganiserId 1 = Thabo Nkosi, OrganiserId 2 = Lerato Dube
-- EventTypeId 1 = Run, 2 = Walk, 3 = Cycle
INSERT INTO dbo.Events (Name, Description, Date, Location, Distance, EventTypeId, OrganiserId,
BannerImageUrl)
VALUES
    ('Pretoria Spring Fun Run', 'A community fun run through the Pretoria CBD and Union Buildings gardens.',
        '2026-10-18T07:00:00', 'Pretoria, Gauteng', 10.00, 1, 1, NULL),
    ('Cape Peninsula Cycle Classic', 'A scenic cycling event along the Cape Peninsula coastline.',
        '2026-11-08T06:00:00', 'Cape Town, Western Cape', 100.00, 3, 2, NULL),
    ('Durban Beachfront Charity Walk', 'A family-friendly charity walk along the Durban beachfront promenade.',
```

```
        '2026-09-27T08:00:00', 'Durban, KwaZulu-Natal', 5.00, 2, 1, NULL);



/* ---- Categories: 2-3 per event ------------------------------------- */
-- EventId 1 = Pretoria Spring Fun Run
INSERT INTO dbo.Categories (EventId, Name) VALUES
    (1, 'Under 20'),
    (1, 'Senior (20-39)'),
    (1, 'Veteran (40+)');
-- EventId 2 = Cape Peninsula Cycle Classic
INSERT INTO dbo.Categories (EventId, Name) VALUES
    (2, '50km'),
    (2, '100km');
-- EventId 3 = Durban Beachfront Charity Walk
INSERT INTO dbo.Categories (EventId, Name) VALUES
```

```
    (3, 'Open'),
    (3, 'Family (with children)');

/* ---- Enrolments ---------------------------------------------------- */
```

```
-- ParticipantId 3 = Sipho Mahlangu, ParticipantId 4 = Anika van Wyk

INSERT INTO dbo.Enrolments (ParticipantId, EventId, CategoryId, EnrolmentStatus)

VALUES

    (3, 1, 2, 'Confirmed'),  -- Sipho -> Pretoria Fun Run -> Senior (20-39)

    (4, 1, 3, 'Confirmed'),  -- Anika -> Pretoria Fun Run -> Veteran (40+)

    (3, 2, 5, 'Pending'),    -- Sipho -> Cape Peninsula Cycle Classic -> 100km

    (4, 3, 6, 'Confirmed');  -- Anika -> Durban Beachfront Charity Walk -> Open

/* ---- Results: captured for the two Confirmed, already-concluded style enrolments ---- */
```

```
-- EnrolmentId 1 = Sipho @ Pretoria Fun Run, EnrolmentId 2 = Anika @ Pretoria Fun Run

INSERT INTO dbo.Results (EnrolmentId, FinishTime, FinishingPosition)

VALUES

    (1, '00:52:14', 47),

    (2, '00:58:03', 112);
```

```
/* ============================================================================

   Verification

   Run this on its own after the script finishes - DB_NAME() should

   return 'RaceDay', and each SELECT should return your seeded rows.

   ============================================================================ */

SELECT DB_NAME() AS CurrentDatabase;

SELECT * FROM dbo.Users;

SELECT * FROM dbo.EventTypes;


SELECT * FROM dbo.Events;

SELECT * FROM dbo.Categories;
```

```
SELECT * FROM dbo.Enrolments;

SELECT * FROM dbo.Results;
```

RESULT OF THE FINAL OUTPUT


File Edit View Query Git Project Tools Extensions Window Help Search
Sign in
ADMIN
New Query
RaceDay
Execute
Object Explorer
Connect
SQLQuery1.s...tudent (94))*
return 'RaceDay', and each SELECT should return your seeded rows.
SELECT DB_NAME() AS CurrentDatabase;
SELECT * FROM Users;
SELECT * FROM EventTypes;
SELECT * FROM Events;
SELECT * FROM Categories;
SELECT * FROM Enrolments;
SELECT * FROM Results;
100 %
No issues found
Ln: 252, Ch: 23
(148 chars, 6 lines)
SPC
CRLF
UTF-8
Results
Messages
UserId FullName Email PasswordHash Role ProfilePictureUrl CreatedAt
1 1 Thabo Nkosi thabo.nkosi@raceday.co.za AQAAAAIAAYagAAAAEHash001== Organiser NULL 2026-09-03 13:52:11.2176213
2 2 Lerato Dube lerato.dube@raceday.co.za AQAAAAIAAYagAAAAEHash002== Organiser NULL 2026-09-03 13:52:11.2176213
3 3 Sipho Mahlangu sipho.mahlangu@example.com AQAAAAIAAYagAAAAEHash003== Participant NULL 2026-09-03 13:52:11.2176213
4 4 Anika van Wyk anika.vanwyk@example.com AQAAAAIAAYagAAAAEHash004== Participant NULL 2026-09-03 13:52:11.2176213
EventTypeId Name
1 3 Cycle
2 1 Run
3 2 Walk
EventId Name Description Date Location Distance EventTypeId OrganiserId BannerImageUrl
1 1 Pretoria Spring Fun Run A community fun run through the Pretoria CBD and ... 2026-10-18 07:00:00.0000000 Pretoria, Gauteng 10.00 1 1 NULL
2 2 Cape Peninsula Cycle Classic A scenic cycling event along the Cape Peninsula c... 2026-11-08 06:00:00.0000000 Cape Town, Western Cape 100.00 3 2 NULL
3 3 Durban Beachfront Charity Walk A family-friendly charity walk along the Durban bea... 2026-09-27 08:00:00.0000000 Durban, KwaZulu-Natal 5.00 2 1 NULL
CategoryId EventId Name
1 2 1 Senior (20-39)
2 1 1 Under 20
3 3 1 Veteran (40+)
4 5 2 100km
5 4 2 50km
6 7 3 Family (with ...
7 6 3 Open
EnrolmentId ParticipantId EventId CategoryId EnrolmentStatus EnrolmentDate
1 1 3 1 2 Confirmed 2026-09-03 13:52:47.2798157
2 2 4 1 3 Confirmed 2026-09-03 13:52:47.2798157
3 3 3 2 5 Pending 2026-09-03 13:52:47.2798157
4 4 4 3 6 Confirmed 2026-09-03 13:52:47.2798157
ResultId EnrolmentId FinishTime FinishingPosition
1 1 1 00:52:14 47
2 2 2 00:58:03 112
Query executed successfully.
(local)\SQLEXPRESS (17.0 RTM)
LabVM2049826\Student (94)
RaceDay
00:00:00
Row: 1, Col: 1
23 rows
Ready
Select Repository