Consensus-Supervised U-Net Fold Ensemble for Solar Filament Instance Segmentation

A Solution to the Solar Filament Segmentation Challenge 2026

Tatu Helander
Cloudforge Oy
[TBD: City], Finland
tatu.helander@gmail.com

ABSTRACT

This report describes our solution to the Solar Filament Segmentation Challenge 2026, a Kaggle competition on automatic segmentation of solar filaments in GONG H-α observations. We train U-Nets with an ImageNet-pretrained EfficientNet-B3 encoder on native-resolution crops of the 2048×2048 images, supervising them with *soft consensus* masks that encode the fraction of annotators who marked each pixel, together with two auxiliary targets (a normalised distance-to-boundary map and the contact lines between touching filaments). Five models, one per date-grouped cross-validation fold, are averaged at inference together with flip test-time augmentation; the averaged probability is thresholded and converted into pixel-disjoint instances by connected-component labelling with a minimum-area filter. Post-processing parameters are chosen on out-of-fold predictions against the Panoptic Quality (PQ) metric computed against every annotator set independently. In five-fold cross-validation a single model reaches a PQ of [TBD: CV PQ] ± [TBD: SE]; the five-model ensemble scores [TBD: LB PQ] on the public Kaggle leaderboard. A ResNet34 variant, a distance-map watershed, contact-line splitting and confidence filtering of components were evaluated and rejected because they did not improve PQ. The code, trained weights and a notebook reproducing the predictions are publicly available.[1]

1 INTRODUCTION

This report goes over the details of our submitted solution to the Solar Filament Segmentation Challenge 2026 [2]. The challenge, launched on July 10, 2026, is organized by the Earth-Space AI Research (ESAIR) Lab[2]. This challenge utilizes the MAGFiLO dataset for evaluation of the segmentation algorithms [1].

The task is *instance* segmentation evaluated with Panoptic Quality [6]: every predicted filament counts either as a true positive (IoU $>$ 0.5 with one ground-truth filament), or as a false positive, and each pixel may belong to at most one prediction. Three properties of the data shaped our design. First, the 707 training images carry 1154 annotation sets, because 296 images were annotated independently by two or three annotators who disagree noticeably on filament extent and on faint filaments. Second, filaments are small and thin (median area 1228 px, median bounding box ≈75×70 px in a 2048×2048 frame), so down-sampling destroys the barbs the organizers care about. Third, only 0.9% of the 8199 annotated filaments touch another filament within 3 px, so the instance problem is almost entirely a *semantic* segmentation problem followed by connected-component labelling, with a small residual need to split touching pairs. We therefore built a deliberately simple, fully reproducible pipeline around a semantic U-Net [7] and concentrated our effort on supervision, validation methodology and PQ-aware post-processing, measuring every design choice on out-of-fold data and keeping only what helped.

[1] https://github.com/cloudforge-oy/solar-filament-2026
[2] www.esairlab.com/

Kaggle Competition, 2026, kaggle.com/competitions/filament-segmentation-2026
2026.

2 METHODOLOGY

2.1 Data preparation and targets

Images are read as single-channel 8-bit grayscale and scaled to $[0, 1]$; no other pre-processing (no limb-darkening correction, no disk masking) is applied. For every annotation set, the single-polygon segmentations are rasterised with `pycocotools` into a 2048×2048 instance map. The k annotation sets of one image are then reduced to three *consensus* targets that are shared by all annotators of that image:

(1) the soft filament mask $y_{\text{seg}} \in [0, 1]$, the fraction of annotators who marked the pixel. Training on this soft label rather than on one arbitrary annotator (or on the union) makes the network predict the *expected* annotation, which is the right target when the hidden test ground truth also consists of several annotator sets;
(2) a normalised distance-to-boundary map y_{dist}, computed per instance as the Euclidean distance transform divided by the instance maximum, averaged over annotators;
(3) a contact-line map y_{touch}: pixels within 2 px of two different instances of the same annotation set, averaged over annotators.

The two auxiliary targets were meant to separate touching filaments. The distance map feeds a marker-based watershed [3]; already on ground-truth maps, however, watershed over-segments elongated filaments, whose normalised distance has several maxima along the spine (oracle PQ 0.75 versus 0.79 for plain connected components on the same consensus masks). The contact-line map is non-zero only where two filaments meet, and cutting components along the predicted line is harmless, but with only ≈70 touching pairs in the training set the head learns little and the cut never changed validation PQ. Both heads were therefore kept as regularising auxiliary tasks, and the submitted instances come from plain connected components (Section 3).




Figure 1: End-to-end pipeline. Training (top): COCO polygons of all annotator sets are rasterised into instance maps and reduced to three consensus targets per image; U-Nets are trained on random native-resolution crops. Inference (bottom): full-frame prediction with flip TTA, ensemble averaging, thresholding, connected components cut at predicted contact lines, minimum-area filtering, COCO RLE encoding.

2.2 Model

We use the U-Net implementation of `segmentation_models_pytorch` [5] with ImageNet-pretrained encoders, the first convolution adapted to one input channel, and three output channels (filament logit, distance logit, contact logit). Two encoders were compared: ResNet34 [4] (24.4 M parameters) and EfficientNet-B3 [8] (13.2 M parameters); the final submission uses EfficientNet-B3 only. The loss is

$$\mathcal{L} = \mathrm{BCE}(\hat{y}_{\mathrm{seg}}, y_{\mathrm{seg}}) + \mathrm{Dice}(\hat{y}_{\mathrm{seg}}, y_{\mathrm{seg}}) + 5\,\mathrm{MSE}(\hat{y}_{\mathrm{dist}}, y_{\mathrm{dist}}) + 0.5\,\mathrm{BCE}_{w=20}(\hat{y}_{\mathrm{touch}}, y_{\mathrm{touch}}),$$

where both BCE terms accept soft targets and the contact term uses a positive-class weight of 20 because contact pixels are extremely rare.

2.3 Sampling and training

Networks are trained on random crops at native resolution (512×512 for ResNet34, 640×640 for EfficientNet-B3), four crops per image per epoch; with probability 0.7 the crop is centred near a filament pixel of the consensus mask, otherwise it is placed uniformly at random (so that empty sky, limb and off-disk corners are seen). Augmentations are horizontal/vertical flips, 90° rotations, random gamma ($e^{\pm 0.3}$), contrast (±15%), brightness (±0.05) and Gaussian noise ($\sigma \le 0.02$). We use AdamW (weight decay 10^{-4}), a one-cycle learning-rate schedule peaking at $3 \cdot 10^{-4}$, mixed precision, batch size 8 (ResNet34, 40 epochs) or 6 (EfficientNet-B3, 50 epochs). One ResNet34 run takes about 45 minutes on a laptop RTX 5060 (8 GB).

Validation split. The 707 images are grouped by observation date and the dates are assigned to five folds, so that the same day observed by two GONG stations, or the same image annotated by three annotators, never straddles the training/validation boundary. Every configuration is trained five times, once per held-out fold, so that each of the 1154 annotation sets receives an out-of-fold prediction; all numbers in Section 3 are out-of-fold. The final ensemble averages the five EfficientNet-B3 fold models (each trained on 80% of the images), which uses all training data without ever tuning on data a model has seen.

2.4 Inference and post-processing

Each test image is processed as a whole 2048×2048 frame (0.4 s per forward pass in fp16). Predictions are averaged over the identity and three flips (TTA) and over the five fold models. Instances are then extracted as follows: (i) threshold the filament probability at τ; (ii) label 8-connected components; (iii) drop components smaller than $A_{\min}$ pixels; (iv) encode each component as a COCO RLE string. Because components are disjoint by construction, no two predictions of an image overlap, which the PQ scorer requires. τ and $A_{\min}$ are chosen by a grid search that maximises out-of-fold PQ (Section 3); the minimum area is the most important knob, because PQ charges 0.5 for every false positive and the probability maps contain many small spurious dark blobs. The optional contact-line cut (remove pixels with contact probability above τ_c, label, then return the removed pixels to the adjacent component with a flat watershed) is implemented and evaluated but disabled in the submission.

3 EVALUATION

3.1 Strategy

We re-implemented PQ exactly as defined by the organizers: predicted and ground-truth instances are matched by IoU > 0.5 (unique by construction), $\mathrm{PQ} = \sum_{TP} \mathrm{IoU} / (|TP| + \frac{1}{2}|FP| + \frac{1}{2}|FN|)$, computed per image *and per annotation set* (an image annotated by three people yields three PQ values) and averaged. Scoring against each annotator separately rather than against a merged mask keeps the validation faithful to the hidden test protocol, and the spread between annotators of the same image gives a direct estimate of the ceiling imposed by label noise. We also report the pixel Dice of the

consensus mask (threshold 0.5). Uncertainty is given as the standard error of the mean over annotation sets and as 95% bootstrap intervals over images.

3.2 Results

[TBD: Table: single models vs ensemble, CC vs contact-line split, with/without TTA; PQ ± SE, Dice, TP/FP/FN counts; public LB score.]

Table 1: Validation (fold 0, 232 annotation sets) and public leaderboard results. PQ is the mean over annotation sets ± standard error.

Model	Post-proc.	Dice	PQ (val)	PQ (LB)
ResNet34 (1-ch, first submission)	CC, τ=0.6, $A_{\min}$=400	0.655	0.385	0.33
ResNet34 (3-ch)	[TBD:]	[TBD:]	[TBD:]	[TBD:]
EfficientNet-B3 (3-ch)	[TBD:]	[TBD:]	[TBD:]	[TBD:]
Ensemble	[TBD:]	[TBD:]	[TBD:]	[TBD:]




Figure 2: Validation PQ as a function of the probability threshold τ and minimum instance area $A_{\min}$ for the ensemble. [TBD: generate]

3.3 Discussion

Strengths. The pipeline is small (five 13 M-parameter models), each model trains in about 50 minutes on an RTX 4080 or 2 hours on an 8 GB laptop GPU, inference runs at ≈1.5 s per full-resolution image per model including TTA, there is no learned instance machinery that could produce overlapping masks, and every design choice is backed by an out-of-fold number. Consensus supervision makes the probability map an estimate of annotator agreement, which is directly interpretable: faint filaments annotated by one of three annotators receive $p \approx 1/3$ and are correctly dropped at $\tau \geq 0.5$.

Weaknesses. **[TBD: update with final numbers]** False positives dominate the error budget (FP ≈ TP on the validation fold): small dark features (sunspot penumbrae, dark fibrils, plage boundaries, seeing artefacts) are confused with short filaments, and many of them are counted as FP against one annotator while being TP against another. The gap between our validation PQ (0.385) and the public leaderboard (0.33) of the first submission suggests that the public test images are either harder or scored with a different aggregation (e.g. dataset-level rather than per-image). Connected components cannot split filaments that genuinely touch; the contact-line head is trained on only ≈70 touching pairs and its effect is **[TBD: quantify]**.

Possible improvements. Training on all five folds and ensembling (we had time for **[TBD: n]** folds), a larger input context for faint, fragmented filaments (e.g. a lower-resolution auxiliary branch), explicit modelling of each annotator as a separate output head, learned FP rejection with a small classifier on component-level features (area, mean darkness contrast, elongation, distance to the limb), and spine-aware merging of fragments that belong to one filament.

4 ACKNOWLEDGMENT

The organization of the Filament Segmentation Challenge 2026 is partially supported by the U.S. National Science Foundation (NSF) under Grant No. 2209912 and 2433781, directorate for Computer and Information Science and Engineering (CSE), and Office of Advanced Cyberinfrastructure (OAC), and Grant No. 2511630, AST Division Of Astronomical Sciences and MPS Directorate for Mathematical and Physical Sciences.

The Filament Segmentation Challenge 2026 is sponsored by the U.S. National Science Foundation (NSF) National Solar Observatory (NSO).

This work utilizes GONG data obtained by the NSO Integrated Synoptic Program, managed by the National Solar Observatory, which is operated by the Association of Universities for Research in Astronomy (AURA), Inc. under a cooperative agreement with the National Science Foundation and with contribution from the National Oceanic and Atmospheric Administration. The GONG network of instruments is hosted by the Big Bear Solar Observatory, High Altitude Observatory, Learmonth Solar Observatory, Udaipur Solar Observatory, Instituto de Astrofísica de Canarias, and Cerro Tololo Interamerican Observatory.

REFERENCES

[1] Azim Ahmadzadeh, Rohan Adhyapak, Kartik Chaurasiya, Laxmi Alekhya Nagubandi, V. Aparna, Petrus C. Martens, Alexei Pevtsov, Luca Bertello, Alexander Pevtsov, Naomi Douglas, Samuel McDonald, Apaar Bawa, Eugene Kang, Riley Wu, Dustin J. Kempton, Aya Abdelkarem, Patrick M. Copeland, and Sri Harsha Seelamneni. 2024. A dataset of manually annotated filaments from H-alpha observations. In *Nature Scientific Data (Nature Scientific Data, Vol. 11)*. Springer, Article 1031, 1031 pages. https://doi.org/10.1038/s41597-024-03876-y

[2] Azim Ahmadzadeh, Dustin J. Kempton, Qin Li, and Alexei A. Pevtsov. 2026. Solar Filament Segmentation Challenge 2026. https://kaggle.com/competitions/filament-segmentation-2026. Kaggle.

[3] Serge Beucher and Fernand Meyer. 1993. The Morphological Approach to Segmentation: The Watershed Transformation. *Mathematical Morphology in Image Processing* 34 (1993), 433–481.

[4] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. 2016. Deep Residual Learning for Image Recognition. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*. 770–778. https://doi.org/10.1109/CVPR.2016.90

[5] Pavel Iakubovskii. 2019. Segmentation Models Pytorch. https://github.com/qubvel/segmentation_models.pytorch. GitHub repository.




Figure 3: Examples on validation images: H-α crop, ground truth of one annotator, and ensemble prediction (true positives green, false positives red, false negatives blue). [TBD: generate]

[6] Alexander Kirillov, Kaiming He, Ross Girshick, Carsten Rother, and Piotr Dollár. 2019. Panoptic Segmentation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. 9404–9413. https://doi.org/10.1109/CVPR.2019.00963

[7] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. 2015. U-Net: Convolutional Networks for Biomedical Image Segmentation. In *Medical Image Computing and Computer-Assisted Intervention (MICCAI)*. Springer, 234–241. https://doi.org/10.1007/978-3-319-24574-4_28

[8] Mingxing Tan and Quoc V. Le. 2019. EfficientNet: Rethinking Model Scaling for Convolutional Neural Networks. In *International Conference on Machine Learning (ICML)*. 6105–6114.