

# kettle入门(二) 之 kettle连接oracle报的坑爹错误 Error occurred while trying to connect to the database 的几种情况 - xiaohai798的专栏 - CSDN博客

## 1 引言


在用kettle开发抽取oracle数据的脚本时，时常会出现 Error occurred while trying to connect to the database 错误，但是仔细观察日志，引起这个错误的原因不尽相同。这个错误看起来很简单，但是有时候越简单的错误越没有耐心改，尤其是忙的时候，不小心填错了某个参数导致这个错误但是自己感觉没问题却跑不成功，这是最烦人的。这时候需要淡定、不妨上网查查，错误也许就可以愉快的解决了。下面给出这错误的**更细节错误**的不同发生情况。

## 2 示例


有个很简单的ktr脚本（当前kettle版本3.0.4），如下图：



表输入正常的配置信息如下：




下图 kettle安装文件目录（有jar包）的情况：



按照上述配置，ktr脚本是可以正常执行完的。

## 1 首先来看 缺少ojdbc jar包的错

下图是ojdbc包被删除的运行情况：




日志信息:

```
2014/11/18 23:25:16 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : An error occurred, processing will be stopped:
2014/11/18 23:25:16 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Error occured while trying to connect to the database
2014/11/18 23:25:16 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) :
2014/11/18 23:25:16 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Exception while loading class
2014/11/18 23:25:16 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : oracle.jdbc.driver.OracleDriver
2014/11/18 23:25:16 - 表输入 2 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : 错误初始化步骤[表输入 2]
```

重点是

exception while loading class oracle.jdbc.driver.OracleDriver。意思是加载类 oracle.jdbc.driver.OracleDriver 异常 这很有可能就是jar包出问题。

## 2 下面是ip地址输入错误




运行后:

日志给出的错误信息：

```
2014/11/18 23:29:41 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : An error occurred, processing will be stopped:
2014/11/18 23:29:41 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Error occured while trying to connect to the database
2014/11/18 23:29:41 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) :
2014/11/18 23:29:41 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Error connecting to database: (using class oracle.jdbc.driver.OracleDriver)
2014/11/18 23:29:41 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Io 异常: The Network Adapter could not establish the connection
```

Io异常大概意思是：网络适配器不能建立连接。

### 3 数据库名错误



运行后：

日志报错的情况：

An error occurred, processing will be stopped: Error occured while trying to connect to the database

2014/11/18 23:34:40 - 表输出.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Listener refused the connection with the following error:

ORA-12505, TNS:listener does not currently know of SID given in connect descriptor The Connection descriptor used by the client was:127.0.0.1:1521:orc

大概意思：监听由于下面的错误拒绝了连接：TNS（oracle 服务端和客户端通信协议）监听不知道当前的sid（数据库的唯一标识），这个sid在连接描述器中给出，使用这个描述器的客户端是127.0.0.1:1521:orc

### 4 端口号不正确

Connection information

General Pooling MySQL Oracle Informix SQL Server SAP R/3 Generic »4

Connection name orcl

Connection type  
MySQL  
Oracle  
AS/400  
MS Access  
MS SQL Server  
IBM DB2  
PostgreSQL

Method of access  
Native (JDBC)  
ODBC  
OCI  
JNDI

Server host name 127.0.0.1

Database name orcl

Port number 152

Username scott

Password \*\*\*\*

运行后:


日志情况:

错误与ip地址不准确一样:

2014/11/18 23:29:41 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : An error occurred, processing will be stopped:  
2014/11/18 23:29:41 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Error occured while trying to connect to the database  
2014/11/18 23:29:41 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) :  
2014/11/18 23:29:41 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Error connecting to database: (using class oracle.jdbc.driver.OracleDriver)  
2014/11/18 23:29:41 - 表输入 2.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Io 异常: The Network Adapter could not establish the connection

## 5 用户名或密码错误





运行后:

用户名或者密码错误, 日志信息都是如下:

```
!014/12/02 22:19:15 - 表输出.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : An error occurred initialising this step:
!014/12/02 22:19:15 - 表输出.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Error occurred while trying to connect to the database
!014/12/02 22:19:15 - 表输出.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) :
!014/12/02 22:19:15 - 表输出.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Error connecting to database: (using class oracle.jdbc.driver.OracleDriver)
!014/12/02 22:19:15 - 表输出.0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : ORA-01017: invalid username/password; logon denied
```

大概意思是: 无效的用户名或密码, 登陆被拒绝

## 6 运行服务器没有权限访问远程数据库

从运行服务器ping 远程数据库机器ip:

```
Pinging 134.64.60.173 with 32 bytes of data:

Reply from 134.64.60.173: bytes=32 time<1ms TTL=252
Reply from 134.64.60.173: bytes=32 time<1ms TTL=252
Reply from 134.64.60.173: bytes=32 time<1ms TTL=252
Reply from 134.64.60.173: bytes=32 time<1ms TTL=252


Ping statistics for 134.64.60.173:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

从运行服务器telnet 远程数据库端口:

```
C:\Documents and Settings\Administrator>telnet 134.64.60.173 1521_
```



都是通的，但是表输出是这个



的脚本会报错：

运行后：

```
20:07:00 - Perf_All_Run - 正在初始化 3 步骤...
20:07:00 - 表输出 0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : An error occurred initializing this step.
20:07:00 - 表输出 0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Error occurred while trying to connect to the database
20:07:00 - 表输出 0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : Error connecting to database. (using class oracle.jdbc.driver.OracleDriver)
20:07:00 - 表输出 0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : ORA-00604: error occurred at recursive SQL level 10BA-20001: Logon rejected@ORA-00512: at line 32
20:07:00 - 表输出 0 - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : 错误初始化步骤[表输出]
20:07:00 - Perf_All_Run - ERROR (version 3.0.4, build 53 from 2008/06/24 18:14:00) : 步骤 [表输出 0] 初始化失败!
```

logon rejected 拒绝登陆。运行脚本的机器没有访问数据库的权限导致此错误。

在这里 是表输出的数据库 设置了黑白名单 而运行服务器不在它的白名单里 导致此错误

### 3 总结

遇到类似的此类错误，需要淡定仔细的观察日志，使用排除法，才能快速的定位并解决掉问题。