

Musical Heart Rate Adjuster

Group #12

<https://github.com/revan/HeartRateAdjuster>

Kenny Bambridge, Jonathan Chang, Samani Gikandi,
Tae-Min Kim, Nikhil Shenoy, Revan Sopher

March 11, 2014



Contents

1	Customer Statement of Requirements/Project Proposal	5
1.1	Problem	5
1.1.1	More Specifically	5
1.1.2	Background	7
1.1.3	Devices and Specifications	7
1.2	Solution	7
1.2.1	Music	8
1.2.2	Database	9
1.2.3	System Architecture Diagram	9
1.2.4	Product Usage	10
1.2.5	Product Ownership (tentative)	11
1.3	Glossary of Terms	12
2	System Requirements	13
2.1	Functional Requirements	13
2.2	Non-Functional Requirements	15
2.3	On-Screen Appearance Requirements	15
2.4	Organization	22
2.4.1	Stakeholders	22
2.4.2	Actors and Goals	24
2.5	Use Cases	24
2.5.1	Casual Description of Use Cases	25
2.5.2	Traceability Matrix	25
2.5.3	Fully-Dressed Description of Use Cases	27
2.5.4	Use Case Diagram	34
2.5.5	System Sequence Diagrams	35
2.5.6	System Operation Contracts	37
2.5.7	Mathematical Model	38
3	User Interface Specification	39
3.1	Preliminary Design	39
3.1.1	Use Case UC-2: decreaseHeartRate	39
3.1.2	Use Case UC-3: getNextSong	40
3.1.3	Use Case UC-4: pausePlayback	41

3.1.4	Use Case UC-5: getStatistics	42
3.2	Effort Estimation	42
4	Domain Model	45
4.1	Concept Definitions	45
4.2	Association Definitions	46
4.3	Attribute Definitions	47
4.4	Tracability Matrix	48
5	Plan of Work	49
5.1	Gantt Chart	50
5.2	Product Ownership	50
5.3	Breakdown of Responsibilities	51
6	Interaction Diagrams	52
6.1	Alternate Scenarios	58
6.2	Design Patterns	60
6.3	Assignment of Responsibilities	60
7	Class Diagram and Interface Specification	62
7.1	Class Diagram	63
7.1.1	Class Diagram for Data Management	63
7.2	Data Types and Operation Signatures	65
7.3	Traceability Matrix	68
8	System Architecture and System Design	69
8.1	Architectural Styles	69
8.2	Identifying Subsystems	69
8.3	Mapping Subsystems to Hardware	69
8.4	Persistent Data Storage	69
8.5	Network Protocol	70
8.6	Global Control Flow	70
8.6.1	Execution Orderness	70
8.6.2	Time Dependency	70
8.6.3	Concurrency	70
8.7	Hardware Requirements	70

Team Profile

Nikhil Shenoy C++, Python

Revan Sopher Android programming, web programming, Java, Python

Tae-Min Kim Java, C++, Python

Samani Gikandi Java, C, Ruby, Network programming, Device driver/firmware programming

Kenny Bambridge IOS programming, web programming, Java, Python

Jonathan Chang documentation, organization, C++

1 Customer Statement of Requirements/Project Proposal

1.1 Problem

There seems to be a growing concern over the bevy of health-related issues that society faces: cancer, obesity, heart diseases. This is evidenced by the estimated \$25.9 billion that consumers spent on fitness membership in 2013 or the government's seemingly carte blanche spending on "perfecting" the healthcare.gov website. While it is impossible to completely eliminate health problems, we focus on a small, albeit interesting subset of the health industry - personal health monitoring. Just like "an apple a day keeps the doctor away," our project seeks to maintain the personal health of an individual, keeping him in the best physical shape possible, and reducing the risk of health problems.

1.1.1 More Specifically

Lack of education about proper fitness is a widespread problem. Many people in the country would like to exercise and stay in shape, but only a small subset of those people know how to monitor their health in a way that allows them to stay fit. There are several methods out there which people can use to get the proper information; tools such as fitness blogs, the President's Council on Fitness, Sports, and Nutrition, and the classic visit to the doctor's office are all excellent examples. However, many people don't know about those methods or choose not to utilize them, and they do their body a disservice by performing exercises that could be detrimental to their health. The Internet is littered with articles such as "9 Exercises You're Doing Wrong" and "The 7 Fitness Myths You Need to Know". With information like this readily available to exercisers, it can be hard to find correct information. And even if one does find correct information, he must check to see if that information applies to a person with his body shape and size. The general problem of finding correct exercise information is that there is no set standard; there is no "one size fits all" set of guidelines which one can follow to have an effective workout. Everybody's body responds differently to different exercises, so the best that the medical community can do is to provide a set of recommendations for people of the most average body type. While this set of recommendations is good in the general, they will never tailor to the needs of one's body and workout. Finding the correct exercise information for one's

body type is quite a difficult problem, and it will continue to be a problem until a solution is provided to track each person's exercise routine.

Of all the different metrics for measuring the quality of one's fitness, heart rate is the most important factor in determining whether a workout was effective. Monitoring one's heart rate is useful because it determines whether the exerciser is performing his exercise safely as well as successfully. Experts recommend that one's target heart rate during exercise should be between 60-85% percent of the maximum heart rate, and that anything higher than 85% increases cardiovascular and orthopedic risk to the exerciser. Naturally, the target heart rate varies for people of different ages, so one should always take this into account before starting a fitness regimen. Also, the frequency of exercise before the new regimen should be considered. If one has not exercised frequently before starting the new regimen, then he should start exercising at a rate that is towards the lower end of the target heart rate zone and then gradually increase his activity once his body gets accustomed to the exercise. Heart rate is a significant, if not the most important, factor in determining whether a workout was done correctly and effectively, and it must be monitored closely in order to prevent injury.

Unfortunately, there are people who don't know how to correctly monitor their heart rate, and they mistakenly create a certain fitness plan based on wrong information and end up not optimizing their workout. They go to the gym, run on the treadmill at a light pace, and consider that enough to maintain their health. They do not check their heart rate and make sure they are in the safe region of activity. This critical lack of measurement affects the entire workout. For an exercise to be effective, one must maintain a heart rate that is within the target range for an extended period of time. If not, the exerciser either puts himself at risk of injury or completes a workout that does very little to improve his fitness. Some use exhaustion and soreness after a workout as a judge of an effective workout. Although these methods do give an indication as to how effective the exercise was, they do not provide an insightful and accurate description of one's health. As a result, these people continue bad habits and routines that hinder their progress to stay fit; in fact, they may not be even making progress.

A solution to the problem of uninformed exercise must have three main components; it must include all relevant medical data such as heart rate information, create a fitness plan that fits relatively well to the client's body, and provide the client with feedback about the effectiveness of his workout. Once all these components come together, the client will be able to correctly monitor his health during exercise and get the most out of his workout.

1.1.2 Background

A healthy lifestyle depends upon a plethora of factors including environment, nutrition, socialization, and mental stability. However, we identified physical fitness and sleep as the two key factors to leading a healthy lifestyle. Their importance cannot be overstated.

Physical fitness or exercise fortifies the body, allowing one to stay in shape, avoid injuries, develop confidence, become stronger, and sleep better. Sufficient physical activity can reduce the risk of such symptoms as stress, depression, diabetes, high blood pressure, osteoporosis, and obesity.

Meanwhile, sleep is critical to the mind. It refreshes the brain, helps with daily functioning, uplifts one's mood and emotional well being, increases productivity, and improves learning and memory. "Good" sleep can lower the probability of contracting the following: heart disease, kidney disease, high blood pressure, diabetes, and stroke.

1.1.3 Devices and Specifications

Heart Rate monitor:

Uses Bluetooth or ANT+ to connect to smartphone

Smartphone:

Needs to be running Android 4.3+

Needs to have radio supporting Bluetooth 4.0+

1.2 Solution

It has been well documented that exercise and sleep both hold a significant impact on heart rate[14-15]. However from experience, we believe that the link between exercise and sleep and heart rate holds true for the converse as well. One of the targets of a good workout is an increased heart rate. On the other hand, high-quality sleep entails a decreasing heart rate.

Our proposed solution is designed to affect people's health by providing limited control to their heart rates. Our Musical Heart Rate Adjuster is targeted to operate in two areas where it can be the most effective - workouts and sleep - which in turn offer the aforementioned health benefits. We do not plan on adjusting heart rate with the intent of skipping the rigors of exercise or the process of falling asleep; on the contrary, we wish to adjust

heart rate to induce better quality workouts and sleep.

Our plan is composed of a few steps. First, we intend to increase the effectiveness of workouts by matching heart rate to an appropriate selection and tempo of music. This music can be adjusted accordingly to stimulate heart rates to reach a desired intensity of exercise. The music, which will be discussed later, performs the task of simulating workout difficulty. As an added benefit, studies have shown exercising while listening to music to provide many benefits, such as increased motivation and endurance, distraction from otherwise unbearable stress, and increased heart rate, among others.

Then, we seek to improve the quality of sleep by finding soothing music to gradually slow down a user's heart rate. In this instance, we use music as an instrument to aid users in falling asleep more quickly, and hopefully improve the performance of their rest. Listening to right music can also improve the quality of sleep; for instance, music by classical composer Mozart has been shown to increase health factors such as relaxation and mental stimulation.

1.2.1 Music

We utilize music to affect heart rate in two ways. In addition to identifying and playing music with speeds in the same vicinity as heartbeat, we also wish to be able to adjust the tempo of the music. A simple compound microscope has both a coarse adjustment knob as well as a fine adjustment knob. Our song library will organize songs into different categories, acting as a coarse adjuster for heart rates. Meanwhile, to add a little fine-tuning to adjust the heart rates, we will either write or find an existing application for an audio tempo changer. Given current heart rate, and subsequently, current music tempo, we will continually adjust the music tempo while measuring for changes in heart rate. This will occur until we hit the specified target heart rate, give or take a few BPM. Thus, if there is no difference in heart rate, either the targeted heart rate has been reached - otherwise, the music tempo has not been adjusted enough.

We are interested in analyzing the magnitude of the effect of our music application on heart rate and finding a rough correlation based on the data that the MOTOACTV provides. All parties should remember, however, that correlation is not causation. While we take the assumption that the general public will react to music in similar ways (music with a slower tempo will decrease heart rate while music with a higher tempo will increase heart rate), it is difficult to know how every individual will react to the same music and can never be 100 percent accurate.

This will probably take some experimentation with test subjects in several situations such as rest, running, weight-lifting, and playing basketball. Time-permitting, we will also

find the ability of music to slow down heart rate and affect sleep by analyzing sleep monitor graphs. As a side experiment, we could measure the effect of several well-known classical songs on sleep quality.

Finally, we will be able to develop an algorithm for ranking the songs that induce the best performance. Even better, we could potentially toy around with machine learning to have our algorithm improve after more and more data sets. With the application of machine learning, each user's individual MOTOACTV device may correct itself in the case that a specific user does not follow the general trend as stated previously (a user's heart rate might increase from slow music rather than fast music). This way, our MOTOACTV will be able to increase both exercise and sleep performance through our own custom music player application, located on and loaded by the device. This application will utilize the user's music library stored locally on the device's memory.

1.2.2 Database

Users will want to monitor their personal health status, so our project will allow the user to view his workout data directly on his phone. This eliminates the inconvenience of having the user log in to a personal account on a website to view his data, because everything he needs will be on the phone itself. All the data collected from the workout will be stored locally on the phone, and the system will perform the necessary database calls to retrieve that data. That data will be processed and formatted into different graphs that will display the correlation between music and heart rate.

1.2.3 System Architecture Diagram

This diagram highlights our system architecture: Our heart rate monitor senses the user's BPM and transmits the data to the Android phone via Bluetooth as requested by the app. The phone then uploads the data to the server and database which processes the data. The system is then able to select the appropriate songs, and then display suitable graphs once the workout is completed.



Heart Rate Monitor 1



Phone/Android App 1



Computer/Webpage



Server/Database

Figure 1.1: System design

1.2.4 Product Usage

- The heart rate monitor should only be worn while it is in use - only while the user is exercising. While it is safe to wear the heart rate monitor during other times, there will be no benefit unless the application is currently running.

- Users may choose to use the Musical Heart Rate Adjuster while not sleeping or exercising if they wish to adjust their heart rate for alternate reasons (possibly for playing video games or preparing for an exam).
- The user will run the android application, and then input a target heart rate. The software will then choose a song based on your current heart rate and begin to either raise or lower it. Once the target heart rate is obtained within a certain tolerance, the software will work to maintain this heart rate rather than increasing/decreasing it.
- Music will be selected from the user's own personal music library (which should be stored on the flash memory of the Android device) to either increase or decrease the user's heart-rate. Music will be played by our software.
- The software will select and play music according to the user's current heart rate in real-time as it receives information from the connected heart rate monitor.
- Music will be delivered through the headphone jack on the Android device or through any bluetooth device.
- Receive information on the songs that are listened to in relation to their usage of the Android device. (What songs were listened to, which songs were the most effective at changing their heart rate, etc.)

1.2.5 Product Ownership (tentative)

Our team will be divided into three smaller sub-teams of two individuals each, the pairings listed below. Each sub-team will be responsible for music, hardware, or web and provide a brief description of their work on a shared Google drive folder. They will also include the necessary UML diagrams and charts. Every week (or bi-week) we will meet together for 1-3 hours during the timeframe determined by When2meet. During the meeting, we will have a specific agenda that primarily involves the week's progress and upcoming deliverable. Our discussion will probably be centered along the following questions: 1) What did you work on this past week? 2) What do you plan on working on next week? 3) Are there any changes that need to be made to the project? Every week, a different team member will take the lead for the next deliverable to ensure that everything is on time.

- Nikhil and Samani will develop a system to select or modify a track based on requested BPM. If possible they will incorporate machine learning into the system.
- Jonathan and Kenny will design the website converts data into useful graphs for users to view and evaluate. They will also work on a database that receives, stores, and processes the data from the MOTOACTV, before sending it to the website.

- Revan and Tae-min will program the Android application and work on interfacing with the heart rate monitor.

1.3 Glossary of Terms

Electrocardiography (ECG) ECG is an interpretation of the electrical activity of the heart over a period of time as measured across the thorax or chest. This interpretation is produced by attaching electrodes to the surface of the skin. This is generally used to measure the heart's electrical conduction system by picking up electrical impulses generated by the polarization and depolarization of cardiac tissue.

Beats per Minute (BPM) BPM is the amount of times that the heart beats given one minute of time.

Resting Heart Rate The resting heart rate is the heart rate measured while the subject is both awake and inactive, not having performed physical activity prior. This resting heart rate, measured in bpm, is the initial value that the user should have before using our device to raise or lower their heart rate.

Database Databases are a place to store information. In our case, this is where we will store and process important data received from our health devices, allowing our system to simply act as a pleasant interface for the user.

Target Heart Rate The target heart rate is the heart rate which the user wishes to achieve. This will be lower than the recorded resting heart rate if the user is attempting to sleep, and higher than the recorded resting heart rate if the user is planning to work out. The user's maximum heart rate is based on how old the user is (220 minus the user's age), and the recommended target heart rate while exercising is between 50 and 85 percent, depending on how active the user normally is. While sleeping, people's heart rates generally drop approximately 8 percent from their resting heart rate, so the user's target heart rate should be approximately $[(\text{heart rate before sleeping}) \times 0.92]$

Smartphone Smartphones are mobile phones which contain features that are more advanced than basic mobile phones. In our case, any Android device which has the capability to use Bluetooth will suffice to interact with the sensors which will be put on the body.

Heart Rate Monitor A device which is able to monitor the user's heart rate. In our experiment we will be using a third party heart rate monitor (worn as a chest strap) which has sensors that are connected to the skin along with the MOTOACTV watch. The chest strap will record the heart rate while the watch will display the user's current heart rate in real time.

2 System Requirements

Based upon our consumer needs, we derived a list of requirements for our system to possess. For features that must be implemented by the system, we state that "The user shall," whereas for features that are preferred, but not "mandatory," we state that "The user should." For each requirement, we assign an identifier in the form of REQ-x, as well as a priority weight from 1 to 5. A higher priority weight indicates that the corresponding requirement is more essential to the success of the project, and more critical to fulfilling the customer's needs.

2.1 Functional Requirements

Identifier	Priority	Description
REQ-1	5	The system shall log user BPM data using the Heart Rate Monitor sensor during active periods.
REQ-2	4	The system shall allow user to select a target heart rate on the Android application.
REQ-3	3	The system shall determine a song to play based on whether the target heart rate is greater than or less than the resting heart rate.
REQ-4	5	The system shall play the designated song through either headphones or Bluetooth speakers to adjust user heart rate.
REQ-5	3	The system shall store the BPM data of each song in the database.
REQ-6	2	The system shall at the very least, output graphs relating BPM versus song speed.

REQ-7	1	The system should adjust the tempo of the song to attempt to match the user's BPM and stop when within a defined range.
REQ-8	1	The system should allow the user some control when they use the "Display Statistics" feature. That is, they should be able to customize the details of how the data is displayed (type of graph or specific categories of data).
REQ-9	1	The system should rank the songs that induce the best performance and use machine learning to improve the song selection algorithm.
REQ-10	1	The user should be able to change the current song if he is unsatisfied with it.
REQ-11	1	The user should be able to view his current heart rate as long as the chest strap is recording that information.
REQ-12	1	The user should be able to pause the current track if he needs to interrupt his activity for some reason

Our functional requirements spell out the behavior of our system and reaction to user input. Our system is composed of several aspects such as the heart rate monitor, android device, server and database. These requirements describe some of the interactions between these components and the effects that the system as a whole produces. The images in the appearance requirements section later on provide more insight on the requirements and functionality of our system.

For our system to be able to accomplish any of its goals, it must first be able to record the relevant BPM data. Therefore, our REQ-1 is of utmost important. There is, however, an important scenario we must consider. If the the heart rate sensor is removed (accidentally or intentionally) while the user is active, any later data collected and song played may be skewed. Thus, the time in between active periods is irrelevant and will have no effect on the software.

In regards to music playback, it is desirable for our system to do the data processing and song section, to reduce the burden on the user. Again, after collecting the BPM data and storing it in our database, our system will use a pre-determined algorithm to analyze song tempo and bpm correlation to determine song selection (REQ-3 & REQ-5). As for physical playback, the choice of whether to use headphones or speakers will not have any effect on the performance of the system. The choice is simply the user's preference (REQ-4).

To safeguard against mistakes, and prevent negative side-effects, if the system makes an incorrect decision, there will be no negative consequences on the user's health. It should be able to re-adjust once it realizes that the song's tempo does not match the user's current and target heart rates (REQ-7). For REQ-9, this ranking system will be completely local and only relevant to the user of the system. This is just an optional improvement to our system to enhance the user's experience.

2.2 Non-Functional Requirements

Requirement	Priority Weight	Description
REQ-13	5	The Android interface shall have a minimal number of navigation menus; the user should not need more than three taps to find the information he needs
REQ-14	5	The user shall not be able to directly modify any data in the database. All data must be programmatically gathered and processed
REQ-15	3	The user should wear the device only when the user wishes to alter their heart-rate; the device will not provide useful information if it is worn when the user does not plan to increase or decrease their heart-rate.
REQ-16	3	The Android application should be intuitive and simple to use.

Meanwhile, our non-functional requirements are more descriptive than practical, listing the qualities of our system. These requirements are based on the term FURPS+, which includes functionality, usability, reliability, and performance.

2.3 On-Screen Appearance Requirements

This section contains mockups of the Android application's user interface. Although the arrangement and display is subject to change, these images contain all the essential information that needs to be conveyed to the user, as well as all the necessary inputs.

The inputs used while exercising, such as the BPM sliders and the music controls, take up a large amount of screen space to facilitate active use. Information display, such as the current track and BPM, is placed unobtrusively around the input methods. The configu-

ration settings are hidden in a drop-down menu, as per the Android design standard.



Figure 2.1: The main screen of the app provides a menu button, selectors for Target Peak and Resting BPM, a display of the current track, a display of the current BPM, and the option to Play/Pause and Skip the current track.



Figure 2.2: Pressing the “Raise/Lower” button toggles between attempting to raise or lower the BPM.



Figure 2.3: Pressing the menu button opens the context menu, providing the option to view statistics, edit settings, and view information about the app.



Figure 2.4: Selecting the Statistics option from the context menu displays a graph of user heart rate and song transitions.



Figure 2.5: The settings page allows the user to open a menu to Log in, to edit the location of the media library (this is done via the OS's directory selection), and configure additional parameters such as music generation (if there is time to implement this feature).



Figure 2.6: Selecting the Log in option prompts the user for their credentials.



Figure 2.7: Selecting the About option from the context menu provides a description of the application.

2.4 Organization

2.4.1 Stakeholders

Stakeholders include individuals and organizations which are interested in the completion and use of a given product. The amount of stakeholders and different types of stakeholders relies on the versatility and ease-of-use of the product in question. Due to this software's very simple interface and design, stakeholders may include users of all ages and multiple types of organizations who are interested in obtaining easier sleep or a more energetic workout. Examples of potential stakeholders include:

1. Individuals who are interested in maintaining their health personally without out-

side help. With the many functions of the application, users have the capability of maintaining their health without the need to consult other people. People who are introverts or do not have easy access to another person who is able to easily analyze the individual's personal health would be very interested in this application. After running this application through their workout or sleep, users can easily consult the graphs which are produced rather than consulting a personal trainer or doctor about their health.

2. Organizations that specialize in helping people fall asleep. Rather than having to prescribe pills to every customer who has trouble sleeping, they will have the option to suggest this product to the customer for minor cases. While prescribing pills may tend to have slightly more dangerous side-effects, our product does not introduce any chemicals to the body which may potentially cause harm to the consumer. Organizations who are interested in a cleaner alternative to help people with their sleeping problems would be stakeholders for this product.
3. Organizations that specialize in promoting exercise and personal health. Not only does this product help those who are trying to sleep, but also those who wish to be more fit. While personal trainers may know how to help the customers and be great motivators, organizations may be interested in helping a larger pool of customers without having to increase the amount of hands that they have working. With this product organizations may grant customers the option of being self-sufficient, helping to increase self-esteem, as well as a great motivator as the application works to increase the user's heart rate allowing them to push onward and burn calories easily.
4. Organizations interested in monitoring and researching people's health. While there are many users who are able to use the product's graphs and understand how their health and workout are, there are many users who still prefer the assistance of outside sources. This product may also be used by these outside sources to help them collect extra data on an individual's health. Rather than having the customer come to their location and run a couple tests in a single day, the organization will have the ability to provide this product to the customer and collect more regular data to understand the customer's day-to-day life rather than a couple of tests run at their office.

More specifically, this product may see stakeholders in:

- Personal Trainers
- Athletes
- Coaches
- Doctors

- Researchers
- Pharmacies
- Therapists
- General population

2.4.2 Actors and Goals

Actors can be defined as are people or devices that will directly interact with the product, and can also be loosely labeled as either "initiators" or "participators". These actors will have a specific goal with the given product, which is what the actors are attempting to achieve by interacting with the system. Actors and their respective goals are:

<i>Actor</i>	<i>Actor's Goal</i>
User(initiator)	To increase heart rate for exercising
User(initiator)	To decrease heart rate for sleeping
User(initiator)	To analyze health information from given graphs
Chest strap (participator)	To monitor the user's heart rate

This product is one which only requires the interaction of one human actor, the user of the product. While there is the potential for other humans to interact with the user's health information which is produced, only the user himself is considered an actor. The headband and chest strap are participating actors that are worn by the user to monitor information and relay the information via Bluetooth back to the smartphone which is running the application.

2.5 Use Cases

Use Cases are specific tasks that are created together by the designer and the client to simulate what the client wants out of his software solution. They are meant to describe the main features of the project such that the designer can easily address the needs of the client and create a product around those needs. Below is a casual description of the use cases for the reader to get a general idea of how the software should be used. Later, fully described use cases are shown for additional insight into the different cases.

2.5.1 Casual Description of Use Cases

Use Case	Action	Description
UC-1	logData	The system will log heart rate and music metadata.
UC-2	setTarget-HeartRate	The user can change the heart rate that the system is targeting.
UC-3	skipSong	The user can elect to skip the current song. The system will begin playing a different song.
UC-4	toggle-Playback	The user can toggle the system between playing and not playing music.
UC-5	displayStatistics	The user can request the statistics about the current workout. This can be performed while the workout is in progress or after the workout has been completed.
UC-6	getHeartRate	The user can view his current heart rate. This can be used when the user does not want to see all of the statistics from the workout and just wants his heart rate.
UC-7	provide-MusicData	

2.5.2 Traceability Matrix

The Traceability Matrix allows the reader to cross the functional and non-functional requirements described earlier with the use cases. This demonstrates which use cases fulfill each requirement, and the total priority weight of each use case will determine which cases are the most important. If an X is present at any point in the the column for a Use Case, then the corresponding requirement's priority weight must be added to the sum. The remaining Xs in the column are similarly considered, and the total priority weight for the Use Case is listed at the bottom of the column.

	Pri- ority Weight	UC-1	UC-2	UC-3	UC-4	UC-5	UC-6	UC-7
REQ-1	5	X			X	X	X	
REQ-2	4	X	X					
REQ-3	3	X	X	X				
REQ-4	5	X		X				
REQ-5	3	X				X		
REQ-6	2					X		
REQ-7	1	X	X	X				
REQ-8	1					X		
REQ-9	1					X		
REQ-10	1			X				
REQ-11	1						X	
REQ-12	1				X			
REQ-13	5	X	X	X	X	X	X	
REQ-14	5	X	X			X		
REQ-15	3	X	X	X	X	X	X	
REQ-16	3	X	X	X	X	X	X	
Total Weight		37	37	21	17	25	19	

2.5.3 Fully-Dressed Description of Use Cases

Use Case UC-1: increaseHeartRate
<p>Related Requirements: REQ-1, REQ-2, REQ-3, REQ-4, REQ-5, REQ-7, REQ-13, REQ-14, REQ-15, REQ-16</p> <p>Initiating Actor: User</p> <p>Actor's Goal: To enter a target heart rate and begin the workout</p> <p>Preconditions:</p> <ul style="list-style-type: none">• The system displays the selection menu for heart rate <p>Postconditions:</p> <ul style="list-style-type: none">• The system starts recording the heart rate of the user and the data from the workout if not already recording.• The system uses the recorded heart rate to run the music selection algorithm <p>Flow of Events for Main Success Scenario:</p> <ul style="list-style-type: none">• → User enters the target heart rate into the application.• ← Chest strap retrieves current heart rate and stores it in the database• → User presses the start button• ← Timer initiates a five-second countdown until the start of the exercise.• ← Timer initiates another 20 second countdown to detect whether the user has started exercising. If the heart rate has not significantly changed within that time, an error will be displayed and the system will display the home screen.• ← If the heart rate does change significantly, then the user should continue exercising.• ← Music selector uses music algorithm to play appropriate music.• ← Database begins recording data about the workout and stores it in the database.

This is one of the main use cases for the software. It allows the user to increase his heart rate to the proper level according to the data that he inputs. Specifically, the user will initiate the process by entering the target heart rate for his exercise. The Mobile Interface will request the current heart rate from the Chest Strap, then store that number in the Database. Once the Database has this data, it will signal the Music Selector to initiate the music selection algorithm. As the algorithm is running, the Chest Strap will store data about the workout, notably heart rate over time and song playing records, in the Database. If the user is exercising at a heart rate above the target, the Music Selector will attempt to maintain this heart rate. Incorrect number entry is impossible due to the slider selector UI element.

Use Case UC-2: setTargetHeartRate

Related Requirements: REQ-2, REQ-3, REQ-7, REQ-13, REQ-14, REQ-15, REQ-16

Initiating Actor: User

Actor's Goal: To change the heart rate that the system is targeting

Preconditions:

- The system displays the selection menu for heart rate

Postconditions:

- The system updates the target heart rate used for music selection

Flow of Events for Main Success Scenario:

→ User selects “Raise” option on main UI

→ System sets current value of “Raise” selector as current target

OR

→ User selects “Lower” option on main UI

→ System sets current value of “Lower” selector as current target

OR

→ User modifies current selector value on main UI

→ System sets new value of selector as current target

In this use case, the user can modify the heart rate targeted by the music selection algorithm. This can be achieved by modifying one of the UI selectors, or by toggling the direction (raise or lower). For this reason, this could be split into several use cases, but since the functionality is the same we consolidate into one.

Use Case UC-3: getNextSong

Related Requirements: REQ-3, REQ-4, REQ-7, REQ-10, REQ-13, REQ-16

Initiating Actor: User

Actor's Goal: To play a different song

Preconditions:

- The system is currently playing music.

Postconditions:

- A different song is being played at the same rate at which the previous song was playing

Flow of Events for Main Success Scenario:

- → User selects the "Next Song" button.
- → Mobile interface requests the next song from the Music Selector
- Music Selector retrieves next track from file system while maintaining the current rate of workout.
- → Music Selector passes the new song to the Music Player
- ← Music Player begins playing next track

The getNextSong case is one of the conveniences for the user. If the user does not like the song he is currently listening to, he can select a button on the Android device to advance to the next song. The Mobile Interface will request a different song from the Music Selector. The Music Selector will choose a song that will be adjusted to match the path that the algorithm has set out to reach the target heart rate. The songs will be selected from the user's music library which has already been loaded onto the device. In the case that the device does not contain another song which matches the current song's bpm/tempo to switch to, the device will select a song from the next highest/lowest level to reach the target heart rate (a faster song if heart rate is to be increased, a slower song if heart rate is to be decreased). Although the song may be out of range for the user's current heart rate, there will be no negative effects of using a song which is only slightly lower or slightly higher. The device will not choose a song that is very far out of the current range.

Use Case UC-4: pausePlayback

Related Requirements: REQ-1, REQ-12, REQ-13, REQ-16

Initiating Actor: User

Actor's Goal: Pause the playback of music

Preconditions:

- The system is playing music

Postconditions:

- The system stops recording the heart rate of the user and the data from the workout.

Flow of Events for Main Success Scenario:

- → User selects "Pause" option on mobile interface.
- → Mobile interface tells the Music Selector to hold its current state and the Music Player to stop playing music.
- ← Mobile interface displays a play button for so that the user can resume the workout.

The pausePlayback case is another straightforward, convenience-based use case. If the user needs to interrupt the workout for some reason and needs to stop the music, then all he has to do is press the pause button on the device. To resume the music, he must press the button again. The system will make sure that this function is working properly. If no music is currently being played, it is considered to be paused and may be resumed. If music is being played, it is considered to be resumed and may be paused. The system will know whether music is playing or not. The heart rate shall also be paused/resumed as the music is. If it is not already recording, and should be, it will start recording (refer to postconditions for UC1, UC2).

Use Case UC-5: getStatistics

Related Requirements: REQ-1, REQ-5, REQ-6, REQ-8, REQ-9, REQ-13, REQ-14, REQ-16

Initiating Actor: User

Actor's Goal: Return statistics about the user's workout.

Preconditions:

- The system is no longer playing music.

Postconditions:

- The application displays the graphs of the user's heart rate versus time, along with other metrics.

Flow of Events for Main Success Scenario:

- → User selects the "Display Statistics" option.
- → Mobile interface requests the appropriate data from the Database.
- → Database then passes the data to the Statistics Generator, which organizes the data for presentation.
- ← The Statistics Generator passes the organized data back to the Mobile Interface.
- ← Mobile Interface displays the graphs to the user.


The getStatistics use case is important because it allows the user to see the results of his workout once he is done. The user initiates the action by selecting the "Display Statistics" option in the UI, which causes the system to retrieve all the data for the current workout from the database. The database retrieves the data that the user selected on the main screen and passes that data to the Statistics Generator. The Statistics Generator creates graphs that track different metrics, such as the music track that produced the best results over time, and passes the graphs and tables back to the Mobile Interface. Finally, the Mobile Interface displays the requested graphs and tables to the user. Time-permitting, the system can be developed to allow the Display Statistics functionality to be available during the workout. The getStatistics function is relatively simple; the user will be presented with a button that he can press to retrieve the statistics. He will then be presented with a menu

that asks him which statistics he would like to see. The Mobile Interface will check for invalid values that the user might enter and are not directly related to the statistics options that are presented. If an invalid option is selected, the Mobile Interface will reset the display and ask the user to enter correct values. Possible statistics that could be displayed are the frequency with which a certain song is played, which indicates a song that makes the user especially productive. A graph might show the user how fast his heart rate approaches the target heart rate over the duration of his workout.

Use Case UC-6: getHeartRate
<p>Related Requirements: REQ-1, REQ-11, REQ-13, REQ-15, REQ-16</p> <p>Initiating Actor: User</p> <p>Actor's Goal: View the current heart rate.</p> <p>Preconditions:</p> <ul style="list-style-type: none"> • The device should already be monitoring the user's heart rate. <p>Postconditions:</p> <ul style="list-style-type: none"> • The current heart rate is displayed on the screen of the Android application. <p>Flow of Events for Main Success Scenario:</p> <ul style="list-style-type: none"> → Mobile Interface requests current heart rate from chest strap. ← Chest Strap returns the current value of the heart rate. ← Mobile Interface displays the heart rate to the user.


The getHeartRate case is similar to the getStatistics case, but it allows the user to see only his current heart rate. The full analysis provided by getStatistics may not be necessary at times, and this case allows the user to easily see his heart rate during the exercise. Once a second, the system requests the current heart rate from the chest strap. The chest strap then returns the heart rate, and the User Interface displays to the screen. For this function to work, the chest strap must be strapped firmly to the chest in the region of the heart. If not, the Chest Strap will be unable to record the current heart rate correctly. Also, the chest strap should not be moved or tampered with in any way while the device is recording the current heart rate. If no data is received from the chest strap, the system will present the user with a message saying that the chest strap is not properly fastened.

2.5.4 Use Case Diagram




2.5.5 System Sequence Diagrams


sd UC-1 increaseHeartRate




sd UC-2 decreaseHeartRate




sd UC-3 getNextSong




sd UC-4 pausePlayback



sd UC-5 getStatistics



sd UC-6 getHeartRate



2.5.6 System Operation Contracts

OC-1: Enter Target Heart-rate

- **Precondition:** No target heart-rate has been entered into the system
- **Postcondition:** The system begins to work its algorithm and plays appropriate music.

OC-2: Select Function("lower")

- **Precondition:** The recorded heart rate is above the resting heart rate.
- **Postcondition:**

- The system starts recording the heart rate of the user and the data from the workout if not already recording.
- The system uses the lower target heart rate as a target for the music selection algorithm.

OC-3: Select Function("Next Song")

- **Precondition:** The device is playing a song which needs to be changed.
- **Postcondition:** A different song is being played at the same rate at which the previous song was playing.

OC-4: Select Function("Pause")

- **Precondition:** The device is currently playing a song.
- **Postcondition:** The system stops recording the heart rate of the user and the data from the workout.

OC-5: Select Function("Display Statistics")

- **Precondition:** The user has either finished his workout or is in the middle of his workout and would like to see his statistics.
- **Postcondition:** The device retrieves the data from the databases, organizes it, and presents it to the user in the form of charts and tables.

OC-6: Select Function("Display Heart Rate")

- **Precondition:** The device should already be monitoring the user's heart rate.
- **Postcondition:** The current heart rate is displayed on the screen of the Android application.

2.5.7 Mathematical Model

The selection of which track to play requires a mathematical model. At its simplest, this consists of selecting the track with the closest BPM, that is to say minimizing the difference in BPM:

$$\min(|target_{BPM} - track_{BPM}|) \quad (2.1)$$

If time permits, this simple model can be replaced with a more complex model incorporating Machine Learning to learn which tracks are more effective than others at changing pulse.

3 User Interface Specification

3.1 Preliminary Design

3.1.1 Use Case UC-2: decreaseHeartRate




Figure 3.1: System design

For the first two use cases, the user's goal is to select a target heart rate for his workout. Because they are essentially two versions of the same task, we only include a single preliminary design of this use case. As seen from the screenshots of our "home" screen above, we seek to minimize user effort in accomplishing his desired goal. 1) To decrease heart rate, a user simply needs to press the "Raise" button to toggle the setting to "Lower." This means that he is now in the correct mode to lower his heart rate. 2) Next, the user must select his target BPM. There are two options: Peak BPM and Resting BPM. The user needs to

swipe upwards or downwards to scroll and select his desired Peak BPM, for the workout, and then choose a more relaxed, Resting BPM.

When finished, the system does the remainder of the work, helping the user to increase or decrease his heart rate, and then indicating the continuous effect in the bottom left corner, allowing the user to monitor his condition. This feedback is also furthered discussed in the `getStatistics` use case later on. (Again, fulfilling use case 1 and increasing heart rate is self-explanatory. The user merely needs to toggle the button back to "Raise" and select his BPM.)

3.1.2 Use Case UC-3: `getNextSong`




Figure 3.2: System design

To switch tracks is also very simple. It takes the user one simple tap to achieve his desired outcome. On the provided image of our concept interface, our application appears very similar to a mainstream music player. In the bottom right corner is the double-arrowed fast forward button. The user taps this button to advance to another song, and then the system fulfills that request by running its algorithm and picking out another track from

the user's music library. The "Current Track:" label will also be updated accordingly, and possibly even the cover art of the album.

3.1.3 Use Case UC-4: `pausePlayback`




Figure 3.3: System design

Use Case 4, `pausePlayback` also proves to be extremely intuitive. Just like most music players, our application has a button located on the bottom center of the screen designed for the purpose of pausing the current song, or playing it, depending on the current state. The user just needs a single tap on the universal play/pause button to achieve his goal of pausing the song. When this is done, the system responds by stopping its collection of heart rate data, and freezing the screen in its current state. (This would be readily updated upon playback.)

3.1.4 Use Case UC-5: getStatistics




Figure 3.4: System design

For use case 5, the user desires to view the statistics of his workout. To simplify the process for the user down to two clicks, we added a menu button in the top right corner of the screen. After pressing that menu button, a scroll-down menu with three options appears. The user needs to tap "Selections" to bring up his workout information. The system is constantly logging the user data, and compiles a few useful graphs such as heart rate versus time. Other different metrics may also be selected, allowing the user instant access to data that can help him improve his workout.

We omit use case 6 in our preliminary design because we feel that it is self-explanatory. The user may tap the BPM square in the lower left corner to update his BPM, but most likely, the BPM will be updated in real time. In that case, the user simply needs to look at the screen to view his current BPM.

3.2 Effort Estimation

First we need to calculate the Use Case Points (UCP).

$$UCP = UUCP * TCF * ECF \quad (3.1)$$

Where Unadjusted Use Case Points (UUCPs) are computed as a sum of these two components:

1. The Unadjusted Actor Weight (UAW), based on the combined complexity of all the actors in all the use cases.
2. The Unadjusted use Case Weight (UUCW), based on the total number of activities (or steps) contained in all the use case scenarios.

Unadjusted Actor Weight (UAW) and Unadjusted Use Case Weight (UUCW)

Actor	Complexity	Weight
Users	Complex	3
Mobile App	Average	2

$$UAW = 3 + 2 = 5 \quad (3.2)$$

Now we reference the Use Case table from 2.5.1 to calculate the UUCW.

$$UUCW = 15 + 15 + 8 + 10 + 12 + 18 = 78 \quad (3.3)$$

There the UUCP is:

$$UUCP = 5 + 78 = 83 \quad (3.4)$$

Technical Complexity Factor (TCF)-Nonfunctional Requirements

Below is a table of Technical complexity factors and their weights.

Technical Factor	Description	Weight	Perceived Complexity	Calculated Factor
T1	Friendly interface that the user understands	2	1	2
T2	Internal processing of heart beat data to music and adjusting BPM shouldn't be too complex	2	3	6
T3	Good Performance	1	2	2
T4	Security is a minor concern	1	2	2
T5	No direct access to third parties	2	3	6
T6	Ease of use is very important	3	3	9
	Technical Factor Total (TFT)			27

And $TCF = C1 + C2 \times TFT$, and $C1 = 0.6, C2 = 0.01$, so

$$TCF = 0.6 + 0.01 * 27 = 0.87 \quad (3.5)$$

Environment Complexity Factor (ECF)

The environmental factors measure the experience level of the people on the project and the stability of the project.

Environmental Factor	Description	Weight	Perceived Impact	Calculated Factor
E1	Mostly beginners at UML based development	1.5	1	1.5
E2	Decent familiarity with application problem	0.5	3	1.5
E3	Quite knowledgable about the Object-Oriented approach	1.5	3	4.5
E4	Somewhat motivated about the problem	1	2	2
E5	Programming language proficiency	2	3	6
	Environmental Factor Total (EFT)			15.5

Here is the formula to calculate ECF

$$ECF = C1 + C2 * EFT \quad (3.6)$$

Where $C1 = 1.4, C2 = 0.03$. Therefore we calculate the ECF.

$$ECF = 1.4 + (-0.03 * 15) = 0.965 \quad (3.7)$$

So we calculate the final UCP:

$$UCP = 83 * 0.87 * 0.965 = 69.68 \quad (3.8)$$

If we assume that productivity factor is 30 hours per user case point. The effort estimation would be 2,090.

4 Domain Model

4.1 Concept Definitions

Responsibility	Type	Concept
Pairing/communicating with HRM	D	HRM manager
Retrieve logged data	D	log retriever
Musical Playback	D	music playerbacker
Logging tracks as they are played	D	track logger
Queue Next Track(s)	D	track queuer
Listen for user input	D	general UI
Graphically displaying music information	D	playback view
Graphically displaying heart rate info	D	heart beat view
Graphically displaying current workout data	D	workout view
Graphically displaying previous workout data	D	history view
Data store for workout data	K	workout store
Data store for music metadata	K	metadata store
Data store for music files	K	music store

4.2 Association Definitions

Concept Pair	Association Description	Association Name
music playerbacker ↔ metadata store	music playerbacker retrieves information about the current track from metadata store	data retrieval
history view ↔ workout store	history view retrieves data about previous workouts from the workout store	data retrieval
track logger ↔ music playerbacker	tracks played by music playerbacker are logged by track logger	data logging
music playerbacker ↔ track queuer	music playerbacker retrieves the next track from the track queuer	data retrieval
music playerbacker ↔ playback view	playback view displays information based on the data in music playerbacker	human data interface
hrm manager ↔ general UI	general UI pairs and reports hrm status based on hrm manager	human data interface
heart beat view ↔ hrm manager	retrieves and displays heart rate data from the hrm manager	human data interface
log retriever ↔ workout store	log retriever fetches logs from the workout store and barks at the mailman	data logging
music playerbacker ↔ music store	music playerbacker plays songs from the music store	data retrieval

4.3 Attribute Definitions

Concept	Attribute	Attribute Definition
HRM manager	data logging	Data logging has to with the storage or retrieval of logged data or the logging of data.
log retriever		
track logger		
music playerbacker	human data interface	Human data interfaces deal with the interaction between the user and the data.
track queuer		
general UI		
playback view		
heart beat view		
workout view		
history view		
workout store	data storage	Data storage deals with the storage of the data.
metadata store		
music store		

4.4 Tracability Matrix

	HRM manager	log retriever	track logger	music playerbacker	track queuer	general UI	playback view	heart beat view	workout view	history view	workout store	metadata store	music store
UC-1	X			X	X	X	X				X	X	
UC-2	X			X	X	X	X				X	X	
UC-3			X	X	X	X	X					X	X
UC-4	X			X		X	X	X	X		X		
UC-5		X				X				X	X		
UC-6	X					X		X	X		X		

5 Plan of Work

Looking ahead at some of the due dates in the near future, our group will probably be mixing documentation with development during the course of March. Up until now, we have been primarily working on laying the foundations of our project. We have been examining customer and system requirements and extracting specifications from them. We have been envisioning preliminary design as well as analyzing user estimation. We have derived our domain and mathematical models. In the upcoming weeks, we will be working on some UML diagrams to make our lives a lot easier when we begin to code. We will complete the sequence and class diagrams to help us understand exactly which attributes and classes we need to account for. We will also design our system architecture to further our understanding on how each of the components of our system interface and communicate with each other. We will identify any data algorithms or structures needed to store the information generated by the phone and the heart rate monitor. Finally, we will continue to revise our designs and implementations from our previous iteration and construct tests to ensure that our system works as planned. By doing this preliminary design and analysis in conjunction with the upcoming deliverables, we will develop a solid understanding of what pieces of software actually need to be written. We will have a snapshot of our system and hopefully foresee some of the problems that might have occurred had we rushed straight into coding. The included Gantt chart serves as a visual roadmap of our project plan.

5.1 Gantt Chart




Figure 5.1: Pressing the menu button opens the context menu, providing the option to view statistics, edit settings, and view information about the app.

5.2 Product Ownership

Our team will be divided into three smaller sub-teams of two individuals each, the pairings listed below. Each sub-team will be responsible for developing a specific sub-product during the bulk of their time. Upon completion of a significant portion of work, they will provide a brief description of their activity before they push it to our Github repository. In addition to documentation, they will also include the necessary UML diagrams, charts, algorithms, and source code. Every week, or at least once before each deliverable, we will meet together for 1-3 hours during a timeframe determined by a combination of GroupMe and When2meet. During the meeting, we will have a specific agenda that primarily involves the week's progress and upcoming deliverable. Our discussion will probably be centered along the following questions: 1) What did you work on this past week? 2) What do you plan on working on next week? 3) Are there any revisions that need to be made to the project? Every week, a team member will take the lead for the next deliverable to ensure that everything is on time.

- Revan and Tae-Min will work on the general user interface of the mobile application. They will design the layout and basic functionality of the Android app, and set up the communication protocol between the heart rate monitor and the phone.
- Kenny and Samani will work on the music aspect of the mobile application. They will study music playback features such as track selection and queuing to provide

customers with a seamless music player experience. They will also be responsible for the nuances of audio playback such as crossfading transitions and tempo adjustments.

- Jon and Nikhil will work on the data logging faculties that are necessary to provide the user with feedback about his/her workout. They will work with a server that captures heart rate and music data from the phone and possibly directly from the heart rate monitor. They will determine how to process this information on the server and create customizable graphical displays for user's to view.

5.3 Breakdown of Responsibilities

	Past	Present	Future
Jonathan	Problem Statement, Enumerated Functional Requirements, Preliminary Design, References	Plan of Work	Project Management, Interaction Diagrams, Class Diagrams
Kenny	User Effort Estimation	Domain Analysis	System Architecture and System Design
Nikhil	Enumerated Nonfunctional Requirements, Use Cases (Casual Description, Traceability Matrix, Fully-Dressed Description)	System Operation Contracts	Project Management, Interaction Diagrams, Class Diagrams
Revan	On-Screen Appearance Requirements, Use Case Diagrams	Mathematical Model	Class Diagrams, System Architecture and System Design
Samani	System Sequence Diagrams	Domain Analysis	System Architecture and System Design
Tae-min	Glossary of Terms, Stakeholders, Actors, Goals	System Operation Contracts	Algorithms and Data Structures

6 Interaction Diagrams




Figure 6.1: Interaction diagram for the increaseHeartRate case

Since our first two use cases are very similar, we only include the interaction diagram for UC-1, increaseHeartRate. Again, the user toggles the “raise” button from the home screen and scrolls to the desired BPM. The database manager coordinates with the heart rate monitor and uses its own algorithm to determine the appropriate song for the music player

to play for the user. Then, it waits five seconds for the user to begin his workout. Upon playback, the database manager continuously receives the user’s current BPM and makes adjustments to the song’s tempo accordingly.




Figure 6.2: Interaction diagram for `getNextSong()`

For our third use case, the user’s goal is to listen to another song. Similar to the “skip” button on most standard music players, we included a double fast-forward arrow for users’ convenience. When pressed, the controller immediately contacts the database manager. The database manager selects another track based on its song-selection algorithm for the music player to play. (If the user is currently trying to change his/her heart rate, the database manager will take that into count and select a song of a similar speed.) It also returns the cover art and new song title for the mobile interface to display.




Figure 6.3: Interaction diagram for `pausePlayback()`

Our `pausePlayback` sequence is fairly simple. The user initiates the request by tapping the play/pause button. Then the controller informs the database manager to store the current state settings for future use, and the database manager proceeds to stop recording data and allows the music player to stop the song. The mobile display also updates accordingly.




Figure 6.4: Interaction diagram for `getStatistics()`

In UC-5, `getStatistics`, the user begins with two button presses to achieve their goal. First, they bring up the menu button in the top right hand corner and then press “Statistics” from the dropdown. The controller passes this request to the database manager, which quickly retrieves and updates the data. Then, it calculates statistics, creates some graphs, and then returns the output to the controller to display. (Note that the user must select from the options available in order to view his workout history.)




Figure 6.5: Interaction diagram for `getHeartRate()`

UC-6, `getHeartRate` is very similar to UC-5. This use case is also applicable for UC-1, because the Heart Rate is important, needing to be determined continuously. The controller takes the request from the user and passes it to the database manager to handle. The database manager then takes the current BPM value from the Heart Rate Monitor and updates the value for the mobile interface to display to the user.

6.1 Alternate Scenarios




Figure 6.6: Alternate interaction diagram for `getStatistics` without the Statistics Generator Object




Figure 6.7: Alternate interaction diagram for `getStatistics()` using `getGraphs()`




Figure 6.8: Alternate interaction diagram for `getStatistics()` using `calculateStatistics()`

Alternate scenarios could occur mainly during the `getStatistics()` use case. Here, the user can select which particular graphs or data he may want to see. In the original diagram, a dedicated Statistics Generator object was created to handle the organization and creation of all statistics. This object greatly simplifies the `displayStatistics()` case because all the calculations are done outside of the database. However, this is not the only way to solve the case, with the alternative solution being that the statistics are generated directly by the database. Advantages of this are that there is no need to transfer the data between two objects and worry about the communication scheme between them. Also, the time needed to flesh out an entirely new class to handle the calculations would be eliminated. Three different scenarios of keeping the statistics-generation functionality are displayed above. In these diagrams, it is assumed that the user has selected all the options available for `getStatistics()`, and thus all the graphs and statistics available to the database are displayed to the user. This may not always be the case, as some users may prefer to see graphs only, or numbers only. Some users would like to see a certain combination of both. Thus, our alternate scenarios for the `getStatistics()` consist of various combinations of all the different display options. For simplicity, only the cases for displaying only graphs and for displaying only numbers are shown in separate interaction diagrams.

Although keeping the statistics-generation functionality can be contained entirely within the database, we implemented it within a Statistics Generator object. This decision was made to keep consistency with the High Cohesion and Low Coupling Principles. If we hadn't made the separation, then the database would have too many responsibilities to

take care of. By creating a dedicated Statistics Generator object, the statistics can be fully fleshed out and managed without having to worry about other responsibilities.

6.2 Design Patterns

This project was developed through a mainly object-oriented approach. We were able to boil our system down to a few, distinct actors, and an object-oriented approach seemed appropriate to model our system. As evidenced by the interaction diagrams, there are five main actors: the user, the mobile interface, the database, the music player, and the heart rate monitor. Each of these actors has a specific set of actions that they can perform, and these actions are not very tightly coupled to those of other actions in the system. For example, the music player is designated to solely play the music on the device. It does not have access to the music algorithm or the heart rate; its sole job is to respond to requests about playing or pausing the music. Similarly, the database manager is solely responsible for manipulating data and handling requests. These characteristics are prime examples of the High Cohesion principles, because each actor in the system has its own specific tasks, and the respective actors are designed to that their tasks are carried out very well. We acknowledge that some of the actors are more important than the others, such as the database manager and the mobile interface, but this is out of necessity. The user interacts directly with the interface, and the interface talks directly to the database in most cases. The other objects in the system are more supplementary in the sense that they carry out the commands given to them by the database-mobile-interface pair. Although there is some communication between the different objects, the communication has been designed such that each method call is specific, efficient, and effective. This cuts back on unnecessary communication between the objects and allows for the system to be optimized. The Low Coupling Principle requires that objects should “not take on too many communication responsibilities”, and our design fulfills the requirement because we have minimized the number of interactions to just the necessary ones. All in all, our object-oriented design encompasses aspects from both the High Cohesion and Low Coupling principles, and creates an effective solution to the heart rate monitoring problem.

6.3 Assignment of Responsibilities

A prime example can be found in UC-4, `pausePlayback`. Each object submits a request to the next object in line before reaching the Music Player, which is supposed to fulfill the “pause” function. At this point, the interactions start coming back. It is clearly seen that each object in this example transmits at most two messages, and no object performs more than a single computation. A similar theme exists in UC-6, `getHeartRate`. Each object essentially sends one message and receives one message. Furthermore, each object does not need to fulfill more than two active responsibilities. We believed that by distributing

the workload for each object through the High Cohesion Principle and the Low Coupling Principle, we would be reaching the best balance. The Expert Doer Principle was not followed as closely because the communication links of the objects we used are a bit longer. In our design, the “one who knows” often passes on the knowledge to another object that “needs to know” before the task is actually fulfilled. For instance, the Database Manager often causes the Controller to update the display and show the user rather than directly communicating with the user. Basically, our Controller and Database Manager are both extremely important, so oftentimes, they both end up with most of the implementation details.

7 Class Diagram and Interface Specification

7.1 Class Diagram

7.1.1 Class Diagram for Data Management




Figure 7.1: Class relationship for managing data

7.2 Data Types and Operation Signatures

Data Manager
<p>Variables:</p> <ul style="list-style-type: none">• workoutData: Data Assembler. This is a Data Assembler object which stores the data points retrieved from storage. It also stores the songs and their metadata.• workoutGraphs : Graph Container. This is a Graph Container object which stores the different graphs that were requested by the User Interface.
<p>Functions:</p> <ul style="list-style-type: none">• storeInitialState(double initialRate, double targetRate) : bool. This function stores the initial state of the system, which is captured in the form of the user's initial heart rate and the target heart rate.• storeCurrentTrack(string song) : bool. This function is used by the Music Module to store the current track being played. This information is later used for the playlist.• storeCurrentHR(double heartRate) : bool. This function is used to store the current heart rate into the data storage. It is used by the User Interface while the user is working out with the system.• getArtistVsBPM() : graph. This function will access the data stored in the Data Assembler and create a histogram displaying the artist who's songs were played most often at different BPMs. The Data Manager will select the appropriate graph from the Graph Container and return it to the UI.• getGenreVsBPM() : graph. This function will create a histogram of the most frequent genres at different BPMs. The data will be accessed from the Data Assembler and plotted by the Graph Container. The final graph will be selected by the Data Manager from the Graph Container• getTempoVsBPM() : graph. This function will return a graph of the music's tempo versus the user's BPM.• getHRvsTime() : graph. This function will return a graph of the user's heart rate over time.• getPlaylist(): string array. This function will return an array of the music that was played during the workout.• storeCurrentTime() : bool. This is an auxiliary function which stores the current system time in the data storage every time storeCurrentHR() is called. It will associate the time with the current heart rate.

Data Assembler

Variables:

- playlist: string array. This variable will store the names of the songs that were played during the workout.
- heartRates: Ordered Pair array. This variable will store the retrieved data points in ascending order.

Functions:

- createPlaylist() : string array. This function will fetch the songs played during the workout from the data storage and arrange them in the playlist array and return it.
- calcHRchange() : orderedPair. This function will retrieve all the heart rates and system times from the data storage and organize them into ordered pairs. The ordered pairs are stored in an array and returned to the caller.
- retrieveHR() : double. This function retrieves a heart rate from the data storage.
- retrieveTime() : double. This function retrieves a time from the data storage.
- retrieveSong() : string. This function retrieves a song name from data storage.

Graph Container
<p>Variables:</p> <ul style="list-style-type: none"> • graphs : graph array. This variable contains an array of the different graphs that were requested by the User Interface.
<p>Functions:</p> <ul style="list-style-type: none"> • createArtistVsBPM(Data Assembler workoutData) : bool. This function takes the names of the artists and heart rates stored in the Data Assembler and graphs them against each other. • createGenreVsBPM(Data Assembler workoutData) : bool. This function graphs the genre of the music versus the user's heart rate using the data from workoutData. • createTempoVsBPM(Data Assembler workoutData) : bool. This function graphs the tempo of the music versus the user's heart rate using the workoutData object. • createHRVsTime(Data Assembler workoutData) : bool. This function graphs the user's heart rate versus time using the workoutData object.

Ordered Pair
<p>Variables:</p> <ul style="list-style-type: none"> • x : double. This variable stores the x-coordinate of the data point. • y : double. This variable stores the y-coordinate of the data point.
<p>Functions:</p> <ul style="list-style-type: none"> • setX(double newX) : bool. This function sets the value of the variable x. • getX() : double. This function returns the current value of the variable x. • setY(double newY) : bool. This function sets the value of the variable y. • getY() : double. This function returns the current value of the variable y.

7.3 Traceability Matrix

<i>Domain Concepts</i>	<i>Class</i>			
	Data Manager	Data Assembler	Graph Container	Ordered Pair
HRM Manager	X			
Log Retriever	X			
Track Logger	X			
Music Playerbacker	X			
Track Queuer	X	X		
General UI	X	X		
Playback View	X	X	X	
Heart Beat View	X	X	X	
Workout View	X	X	X	
History View	X	X	X	
Workout Store	X	X		X
Metadata Store	X	X		X
Music Store	X	X		X

From our domain concepts, we derived four classes: data manager, data assembler, graph container, and ordered pair. Our data manager is essentially involved with every domain. Its purpose is to log and manage various types of data, and store the packaged data other objects to retrieve. Essentially, the data manger acts as an intermediary in most steps, but only providing a minimal interface for modules so that data cannot be tampered with or seen, just used.

Next, our data assembler is charged with retrieving the appropriate data from the database and packaging it in a convenient form for usage. For instance, we can take songs and metadata from their storage locations and return playlists. We can also take our data and create ordered pairs for our graph container. Then, our graph container contains an array of the requested graphs, and it is involved with the domain concepts that require various views. Using our data assembler allows us to have a nice container of data to graph. Finally, our ordered pair class was derived from the storage concepts. We use it to store data points, so that we will be able to access them.

8 System Architecture and System Design

8.1 Architectural Styles

Our system utilizes a three-tier architecture system and consists of 3 layers. These include a presentation tier, an application tier, and a data tier. Our presentation layer is primarily represented by our mobile interface which is used to display our application’s relevant information. It also allows the user to interact with our system by inputting commands and accepting outputs. Meanwhile, our application layer consists of logical operations and data access. For example, our song-selection algorithm would be included in this layer. This application layer uses logical operations to convert raw user data into readable results. Finally, our data tier consists of our database where our information is stored and retrieved.

These three tiers are separated from each other to allow for encapsulation and data abstraction. We want each tier to hide its usage from implementation and to preserve the integrity of our data. We also want to reduce the overall complexity of our system. However, each tier must maintain a sufficient level of communication and be able to retrieve needed data from each other. In a common scenario for our system, our application layer may request information from the data tier. It then processes this information and returns it to the presentation tier in response to the user request. A visual diagram was provided in our earlier stage of planning in the section titled System Architecture Diagram.

8.2 Identifying Subsystems

8.3 Mapping Subsystems to Hardware

8.4 Persistent Data Storage

Since Android provides full support for SQLite databases, it is the type of storage that we have chosen for the application. The wide variety of fully-developed features allows us to focus more on the actual organization and management of the data in relation to the other modules. All that is needed is a simple call to the data base to retrieve the raw data, and the custom designed objects illustrated in the Class Diagram then do their own

processing on the data. SQLite allows us to store all the data specific to application on the device itself, which is advantageous for a mobile application such as ours. The goal is for the user to be able to record and view his workout data without having to use any external devices other than his phone and the chest strap, and internal data storage via the SQLite database allows our application this benefit. The database will be accessible only to the Data Manager and the Data Assembler. In regards to the Data Manager, the only interactions with the database will be to store the initial state of the system, store the current music track, and store the current heart rate. It will not retrieve anything from the database, because that is the purpose of the Data Assembler. The Data Assembler is the other object that will interact with the database. It will issue requests for the various data that the UI would like to graph, which include the heart rate, the current times, and the songs. Thus, the Data Manager and Data Assembler are the only objects that have direct access to the database.

8.5 Network Protocol

8.6 Global Control Flow

8.6.1 Execution Orderness

The execution order is a mix of procedure-driven and event-driven. From a broad view, the use of the program follows the same steps: the user starts the music, the system runs, then the user stops the music. However, the system provides a variety of interface options to activate events during the execution: a user may pause or skip playback, and view their statistics, at any time.

8.6.2 Time Dependency

The system is real-time, with a timer firing once a second. This timer triggers the fetching of the heart rate from the monitor, and triggers the logging of this data.

8.6.3 Concurrency

The Android standard concurrency model is that the main thread handles UI, so lengthy tasks must be performed on a background thread else the UI becomes unresponsive. As such, the network IO of the music selection system must certainly be in a different thread. Synchronization is unnecessary as there is no shared resource.

8.7 Hardware Requirements

The system requires:

- Touch screen display with minimum resolution of 640 x 480 pixels
- Storage space for music library, minimum size of 100 Mb
- Bluetooth for communication with a heart rate monitor
- Network connection for communicating with music selection service
- Audio playback capabilities

All of these requirements are met by most Android phones on the market.

Individual Contributions Breakdown

	Kenny Bambridge	Jonathan Chang	Samani Gikandi	Tae- Min Kim	Nikhil Shenoy	Revan Sopher
Problem Statement	X	X	X	X	X	X
Glossary of Terms				X		
System Requirements		X			X	X
Func. Requirements		X		X		
Non-Func. Req.					X	
Appearance Req.		X				X
Stakeholders				X		
Actors and Goals				X		
System Sequence Diagram			X			
Preliminary Design		X				X
User Effort Estimation	X					
Use Cases				X	X	X
System Sequence Diagrams			X			
User Effort Estimation	X					
Domain Model	X		X			
Operation Contracts				X	X	
Mathematical Model						X
Plan of Work		X				
Interaction Diagrams		X			X	
Project Management	X	X	X	X	X	X
LaTeX Maintenance	X	X	X	X	X	X

References

References 1-5 are the final project reports of the previous groups who worked on the Personal Health Monitoring projects. They were consulted in conjunction with Professor Marsic's Software Engineering textbook as a guide for formatting guidelines, content ideas, and inspiration.

- [0] http://www.ece.rutgers.edu/~marsic/books/SE/book-SE_marsic.pdf
 [1] <http://www.ece.rutgers.edu/~marsic/books/SE/projects/HealthMonitor/2013-g7-report3.pdf>
 [2] <http://www.ece.rutgers.edu/~marsic/books/SE/projects/HealthMonitor/2013-g8-report3.pdf>
 [3] <http://www.ece.rutgers.edu/~marsic/books/SE/projects/HealthMonitor/2012-g1-report3.pdf>
 [4] <http://www.ece.rutgers.edu/~marsic/books/SE/projects/HealthMonitor/2012-g2-report3.pdf>
 [5] <http://www.ece.rutgers.edu/~marsic/books/SE/projects/HealthMonitor/2012-g3-report3.pdf>

Reference 6 is a review of the Motorola MOTOACTV device. They provided us with the specifications and usage details to help us develop our project proposal.

- [7] <http://reviews.cnet.com/specialized-electronics/motorola-MOTOACTV-gps-fitness/4505->

References 7-8 are Wikipedia articles that helped educate us on electroencephalography and electroencephalogram define the terms for our glossary.

- [7] <http://en.wikipedia.org/wiki/Electroencephalography>
[8] <http://www.scholarpedia.org/article/Electroencephalogram>

Reference 9 provided us with an opening statistic to highlight the industry demand for fitness.

- [9] <http://www.statista.com/statistics/242190/us-fitness-industry-revenue-by-sector/>

References 10-11 are pictures that we used for our cover.

- [10] https://yt4.ggpht.com/-knZVRWVniHU/AAAAAAAAAI/AAAAAAAAAA/QN5_n28x_R0/s900-c-k-no
[11] http://www2.hu-berlin.de/fpm/graphics/logo_heartbeat-note.png

References 12-13 are information about target heart rates.

- [12] <http://www.webmd.com/fitness-exercise/healthtool-target-heart-rate-calculator>
[13] <http://www.livestrong.com/article/105256-normal-heart-rate-sleeping/>

References 14-15 explain how exercise and sleep affect heart rate.

- [14] <http://www.active.com/fitness/articles/how-does-exercise-affect-your-heart>
- [15] <http://www.webmd.com/sleep-disorders/features/how-sleep-affects-your-heart>

Reference 16 was consulted in describing the Architectural style of our system.

- [16] http://en.wikipedia.org/wiki/Multitier_architecture