

# NIST Big Data Interoperability Framework

## Volume 8: Reference Architecture Interfaces

---

**Wo L Chang  
Gregor von Laszewski**

Editor

---

[laszewski@gmail.com](mailto:laszewski@gmail.com)

---

<https://github.com/cloudmesh/cloudmesh-nist>

June 17, 2019 - 03:11 PM

Created by Cloudmesh & Cyberaide Bookmanager, <https://github.com/cyberaide/bookmanager>

# **NIST BIG DATA INTEROPERABILITY FRAMEWORK: VOLUME 8, REFERENCE ARCHITECTURE INTERFACES**

Editor: Gregor von Laszewski, Working Group co-Chair: Wo Chang

**Copyrights and Permissions:** Official publications of the National Institute of Standards and Technology are not subject to copyright in the United States. Foreign rights are reserved. Questions concerning the possibility of copyrights in foreign countries should be referred to the Office of Chief Counsel at NIST via email to [nistcounsel@nist.gov](mailto:nistcounsel@nist.gov).

# NIST BIG DATA INTEROPERABILITY FRAMEWORK: VOLUME 8, REFERENCE ARCHITECTURE INTERFACES

[NIST Big Data Interoperability Framework: Volume 8, Reference Architecture Interfaces](#)

## [1 Introduction](#)

[1.1 Background](#)

[1.2 Scope and Objectives of the Reference Architectures Subgroup](#)

[1.3 Report Production](#)

[1.4 Report Structure](#)

## [2 NBDRA Interface Requirements](#)

[2.1 High-Level Requirements of the Interface Approach](#)

[2.1.1 Technology- and Vendor-Agnostic](#)

[2.1.2 Support of Plug-In Compute Infrastructure](#)

[2.1.3 Orchestration of Infrastructure and Services](#)

[2.1.4 Orchestration of Big Data Applications and Experiments](#)

[2.1.5 Reusability](#)

[2.1.6 Execution Workloads](#)

[2.1.7 Security and Privacy Fabric Requirements](#)

[2.2 Component-Specific Interface Requirements](#)

[2.2.1 System Orchestrator Interface Requirements](#)

[2.2.2 Data Provider Interface Requirements](#)

[2.2.3 Data Consumer Interface Requirements](#)

[2.2.4 Big Data Application Interface Provider Requirements](#)

[2.2.5 Big Data Provider Framework Interface Requirements](#)

[2.2.6 Big Data Application Provider to Big Data Framework Provider Interface](#)

## [3 Specification Paradigm](#)

[3.1 Hybrid and Multiple Frameworks](#)

[3.2 Design by Resource-Oriented Architecture](#)

[3.3 Design by Example](#)

[3.4 Version Management](#)

[3.5 Interface Compliancy](#)

[3.6 Refernce implementations](#)

## [4 Specification](#)

[4.1 List of specifications](#)

[4.2 Authentication](#)

[4.3 Status Codes and Error Responses](#)

[4.4 Identity](#)

[4.4.1 Organization](#)

[4.4.2 User](#)

[4.4.3 Public Key Store](#)

[4.5 General Resources](#)

[4.5.1 Timestamp](#)

[4.5.2 Alias](#)  
[4.5.3 Variables](#)  
[4.5.4 Default](#)  
[4.6 Data Management](#)  
[4.6.1 Filestore](#)  
[4.6.2 Replica](#)  
[4.6.3 Database](#)  
[4.6.4 Virtual Directory](#)  
[4.7 Compute Management - Virtual Clusters](#)  
[4.7.1 Virtual Cluster](#)  
[4.7.2 Scheduler](#)  
[4.8 Compute Management - Virtual Machines](#)  
[4.8.1 Image](#)  
[4.8.2 Flavor](#)  
[4.8.3 Virtual Machine](#)  
[4.8.4 Secgroup](#)  
[4.8.5 Nic](#)  
[4.9 Compute Management - Containers](#)  
[4.9.1 Containers](#)  
[4.10 Compute Management - Functions](#)  
[4.10.1 Microservice](#)  
[4.11 Reservation](#)  
[4.11.1 Reservation](#)  
[4.12 Data Streams](#)  
[4.12.1 Stream](#)  
[4.12.2 Filter](#)  
[4.13 Deployment](#)  
[4.13.1 Deployment](#)  
[5 Acronyms and Terms](#)  
[Bibliography](#)

# **NIST BIG DATA INTEROPERABILITY FRAMEWORK: VOLUME 8, REFERENCE ARCHITECTURE INTERFACES**

## **NIST Special Publication 1500-9**

---

# **NIST Big Data Interoperability Framework: Volume 8, Reference Architecture Interfaces**

---

NIST Big Data Public Working Group  
Reference Architecture Subgroup

July 2019

This publication is available free of charge from:  
<https://doi.org/10.6028/NIST.SP.1500-9>



# **NIST Special Publication 1500-9**

## **NIST Big Data Interoperability Framework: Volume 8, Reference Architecture Interfaces**

NIST Big Data Public Working Group (NBD-PWG)  
Definitions and Taxonomies Subgroup  
*Information Technology Laboratory*  
*National Institute of Standards and Technology*  
*Gaithersburg, MD 20899*

This publication is available free of charge from:  
<https://doi.org/10.6028/NIST.SP.1500-9>

July 2019



U.S. Department of Commerce  
*Wilbur L. Ross, Jr., Secretary*

National Institute of Standards and Technology  
*Walter Copan, NIST Director and Undersecretary of Commerce for Standards and Technology*

---

Abstract

This document summarizes interfaces that are instrumental for the interaction with Clouds, Containers, and High Performance Computing (HPC) systems to manage virtual clusters to support the NIST Big Data Reference Architecture (NBDRA). The REpresentational State Transfer (REST) paradigm is used to define these interfaces, allowing easy integration and adoption by a wide variety of frameworks.

Big Data is a term used to describe extensive datasets, primarily in the characteristics of volume, variety, velocity, and/or variability. While opportunities exist with Big Data, the data characteristics can overwhelm traditional technical approaches, and the growth of data is outpacing scientific and technological advances in data analytics. To advance progress in Big Data, the NIST Big Data Public Working Group (NBD-PWG) is working to develop consensus on important fundamental concepts related to Big Data. The results are reported in the ***NIST Big Data Interoperability Framework (NBDIF)*** series of volumes. This volume, Volume 8, uses the work performed by the NBD-PWG to identify objects instrumental for the NIST Big Data Reference Architecture (NBDRA) which is introduced in the NBDIF: Volume 6, ***Reference Architecture***.

## Keywords

Adoption; barriers; implementation; interfaces; market maturity; organizational maturity; project maturity; system modernization.

---

## Acknowledgements

This document reflects the contributions and discussions by the membership of the NBD-PWG, cochaired by Wo Chang (NIST ITL), Bob Marcus (ET-Strategies), and Chaitan Baru (San Diego Supercomputer Center; National Science Foundation). For all versions, the Subgroups were led by the following people: Nancy Grady (SAIC), Natasha Balac (SDSC), and Eugene Luster (R2AD) for the Definitions and Taxonomies Subgroup; Geoffrey Fox (Indiana University) and Tsegereda Beyene (Cisco Systems) for the Use Cases and Requirements Subgroup; Arnab Roy (Fujitsu), Mark Underwood (Krypton Brothers; Synchrony Financial), and Akhil Manchanda (GE) for the Security and Privacy Subgroup; David Boyd (InCadence Strategic Solutions), Orit Levin (Microsoft), Don Krapohl (Augmented Intelligence), and James Ketner (AT&T) for the Reference Architecture Subgroup; and Russell Reinsch (Center for Government Interoperability), David Boyd (InCadence Strategic Solutions), Carl Buffington (Vistrionix), and Dan McClary (Oracle), for the Standards Roadmap Subgroup, Gregor von Laszewski (Indiana University) for the Interface Subgroup.

The following milestone releases exist:

- Version 2.1: A previous volume used the definitions of the schema based on examples only. It was easier to read but only included the definition of the resources and not the interaction with the resources. This volume was in place until June 2018.
- Version 2.2: This version was significantly changed and used OpenAPI 2.0 to

- specify the interfaces between the various services and components.
- Version 3.1.1: The version includes significant improvements of the object specifications but are still using OpenAPI 2.0.
- Version 3.2.0: All specifications have been updated to OpenAPI 3.0.2. Significant updates have been done to a number of specifications.

The editors for these documents are:

- Gregor von Laszewski (Indiana University)
- Wo Chang (NIST).

Laurie Aldape (Energetics Incorporated) and Elizabeth Lennon (NIST) provided editorial assistance across all NBDIF volumes.

NIST SP 1500-9, Draft NIST Big Data Interoperability Framework: Volume 8, Reference Architecture Interfaces, Version 2 has been collaboratively authored by the NBD-PWG. As of the date of publication, there are over six hundred NBD-PWG participants from industry, academia, and government. Federal agency participants include the National Archives and Records Administration (NARA), National Aeronautics and Space Administration (NASA), National Science Foundation (NSF), and the U.S. Departments of Agriculture, Commerce, Defense, Energy, Census, Health and Human Services, Homeland Security, Transportation, Treasury, and Veterans Affairs.

NIST would like to acknowledge the specific contributions to this volume, during Version 1 and/or Version 2 activities. **Contributors** are members of the NIST Big Data Public Working Group who dedicated great effort to prepare and gave substantial time on a regular basis to research and development in support of this document. This includes the following NBD-PWG members:

- Gregor von Laszewski, Indiana University
- Wo Chang, National Institute of Standard and Technology,
- Fugang Wang, Indiana University
- Geoffrey C. Fox, Indiana University
- Shirish Joshi, Indiana University
- Badi Abdul-Wahid, formerly Indiana Univresity
- Alicia Zuniga-Alvarado, Consultant
- Robert C. Whetsel, DISA/NBIS
- Pratik Thakkar, Philips

---

## Executive Summary

The ***NIST Big Data Interoperability Framework (NBDIF): Volume 8, Reference Architecture Interfaces*** document was prepared by the NIST Big Data Public Working Group (NBD-PWG) Reference Architecture Subgroup to identify interfaces in support of the NIST Big Data Reference Architecture (NBDRA). The interface define resources that are part of the

NBDRA. These resources are formulated in OpenAPI 3.0.2 format and can be easily integrated into a REpresentational State Transfer (REST) framework or an object-based framework.

The resources were categorized in groups that are identified by the NBDRA set forward in the **NBDIF: Volume 6, Reference Architecture** document. While the **NBDIF: Volume 3, Use Cases and General Requirements** document provides *application*-oriented high-level use cases, the use cases defined in this document are subsets of them and focus on *interface* use cases. The interface use cases are not meant to be complete examples, but showcase why the resource has been defined. Hence, the interfaces use cases are only representative, and do not encompass the entire spectrum of Big Data usage. All the interfaces were openly discussed in the working group [1]. Additions to the interfaces are welcome and the NBD-PWG is open to discuss any contributions.

The **NIST Big Data Interoperability Framework (NBDIF)** was released in three versions, which correspond to the three stages of the NBD-PWG work. Version 3 (current version) of the NBDIF volumes resulted from Stage 3 work with major emphasis on the validation of the NBDRA Interfaces and content enhancement. Stage 3 work built upon the foundation created during Stage 2 and Stage 1. The current effort documented in this volume reflects concepts developed within the rapidly evolving field of Big Data. The three stages (in reverse order) aim to achieve the following with respect to the NIST Big Data Reference Architecture (NBDRA):

- Stage 1: Identify the high-level Big Data reference architecture key components, which are technology-, infrastructure-, and vendor-agnostic.
- Stage 2: Define general interfaces between the NBDRA components; and
- Stage 3: Validate the NBDRA by building Big Data general applications through the general interfaces;

The NBDIF consists of nine volumes, each of which addresses a specific key topic, resulting from the work of the NBD-PWG. The nine volumes are as follows:

- Volume 1, Definitions [2]
- Volume 2, Taxonomies [3]
- Volume 3, Use Cases and General Requirements [4]
- Volume 4, Security and Privacy [5]
- Volume 5, Architectures White Paper Survey [6]
- Volume 6, Reference Architecture [7]
- Volume 7, Standards Roadmap [8]
- Volume 8, Reference Architecture Interfaces (this volume) [9]
- Volume 9, Adoption and Modernization [10]

During Stage 1, Volumes 1 through 7 were conceptualized, organized and written. The finalized Version 1 documents can be downloaded from the V1.0 Final Version page of the NBD-PWG website [11].

During Stage 2, the NBD-PWG developed Version 2 of the NBDIF Version 1 volumes, with the exception of Volume 5, which contained the completed architecture survey work that was

used to inform Stage 1 work of the NBD-PWG. The goals of Version 2 were to enhance the Version 1 content, define general interfaces between the NBDRA components by aggregating low-level interactions into high-level general interfaces, and demonstrate how the NBDRA can be used. As a result of the Stage 2 work, the need for NBDIF Volume 8 and NBDIF Volume 9 were identified and the two new volumes were created. Version 2 of the NBDIF volumes, resulting from Stage 2 work, can be downloaded from the V2.0 Final Version page of the NBD-PWG website [12].

This document is the result of Stage 3 work of the NBD-PWG. Coordination of the group is conducted on the NBD-PWG web page [1].

# 1 INTRODUCTION

## 1.1 BACKGROUND

---

There is broad agreement among commercial, academic, and government leaders about the potential of Big Data to spark innovation, fuel commerce, and drive progress. Big Data is the common term used to describe the deluge of data in today's networked, digitized, sensor-laden, and information-driven world. The availability of vast data resources carries the potential to answer questions previously out of reach, including the following:

- How can a potential pandemic reliably be detected early enough to intervene?
- Can new materials with advanced properties be predicted before these materials have ever been synthesized?
- How can the current advantage of the attacker over the defender in guarding against cybersecurity threats be reversed?

There is also broad agreement on the ability of Big Data to overwhelm traditional approaches. The growth rates for data volumes, speeds, and complexity are outpacing scientific and technological advances in data analytics, management, transport, and data user spheres.

Despite widespread agreement on the inherent opportunities and current limitations of Big Data, a lack of consensus on some important fundamental questions continues to confuse potential users and stymie progress. These questions include the following:

- How is Big Data defined?
- What attributes define Big Data solutions?
- What is new in Big Data?
- What is the difference between Big Data and **bigger data** that has been collected for years?
- How is Big Data different from traditional data environments and related applications?
- What are the essential characteristics of Big Data environments?
- How do these environments integrate with currently deployed architectures?
- What are the central scientific, technological, and standardization challenges that need to be addressed to accelerate the deployment of robust, secure Big Data solutions?

Within this context, on March 29, 2012, the White House announced the Big Data Research and Development Initiative (The White House Office of Science and Technology Policy, “Big Data is a Big Deal,” **OSTP Blog**, accessed February 21, 2014 [13]. The initiative’s goals include helping to accelerate the pace of discovery in science and engineering, strengthening national security, and transforming teaching and learning by improving analysts’ ability to extract knowledge and insights from large and complex collections of digital data.

Six federal departments and their agencies announced more than \$200 million in commitments spread across more than 80 projects, which aim to significantly improve the tools and techniques needed to access, organize, and draw conclusions from huge volumes of digital data. The initiative also challenged industry, research universities, and nonprofits to join with the federal government to make the most of the opportunities created by Big Data.

Motivated by the White House initiative and public suggestions, the National Institute of Standards and Technology (NIST) accepted the challenge to stimulate collaboration among industry professionals to further the secure and effective adoption of Big Data. As a result of NIST's Cloud and Big Data Forum held on January 15–17, 2013, there was strong encouragement for NIST to create a public working group for the development of a Big Data Standards Roadmap. Forum participants noted that this roadmap should define and prioritize Big Data requirements, including interoperability, portability, reusability, extensibility, data usage, analytics, and technology infrastructure. In doing so, the roadmap would accelerate the adoption of the most secure and effective Big Data techniques and technology.

On June 19, 2013, the NIST Big Data Public Working Group (NBD-PWG) was launched with extensive participation by industry, academia, and government from across the nation. The scope of the NBD-PWG involves forming a community of interests from all sectors—including industry, academia, and government—with the goal of developing consensus on definitions, taxonomies, secure reference architectures, security and privacy, and, from these, a standards roadmap. Such a consensus would create a vendor-neutral, technology- and infrastructure-independent framework that would enable Big Data stakeholders to identify and use the best analytics tools for their processing and visualization requirements on the most suitable computing platform and cluster, while also allowing added value from Big Data service providers.

The **NIST Big Data Interoperability Framework (NBDIF)** was released in three versions, which correspond to the three stages of the NBD-PWG work. Version 3 (current version) of the NBDIF volumes resulted from Stage 3 work with major emphasis on the validation of the NBDRA Interfaces and content enhancement. Stage 3 work built upon the foundation created during Stage 2 and Stage 1. The current effort documented in this volume reflects concepts developed within the rapidly evolving field of Big Data. The three stages (in reverse order) aim to achieve the following with respect to the NIST Big Data Reference Architecture (NBDRA).

Stage 3: Validate the NBDRA by building Big Data general applications through the general interfaces; Stage 2: Define general interfaces between the NBDRA components; and Stage 1: Identify the high-level Big Data reference architecture key components, which are technology-, infrastructure-, and vendor-agnostic.

The NBDIF consists of nine volumes, each of which addresses a specific key topic, resulting from the work of the NBD-PWG. The nine volumes are as follows:

- Volume 1, Definitions [2]
- Volume 2, Taxonomies [3]
- Volume 3, Use Cases and General Requirements [4]

- Volume 4, Security and Privacy [5]
- Volume 5, Architectures White Paper Survey [6]
- Volume 6, Reference Architecture [7]
- Volume 7, Standards Roadmap [8]
- Volume 8, Reference Architecture Interfaces (this volume) [9]
- Volume 9, Adoption and Modernization [10]

During Stage 1, Volumes 1 through 7 were conceptualized, organized and written. The finalized Version 1 documents can be downloaded from the V1.0 Final Version page of the NBD-PWG website [11].

During Stage 2, the NBD-PWG developed Version 2 of the NBDIF Version 1 volumes, with the exception of Volume 5, which contained the completed architecture survey work that was used to inform Stage 1 work of the NBD-PWG. The goals of Version 2 were to enhance the Version 1 content, define general interfaces between the NBDRA components by aggregating low-level interactions into high-level general interfaces, and demonstrate how the NBDRA can be used. As a result of the Stage 2 work, the need for NBDIF Volume 8 and NBDIF Volume 9 were identified and the two new volumes were created. Version 2 of the NBDIF volumes, resulting from Stage 2 work, can be downloaded from the V2.0 Final Version page of the NBD-PWG website [12].

## 1.2 SCOPE AND OBJECTIVES OF THE REFERENCE ARCHITECTURES SUBGROUP

Reference architectures provide “an authoritative source of information about a specific subject area that guides and constrains the instantiations of multiple architectures and solutions” [14]. Reference architectures generally serve as a foundation for solution architectures and may also be used for comparison and alignment of instantiations of architectures and solutions.

The goal of the NBD-PWG Reference Architecture Subgroup is to develop an open reference architecture for Big Data that achieves the following objectives:

- Provides a common language for the various stakeholders;
- Encourages adherence to common standards, specifications, and patterns;
- Provides consistent methods for implementation of technology to solve similar problem sets;
- Illustrates and improves understanding of the various Big Data components, processes, and systems, in the context of a vendor- and technology-agnostic Big Data conceptual model;
- Provides a technical reference for U.S. government departments, agencies, and other consumers to understand, discuss, categorize, and compare Big Data solutions; and
- Facilitates analysis of candidate standards for interoperability, portability, reusability, and extendibility.

The NBDRA is a high-level conceptual model crafted to serve as a tool to facilitate open discussion of the requirements, design structures, and operations inherent in Big Data. The

NBDRA is intended to facilitate the understanding of the operational intricacies in Big Data. It does not represent the system architecture of a specific Big Data system, but rather is a tool for describing, discussing, and developing system-specific architectures using a common framework of reference. The model is not tied to any specific vendor products, services, or reference implementation, nor does it define prescriptive solutions that inhibit innovation.

The NBDRA does not address the following:

- Detailed specifications for any organization's operational systems;
- Detailed specifications of information exchanges or services; and
- Recommendations or standards for integration of infrastructure products.

The goals of the Subgroup were realized throughout the three planned phases of the NBD-PWG work, as outlined in [Section 1.3](#).

## 1.3 REPORT PRODUCTION

---

The **NBDIF: Volume 8, References Architecture Interfaces** is one of nine volumes, whose overall aims are to define and prioritize Big Data requirements, including interoperability, portability, reusability, extensibility, data usage, analytic techniques, and technology infrastructure to support secure and effective adoption of Big Data. The overall goals of this volume are to define and specify interfaces to implement the Big Data Reference Architecture. This volume arose from discussions during the weekly NBD-PWG conference calls. Topics included in this volume began to take form in Phase 2 of the NBD-PWG work. During the discussions, the NBD-PWG identified the need to specify a variety of interfaces.

Phase 3 work, which built upon the groundwork developed during Phase 2, included an early specification based on resource object specifications that provided a simplified version of an API interface design.

## 1.4 REPORT STRUCTURE

---

To enable interoperability between the NBDRA components, a list of well-defined NBDRA interfaces is needed. These interfaces are documented in this volume. To introduce them, the NBDRA structure will be followed, focusing on interfaces that allow bootstrapping of the NBDRA. The document begins with a summary of requirements that will be integrated into our specifications. Subsequently, each section will introduce a number of objects that build the core of the interface addressing a specific aspect of the NBDRA. A selected number of **interface use cases** will be showcased to outline how the specific interface can be used in a reference implementation of the NBDRA. Validation of this approach can be achieved while applying it to the application use cases that have been gathered in the **NBDIF: Volume 3, Use Cases and Requirements** document. These application use cases have considerably contributed towards the design of the NBDRA. Hence the expectation is that: (1) the interfaces can be used to help implement a Big Data architecture for a specific use case; and (2) the proper

implementation. This approach can facilitate subsequent analysis and comparison of the use cases.

The organization of this document roughly corresponds to the process used by the NBD-PWG to develop the interfaces. Following the introductory material presented in [Section 1](#), the remainder of this document is organized as follows:

- [Section 2](#) presents the interface requirements;
- [Section 3](#) presents the specification paradigm that is used;
- [Section 4](#) presents several objects grouped by functional use while providing a summary table of selected proposed objects in [Section 4.1](#).

While each NBDIF volume was created with a specific focus within Big Data, all volumes are interconnected. During creation, the volumes gave and/or received input from other volumes. Broad topics (e.g., definition, architecture) may be discussed in several volumes with the discussion circumscribed by the volume's particular focus. Arrows shown in [Figure 1](#) indicate the main flow of input/output. Volumes 2, 3, and 5 (blue circles) are essentially standalone documents that provide output to other volumes (e.g., to Volume 6). These volumes contain the initial situational awareness research. Volumes 4, 7, 8, and 9 (green circles) primarily received input from other volumes during the creation of the particular volume. Volumes 1 and 6 (red circles) were developed using the initial situational awareness research and continued to be modified based on work in other volumes. These volumes also provided input to the green circle volumes.



Figure 1: NBDIF Documents Navigation Diagram Provides Content Flow Between Volumes

## 2 NBDRA INTERFACE REQUIREMENTS

The development of a Big Data reference architecture requires a thorough understanding of current techniques, issues, and concerns. To this end, the NBD-PWG collected use cases to gain an understanding of current applications of Big Data, conducted a survey of reference architectures to understand commonalities within Big Data architectures in use, developed a taxonomy to understand and organize the information collected, and reviewed existing technologies and trends relevant to Big Data. The results of these NBD-PWG activities were used in the development of the NBDRA ([Figure 2](#)) and the interfaces presented herein. Detailed descriptions of these activities can be found in the other volumes of the **NBDIF**.




Figure 2: NIST Big Data Reference Architecture (NBDRA)

This vendor-neutral, technology- and infrastructure-agnostic conceptual model, the NBDRA, is shown in [Figure 2](#) and represents a Big Data system composed of five logical functional components connected by interoperability interfaces (i.e., services). Two fabrics envelop the components, representing the interwoven nature of management and security and privacy with all five of the components. These two fabrics provide services and functionality to the five main roles in the areas specific to Big Data and are crucial to any Big Data solution. Note: None of the terminology or diagrams in these documents is intended to be normative or to

imply any business or deployment model. The terms **provider** and **consumer** as used are descriptive of general roles and are meant to be informative in nature.

The NBDRA is organized around five major roles and multiple sub-roles aligned along two axes representing the two Big Data value chains: the Information Value (horizontal axis) and the Information Technology (IT; vertical axis). Along the Information Value axis, the value is created by data collection, integration, analysis, and applying the results following the value chain. Along the IT axis, the value is created by providing networking, infrastructure, platforms, application tools, and other IT services for hosting of and operating the Big Data in support of required data applications. At the intersection of both axes is the Big Data Application Provider role, indicating that data analytics and its implementation provide the value to Big Data stakeholders in both value chains. The term **provider** as part of the Big Data Application Provider and Big Data Framework Provider is there to indicate that those roles provide or implement specific activities and functions within the system. It does not designate a service model or business entity.

The DATA arrows in [Figure 2](#) show the flow of data between the system's main roles. Data flows between the roles either physically (i.e., by value) or by providing its location and the means to access it (i.e., by reference). The SW arrows show transfer of software tools for processing of Big Data *in situ*. The Service Use arrows represent software programmable interfaces. While the main focus of the NBDRA is to represent the run-time environment, all three types of communications or transactions can happen in the configuration phase as well. Manual agreements (e.g., service-level agreements) and human interactions that may exist throughout the system are not shown in the NBDRA.

Detailed information on the NBDRA conceptual model is presented in the **NBDIF: Volume 6, Reference Architecture** document.

Prior to outlining the specific interfaces, general requirements are introduced and the interfaces are defined.

## **2.1 HIGH-LEVEL REQUIREMENTS OF THE INTERFACE APPROACH**

---

This section focuses on the high-level requirements of the interface approach that are needed to implement the reference architecture depicted in [Figure 2](#).

### **2.1.1 Technology- and Vendor-Agnostic**

Due to the many different tools, services, and infrastructures available in the general area of Big Data, an interface ought to be as vendor-independent as possible, while, at the same time, be able to leverage best practices. Hence, a methodology is needed that allows extension of interfaces to adapt and leverage existing approaches, but also allows the interfaces to provide merit in easy specifications that assist the formulation and definition of the NBDRA.

### 2.1.2 Support of Plug-In Compute Infrastructure

As Big Data is not just about hosting data, but about analyzing data, the interfaces provided herein must encapsulate a rich infrastructure environment that is used by data scientists. This includes the ability to integrate (or plug-in) various compute resources and services to provide the necessary compute power to analyze the data. These resources and services include the following:

- Access to hierarchy of compute resources from the laptop/desktop, servers, data clusters, and clouds;
- The ability to integrate special-purpose hardware such as graphics processing units (GPUs) and field-programmable gate arrays (FPGAs) that are used in accelerated analysis of data; and
- The integration of services including microservices that allow the analysis of the data by delegating them to hosted or dynamically deployed services on the infrastructure of choice.

### 2.1.3 Orchestration of Infrastructure and Services

From review of the use case collection, presented in the **NBDIF: Volume 3, Use Cases and General Requirements** document [4], the need arose to address the mechanism of preparing suitable infrastructures for various use cases. As not every infrastructure is suited for every use case, a custom infrastructure may be needed. As such, this document is not attempting to deliver a single deployed NBDRA, but allow the setup of an infrastructure that satisfies the particular use case. To achieve this task, it is necessary to provision software stacks and services while orchestrating their deployment and leveraging infrastructures. It is not the focus of this document to replace existing orchestration software and services, but provide an interface to them to leverage them as part of defining and creating the infrastructure. Various orchestration frameworks and services could therefore be leveraged, even as part of the same framework, and work in orchestrated fashion to achieve the goal of preparing an infrastructure suitable for one or more applications.

### 2.1.4 Orchestration of Big Data Applications and Experiments

The creation of the infrastructure suitable for Big Data applications provides the basic computing environment. However, Big Data applications may require the creation of sophisticated applications as part of interactive experiments to analyze and probe the data. For this purpose, the applications must be able to orchestrate and interact with experiments conducted on the data while assuring reproducibility and correctness of the data. For this purpose, a **System Orchestrator** (either the data scientists or a service acting on behalf of the data scientist) is used as the command center to interact on behalf of the Big Data Application Provider to orchestrate dataflow from Data Provider, carry out the Big Data application life cycle with the help of the Big Data Framework Provider, and enable the Data Consumer to consume Big Data processing results. An interface is needed to describe these interactions and

to allow leveraging of experiment management frameworks in scripted fashion. A customization of parameters is needed on several levels. On the highest level, application-motivated parameters are needed to drive the orchestration of the experiment. On lower levels, these high-level parameters may drive and create service-level agreements, augmented specifications, and parameters that could even lead to the orchestration of infrastructure and services to satisfy experiment needs.

### 2.1.5 Reusability

The interfaces provided must encourage reusability of the infrastructure, services, and experiments described by them. This includes (1) reusability of available analytics packages and services for adoption; (2) deployment of customizable analytics tools and services; and (3) operational adjustments that allow the services and infrastructure to be adapted while at the same time allowing for reproducible experiment execution.

### 2.1.6 Execution Workloads

One of the important aspects of distributed Big Data services can be that the data served is simply too big to be moved to a different location. Instead, an interface could allow the description and packaging of analytics algorithms, and potentially also tools, as a payload to a data service. This can be best achieved, not by sending the detailed execution, but by sending an interface description that describes how such an algorithm or tool can be created on the server and be executed under security considerations (integrated with authentication and authorization in mind).

### 2.1.7 Security and Privacy Fabric Requirements

Although the focus of this document is not security and privacy, which are documented in the **NBDIF: Volume 4, Security and Privacy** [5], the interfaces defined herein must be capable of integration into a secure reference architecture that supports secure execution, secure data transfer, and privacy. Consequently, the interfaces defined herein can be augmented with frameworks and solutions that provide such mechanisms. Thus, diverse requirement needs stemming from different use cases addressing security need to be distinguished. To contrast that the security requirements between applications can vary drastically, the following example is provided. Although many of the interfaces and their objects to support Big Data applications in physics are similar to those in healthcare, they differ in the integration of security interfaces and policies. While in physics the protection of data is less of an issue, it is a stringent requirement in healthcare. Thus, deriving architectural frameworks for both may use largely similar components, but addressing security issues will be very different. The security of interfaces may be addressed in other documents. In this document, they are considered an advanced use case showcasing that the validity of the specifications introduced here is preserved, even if security and privacy requirements differ vastly among application use cases.

## 2.2 COMPONENT-SPECIFIC INTERFACE REQUIREMENTS

---

This section summarizes the requirements for the interfaces of the NBDRA components. The five components are listed in [Figure 2](#) and addressed in [Section 2.2.1](#) (System Orchestrator Interface Requirements) and [Section 2.2.4](#) (Big Data Application Provider to Big Data Framework Provider Interface) of this document. The five main functional components of the NBDRA represent the different technical roles within a Big Data system and are the following:

- System Orchestrator: Defines and integrates the required data application activities into an operational vertical system (see [Section 2.2.1](#));
- Data Provider: Introduces new data or information feeds into the Big Data system (see [Section 2.2.2](#));
- Data Consumer: Includes end users or other systems that use the results of the Big Data Application Provider (see [Section 2.2.3](#));
- Big Data Application Provider: Executes a data life cycle to meet security and privacy requirements as well as System Orchestrator-defined requirements (see [Section 2.2.4](#));
- Big Data Framework Provider: Establishes a computing framework in which to execute certain transformation applications while protecting the privacy and integrity of data (see [Section 2.2.5](#)); and
- Big Data Application Provider to Framework Provider Interface: Defines an interface between the application specification and the provider (see [Section 2.2.6](#)).

## 2.2.1 System Orchestrator Interface Requirements

The System Orchestrator role includes defining and integrating the required data application activities into an operational vertical system. Typically, the System Orchestrator involves a collection of more specific roles, performed by one or more actors, which manage and orchestrate the operation of the Big Data system. These actors may be human components, software components, or some combination of the two. The function of the System Orchestrator is to configure and manage the other components of the Big Data architecture to implement one or more workloads that the architecture is designed to execute. The workloads managed by the System Orchestrator may be assigning/provisioning framework components to individual physical or virtual nodes at the lower level, or providing a graphical user interface that supports the specification of workflows linking together multiple applications and components at the higher level. The System Orchestrator may also, through the Management Fabric, monitor the workloads and system to confirm that specific quality of service requirements is met for each workload, and may elastically assign and provision additional physical or virtual resources to meet workload requirements resulting from changes/surges in the data or number of users/transactions. The interface to the System Orchestrator must be capable of specifying the task of orchestration the deployment, configuration, and the execution of applications within the NBDRA. A simple vendor-neutral specification to coordinate the various parts either as simple parallel language tasks or as a workflow specification is needed to facilitate the overall coordination. Integration of existing tools and services into the System Orchestrator as extensible interfaces is desirable.

## 2.2.2 Data Provider Interface Requirements

The Data Provider role introduces new data or information feeds into the Big Data system for discovery, access, and transformation by the Big Data system. New data feeds are distinct from the data already in use by the system and residing in the various system repositories. Similar technologies can be used to access both new data feeds and existing data. The Data Provider actors can be anything from a sensor, to a human inputting data manually, to another Big Data system. Interfaces for data providers must be able to specify a data provider so it can be located by a data consumer. It also must include enough details to identify the services offered so they can be pragmatically reused by consumers. Interfaces to describe pipes and filters must be addressed.

## 2.2.3 Data Consumer Interface Requirements

Like the Data Provider, the role of Data Consumer within the NBDRA can be an actual end user or another system. In many ways, this role is the mirror image of the Data Provider, with the entire Big Data framework appearing like a Data Provider to the Data Consumer. The activities associated with the Data Consumer role include the following:

- Search and Retrieve,
- Download,
- Analyze Locally,
- Reporting,
- Visualization, and
- Data to Use for Their Own Processes.

The interface for the data consumer must be able to describe the consuming services and how they retrieve information or leverage data consumers.

## 2.2.4 Big Data Application Interface Provider Requirements

The Big Data Application Provider role executes a specific set of operations along the data life cycle to meet the requirements established by the System Orchestrator, as well as meeting security and privacy requirements. The Big Data Application Provider is the architecture component that encapsulates the business logic and functionality to be executed by the architecture. The interfaces to describe Big Data applications include interfaces for the various subcomponents including collections, preparation/curation, analytics, visualization, and access. Some of the interfaces used in these subcomponents can be reused from other interfaces, which are introduced in other sections of this document. Where appropriate, application-specific interfaces will be identified and examples provided with a focus on use cases as identified in the **NBDIF: Volume 3, Use Cases and General Requirements**.

### 2.2.4.1 Collection

In general, the collection activity of the Big Data Application Provider handles the interface with the Data Provider. This may be a general service, such as a file server or web server configured by the System Orchestrator to accept or perform specific collections of data, or it may be an application-specific service designed to pull data or receive pushes of data from the Data Provider. Since this activity is receiving data at a minimum, it must store/buffer the received data until it is persisted through the Big Data Framework Provider. This persistence need not be to physical media but may simply be to an in-memory queue or other service provided by the processing frameworks of the Big Data Framework Provider. The collection activity is likely where the extraction portion of the Extract, Transform, Load (ETL)/Extract, Load, Transform (ELT) cycle is performed. At the initial collection stage, sets of data (e.g., data records) of similar structure are collected (and combined), resulting in uniform security, policy, and other considerations. Initial metadata is created (e.g., subjects with keys are identified) to facilitate subsequent aggregation or look-up methods.

#### 2.2.4.2 Preparation

The preparation activity is where the transformation portion of the ETL/ELT cycle is likely performed, although analytics activity will also likely perform advanced parts of the transformation. Tasks performed by this activity could include data validation (e.g., checksums/hashes, format checks), cleaning (e.g., eliminating bad records/fields), outlier removal, standardization, reformatting, or encapsulating. This activity is also where source data will frequently be persisted to archive storage in the Big Data Framework Provider and provenance data will be verified or attached/associated. Verification or attachment may include optimization of data through manipulations (e.g., deduplication) and indexing to optimize the analytics process. This activity may also aggregate data from different Data Providers, leveraging metadata keys to create an expanded and enhanced data set.

#### 2.2.4.3 Analytics

The analytics activity of the Big Data Application Provider includes the encoding of the low-level business logic of the Big Data system (with higher-level business process logic being encoded by the System Orchestrator). The activity implements the techniques to extract knowledge from the data based on the requirements of the vertical application. The requirements specify the data processing algorithms to produce new insights that will address the technical goal. The analytics activity will leverage the processing frameworks to implement the associated logic. This typically involves the activity providing software that implements the analytic logic to the batch and/or streaming elements of the processing framework for execution. The messaging/communication framework of the Big Data Framework Provider may be used to pass data or control functions to the application logic running in the processing frameworks. The analytic logic may be broken up into multiple modules to be executed by the processing frameworks which communicate, through the messaging/communication framework, with each other and other functions instantiated by the Big Data Application Provider.

#### 2.2.4.4 Visualization

The visualization activity of the Big Data Application Provider prepares elements of the processed data and the output of the analytic activity for presentation to the Data Consumer. The objective of this activity is to format and present data in such a way as to optimally communicate meaning and knowledge. The visualization preparation may involve producing a text-based report or rendering the analytic results as some form of graphic. The resulting output may be a static visualization and may simply be stored through the Big Data Framework Provider for later access. However, the visualization activity frequently interacts with the access activity, the analytics activity, and the Big Data Framework Provider (processing and platform) to provide interactive visualization of the data to the Data Consumer based on parameters provided to the access activity by the Data Consumer. The visualization activity may be completely application-implemented, leverage one or more application libraries, or may use specialized visualization processing frameworks within the Big Data Framework Provider.

#### 2.2.4.5 Access

The access activity within the Big Data Application Provider is focused on the communication/interaction with the Data Consumer. Like the collection activity, the access activity may be a generic service such as a web server or application server that is configured by the System Orchestrator to handle specific requests from the Data Consumer. This activity would interface with the visualization and analytic activities to respond to requests from the Data Consumer (who may be a person) and uses the processing and platform frameworks to retrieve data to respond to Data Consumer requests. In addition, the access activity confirms that descriptive and administrative metadata and metadata schemes are captured and maintained for access by the Data Consumer and as data is transferred to the Data Consumer. The interface with the Data Consumer may be synchronous or asynchronous in nature and may use a pull or push paradigm for data transfer.

### 2.2.5 Big Data Provider Framework Interface Requirements

Data for Big Data applications are delivered through data providers. They can be either local providers, data contributed by a user, or distributed data providers, data on the Internet. This interface must be able to provide the following functionality:

- Interfaces to files,
- Interfaces to virtual data directories,
- Interfaces to data streams, and
- Interfaces to data filters.

#### 2.2.5.1 Infrastructures Interface Requirements

This Big Data Framework Provider element provides all the resources necessary to host/run the

activities of the other components of the Big Data system. Typically, these resources consist of some combination of physical resources, which may host/support similar virtual resources. The NBDRA needs interfaces that can be used to deal with the underlying infrastructure to address networking, computing, and storage.

#### 2.2.5.2 Platforms Interface Requirements

As part of the NBDRA platforms, interfaces are needed that can address platform needs and services for data organization, data distribution, indexed storage, and file systems.

#### 2.2.5.3 Processing Interface Requirements

The processing frameworks for Big Data provide the necessary infrastructure software to support implementation of applications that can deal with the volume, velocity, variety, and variability of data. Processing frameworks define how the computation and processing of the data is organized. Big Data applications rely on various platforms and technologies to meet the challenges of scalable data analytics and operation. A requirement is the ability to interface easily with computing services that offer specific analytics services, batch processing capabilities, interactive analysis, and data streaming.

#### 2.2.5.4 Crosscutting Interface Requirements

Several crosscutting interface requirements within the Big Data Framework Provider include messaging, communication, and resource management. Often these services may be hidden from explicit interface use as they are part of larger systems that expose higher-level functionality through their interfaces. However, such interfaces may also be exposed on a lower level in case finer-grained control is needed. The need for such crosscutting interface requirements will be extracted from the **NBDIF: Volume 3, Use Cases and General Requirements** document.

#### 2.2.5.5 Messaging/Communications Frameworks

Messaging and communications frameworks have their roots in the High Performance Computing environments long popular in the scientific and research communities. Messaging/Communications Frameworks were developed to provide application programming interfaces (APIs) for the reliable queuing, transmission, and receipt of data.

#### 2.2.5.6 Resource Management Framework

As Big Data systems have evolved and become more complex, and as businesses work to leverage limited computation and storage resources to address a broader range of applications and business challenges, the requirement to effectively manage those resources has grown significantly. While tools for resource management and **elastic computing** have expanded and

matured in response to the needs of cloud providers and virtualization technologies, Big Data introduces unique requirements for these tools. However, Big Data frameworks tend to fall more into a distributed computing paradigm, which presents additional challenges.

## 2.2.6 Big Data Application Provider to Big Data Framework Provider Interface

The Big Data Framework Provider typically consists of one or more hierarchically organized instances of the components in the NBDRA IT value chain ([Figure 2](#)). There is no requirement that all instances at a given level in the hierarchy be of the same technology. In fact, most Big Data implementations are hybrids that combine multiple technology approaches to provide flexibility or meet the complete range of requirements, which are driven from the Big Data Application Provider.

## 3 SPECIFICATION PARADIGM

This section summarizes the elementary specification paradigm.

### 3.1 HYBRID AND MULTIPLE FRAMEWORKS

---

To avoid vendor lock-in, Big Data systems must be able to deal with hybrid and multiple frameworks. This is not only true for Clouds, containers, DevOps, but also for components of the NBDRA.

### 3.2 DESIGN BY RESOURCE-ORIENTED ARCHITECTURE

---

A resource-oriented architecture represents a software architecture and programming paradigm for designing and developing software in the form of resources. It is often associated with ***REpresentational State Transfer (REST)*** interfaces. The resources are software components which can be reused in concrete reference implementations. The service specification is conducted with OpenAPI, allowing use to provide it in a very general form that is independent of the framework or computer language in which the services can be specified. Note that OpenAPI defines services in REST. The previous version only specified the resource objects.

### 3.3 DESIGN BY EXAMPLE

---

To accelerate discussion among the NBD-PWG members, contributors to this document are encouraged to also provide the NBD-PWG with examples.

### 3.4 VERSION MANAGEMENT

---

Previous work that shaped the current version of this volumes and are documented In GitHub [15] with prior versions of Volume 8 [16][17] and Cloudmesh [18] in support of the NIST Big Data Architecture Framework [1].

During the design phase and development period of each version of this document, enhancements are managed through GitHub and community contributions are managed via GitHub issues. This allows preservation of the history of this document. When a new version is ready, the version will be tagged in GitHub. Older versions will, through this process, also be available as historical documents. Discussions about objects in written form are communicated as GitHub issues.

### 3.5 INTERFACE COMPLIANCY

---

Due to the easy extensibility of the resource objects specified in this document and their

interfaces, it is important to introduce a terminology that allows the definition of interface compliancy. We define three levels of interface compliance as follows:

- Full Compliance: These are reference implementations that provide full compliance to the objects defined in this document. A version number is added to assure that the snapshot in time of the objects is associated with the version. A full compliant framework implements all objects.
- Partial Compliance: These are reference implementations that provide partial compliance to the objects defined in this document. A version number will be added to assure that the snapshot in time of the objects is associated with the version. This reference implementation implements a partial list of the objects and interfaces. A document is to be added that specifies the differences to a full compliant implementation.
- Extended Compliance: In addition to full and partial compliance additional resources can be identified while documenting additional resource objects and interfaces that are not included in the current specification. The extended compliance document can lead to additional improvements of the current specification.

## 3.6 REFERNCE IMPLEMENTATIONS

Documents generated during a reference implementation can be forwarded to the Reference Architecture Subgroup for further discussion and for possible future modifications based on additional practical user feedback.

## 4 SPECIFICATION

The specifications in this section are provided through an automated document creation process using the actual OpenAPI specifications yaml files as the source. All OpenAPI specifications located in the cloudmesh/cloudmesh-nist/spec/ directory in GitHub [19].

Limitations of the current implementation are as follows. It is a demonstration that showcases the generation of a fully functioning REST service based on the specifications provided in this document. However, it is expected that scalability, distribution of services, and other advanced options need to be addressed based on application requirements.

### 4.1 LIST OF SPECIFICATIONS

---

The following table lists the current set of resource objects that are defined in this draft. Additional objects are also available in GitHub [19].

[Table 1](#) shows the list of currently included specification in this version of the document.

Table 1: Specifications

Service	Version	Date	Reference	Section
Alias	3.2.0	14-06-2019		<a href="#">Section 4.5.2</a>
Database	3.2.0	08-06-2019		<a href="#">Section 4.6.3</a>
Default	3.2.0	14-06-2019		<a href="#">Section 4.5.4</a>
File	3.2.0	14-06-2019		<a href="#">Section 4.6.1</a>
Flavor	3.2.0	08-06-2019		<a href="#">Section 4.8.2</a>
Image	3.2.0	08-06-2019		<a href="#">Section 4.8.1</a>
Nic	3.2.0	08-06-2019		<a href="#">Section 4.8.5</a>
Organization	3.2.0	14-06-2019		<a href="#">Section 4.4.1</a>
Public Key Store	3.2.0	14-06-2019		<a href="#">Section 4.4.3</a>
Replica	3.2.0	14-06-2019		<a href="#">Section 4.6.2</a>
Reservation	3.2.0	14-06-2019		<a href="#">Section 4.11.1</a>
Scheduler	3.2.0	08-06-2019		<a href="#">Section 4.7.2</a>
Secgroup	3.2.0	08-06-2019		<a href="#">Section 4.8.4</a>
Timestamp	3.2.0	14-06-2019		<a href="#">Section 4.5.1</a>
User	3.2.0	14-06-2019		<a href="#">Section 4.4.2</a>
Variables	3.2.0	14-06-2019		<a href="#">Section 4.5.3</a>
Virtual Cluster	3.2.0	08-06-2019		<a href="#">Section 4.7.1</a>

Virtual Directory	3.2.0	14-06-2019		<a href="#">Section 4.6.4</a>
Virtual Machine	3.2.0	08-06-2019		<a href="#">Section 4.8.3</a>
Containers	3.2.0	14-06-2019		<a href="#">Section 4.9.1</a>
Deployment	3.2.0	08-06-2019		<a href="#">Section 4.13.1</a>
Filter	3.2.0	08-06-2019		<a href="#">Section 4.12.2</a>
Microservice	3.2.0	14-06-2019		<a href="#">Section 4.10.1</a>
Stream	3.2.0	08-06-2019		<a href="#">Section 4.12.1</a>

[Figure 3](#) shows the provider view of the specification resources.




Figure 3: Provider view

[Figure 4](#) shows the resources view of the specification resources.




Figure 4: Resource view

## 4.2 AUTHENTICATION

---

Mechanisms are not included in this specification to manage authentication to external services. However, the working group has shown multiple solutions to this as part of cloudmesh. This includes the possibility of a

- **Local configuration file:** A configuration file is managed locally to allow access to the clouds. It is the designer's responsibility not to expose such credentials.
- **Session based authentication:** No passwords are stored in the configuration file and access is granted on a per session basis where the password needs to be entered.
- **Service based authentication:** The authentication is delegated to an external process. The service that acts on behalf of the user needs to have access to the appropriate cloud provider credentials

An example for a configuration file is provided at [20].

## 4.3 STATUS CODES AND ERROR RESPONSES

---

In case of an error or a successful response, the response header contains a HTTP code (see <https://tools.ietf.org/html/rfc7231>). The response body usually contains the following:

- The HTTP response code;
- An accompanying message for the HTTP response code; and
- A field or object where the error occurred.

Table 1: HTTP Response Codes

HTTP Response	Operation D	escription
200 Ok	GET, PUT, DELETE	No error, operation successful.
201 Created	POST	Successful creation of a resource.
204 No Content	GET, PUT, DELETE	Successful but no content.
400 Bad Request	GET, POST, PUT, DELETE	The request could not be understood.
401 Unauthorized	GET, POST, PUT, DELETE	User must authorize.
403 Forbidden	GET, POST, PUT, DELETE	The request has been refused due to authorization failure.

---

404 Not Found	GET, POST, PUT, DELETE	The requested resource could not be found.
405 Not Allowed	GET, POST, PUT, DELETE	The method is not allowed on the resource.
500 Server Error	GET, POST PUT	Internal Server error.

---

In the specification such responses are indicated and if a simple response is returned the term **Message** is used.

## 4.4 IDENTITY

---

As part of services an identity often needs to be specified. In addition, such persons [21] are often part of groups. Thus, three important terms related to the identity are distinguished as follows:

- Organization: The information representing an Organization that manages a Big Data Service ([Section 4.4.1](#))
- Group: A group that a person may belong to that is important to define access to services (included in [Section 4.4.1](#))
- User: The information identifying the profile of a person ([Section 4.4.2](#))

### 4.4.1 Organization

An important concept in many services is the management of a group of users in an organization. Within an organization we distinguish different groups of users. Groups can be used to characterize roles users can fulfill. Users can belong to multiple groups. Such groups can also be used to specify access rights to services.

#### 4.4.1.1 Schema Organization

[Reference:](#) 

---

Property	Type	Description
name	string	Name of the organization
users	array[User]	List of users

---

#### 4.4.1.2 Schema Group

[Reference:](#) 

---

Property	Type	Description
name	string	The name of the group
description	string	The description of the group
users	array[string]	The user names that are members of the group

#### 4.4.1.3 Paths

HTTP	Path	Summary
get	/organization	Returns a list of organizations
get	/organization/{name}	Returns the named organization
put	/organization/{name}	Uploads an organization to the list of organizations
delete	/organization/{name}	Deletes the named organization
get	/organization/{name}/user	Returns all users of the organization
get	/organization/{name}/user/{user}	Returns the specific user of that organization
put	/organization/{name}/user/{user}	Updates or adds a user in the organization
delete	/organization/{name}/user/{user}	Delete an user in the organization
get	/organization/{name}/group/	Returns all group names
get	/organization/{name}/group/{group}	Returns the specific group of that organization
put	/organization/{name}/group/{group}	Updates or adds a group in the organization
delete	/organization/{name}/group/{group}	Delete a group in the organization
put	/organization/{name}/group/{group}/{user}	Updates or adds a user name to the group
delete	/organization/{name}/group/{group}/{user}	Delete a user in the group

##### 4.4.1.3.1 /organization

#### 4.4.1.3.1.1 GET /organization

Returns a list of all organizations

Responses

Code	Description	Schema
200	The list of organizations	array[ <a href="#">Organization</a> ]
401	Not authorized	String

#### 4.4.1.3.2 /organization/{name}

##### 4.4.1.3.2.1 GET /organization/{name}

Returns an organization by name

Responses

Code	Description	Schema
200	Retruning the information of the organization	<a href="#">Organization</a>
401	Not authorized	String
404	The named organization could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the organization	True	String

##### 4.4.1.3.2.2 PUT /organization/{name}

Uploads an organization to the list of organizations

Responses

Code	Description	Schema
200	Organization created or updated	String
401	Not authorized	String
404	The organization could not be found	String

## Request Body

Located in	Description	Required	Schema
Body	The organization to be uploaded	True	<a href="#">Organization</a>

4.4.1.3.2.3 DELETE /organization/{name}

Deletes an organization by name

## Responses

Code	Description	Schema
200	Deletion successful	String
401	Not authorized	String
404	The named organization could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the organization	True	String

4.4.1.3.3 /organization/{name}/user

4.4.1.3.3.1 GET /organization/{name}/user

Returns all users of the organization

## Responses

Code	Description	Schema
200	The organization	<a href="#">Organization</a>
401	Not authorized	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the organization	True	String

4.4.1.3.4 /organization/{name}/user/{user}

#### 4.4.1.3.4.1 GET /organization/{name}/user/{user}

Returns the specific user of that organization

#### Responses

Code	Description	Schema
200	The user	<a href="#">User</a>
401	Not authorized	String
404	The organization or user could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the organization	True	String
user	path	The user name	True	String

#### 4.4.1.3.4.2 PUT /organization/{name}/user/{user}

Updates or adds a user in the organization

#### Responses

Code	Description	Schema
200	User added sucessfully	String
401	Not authorized	String
404	The organization or user could not be found\	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the organization	True	String
user	path	The user name	True	String

#### Request Body

Located in	Description	Required	Schema
Body	The user to be uploaded	True	<a href="#">User</a>

4.4.1.3.4.3 DELETE /organization/{name}/user/{user}

Delete an user in the organization

Responses

Code	Description	Schema
200	Deletion successful	String
401	Not authorized	String
404	The organization or user could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the organization	True	String
user	path	The user name	True	String

4.4.1.3.5 /organization/{name}/group/

4.4.1.3.5.1 GET /organization/{name}/group/

Returns all group names

Responses

Code	Description	Schema
200	Returning the information of the group	array[String]
400	No group found	String
401	Not authorized	String
404	The organization or group could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the organization	True	String

4.4.1.3.6 /organization/{name}/group/{group}

4.4.1.3.6.1 GET /organization/{name}/group/{group}

Returns the specific group of that organization

#### Responses

Code	Description	Schema
200	The group	<a href="#">Group</a>
401	Not authorized	String
404	The organization or group could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the organization	True	String
group	path	The group name	True	String

4.4.1.3.6.2 PUT /organization/{name}/group/{group}

Updates or adds a group in the organization

#### Responses

Code	Description	Schema
200	Group added sucessfully	String
401	Not authorized	String
404	The organization or group could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the group	True	String
group	path	The group name	True	String

4.4.1.3.6.3 DELETE /organization/{name}/group/{group}

Delete a group in the organization

#### Responses

Code	Description	Schema

200	Deletion successful	String
401	Not authorized	String
404	The organization or group could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the organization	True	String
group	path	The group name	True	String

4.4.1.3.7 /organization/{name}/group/{group}/{user}

4.4.1.3.7.1 PUT /organization/{name}/group/{group}/{user}

Updates or adds a user name to the group

#### Responses

Code	Description	Schema
200	User added sucessfully	String
401	Not authorized	String
404	The organization, group, or user could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the group	True	String
group	path	The group name	True	String
user	path	The user name	True	String

4.4.1.3.7.2 DELETE /organization/{name}/group/{group}/{user}

Delete a user in the group

#### Responses

Code	Description	Schema
200	Deletion successful	String

401	Not authorized	String
404	The organization, group, or user could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the organization	True	String
group	path	The group name	True	String
user	path	The user name	True	String

### 4.4.1.4 organization.yaml

```

openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 14-06-2019
  x-status: defined
  title: Organization
  description: |- 
    An important concept in many services is the management of a group
    of users in an organization. Within an organization we distinguish
    different groups of users. Groups can be used to characterize roles
    users can fulfill. Users can belong to multiple groups. Such groups can
    also be used to specify access rights to services.

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: NIST BDRA Interface Subgroup
    url: https://cloudmesh-community.github.io/nist/spec/
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /organization:
    get:
      tags:
        - Organization
      summary: Returns a list of organizations
      description: Returns a list of all organizations
      operationId: cloudmesh.organization.list
      responses:
        '200':
          description: The list of organizations
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Organization'
        '401':
          description: Not authorized
  /organization/{name}:
    get:
      tags:
        - Organization
      summary: Returns the named organization
      description: Returns an organization by name
      operationId: cloudmesh.organization.find_by_name
      parameters:
        - name: name
          in: path
          required: true
          schema:
            type: string
            description: The name of the organization
      responses:
        '200':
          description: Retruning the information of the organization
          content:

```

```

application/json:
  schema:
    $ref: '#/components/schemas/Organization'
'401':
  description: Not authorized
'404':
  description: The named organization could not be found
put:
tags:
- Organization
summary: Uploads an organization to the list of organizations
description: Uploads an organization to the list of organizations
operationId: cloudmesh.organization.add
requestBody:
  description: The organization to be uploaded
  required: true
  content:
    application/json:
      schema:
        $ref: '#/components/schemas/Organization'
responses:
'200':
  description: Organization created or updated
'401':
  description: Not authorized
'404':
  description: The organization could not be found
delete:
tags:
- Organization
summary: Deletes the named organization
description: Deletes an organization by name
operationId: cloudmesh.organization.delete_by_name
parameters:
- name: name
  in: path
  required: true
  schema:
    type: string
    description: The name of the organization
responses:
'200':
  description: Deletion successful
'401':
  description: Not authorized
'404':
  description: The named organization could not be found
/organization/{name}/user:
get:
tags:
- Organization
summary: Returns all users of the organization
description: Returns all users of the organization
operationId: cloudmesh.organization.user.list
parameters:
- name: name
  in: path
  required: true
  schema:
    type: string
    description: The name of the organization
responses:
'200':
  description: The organization
  content:
    application/json:
      schema:
        $ref: "#/components/schemas/Organization"
'401':
  description: Not authorized
/organization/{name}/user/{user}:
get:
tags:
- Organization
summary: Returns the specific user of that organization
description: Returns the specific user of that organization
operationId: cloudmesh.organization.user.get_by_name
parameters:
- name: name
  in: path
  required: true
  schema:
    type: string
    description: The name of the organization
- name: user
  description: The user name
  in: path
  required: true
  schema:

```

```

    type: string
responses:
  '200':
    description: The user
    content:
      application/json:
        schema:
          $ref: "user.yaml#/components/schemas/User"
  '401':
    description: Not authorized
  '404':
    description: The organization or user could not be found
put:
  tags:
    - Organization
  summary: Updates or adds a user in the organization
  description: Updates or adds a user in the organization
  operationId: cloudmesh.organization.user.add
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the organization
    - name: user
      in: path
      required: true
      schema:
        type: string
      description: The user name
  requestBody:
    description: The user to be uploaded
    required: true
    content:
      application/json:
        schema:
          $ref: 'user.yaml#/components/schemas/User'
responses:
  '200':
    description: User added sucessfully
  '401':
    description: Not authorized
  '404':
    description: The organization or user could not be found\
delete:
  tags:
    - Organization
  summary: Delete an user in the organization
  description: Delete an user in the organization
  operationId: cloudmesh.organization.user.delete
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the organization
    - name: user
      in: path
      required: true
      schema:
        type: string
      description: The user name
  responses:
    '200':
      description: Deletion successful
    '401':
      description: Not authorized
    '404':
      description: The organization or user could not be found
/organization/{name}/group/:
get:
  tags:
    - Organization
  summary: Returns all group names
  description: Returns all group names
  operationId: cloudmesh.organization.group.list
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the organization
  responses:
    '200':
      description: Returning the information of the group
      content:

```

```

application/json:
  schema:
    type: array
    items:
      type: string
'400':
  description: No group found
'401':
  description: Not authorized
'404':
  description: The organization or group could not be found
/organization/{name}/group/{group}:
get:
tags:
  - Organization
summary: Returns the specific group of that organization
description: Returns the specific group of that organization
operationId: cloudmesh.organization.group.get_by_name
parameters:
  - name: name
    in: path
    required: true
    schema:
      type: string
    description: The name of the organization
  - name: group
    in: path
    required: true
    schema:
      type: string
    description: The group name
responses:
  '200':
    description: The group
    content:
      application/json:
        schema:
          $ref: "#/components/schemas/Group"
  '401':
    description: Not authorized
  '404':
    description: The organization or group could not be found
put:
tags:
  - Organization
summary: Updates or adds a group in the organization
description: Updates or adds a group in the organization
operationId: cloudmesh.organization.group.add
parameters:
  - name: name
    in: path
    required: true
    schema:
      type: string
    description: The name of the group
  - name: group
    in: path
    required: true
    schema:
      type: string
    description: The group name
responses:
  '200':
    description: Group added sucessfully
  '401':
    description: Not authorized
  '404':
    description: The organization or group could not be found
delete:
tags:
  - Organization
summary: Delete a group in the organization
description: Delete a group in the organization
operationId: cloudmesh.organization.groop.delete
parameters:
  - name: name
    in: path
    required: true
    schema:
      type: string
    description: The name of the organization
  - name: group
    in: path
    required: true
    schema:
      type: string
    description: The group name
responses:
  '200':

```

```

        description: Deletion successful
    '401':
        description: Not authorized
    '404':
        description: The organization or group could not be found
/organization/{name}/group/{group}/{user}:
  put:
    tags:
      - Organization
    summary: Updates or adds a user name to the group
    description: Updates or adds a user name to the group
    operationId: cloudmesh.organization.group.user.add
    parameters:
      - name: name
        in: path
        required: true
        schema:
          type: string
        description: The name of the group
      - name: group
        in: path
        required: true
        schema:
          type: string
      - name: user
        in: path
        required: true
        schema:
          type: string
    responses:
      '200':
        description: User added sucessfully
      '401':
        description: Not authorized
      '404':
        description: The organization, group, or user could not be found
  delete:
    tags:
      - Organization
    summary: Delete a user in the group
    description: Delete a user in the group
    operationId: cloudmesh.organization.greop.delete.user
    parameters:
      - name: name
        in: path
        required: true
        schema:
          type: string
        description: The name of the organization
      - name: group
        in: path
        required: true
        schema:
          type: string
      - name: user
        in: path
        required: true
        schema:
          type: string
    responses:
      '200':
        description: Deletion successful
      '401':
        description: Not authorized
      '404':
        description: The organization, group, or user could not be found
components:
  schemas:
    Organization:
      type: object
      properties:
        name:
          description: Name of the organization
          type: string
        users:
          description: List of users
          type: array
          items:
            $ref: "user.yaml#/components/schemas/User"
    Group:
      type: object
      description: The groups
      properties:
        name:
          type: string

```

```

        description: The name of the group
        description:
        type: string
        description: The description of the group
      users:
        description: The user names that are members of the group
        type: array
        items:
          type: string

```

## 4.4.2 User

Services need to specify which users have access to them. User information can be reused in other services and organized in a virtual organization. A user can be added to a named list of users within this organization. A group associated with the user can be used to augment users to be part of one or more groups.

### 4.4.2.1 Schema User

[Reference:](#) 

Property	Type	Description
username	string	The unique username associated with the user
firstname	string	The firstname of the user
lastname	string	The lastname of the user
email	string	The email of the user
comment	string	A comment regarding the user
publickey	string	The public key of the user

### 4.4.2.2 Paths

HTTP	Path	Summary
get	/user	Returns a list of users
put	/user	Uploads a user to the list of users
get	/user/{name}	Returns the named user
delete	/user/{name}	Deletes the named user

#### 4.4.2.2.1 /user

##### 4.4.2.2.1.1 GET /user

Returns a list of all users

## Responses

Code	Description	Schema
200	The list of users	array[ <a href="#">User</a> ]
400	No users found	String
401	Not authorized	String

4.4.2.2.1.2 PUT /user

Uploads a user to the list of users

## Responses

Code	Description	Schema
200	User updated	String
400	Error updating user.	String
401	Not authorized	String

## Request Body

Located in	Description	Required	Schema
Body	The user to be uploaded	True	<a href="#">User</a>

4.4.2.2.2 /user/{name}

4.4.2.2.2.1 GET /user/{name}

Returns an user by name

## Responses

Code	Description	Schema
200	Returning the information of the user	<a href="#">User</a>
400	No user found	String
401	Not authorized	String
404	The named user could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the user	True	String

#### 4.4.2.2.2 DELETE /user/{name}

Deletes an user by name

#### Responses

Code	Description	Schema
200	Deletion successful	String
400	No user found	String
401	Not authorized	String
404	The named user could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the user	True	String

#### 4.4.2.3 user.yaml

```

openapi: "3.0.2"
info:
  version: "3.2.0"
  x-date: 14-06-2019
  x-status: defined
  title: User
  description: |- 
    Services need to specify which users have access to them. User
    information can be reused in other services and organized in a virtual
    organization. A user can be added to a named list of users within this
    organization. A group associated with the user can be used to augment
    users to be part of one or more groups.

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: Cloudmesh User
    url: https://cloudmesh-community.github.io/nist/spec/
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /user:
    get:
      tags:
        - User
      summary: Returns a list of users
      description: Returns a list of all users
      operationId: cloudmesh.user.list
      responses:
        '200':
          description: The list of users
          content:
            application/json:
              schema:

```

```

        type: array
        items:
          $ref: '#/components/schemas/User'
        '400':
          description: No users found
        '401':
          description: Not authorized
      put:
        tags:
          - User
        summary: Uploads a user to the list of users
        description: Uploads a user to the list of users
        operationId: cloudmesh.user.add
        requestBody:
          description: The user to be uploaded
          required: true
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/User'
        responses:
          '200':
            description: User updated
          '400':
            description: Error updating user.
          '401':
            description: Not authorized
    /user/{name}:
      get:
        tags:
          - User
        summary: Returns the named user
        description: Returns an user by name
        operationId: cloudmesh.user.find_by_name
        parameters:
          - name: name
            in: path
            required: true
            schema:
              type: string
            description: The name of the user
        responses:
          '200':
            description: Returning the information of the user
            content:
              application/json:
                schema:
                  $ref: '#/components/schemas/User'
          '400':
            description: No user found
          '401':
            description: Not authorized
          '404':
            description: The named user could not be found
      delete:
        tags:
          - User
        summary: Deletes the named user
        description: Deletes an user by name
        operationId: cloudmesh.user.delete_by_name
        parameters:
          - name: name
            in: path
            required: true
            schema:
              type: string
            description: The name of the user
        responses:
          '200':
            description: Deletion successful
          '400':
            description: No user found
          '401':
            description: Not authorized
          '404':
            description: The named user could not be found
  components:
    schemas:
      User:
        type: object
        properties:
          username:
            type: string
            description: The unique username associated with the user
          firstname:
            type: string
            description: The firstname of the user
          lastname:
            type: string

```

```

description: The lastname of the user
email:
  type: string
  description: The email of the user
comment:
  type: string
  description: A comment regarding the user
publickey:
  type: string
  description: The public key of the user

```

### 4.4.3 Public Key Store

Many services and frameworks use Secure Shell (SSH) keys to authenticate. This service allows the convenient storage of the public keys.

#### 4.4.3.1 Schema Key

Reference: 

Property	Type	Description
name	string	The name of the public key
value	string	The value of the public key
kind	string	The key kind such as rsa, dsa
group	string	An optional group name allowing to group keys to create custom key groups within the public key store
comment	string	A comment for the public key
uri	string	The uri of the public key if any
fingerprint	string	The fingerprint of the public key

#### 4.4.3.2 Paths

HTTP	Path	Summary
get	/key	Returns a list of keys
put	/key	Set a key
get	/key/{name}	Returns the named key
delete	/key/{name}	Deletes the named key

##### 4.4.3.2.1 /key

###### 4.4.3.2.1.1 GET /key

Returns a list of all keys

## Responses

Code	Description	Schema
200	The list of keys	array[ <a href="#">Key</a> ]
400	No key found	String
401	Not authorized	String

4.4.3.2.1.2 PUT /key

Sets the named key

## Responses

Code	Description	Schema
200	Key updated	String
400	Error updating key.	String
401	Not authorized	String

## Request Body

Located in	Description	Required	Schema
Body	The new key to create	True	<a href="#">Key</a>

4.4.3.2.2 /key/{name}

4.4.3.2.2.1 GET /key/{name}

Returns a key by name

## Responses

Code	Description	Schema
200	Returning the information of the key	<a href="#">Key</a>
400	No key found	String
401	Not authorized	String
404	The named key could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the key	True	String

#### 4.4.3.2.2.2 DELETE /key/{name}

Deletes a key by name

#### Responses

Code	Description	Schema
200	Deletion successful	String
400	No key found	String
401	Not authorized	String
404	The named key could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the key	True	String

#### 4.4.3.3 publickeystore.yaml

```

openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 14-06-2019
  x-status: defined
  title: Public Key Store
  description: |- 
    Many services and frameworks use Secure Shell (SSH) keys to
    authenticate. This service allows the convenient storage of the
    public keys.

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: NIST BDRA Interface Subgroup
    url: https://cloudmesh-community.github.io/nist
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /key:
    get:
      tags:
        - Key
      summary: Returns a list of keys
      description: Returns a list of all keys
      operationId: cloudmesh.key.list
      responses:
        '200':
          description: The list of keys
          content:
            application/json:
              schema:
                type: array
                items:

```

```

        $ref: '#/components/schemas/Key'
    '400':
        description: No key found
    '401':
        description: Not authorized
  put:
    tags:
      - Key
    summary: Set a key
    description: Sets the named key
    operationId: cloudmesh.key.add
    requestBody:
      description: The new key to create
      required: true
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/Key'
  responses:
    '200':
      description: Key updated
    '400':
      description: Error updating key.
    '401':
      description: Not authorized
/key/{name}:
  get:
    tags:
      - Key
    summary: Returns the named key
    description: Returns a key by name
    operationId: cloudmesh.key.find_by_name
    parameters:
      - name: name
        in: path
        required: true
        schema:
          type: string
          description: The name of the key
    responses:
      '200':
        description: Returning the information of the key
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Key'
      '400':
        description: No key found
      '401':
        description: Not authorized
      '404':
        description: The named key could not be found
  delete:
    tags:
      - Key
    summary: Deletes the named key
    description: Deletes a key by name
    operationId: cloudmesh.key.delete_by_name
    parameters:
      - name: name
        in: path
        required: true
        schema:
          type: string
          description: The name of the key
    responses:
      '200':
        description: Deletion successful
      '400':
        description: No key found
      '401':
        description: Not authorized
      '404':
        description: The named key could not be found
components:
  schemas:
    Key:
      type: object
      description: the public key
      properties:
        name:
          type: string
          description: The name of the public key
        value:
          type: string
          description: The value of the public key
      kind:
        type: string
        description: The key kind such as rsa, dsa

```

```

group:
  type: string
  description: An optional group name allowing to group keys to create
               custom key groups within the public key store
comment:
  type: string
  description: A comment for the public key
uri:
  type: string
  description: The uri of the public key if any
fingerprint:
  type: string
  description: The fingerprint of the public key

```

## 4.5 GENERAL RESOURCES

---

### 4.5.1 Timestamp

Data often needs to be time stamped to indicate when it has been accessed, created, or modified. All objects defined in this document will have, in their final version, a timestamp. The date-time string is defined in [RFC3339](#).

#### 4.5.1.1 Schema Timestamp

Reference: 

Property	Type	Description
accessed	string(date-time)	The time stamp when the object was last accessed
created	string(date-time)	The time stamp when the object was created
modified	string(date-time)	The time stamp when the object was modified

#### 4.5.1.2 Paths

HTTP	Path	Summary
get	/timestamp	Returns the time

#### 4.5.1.2.1 /timestamp

##### 4.5.1.2.1.1 GET /timestamp

Returns the time to be used in a timestamp

Responses

---

Code	Description	Schema
200	The current time and date	string

#### 4.5.1.3 timestamp.yaml

```

openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 14-06-2019
  x-status: defined
  title: Timestamp
  description: |- 
    Data often needs to be time stamped to indicate when it has been
    accessed, created, or modified. All objects defined in this
    document will have, in their final version, a timestamp.
    The date-time string is defined in
    [RFC3339](https://xml2rfc.ietf.org/public/rfc/html/rfc3339.html#anchor14).

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: NIST BDRA Interface Subgroup
    url: https://cloudmesh-community.github.io/nist/spec/
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /timestamp:
    get:
      summary: Returns the time
      description: Returns the time to be used in a timestamp
      responses:
        '200':
          description: The current time and date
          content:
            application/json:
              schema:
                type: string
                example: 1985-04-12T23:20:50.52Z
components:
  schemas:
    Timestamp:
      type: object
      description: the timestamp
      properties:
        accessed:
          type: string
          format: date-time
          description: The time stamp when the object was last accessed
          example: 1985-04-12T23:20:50.52Z
        created:
          type: string
          format: date-time
          description: The time stamp when the object was created
          example: 1985-04-12T23:20:50.52Z
        modified:
          type: string
          format: date-time
          description: The time stamp when the object was modified
          example: 1985-04-12T23:20:50.52Z

```

#### 4.5.2 Alias

Often a user has the desire to create a custom name for an object. An alias allows to do that while assosication a user defined name or **alias** to a previously used name. The aliases could be shared with other users. A name could have one or more aliases.

##### 4.5.2.1 Schema Alias

Reference: 

Property	Type	Description
name	string	The name of the alias
source	string	The original object name

#### 4.5.2.2 Paths

HTTP	Path	Summary
get	/alias	Returns a list of aliases
put	/alias	Set an alias
get	/alias/{name}	Returns the named alias
delete	/alias/{name}	Deletes the named alias

##### 4.5.2.2.1 /alias

###### 4.5.2.2.1.1 GET /alias

Returns a list of all aliases

###### Responses

Code	Description	Schema
200	The list of aliases	array[ <a href="#">Alias</a> ]
400	No alias found	String
401	Not authorized	String

###### 4.5.2.2.1.2 PUT /alias

Sets the named alias

###### Responses

Code	Description	Schema
200	Alias updated	String
400	Error updating alias	String
401	Not authorized	String

###### Request Body

Located in	Description	Required	Schema
Body	The new alias to create	True	<a href="#">Alias</a>

4.5.2.2.2 /alias/{name}

4.5.2.2.2.1 GET /alias/{name}

Returns an alias by name

Responses

Code	Description	Schema
200	Returning the information of the alias	<a href="#">Alias</a>
400	No alias found	String
401	Not authorized	String
404	The named alias could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the alias	True	String

4.5.2.2.2 DELETE /alias/{name}

Deletes an alias by name

Responses

Code	Description	Schema
200	Deletion successful	String
400	No alias found	String
401	Not authorized	String
404	The named alias could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the alias	True	String

#### 4.5.2.3 alias.yaml

```
openapi: '3.0.2'
info:
  version: 3.2.0
  x-date: 14-06-2019
  x-status: defined
  title: Alias
  description: |-  

    Often a user has the desire to create a custom name for an object. An  

    alias allows to do that while while assosication a user defined name or  

    *alias* to a previously used name. The aliases could be shared with other  

    users. A name could have one or more aliases.  

  termsOfService: 'https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt'  

  contact:  

    name: NIST BDRA Interface Subgroup  

    url: https://cloudmesh-community.github.io/nist/spec/  

  license:  

    name: Apache 2.0  

    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt  

servers:  

  - url: /cloudmesh/v3  

paths:  

  /alias:  

    get:  

      tags:  

        - Alias  

      summary: Returns a list of aliases  

      description: Returns a list of all aliases  

      operationId: cloudmesh.alias.list  

      responses:  

        '200':  

          description: The list of aliases  

          content:  

            application/json:  

              schema:  

                type: array  

                items:  

                  $ref: '#/components/schemas/Alias'  

        '400':  

          description: No alias found  

        '401':  

          description: Not authorized  

    put:  

      tags:  

        - Alias  

      summary: Set an alias  

      description: Sets the named alias  

      operationId: cloudmesh.alias.add  

      requestBody:  

        description: The new alias to create  

        required: true  

        content:  

          application/json:  

            schema:  

              $ref: '#/components/schemas/Alias'  

      responses:  

        '200':  

          description: Alias updated  

        '400':  

          description: Error updating alias  

        '401':  

          description: Not authorized  

  /alias/{name}:  

    get:  

      tags:  

        - Alias  

      summary: Returns the named alias  

      description: Returns an alias by name  

      operationId: cloudmesh.alias.find_by_name  

      parameters:  

        - name: name  

          in: path  

          required: true  

          schema:  

            type: string  

          description: The name of the alias  

      responses:  

        '200':  

          description: Returning the information of the alias  

          content:  

            application/json:  

              schema:  

                $ref: '#/components/schemas/Alias'  

        '400':
```

```

        description: No alias found
    '401':
        description: Not authorized
    '404':
        description: The named alias could not be found
delete:
tags:
- Alias
summary: Deletes the named alias
description: Deletes an alias by name
operationId: cloudmesh.alias.delete_by_name
parameters:
- name: name
  in: path
  required: true
  schema:
    type: string
  description: The name of the alias
responses:
'200':
    description: Deletion successful
'400':
    description: No alias found
'401':
    description: Not authorized
'404':
    description: The named alias could not be found
components:
schemas:
Alias:
  type: object
  description: the alias
  properties:
    name:
      type: string
      description: The name of the alias
    source:
      type: string
      description: The original object name

```

### 4.5.3 Variables

Variables are a simple string key value storage to store simple values. Each variable can have a datatype, so that it can be used for serialization into other formats. Internally they are stored as strings.

#### 4.5.3.1 Schema Variable

[Reference:](#) 

Property	Type	Description
name	string	Name of the variable
value	string	Type of the variable
description	string	A description of the variable
datatype	string	The data type of the variable which can be used for serialization

#### 4.5.3.2 Paths

HTTP	Path	Summary
------	------	---------

get	/variable	Returns a the variables
put	/variable	Set the value of a variable
get	/variable/{name}	Returns the named variable
delete	/variable/{name}	Deletes the named variable

#### 4.5.3.2.1 /variable

##### 4.5.3.2.1.1 GET /variable

Returns the variables

Responses

Code	Description	Schema
200	The list of variables	array[ <a href="#">Variable</a> ]
400	No variable found	String

##### 4.5.3.2.1.2 PUT /variable

Set the value of the named variable

Responses

Code	Description	Schema
200	Variable updated	String
400	Error updating variable	String
401	Not authorized	String

Request Body

Located in	Description	Required	Schema
Body	The variable and its value	True	<a href="#">Variable</a>

#### 4.5.3.2.2 /variable/{name}

##### 4.5.3.2.2.1 GET /variable/{name}

Returns the named variable

## Responses

Code	Description	Schema
200	Returning the information of the variable	<a href="#">Variable</a>
400	No variable found	String
401	Not authorized	String
404	The named variable could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the variable	True	String

4.5.3.2.2.2 DELETE /variable/{name}

Deletes a variable by name

## Responses

Code	Description	Schema
200	Deletion successful	String
400	No variable found	String
401	Not authorized	String
404	The named variable could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the variable	True	String

4.5.3.3 variables.yaml

```
openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 14-06-2019
  x-status: defined
  title: Variables
  description: |-  
    Variables are a simple string key value storage to store simple  
    values. Each variable can have a datatype, so that it can be used for  
    serialization into other formats. Internally they are stored as strings.
```

```

termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
contact:
  name: NIST BDRA Interface Subgroup
  url: https://cloudmesh-community.github.io/nist/spec/
license:
  name: Apache 2.0
  url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /variable:
    get:
      tags:
        - Variable
      summary: Returns a the variables
      description: Returns the variables
      operationId: cloudmesh.variable.list
      responses:
        '200':
          description: The list of variables
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Variable'
        '400':
          description: No variable found
    put:
      tags:
        - Variable
      summary: Set the value of a variable
      description: Set the value of the named variable
      operationId: cloudmesh.variable.add
      requestBody:
        description: The variable and its value
        required: true
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/Variable'
      responses:
        '200':
          description: Variable updated
        '400':
          description: Error updating variable
        '401':
          description: Not authorized
  /variable/{name}:
    get:
      tags:
        - Variable
      summary: Returns the named variable
      description: Returns the named variable
      operationId: cloudmesh.variable.find_by_name
      parameters:
        - name: name
          in: path
          required: true
          schema:
            type: string
            description: The name of the variable
      responses:
        '200':
          description: Returning the information of the variable
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/Variable'
        '400':
          description: No variable found
        '401':
          description: Not authorized
        '404':
          description: The named variable could not be found
    delete:
      tags:
        - Variable
      summary: Deletes the named variable
      description: Deletes a variable by name
      operationId: cloudmesh.variable.delete_by_name
      parameters:
        - name: name
          in: path
          required: true
          schema:
            type: string
            description: The name of the variable
      responses:
        '200':

```

```

        description: Deletion successful
'400':
    description: No variable found
'401':
    description: Not authorized
'404':
    description: The named variable could not be found
components:
schemas:
Variable:
type: object
description: the variables
properties:
name:
    type: string
    description: Name of the variable
value:
    type: string
    description: Type of the variable
description:
    type: string
    description: A description of the variable
datatype:
    type: string
    description: The data type of the variable which can be used for
    serialization

```

#### 4.5.4 Default

A default is a special variable that has a context associated with it. This allows one to define values that can be easily retrieved based on the associated context. For example, a default could be the image name for a cloud where the context is defined by the cloud name. In addition to the context, the service name is also specified since a service could have multiple contexts. To be able to define the kind of service there is also a kind attribute.

##### 4.5.4.1 Schema Default

[Reference:](#) 

Property	Type	Description
name	string	The name of the default
value	string	The value of the default
context	string	The context of the default

##### 4.5.4.2 Paths

HTTP	Path	Summary
get	/default	Returns a list of defaults
put	/default	Set a default
get	/default/{name}	Returns the named default
delete	/default/{name}	Deletes the named default

###### 4.5.4.2.1 /default

#### 4.5.4.2.1.1 GET /default

Returns a list of all defaults

Responses

Code	Description	Schema
200	The list of defaults	array[ <a href="#">Default</a> ]
400	No default found	String

#### 4.5.4.2.1.2 PUT /default

Sets the named default

Responses

Code	Description	Schema
200	Default updated	String
400	Error updating default.	String

Request Body

Located in	Description	Required	Schema
Body	The new default to create	True	<a href="#">Default</a>

#### 4.5.4.2.2 /default/{name}

##### 4.5.4.2.2.1 GET /default/{name}

Returns a default by name

Responses

Code	Description	Schema
200	Returning the information of the default	<a href="#">Default</a>
400	No default found	String
404	The named default could not be found	String

Parameters

---

Name	Located in	Description	Required	Schema
name	path	The name of the default	True	String

#### 4.5.4.2.2.2 DELETE /default/{name}

Deletes a default by name

#### Responses

Code	Description	Schema
200	Deletion successful	String
400	No default found	String
404	The named default could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the default	True	String

#### 4.5.4.3 default.yaml

```

openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 14-06-2019
  x-status: defined
  title: Default
  description: |- 
    A default is a special variable that has a context associated with
    it. This allows one to define values that can be easily retrieved
    based on the associated context. For example, a default could be
    the image name for a cloud where the context is defined by the
    cloud name. In addition to the context, the service name is also specified
    since a service could have multiple contexts. To be able to
    define the kind of service there is also a kind attribute.

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: NIST BDRA Interface Subgroup
    url: https://cloudmesh-community.github.io/nist/spec/
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /default:
    get:
      tags:
        - Default
      summary: Returns a list of defaults
      description: Returns a list of all defaults
      operationId: cloudmesh.default.list
      responses:
        '200':
          description: The list of defaults
          content:
            application/json:
              schema:
                type: array

```

```

      items:
        $ref: '#/components/schemas/Default'
    '400':
      description: No default found
  put:
    tags:
      - Default
    summary: Set a default
    description: Sets the named default
    operationId: cloudmesh.default.add
    requestBody:
      description: The new default to create
      required: true
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/Default'
  responses:
    '200':
      description: Default updated
    '400':
      description: Error updating default.
/default/{name}:
  get:
    tags:
      - Default
    summary: Returns the named default
    description: Returns a default by name
    operationId: cloudmesh.default.find_by_name
    parameters:
      - name: name
        in: path
        required: true
        schema:
          type: string
        description: The name of the default
    responses:
      '200':
        description: Returning the information of the default
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Default'
      '400':
        description: No default found
      '404':
        description: The named default could not be found
  delete:
    tags:
      - Default
    summary: Deletes the named default
    description: Deletes a default by name
    operationId: cloudmesh.default.delete_by_name
    parameters:
      - name: name
        in: path
        required: true
        schema:
          type: string
        description: The name of the default
    responses:
      '200':
        description: Deletion successful
      '400':
        description: No default found
      '404':
        description: The named default could not be found
components:
  schemas:
    Default:
      type: object
      description: the defaults
      properties:
        name:
          type: string
          description: The name of the default
          example: "image"
        value:
          type: string
          description: The value of the default
          example: "m1.medium"
        context:
          type: string
          description: The context of the default
          example: "cloud.vm.flavor"

```

## 4.6 DATA MANAGEMENT

---

## 4.6.1 Filestore

A file store is a resource allowing storage of data as a traditional file. Instead of using the name **filestore** we simply use the name **file**. A file store can contain any number of files with additional attributes describing the file. A file store is typically located on the same cloud services. This contrasts virtual directories that are just pointers to files, which could include files located in file stores.

### 4.6.1.1 Schema File

Reference: 

Property	Type	Description
name	string	The name of the file
endpoint	string	The location of the file
checksum	string	The checksum of the file
size	integer	The size of the file in byte
content	string(binary)	the content of the file

### 4.6.1.2 Paths

HTTP	Path	Summary
get	/file	Returns a list of files in the file store
put	/file	Uploads a file to the list of files in the file store
get	/file/{name}	Returns the named file in the file store
delete	/file/{name}	Deletes the named file in the file store

#### 4.6.1.2.1 /file

##### 4.6.1.2.1.1 GET /file

Returns a list of all files

##### Responses

Code	Description	Schema
200	The list of files	array[ <a href="#">File</a> ]
400	No files found	String

#### 4.6.1.2.1.2 PUT /file

Uploads a file to the list of files in the file store

#### Responses

Code	Description	Schema
200	File updated	String
400	Error updating file.	String

#### Request Body

Located in	Description	Required	Schema
Body	The file to be uploaded	True	<a href="#">File</a>

#### 4.6.1.2.2 /file/{name}

##### 4.6.1.2.2.1 GET /file/{name}

Returns an file by name in the file store

#### Responses

Code	Description	Schema
200	Returning the information of the file store	<a href="#">File</a>
400	No file found	String
401	Not authorized	String
404	The named file could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the file	True	String

#### 4.6.1.2.2.2 DELETE /file/{name}

Deletes an file by name

#### Responses

Code	Description	Schema
200	Deletion successful	String
400	No file found	String
401	Not authorized	String
404	The named file could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the file	True	String

### 4.6.1.3 filestore.yaml

```

openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 14-06-2019
  x-status: defined
  title: File
  description: |-
    A file store is a resource allowing storage of data as a traditional file.
    Instead of using the name *filestore* we simply use the name *file*.
    A file store can contain any number of files with additional attributes
    describing the file. An file store is typically located on the same cloud
    services. This contrasts virtual directories that are just pointers to
    files, which could include files located in file stores.

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: NIST BDRA Interface Subgroup
    url: https://cloudmesh-community.github.io/nist/spec/
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /file:
    get:
      tags:
        - File
      summary: Returns a list of files in the file store
      description: Returns a list of all files
      operationId: cloudmesh.file.list
      responses:
        '200':
          description: The list of files
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/File'
        '400':
          description: No files found
    put:
      tags:
        - File
      summary: Uploads a file to the list of files in the file store
      description: Uploads a file to the list of files in the file store
      operationId: cloudmesh.file.add
      requestBody:
        description: The file to be uploaded
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/File'

```

```

responses:
  '200':
    description: File updated
  '400':
    description: Error updating file.

/file/{name}:
get:
  tags:
    - File
  summary: Returns the named file in the file store
  description: Returns an file by name in the file store
  operationId: cloudmesh.file.find_by_name
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the file
  responses:
    '200':
      description: Returning the information of the file store
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/File'
    '400':
      description: No file found
    '401':
      description: Not authorized
    '404':
      description: The named file could not be found
delete:
  tags:
    - File
  summary: Deletes the named file in the file store
  description: Deletes an file by name
  operationId: cloudmesh.file.delete_by_name
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the file
  responses:
    '200':
      description: Deletion successful
    '400':
      description: No file found
    '401':
      description: Not authorized
    '404':
      description: The named file could not be found
components:
schemas:
  File:
    type: object
    description: an object representing a file
    properties:
      name:
        type: string
        description: The name of the file
      endpoint:
        type: string
        description: The location of the file
      checksum:
        type: string
        description: The checksum of the file
      size:
        type: integer
        description: The size of the file in byte
      content:
        type: string
        format: binary
        description: the content of the file

```

## 4.6.2 Replica

In many distributed systems, it is important that a file can be replicated among different

systems to provide faster access. It is important to provide a mechanism to trace the pedigree of the file while pointing to its original source. A replica will point to a file in a file store and store the contents in the file store instead of the replica. The replica is just a pointer.

#### 4.6.2.1 Schema Replica

Reference: 

Property	Type	Description
name	string	The name of the replica
filename	string	The original filename
endpoint	string	The location of the file
checksum	string	The checksum of the file
size	integer	The size of the file in byte

#### 4.6.2.2 Paths

HTTP	Path	Summary
get	/replica	Returns a list of replicas
put	/replica	Uploads a replica to the list of replicas
get	/replica/{name}	Returns the named replica
delete	/replica/{name}	Deletes the named replica

##### 4.6.2.2.1 /replica

###### 4.6.2.2.1.1 GET /replica

Returns a list of all replicas

Responses

Code	Description	Schema
200	The list of replicas	array[ <a href="#">Replica</a> ]
400	No replicas found	String
401	Not authorized	String

###### 4.6.2.2.1.2 PUT /replica

Uploads a replica to the list of replicas

Responses

Code	Description	Schema
200	Replica updated	String
400	Error updating replica.	String
401	Not authorized	String

Request Body

Located in	Description	Required	Schema
Body	The replica to be uploaded	True	<a href="#">Replica</a>

4.6.2.2.2 /replica/{name}

4.6.2.2.1 GET /replica/{name}

Returns an replica by name

Responses

Code	Description	Schema
200	Returning the information of the replica	<a href="#">Replica</a>
400	No replica found	String
401	Not authorized	String
404	The named replica could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the replica	True	String

4.6.2.2.2 DELETE /replica/{name}

Deletes an replica by name

Responses

---

Code	Description	Schema
200	Deletion successful	String
400	No replica found	String
401	Not authorized	String
404	The named replica could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the replica	True	String

### 4.6.2.3 replica.yaml

```

openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 14-06-2019
  x-status: TODO
  title: Replica
  description: |-
    In many distributed systems, it is important that a file can be
    replicated among different systems to provide faster access. It is
    important to provide a mechanism to trace the pedigree of the file
    while pointing to its original source. A replica will point to a file in
    a file store and store the contents in the file store instead of the
    replica. The replica is just a pointer.

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: NIST BDRA Interface Subgroup
    url: https://cloudmesh-community.github.io/nist/spec/
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /replica:
    get:
      tags:
        - Replica
      summary: Returns a list of replicas
      description: Returns a list of all replicas
      operationId: cloudmesh.replica.list
      responses:
        '200':
          description: The list of replicas
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Replica'
        '400':
          description: No replicas found
        '401':
          description: Not authorized
    put:
      tags:
        - Replica
      summary: Uploads a replica to the list of replicas
      description: Uploads a replica to the list of replicas
      operationId: cloudmesh.replica.add
      requestBody:
        description: The replica to be uploaded
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Replica'

```

```

responses:
  '200':
    description: Replica updated
  '400':
    description: Error updating replica.
  '401':
    description: Not authorized
/replica/{name}:
get:
  tags:
    - Replica
  summary: Returns the named replica
  description: Returns an replica by name
  operationId: cloudmesh.replica.find_by_name
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the replica
  responses:
    '200':
      description: Returning the information of the replica
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/Replica'
    '400':
      description: No replica found
    '401':
      description: Not authorized
    '404':
      description: The named replica could not be found
delete:
  tags:
    - Replica
  summary: Deletes the named replica
  description: Deletes an replica by name
  operationId: cloudmesh.replica.delete_by_name
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the replica
  responses:
    '200':
      description: Deletion successful
    '400':
      description: No replica found
    '401':
      description: Not authorized
    '404':
      description: The named replica could not be found
components:
schemas:
  Replica:
    type: object
    description: An entry representing a file replica record
    properties:
      name:
        type: string
        description: The name of the replica
      filename:
        type: string
        description: The original filename
      endpoint:
        type: string
        description: The location of the file
      checksum:
        type: string
        description: The checksum of the file
      size:
        type: integer
        description: The size of the file in byte

```

### 4.6.3 Database

The database specification allows to register a database and perform elementary operations to use this database. We distinguish actions related to the registration, the adding of a schema, the insertion of data and the query of data. The data base is defined by a name an endpoint (e.g.,

host, port), and a protocol used (e.g., SQL, MongoDB, graphgl, and others).

#### 4.6.3.1 Schema Database

[Reference:](#) 

Property	Type	Description
name	string	Name of the database
description	string	Description of the database
endpoint	string	Endpoint of the database
kind	string	the kind of the database

#### 4.6.3.2 Schema Definition

[Reference:](#) 

Property	Type	Description
name	string	Name of the database
description	string	Description of the database
kind	string	The kind of the definition
schema	string	The schema associated with the table or collection

#### 4.6.3.3 Schema Record

[Reference:](#) 

Property	Type	Description
status	string	The status of the reurn
result	string	The result of the quesy in json string format

#### 4.6.3.4 Schema Query

[Reference:](#) 

Property	Type	Description
status	string	The query string

#### 4.6.3.5 Paths

HTTP	Path	Summary
get	/database	Returns all databases
delete	/database	Deletes a database from the list of databases
get	/database/{name}	Get the list of tables or collections for the database
put	/database/{name}	Upload a news table or collection
get	/database/{name}/{table_or_collection}	Query the table or collection
put	/database/{name}/{table_or_collection}	add data to the table or collection

##### 4.6.3.5.1 /database

###### 4.6.3.5.1.1 GET /database

Returns all databases

Responses

Code	Description	Schema
200	List of databases	array[ <a href="#">Database</a> ]
400	No database found	String
401	Not authorized	String
404	Named database not found	String

###### 4.6.3.5.1.2 DELETE /database

Deletes a database from the list of databases

Responses

Code	Description	Schema
200	Deletion successful	String
400	No database found	String
401	Not authorized	String

404     Named database not found     String

---

#### Parameters

Name	Located in	Description	Required	Schema
name	path	Name of the database	True	String

4.6.3.5.2 /database/{name}

4.6.3.5.2.1 GET /database/{name}

#### Responses

Code	Description	Schema
200	successfully returned the list	array[ <a href="#">Definition</a> ]
400	No database found	String
401	Not authorized	String
404	Named database not found	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	Name of the collections or tables	True	String

4.6.3.5.2.2 PUT /database/{name}

#### Responses

Code	Description	Schema
200	successfully returned the list	<a href="#">Definition</a>
400	No database found	String
401	Not authorized	String
404	Named database not found	String

#### Parameters

Name	Located in	Description	Required	Schema

name	path	Name of the collections or tables	True	String
------	------	-----------------------------------	------	--------

4.6.3.5.3 /database/{name}/{table\_or\_collection}

4.6.3.5.3.1 GET /database/{name}/{table\_or\_collection}

## Responses

Code	Description	Schema
200	Successfull query	array[ <a href="#">Record</a> ]
400	No database found	String
401	Not authorized	String
404	Named database not found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	Name of the database	True	String
table_or_collection	path	Name of the table or collection	True	String
query	path	Database Query	True	<a href="#">Query</a>

4.6.3.5.3.2 PUT /database/{name}/{table\_or\_collection}

## Responses

Code	Description	Schema
200	successfully uploaded	<a href="#">Record</a>
400	No database found	String
401	Not authorized	String
404	Named database not found	String

## Parameters

Name	Located in	Description	Required	Schema
------	------------	-------------	----------	--------

name	path	Name of the database	True	String
table_or_collection	path	Name of the table or collection	True	String

## Request Body

Located in	Description	Required	Schema
Body	Record to be uploaded	True	<a href="#">Record</a>

### 4.6.3.6 database.yaml

```

openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 08-06-2019
  x-status: TODO
  title: Database
  description: |- 
    The database specification allows to register a database and perform
    elementary operations to use this database. We distinguish actions
    related to the registration, the adding of a schema, the insertion of
    data and the query of data. The data base is defined by a name an endpoint
    (e.g., host, port), and a protocol used (e.g., SQL, MongoDB, graphql, and
    others).

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: NIST BDRA Interface Subgroup
    url: https://cloudmesh-community.github.io/nist/spec/
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /database:
    get:
      tags:
        - "Database Registry"
      summary: Returns all databases
      description: Returns all databases
      operationId: cloudmesh.database.get
      responses:
        '200':
          description: List of databases
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: "#/components/schemas/Database"
        '400':
          description: No database found
        '401':
          description: Not authorized
        '404':
          description: Named database not found
    delete:
      tags:
        - "Database Registry"
      summary: Deletes a database from the list of databases
      description: Deletes a database from the list of databases
      operationId: cloudmesh.database.delete
      parameters:
        - name: name
          description: Name of the database
          in: path
          required: true
          schema:
            type: string
      responses:
        '200':
          description: Deletion successful

```

```

'400':
  description: No database found
'401':
  description: Not authorized
'404':
  description: Named database not found
/database/{name}:
get:
  tags:
    - "Database Definition"
  summary: "Get the list of tables or collections for the database"
  description: ""
  operationId: "cloudmesh.database.get.collections_or_tables"
  parameters:
    - name: name
      description: Name of the collections or tables
      in: path
      required: true
      schema:
        type: string
  responses:
    '200':
      description: "successfully returned the list"
      content:
        application/json:
          schema:
            type: array
            items:
              $ref: "#/components/schemas/Definition"
    '400':
      description: No database found
    '401':
      description: Not authorized
    '404':
      description: Named database not found
put:
  tags:
    - "Database Definition"
  summary: "Upload a news table or collection"
  description: ""
  operationId: "cloudmesh.database.put.collections_or_tables"
  parameters:
    - name: name
      description: Name of the collections or tables
      in: path
      required: true
      schema:
        type: string
  responses:
    '200':
      description: "successfully returned the list"
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/Definition"
    '400':
      description: No database found
    '401':
      description: Not authorized
    '404':
      description: Named database not found
/database/{name}/{table_or_collection}:
get:
  tags:
    - "Database Data Interaction"
  summary: "Query the table or collection"
  description: ""
  operationId: "cloudmesh.database.data.get"
  parameters:
    - name: name
      description: Name of the database
      in: path
      required: true
      schema:
        type: string
    - name: table_or_collection
      description: Name of the table or collection
      in: path
      required: true
      schema:
        type: string
    - name: query
      description: Database Query
      in: path
      required: true
      schema:
        $ref: "#/components/schemas/Query"
  responses:
    '200':

```

```

description: Successful query
content:
  application/json:
    schema:
      type: array
      items:
        $ref: "#/components/schemas/Record"
'400':
  description: No database found
'401':
  description: Not authorized
'404':
  description: Named database not found
put:
  tags:
    - "Database Data Interaction"
  summary: "add data to the table or collection"
  description: ""
  operationId: "cloudmesh.database.data.put"
  parameters:
    - name: name
      description: Name of the database
      in: path
      required: true
      schema:
        type: string
    - name: table_or_collection
      description: Name of the table or collection
      in: path
      required: true
      schema:
        type: string
  requestBody:
    description: Record to be uploaded
    required: true
    content:
      application/json:
        schema:
          $ref: "#/components/schemas/Record"
  responses:
    '200':
      description: "successfully uploaded"
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/Record"
    '400':
      description: No database found
    '401':
      description: Not authorized
    '404':
      description: Named database not found
components:
  schemas:
    Database:
      type: object
      description: Defines a database object as an entry
      properties:
        name:
          type: string
          description: Name of the database
        description:
          type: string
          description: Description of the database
        endpoint:
          type: string
          description: Endpoint of the database
        kind:
          type: string
          description: the kind of the database
    Definition:
      type: object
      description: Defines a database collection or Table
      properties:
        name:
          type: string
          description: Name of the database
        description:
          type: string
          description: Description of the database
        kind:
          type: string
          description: The kind of the definition
        schema:
          type: string
          description: The schema associated with the table or collection
    Record:
      type: object
      description: The result of a query

```

```

properties:
  status:
    type: string
    description: The status of the return
  result:
    type: string
    description: The result of the query in json string format
Query:
  type: object
  description: The query
  properties:
    status:
      type: string
      description: The query string

```

## 4.6.4 Virtual Directory

A virtual directory is a collection of files, replicas, streams or other virtual directories.

### 4.6.4.1 Schema Virtualdirectory

[Reference:](#) 

Property	Type	Description
name	string	The name of the virtual directory
description	string	Description of the virtual directory
host	string	Remote host of the virtual directory
location	string	Remote location, e.g., a directory with full path on a host
protocol	string	Access protocol (e.g. HTTP, FTP, SSH, etc.)
credential	object	Credential to access

### 4.6.4.2 Paths

HTTP	Path	Summary
get	/virtualdirectory	Returns a list of virtual directories
put	/virtualdirectory	Uploads a virtual directory to the list of virtual directories
get	/virtualdirectory/{name}	Returns the named virtual directory
delete	/virtualdirectory/{name}	Deletes the named virtual directory
get	/virtualdirectory/{name}/{filename}	Returns the specific file of that virtual directory
put	/virtualdirectory/{name}/{filename}	Updates or adds a virtual file in the virtual directory

---

delete	/virtualdirectory/{name}/{filename}	Delete an user in the virtual directory
--------	-------------------------------------	---

---

#### 4.6.4.2.1 /virtualdirectory

##### 4.6.4.2.1.1 GET /virtualdirectory

Returns a list of all virtual directories

#### Responses

---

Code	Description	Schema
200	The list of virtual directories	array[ <a href="#">Virtualdirectory</a> ]
400	No virtual directories found	String
401	Not authorized	String

---

##### 4.6.4.2.1.2 PUT /virtualdirectory

Uploads a virtual directory to the list of virtual directories

#### Responses

---

Code	Description	Schema
200	Virtual directory updated	String
400	Error updating virtual directory.	String
401	Not authorized	String

---

#### Request Body

---

Located in	Description	Required	Schema
Body	The virtual directory to be uploaded	True	<a href="#">Virtualdirectory</a>

---

#### 4.6.4.2.2 /virtualdirectory/{name}

##### 4.6.4.2.2.1 GET /virtualdirectory/{name}

Returns an virtual directory by name

#### Responses

---

Code	Description	Schema
200	Returning the information of the virtual directory	<a href="#">Virtualdirectory</a>
400	No virtual directory found	String
401	Not authorized	String
404	The named virtual directory could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the virtual directory	True	String

4.6.4.2.2.2 DELETE /virtualdirectory/{name}

Deletes an virtual directory by name

## Responses

Code	Description	Schema
200	Deletion successful	String
400	No Virtual directory found	String
401	Not authorized	String
404	The named virtual directory could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the virtual directory	True	String

4.6.4.2.3 /virtualdirectory/{name}/{filename}

4.6.4.2.3.1 GET /virtualdirectory/{name}/{filename}

Returns the specific file of that virtual directory

## Responses

Code	Description	Schema
200	upload ok	<a href="#">File</a>

---

401	Not authorized	String
-----	----------------	--------

---

## Parameters

---

Name	Located in	Description	Required	Schema
name	path	The name of the virtual directory	True	String
filename	path	The filename	True	String

---

4.6.4.2.3.2 PUT /virtualdirectory/{name}/{filename}

Updates or adds a virtual file in the virtual directory

## Responses

---

Code	Description	Schema
200	User added sucessfully	String
401	Not authorized	String

---

## Parameters

---

Name	Located in	Description	Required	Schema
name	path	The name of the virtual directory	True	String
filename	path	The filename	True	String

---

## Request Body

---

Located in	Description	Required	Schema
Body	The user to be uploaded	True	<a href="#">File</a>

---

4.6.4.2.3.3 DELETE /virtualdirectory/{name}/{filename}

Delete an user in the virtual directory

## Responses

---

Code	Description	Schema
200	Deletion successful	String
401	Not authorized	String

---

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the virtual directory	True	String
filename	path	The filename	True	String

### 4.6.4.3 virtualdirectory.yaml

```

openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 14-06-2019
  x-status: defined
  title: Virtual Directory
  description: |- 
    A virtual directory is a collection of files, replicas, streams or other
    virtual directories.

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: NIST BDRA Interface Subgroup Service
    url: https://cloudmesh-community.github.io/nist/spec/
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /virtualdirectory:
    get:
      tags:
        - Virtual directory
      summary: Returns a list of virtual directories
      description: Returns a list of all virtual directories
      operationId: cloudmesh.virtual directory.list
      responses:
        '200':
          description: The list of virtual directories
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Virtualdirectory'
        '400':
          description: No virtual directories found
        '401':
          description: Not authorized
    put:
      tags:
        - Virtual directory
      summary: Uploads a virtual directory to the list of virtual directories
      description: Uploads a virtual directory to the list of virtual directories
      operationId: cloudmesh.virtual directory.add
      requestBody:
        description: The virtual directory to be uploaded
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Virtualdirectory'
      responses:
        '200':
          description: Virtual directory updated
        '400':
          description: Error updating virtual directory.
        '401':
          description: Not authorized
  /virtualdirectory/{name}:
    get:
      tags:
        - Virtual directory
      summary: Returns the named virtual directory
      description: Returns an virtual directory by name
      operationId: cloudmesh.virtualdirectory.find_by_name
      parameters:
        - name: name

```

```

in: path
required: true
schema:
  type: string
description: The name of the virtual directory
responses:
  '200':
    description: Returning the information of the virtual directory
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/Virtualdirectory'
  '400':
    description: No virtual directory found
  '401':
    description: Not authorized
  '404':
    description: The named virtual directory could not be found
delete:
tags:
- Virtual directory
summary: Deletes the named virtual directory
description: Deletes an virtual directory by name
operationId: cloudmesh.virtualdirectory.delete_by_name
parameters:
- name: name
  in: path
  required: true
  schema:
    type: string
  description: The name of the virtual directory
responses:
  '200':
    description: Deletion successful
  '400':
    description: No Virtual directory found
  '401':
    description: Not authorized
  '404':
    description: The named virtual directory could not be found

/virtualdirectory/{name}/{filename}:
get:
tags:
- Virtual directory
summary: Returns the specific file of that virtual directory
description: Returns the specific file of that virtual directory
operationId: cloudmesh.virtualdirectory.file.get_by_name
parameters:
- name: name
  in: path
  required: true
  schema:
    type: string
  description: The name of the virtual directory
- name: filename
  description: The filename
  in: path
  required: true
  schema:
    type: string
  description: The filename
responses:
  '200':
    description: upload ok
    content:
      application/json:
        schema:
          $ref: "filestore.yaml#/components/schemas/File"
  '401':
    description: Not authorized
put:
tags:
- Virtual directory
summary: Updates or adds a virtual file in the virtual directory
description: Updates or adds a virtual file in the virtual directory
operationId: cloudmesh.virtualdirectory.file.add
parameters:
- name: name
  in: path
  required: true
  schema:
    type: string
  description: The name of the virtual directory
- name: filename
  description: The filename
  in: path
  required: true
  schema:
    type: string
  description: The filename

```

```

requestBody:
  description: The user to be uploaded
  required: true
  content:
    application/json:
      schema:
        $ref: "filestore.yaml#/components/schemas/File"
responses:
  '200':
    description: User added sucessfully
  '401':
    description: Not authorized
delete:
  tags:
    - Virtual directory
  summary: Delete an user in the virtual directory
  description: Delete an user in the virtual directory
  operationId: cloudmesh.virtualdirectory.file.delete
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the virtual directory
    - name: filename
      in: path
      required: true
      schema:
        type: string
      description: The filename
  responses:
    '200':
      description: Deletion successful
    '401':
      description: Not authorized
components:
  schemas:
    Virtualdirectory:
      type: object
      description: the virtual directory
      properties:
        name:
          description: The name of the virtual directory
          type: string
        description:
          description: Description of the virtual directory
          type: string
        host:
          description: Remote host of the virtual directory
          type: string
        location:
          description: Remote location, e.g., a directory with full path on a
            host
          type: string
        protocol:
          description: Access protocol (e.g. HTTP, FTP, SSH, etc.)
          type: string
        credential:
          description: Credential to access
          type: object

```

## 4.7 COMPUTE MANAGEMENT - VIRTUAL CLUSTERS

### 4.7.1 Virtual Cluster

A Virtual Cluster is modeled as manager node, and one or more compute nodes. The manager node usually serves as a login node and can be accessed from outside via a public IP. The compute nodes are connected to the manager node via a private, usually high performance (high throughput and low latency), network and thus accessible only from the manager node. To use the virtual cluster, login to the manager node, and from there one can login to any compute node, or submit a job to run on the compute nodes.

#### 4.7.1.1 Schema Virtualcluster

[Reference:](#) 

Property	Type	Description
name	string	The name of the virtual cluster
description	string	A description of the virtual cluster
owner	string	Username of the owner of the virtual cluster
manager	<a href="#">Node</a>	Manager node of the virtual cluster
nodes	array[Node]	List of nodes of the virtual cluster

#### 4.7.1.2 Schema Node

[Reference:](#) 

Property	Type	Description
name	string	Name of the node
state	string	Power state of the node
ncpu	integer	Number of virtual CPUs of the node
ram	string	RAM size of the node
disk	string	Disk size of the node
nics	array[NIC]	List of network interfaces of the node

#### 4.7.1.3 Schema NIC

[Reference:](#) 

Property	Type	Description
mac	string	MAC address of the node
ip	string	IP address of the node

#### 4.7.1.4 Paths

HTTP	Path	Summary
get	/virtualcluster	Returns a list of virtual clusters
put	/virtualcluster	Uploads an virtual cluster to the

		list of virtual clusters
get	/virtualcluster/{name}	Returns the named virtual cluster
delete	/virtualcluster/{name}	Deletes the named virtual cluster
get	/virtualcluster/{name}/{nodename}	Node of the named virtual cluster
put	/virtualcluster/{name}/{nodename}	Updates or adds a node to the virtual cluster
delete	/virtualcluster/{name}/{nodename}	Delete a node in the virtual cluster

#### 4.7.1.4.1 /virtualcluster

##### 4.7.1.4.1.1 GET /virtualcluster

Returns a list of all virtual clusters

##### Responses

Code	Description	Schema
200	The list of virtual clusters	array[ <a href="#">Virtualcluster</a> ]
401	Not authorized	String
400	No Virtual clusters found	String

##### 4.7.1.4.1.2 PUT /virtualcluster

Uploads an virtual cluster to the list of virtual clusters

##### Responses

Code	Description	Schema
200	Virtual cluster updated or created	String
400	Error updating Virtual cluster	String
401	Not authorized	String

##### Request Body

Located in	Description	Required	Schema
Body	The virtual cluster to be uploaded	True	<a href="#">Virtualcluster</a>

##### 4.7.1.4.2 /virtualcluster/{name}

#### 4.7.1.4.2.1 GET /virtualcluster/{name}

Returns an virtual cluster by name

#### Responses

Code	Description	Schema
200	Returning the information of the virtual cluster	<a href="#">Virtualcluster</a>
400	No virtual cluster found	String
401	Not authorized	String
404	The named virtual cluster could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the virtual cluster	True	String

#### 4.7.1.4.2.2 DELETE /virtualcluster/{name}

Deletes an virtual cluster by name

#### Responses

Code	Description	Schema
200	Deletion successful	String
400	No Virtual cluster found	String
401	Not authorized	String
404	The named virtual cluster could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the virtual cluster	True	String

#### 4.7.1.4.3 /virtualcluster/{name}/{nodename}

##### 4.7.1.4.3.1 GET /virtualcluster/{name}/{nodename}

Returns the specific node of the named virtual cluster. If the node name is manager, the

manager node is used. A compute node can not be named manager

## Responses

Code	Description	Schema
200	Node info	<a href="#">Node</a>
401	Not authorized	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the virtual cluster	True	String
nodename	path	The nodename	True	String

4.7.1.4.3.2 PUT /virtualcluster/{name}/{nodename}

Updates or adds a node to the virtual cluster. If the node name is manager, the manager node is uploaded.

## Responses

Code	Description	Schema
200	Node added sucessfully	String
401	Not authorized	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the virtual cluster	True	String
nodename	path	The nodename	True	String

## Request Body

Located in	Description	Required	Schema
Body	The node to be uploaded	True	<a href="#">Node</a>

4.7.1.4.3.3 DELETE /virtualcluster/{name}/{nodename}

## Delete a node in the virtual cluster

### Responses

Code	Description	Schema
200	Deletion successful	String
401	Not authorized	String

### Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the virtual cluster	True	String
nodename	path	The nodename	True	String

### 4.7.1.5 virtualcluster.yaml

```
openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 08-06-2019
  x-status: TODO
  title: Virtual Cluster
  description: |- 
    A Virtual Cluster is modeled as manager node, and one or more
    compute nodes. The manager node usually serves as a login node and
    can be accessed from outside via a public IP. The compute nodes are
    connected to the manager node via a private, usually high performance (high
    throughput and low latency), network and thus accessible only from the
    manager node. To use the virtual cluster, login to the manager node, and
    from there one can login to any compute node, or submit a job to run on the
    compute nodes.

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: NIST BDRA Interface Subgroup Service
    url: https://cloudmesh-community.github.io/nist/spec/
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /virtualcluster:
    get:
      tags:
        - Virtual cluster
      summary: Returns a list of virtual clusters
      description: Returns a list of all virtual clusters
      operationId: cloudmesh.virtualcluster.list
      responses:
        '200':
          description: The list of virtual clusters
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Virtualcluster'
        '401':
          description: Not authorized
        '400':
          description: No Virtual clusters found
    put:
      tags:
        - Virtual cluster
      summary: Uploads an virtual cluster to the list of virtual clusters
```

```

description: Uploads an virtual cluster to the list of virtual clusters
operationId: cloudmesh.virtualcluster.add
requestBody:
  description: The virtual cluster to be uploaded
  required: true
  content:
    application/json:
      schema:
        $ref: '#/components/schemas/Virtualcluster'
responses:
  '200':
    description: Virtual cluster updated or created
  '400':
    description: Error updating Virtual cluster
  '401':
    description: Not authorized
/virtualcluster/{name}:
get:
  tags:
    - Virtual cluster
  summary: Returns the named virtual cluster
  description: Returns an virtual cluster by name
  operationId: cloudmesh.virtualcluster.find_by_name
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the virtual cluster
  responses:
    '200':
      description: Returning the information of the virtual cluster
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/Virtualcluster'
    '400':
      description: No virtual cluster found
    '401':
      description: Not authorized
    '404':
      description: The named virtual cluster could not be found
delete:
  tags:
    - Virtual cluster
  summary: Deletes the named virtual cluster
  description: Deletes an virtual cluster by name
  operationId: cloudmesh.virtualcluster.delete_by_name
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the virtual cluster
  responses:
    '200':
      description: Deletion successful
    '400':
      description: No Virtual cluster found
    '401':
      description: Not authorized
    '404':
      description: The named virtual cluster could not be found
/virtualcluster/{name}/{nodename}:
get:
  tags:
    - Virtual cluster
  summary: Node of the named virtual cluster
  description: Returns the specific node of the named virtual cluster. If the node name is manager, the manager node is used. A compute node can not be named manager
  operationId: cloudmesh.virtualcluster.node.get_by_name
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the virtual cluster
    - name: nodename
      description: The nodename
      in: path
      required: true
      schema:
        type: string
      description: The name of the virtual cluster
  responses:
    '200':

```

```

        description: Node info
        content:
          application/json:
            schema:
              $ref: "#/components/schemas/Node"
        '401':
          description: Not authorized
      put:
        tags:
          - Virtual cluster
        summary: Updates or adds a node to the virtual cluster
        description: Updates or adds a node to the virtual cluster. If
          the node name is manager, the manager node is uploaded.
        operationId: cloudmesh.virtualcluster.node.add
        parameters:
          - name: name
            in: path
            required: true
            schema:
              type: string
            description: The name of the virtual cluster
          - name: nodename
            description: The nodename
            in: path
            required: true
            schema:
              type: string
            description: The node to be uploaded
        requestBody:
          content:
            application/json:
              schema:
                $ref: "#/components/schemas/Node"
        responses:
          '200':
            description: Node added sucessfully
          '401':
            description: Not authorized
      delete:
        tags:
          - Virtual cluster
        summary: Delete a node in the virtual cluster
        description: Delete a node in the virtual cluster
        operationId: cloudmesh.virtualcluster.node.delete
        parameters:
          - name: name
            in: path
            required: true
            schema:
              type: string
            description: The name of the virtual cluster
          - name: nodename
            description: The nodename
            in: path
            required: true
            schema:
              type: string
            description: The node to be deleted
        responses:
          '200':
            description: Deletion successful
          '401':
            description: Not authorized
    components:
      schemas:
        Virtualcluster:
          type: object
          properties:
            name:
              description: The name of the virtual cluster
              type: string
            description:
              description: A description of the virtual cluster
              type: string
            owner:
              description: Username of the owner of the virtual cluster
              type: string
            manager:
              description: Manager node of the virtual cluster
              $ref: "#/components/schemas/Node"
            nodes:
              description: List of nodes of the virtual cluster
              type: array
              items:
                $ref: "#/components/schemas/Node"
    Node:
      type: object
      properties:
        name:

```

```

        type: string
        description: Name of the node
state:
        type: string
        description: Power state of the node
ncpu:
        type: integer
        description: Number of virtual CPUs of the node
ram:
        type: string
        description: RAM size of the node
disk:
        type: string
        description: Disk size of the node
nics:
        type: array
        description: List of network interfaces of the node
        items:
            $ref: "#/components/schemas/NIC"
NIC:
        type: object
        properties:
            mac:
                type: string
                description: MAC address of the node
            ip:
                type: string
                description: IP address of the node

```

## 4.7.2 Scheduler

The queue is a special scheduler that allows tasks to be scheduled while doing queue policies, such as LIFO, FIFO, and so on. A queue returns the next task to be executed. Tasks can be added and deleted.

### 4.7.2.1 Schema Task

[Reference:](#) 

Property	Type	Description
name	string	Name of the scheduler
user	string	The username the task belongs to
description	string	The description of the task
kind	string	The kind of the task

### 4.7.2.2 Schema Policy

[Reference:](#) 

Property	Type	Description
name	string	Name of the scheduler policy
description	string	The description of the policy
kind	string	The kind of the policy
parameters	string	parameters to define the behaviour of the scheduler

#### 4.7.2.3 Paths

HTTP	Path	Summary
get	/task/next	Returns the next tasks and removed it from the list of tasks
get	/task/info	Returns information about the task that is to be scheduled next
get	/task/pop	Removes the next task to be scheduled, but does not exuale executes it. scheduled next
get	/task	Returns a list of tasks
put	/task	Uploads a task to the list of tasks
get	/task/{name}	Returns the named task
delete	/task/{name}	Deletes the named task
get	/policy	Returns the policy
put	/policy	Uploads the policy

##### 4.7.2.3.1 /task/next

###### 4.7.2.3.1.1 GET /task/next

Returns the next task

Responses

Code	Description	Schema
200	The task	array[ <a href="#">Task</a> ]
400	No tasks found	String
401	Not authorized	String

##### 4.7.2.3.2 /task/info

###### 4.7.2.3.2.1 GET /task/info

Returns the next task

Responses

Code	Description	Schema

200	The task	array[ <a href="#">Task</a> ]
400	No tasks found	String
401	Not authorized	String

4.7.2.3.3 /task/pop

4.7.2.3.3.1 GET /task/pop

Returns the next task

Responses

Code	Description	Schema
200	The task	array[ <a href="#">Task</a> ]
400	No tasks found	String
401	Not authorized	String

4.7.2.3.4 /task

4.7.2.3.4.1 GET /task

Returns a list of all tasks

Responses

Code	Description	Schema
200	The list of tasks	array[ <a href="#">Task</a> ]
400	No tasks found	String
401	Not authorized	String

4.7.2.3.4.2 PUT /task

Uploads a task to the list of tasks

Responses

Code	Description	Schema
200	Task updated	String
400	Error updating task.	String

401	Not authorized	String
-----	----------------	--------

## Request Body

Located in	Description	Required	Schema
Body	The task to be uploaded	True	<a href="#">Task</a>

4.7.2.3.5 /task/{name}

4.7.2.3.5.1 GET /task/{name}

Returns an task by name

## Responses

Code	Description	Schema
200	Returning the information of the task	<a href="#">Task</a>
400	No task found	String
401	Not authorized	String
404	The named task could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the task	True	String

4.7.2.3.5.2 DELETE /task/{name}

Deletes an task by name

## Responses

Code	Description	Schema
200	Deletion successful	String
400	No task found	String
401	Not authorized	String
404	The named task could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the task	True	String

4.7.2.3.6 /policy

4.7.2.3.6.1 GET /policy

Returns the policy

## Responses

Code	Description	Schema
200	The policy	array[ <a href="#">Policy</a> ]
400	No tasks found	String
401	Not authorized	String

4.7.2.3.6.2 PUT /policy

Uploads a task to the list of tasks

## Responses

Code	Description	Schema
200	Task updated	String
400	Error updating task	String
401	Not authorized	String

## Request Body

Located in	Description	Required	Schema
Body	The Policy	True	<a href="#">Policy</a>

4.7.2.4 scheduler.yaml

```
openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 08-06-2019
  x-status: TODO
  title: Scheduler
  description: |-
```

The queue is a special scheduler that allows tasks to be scheduled while doing queue policies, such as LIFO, FIFO, and so on. A queue returns the next task to be executed. Tasks can be added and deleted.

```

termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
contact:
  name: NIST BDRA Interface Subgroup
  url: https://cloudmesh-community.github.io/nist
license:
  name: Apache 2.0
  url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3/scheduler
paths:
  /task/next:
    get:
      tags:
        - Task
      summary: Returns the next tasks and removed it from the list of tasks
      description: Returns the next task
      operationId: cloudmesh.task.next
      responses:
        '200':
          description: The task
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Task'
        '400':
          description: No tasks found
        '401':
          description: Not authorized
  /task/info:
    get:
      tags:
        - Task
      summary: Returns information about the task that is to be scheduled next
      description: Returns the next task
      operationId: cloudmesh.task.info
      responses:
        '200':
          description: The task
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Task'
        '400':
          description: No tasks found
        '401':
          description: Not authorized
  /task/pop:
    get:
      tags:
        - Task
      summary: Removes the next task to be scheduled, but does not execute it.
      description: Returns the next task
      operationId: cloudmesh.task.pop
      responses:
        '200':
          description: The task
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Task'
        '400':
          description: No tasks found
        '401':
          description: Not authorized
  /task:
    get:
      tags:
        - Task
      summary: Returns a list of tasks
      description: Returns a list of all tasks
      operationId: cloudmesh.task.list
      responses:
        '200':
          description: The list of tasks

```

```

content:
  application/json:
    schema:
      type: array
      items:
        $ref: '#/components/schemas/Task'
'400':
  description: No tasks found
'401':
  description: Not authorized
put:
tags:
- Task
summary: Uploads a task to the list of tasks
description: Uploads a task to the list of tasks
operationId: cloudmesh.task.add
requestBody:
  description: The task to be uploaded
  required: true
  content:
    application/json:
      schema:
        $ref: '#/components/schemas/Task'
responses:
'200':
  description: Task updated
'400':
  description: Error updating task.
'401':
  description: Not authorized
/task/{name}:
get:
tags:
- Task
summary: Returns the named task
description: Returns an task by name
operationId: cloudmesh.task.find_by_name
parameters:
- name: name
  in: path
  required: true
  schema:
    type: string
    description: The name of the task
responses:
'200':
  description: Returning the information of the task
  content:
    application/json:
      schema:
        $ref: '#/components/schemas/Task'
'400':
  description: No task found
'401':
  description: Not authorized
'404':
  description: The named task could not be found
delete:
tags:
- Task
summary: Deletes the named task
description: Deletes an task by name
operationId: cloudmesh.task.delete_by_name
parameters:
- name: name
  in: path
  required: true
  schema:
    type: string
    description: The name of the task
responses:
'200':
  description: Deletion successful
'400':
  description: No task found
'401':
  description: Not authorized
'404':
  description: The named task could not be found
/policy:
get:
tags:
- Task
summary: Returns the policy
description: Returns the polocy
operationId: cloudmesh.task.policy.list
responses:
'200':
  description: The policy

```

```

content:
  application/json:
    schema:
      type: array
      items:
        $ref: '#/components/schemas/Policy'
'400':
  description: No tasks found
'401':
  description: Not authorized
put:
tags:
- Task
summary: Uploads the policy
description: Uploads a task to the list of tasks
operationId: cloudmesh.task.policy.add
requestBody:
  description: The Policy
  required: true
  content:
    application/json:
      schema:
        $ref: '#/components/schemas/Policy'
responses:
'200':
  description: Task updated
'400':
  description: Error updating task
'401':
  description: Not authorized
components:
schemas:
Task:
  type: object
  description: The scheduler
  properties:
    name:
      type: string
      description: Name of the scheduler
    user:
      type: string
      description: The username the task belongs to
    description:
      type: string
      description: The description of the task
    kind:
      type: string
      description: The kind of the task
Policy:
  type: object
  description: The policy of the scheduler
  properties:
    name:
      type: string
      description: Name of the scheduler policy
    description:
      type: string
      description: The description of the policy
    kind:
      type: string
      description: The kind of the policy
    parameters:
      type: string
      description: parameters to define the behaviour of the scheduler

```

## 4.8 COMPUTE MANAGEMENT - VIRTUAL MACHINES

This section summarizes a basic interface specification of virtual machines.

### 4.8.1 Image

To execute virtual machines, we need an image that specifies the details of the operating system.

#### 4.8.1.1 Schema Image

## Reference:

Property	Type	Description
name	string	A unique name of the image
cloud	string	The name of the cloud
label	string	A label that can be defined by the user for the image
description	string	A description for the image
osType	string	The OS type of the image
osVersion	string	The OS version of the image
status	string	The status of the image
progress	integer	The loading progress percentage of the image
visibility	string	The visibility of the image
requirement	<a href="#">Requirements</a>	Minimum requirement to run the image

### 4.8.1.2 Schema Requirements

## Reference:

Property	Type	Description
size	integer	Minimum disk size in bytes required for the image
ram	integer	Minimum ram size in bytes to run the image
cpu	string	CPU required to run the image
cores	integer	Minimum number of cores

### 4.8.1.3 Paths

HTTP	Path	Summary
get	/image/{cloud}	Returns a list of images for the cloud
put	/image/{cloud}	Add a image
get	/image/{cloud}/{name}	Returns the named image
delete	/image/{cloud}/{name}	Deletes the named image

#### 4.8.1.3.1 /image/{cloud}

##### 4.8.1.3.1.1 GET /image/{cloud}

Returns a list of all images

#### Responses

Code	Description	Schema
200	The list of images	array[ <a href="#">Image</a> ]
400	No Image found	String
401	Not authorized	String

#### Parameters

Name	Located in	Description	Required	Schema
cloud	path	The name of the cloud	True	String

4.8.1.3.1.2 PUT /image/{cloud}

Sets the named image

#### Responses

Code	Description	Schema
200	Image updated	String
400	Error updating image.	String
401	Not authorized	String

#### Parameters

Name	Located in	Description	Required	Schema
cloud	path	The name of the cloud	True	String

#### Request Body

Located in	Description	Required	Schema
Body	The image to add or modify	True	<a href="#">Image</a>

4.8.1.3.2 /image/{cloud}/{name}

4.8.1.3.2.1 GET /image/{cloud}/{name}

Returns a image by name

Responses

Code	Description	Schema
200	Returning the information of the image	<a href="#">Image</a>
400	No Image found	String
401	Not authorized	String
404	The named image could not be found	String

Parameters

Name	Located in	Description	Required	Schema
cloud	path	The name of the cloud	True	String
name	path	The name of the image	True	String

4.8.1.3.2.2 DELETE /image/{cloud}/{name}

Deletes a image by name

Responses

Code	Description	Schema
200	Deletion successful	String
400	No Image found	String
401	Not authorized	String
404	The named image could not be found	String

Parameters

Name	Located in	Description	Required	Schema
cloud	path	The name of the cloud	True	String
name	path	The name of the image	True	String

4.8.1.4 image.yaml

```
openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 08-06-2019
```

```

x-status: TODO
title: Image
description: |-  

    To execute virtual machines, we need an image that specifies the  

    details of the operationg system.  

termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
contact:
  name: NIST BDRA Interface Subgroup
  url: https://cloudmesh-community.github.io/nist/spec/
license:
  name: Apache 2.0
  url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /image/{cloud}:
    get:
      tags:
        - Image
      summary: Returns a list of images for the cloud
      description: Returns a list of all images
      operationId: cloudmesh.image.list
      parameters:
        - name: cloud
          in: path
          required: true
          schema:
            type: string
            description: The name of the cloud
      responses:
        '200':
          description: The list of images
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Image'
        '400':
          description: No Image found
        '401':
          description: Not authorized
    put:
      tags:
        - Image
      summary: Add a image
      description: Sets the named image
      operationId: cloudmesh.image.add
      parameters:
        - name: cloud
          in: path
          required: true
          schema:
            type: string
            description: The name of the cloud
      requestBody:
        description: The image to add or modify
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Image'
      responses:
        '200':
          description: Image updated
        '400':
          description: Error updating image.
        '401':
          description: Not authorized
  /image/{cloud}/{name}:
    get:
      tags:
        - Image
      summary: Returns the named image
      description: Returns a image by name
      operationId: cloudmesh.image.find_by_name
      parameters:
        - name: cloud
          in: path
          required: true
          schema:
            type: string
        - name: name
          in: path
          required: true
          schema:
            type: string

```

```

        description: The name of the image
responses:
'200':
    description: Returning the information of the image
    content:
        application/json:
            schema:
                $ref: '#/components/schemas/Image'
'400':
    description: No Image found
'401':
    description: Not authorized
'404':
    description: The named image could not be found
delete:
tags:
- Image
summary: Deletes the named image
description: Deletes a image by name
operationId: cloudmesh.image.delete_by_name
parameters:
- name: cloud
    description: The name of the cloud
    in: path
    required: true
    schema:
        type: string
- name: name
    in: path
    required: true
    schema:
        type: string
    description: The name of the image
responses:
'200':
    description: Deletion successful
'400':
    description: No Image found
'401':
    description: Not authorized
'404':
    description: The named image could not be found
components:
schemas:
Image:
    type: object
    properties:
        name:
            type: string
            description: A unique name of the image
        cloud:
            type: string
            description: The name of the cloud
        label:
            type: string
            description: A label that can be defined by the user for the image
        description:
            type: string
            description: A description for the image
        osType:
            type: string
            description: The OS type of the image
        osVersion:
            type: string
            description: The OS version of the image
        status:
            type: string
            description: The status of the image
        progress:
            type: integer
            description: The loading progress percentage of the image
        visibility:
            description: The visibility of the image
            type: string
        requirement:
            $ref: "#/components/schemas/Requirements"
            description: Minimum requirement to run the image
Requirements:
    type: object
    properties:
        size:
            type: integer
            description: Minimum disk size in bytes required for the image
        ram:
            type: integer
            description: Minimum ram size in bytes to run the image
        cpu:
            type: string
            description: CPU required to run the image

```

```

cores:
  type: integer
  description: Minimum number of cores

```

## 4.8.2 Flavor

The flavor specifies elementary information about a virtual machine or compute node. This information includes name, id, label, ram size, swap size, disk space, availability of ephemeral disk, available bandwidth, price value, cloud name. Flavors and the corresponding information are essential to size a virtual cluster appropriately.

### 4.8.2.1 Schema Flavor

Reference: 

Property	Type	Description
name	string	Name of the flavor
id	string	The id of the flavor for the named cloud
label	string	A label that a user can set for this flavor
description	string	A description for the flavor
ram	integer	Number of bytes used for the image in RAM
swap	integer	Number of bytes used for the image in SWAP
disk	integer	Number of bytes used for the disk
ephemeral_disk	boolean	Specifies whether the flavor features an ephemeral disk
bandwidth	integer	Bandwidth of the node
price	number	Price for the flavor
cloud	string	Name of the cloud this flavor is used in

### 4.8.2.2 Paths

HTTP	Path	Summary
get	/flavor/{cloud}	Returns a list of flavors for the cloud
put	/flavor/{cloud}	Add a flavor
get	/flavor/{cloud}/{name}	Returns the named flavor
delete	/flavor/{cloud}/{name}	Deletes the named flavor

4.8.2.2.1 /flavor/{cloud}

4.8.2.2.1.1 GET /flavor/{cloud}

Returns a list of all flavors

Responses

Code	Description	Schema
200	The list of flavors	array[ <a href="#">Flavor</a> ]
400	No Flavor found	String
401	Not authorized	String

Parameters

Name	Located in	Description	Required	Schema
cloud	path	The name of the cloud	True	String

4.8.2.2.1.2 PUT /flavor/{cloud}

Sets the named flavor

Responses

Code	Description	Schema
200	Flavor updated	String
400	Error updating flavor.	String
401	Not authorized	String

Parameters

Name	Located in	Description	Required	Schema
cloud	path	The name of the cloud	True	String

Request Body

Located in	Description	Required	Schema
Body	The flavor to add or modify	True	<a href="#">Flavor</a>

4.8.2.2.2 /flavor/{cloud}/{name}

#### 4.8.2.2.1 GET /flavor/{cloud}/{name}

Returns a flavor by name

#### Responses

Code	Description	Schema
200	Returning the information of the flavor	<a href="#">Flavor</a>
400	No Flavor found	String
401	Not authorized	String
404	The named flavor could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
cloud	path	The name of the cloud	True	String
name	path	The name of the flavor	True	String

#### 4.8.2.2.2 DELETE /flavor/{cloud}/{name}

Deletes a flavor by name

#### Responses

Code	Description	Schema
200	Deletion successful	String
400	No Flavor found	String
401	Not authorized	String
404	The named flavor could not be found	String

#### Parameters

Name	Located in	Description	Required	Schema
cloud	path	The name of the cloud	True	String
name	path	The name of the flavor	True	String

#### 4.8.2.3 flavor.yaml

```

openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 08-06-2019
  x-status: defined
  title: Flavor
  description: |-  

    The flavor specifies elementary information about a virtual machine  

    or compute node. This information includes name, id, label, ram size,  

    swap size, disk space, availability of ephemeral disk, available  

    bandwidth, price value, cloud name. Flavors and the corresponding  

    information are essential to size a  

    virtual cluster appropriately.

termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
contact:
  name: NIST BDRA Interface Subgroup
  url: https://cloudmesh-community.github.io/nist
license:
  name: Apache 2.0
  url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /flavor/{cloud}:
    get:
      tags:
        - Flavor
      summary: Returns a list of flavors for the cloud
      description: Returns a list of all flavors
      operationId: cloudmesh.flavor.list
      parameters:
        - name: cloud
          in: path
          required: true
          schema:
            type: string
            description: The name of the cloud
      responses:
        '200':
          description: The list of flavors
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Flavor'
        '400':
          description: No Flavor found
        '401':
          description: Not authorized
    put:
      tags:
        - Flavor
      summary: Add a flavor
      description: Sets the named flavor
      operationId: cloudmesh.flavor.add
      parameters:
        - name: cloud
          in: path
          required: true
          schema:
            type: string
            description: The name of the cloud
      requestBody:
        description: The flavor to add or modify
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Flavor'
      responses:
        '200':
          description: Flavor updated
        '400':
          description: Error updating flavor.
        '401':
          description: Not authorized
  /flavor/{cloud}/{name}:
    get:
      tags:
        - Flavor
      summary: Returns the named flavor
      description: Returns a flavor by name
      operationId: cloudmesh.flavor.find_by_name
      parameters:
        - name: cloud
          in: path

```

```

description: The name of the cloud
required: true
schema:
  type: string
- name: name
  in: path
  required: true
  schema:
    type: string
    description: The name of the flavor
responses:
  '200':
    description: Returning the information of the flavor
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/Flavor'
  '400':
    description: No Flavor found
  '401':
    description: Not authorized
  '404':
    description: The named flavor could not be found
delete:
  tags:
    - Flavor
  summary: Deletes the named flavor
  description: Deletes a flavor by name
  operationId: cloudmesh.flavor.delete_by_name
  parameters:
    - name: cloud
      description: The name of the cloud
      in: path
      required: true
      schema:
        type: string
    - name: name
      description: The name of the flavor
      in: path
      required: true
      schema:
        type: string
  responses:
    '200':
      description: Deletion successful
    '400':
      description: No Flavor found
    '401':
      description: Not authorized
    '404':
      description: The named flavor could not be found
components:
  schemas:
    Flavor:
      type: object
      description: The flavor
      properties:
        name:
          type: string
          description: Name of the flavor
        id:
          type: string
          description: The id of the flavor for the named cloud
        label:
          type: string
          description: A label that a user can set for this flavor
        description:
          type: string
          description: A description for the flavor
        ram:
          type: integer
          description: Number of bytes used for the image in RAM
        swap:
          type: integer
          description: Number of bytes used for the image in SWAP
        disk:
          type: integer
          description: Number of bytes used for the disk
        ephemeral_disk:
          type: boolean
          description: Specifies whether the flavor features an ephemeral disk
        bandwidth:
          type: integer
          description: Bandwidth of the node
        price:
          type: number
          description: Price for the flavor
        cloud:
          type: string

```

```
description: Name of the cloud this flavor is used in
```

### 4.8.3 Virtual Machine

Vm is a service to manage virtual machines.

#### 4.8.3.1 Schema Vm

Reference: [cloud](#)

Property	Type	Description
provider	string	Name of the provider
name	string	the unique name of the virtual machine
image	string	the image name for the virtual machine
flavor	string	the flavor name for the virtual machine
region	string	an optional region
state	string	The state of the virtual machine
private_ips	string	The private IPs
public_ips	string	The public IPS
metadata	string	The meta data passed along to the virtual machine

#### 4.8.3.2 Paths

HTTP	Path	Summary
get	/vm/{cloud}	Returns a list of virtual machines for the cloud
put	/vm/{cloud}	Add a virtual machine
get	/vm/{cloud}/{name}	Returns the named virtual machine
delete	/vm/{cloud}/{name}	Deletes the named virtual machine

##### 4.8.3.2.1 /vm/{cloud}

###### 4.8.3.2.1.1 GET /vm/{cloud}

Returns a list of all virtual machines

Responses

Code	Description	Schema
------	-------------	--------

---

200	The list of virtual machines	array[ <a href="#">Vm</a> ]
400	No Vm found	String
401	Not authorized	String

---

#### Parameters

---

Name	Located in	Description	Required	Schema
cloud	path	The name of the cloud	True	String

---

4.8.3.2.1.2 PUT /vm/{cloud}

Sets the named virtual machine

#### Responses

---

Code	Description	Schema
200	Vm updated	String
400	Error updating virtual machine	String
401	Not authorized	String

---

#### Parameters

---

Name	Located in	Description	Required	Schema
cloud	path	The name of the cloud	True	String

---

#### Request Body

---

Located in	Description	Required	Schema
Body	The virtual machine to add or modify	True	<a href="#">Vm</a>

---

4.8.3.2.2 /vm/{cloud}/{name}

4.8.3.2.2.1 GET /vm/{cloud}/{name}

Returns a virtual machine by name

#### Responses

---

Code	Description	Schema
200	Returning the information of the virtual machine	<a href="#">Vm</a>
400	No Vm found	String
401	Not authorized	String
404	The named virtual machine could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
cloud	path	The name of the cloud	True	String
name	path	The name of the virtual machine	True	String

4.8.3.2.2.2 DELETE /vm/{cloud}/{name}

Deletes a virtual machine by name

## Responses

Code	Description	Schema
200	Deletion successful	String
400	No Vm found	String
401	Not authorized	String
404	The named virtual machine could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
cloud	path	The name of the cloud	True	String
name	path	The name of the virtual machine	True	String

4.8.3.3 vm.yaml

```
openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 08-06-2019
  x-status: TODO
  title: Virtual Machine
  description: |-  

    Vm is a service to manage virtual machines.  

  termsOfService: https://github.com/cloudmesh-community/nist/blob/master/LICENSE.txt  

  contact:
```

```

name: NIST BDRA Interface Subgroup Service
url: https://cloudmesh-community.github.io/nist/spec/
license:
  name: Apache 2.0
  url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /vm/{cloud}:
    get:
      tags:
        - Vm
      summary: Returns a list of virtual machines for the cloud
      description: Returns a list of all virtual machines
      operationId: cloudmesh.vm.list
      parameters:
        - name: cloud
          in: path
          required: true
          schema:
            type: string
          description: The name of the cloud
      responses:
        '200':
          description: The list of virtual machines
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Vm'
        '400':
          description: No Vm found
        '401':
          description: Not authorized
    put:
      tags:
        - Vm
      summary: Add a virtual machine
      description: Sets the named virtual machine
      operationId: cloudmesh.vm.add
      parameters:
        - name: cloud
          in: path
          required: true
          schema:
            type: string
          description: The name of the cloud
      requestBody:
        description: The virtual machine to add or modify
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Vm'
      responses:
        '200':
          description: Vm updated
        '400':
          description: Error updating virtual machine
        '401':
          description: Not authorized
  /vm/{cloud}/{name}:
    get:
      tags:
        - Vm
      summary: Returns the named virtual machine
      description: Returns a virtual machine by name
      operationId: cloudmesh.vm.find_by_name
      parameters:
        - name: cloud
          in: path
          description: The name of the cloud
          required: true
          schema:
            type: string
        - name: name
          in: path
          description: The name of the virtual machine
          required: true
          schema:
            type: string
      responses:
        '200':
          description: Returning the information of the virtual machine
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/Vm'
        '400':

```

```

        description: No Vm found
    '401':
        description: Not authorized
    '404':
        description: The named virtual machine could not be found
delete:
tags:
- Vm
summary: Deletes the named virtual machine
description: Deletes a virtual machine by name
operationId: cloudmesh.vm.delete_by_name
parameters:
- name: cloud
  description: The name of the cloud
  in: path
  required: true
  schema:
    type: string
- name: name
  in: path
  description: The name of the virtual machine
  required: true
  schema:
    type: string
responses:
'200':
    description: Deletion successful
'400':
    description: No Vm found
'401':
    description: Not authorized
'404':
    description: The named virtual machine could not be found
components:
schemas:
Vm:
  type: object
  properties:
    provider:
      type: string
      description: Name of the provider
    name:
      type: string
      description: the unique name of the virtual machine
    image:
      type: string
      description: the image name for the virtual machine
    flavor:
      type: string
      description: the flavor name for the virtual machine
    region:
      type: string
      description: an optional region
    state:
      type: string
      description: The state of the virtual machine
    private_ips:
      type: string
      description: The private IPs
    public_ips:
      type: string
      description: The public IPs
    metadata:
      type: string
      description: The meta data passed along to the virtual machine

```

## 4.8.4 Secgroup

A security group defines the incoming and outgoing security rules which can then be assigned to a node. The connection to and from the node will be determined by the security group rules, in addition to any other possible rules applied on network devices or from the instance's firewall settings. A security group may have one or multiple rules and a node may be associated with one or more security groups.

### 4.8.4.1 Schema Secgroup

[Reference:](#) 

Property	Type	Description
name	string	Name of the security group
description	string	Describes what the security group is for
rules	array[SecGroupRule]	List of Security group rules

#### 4.8.4.2 Schema SecGroupRule

[Reference:](#) 

Property	Type	Description
name	string	Unique name of the rule
ingress	boolean	The defined security group rule is for ingress if True
egress	boolean	The defined security group rule is for egress if True
remote_group	string	Name of the group if the rule is defined by group instead of IP range
protocol	string	The protocol used such as TCP, UDP, ICMP
from_port	integer	Port range starting port
to_port	integer	Port range ending port
cidr	string	The source or destination network in CIDR notation, e.g., 129.79.0.0/16

#### 4.8.4.3 Paths

HTTP	Path	Summary
get	/secgroup	Returns all security groups
get	/secgroup/{name}	Return the security group by name
post	/secgroup/{name}	Create a new named security group
post	/secgroup/{name}/rule	Create a new rule in the specified security group
get	/secgroup/{name}/rule/{rule}	Get an existing rule from the specified security group
delete	/secgroup/{name}/rule/{rule}	Delete an existing rule from the specified security group

##### 4.8.4.3.1 /secgroup

#### 4.8.4.3.1.1 GET /secgroup

Returns all security groups

#### Responses

Code	Description	Schema
200	security group information	array[ <a href="#">Secgroup</a> ]
400	Not found	String
401	Not authorized	String

#### 4.8.4.3.2 /secgroup/{name}

##### 4.8.4.3.2.1 GET /secgroup/{name}

Return the security group by name

#### Responses

Code	Description	Schema
200	security group information	<a href="#">Secgroup</a>
400	Not found	String
401	Not authorized	String

#### Parameters

Name	Located in	Description	Required	Schema
name	path	name of the security group	True	String

#### 4.8.4.3.2.2 POST /secgroup/{name}

Create a new named security group

#### Responses

Code	Description	Schema
201	Created	String
401	Not authorized	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the security group to create	True	String

4.8.4.3.3 /secgroup/{name}/rule

4.8.4.3.3.1 POST /secgroup/{name}/rule

Create a new rule in security group

## Responses

Code	Description	Schema
200	Created	String
400	Not found	String
401	Not authorized	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the new security group to create	True	String

Request Body

Located in	Description	Required	Schema
Body	The new security group rule to create	True	<a href="#">SecGroupRule</a>

4.8.4.3.4 /secgroup/{name}/rule/{rule}

4.8.4.3.4.1 GET /secgroup/{name}/rule/{rule}

Create a new rule in security group

## Responses

Code	Description	Schema
200	The security group rule definition info	<a href="#">Secgrouprule</a>

---

400	Not found	String
401	Not authorized	String

---

## Parameters

---

Name	Located in	Description	Required	Schema
name	path	The named of the security group from which the rule will be deleted	True	String
rule	path	The rule to be added	True	String

---

4.8.4.3.4.2 DELETE /secgroup/{name}/rule/{rule}

## Create a new rule in security group

### Responses

---

Code	Description	Schema
200	Deleted sucessfully	String
400	Not found	String
401	Not authorized	String

---

## Parameters

---

Name	Located in	Description	Required	Schema
name	path	The named of the secgroup from which the rule will be deleted	True	String
rule	path	The rule to be deleted	True	String

---

## 4.8.4.4 secgroup.yaml

```
openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 08-06-2019
  x-status: TODO
  title: Secgroup
  description: |-
    A security group defines the incoming and outgoing security rules
    which can then be assigned to a node. The connection to and from the node
    will be determined by the security group rules, in addition to any other
    possible rules applied on network devices or from the instance's firewall
    settings. A security group may have one or multiple rules and a node may be
    associated with one or more security groups.
```

```

termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
contact:
  name: NIST BDRA Interface Subgroup
  url: https://cloudmesh-community.github.io/nist
license:
  name: Apache 2.0
  url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /secgroup:
    get:
      tags:
        - Security group
      summary: Returns all security groups
      description: Returns all security groups
      operationId: cloudmesh.secgroup.get
      responses:
        '200':
          description: security group information
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: "#/components/schemas/Secgroup"
        '400':
          description: Not found
        '401':
          description: Not authorized
    /secgroup/{name}:
      get:
        tags:
          - Security group
        summary: Return the security group by name
        description: Return the security group by name
        operationId: cloudmesh.secgroup.get_by_name
        parameters:
          - name: name
            description: name of the security group
            in: path
            required: true
            schema:
              type: string
        responses:
          '200':
            description: security group information
            content:
              application/json:
                schema:
                  $ref: "#/components/schemas/Secgroup"
          '400':
            description: Not found
          '401':
            description: Not authorized
      post:
        tags:
          - Security group
        summary: Create a new named security group
        description: Create a new named security group
        operationId: cloudmesh.secgroup.add
        parameters:
          - in: path
            name: name
            required: true
            description: The name of the security group to create
            schema:
              type: string
        responses:
          '201':
            description: Created
          '401':
            description: Not authorized
    /secgroup/{name}/rule:
      post:
        tags:
          - Security group
        summary: Create a new rule in the specified security group
        description: Create a new rule in security group
        operationId: cloudmesh.secgroup.add_rule
        parameters:
          - in: path
            name: name
            required: true
            description: The name of the new security group to create
            schema:
              type: string
        requestBody:
          description: The new security group rule to create
          required: true

```

```

content:
  application/json:
    schema:
      $ref: '#/components/schemas/SecGroupRule'
responses:
  '200':
    description: Created
  '400':
    description: Not found
  '401':
    description: Not authorized
/secgroup/{name}/rule/{rule}:
get:
  tags:
  - Security group
  summary: Get an existing rule from the specified security group
  description: Create a new rule in security group
  operationId: cloudmesh.secgroup.get_rule
  parameters:
    - in: path
      name: name
      required: true
      description: The named of the security group from which the rule will be deleted
      schema:
        type: string
    - in: path
      name: rule
      required: true
      description: The rule to be added
      schema:
        type: string
  responses:
    '200':
      description: The security group rule definition info
      content:
        application/json:
          schema:
            $ref: "#/components/schemas/SecGroupRule"
    '400':
      description: Not found
    '401':
      description: Not authorized
delete:
  tags:
  - Security group
  summary: Delete an existing rule from the specified security group
  description: Create a new rule in security group
  operationId: cloudmesh.secgroup.delete_rule
  parameters:
    - in: path
      name: name
      required: true
      description: The named of the secgroup from which the rule will be deleted
      schema:
        type: string
    - in: path
      name: rule
      required: true
      description: The rule to be deleted
      schema:
        type: string
  responses:
    '200':
      description: Deleted sucessfully
    '400':
      description: Not found
    '401':
      description: Not authorized
components:
schemas:
  Secgroup:
    type: object
    description: the security group object
    properties:
      name:
        type: string
        description: Name of the security group
      description:
        type: string
        description: Describes what the security group is for
    rules:
      type: array
      description: List of Security group rules
      items:
        $ref: "#/components/schemas/SecGroupRule"
  SecGroupRule:
    type: object
    description: security group rule
    properties:

```

```

name:
  type: string
  description: Unique name of the rule
ingress:
  type: boolean
  description: The defined security group rule is for ingress if True
egress:
  type: boolean
  description: The defined security group rule is for egress if True
remote_group:
  type: string
  description: Name of the group if the rule is defined by group instead of IP range
protocol:
  type: string
  description: The protocol used such as TCP, UDP, ICMP
from_port:
  type: integer
  description: Port range starting port
to_port:
  type: integer
  description: Port range ending port
cidr:
  type: string
  description: The source or destination network in CIDR notation, e.g., 129.79.0.0/16

```

## 4.8.5 Nic

A service to store Network Interface Controller (NIC) information.

### 4.8.5.1 Schema Nic

Reference: 

Property	Type	Description
name	string	Name of the network interface controller
kind	string	Kind of the network interface controller (wifi, WAN, ...)
mac	string	The mac address
ip	string	The IP address
mask	string	The network mask
broadcast	string	The broadcast address
gateway	string	The gateway address
mtu	integer	The MTU of the NIC
bandwidth	integer	The bandwidth in bps

### 4.8.5.2 Paths

HTTP	Path	Summary
get	/nic	Returns a list of network interface controllers
put	/nic	Set a network interface controller
get	/nic/{name}	Returns the named network interface controller

delete /nic/{name} Deletes the named network interface controller

---

4.8.5.2.1 /nic

4.8.5.2.1.1 GET /nic

Returns a list of all network interface controllers

Responses

Code	Description	Schema
200	The list of network interface controllers	array[Nic]
400	No Nic found	String
401	Not authorized	String

4.8.5.2.1.2 PUT /nic

Sets the named network interface controller

Responses

Code	Description	Schema
200	Nic updated	String
400	Error updating network interface controller	String
401	Not authorized	String

Request Body

Located in	Description	Required	Schema
Body	The new nic to create	True	<a href="#">Nic</a>

4.8.5.2.2 /nic/{name}

4.8.5.2.2.1 GET /nic/{name}

Returns a network interface controller by name

Responses

Code	Description	Schema

200	Returning the information of the network interface controller	<a href="#">Nic</a>
400	No Nic found	String
401	Not authorized	String
404	The named network interface controller could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the network interface controller	True	String

### 4.8.5.2.2.2 DELETE /nic/{name}

Deletes a network interface controller by name

## Responses

Code	Description	Schema
200	Deletion successful	String
400	No Nic found	String
401	Not authorized	String
404	The named network interface controller could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the network interface controller	True	String

### 4.8.5.3 nic.yaml

```

openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 08-06-2019
  x-status: TODO
  title: Nic
  description: |- 
    A service to store Network Interface Controller (NIC) information.

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:

```

```

name: NIST BDRA Interface Subgroup
url: https://cloudmesh-community.github.io/nist
license:
  name: Apache 2.0
  url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /nic:
    get:
      tags:
        - Nic
      summary: Returns a list of network interface controllers
      description: Returns a list of all network interface controllers
      operationId: cloudmesh.nic.list
      responses:
        '200':
          description: The list of network interface controllers
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Nic'
        '400':
          description: No Nic found
        '401':
          description: Not authorized
    put:
      tags:
        - Nic
      summary: Set a network interface controller
      description: Sets the named network interface controller
      operationId: cloudmesh.nic.add
      requestBody:
        description: The new nic to create
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Nic'
      responses:
        '200':
          description: Nic updated
        '400':
          description: Error updating network interface controller
        '401':
          description: Not authorized
  /nic/{name}:
    get:
      tags:
        - Nic
      summary: Returns the named network interface controller
      description: Returns a network interface controller by name
      operationId: cloudmesh.nic.find_by_name
      parameters:
        - name: name
          in: path
          required: true
          schema:
            type: string
            description: The name of the network interface controller
      responses:
        '200':
          description: Returning the information of the network interface controller
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/Nic'
        '400':
          description: No Nic found
        '401':
          description: Not authorized
        '404':
          description: The named network interface controller could not be found
    delete:
      tags:
        - Nic
      summary: Deletes the named network interface controller
      description: Deletes a network interface controller by name
      operationId: cloudmesh.nic.delete_by_name
      parameters:
        - name: name
          in: path
          required: true
          schema:
            type: string
            description: The name of the network interface controller
      responses:

```

```

'200':
  description: Deletion successful
'400':
  description: No Nic found
'401':
  description: Not authorized
'404':
  description: The named network interface controller could not be found
components:
schemas:
  Nic:
    type: object
    description: The network interface controller
    properties:
      name:
        type: string
        description: Name of the network interface controller
      kind:
        type: string
        description: Kind of the network interface controller (wifi, WAN, ...)
      mac:
        type: string
        description: The mac address
      ip:
        type: string
        description: The IP address
      mask:
        type: string
        description: The network mask
      broadcast:
        type: string
        description: The broadcast address
      gateway:
        type: string
        description: The gateway address
      mtu:
        type: integer
        description: The MTU of the NIC
      bandwidth:
        type: integer
        description: The bandwidth in bps

```

## 4.9 COMPUTE MANAGEMENT - CONTAINERS

---

### 4.9.1 Containers

Numerous different containers are likely to be created and handling them becomes more and more time consuming as their number increases. This service helps to solve that issue by storing containers and their corresponding information.

#### 4.9.1.1 Schema Container

[Reference:](#) 

Property	Type	Description
name	string	Name of the container
version	string	Version of the container
label	string	Label of the container
type	string	Type of the container
definition	string	Definition or manifest of the container
imgURI	string	URI of the container

---

tags	array[string]	Tags of the container
------	---------------	-----------------------

---

#### 4.9.1.2 Paths

---

HTTP	Path	Summary
get	/container	Returns a list of containers
put	/container	Set an container
get	/container/{name}	Returns the named container
delete	/container/{name}	Deletes the named container

---

##### 4.9.1.2.1 /container

###### 4.9.1.2.1.1 GET /container

Returns a list of all containers

###### Responses

---

Code	Description	Schema
200	The list of containerses	array[ <a href="#">Container</a> ]
400	No Container found	String

---

###### 4.9.1.2.1.2 PUT /container

Sets the named container

###### Responses

---

Code	Description	Schema
200	Container updated	String
401	Not authorized	String
400	Error updating container.	String

---

###### Request Body

---

Located in	Description	Required	Schema
Body	The new container to create	True	<a href="#">Container</a>

---

4.9.1.2.2 /container/{name}

4.9.1.2.2.1 GET /container/{name}

Returns an container by name

Responses

Code	Description	Schema
200	Returning the information of the container	<a href="#">Container</a>
400	No Container found	String
401	Not authorized	String
404	The named container could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the container	True	String

4.9.1.2.2.2 DELETE /container/{name}

Deletes an container by name

Responses

Code	Description	Schema
200	Deletion successful	String
400	No Container found	String
401	Not authorized	String
404	The named container could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the container	True	String

4.9.1.3 containers.yaml

```
openapi: "3.0.2"
```

```

info:
  version: 3.2.0
  x-date: 14-06-2019
  x-status: defined
  title: Containers
  description: |-  

    Numerous different containers are likely to be created and handling them  

    becomes more and more time consuming as their number increases. This service  

    helps to solve that issue by storing containers and their corresponding  

    information.

termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
contact:
  name: NIST BDRA Interface Subgroup
  url: https://cloudmesh-community.github.io/nist
license:
  name: Apache 2.0
  url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /container:
    get:
      tags:
        - Container
      summary: Returns a list of containers
      description: Returns a list of all containers
      operationId: cloudmesh.container.list
      responses:
        '200':
          description: The list of containeres
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Container'
        '400':
          description: No Container found
    put:
      tags:
        - Container
      summary: Set an container
      description: Sets the named container
      operationId: cloudmesh.container.add
      requestBody:
        description: The new container to create
        required: true
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/Container'
      responses:
        '200':
          description: Container updated
        '401':
          description: Not authorized
        '400':
          description: Error updating container.
  /container/{name}:
    get:
      tags:
        - Container
      summary: Returns the named container
      description: Returns an container by name
      operationId: cloudmesh.container.find_by_name
      parameters:
        - name: name
          in: path
          required: true
          schema:
            type: string
          description: The name of the container
      responses:
        '200':
          description: Returning the information of the container
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/Container'
        '400':
          description: No Container found
        '401':
          description: Not authorized
        '404':
          description: The named container could not be found
    delete:
      tags:

```

```

    - Container
summary: Deletes the named container
description: Deletes an container by name
operationId: cloudmesh.container.delete_by_name
parameters:
  - name: name
    in: path
    required: true
    schema:
      type: string
      description: The name of the container
responses:
  '200':
    description: Deletion successful
  '400':
    description: No Container found
  '401':
    description: Not authorized
  '404':
    description: The named container could not be found
components:
schemas:
  Container:
    type: object
    description: A record representing a container
    properties:
      name:
        type: string
        description: Name of the container
      version:
        type: string
        description: Version of the container
      label:
        type: string
        description: Label of the container
      type:
        type: string
        description: Type of the container
      definition:
        type: string
        description: Definition or manifest of the container
      imgURI:
        type: string
        description: URI of the container
      tags:
        type: array
        description: Tags of the container
        items:
          type: string

```

## 4.10 COMPUTE MANAGEMENT - FUNCTIONS

### 4.10.1 Microservice

As part of microservices, a function with parameters that can be invoked has been defined.

#### 4.10.1.1 Schema Microservice

Reference: 

Property	Type	Description
name	string	Name of the microservice
endpoint	string	The end point of the microservice
function	string	The function the microservice represents
description		The description of the microservice

#### 4.10.1.2 Paths

HTTP	Path	Summary
get	/microservice	Returns a list of microservicees
put	/microservice	Set an microservice
get	/microservice/{name}	Returns the named microservice
delete	/microservice/{name}	Deletes the named microservice

4.10.1.2.1 /microservice

4.10.1.2.1.1 GET /microservice

Returns a list of all microservicees

Responses

Code	Description	Schema
200	The list of microserviceses	array[ <a href="#">Microservice</a> ]
400	No Microservice found	String
401	Not authorized	String

4.10.1.2.1.2 PUT /microservice

Sets the named microservice

Responses

Code	Description	Schema
200	Microservice updated	String
400	Error updating microservice	String
401	Not authorized	String

Request Body

Located in	Description	Required	Schema
Body	The new microservice to create	True	<a href="#">Microservice</a>

4.10.1.2.2 /microservice/{name}

4.10.1.2.2.1 GET /microservice/{name}

Returns the named microservice

Responses

Code	Description	Schema
200	Returns the microservice	<a href="#">Microservice</a>
400	No Microservice found	String
401	Not authorized	String
404	The named microservice could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the microservice	True	String

4.10.1.2.2.2 DELETE /microservice/{name}

Deletes an microservice by name

Responses

Code	Description	Schema
200	Deletion successful	String
400	No Microservice found	String
401	Not authorized	String
404	The named microservice could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the microservice	True	String

4.10.1.3 microservice.yaml

```
openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 14-06-2019
  x-status: defined
```

```

title: Microservice
description: |-  

  As part of microservices, a function with parameters that can be  

  invoked has been defined.  

termsOfService: "https://github.com/cloudmesh-nist/blob/master/LICENSE.txt"
contact:
  name: NIST BDRA Interface Subgroup
  url: https://cloudmesh-community.github.io/nist
license:
  name: Apache 2.0
  url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /microservice:
    get:
      tags:
        - Microservice
      summary: Returns a list of microservicees
      description: Returns a list of all microservicees
      operationId: cloudmesh.microservice.list
      responses:
        '200':
          description: The list of microservices
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Microservice'
        '400':
          description: No Microservice found
        '401':
          description: Not authorized
    put:
      tags:
        - Microservice
      summary: Set an microservice
      description: Sets the named microservice
      operationId: cloudmesh.microservice.add
      requestBody:
        description: The new microservice to create
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Microservice'
      responses:
        '200':
          description: Microservice updated
        '400':
          description: Error updating microservice
        '401':
          description: Not authorized
  /microservice/{name}:
    get:
      tags:
        - Microservice
      summary: Returns the named microservice
      description: Returns the named microservice
      operationId: cloudmesh.microservice.find_by_name
      parameters:
        - name: name
          in: path
          required: true
          schema:
            type: string
            description: The name of the microservice
      responses:
        '200':
          description: Returns the microservice
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/Microservice'
        '400':
          description: No Microservice found
        '401':
          description: Not authorized
        '404':
          description: The named microservice could not be found
    delete:
      tags:
        - Microservice
      summary: Deletes the named microservice
      description: Deletes an microservice by name
      operationId: cloudmesh.microservice.delete_by_name
      parameters:

```

```

- name: name
  in: path
  required: true
  schema:
    type: string
  description: The name of the microservice
responses:
  '200':
    description: Deletion successful
  '400':
    description: No Microservice found
  '401':
    description: Not authorized
  '404':
    description: The named microservice could not be found
components:
  schemas:
    Microservice:
      type: object
      description: The microservice
      properties:
        name:
          type: string
          description: Name of the microservice
        endpoint:
          type: string
          description: The end point of the microservice
        function:
          type: string
          description: The function the microservice represents
        description:
          type: string
          description: The description of the microservice

```

## 4.11 RESERVATION

---

### 4.11.1 Reservation

Some services may consume a considerable amount of resources, necessitating the reservation of resources.

#### 4.11.1.1 Schema Reservation

[Reference:](#) 

Property	Type	Description
name	string	Name of the reservation
service	string	The name of the service on which we reserve
description	string	The description of the reservation
start	string(date)	The start time and date
end	string(date)	The end time and date

#### 4.11.1.2 Paths

HTTP	Path	Summary
get	/reservation	Returns a list of reservations

put	/reservation	Uploads a reservation to the list of reservations
get	/reservation/{name}	Returns the named reservation
delete	/reservation/{name}	Deletes the named reservation

4.11.1.2.1 /reservation

4.11.1.2.1.1 GET /reservation

Returns a list of all reservations

Responses

Code	Description	Schema
200	The list of reservations	array[ <a href="#">Reservation</a> ]
400	No Reservations found	String

4.11.1.2.1.2 PUT /reservation

Uploads a reservation to the list of reservations

Responses

Code	Description	Schema
200	Reservation updated	String
400	Error updating reservation	String

Request Body

Located in	Description	Required	Schema
Body	The reservation to be uploaded	True	<a href="#">Reservation</a>

4.11.1.2.2 /reservation/{name}

4.11.1.2.2.1 GET /reservation/{name}

Returns an reservation by name

Responses

Code	Description	Schema

200	Returning the information of the reservation	<a href="#">Reservation</a>
400	No reservation found	String
401	Not authorized	String
404	The named reservation could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the reservation	True	String

4.11.1.2.2.2 DELETE /reservation/{name}

Deletes an reservation by name

## Responses

Code	Description	Schema
200	Deletion successful	String
400	No reservation found	String
401	Not authorized	String
404	The named reservation could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the reservation	True	String

4.11.1.3 reservation.yaml

```

openapi: '3.0.2'
info:
  version: 3.2.0
  x-date: 14-06-2019
  x-status: defined
  title: Reservation
  description: |- 
    Some services may consume a considerable amount of resources,
    necessitating the reservation of resources.

  termsOfService: 'https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt'
  contact:
    name: NIST BDRA Interface Subgroup
    url: https://cloudmesh-community.github.io/nist
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3

```

```

paths:
  /reservation:
    get:
      tags:
        - Reservation
      summary: Returns a list of reservations
      description: Returns a list of all reservations
      operationId: cloudmesh.reservation.list
      responses:
        '200':
          description: The list of reservations
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Reservation'
        '400':
          description: No Reservations found
    put:
      tags:
        - Reservation
      summary: Uploads a reservation to the list of reservations
      description: Uploads a reservation to the list of reservations
      operationId: cloudmesh.reservation.add
      requestBody:
        description: The reservation to be uploaded
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Reservation'
      responses:
        '200':
          description: Reservation updated
        '400':
          description: Error updating reservation
  /reservation/{name}:
    get:
      tags:
        - Reservation
      summary: Returns the named reservation
      description: Returns an reservation by name
      operationId: cloudmesh.reservation.find_by_name
      parameters:
        - name: name
          in: path
          required: true
          schema:
            type: string
            description: The name of the reservation
      responses:
        '200':
          description: Returning the information of the reservation
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/Reservation'
        '400':
          description: No reservation found
        '401':
          description: Not authorized
        '404':
          description: The named reservation could not be found
    delete:
      tags:
        - Reservation
      summary: Deletes the named reservation
      description: Deletes an reservation by name
      operationId: cloudmesh.reservation.delete_by_name
      parameters:
        - name: name
          in: path
          required: true
          schema:
            type: string
            description: The name of the reservation
      responses:
        '200':
          description: Deletion successful
        '400':
          description: No reservation found
        '401':
          description: Not authorized
        '404':
          description: The named reservation could not be found
components:
  schemas:
    Reservation:

```

```

type: object
description: The reservation
properties:
  name:
    type: string
    description: Name of the reservation
  service:
    type: string
    description: The name of the service on which we reserve
  description:
    type: string
    description: The description of the reservation
  start:
    type: string
    format: date
    description: The start time and date
  end:
    type: string
    format: date
    description: The end time and date

```

## 4.12 DATA STREAMS

---

### 4.12.1 Stream

The stream object describes a data flow, providing information about the rate and number of items exchanged while issuing requests to the stream. A stream may return data items in a specific format that is defined by the stream.

#### 4.12.1.1 Schema Stream

[Reference:](#) 

Property	Type	Description
name	string	Name of the stream
format	string	Format of the stream
rate	integer	The rate of messages
limit	integer	The limit of items send

#### 4.12.1.2 Paths

HTTP	Path	Summary
get	/stream	Returns a list of streams
put	/stream	Set an stream
get	/stream/{name}	Returns the named stream
delete	/stream/{name}	Deletes the named stream

##### 4.12.1.2.1 /stream

###### 4.12.1.2.1.1 GET /stream

Returns a list of all streams

Responses

Code	Description	Schema
200	The list of streamses	array[ <a href="#">Stream</a> ]
400	No Stream found	String
401	Not authorized	String

4.12.1.2.1.2 PUT /stream

Sets the named stream

Responses

Code	Description	Schema
200	Stream updated	String
400	Error updating stream	String
401	Not authorized	String

Request Body

Located in	Description	Required	Schema
Body	The new stream to create	True	<a href="#">Stream</a>

4.12.1.2.2 /stream/{name}

4.12.1.2.2.1 GET /stream/{name}

Returns an stream by name

Responses

Code	Description	Schema
200	Returning the information of the stream	<a href="#">Stream</a>
400	No Stream found	String
401	Not authorized	String
404	The named stream could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the stream	True	String

4.12.1.2.2.2 DELETE /stream/{name}

Deletes an stream by name

## Responses

Code	Description	Schema
200	Deletion successful	String
400	No Stream found	String
401	Not authorized	String
404	The named stream could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the stream	True	String

4.12.1.3 stream.yaml

```
openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 08-06-2019
  x-status: TODO
  title: Stream
  description: |- 
    The stream object describes a data flow, providing information
    about the rate and number of items exchanged while issuing requests
    to the stream. A stream may return data items in a specific format
    that is defined by the stream.

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: NIST BDRA Interface Subgroup
    url: https://cloudmesh-community.github.io/nist
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /stream:
    get:
      tags:
        - Stream
      summary: Returns a list of streams
      description: Returns a list of all streams
      operationId: cloudmesh.stream.list
      responses:
        '200':
```

```

        description: The list of streams
    content:
        application/json:
            schema:
                type: array
                items:
                    $ref: '#/components/schemas/Stream'
    '400':
        description: No Stream found
    '401':
        description: Not authorized
  put:
    tags:
        - Stream
    summary: Set an stream
    description: Sets the named stream
    operationId: cloudmesh.stream.add
    requestBody:
        description: The new stream to create
        required: true
    content:
        application/json:
            schema:
                $ref: '#/components/schemas/Stream'
  responses:
    '200':
        description: Stream updated
    '400':
        description: Error updating stream
    '401':
        description: Not authorized
/stream/{name}:
  get:
    tags:
        - Stream
    summary: Returns the named stream
    description: Returns an stream by name
    operationId: cloudmesh.stream.find_by_name
    parameters:
        - name: name
          in: path
          required: true
          schema:
              type: string
              description: The name of the stream
    responses:
      '200':
        description: Returning the information of the stream
        content:
            application/json:
                schema:
                    $ref: '#/components/schemas/Stream'
      '400':
        description: No Stream found
      '401':
        description: Not authorized
      '404':
        description: The named stream could not be found
  delete:
    tags:
        - Stream
    summary: Deletes the named stream
    description: Deletes an stream by name
    operationId: cloudmesh.stream.delete_by_name
    parameters:
        - name: name
          in: path
          required: true
          schema:
              type: string
              description: The name of the stream
    responses:
      '200':
        description: Deletion successful
      '400':
        description: No Stream found
      '401':
        description: Not authorized
      '404':
        description: The named stream could not be found
components:
  schemas:
    Stream:
        type: object
        description: The stream
        properties:
            name:
                type: string
                description: Name of the stream

```

```

format:
  type: string
  description: Format of the stream
rate:
  type: integer
  description: The rate of messages
limit:
  type: integer
  description: The limit of items send

```

## 4.12.2 Filter

Filters can operate on a variety of objects and reduce the information received based on a search criterion.

### 4.12.2.1 Schema Filter

[Reference:](#) 

Property	Type	Description
name	string	Name of the filter
function	string	The function of the data exchanged in the stream
kind	string	The filter kind or type

### 4.12.2.2 Paths

HTTP	Path	Summary
get	/filter	Returns a list of filters
put	/filter	Set an filter
get	/filter/{name}	Returns the named filter
delete	/filter/{name}	Deletes the named filter

#### 4.12.2.2.1 /filter

##### 4.12.2.2.1.1 GET /filter

Returns a list of all filters

Responses

Code	Description	Schema
200	The list of filters	array[ <a href="#">Filter</a> ]
400	No Filter found	String

#### 4.12.2.2.1.2 PUT /filter

Sets the named filter

Responses

Code	Description	Schema
200	Filter updated	String
401	Not authorized	String
400	Error updating filter	String

Request Body

Located in	Description	Required	Schema
Body	The new filter to create	True	<a href="#">Filter</a>

#### 4.12.2.2 /filter/{name}

##### 4.12.2.2.1 GET /filter/{name}

Returns an filter by name

Responses

Code	Description	Schema
200	Returning the information of the filter	<a href="#">Filter</a>
400	No Filter found	String
401	Not authorized	String
404	The named filter could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the filter	True	String

#### 4.12.2.2.2 DELETE /filter/{name}

Deletes an filter by name

## Responses

Code	Description	Schema
200	Deletion successful	String
400	No Filter found	String
401	Not authorized	String
404	The named filter could not be found	String

## Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the filter	True	String

### 4.12.2.3 filter.yaml

```
openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 08-06-2019
  x-status: TODO
  title: Filter
  description: |- 
    Filters can operate on a variety of objects and reduce the
    information received based on a search criterion.

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: NIST BDRA Interface Subgroup
    url: https://cloudmesh-community.github.io/nist
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /filter:
    get:
      tags:
        - Filter
      summary: Returns a list of filteres
      description: Returns a list of all filteres
      operationId: cloudmesh.filter.list
      responses:
        '200':
          description: The list of filteres
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Filter'
        '400':
          description: No Filter found
    put:
      tags:
        - Filter
      summary: Set an filter
      description: Sets the named filter
      operationId: cloudmesh.filter.add
      requestBody:
        description: The new filter to create
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Filter'
      responses:
```

```

'200':
  description: Filter updated
'401':
  description: Not authorized
'400':
  description: Error updating filter
/filter/{name}:
get:
  tags:
    - Filter
  summary: Returns the named filter
  description: Returns an filter by name
  operationId: cloudmesh.filter.find_by_name
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the filter
  responses:
    '200':
      description: Returning the information of the filter
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/Filter'
    '400':
      description: No Filter found
    '401':
      description: Not authorized
    '404':
      description: The named filter could not be found
delete:
  tags:
    - Filter
  summary: Deletes the named filter
  description: Deletes an filter by name
  operationId: cloudmesh.filter.delete_by_name
  parameters:
    - name: name
      in: path
      required: true
      schema:
        type: string
      description: The name of the filter
  responses:
    '200':
      description: Deletion successful
    '400':
      description: No Filter found
    '401':
      description: Not authorized
    '404':
      description: The named filter could not be found
components:
schemas:
  Filter:
    type: object
    description: The filter
    properties:
      name:
        type: string
        description: Name of the filter
      function:
        type: string
        description: The function of the data exchanged in the stream
      kind:
        type: string
        description: The filter kind or type

```

## 4.13 DEPLOYMENT

---

### 4.13.1 Deployment

A service to store software stack deployments.

#### 4.13.1.1 Schema Deployment

## Reference:

Property	Type	Description
kind	string	the kind of the deployment
specification	string	the specification of the deployment

### 4.13.1.2 Paths

HTTP	Path	Summary
get	/deployment	Returns a list of deploymentes
put	/deployment	Set an deployment
get	/deployment/{name}	Returns the named deployment
delete	/deployment/{name}	Deletes the named deployment

#### 4.13.1.2.1 /deployment

##### 4.13.1.2.1.1 GET /deployment

Returns a list of all deploymentes

##### Responses

Code	Description	Schema
200	The list of deploymentses	array[ <a href="#">Deployment</a> ]
400	No Deployment found	String

##### 4.13.1.2.1.2 PUT /deployment

Sets the named deployment

##### Responses

Code	Description	Schema
200	Deployment updated	String
400	Error updating deployment	String
401	Not authorized	String

##### Request Body

Located in	Description	Required	Schema
Body	The new deployment to create	True	<a href="#">Deployment</a>

4.13.1.2.2 /deployment/{name}

4.13.1.2.2.1 GET /deployment/{name}

Returns an deployment by name

Responses

Code	Description	Schema
200	Returning the information of the deployment	<a href="#">Deployment</a>
400	No Deployment found	String
404	The named deployment could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the deployment	True	String

4.13.1.2.2 DELETE /deployment/{name}

Deletes an deployment by name

Responses

Code	Description	Schema
200	Deletion successful	String
400	No Deployment found	String
401	Not authorized	String
404	The named deployment could not be found	String

Parameters

Name	Located in	Description	Required	Schema
name	path	The name of the deployment	True	String

### 4.13.1.3 deployment.yaml

```
openapi: "3.0.2"
info:
  version: 3.2.0
  x-date: 08-06-2019
  x-status: TODO
  title: Deployment
  description: |-  
    A service to store software stack deployments.  

  termsOfService: "https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt"
  contact:
    name: NIST BDRA Interface Subgroup
    url: https://cloudmesh-community.github.io/nist
  license:
    name: Apache 2.0
    url: https://github.com/cloudmesh/cloudmesh-nist/blob/master/LICENSE.txt
servers:
  - url: /cloudmesh/v3
paths:
  /deployment:
    get:
      tags:
        - Deployment
      summary: Returns a list of deploymentes
      description: Returns a list of all deploymentes
      operationId: cloudmesh.deployment.list
      responses:
        '200':
          description: The list of deploymentes
          content:
            application/json:
              schema:
                type: array
                items:
                  $ref: '#/components/schemas/Deployment'
        '400':
          description: No Deployment found
    put:
      tags:
        - Deployment
      summary: Set an deployment
      description: Sets the named deployment
      operationId: cloudmesh.deployment.add
      requestBody:
        description: The new deployment to create
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/Deployment'
      responses:
        '200':
          description: Deployment updated
        '400':
          description: Error updating deployment
        '401':
          description: Not authorized
  /deployment/{name}:
    get:
      tags:
        - Deployment
      summary: Returns the named deployment
      description: Returns an deployment by name
      operationId: cloudmesh.deployment.find_by_name
      parameters:
        - name: name
          in: path
          required: true
          schema:
            type: string
          description: The name of the deployment
      responses:
        '200':
          description: Returning the information of the deployment
          content:
            application/json:
              schema:
                $ref: '#/components/schemas/Deployment'
        '400':
          description: No Deployment found
        '404':
          description: The named deployment could not be found
    delete:
      tags:
```

```
- Deployment
summary: Deletes the named deployment
description: Deletes an deployment by name
operationid: cloudmesh.deployment.delete_by_name
parameters:
- name: name
  in: path
  required: true
  schema:
    type: string
  description: The name of the deployment
responses:
'200':
  description: Deletion successful
'400':
  description: No Deployment found
'401':
  description: Not authorized
'404':
  description: The named deployment could not be found
components:
schemas:
  Deployment:
    type: object
    description: the deployment
    properties:
      kind:
        type: string
        description: the kind of the deployment
      specification:
        type: string
        description: the specification of the deployment
```

## 5 ACRONYMS AND TERMS

The following acronyms and terms are used in this volume.

ACID

Atomicity, Consistency, Isolation, Durability

API

Application Programming Interface

ASCII

American Standard Code for Information Interchange

BASE

Basically Available, Soft state, Eventual consistency

Container

See [http://csrc.nist.gov/publications/drafts/800-180/sp800-180\\_draft.pdf](http://csrc.nist.gov/publications/drafts/800-180/sp800-180_draft.pdf)

Cloud Computing

The practice of using a network of remote servers hosted on the Internet to store, manage, and process data, rather than a local server or a personal computer. See <http://nvlpubs.nist.gov/nistpubs/Legacy/SP/nistspecialpublication800-145.pdf>.

DevOps

A clipped compound of software DEvelopment and information technology OPerationS

Deployment

The action of installing software on resources

HTTP

HyperText Transfer Protocol HTTPS HTTP Secure

Hybrid

Cloud See <http://nvlpubs.nist.gov/nistpubs/Legacy/SP/nistspecialpublication800-145.pdf>.

IaaS

Infrastructure as a Service SaaS Software as a Service

ITL

Information Technology Laboratory

Microservice Architecture

Is an approach to build applications based on many smaller modular services. Each module supports a specific goal and uses a simple, well-defined interface to communicate with other sets of services.

NBD-PWG

NIST Big Data Public Working Group

NBDRA

NIST Big Data Reference Architecture

NBDRAI

NIST Big Data Reference Architecture Interface

NIST

National Institute of Standards and Technology

OS

Operating System

REST

REpresentational State Transfer

Replica

A duplicate of a file on another resource to avoid costly transfer costs in case of frequent access.

Serverless Computing

Serverless computing specifies the paradigm of function as a service (FaaS). It is a cloud computing code execution model in which a cloud provider manages the function deployment and utilization while clients can utilize them. The charge model is based on

execution of the function rather than the cost to manage and host the VM or container.

### Software Stack

A set of programs and services that are installed on a resource to support applications.

### Virtual File System

An abstraction layer on top of a distributed physical file system to allow easy access to the files by the user or application.

### Virtual Machine

A VM is a software computer that, like a physical computer, runs an operating system and applications. The VM is composed of a set of specification and configuration files and is backed by the physical resources of a host.

### Virtual Cluster

A virtual cluster is a software cluster that integrates either VMs, containers, or physical resources into an agglomeration of compute resources. A virtual cluster allows users to authenticate and authorize to the virtual compute nodes to utilize them for calculations. Optional high-level services that can be deployed on a virtual cluster may simplify interaction with the virtual cluster or provide higher-level services.

### Workflow

The sequence of processes or tasks

### WWW

World Wide Web

## BIBLIOGRAPHY

- [1] NIST, “Big Data Public Working Group (NBD-PWG).” [Online]. Available: <https://bigdatawg.nist.gov/>
- [2] W. L. Chang (Co-Chair), N. Grady (Subgroup Co-chair), and NIST Big Data Public Working Group, “NIST Big Data Interoperability Framework: Volume 1, Big Data Definitions (NIST SP 1500-1 VERSION 3),” National Institute of Standards; Technology (NIST), Gaithersburg, MD, Jul. 2019 [Online]. Available: [https://bigdatawg.nist.gov/show\\_InputDoc.php](https://bigdatawg.nist.gov/show_InputDoc.php)
- [3] W. L. Chang (Co-Chair), N. Grady (Subgroup Co-chair), and NIST Big Data Public Working Group, “NIST Big Data Interoperability Framework: Volume 2, Big Data Taxonomies (NIST SP 1500-2 VERSION 3),” National Institute of Standards; Technology (NIST), Gaithersburg, MD, Jul. 2019 [Online]. Available: [https://bigdatawg.nist.gov/show\\_InputDoc.php](https://bigdatawg.nist.gov/show_InputDoc.php)
- [4] W. L. Chang (Co-Chair), G. Fox (Subgroup Co-chair), and NIST Big Data Public Working Group, “NIST Big Data Interoperability Framework: Volume 3, Big Data Use Cases and General Requirements (NIST SP 1500-3 VERSION 3),” National Institute of Standards; Technology (NIST), Gaithersburg, MD, Jul. 2019 [Online]. Available: [https://bigdatawg.nist.gov/show\\_InputDoc.php](https://bigdatawg.nist.gov/show_InputDoc.php)
- [5] W. L. Chang (Co-Chair), A. Roy (Subgroup Co-chair), M. Underwood (Subgroup Co-chair), and NIST Big Data Public Working Group, “NIST Big Data Interoperability Framework: Volume 4, Big Data Security and Privacy (NIST SP 1500-4 VERSION 3),” National Institute of Standards; Technology (NIST), Gaithersburg, MD, Jul. 2019 [Online]. Available: [https://bigdatawg.nist.gov/show\\_InputDoc.php](https://bigdatawg.nist.gov/show_InputDoc.php)
- [6] W. L. Chang (Co-Chair), S. Mishra (Editor), and NIST Big Data Public Working Group, “NIST Big Data Interoperability Framework: Volume 5, Big Data Architectures White Paper Survey (NIST SP 1500-5 VERSION 1),” National Institute of Standards; Technology (NIST), Gaithersburg, MD, Sep. 2019 [Online]. Available: [https://bigdatawg.nist.gov/show\\_InputDoc.php](https://bigdatawg.nist.gov/show_InputDoc.php)
- [7] W. L. Chang (Co-Chair), D. Boyd (Subgroup Co-chair), O. Levin (Version 1 Subgroup Co-Chair), and NIST Big Data Public Working Group, “NIST Big Data Interoperability Framework: Volume 6, Big Data Reference Architecture (NIST SP 1500-6 VERSION 3),” National Institute of Standards; Technology (NIST), Gaithersburg, MD, Jul. 2019 [Online]. Available: [https://bigdatawg.nist.gov/show\\_InputDoc.php](https://bigdatawg.nist.gov/show_InputDoc.php)
- [8] W. L. Chang (Co-Chair), R. Reinsch (Subgroup Co-chair), D. Boyd (Version 1 Subgroup Co-chair), C. Buffington (Version 1 Subgroup Co-chair), and NIST Big Data Public Working Group, “NIST Big Data Interoperability Framework: Volume 7, Big Data Standards Roadmap

(NIST SP 1500-7 VERSION 3)," National Institute of Standards; Technology (NIST), Gaithersburg, MD, Jul. 2019 [Online]. Available: [https://bigdatawg.nist.gov/show\\_InputDoc.php](https://bigdatawg.nist.gov/show_InputDoc.php)

[9] W. L. Chang (Co-Chair), G. von Laszewski (Editor), and NIST Big Data Public Working Group, "NIST Big Data Interoperability Framework: Volume 8, Big Data Reference Architecture Interfaces (NIST SP 1500-9 VERSION 2)," National Institute of Standards; Technology (NIST), Gaithersburg, MD, Jul. 2019 [Online]. Available: [https://bigdatawg.nist.gov/show\\_InputDoc.php](https://bigdatawg.nist.gov/show_InputDoc.php)

[10] W. L. Chang (Co-Chair), R. Reinsch (Subgroup Co-chair), C. Austin (Editor), and NIST Big Data Public Working Group, "NIST Big Data Interoperability Framework: Volume 9, Adoption and Modernization (NIST SP 1500-10 VERSION 2)," National Institute of Standards; Technology (NIST), Gaithersburg, MD, Jul. 2019 [Online]. Available: [https://bigdatawg.nist.gov/show\\_InputDoc.php](https://bigdatawg.nist.gov/show_InputDoc.php)

[11] NIST, "V1.0 final version page of the nbd-pwg website." Web Page, Sep-2015 [Online]. Available: [https://bigdatawg.nist.gov/V1\\_output\\_docs.php](https://bigdatawg.nist.gov/V1_output_docs.php)

[12] NIST, "21.0 final version page of the nbd-pwg website." Web Page, Sep-2015 [Online]. Available: [https://bigdatawg.nist.gov/V2\\_output\\_docs.php](https://bigdatawg.nist.gov/V2_output_docs.php)

[13] The White House Office of Science and Technology Policy, "Big Data is a Big Deal." OSTP Blog, Feb-2014 [Online]. Available: <http://www.whitehouse.gov/blog/2012/03/29/big-data-big-deal>

[14] Department of Defense, "The dodaf architecture framework version 2.02," Department of Defense, Report 2.02, Apr. 2010 [Online]. Available: <https://dodcio.defense.gov/library/dod-architecture-framework/>

[15] G. von Laszewski, "NIST bdra vol 8. GitHub issues." GitHub, Jun-2019 [Online]. Available: <https://github.com/cloudmesh/cloudmesh-nist/issues>

[16] G. von Laszewski, "Nist bdra volume 8 github history." GitHub, Jun-2019 [Online]. Available: <https://github.com/cloudmesh/cloudmesh-nist/commits/master/docs/nistvol8-2.epub>

[17] G. von Laszewski *et al.*, "NIST big data interoperability framework: Volume 8, reference architecture interfaces," National Institute of Standards; Technology (NIST), Gaithersburg, MD, Special Publication (NIST SP), Oct. 2015 [Online]. Available: <https://github.com/cloudmesh/cloudmesh-nist/raw/master/history/NIST.SP.1500-9.pdf>

[18] G. von Laszewski, F. Wang, B. Abdul-Wahid, H. Lee, G. C. Fox, and and Wo Chang, "Cloudmesh in support of the nist big data architecture framework," Indiana University, 2017 [Online]. Available: <https://github.com/cyberaide/nist/blob/master/vonLaszewski-nist.pdf>

[19] G. von Laszewski, "NIST bdra vol 8. OpenAPI specifications." GitHub, Jun-2019

[Online]. Available: <https://github.com/cloudmesh-community/nist/tree/master/spec>

[20] G. von Laszewski, “Configuration file example: Coudmesh4.yaml.” GitHub, Jun-2019 [Online]. Available: <https://github.com/cloudmesh/cloudmesh-cloud/blob/master/cloudmesh/etc/cloudmesh4.yaml>

[21] Internet2 Middleware Architecture Committee for Education, “EduPerson object class specification,” Internet2, 2016, 201602, Mar. 2016 [Online]. Available: <http://software.internet2.edu/eduperson/internet2-mace-dir-eduperson-201602.html>