

PLUNGING INTO KUBERNETES cloudogu


— AN INTRODUCTION


JOHANNES SCHNATTERER CLOUDOGU GMBH


VERSION: 202007061906-EA91F6A



Container Recap







[₱] https://web.archive.org/web/20180701005535/https://www.docker.com/what-container



- For some use cases: Nothing!
- For others:
 - High availability
 - Load Balancing
 - Solutions for challenges of distributed systems, e.g networking, storage
 - Scaling out containers
 - Rolling updates

Solution:

Container orchestrator



Kubernetes (k8s)

You will see the following features hands-on:

- Scheduling containers on multiple nodes
- Scaling out (scaling horizontally)
- Load balancing
- Self healing
- Rolling updates



Cluster access

Start container with all tools necessary \$ docker run -it cloudogu/k8s-training \$ k8s-training-auth fdt 2020 # Test connection: no error means success \$ kubectl version

First deployment

```
$ NAME=think-of-something-unique
$ kubectl create deployment $NAME --image=cloudogu/hello-k8s


# Success?
$ k get deployment $NAME
```

Access via the internet


```
k expose deployment $NAME --port=80 --target-port 8080 --type=LoadBalancer

# Query EXTERNAL-IP, then open in browser
k get service $NAME
```






Deployment → **Pod** → **Container**



\$ k get pod | grep \$NAME

Pod → Node



- \$ k get pod -owide \$ k get node



Scaling out


```
$ k scale deployment $NAME --replicas=3
$ k get deployment $NAME
$ k get pod | grep $NAME
```

Load Balancing

- Reload app in browser multiple times (look at "pod:")
- or run script:

```
# k get service $NAME
$ EXTERNAL_IP=w.x.y.z
$ while [ 1 ]; do echo $(curl -s http://$EXTERNAL_IP/api/hostName); done
```

Services



Self healing

```
# New terminal (or use tmux)
$ docker run -it cloudogu/k8s-training
$ k8s-training-auth fdt 2020

# k get service $NAME
$ EXTERNAL_IP=w.x.y.z
$ while [ 1 ]; do echo $(curl -s http://$EXTERNAL_IP/api/hostName); done

$ k scale deployment $NAME --replicas=2
$ k get pod | grep $NAME

$ PODNAME=one-of-your-pods
$ k delete pod $PODNAME

$ k get pod | grep $NAME
```

Rolling update



Key takeaways

- **k8s** run containers in a cluster (on multiple nodes)
- pod smallest resource in k8s (comprising containers)
- deployment
 - scaling out containers
 - self-healing
 - rolling updates
- service
 - cluster access
 - load balancing

Johannes Schnatterer

Cloudogu GmbH

- my.cloudogu.com
- Cloudogu.com/schulungen



- Questions or feedback?
- https://forum.cloudogu.com/topic/65
- @cloudogu
- @jschnatterer

#!/usr/bin/env bash BASEDIR=\$(dirname \$0) sed -n -e '/bash/, // p' \${BASEDIR}/03-k8s.md | sed '/bash/d;

s//\n---\n/' | tee listings.txt