

# // KUBERNETES EINSTIEG: MIT DER TÜR INS HAUS

JOHANNES SCHNATTERER

*CLOUDOGU GMBH*

VERSION: 202007081513-5A7D5E5



# Pull image for workshop

```
# Start container with all tools necessary for workshop  
$ docker run -it clouddogu/k8s-training
```

# ▮ Container Recap

▮ <https://web.archive.org/web/20180701005535/https://www.docker.com/what-container>

# Operations on "plain" Docker host in production — what is missing?

- ✈ For some use cases: Nothing!
- For others:
  - High availability
  - Load Balancing
  - Solutions for challenges of distributed systems, e.g networking, storage
  - Scaling out containers
  - Rolling updates

**Solution:**

**Container orchestrator**



## Kubernetes (k8s)

You will see the following features hands-on:

- Scheduling containers on multiple nodes
- Scaling out (scaling horizontally)
- Load balancing
- Self healing
- Rolling updates





# Cluster access

```
# In clouddogu/k8s-training container - Create cluster config  
$ k8s-training-auth fdt 2020  
  
# Test connection: no error means success  
$ kubectl version
```

# First deployment

```
$ NAME=think-of-something-unique  
$ kubectl create deployment $NAME --image=clouddogu/hello-k8s  
# Success?  
$ k get deployment $NAME
```

# Access via the internet

```
k expose deployment $NAME --port=80 --target-port 8080 --type=LoadBalancer  
  
# Query EXTERNAL-IP, then open in browser  
k get service $NAME
```

▯ <https://media.giphy.com/media/z9sFrQMfEME5a/giphy.gif>



# Deployment → Pod → Container

```
$ k get pod | grep $NAME
```

# Pod ↔ Node

```
$ k get pod -owide  
$ k get node
```

# High availability?



# Scaling out

```
$ k scale deployment $NAME --replicas=2  
$ k get deployment $NAME  
$ k get pod | grep $NAME
```

# Load Balancing

- Reload app in browser multiple times (look at "pod:")
- or run script:

```
# k get service $NAME  
$ EXTERNAL_IP=w.x.y.z  
$ while [ 1 ]; do echo $(curl -s http://$EXTERNAL_IP/api/hostname); done
```

# Services

# Self healing

```
# New terminal (or use tmux)
$ docker run -it clouddogu/k8s-training
$ k8s-training-auth fdt 2020
```

```
# k get service $NAME
$ EXTERNAL_IP=w.x.y.z
$ while [ 1 ]; do echo $(curl -s http://$EXTERNAL_IP/api/hostname); done
```

```
$ k get pod | grep $NAME
```

```
$ PODNAME=one-of-your-pods
$ k delete pod $PODNAME
```

```
$ k get pod | grep $NAME
```

# Rolling update

```
$ EXTERNAL_IP=w.x.y.z
$ while [ 1 ]; do
    echo $(curl -s --connect-timeout 1 -m 1 http://$EXTERNAL_IP/api/appVersion);
done
# -m 0 max-time
```

```
# Other terminal
$ k get pod | grep $NAME

$ k set image deploy $NAME hello-k8s=cloudogu/hello-k8s:1.9.1

# Multiple times
$ k get pod | grep $NAME
```



# Key takeaways

- **k8s** - run containers in a cluster (on multiple nodes)
- **pod** - smallest resource in k8s (comprising containers)
- **deployment**
  - scaling out containers
  - self-healing
  - rolling updates
- **service**
  - cluster access
  - load balancing



# Johannes Schnatterer

Cludogu GmbH

▮ [my.cludogu.com](https://my.cludogu.com)

▮ [cludogu.com/schulungen](https://cludogu.com/schulungen)

▮ **Questions or feedback?**

▮ <https://forum.cludogu.com/topic/65>

 [@cludogu](https://twitter.com/cludogu)

 [@jschnatterer](https://twitter.com/jschnatterer)