// CODE ☑ CLUSTER: BOOSTING DEVELOPMENT WITH A LOCAL KUBERNETES OPS PLATFORM

Johannes Schnatterer, Cloudogu GmbH



@ @schnatterer@floss.social

in in/jschnatterer

Version: 202406050933-a7d678d





What is your profession?

Software Engineer / Developer



What is your profession?

Platform Engineer / Ops person



Who uses Kubernetes for local development?

K3d Minkube Microk8s k3s KIND

Docker Desktop kOs

Rancher Desktop




Kubernetes is a platform for building platforms. It's a better place to start; not the endgame.

10:04 PM · Nov 27, 2017

237 Reposts 44 Quotes 748 Likes 22 Bookmarks

twitter.com/kelseyhightower/status/935252923721793536

Start a local k8s cluster with one command



Next, start the platform


















So, let's write a little script...



Why not start the platform with one command?

Meet GOP

a GitOps-based operational stack (platform)













```
COMMIT='42e5f80'
bash <(curl -s \
  "https://raw.githubusercontent.com/cloudogu/gitops-playground/$COMMIT/scripts/init-cluster.sh") \
  --bind-ingress-port=80 \
   && docker run --rm -t -u (id -u) \setminus
    -v ~/.config/k3d/kubeconfig-gitops-playground.yaml:/home/.kube/config \
    --net=host \
    ghcr.io/cloudogu/gitops-playground:$COMMIT --yes --base-url=http://localhost --ingress-nginx \
      --argord --monitoring --vault=dev --mailhog
```







scripts/init-cluster.sh

```
k3d cluster create gitops-playground \
  # Mount port for ingress
  -p 80:80@server:0:direct \
  # Pin image for reproducibility
  --image=rancher/k3s:v1.29.1-k3s2 \
  # Disable built-in ingress controller, because we want to use the same one locally and in prod
  --k3s-arg=--disable=traefik@server:0 \
  # Allow node ports < 30000
  --k3s-arg=--kube-apiserver-arg=service-node-port-range=8010-65535@server:0 \
  # Hacks to make Docker available in Jenkins
  -v /var/run/docker.sock:/var/run/docker.sock@server:0 \
  -v /etc/group:/etc/group@server:0 -v /tmp:/tmp@server:0 \
  -p 30000:30000@server:0:direct
# Write kubeconfig to ~/.config/k3d/kubeconfig-gitops-playground.yaml
k3d kubeconfig write gitops-playground
```

docker run

```
docker run
  # Remove container after running, keeping your device clean
  # (remove in case of error to preserve logs)
  - - rm
  # Colorful output, please
  -t
  # Run as current user, so files written to /tmp are accessible for you
  -u $(id -u) \
  # Mount kubeconfig for k3d
  -v ~/.config/k3d/kubeconfig-gitops-playground.yaml:/home/.kube/config \
  # Make k3d cluster available
  --net=host \
ghcr.io/cloudogu/gitops-playground:$COMMIT #Params for image go here
```

ghcr.io/cloudogu/gitops-playground

- OCI image
- Contains logic to install and configure the tools
- App written in Groovy (and bash (2))
- Additional resources to run e.g. in air-gapped envs







Your turn



@ giphy.com/gifs/JIX9t2j0ZTN9S

Exercises "\"





Deploy broken app via GitOps, get alerted and fix problem

• GitOps process 👀 🗔 😨









Promote a change in code all the way to production using GitOps

Monitoring (2)





Deploy a Grafana dashboard for an app using GitOps

Secrets Management





Integrate secrets into app, propagate updates automatically

Progressive Delivery



Watch a canary release live with argo roll

Getting started

- Login: admin / admin
- scmm.localhost
- argocd.localhost
- ografana.localhost
- wault.localhost
- mailhog.localhost
- jenkins.localhost



Exercise: GitOps+Alerting Parting






Deploy broken app via GitOps, get alerted and fix problem

Exercise: Alerting

- 1. Add repo to Argo CD
- 2. Create Argo CD Application YAML
- 3. Deploy, receive alert and fix app
- Hint: Edit file in SCM-Manager



1. Add repo to Argo CD

Add this repo to Argo CD (via GitOps):

http://scmm-scm-manager.default.svc.cluster.local/scm/repo/exercises/broken-application

- 1. Add to repositories in Argo CD's config:
 - scmm.localhost/scm/repo/argocd/argocd/code/sources/main/argocd/values.yaml
- 2. Authorize Project to use the repo by adding it to sourceRepos here:
 - scmm.localhost/scm/repo/argocd/argocd/code/sources/main/projects/example-apps.yaml

2. Create Argo CD Application YAML

- Go to argocd.localhost, click + NEW APP
- Enter Name: broken
- Click on Project Name, choose example apps
- Click on Repository URL, choose the broken-application repo
- Enter Path: .
- Click on Cluster URL, choose https://kubernetes.default.svc
- Enter Namespace: example-apps-staging
- At the top, click EDITAS YAML and copy content

3. Deploy, receive alert and fix app


- Paste content here:
 - scmm.localhost/scm/repo/argocd/example-apps/code/sourceext/create/main/argocd/
- Enter Filename: broken.yaml, and Commit Message, then click commit



- Check email in mailhog.localhost
- Follow link to ArgoCD-UI, analyse error
- Fix error in repo:
 - scmm.localhost/scm/repo/argocd/example-apps/code/sources/main/argocd/broken.yaml
- Go to pargocd.localhost/applications/argocd/broken, click
- Open application in Browser
- Have a closer look at the concepts behind this



Alerting in GOP





Argo CD config:

- github.com/cloudogu/gitops-playground/blob/0.2.0/argocd/argocd/argocd/values.ftl.yaml
- scmm.localhost/scm/repo/argocd/argocd/code/sources/main/argocd/values.yaml

See also

- GitOps repo structure in GOP
- ** Exercise: GitOps process



Exercise: GitOps process • Ci









Promote a change in code all the way to production using GitOps


- Warmup
- GitOps with CI server and promotion



- 1. Open Argo CD Application:
 - argocd.localhost/applications/example-apps-staging/petclinic-plain
- 2. Open app in Browser:
 - staging.petclinic-plain.petclinic.localhost
- 3. Change welcome message in config repo:
 - scmm.localhost/scm/repo/argocd/example-apps/code/sources/main/apps/spring-petclinic-plain/staging/generatedResources/messages.yaml
- 4. Press CREFRESH in ArgoCD UI
- 5. Restart deploy in ArgoCD UI 🔁 Watch GitOps deployment
- 6. Reload app in Browser 🗅 Shows new message 🔯



Hint: Edit file in SCM-Manager



GitOps with CI server and promotion 🚀

First:

Accept Pull Request for petclinic-plain to deploy prod



Then:

- 1. Change app, build image, deploy staging
- 2. Accept PR, deploy production


1. Change app, build image, deploy staging

- 1. Open staging app in Browser:
 - staging.petclinic-plain.petclinic.localhost
- 2. Change welcome message in app repo
 - scmm.localhost/scm/repo/argocd/petclinic-plain/code/sources/main/src/main/resources/messages/messages.properties
- 3. Wait for Build
 - jenkins.localhost/job/example-apps/job/petclinic-plain/job/main
- 4. Open Argo CD Application for staging:
 - argocd.localhost/applications/example-apps-staging/petclinic-plain
- 5. Press Greffesh in ArgoCD UI Watch GitOps deployment
- 6. Reload app in Browser D Shows message in staging 🗟

2. Accept PR, deploy production

- 1. Open production app in Browser:
 - production.petclinic-plain.petclinic.localhost
- 2. Open Argo CD Application for production:
 - argocd.localhost/applications/example-apps-production/petclinic-plain
- 3. Accept Pull Request for petclinic-plain
 - scmm.localhost/scm/repo/argocd/example-apps/pull-requests
- 4. Press CREFRESH in ArgoCD UI Watch GitOps deployment
- 5. Reload app in Browser D Shows message in production 😂 😂
- 6. Have a closer look at the concepts behind this

GitOps repo structure in GOP



- scmm.localhost/scm/repo/argocd/petclinic-plain/code/sources/main/Jenkinsfile uses
- github.com/cloudogu/gitops-build-lib

cloudogu.com/blog/gitops-repository-patterns-part-6-examples



Exercise: Secrets Management





Integrate secrets into app, propagate updates automatically


- Warmup
- Mount secret into app

Warmup 💖

- Secret exposed via HTTP
 - staging.nginx-helm.nginx.localhost/secret
- Change in Vault:
 - vault.localhost/ui/vault/secrets/secret/edit/staging/nginx-helm-jenkins
- Watch it propagate automatically (<2 min)
 Either reload Browser or:

```
while ; do echo -n "$(date '+%Y-%m-%d %H:%M:%S'): " ; \
   curl staging.nginx-helm.nginx.localhost/secret/ ; echo; sleep 1; done
```

Warmup in time-lapse





Mount secret into app 🚀



TODO summarize and link steps

External Secrets Operator with Vault





ESO+Vault config in GOP

- SecretStore per Namespace:
 - scmm.localhost/scm/repo/argocd/cluster-resources/code/sources/main/misc/secrets/secret-store-staging.yaml
- Example External Secret:
 - scmm.localhost/scm/repo/argocd/nginx-helm-jenkins/code/sources/main/k8s/staging/external-secret.yaml
- Mounted into app:
 - scmm.localhost/scm/repo/argocd/nginx-helm-jenkins/code/sources/main/k8s/values-shared.yaml

TODO

Johannes Schnatterer, Cloudogu GmbH



b Join my team: cloudogu.com/join/cloud-engineer







Legal

- Vault is a registered trademark of Hashicorp
- Docker is a registered trademark of Docker Inc
- Kubernetes is a registered trademark of the Linux Foundation
- Git is a registered trademark of Software Freedom Conservancy
- Grafana is a registered trademark of Grafana Labs The Grafana Labs Marks are trademarks of Grafana Labs, and are used with Grafana Labs' permission. We are not affiliated with, endorsed or sponsored by Grafana Labs or its affiliat