

# // CODE ➡ CLUSTER: BOOSTING DEVELOPMENT WITH A LOCAL KUBERNETES OPS PLATFORM

Johannes Schnatterer, Clouddogu GmbH

Slides



 @schnatterer@floss.social

 in/jschnatterer

Version: 202405231747-0983d13



# What is your profession?



Software Engineer / Developer



# What is your profession?



Platform Engineer / Ops person



**Who uses Kubernetes for local development?**

k3d Minkube Microk8s k3s KIND

Docker Desktop k0s

Rancher Desktop



**Kelsey Hightower** ✓

@kelseyhightower

Kubernetes is a platform for building platforms. It's a better place to start; not the endgame.

10:04 PM · Nov 27, 2017

---


**237** Reposts   **44** Quotes   **748** Likes   **22** Bookmarks

 [twitter.com/kelseyhightower/status/935252923721793536](https://twitter.com/kelseyhightower/status/935252923721793536)


# Start a k8s cluster in ~10s

```
k3d cluster create test
```

# Now start the platform



NGINX...



**Let's write a little script...**





a98089f ▾

/ scripts / apply.sh

↑ Top

Code

Blame

Raw



```
669 --metrics | --monitoring ) shift;; # Ignore, used in groovy only
670 --mailhog-url           ) shift 2;; # Ignore, used in groovy only
671 --vault                 ) shift 2;; # Ignore, used in groovy only
672 --petclinic-base-domain ) shift 2;; # Ignore, used in groovy only
673 --nginx-base-domain    ) shift 2;; # Ignore, used in groovy only
674 --destroy              ) DESTROY=true; shift;;
675 --config-file          ) shift;; # Ignore, used in groovy only
676 --config-map           ) shift;; # Ignore, used in groovy only
677 --output-config-file   ) OUTPUT_CONFIG_FILE=true; shift;;
678 --                     ) shift; break ;;
679 *) break ;;
680 esac
681 done
682 }
683
684 main "$@"
```



**Wouldn't it be great to start the platform locally with one command?**

# Meet GOP



```
COMMIT='8e21bd4'
bash <(curl -s \
  "https://raw.githubusercontent.com/cloudogu/gitops-playground/$COMMIT/scripts/init-cluster.sh" \
  --bind-ingress-port=80 \
  && sleep 2 && docker run --rm -it --pull=always -u $(id -u) \
    -v ~/.config/k3d/kubeconfig-gitops-playground.yaml:/home/.kube/config \
    --net=host \
    ghcr.io/cloudogu/gitops-playground:$COMMIT --yes --argocd --base-url=http://local.gd
# Other interesting options --monitoring --vault=dev
```