



# Development of an Intelligent Thermal Management System for BYD DM-i Hybrid Engine

Guoxiang lu, Dongsheng Yang, Yulong Rong, Zewen Gong, and Bo Wang BYD Auto Industry Company Limited

**Citation:** lu, G., Yang, D., Rong, Y., Gong, Z. et al., "Development of an Intelligent Thermal Management System for BYD DM-i Hybrid Engine," SAE Technical Paper 2021-01-1153, 2021, doi:10.4271/2021-01-1153.

## Abstract

BYD recently introduced its new DM-i (Dual Mode-Intelligent) plug-in hybrid architecture with a new dedicated 1.5NA (Naturally Aspirated) high-efficiency engine, which can reach a peak of 43% brake thermal efficiency. With this architecture, the vehicle is mainly driven by motors and engine only starts when required. This requires that once started, the engine can reach its best working temperature as quick as possible. To achieve this target, a new intelligent thermal management system was designed. This system adopted an advanced split cooling strategy to control the flow ratio between cylinder block and head, which was realized by the combination of one electronic thermostat and one wax thermostat. An electronic water pump was used to actively control the coolant flow

rate. Together with the intelligent control of thermal needs under all working conditions, the new thermal management system realized the following benefits: faster engine warm-up, better fuel economy and lower pollutant emissions. 1D (One Dimensional) simulation was used to optimize the flow ratio between cylinder block and head. By analyzing the flow distribution, temperature level and pressure drop of each component in the HT (High Temperature) loop and LT (Low Temperature) loop, the cooling performance of this new thermal management system was evaluated and optimized. 3D (Three Dimensional) simulation was used to optimize the flow channel design. Finally, the performance of the thermal management cooling system was validated on the engine test bench and the coolant temperature was calibrated for the whole engine map.

## Introduction


The intelligent engine thermal management system is able to decouple the cooling system operation with engine speed. The traditional mechanical driven parts are replaced by electrical ones, such as electronic water pump, electronic thermostat and electronic fan, etc., so that the cooling performance can be precisely controlled with the optimized control strategy. The performance of the thermal management system is critical to realize good fuel economy and reduced emissions. A good engine thermal management system should be able to realize the following functions [1]:

1. Keep the engine working at the optimal temperature, reduce knock tendency and improve fuel economy.
2. Reduce the engine parasitic loss, shorten the warm-up time and reduce emissions.
3. Keep the optimal oil temperature to reduce engine friction and wear, increase the engine service interval and durability.

Lots of researches have been done in the last few decades on the intelligent engine thermal management system. Cipollone et al. [2] used 1D simulation to study the effect of double cooling circuits at different temperatures on engine performance. Results showed that the engine warm-up time

can be reduced by 30% with 4%~5% benefit in fuel consumption. Castiglione et al. [3] proposed a Robust Model Predictive Control (MPC) methodology for quick engine warm up, which reduced 60% the coolant flow with the help of electronic water pump. Results showed that compared to the traditional cooling system, it took 180 seconds less for the cylinder wall to be warmed up to 120°C. Cortona et al. [4] designed and simulated the performance of two cooling system setup, one with an electronic water pump and a wax thermostat, another one with an electronic water pump and an electronic thermostat. Results were validated with bench test data. It was shown that the combination of electronic water pump and electronic thermostat can precisely control the coolant temperature, reduce the water pump energy consumption and achieve quick engine warm up. Choukroun et al. [5] developed an intelligent thermal management system consisting of an electronic water pump, an electronic thermostat and an electronic fan. The performance was checked by simulation and validated by wind tunnel test results. It was shown that this concept allowed a reduced warm-up time by 50% and 2%~3% fuel consumption on the NEDC cycle.

BYD introduced a new DM-i plug-in hybrid architecture recently, aiming to have a fuel consumption lower than 4.0 L/100 km. In order to meet the requirement, a new 1.5L DHE (Dedicated Hybrid Engine) was developed. The compression


**FIGURE 19** The external circulation.

## State Four: HT Loop

As shown in Figure 19, when the coolant temperature rises to 95°C, the electronic thermostat will open. In this state, the electronic thermostat and WP are used to accurately control the coolant flow rate so that the coolant can be always kept at the optimal temperature as calibrated.

At low loads, the coolant temperature is higher than 95°C so the electronic thermostat opens naturally without additional heating. The electronic water pump runs at low speed to reduce its power consumption. While for the high load area, when the coolant temperature is below 95°C, the electronic thermostat turns on heating mode to keep the engine runs in HT loop.

Figure 20 shows the comparison of this intelligent thermal management system when applied to DM-i plug-in hybrid architecture and that of the previous generation with a wax thermostat and a mechanical water pump. The warm-up time is shortened by 20% while fuel consumption in the charge-sustaining WLTC cycle can be reduced by 1.3%.

**FIGURE 20** The warm-up time comparison.

## Conclusions

1. A new thermal management system was developed for BYD DM-i 1.5L DHE, including: split cooling of cylinder block and head, electronic WP, electronic thermostat and wax thermostat. Combined with intelligent control strategy, the thermal management performance was greatly improved.
2. 1D and 3D coupled simulation was adopted during the design process. 3D CFD provided the pressure drop, heat transfer coefficient for the 1D simulation and 1D simulation in turn provided flow rate boundary condition for the 3D simulation. The coupling of the 1D and 3D simulation improved simulation accuracy.
3. Simulation results were validated with thermal test bench data. Results showed good agreement within 10% difference. These results showed good accuracy of the 1D and 3D coupling simulation and it can be used to guide the thermal management system concept development with good confidence. The simulation model can also be used for future system upgrading to save cost and development time.
4. Coolant temperature map was calibrated, and four working states were realized. The vehicle's warm-up time was shortened by 20%, and the charge-sustaining fuel consumption in WLTC cycle can be reduced by 1.3%.

## References

1. Canhui, L., Like, X., and Ling, L., "Contribution of the Engine Thermal Management System to Vehicle Fuel Economy," *Design Research* 1003-8639 (Mar. 2014).
2. Cipollone, R., Di Battista, D., and Gualtieri, A., "A Novel Engine Cooling System with Two Circuits Operating at Different Temperatures," *Energy Conversion and Management* 75 (2013): 581-592.
3. Castiglione, T., Pizzonia, F., and Bova, S., "A Novel Cooling System Control Strategy for Internal Combustion Engines," *SAE Int. J. Mater. Manf.* 9, no. 2 (2016), doi:10.4271/2016-01-0226.
4. Cortona, E. and Onder, C., "Engine Thermal Management with Electronic Cooling Pump," SAE Technical Paper, 2000-01-0965, 2000 <https://doi.org/10.4271/2000-01-0965>.
5. Choukroun, A. and Chanfreau, M., "Automatic Control of Electronic Actuators for an Optimized Engine Cooling Thermal Management," SAE Technical Paper, 2001-01-1758 (2001). <https://doi.org/10.4271/2001-01-1758>.
6. Confer, K., Kirwan, J., and Engineer, N., "Development and Vehicle Demonstration of a Systems-Level Approach to Fuel Economy Improvement Technologies," SAE Technical Paper 2013-01-0280 (2013). <https://doi.org/10.4276/2013-01-0280>.
7. Zhu, D., Pritchard, E.G.D., Silverberg, L.M. et al., "A New System Development Framework Driven by a Model-Based Testing Approach Bridged by Information Flow," *IEEE*

*Systems Journal* 12, no. 3 (2016): 2917-2924, doi:[10.1109/JSYST.2016.2631142](https://doi.org/10.1109/JSYST.2016.2631142).

8. Yibin, D., Ronghua, H., Zhaowen, W. et al., "Research on Vehicle Thermal Management System," *Auto Engine* (Jan. 2011).
9. Nan, W., Gang Zhi, T., and Li, Z., "Analysis the Cooling Performance of Cooling Jacket in Engine," *Design and Research*, Dec. 2011.
10. Baoliang, Z., Qinyin, F., Guanghong, H. et al., "1D/3D Coupling Simulation on Vehicle Thermal Management," *Automotive Engineering* (Oct. 2011).
11. Ravi, V., Jentz, R., Kumar, V. et al., "Assessment of Exhaust Actuator Control at Low Ambient Temperature Conditions," SAE Technical Paper [2021-01-0681](https://doi.org/10.4271/2021-01-0681) (2021). <https://doi.org/10.4271/2021-01-0681>.
12. Zhenzhen, H., Jimin, N., and Xiuyong, S., "Optimization Design of Rear-Engine Bus Cooling System Based on 1D/3DCoupling Simulation," SAE Technical Paper [2018-01-0771](https://doi.org/10.4271/2018-01-0771) (2018). <https://doi.org/10.4271/2018-01-0771>.
13. C, S., Sundaram, V., and S, S., "Simulation of Split Engine Cooling System," SAE Technical Paper [2015-26-0196](https://doi.org/10.4271/2015-26-0196) (2015). <https://doi.org/10.4271/2015-26-0196>.

## Contact Information

**Guoxiang Lu**

[harry\\_lu2006@yahoo.com.cn](mailto:harry_lu2006@yahoo.com.cn)

## Definitions/Abbreviations

**DM-i** - Dual Mode-Intelligent

**HT** - High Temperature

**LT** - Low Temperature

**1D** - One Dimensional

**3D** - Three Dimensional

**DHE** - Dedicated Hybrid Engine

**TMM** - Thermal Management Module

**BTE** - Brake Thermal Efficiency

**OEM** - Original Equipment Manufacturer

**WP** - Water Pump

**WJ** - Water Jacket

**IEM** - Integrated Exhaust Manifold

**HTC** - Heat Transfer Coefficient

**WOT** - Wide Open Throttle

**EGR** - Exhaust Gas Recirculation

**BSFC** - Brake Specific Fuel Consumption

**ECU** - Engine Control Unit