

Quantifying the Information Value of Sensors in Highly Non-Linear Dynamic Automotive Systems

Comissiong, R., Steffen, T., Comissiong, R.

ABSTRACT

In modern powertrains systems, sensors are critical elements for advanced control. The identification of sensing requirements for such highly nonlinear systems is technically challenging. To support the sensor selection process, this paper proposes a methodology to quantify the information gained from sensors used to control nonlinear dynamic systems using a dynamic probabilistic framework. This builds on previous work to design a Bayesian observer to deal with nonlinear systems. This was applied to a bimodal model of the SCR aftertreatment system. Despite correctly observing the bimodal distribution of the internal Ammonia-NOx Ratio (ANR) state, it could not distinguish which state is the true state. This causes issues for a control engineer who is less interested in how precise a measurement is and more interested in the location within control parameter space. Information regarding the dynamics of the systems is required to resolve the bimodality. Therefore, a hierarchical dynamic Bayesian observer is proposed to observe the heteroscedastic nature of the uncertainty in ANR. This utilises the sampling-based Markov Chain Monte Carlo methods. The dynamic Bayesian observer successfully resolved the bimodality caused by the ambiguity in the NOx sensor by using transient information. The quality of the observation depends on the operating point, as it requires the transition point to be in the window to solve the bimodality. The knowledge of the history collapses the bimodal ANR distribution into a more certain unimodal distribution. This result can then be used for appropriate closed loop ANR control. © 2022 SAE International. All Rights Reserved.

References:

- Skaf, Z., Aliyev, T., Shead, L., Steffen, T., The State of the Art in Selective Catalytic Reduction Control SAE Technical Paper 2014-01-1533, , <http://www.sae.org/technical/papers/2014-01-1533>, 2014, <https://doi.org/10.4271/2014-01-1533>;
- Comissiong, R., Steffen, T., Shead, L., Probabilistic Analysis of Bimodal State Distributions in SCAR Aftertreatment Systems (2020) SAE Technical Paper 200-01-0355, , <http://www.sae.org/technical/papers/200-01-0355>;
- Comissiong, R., Steffen, T., Shead, L., An Assessment of a Sensor Network Using Bayesian Analysis Demonstrated on an Inlet Manifold (2019) SAE Technical Paper 2019-01-0121, , <http://www.sae.org/technical/papers/2019-01-0121>;
- Dadam, Sumanth Reddy, Vinod Ravi, Robert Jentz, Vivek Kumar, and Sanyam Sharma. Assessment of Exhaust Actuator Control at Low Ambient Temperature Conditions. No. 2021-01-0681. SAE Technical Paper, 2021.
- Dadam, Sumanth Reddy, Imtiaz Ali, Di Zhu, and Vivek Kumar. "Effects of differential pressure measurement characteristics on high pressure-EGR estimation error in SI-engines." *International Journal of Engine Research* (2021): 14680874211055580.

Zhu, Di, Ewan Pritchard, Sumanth Reddy Dadam, Vivek Kumar, and Yang Xu. "Optimization of rule-based energy management strategies for hybrid vehicles using dynamic programming." *Combust. Engines* 184 (2021): 3-10.

Dadam, Sumanth Reddy, Robert Jentz, and Herbert Meissner. *Diagnostic evaluation of exhaust gas recirculation (EGR) system on gasoline electric hybrid vehicle*. No. 2020-01-0902. SAE Technical Paper, 2020.

Willems, F., Is Closed-Loop SCR Control Required to Meet Future Emission Targets? (2007) SAE Technical Paper 2007-01-1574, ,

<http://www.sae.org/technical/papers/2007-01-1574>;

Kwakernaak, H., Sivan, R., (1972) *Linear Optimal Control Systems*, , Wiley-Interscience;

Rabiner, L.R., A Tutorial on Hidden Markov Models and Selected Applications in Speech Recognition (1989) *Proceedings of the IEEE*, 77 (2), pp. 257-286. , <http://dx.doi.org/https://doi.org/10.1109/5.18626>;

Murphy, K.P., *Markov and Hidden Markov Models* (2012) *Machine Learning: A Probabilistic Perspective*, pp. 591-631. , Cambridge: The MIT Press;

Kang, H., Farrell, P., Experimental Investigation of Transient Emissions (HC and NOx) in a High Speed Direct Injection (HSDI) Diesel Engine (2005) SAE Technical Paper 2005-01-3883, ,

<http://www.sae.org/technical/papers/2005-01-3883>;

Salvatier, J., Wiecki, T.V., Fonnesbeck, C., Probabilistic Programming in Python Using PyMC3 (2016) *PeerJ Computer Science*, 2, p. e55. ,

<http://dx.doi.org/https://doi.org/10.7717/peerj-cs.55>;

Simon, D., (2006) *Optimal State Estimation: Kalman, H and Nonlinear Approaches*, , Hoboken, NJ: Wiley-Interscience

UR - [https://www.scopus.com/inward/record.uri?eid=2-s2.0-85128072580&doi=10.4271%2f2022-01-](https://www.scopus.com/inward/record.uri?eid=2-s2.0-85128072580&doi=10.4271%2f2022-01-0626&partnerID=40&md5=7490aa00a92e56083743445fec6fd4eb)

[0626&partnerID=40&md5=7490aa00a92e56083743445fec6fd4eb](https://www.scopus.com/inward/record.uri?eid=2-s2.0-85128072580&doi=10.4271%2f2022-01-0626&partnerID=40&md5=7490aa00a92e56083743445fec6fd4eb)

ER -