

## Jenkins – Add Node to Jenkins Master

---

To add a Node/Slave to Jenkins master.

### Step 1:

Create an VM with same OS and install Java 1.8 as installed on Jenkins master.

Before you can install Jenkins, you need to setup a Java virtual machine on your system.

Here, let's install the latest OpenJDK Runtime Environment 1.8.0 using YUM:

```
sudo yum install java-1.8.0-openjdk.x86_64
```

After the installation, you can confirm it by running the following command:

```
java -version
```

This command will tell you about the Java runtime environment that you have installed:

```
openjdk version "1.8.0_91"
```

```
OpenJDK Runtime Environment (build 1.8.0_91-b14)
```

```
OpenJDK 64-Bit Server VM (build 25.91-b14, mixed mode)
```

In order to help Java-based applications locate the Java virtual machine properly, you need to set two environment variables: "JAVA\_HOME" and "JRE\_HOME".

```
sudo cp /etc/profile /etc/profile_backup
```

```
echo 'export JAVA_HOME=/usr/lib/jvm/jre-1.8.0-openjdk' | sudo tee -a /etc/profile
```

```
echo 'export JRE_HOME=/usr/lib/jvm/jre' | sudo tee -a /etc/profile  
source /etc/profile
```

Finally, you can print them for review:

```
echo $JAVA_HOME
```

```
echo $JRE_HOME
```

### Step2:

Create an project folder on the Node/Slave for the workspace area.

```
[root@localhost project]# pwd
/root/project
[root@localhost project]#
```

The folder should have the same user permission that would be used to authenticate Slave from Master.

For example, if you are using **centos** as the username then the folder “project” should have the same right as below.

```
[centos@localhost root]$ cd ~
[centos@localhost ~]$ ls
[centos@localhost ~]$ pwd
/home/centos
[centos@localhost ~]$ mkdir project
[centos@localhost ~]$ ls -l
total 0
drwxrwxr-x. 2 centos centos 5 May  5 00:26 project
centos@localhost ~$
```

If it does not then,

```
$ chown centos:centos project
```

### Step3:

On the Jenkins master, under the Manage Jenkins

## Jenkins – Add Node to Jenkins Master

The screenshot shows the Jenkins Master interface at the URL 192.168.1.105:8080/manage. On the left, there is a sidebar with 'Slave1' and two 'Idle' status indicators. The main content area lists several options: 'System Log', 'Load Statistics', 'Jenkins CLI', 'Script Console', 'Manage Nodes' (circled in black), and 'About Jenkins'. Each option has a brief description of its function.

Click on “Manage Nodes”.

The screenshot shows the Jenkins Nodes page. On the left sidebar, 'New Node' is circled in black. The main area displays a table of nodes. The table has columns for Name, Architecture, Clock Difference, Free Disk Space, Free Swap Space, Free Temp Space, and Response Time. The 'master' node is listed with a 'Data obtained' status.

S	Name	Architecture	Clock Difference	Free Disk Space	Free Swap Space	Free Temp Space	Response Time
	master	Linux (amd64)	In sync	4.32 GB	820.00 MB	4.32 GB	0ms
	Data obtained	12 min	12 min	12 min	12 min	12 min	12 min


Select as below and click “OK”

The screenshot shows the Jenkins 'New Node' configuration page. The 'Node name' field is set to 'Slave1'. The 'Permanent Agent' radio button is selected and circled in black. The 'Copy Existing Node' option is also visible. The 'OK' button is at the bottom right.

## Jenkins – Add Node to Jenkins Master

---

Click on “New Node”.



Provide the below

Name: < Any name>

Executors: no of jobs to be run parallelly on the slave.

Remote directory : -- on the slave node, the location where the “workspace” would be used temporarily during the JOB execution.


Label: -- Group of Slave machines, eg: -GR1

Launch Method : -- SSH agent

Host name : -- Ip address of the slave machine, eg:- 192.168.1.106.

Credentials: -- Username and pwd to login to the Slave machine by the Master.


In case the slave VM is simple usr and pwd. Then below



Click on “ Jenkins”.

Option 1: -- Adding username and password for VM’s created on laptop.

## Jenkins – Add Node to Jenkins Master



### Jenkins Credentials Provider: Jenkins

**Add Credentials**

Domain: Global credentials (unrestricted)

Kind: Username with password

Scope: Global (Jenkins, nodes, items, all child items, etc)

Username: root


Password: .....

ID:

Enter the username and pwd and click on “Save” Then the below screen, to select the credentials that is just configured


Launch method: Launch agent agents via SSH

Host: 192.168.1.106

Credentials: root/\*\*\*\*\* 

Host Key Verification Strategy: Known hosts file Verification Strategy

**Option 2: - For slave machines created on AWS EC2 instance.**



### Jenkins Credentials Provider: Jenkins

**Add Credentials**

Domain: Global credentials (unrestricted)

Kind: SSH Username with private key

Scope: Global (Jenkins, nodes, items, all child items, etc)

ID:

Description:

Username: centos

Private Key: ☒ Enter directly

Key: 


```
-----BEGIN RSA PRIVATE KEY-----
MIIEowIBAAKCAQEAhXPRbUP6TwUpTT0M0Govo3pxi7yHIntDpISVQpDQmpAlvHbUECQ4ZSFF3AhytSV5fVxvVfWDCvU
316D8cmRBO+dGCG980dy8ydaEcovHk1wyEB4GAr7o2TtnOzdiaeQRd66CFXXeFXd1DHKA==
-----END RSA PRIVATE KEY-----
```

Passphrase:

The credentials created should be selected as above screen.

## Jenkins – Add Node to Jenkins Master

---



Host: 192.168.1.106


Credentials: root/\*\*\*\*\* Add

Host Key Verification Strategy: Non verifying Verification Strategy

Availability: Keep this agent online as much as possible

Node Properties

Select “ non Verifying” as we don’t hve the SSL.



Availability: Keep this agent online as much as possible

**Node Properties**

- ☐ Disable deferred wipeout on this node
- ☐ Environment variables
- ☐ Tool Locations

Save


Click on save.


Once the Agent is successfully installed, the below screen would be visible.


## Jenkins – Add Node to Jenkins Master


---


Jenkins ▸ Nodes ▸ Slave1


 [Back to List](#)


 [Status](#)


 [Delete Agent](#)


 [Configure](#)


 [Build History](#)


 [Load Statistics](#)

 [Script Console](#)

 [Log](#)

 [System Information](#)

 [Disconnect](#)



### Agent Slave1

**Labels**  
[GR1](#)

**Projects tied to Slave1**  
None

[Build Executor Status](#)