



KubeCon



CloudNativeCon

North America 2023

# RBACdoors: How Cryptominers Are Exploiting RBAC Misconfigs



*Greg Castle*

*linkedin.com/in/greg-castle/*

*@mrgcastle*

*@gregcastle.bsky.social*

*GKE Security, Google Cloud*



*Vinayak Goyal*

*@vglovespizza*

*GKE Security, Google Cloud*

Slides: <https://sched.co/1R2tp>

# Cryptomining on Kubernetes



KubeCon



CloudNativeCon

North America 2023

March/April 2023

## CrowdStrike Discovers First-Ever Dero Cryptojacking Campaign Targeting Kubernetes

March 15, 2023 Benjamin Grap - Manoj Ahuja From The Front Lines



**Threat Alert**  
**First-Ever Attack  
Leveraging  
Kubernetes RBAC  
to Backdoor Clusters**



Attack walkthrough: what we saw on GKE

Root cause: Customer misconfig

Prevention

Detection

# What's new here?



KubeCon



CloudNativeCon

North America 2023



K8s misconfigs: [docker](#), [kubelet](#), [dashboard](#)



Container-delivered Cryptominers



Kubernetes-specific hiding and persistence

# High Level Attack Overview



KubeCon



CloudNativeCon

North America 2023

## Root Cause

Customer RBAC misconfiguration: give the whole Internet cluster-admin

## Discovery

Scan for API servers for access

## Execution

Create role bindings to privilege kube-system service account  
Create cryptomining daemonset “kube-controller” in kube-system

## Persistence

Create “cluster-admin” certificate with cluster-admin permissions

## Defense Evasion

Remove evidence of cluster-admin cert creation

Google cloud signals alert customer, GKE assists with investigation, GKE notifies handful of other customers

# What is cluster-admin?



KubeCon



CloudNativeCon

North America 2023

- **All** permissions
- for **all** resources

Root in cluster if used in a ClusterRoleBinding

Used many places, even when it shouldn't be

```
$ kubectl get clusterrole cluster-admin -o yaml
```

```
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
metadata:
  annotations:
  labels:
    kubernetes.io/bootstrapping: rbac-defaults
  name: cluster-admin
rules:
- apiGroups:
  - '*'
  resources:
  - '*'
  verbs:
  - '*'
- nonResourceURLs:
  - '*'
  verbs:
  - '*'
```

# What are system Users/Groups?




KubeCon



CloudNativeCon

North America 2023



# Uses for system:anonymous



KubeCon



CloudNativeCon

North America 2023

- On by default in K8s
- Allows access to health status and version via `system:public-info-viewer` `clusterRoleBinding`
- Load balancers [check liveness](#) before routing
- [kubeadm trust bootstrap](#)



# Note on system:authenticated



KubeCon



CloudNativeCon

North America 2023

All authenticated users! That could mean:

- No-one, or something custom
- everyone@yourcompany.com
- everyone@identityprovider.com
- allcustomers@cloudprovider.com

Avoid binding large groups: least privilege

On GKE: [system:authenticated](#) same as [IAM allAuthenticatedUsers](#)



KubeCon



CloudNativeCon

North America 2023

# Attack Demo

# Attack Observations



KubeCon



CloudNativeCon

North America 2023

- Time to exploitation: 8 days from misconfig
- Blend into system noise
- XMRig bitcoin miner payload
- kubectl user-agent
- K8s updates: new image versions rather than in-payload



KubeCon



CloudNativeCon

North America 2023

# Prevention

# Misconfig surface



KubeCon



CloudNativeCon

North America 2023

- **User** system:anonymous ← Misconfig attacked
- **Group** system:unauthenticated
- **Group** system:authenticated (config dependent)

3 principals x [cluster|namespace]  
= 6 different misconfig possibilities

[YAML examples](#)

# Prevention Options



KubeCon



CloudNativeCon

North America 2023

- Limit API server network access
- Disable anonymous auth completely
- Block *cluster-admin* bindings to system users/groups
- Block *any* bindings to system users/groups
- Block *any* bindings to cluster-admin

# Limit Network Access to API Server



KubeCon



CloudNativeCon

North America 2023

- Protects against: DoS, Authn/z misconfig, API server vulns
- Run in private address space
- Put a firewall in front

On GKE: [private endpoint, authorized networks](#)

# Disable Anonymous Auth



KubeCon



CloudNativeCon

North America 2023

“If you are using RBAC authorization, it is generally considered reasonable to allow anonymous access to the API Server for health checks and discovery purposes.”

— K8s CIS Security Benchmark



# Disable Anonymous Auth



KubeCon



CloudNativeCon

North America 2023

- On by default, API server flag  
`anonymous-auth=false` to disable
- Can't be disabled on many managed K8s platforms

Let's make improvements here! [Discuss at sig-auth Nov 22](#)

# Block cluster-admin Bindings




KubeCon



CloudNativeCon

North America 2023



Prevents misconfig used in the attack

On GKE: As of 1.28 blocked by default

# Block *Any* Bindings to system



KubeCon



CloudNativeCon

North America 2023

From our research, this may affect:

- Limited pre-auth APIs: [kubeadm](#), [rancher](#), [bitnami sealed secrets](#)
- CI/CD metrics
- Legacy Pod Security Policy bindings (EOL anyway)

Can be done with [admission](#), or as detection

# Block Any Bindings To cluster-admin



KubeCon



CloudNativeCon

North America 2023

*“Ensure that the cluster-admin role is only used where required”*

—K8s CIS Benchmark

Careful! Widely used by privileged components

On GKE: Audit/enforce with [CIS benchmark policy bundle](#) in Policy Controller ([K8sRestrictRoleBindings](#))



KubeCon



CloudNativeCon

North America 2023

# Prevent Demo



KubeCon



CloudNativeCon

North America 2023

# Detection

# Detection Opportunities



KubeCon



CloudNativeCon

North America 2023

- Misconfiguration: root cause
- Exploitation: attacker actions on K8s API
- Mining: the crypto miner itself

Find in logs:

- Critical: cluster-admin binding to system user/groups
- Medium: any system user/groups binding
- Low: any cluster-admin binding

[Audit existing rolebindings](#)

On GKE: [Event Threat Detection](#)





KubeCon



CloudNativeCon

North America 2023

# Detect Demo

# Detect Unused Permissions



KubeCon



CloudNativeCon

North America 2023

- cluster-admin isn't the only privileged role
- You can make your own!
- [RBAC Police](#) can tell you about privileged roles, but not if they are unused
- Third party tooling for unused permissions

On GKE: IAM recommender does this for bindings through IAM, but not for RBAC, yet.

💡 6/10 excess permissions

9/20 excess permissions

8/16 excess permissions

8626/8693 excess permissions

💡 1/2 excess permissions

## system:anonymous activity

```
protoPayload.authenticationInfo.principalEmail="system:anonymous"  
protoPayload.authorizationInfo.granted="true"
```

## CSR creation/approval

```
protoPayload.request.@type="certificates.k8s.io/v1.CertificateSigningRequest"  
-protoPayload.authenticationInfo.principalEmail="kubelet-bootstrap"  
-protoPayload.authenticationInfo.principalEmail="system:gcp-controller-manager"  
-protoPayload.authenticationInfo.principalEmail=~"^system:node:"
```

- Communication with known-bad IPs/domains
- Known-bad containers
- Known-bad binaries

On GKE (opt-in): [Event Threat Detection and VM Threat Detection](#)

- Interesting K8s-specific attack
- Prevent:
  - Limit network access
  - Block RBAC bindings to system users/groups
- Detect:
  - [Audit existing rolebindings](#)
  - system:anonymous and CSRs in logs
  - Unused permission detection
  - Cryptominer detection

## Talk Feedback

- [Demo Code](#)
- Attack Blogs: [Crowdstrike](#), [Aqua](#), [Raesene](#)
- [K8s Anonymous Auth](#)
- [System Groups on GKE](#)
- RBAC best practices: [K8s](#), [GKE](#)
- Limit network access to API server [hardening advice](#)
- Gatekeeper [DisallowAnonymous](#)
- [Validating admission policy](#): beta in K8s 1.28
- [Auditing and cleaning up anonymous bindings](#)



# Detection Log Queries



KubeCon



CloudNativeCon

North America 2023

## cluster-admin bindings to system:\*

```
resource.type="k8s_cluster"  
resource.labels.cluster_name="vulnerable-cluster"  
resource.labels.location="us-central1-c"  
protoPayload.request.roleRef.name="cluster-admin"  
protoPayload.request.subjects.name="system:anonymous" OR  
protoPayload.request.subjects.name="system:authenticated" OR  
protoPayload.request.subjects.name="system:unauthenticated"  
protoPayload.methodName:"io.k8s.authorization.rbac.v1.rolebindings" OR  
protoPayload.methodName:"io.k8s.authorization.rbac.v1.clusterrolebindings"  
-protoPayload.response.code="403"
```

## System anonymous actions:

```
resource.type="k8s_cluster"  
resource.labels.cluster_name="vulnerable-cluster"  
resource.labels.location="us-central1-c"  
protoPayload.authenticationInfo.principalEmail="system:anonymous"  
protoPayload.authorizationInfo.granted="true"
```

## CSR Creation and Approvals

```
resource.type="k8s_cluster"  
resource.labels.cluster_name="vulnerable-cluster"  
resource.labels.location="us-central1-c"  
protoPayload.request.@type="certificates.k8s.io/v1.CertificateSigningRequest"  
-protoPayload.authenticationInfo.principalEmail="kubelet-bootstrap"  
-protoPayload.authenticationInfo.principalEmail="system:gcp-controller-manager"  
-protoPayload.authenticationInfo.principalEmail=~"^system:node:"
```