




**KubeCon**



**CloudNativeCon**

**North America 2023**





KubeCon



CloudNativeCon

North America 2023

# Reliable RPCs over Hybrid Clouds, and the End-to-End Argument

*Wenbo Zhu, Vinod Lasrado*

*Google Inc.*

# Hybrid Clouds?



KubeCon




CloudNativeCon

North America 2023

Background: On-prem storage/database services move to Clouds while applications stay on-prem.

Challenges: applications are not yet adapted to the remote SaaS stack, esp. their failure modes and latencies.



# Case Study



KubeCon




CloudNativeCon

North America 2023

## A generalized version

- RDMBS style transactional ops (writes) vs non-transactional ops (reads)
- Client-Cloud RTT >> Server RTT
- Timed-out reads may cause application errors that are visible to end-users
- Timed-out writes will abort the underlying transaction
- Connection-based affinity for server-side sessions and caching, with conn-pools to distribute sessions



# Failure Modes



KubeCon




CloudNativeCon

North America 2023

## L3 failures between the client and Cloud

- Failures affect only a small fraction of “flows” (hence TCP connections) and flows are unidirectional
- Failures often result in short-lived black holes but partial packet losses are also possible
- Transient server or proxy failures (overloading) may happen which are not correlated to L3 failures



# Key Questions




KubeCon




CloudNativeCon

North America 2023



... why is the *RPC* error %  
(much) higher than  
packet loss %?



... shouldn't SaaS hide all  
the errors (that I don't  
need to understand)?



Sure, but it's going to be a  
*cage fight* ...

# Evaluations



KubeCon




CloudNativeCon

North America 2023

## A general-purpose benchmark framework

- Evaluate impacts of different workload and environment parameters
- Evaluate effectiveness of different solutions for minimizing visible errors



# Tail Latencies




KubeCon



CloudNativeCon

North America 2023

Latency PDF at different packet loss rates: request/s = 100; L3 failure window: 10s





# RPC Timeouts (Payload Sizes)




KubeCon



CloudNativeCon

North America 2023

Timeout is set to 4 \*RTT (median E2E). RPCs are not cancelled.



# RPC Timeouts (Request Rates)




KubeCon



CloudNativeCon

North America 2023

Timeout is set to  $4 * \text{RTT}$  (median E2E). RPCs are not cancelled.



# H3/QUIC (Payload sizes)




KubeCon



CloudNativeCon

North America 2023



# H3/QUIC (Request Rates)




KubeCon



CloudNativeCon

North America 2023



# Failure Detection



KubeCon




CloudNativeCon

North America 2023

Fail-fast: detect (suspect) a failed connection (or server) timely

## Detection params

- A: a factor of median RTT
- B: maximum number of pending acks
- ack\_num: number of pending L7 acks in the runtime
- $\text{timeout} = 12 * A * \text{RTT} - 2 * A * \text{RTT} * \min(B, \text{ack\_num})$



# Evaluation Results




KubeCon




CloudNativeCon

North America 2023

Timeliness: MTTFD with injected failures



False-positive: MTTF with failure-free runs



# Failure Recovery



KubeCon



CloudNativeCon

North America 2023

## Decoupled from failure detection timeout

- Shorter timeout for reads and longer timeout for writes, as decided by applications

## Upon a failed connection

- New requests will use a different connection
- Pending reads will be auto-retried immediately on a different connection but only once
- Pending requests will run to completion or will be cancelled after a timeout

## Minimum visible errors

- Read timeout is larger than  $2 * \text{MTTFD}$ , e.g. 300us
- Write timeout is longer than the failure window, e.g. 5s

## Cost of false-positive detection

- Duplicated reads and misrouted writes

# End-to-End Arguments



KubeCon



CloudNativeCon

North America 2023

*E2E Principle: functions such as failure detection and mitigation may “completely and correctly be implemented only” at an application level, and implementing those functions completely and correctly from a lower level is not possible.*

## Key takeaways

- Leverage service-level RPC semantics in failure detection and recovery
- Passive detections to adapt to runtime conditions
- Graceful recovery to handle short failure windows

## Low-level recovery

- Desired if it can be done quickly and transparently (without tearing down TCP connections)
- An optimization aligned with the E2E principle



# Production Environments?



KubeCon




CloudNativeCon

North America 2023

## No silver bullet

Monitoring data is critical to identify root causes and to evaluate solutions

- Client-side transport layer
- Correlation between userspace/guest transports and L3 networking



# eBPF Transport Monitoring



KubeCon




CloudNativeCon

North America 2023

[github.com/google/ebpf-transport-monitoring](https://github.com/google/ebpf-transport-monitoring)

- A standalone toolkit
- Correlation between kernel events (TCP) and user-space events (TLS, HTTP/2)
- Future work: more languages, compact event encoding, QUIC/H3 ...



# Contact Us



KubeCon



CloudNativeCon


North America 2023

## Feedback and contributions

- eBPF transport monitoring
- Benchmark framework
- Example data sets, analytical methods

Discussion: [github.com/google/ebpf-transport-monitoring/issues](https://github.com/google/ebpf-transport-monitoring/issues)

Email: [vlm@google.com](mailto:vlm@google.com), [web@google.com](mailto:web@google.com)



**Please scan the QR Code above  
to leave feedback on this session**