BUOYANT

weaveworks

Flagger, Linkerd, Gateway API: Oh My!

Jason Morgan, Buoyant
Sanskar Jaiswal, Weaveworks

 @BuoyantIO

 buoyant.io

 @weaveworks

 weave.works

Jason Morgan
Technical Evangelist @ Buoyant

@RJasonMorgan

JasonMorgan

@Jason Morgan (Linkerd Slack)

Sanskar Jaiswal
Software Engineer @Weaveworks

@aryan9600_

aryan9600

@aryan9600 (CNCF Slack)

weaveworks

BUOYANT

Gateway API: Introduction

The next generation of Kubernetes networking and load balancing.

Packaged as a new set of APIs, it addresses the shortcomings of Ingress and evolves over it through expressive, extensible, and role-oriented interfaces.

weaveworks

BUOYANT

Gateway API: Why?



weaveworks

BUOYANT

Gateway API: How does it help?

- More interoperability
- Fewer CRDs

Progressive Delivery



weaveworks

BUOYANT

Flagger Overview

Flagger is a progressive delivery tool that automates the release process for applications running on Kubernetes.

It enables:

- ➔ **Safer Releases**: Reduce the risk of introducing a new software version in prod by gradually shifting traffic to it and rollback safely if needed.
- ➔ **Extensive Validation**: Validate SLOs/KPIs by running load tests, acceptance tests and analysing metrics collected via Prometheus, DataDog, StackDriver, etc
- ➔ **Flexible Traffic Routing**: Support for Linkerd, Istio, NGINX, Contour, Skipper, etc.

weaveworks

BUOYANT

Ultralight, ultrafast, security-first **service mesh** for Kubernetes.

- Created by **Buoyant**
- **5+** years in production
- **7,000+** Slack channel members
- **10,000+** GitHub stars
- **200+** contributors
- **Weekly** edge releases
- **Open governance**, neutral home
- The only **CNCF graduated** mesh



and many more...

How does Linkerd work?



Gateway API: Networking Model



A modern set of APIs for deploying L4 and L7 routing in Kubernetes

Designed to be generic, expressive, extensible, and role-oriented

weaveworks

BUOYANT

Gateway API: Resources

```yaml
apiVersion: gateway.networking.k8s.io/v1beta1
kind: Gateway
metadata:
  name: foo-gateway
  namespace: gateway-api-example-ns1
spec:
  gatewayClassName: foo-lb
  listeners:
  - name: prod-web
    port: 80
    protocol: HTTP
    allowedRoutes:
      kinds:
        - kind: HTTPRoute
      namespaces:
        from: Selector
        selector:
          matchLabels:
            expose-apps: "true"
```

```yaml
apiVersion: gateway.networking.k8s.io/v1beta1
kind: HTTPRoute
metadata:
  name: my-route
  namespace: gateway-api-example-ns2
spec:
  parentRefs:
  - kind: Gateway
    name: foo-gateway
    namespace: gateway-api-example-ns1
  rules:
  - backendRefs:
    - name: foo-svc
      port: 8080
```

weaveworks

BUOYANT

Gateway API: Traffic Splitting



How does it all fit?



weave

YANT

DEMO TIME

Please scan the QR Code above to leave feedback on this session