



KubeCon



CloudNativeCon

North America 2022

BUILDING FOR THE ROAD AHEAD

DETROIT 2022

So what if I don't want my Persistent Storage to be yet another Bind Mount

Deep Debroy and Feng Wang

So what if I don't want my Persistent Storage to be yet another Bind Mount



BUILDING FOR THE ROAD AHEAD

DETROIT 2022



KubeCon



CloudNativeCon

North America 2022

BUILDING FOR THE ROAD AHEAD

DETROIT 2022

October 24-28, 2021



Deep Debroy

Software Engineer

Apple



Feng Wang

Software Engineer


Databricks

Introduction

- Current Lifecycle Flow for Pods with Persistent Storage
 - bind mounts
- Alternatives to the Standard Flow for Persistent Storage
 - from a MicroVM perspective
 - challenges
- Surfacing “Direct Assignment” Flows to CSI Plugins
 - with Kubernetes and Kata awareness
 - generic support
- Conclusion


Pod Startup from Kubelet's Perspective

- Kubelet gets notified about pods scheduled on the node




Pod Startup from Kubelet's Perspective

- Kubelet mounts the specified volumes in the pod:
 - In-line volumes (configMap, secrets, etc)
 - Persistent Volumes bound to PVCs



Pod Startup from Kubelet's Perspective


- Kubelet prepares the file system mount
 - Apply FsGroup based on FsGroupChangePolicy
 - Probe and prepare subpaths
 - Determine Security-Enhanced Linux (SELinux) labelling



```
apiVersion: v1
kind: Pod
metadata:
  name: pod1
spec:
  securityContext:
    fsGroup: 4059
    fsGroupChangePolicy: "OnRootMismatch"
    seLinuxOptions:
      level: "s0:c123,c456"
  containers:
    - name: container1
      image: image1
      volumeMounts:
        - mountPath: "/path1"
          name: vol1
          subPath: /subpath1
  volumes:
    - name: vol1
      persistentVolumeClaim:
        claimName: pvc1
```


Pod Startup from Kubelet's Perspective

- Kubelet invokes CRI implementation to
 - Create pod sandbox
 - Pull container images
 - Create containers




Volume Operations during Pod Lifetime

- Kubelet reports file system stats
- Kubelet resizes the mounted volume




Regular Path for FS Operations on a PV



File System Bind Mounts Along the Way

- NodeStaging global path → NodePublish target path
 - Created during CSI NodePublish
- NodePublish target path → Path inside container
 - Created during OCI create container



Current Assumptions in Kubelet

- All volumes have file-systems mounted before container bring-up
 - whenever PV VolumeMode is FileSystem
- Post mount actions *invoked on mounted file system* by Kubelet (and container runtime):
 - fsGroup ownership
 - subpath checks
 - SELinux labelling

Alternative Flow for Volume Mounts

How about a different sequence?

How about a different sequence?

mount volumes *after* container bringup *without* using raw block mode
[use case: microVM environments like Kata]

MicroVM-based Runtime


Kata Containers – A container runtime that runs workloads in a virtual machine.

- **Secure** – container workload runs on a dedicated kernel
- **Lightweight** – faster startup than a full-blown virtual machine
- **Compatible** – compliant to OCI container format and containerd/crio shim interface.


Kata Containers architecture



Kata Shim V2



Regular Path to Mount a PV in Kata



Performance and Security Trade-offs

- **Performance**

virtio-fs has worse performance compared to virtio-blk/virtio-scsi

- **Isolation**


virtio-fs requires file system to be mounted in the host

- **Other Gaps**

virtio-fs may not surface native file system features

Performance Comparison of virtio fs vs blk

fio bandwidth test




test details: <https://gist.github.com/fengwang666/a624c11e26fb7f9035af00fad6cea467>

A New Model for Mounting PVs


Direct Assigned Storage

CSI plugin delegates PV mount and preparation to container runtime


Direct Assign PV to Container Runtime




Direct Assigned PV: Mount Volume




Direct Assigned PV: Unmount Volume



Direct Assigned PV: Volume Stats



Direct Assigned PV: Resize Volume



Implementing Direct Assigned Storage

Container Runtime specific delegation logic in CSI Plugin

Demo

Implementing Direct Assigned Storage

Current: Container Runtime specific delegation logic in CSI Plugin

- No changes in Kubelet, CRI, OCI and CSI specs
- Most post-mount configurations work
- CSI Plugin needs to lookup runtimeClass of pod
- Subpath support not possible

Implementing Direct Assigned Storage

Future: Container Runtime agnostic delegation logic in CSI Plugin

- Enhancements in Kubelet, RuntimeClass and CSI spec
- Kubelet will match capabilities of CSI plugin and runtime
- CSI plugins can use a common proxy to delegate operations
- All post-mount configurations will be supported

KEP-2857: Runtime Assisted Mounting of Persistent Volumes



Open

ddebroy wants to merge 1 commit into `kubernetes:master` from `ddebroy:runtime1` 

Implementing Direct Assigned Storage

Future: Container Runtime agnostic delegation logic in CSI Plugin

- Scoped to ReadWriteOncePod access modes for safety
- Should not be used for mount scenarios that require a secret

KEP-2857: Runtime Assisted Mounting of Persistent Volumes



Open

ddebroy wants to merge 1 commit into `kubernetes:master` from `ddebroy:runtime1` 

Takeaways and Next Steps

- Explored alternatives to the standard mount flow for persistent storage
 - from a microVM perspective
- Ways to delegate mount and post mount configuration to container runtime
 - for block based PVs
 - avoid bind mounts and file-system projections
- Please get involved!
 - KEP-2857 (sig-storage) [[#sig-storage](#) in [kubernetes.slack.com](#)]
 - Kata community [[katacontainers.slack.com](#)]

Questions



Please scan the QR Code above to
leave feedback on this session