Dynamically Testing Individual Microservice Releases In Production



Matt Turner

Outline

- Microservice topologies
- Continuous Deployment / Release
- Testing in production
- Implementation
- Prior art
- Istio
- Override-operator
- Demo
- Challenges and future work
- Conclusions




tetrate


THE ENTERPRISE SERVICE MESH COMPANY

About you


- Never used Istio
- Beginner
- Expert

Microservice Topologies






Service Chains




Service Chains




Service Chains



µService Taxonomy



µService Taxonomy





µService Taxonomy




Continuous Deployment / Release

Testing new versions







Deployment and release stages




Integration tests



Testing in context




Staging environment




Ephemeral environments

Ephemeral




Testing in Production


Do we really need *Test*?



Do we really need *Test*?




End-to-end tests




Implementation

Sidecar proxies






Service mesh



Service mesh



Prior Art

"Breaking up Lyft's Development Monolith"

- Jake Kaufman
- QCon London 2022


- Lyft's proprietary control-plane
- Custom C++ code








Istio Config Recap

- VirtualService "Given a request for a named service, where do I route it?"
 - Select workloads based on headers
 - Select a subset of available workloads, based on a attributes like labels
- DestinationRule "How do I talk to the workloads that have been selected?"
 - Load balancing strategy across them
 - TLS stance
 - Subsets to group them into









DestinationRule

```
apiVersion: networking.istio.io/v1beta1
kind: DestinationRule
metadata:
  name: foo
spec:
  host: foo
  subsets:
    - name: ∨1
      labels: { version: v1 }
    - name: v2
      labels: { version: v2 }
```

```
apiVersion: networking.istio.io/v1beta1
kind: VirtualService
metadata:
   name: foo-overrides
spec:
   hosts: [foo]
http:
```





- match:
 - headers:

```
x-override: "foo:v1"
```

route:

- destination: { host: foo, subset: v1 }
- match:
 - headers:

```
x-override: "foo:v2"
```

route:

- destination: { host: foo, subset: v2 }





- route:
 - destination: { host: foo, subset: v1 }



- match:
 - headers:

```
x-override: { regex: "(.*,|^)foo:v1(,.*|$)" }
```

- route:
 - destination: { host: foo, subset: v1 }
- match:
 - headers:

```
x-override: { regex: "(.*,|^)foo:v2(,.*|$)" }
```


- route:
 - destination: { host: foo, subset: v2 }



Repeated header key

- Curl puts them on the wire as multiple keys
 - This used to be contrary to the spec [RFC 2616 "HTTP/1.1" §4.2]
 - But is now ok [RFC 7230 "HTTP/1.1: Message Syntax and Routing" §3.2.2]
- And golang forwards them as multiple keys
- Envoy presents you a single combined string: "foo,bar,baz"
 - O => Have to match a substring
- Envoy gives you: exact, prefix, suffix, contains, safe_regex
- Istio exposes: exact, prefix, regex (compiles to safe regex)
- Regex it is then
 - Google RE2 syntax
 - Whole-string match
- (.*,|^)foo:v2(,.*|\$) is the tightest regex I can get

Override-[generator, operator]



Demo!

Caveats

- All Services in the namespace will be processed
 - The kubernetes Service is ignored, but all others must meet the requirements
 - Every Pod selected by each Service must have a version label (this is used to build the DR's subsets)
 - At least one of those Pods must have version: v1 (a default route is added to the v1 subset for traffic with no x-override header)
- There are no other VirtualServices or DestinationRules for the Service's hostname
- Services need to forward the x-override header.

Challenges and Future Work

Trusting the Header

- Definitely needs filtering out at the edge
- Could let a compromised workload move laterally
- Lyft's version stuck it in the JWT
- Also means it doesn't have to be forwarded

GitOps integration

- Naïvely looks like transient state
- But a well-solved problem
- CLI for integration with deployment pipelines
 - Needs to read YAML

Interaction with existing Istio resources


- Currently needs the namespace "to itself"
- Doesn't work for the first hop

- Various options including delegated VirtualServices
- Operator uses server-side apply

"Sink to test"

- db-shim **GET** => v1
- db-shim **POST** => v2

V2 database shim



Conditional Routing

Pick service-3:v2 given the caller is Foo, but not Bar

- Useful when the service chain isn't linear
- Or a service is part of more than one chain
- Coming soon with authz

Conclusions

	Basic	Sophisticated
Unit testing		
Testing (in prod)	Staging / ephemeral envs	Overrides
(Canary) Release	K8s rolling-update / DNS "load balancing"	Flagger

Thanks!

Questions @mt165

Slides Videos **mt165.co.uk** Demo code

