



KubeCon



CloudNativeCon

North America 2023





KubeCon



CloudNativeCon

North America 2023

OIDC and Workload Identity in Kubernetes

*Anish Ramasekar, Microsoft &
Ashutosh Kumar, Elastic*

Anish Ramasekar

- Software Engineer at Microsoft working on security
- Maintainer of Secrets Store CSI Driver
- Member of Kubernetes SIG-Auth
- Seattle, WA



Ashutosh Kumar

- Software Engineer at Elastic
- Maintainer of Cluster API Provider Azure



Agenda



KubeCon



CloudNativeCon

North America 2023

- Introduction: Workload Identity
- Authentication and Authorization
- Workload Identity: Functionality and Mechanics
- Demo
- Workload Identity usages in Kubernetes

Introduction: Workload Identity




KubeCon



CloudNativeCon

North America 2023

- Workloads deployed in Kubernetes may require access to external protected resources e.g. on public cloud.
- Workload identity is a way to authenticate and authorize access to workloads(or pods in k8s context) of cloud or external resources in a much more secure way.
- Before we understand workload identity, we can do a refresher of some keywords and Oauth2.0 and OIDC which powers it.



Authentication And Authorization



KubeCon



CloudNativeCon

North America 2023

Let us understand some keywords...

Entity

Something which physically exists e.g individual or service

Identity

Set of attributes of the entity to uniquely identify

Authentication

Way of confirming the identity of an entity

Authorization

Way of verifying what an entity can or cannot access.

Authentication And Authorization



KubeCon




CloudNativeCon

North America 2023

- Quick look into traditional model...

Drawbacks

- Server need to support password authentication.
- Providing password to third party apps can be risky.
- No way to restricting access to only selected resources.
- No way to revoking access to an individual third party, need to revoke for all.



Authentication And Authorization



KubeCon



CloudNativeCon

North America 2023

- OAuth2.0 addresses the limitation...

What is OAuth2.0

- A framework for delegated authority.
- Captured in [RFC-6749](#)
- No way to restricting access to only selected resources.
- Does not define authentication.

OAuth2.0 Roles

- Resource Owner (RO)
- Resource Server (RS)
- Client
- Authorization Server (AS)

Authentication And Authorization




KubeCon



CloudNativeCon

North America 2023



Authentication And Authorization



KubeCon



CloudNativeCon

North America 2023

Open ID connect is a standard added on top of OAuth2.0

- OAuth2.0 does not define authentication mechanism.
- OIDC provides a method for user authentication.
- OIDC introduced 'ID tokens' in form of JWT.
- The JWT contains set of claims used to identify user e.g. email, name etc

Authentication And Authorization




KubeCon



CloudNativeCon

North America 2023

Open ID Connect



Authentication And Authorization




KubeCon



CloudNativeCon

North America 2023



A **workload** is an application running on Kubernetes.

- Has a unique name within a namespace
- References an image that contains the actual code



Use cases for Workload Identity



KubeCon



CloudNativeCon

North America 2023

- Authenticating with the Kubernetes API Server
- Authenticating communication between Kubernetes workloads
- Access to external protected resources

Workload Identity Options



KubeCon



CloudNativeCon

North America 2023

- Kubernetes Certificates API
- Service Mesh
- SPIFFE/SPIRE
- Kubernetes Service Account Token

Kubernetes Service Account Token



KubeCon



CloudNativeCon

North America 2023

- Default Service Account Token
 - Automatically generated
 - **Not that secure**
- Projected Service Account Token

Projected Service Account Token



KubeCon



CloudNativeCon

North America 2023

```
volumes:  
- name: test-token  
  projected:  
    sources:  
    - serviceAccountToken:  
        path: test-token  
        expirationSeconds: 3600  
        audience: test
```

```
{  
  "aud": [  
    "test"  
  ],  
  "exp": 1698626358,  
  "iat": 1698622758,  
  "iss": "https://kubernetes.default.svc.cluster.local",  
  "kubernetes.io": {  
    "namespace": "default",  
    "pod": {  
      "name": "jump",  
      "uid": "a9fa65f0-0601-43aa-bc31-c1926682e08d"  
    },  
    "serviceaccount": {  
      "name": "default",  
      "uid": "7c56382f-440d-44bb-8534-07c23eeb015b"  
    }  
  },  
  "nbf": 1698622758,  
  "sub": "system:serviceaccount:default:default"  
}
```

Workload Identity Federation




KubeCon



CloudNativeCon

North America 2023



Workload Identity Federation




KubeCon



CloudNativeCon

North America 2023



Demo



KubeCon



CloudNativeCon

North America 2023

Create a kind cluster

File: kind-config.yml

```
1 kind: Cluster
2 apiVersion: kind.x-k8s.io/v1alpha4
3 nodes:
4 - role: control-plane
5   extraMounts:
6     - hostPath: sa.pub
7       containerPath: /etc/kubernetes/pki/sa.pub
8     - hostPath: sa.key
9       containerPath: /etc/kubernetes/pki/sa.key
10  kubeadmConfigPatches:
11  - |
12    kind: InitConfiguration
13    nodeRegistration:
14    taints:
15    - key: "kubeadmNode"
16      value: "master"
17      effect: "NoSchedule"
18  - |
19    kind: ClusterConfiguration
20    apiServer:
21      extraArgs:
22        service-account-issuer: https://oidcissuer008.blob.core.windows.net/demo/
23        service-account-key-file: /etc/kubernetes/pki/sa.pub
24        service-account-signing-key-file: /etc/kubernetes/pki/sa.key
25    controllerManager:
26      extraArgs:
27        service-account-private-key-file: /etc/kubernetes/pki/sa.key
28  - role: worker
```



+ kind create cluster --image kindest/node:v1.28.0 --config kind-config.yml --name workload-identity-demo

Creating cluster "workload-identity-demo" ...

✓ Ensuring node image (kindest/node:v1.28.0)

✓ Preparing nodes

✓ Writing configuration

✓ Starting control-plane

✓ Installing CNI

✓ Installing StorageClass

⏏ Joining worker nodes

Other usages in Kubernetes



KubeCon



CloudNativeCon

North America 2023

- Cluster API Provider Azure
- Token requests support in Kubernetes CSI
 - Workload Identity in Secrets Store CSI Driver

Workload Identity in CAPZ



KubeCon



CloudNativeCon

North America 2023

- Cluster API Provider Azure is a SIG Cluster Lifecycle sub project which helps provision k8s clusters on Azure in a declarative way.
- Using service principal to access Azure resources is roughly using user/passwords.

Workload Identity in CAPZ



KubeCon



CloudNativeCon

North America 2023

```
volumes:  
- name: azure-identity-token  
  projected:  
    defaultMode: 420  
    sources:  
    - serviceAccountToken:  
        audience: api://AzureADTokenExchange  
        expirationSeconds: 3600  
        path: azure-identity-token
```

```
volumeMounts:  
- mountPath: /var/run/secrets/azure/tokens  
  name: azure-identity-token  
  readOnly: true
```

Workload Identity in CAPZ



KubeCon



CloudNativeCon

North America 2023


Create an app on azure.


App registrations ...

[+ New registration](#) [🌐 Endpoints](#) [🔑 Troubleshooting](#) [🔄 Refresh](#) [⬇ Download](#) [🔍 Preview features](#) | [🗣 Got feedback?](#)


i Starting June 30th, 2020 we will no longer add any new features to Azure Active Directory Authentication Library (ADAL) and Azure Active Directory Graph. We will continue to provide technical support for ADAL, Azure Active Directory Graph, Azure Active Directory Library (MSAL) and Microsoft Graph. [Learn more](#)

All applications **Owned applications** Deleted applications

 Start typing a display name or application (client) ID to filter these r...

 Add filters

1 applications found

Display name 

AZ

azure-cli-2023-08-07-13-17-27

Workload Identity in CAPZ



KubeCon



CloudNativeCon

North America 2023

Add a credential ...

Allow other identities to impersonate this application by establishing a trust with an external OpenID Connect (OIDC) identity provider. This federation allows you to get tokens to access Microsoft Entra ID protected resources that this application has access to like Azure and Microsoft Graph. [Learn more](#)

Federated credential scenario *

Kubernetes accessing Azure resources

Connect your Kubernetes service account

Please enter the details of the Kubernetes cluster that you want to connect to Microsoft Entra ID. These values will be used by Microsoft Entra ID to validate the connection and should match your Kubernetes OIDC configuration. Issuer has a limit of 600 characters. Subject Identifier is a calculated field with a 600 character limit.

Cluster issuer URL *

Service account issuer URL (Limit of 600 characters)

Namespace *

Namespace

Service account name *

Service account name

Subject identifier

system:serviceaccount:<namespace>:<serviceaccount>

This value is generated based on the Kubernetes account details provided. [Edit \(optional\)](#)

Credential details

Enter and review the details for this credential. The credential name cannot be edited after creation.

Name *

Name (Cannot be changed later)

Description

Limit of 600 characters

Audience

api://AzureADTokenExchange

[Edit \(optional\)](#)

Workload Identity in CAPZ



KubeCon



CloudNativeCon

North America 2023

Supply the app client ID to CAPZ



```
apiVersion: infrastructure.cluster.x-k8s.io/v1beta1
kind: AzureClusterIdentity
metadata:
  name: demo-workload
  namespace: default
spec:
  allowedNamespaces: {}
  clientID: <AZURE_CLIENT_ID>
  tenantID: <AZURE_TENANT_ID>
  type: WorkloadIdentity|
```

Secrets Store CSI Driver



KubeCon



CloudNativeCon

North America 2023

- SIG Auth subproject
- Container Storage Interface (CSI) Storage Driver
- Loads secret into tmpfs mount

Secrets Store CSI Driver




KubeCon



CloudNativeCon

North America 2023



Workload Identity



KubeCon



CloudNativeCon

North America 2023





- [Service Account token volume projection](#)
- [Service Account issuer discovery](#)
- [Workload Identity in GKE](#)
- Workload Identity In CAPZ
 - [CAPZ Workload Identity](#)
 - [Azure Workload Identity](#)
- [Secrets Store CSI Driver](#)



KubeCon



CloudNativeCon

North America 2023

Q & A



PromCon
North America 2021



**Please scan the QR Code above
to leave feedback on this session**