Crossplane

Introduction & Deep Dive

https://crossplane.io

Nic Cope, Bob Haddleton, Matthias Luebken, Jared Watts



What is Crossplane?

- Framework for building cloud native control planes
 - No need to write any code
- Cloud providers have been managing their infrastructure with control planes for years
 - Crossplane helps you build your own with your own opinions
- Extensible backend to manage any infrastructure in any environment
- Configurable frontend to expose declarative APIs (abstractions) for developer self-service



CNCF Project for the Community

- Crossplane is a neutral place for vendors and individuals to come together in enabling control planes
- Launched in Dec 2018 by creators of CNCF graduated Rook project
 - Accepted into Sandbox in June 2020
 - First major "stable" milestone <u>v1.0 released</u> in Dec 2020
 - Moved to Incubation September 2021
 - ∘ <u>v1.10</u> released last week
 - Aiming for Graduation early '23 we need your help!



Project and Community Stats



7,000+

Stars
2x Increase YoY

60,000+

Contributions 2x Increase YoY

1,200+

Contributors **5x** Increase YoY



6,000+

Followers 2x increase YoY



7,000+

Members **5x** increase YoY



28M+

Pulls
10x increase YoY




The Basics

Managed Resources



Managed Resources Example: AWS


Networking Databases Kubernetes Clusters IAM VMs Message Queues Caches Certificates ...and much more...





Managed Resources

```
apiVersion: s3.aws.crossplane.io/v1beta1
kind: Bucket
metadata:
  name: crossplane-deepdive-demo-bucket
spec:
  forProvider:
    acl: private
    locationConstraint: eu-west-1
    paymentConfiguration:
      payer: BucketOwner
    versioningConfiguration:
      status: Enabled
    tagging:
      tagSet:
      - key: Name
        value: CrossplaneDeepDiveDemoBucket
```







Managed Resources

Status contains values returned from the remote API and the condition of the resources.


Successfully requested creation of external resource

Managed Resources Generate K8s Events



Managed Resource Reconciliation

 Controllers reconcile Managed Resources with cloud provider and on-prem APIs (e.g., GCP, AWS, or any API)





Control Plane Internal Stack

Controller Controller Controller Controller Custom Logic Manage External APIs Crossplane Runtime Create/Update/Delete Event, Watch, Request, Controller Runtime Reconciliation CRDs, OpenAPI, Kubernetes API Machinery Persistence (etcd)

Kubernetes Runtime



Run Workloads, Ingress, RBAC

Building Your Control Plane

Composition




Build your own Platform API

- Assemble granular resources. E.g. from multiple clouds.
- Expose as higher level self-service API for your app teams
 - Compose GKE, NodePool, Network, Subnetwork
 - Offer as a single Cluster resource (API) with limited config for developers to self-service
- Hide infrastructure complexity and include policy guardrails
- All with K8s API compatible with kubectl, GitOps, etc.
- No code required, it's all declarative






Claim





Small PostgreSQL





Composite Resources

First we create Composite Resource Definition (XRD) to declare our custom platform API

```
apiVersion: apiextensions.crossplane.io/v1
kind: CompositeResourceDefinition
metadata:
  name: xpostgresglinstances.database.example.org
spec:
  group: database.example.org
  names:
    kind: XPostgreSQLInstance
    plural: xpostgresqlinstances
                                            Custom API Group
  versions:
  - name: v1alpha1
    served: true
                                        Standard openAPIV3
    referenceable: true
    schema:
                                        Schema
      openAPIV3Schema:
        type: object
        properties:
```



Compositions

Then we define Composition which implements XRD

```
apiVersion: apiextensions.crossplane.io/v1
kind: Composition
metadata:
  name: xpostgresqlinstances.aws.database.example.org
spec:
  writeConnectionSecretsToNamespace: crossplane-system
  compositeTypeRef:
    apiVersion: database.example.org/v1alpha1
    kind: XPostgreSQLInstance
  resources:
    - name: parametergroup
      base:
        apiVersion: rds.aws.crossplane.io/v1alpha1
        kind: DBParameterGroup
```

Crossplane

XRD reference

List of Managed Resources to Compose

Patches

Patches enable propagation of data from Composite Resource (XR) down to composed Managed Resources (MR)

patches:

- fromFieldPath: "spec.nodes.count"
 toFieldPath: "spec.forProvider.scalingConfig.desiredSize"

Copy of value from XR spec down to MR spec

```
- fromFieldPath: "spec.nodes.size"
  toFieldPath: "spec.forProvider.instanceTypes[0]"
  transforms:
```

- type: map
map:
 small: t3.small
 medium: t3.medium

large: t3.large

Map transform to manipulate the config data



Extending Crossplane

Providers & Configurations



Current Extension Points

Crossplane is a highly extensible framework

Providers

- You can build a provider to manage anything with an API
- CRUD operations for cloud resources, on-prem services, etc.

Configurations

- Compose resources from providers
- Define your control plane's declarative APIs and abstractions
- These are what your devs see it's how they consume the offerings of your control plane
- Both are Crossplane packages / opinionated OCI Images.




Crossplane Provider Ecosystem





Marketplace for all Extensions

Open for everyone



Composition Functions



```
apiVersion: database.example.org/vlalphal
kind: AcmeCoDatabase
metadata:
   name: example-db
spec:
   parameters:
     storageGB: 20
   compositionRef:
     name: example
```



```
apiVersion: apiextensions.crossplane.io/v1
 kind: Composition
  name: example
   compositeTypeRef:
     apiVersion: database.example.org/v1alpha1
     kind: AcmeCoDatabase
   resources:
   - name: cloudsqlinstance
       apiVersion: database.gcp.crossplane.io/v1beta1
      kind: CloudSQLInstance
         forProvider:
           databaseVersion: POSTGRES_9_6
           region: us-central1
             tier: db-custom-1-3840
             dataDiskType: PD SSD
     - type: FromCompositeFieldPath
       fromFieldPath: spec.parameters.storageGB
       toFieldPath: spec.forProvider.settings.dataDiskSizeMb
       transforms:
       - type: math
           multiply: 1024
```




```
apiVersion: apiextensions.crossplane.io/v2alpha1
kind: Composition
metadata:
  name: example
spec:
  compositeTypeRef:
    apiVersion: database.example.org/vlalphal
    kind: XPostgreSQLInstance
  functions:
  - name: my-cool-function
    type: Container
   container:
      image: xkpg.io/my-cool-function:0.1.0
```



```
apiVersion: apiextensions.crossplane.io/vlalphal
kind: FunctionIO
   apiVersion: database.example.org/vlalphal
  kind: Config
    name: cloudsql
    version: POSTGRES 9 6
observed:
      apiVersion: database.example.org/v1alpha1
      kind: XPostgreSQLInstance
        name: my-db
          matchLabels:
            provider: gcp
        - type: Ready
     - name: uri
      value: postgresql://db.example.org:5432
```







Crossplane Garbage Collection




Claim/Composite Delete Challenges

- Managed resources that fail to delete cleanly are invisible to the user of kubectl delete
- Order of deletion is undefined
- Foreground deletion on Composites didn't work because blockOwnerDeletion was not set on ownerReferences
- Claim is namespaced and Composite is cluster scoped
 - No ownerReference from Composite to Claim is possible.
 - Foreground cascading deletion cannot be executed on Claim



Resource Relationships




finalizer.managedresource..crossplane.io



Claim Delete - Background (default)

kubectl delete -n <namespace> claimName






Foreground Deletion Support

- 1.10 adds compositeDeletePolicy attribute to Claim
 - Claim reconciler sets the PropagationPolicy in the Delete() API call for the Composite
 - Default value is Background
 - "Foreground" will simulate cascading Foreground deletion
- Added blockOwnerDeletion: true on all ownerReferences
 - Delete standalone Composites with –cascade=foreground
- Specifying the propagation policy via –cascade for kubectl delete on a Claim is still ignored



Claim Delete - Foreground

kubectl delete -n <namespace> claimName





Next Steps...



Community is everything



Get Involved

- Website: https://crossplane.io/
- Docs: https://crossplane.io/docs
- GitHub: https://github.com/crossplane/crossplane/crossplane
- Slack: https://slack.crossplane.io/
- Blog: https://blog.crossplane.io/
- Twitter: https://twitter.com/crossplane_io
- Youtube: <u>Crossplane Youtube</u>



Questions?

While we have your attention...we're doing a Crossplane community and adoption survey - help our proposal for Graduation with the CNCF!

https://tinyurl.com/3b5cyfap



