



KubeCon



CloudNativeCon

North America 2022

BUILDING FOR THE ROAD AHEAD

DETROIT 2022

How To Handle Node Shutdown in Kubernetes



BUILDING FOR THE ROAD AHEAD

DETROIT 2022



KubeCon



CloudNativeCon

North America 2022

BUILDING FOR THE ROAD AHEAD


DETROIT 2022

October 24-28, 2021



Ashutosh Kumar

Engineer @VMware India



Xing Yang


Tech Lead @VMware

Agenda

- What is a node shutdown in Kubernetes
- What is a graceful shutdown in Kubernetes
- What is a non graceful shutdown
 - Impact of a non graceful shutdown
 - How non graceful shutdown is handled in Kubernetes
- Demo: non graceful node shutdown
- Next steps

Node Shutdown: Introduction


- Node shutdowns are inevitable in K8s cluster which can result in workload failures.
- Node shutdown causes:
 - Hardware failure
 - Reboot due to a security patch
 - Preemption of short lived cloud compute instances
 -
- A node shutdown could be
 - Graceful
 - Non graceful



Source: <https://kubernetes.io/docs/concepts/overview/components/>

Graceful Shutdown: The What

- Introduced in K8s v1.20 and Beta in v1.21.
- Ability of Kubelet to detect a shutdown ahead of the actual shutdown.
- Kubelet can propagate this event to pods ensuring they shut down gracefully, possibly releasing resources that are being hold.
- Pods with priority class “system-cluster-critical” or “system-node-critical” will be terminated after all other pods.




Graceful Shutdown: The Why

- Prior to this feature, safe draining of nodes required manual intervention.
- Automations that could cause a node restart, required to explicitly drain nodes for safe eviction.
- However, a node shutdown could happen unexpectedly, resulting in unsafe eviction of pods.
- Applications might see errors due to the pods exiting abruptly.

Graceful Shutdown: The How

Kubelet uses “Inhibitor Locks” to postpone shutdown for a specified duration giving a chance for the node to drain and evict pods.

- When Kubelet starts, it acquires the delay type inhibitor lock.
- At shutdown event, Kubelet delays the shutdown for a configurable period of time.



```
kubelet-node ~ # systemd-inhibit --list
Who: kubelet (UID 0/root, PID 1515/kubelet)
What: shutdown
Why: Kubelet needs time to handle node shutdown
Mode: delay

1 inhibitors listed.
```


Graceful Shutdown: The How

- Configurable Kubelet parameters
 - ShutdownGracePeriod
 - Duration that the node should delay the shutdown. This is the total time available for termination of both regular and critical pods.
 - ShutdownGracePeriodCriticalPods
 - Duration used to terminate critical pods. Should be always less than ShutdownGracePeriod.
- Alpha feature Pod Priority based Graceful Node Shutdown in K8s v1.23.

Non Graceful Shutdown: The What


Graceful node shutdown feature in K8s

- Introduced as an Alpha feature in K8s v1.24. Disabled by default. Targeting Beta in v1.26.
- Shutdown that cannot be detected by Kubelet is a non graceful shutdown and this feature handles such shutdown.
- This is especially a problem for stateful pods.



Non Graceful Shutdown: The Why

- The shutdown does not trigger the systemd inhibitor lock.
- ShutdownGracePeriod and ShutdownGracePeriodCriticalPods are not configured properly.
- In case of a non graceful shutdown, the pod moves to Terminating state.
- If the same node comes online, Kubelet detects and it works fine.
- If the original node fails to come online, the pod is stuck in Terminating state.



Non Graceful Shutdown: The Why

Feature gate is disabled

- Created a statefulset.
- Shutdown one node using the `Shut Down Guest OS` from vSphere UI.
- Observed that after 5 mins, the pod changed to `Terminating` state.
- Observed that even after 6 mins, (i.e total 6+5 = 11 mins) the pod is stuck in `Terminating` state.

```
~# kubectl get pod -o wide
```

NAME	READY	STATUS	RESTARTS	AGE	IP	NODE	NOMINATED NODE	READINESS GATES
web-0	1/1	Running	0	19m	10.244.2.4	k8s-node-876-1639279816	<none>	<none>
web-1	1/1	Terminating	0	19m	10.244.1.3	k8s-node-433-1639279804	<none>	<none>

Non Graceful Shutdown: The Why

Feature gate is disabled

- Created a statefulset.
- Shutdown one node using the `Shut Down Guest OS` from vSphere UI.
- Observed that after 5 mins, the pod changed to `Terminating` state.
- Manually deleted the pod using `kubectl delete pod <pod-name> --force --grace-period 0`.
- The pod immediately got scheduled to a different healthy node but was stuck in `ContainerCreating` state for 6 mins. The pod came into `Running` state after 6 mins.

```
~# kubectl get pod -o wide
```

NAME	READY	STATUS	RESTARTS	AGE	IP	NODE	NOMINATED NODE	READINESS GATES
web-0	1/1	Running	0	150m	10.244.2.7	k8s-node-876-1639279816	<none>	<none>
web-1	1/1	Running	0	10m	10.244.1.7	k8s-node-433-1639279804	<none>	<none>

Non Graceful Shutdown: Scope

- Goals
 - Help increase availability of stateful workloads in case node goes into a non-recoverable cases e.g hardware failure or broken OS.
- Non-Goals
 - Node/control plane partitioning other than a node shutdown.
 - In-cluster logic to handle node/control plane partitioning

Non Graceful Shutdown: The How

- Uses Taint `node.kubernetes.io/out-of-service` to handle the shutdown.
- As of now, this feature requires manual intervention i.e. tainting the node that has shutdown non gracefully and may not come back.
- After the taint is applied:
 - Pod GC controller forcefully deletes the pods that do not have a matching toleration.
 - Attach-Detach controller immediately performs a force volume detach operation.
- Now, the new pod comes up successfully quickly on a different node, as the volume can be attached to this pod.

Non Graceful Shutdown: The How

- Feature gate can be enabled by setting the `NodeOutOfServiceVolumeDetach` flag true in the following manner.


```
spec:
  containers:
  - command:
    - --feature-gates=NodeOutOfServiceVolumeDetach=true
```

- Once a node is identified that has been shutdown non gracefully, it can be tainted using the following command.

```
kubectl taint nodes <node-name> node.kubernetes.io/out-of-service=hardwarefailure:NoExecute
```


Non Graceful Shutdown: The How

- Return of a shutdown node
 - Users are required to manually remove the out of service taint after the pods have moved to a new node.
 - In case the taint is not removed from the node after it has returned, no new pods will be scheduled to the node.




Non Graceful Shutdown: The How

- Enabled the non graceful shutdown feature.
- Created a statefulset.
- Shutdown one node using `Shut Down Guest OS` from vSphere UI.
- Observed that after 5 mins, the pod changed to `Terminating` state.
- Taint the shutdown node using the command: `kubectl taint nodes <node-name> node.kubernetes.io.out-of-service=hardwarefailure:No Execute`
- The pod immediately failed over to a different healthy node without waiting for the 6 min detach timeout.



Demo



Next Steps

- Non-graceful node shutdown feature is targeting Beta in K8s v1.26.
- Alternatives
 - [SafeDetach](#)
 - Assumes CSI driver knows whether it is safe to force detach.
 - [Node fencing](#)
 - Monitors partitioned nodes and posts NodeFence CRD object.
 - [CSI Force Detach](#)
 - new CSI controller capability UNPUBLISH_FENCE and node capability FORCE_UNPUBLISH.
 - [Podmon](#)
 - Validate if host is still connected to storage and if there is IO; if not, fence and clean up.

```
// CSIDriverSpec is the specification of a CSIDriver.  
type CSIDriverSpec struct {  
    ...  
    // +optional  
    SafeDetach *bool  
}
```

```
- kind: ConfigMap  
  apiVersion: v1  
  metadata:  
    name: fence-method-fence-rhevnode1  
    namespace: default  
  data:  
    method.properties: |  
      agent_name=fence-rhevnode1  
      namespace=default  
      ip=ovirt.com # address to the rhevnode management  
      username=admin@internal  
      password-script=/usr/sbin/ssh_passwd  
      ssl-insecure=true  
      plug=vm-node1 # the vm name  
      action=reboot  
      ssl=true  
      disable-http-filter=true
```

How to Get Involved

- Shoutouts
 - Ashutosh Kumar ([sonasingh46](#)), David Porter, Derek Carr ([derekwayne carr](#)), Hemant Kumar ([gnufied](#)), Jing Xu ([jingxu97](#)), Michelle Au ([msau42](#)), Mrunal Patel, Tim Hockin ([thockin](#)), Xing Yang ([xing-yang](#)), Yassine Tijani ([yastij](#))
- Further Readings
 - <https://kubernetes.io/blog/2021/04/21/graceful-node-shutdown-beta/>
 - <https://kubernetes.io/blog/2022/05/20/kubernetes-1-24-non-graceful-node-shutdown-alpha/>
- Get Involved
 - [Kubernetes Storage SIG](#)
 - [Kubernetes Node SIG](#)



Please scan the QR Code above to
leave feedback on this session