Java Reflection API Summary Fall 2021 – CPSC 501

java.lang.Object

- public Class getClass()
- public String toString()
- public int hashCode()
- public boolean equals(Object obj)

java.lang.Class

- public Class forName(String classname)
- public Class getComponentType()
- public Constructor[] getConstructors()
- public Constructor[] getDeclaredConstructors()
- public Constructor getConstructor(Class[] parameterTypes)
- public Constructor getDeclaredConstructor(Class[] parameterTypes)
- public Field[] getFields()
- public Field[] getDeclaredFields()
- public Field getField(String name)
- public Field getDeclaredField(String name)
- public Method[] getMethods()
- public Method[] getDeclaredMethods()
- public Method getMethod(String name, Class[] parameterTypes)
- public Method getDeclaredMethod(String name, Class[] parameterTypes)
- public String getName()
- public int getModifiers()

- public Class getSuperclass()
- public Class[] getInterfaces()
- public boolean isArray()
- public boolean isInstance(Object obj)
- public boolean isInterface()
- public boolean isPrimitive()
- public Object newInstance()

${\bf java. lang. reflect.} {\bf Method}$

- public String getName()
- public Class getDeclaringClass()
- public Class[] getExceptionTypes()
- public Class[] getParameterTypes()
- public Class getReturnType()
- public int getModifiers()
- Object invoke(Object obj, Object[] args)

java.lang.Field

- public String getName()
- public Class getDeclaringClass()
- public Class getType()
- public int getModifiers()
- public Object get(Object obj)
- public boolean getBoolean(Object obj)
- public int getInt(Object obj)

- public double getDouble(Object obj)
- public void set(Object obj, Object value)
- public void setBoolean(Object obj, boolean value)
- public void setInt(Object obj, int value)
- public void setDouble(Object obj, double value)

java.lang.Constructor

- public String getName()
- public Class getDeclaringClass()
- public Class[] getExceptionTypes()
- public Class[] getParameterTypes()
- public int getModifiers()
- Object invoke(Object obj, Object[] args)

java.lang.Modifier

- public static boolean isPublic()
- public static boolean isProtected()
- public static boolean isPrivate()
- public static boolean isAbstract()
- public static boolean isStatic()
- public static boolean isFinal()
- public static String toString(int mod)

java.lang.Array

• public static Object newInstance(Class componentType, int length)

- public static int getLength(Object array)
- public static Object get(Object array, int index)
- public static boolean getBoolean(Object array, int index)
- public static int getInt(Object array, int index)
- public static double getDouble(Object array, int index)
- public static void set(Object array, int index, Object value)
- public static void setBoolean(Object array, int index, boolean value)
- public static void setInt(Object array, int index, int value)
- public static double setDouble(Object array, int index, double value)

author: jcleahy@ucalgary.ca