

# Optimization Project: Support Vector Machine

K. Kamtue & Cl. Réda

ENS Cachan

January 12th, 2017

## 1 Project description

- Project
- Optimization problem
- Implementation

## 2 Results

- Testing the implementation
- Plotting the classification frontier

## 3 Extensions

## 4 Demo

## 1 Project description

- Project
- Optimization problem
- Implementation

## 2 Results

- Testing the implementation
- Plotting the classification frontier

## 3 Extensions

## 4 Demo

# Project

## Support Machine Vector

### Objective

**Classify data**

# Project

## Support Machine Vector

### Objective

Classify data

- Applied to **binary classification** ( $y_i \in \{1, -1\}$ );

# Project

## Support Machine Vector

### Objective

Classify data


- Applied to **binary classification** ( $y_i \in \{1, -1\}$ );
- Looking for a **hyperplane**  $f : x \rightarrow \omega^T x$  such as:

$$\forall i, f(x_i) = \begin{cases} < 0 & \text{si } y_i = -1 \\ > 0 & \text{si } y_i = 1 \end{cases} \Leftrightarrow \forall i, y_i \times f(x_i) > 0 \quad (1)$$

# Project

## Support Machine Vector

Figure: Example with two classes (**red** and **blue**)



# Optimization problem

Looking for the optimization problem

## Naive optimization problem

$\gamma$ : distance between the lines  $f(x) = 1$  and  $f(x) = -1$ .



# Optimization problem

Looking for the optimization problem

## Naive optimization problem

$\gamma$ : distance between the lines  $f(x) = 1$  and  $f(x) = -1$ .

$$\begin{aligned} \max_w \quad & \gamma = \frac{2}{\|w\|} \\ \text{subject to} \quad & \forall i, y_i \times f(x_i) > 0 \end{aligned}$$

# Optimization problem

Looking for the optimization problem

## Naive optimization problem

$\gamma$ : distance between the lines  $f(x) = 1$  and  $f(x) = -1$ .

$$\begin{aligned} \max_w \gamma &= \frac{2}{\|w\|} \\ \text{subject to } \forall i, y_i \times f(x_i) &> 0 \end{aligned}$$


$$\begin{aligned} \Leftrightarrow \min_w \frac{1}{2} \|w\|^2 \\ \text{subject to } \forall i, y_i \times f(x_i) &> 0 \end{aligned}$$

**Beware:** if the data set is not linearly separable!

# Optimization

Looking for the optimization problem

Figure: Example with two classes (red and blue)



# Optimization problem

Adapting the problem to **non-separable** sets

Let  $z_i$  be  $\max(0, 1 - y_i \times f(x_i))$  (**Hinge loss**).

# Optimization problem

Adapting the problem to **non-separable** sets

Let  $z_i$  be  $\max(0, 1 - y_i \times f(x_i))$  (**Hinge loss**).

Having the problem **convex** and always **feasible**

Penalty for **classification errors** with  $(z_i)_i$  and  $C$  :

$$\begin{aligned} \min_{w,z} \quad & \frac{1}{2} \|w\|^2 + C \sum_{i \leq m} z_i \\ \text{subject to} \quad & \\ & \forall i, z_i \geq 0 \\ & \forall i, y_i \times (\omega^T x_i) \geq 1 - z_i \end{aligned}$$

## 1 Project description

- Project
- Optimization problem
- Implementation

## 2 Results

- Testing the implementation
- Plotting the classification frontier

## 3 Extensions

## 4 Demo

# Implementation

Solving the optimization problem

- Use **Newton's method** to find  $\omega$  :

Reminder: Update of  $\omega$  with **Newton's method**

$$\omega_{n+1} \leftarrow \omega_n + s \times \nabla^2 \text{obj}(\omega_n)^{-1} \nabla \text{obj}(\omega_n)$$

(finding **step size** value  $s$  by **backtracking line search**)

# Implementation

Solving the optimization problem

- Use **Newton's method** to find  $\omega$  :

Reminder: Update of  $\omega$  with **Newton's method**

$$\omega_{n+1} \leftarrow \omega_n + s \times \nabla^2 \text{obj}(\omega_n)^{-1} \nabla \text{obj}(\omega_n)$$

(finding **step size** value  $s$  by **backtracking line search**)

- Make the problem independant from **dimension**;



# Implementation

Solving the optimization problem

- Use **Newton's method** to find  $\omega$  :

Reminder: Update of  $\omega$  with **Newton's method**

$$\omega_{n+1} \leftarrow \omega_n + s \times \nabla^2 \text{obj}(\omega_n)^{-1} \nabla \text{obj}(\omega_n)$$

(finding **step size** value  $s$  by **backtracking line search**)

- Make the problem independent from **dimension**;
- Use **logarithmic barrier method**.

# Implementation

Independence from dimension: **dual problem**

After Lagrangian calculus and minimization in  $\omega$ :

# Implementation

Independence from dimension: **dual problem**

After Lagrangian calculus and minimization in  $\omega$ :

## Dual problem

$$\begin{aligned} \max_{\lambda \in \mathbb{R}^+{}^m} & -\frac{1}{2} \left\| \sum_i \lambda_i y_i x_i \right\|_2^2 + \mathbf{1}^T \lambda \\ \text{subject to } & \forall i, 0 \leq \lambda_i \leq C \\ & \text{(KKT conditions)} \end{aligned}$$

# Implementation

Independence from dimension: **dual problem**

After Lagrangian calculus and minimization in  $\omega$ :

## Dual problem

$$\begin{aligned} \max_{\lambda \in \mathbb{R}^{+m}} & -\frac{1}{2} \left\| \sum_i \lambda_i y_i x_i \right\|_2^2 + \mathbf{1}^T \lambda \\ \text{subject to } & \forall i, 0 \leq \lambda_i \leq C \\ & \text{(KKT conditions)} \end{aligned}$$

Get **primal solution** from dual solution

$$\omega^* = \sum_i \lambda_i^* y_i x_i$$

# Implementation

Make the problem independant from dimension

Use the **kernel trick** :

## Dual problem

Let  $K$  be  $X^T X$  (linear kernel):

$$\begin{aligned} \max \quad & -\frac{1}{2} \lambda^T \text{diag}(y) K \text{diag}(y) \lambda + \mathbf{1}^T \lambda \\ \text{subject to} \quad & \forall i, 0 \leq \lambda_i \leq C \end{aligned}$$

# Implementation

Delete inequality constraints

Use the **logarithmic barrier method** :

# Implementation

Delete inequality constraints

Use the **logarithmic barrier method** :

Barrier function

$$\begin{aligned}\Phi(\lambda) &= \sum_i (-\log(C - \lambda_i) - \log(\lambda_i)) \\ &= -\sum_i \log((C - \lambda_i)\lambda_i)\end{aligned}$$

# Implementation

Delete inequality constraints

Use the **logarithmic barrier method** :

Barrier function

$$\begin{aligned}\Phi(\lambda) &= \sum_i (-\log(C - \lambda_i) - \log(\lambda_i)) \\ &= -\sum_i \log((C - \lambda_i)\lambda_i)\end{aligned}$$

Final optimization problem

$$\max -\frac{1}{2}\lambda^T \text{diag}(y)K\text{diag}(y)\lambda + \mathbf{1}^T \lambda + \Phi(\lambda)$$



## 1 Project description

- Project
- Optimization problem
- Implementation

## 2 Results


- Testing the implementation
- Plotting the classification frontier

## 3 Extensions

## 4 Demo

# Testing the implementation

## Newton's method convergence



# Testing the implementation

Dependence on the sample size

Table: Time complexity dependence

Set	C	d	n	Iteration number	Time
1	5	40000	10	11	0.315
1	5	40	100	12	0.715
1	5	40	1000	large	> 1,000

# Testing the implementation

Speeding of convergence when  $C$  increases

Performed on the same sample set:

**Table:** Computation time in function of  $C$

Test Set	$C$	$d$	$n$	#iterations	Time	Fail (%)
1	1	40	10	11	25.414	0
1	5	40	10	11	0.177	0
1	10	40	10	11	0.168	0

## 1 Project description

- Project
- Optimization problem
- Implementation

## 2 Results

- Testing the implementation
- Plotting the classification frontier


## 3 Extensions

## 4 Demo

# Plotting the **classification frontier**

Pour  $C = 5, n = 150, d = 200$


Points centrés réduits avec des fonctions gaussiennes (2D) :



# Tracé de la frontière de classification

Pour  $C = 5, n = 150, d = 200$


Points centrés réduits avec des fonctions gaussiennes (3D) :



# Tracé de la frontière de classification

Pour  $C = 5, n = 150, d = 200$

Génération avec des fonctions gaussiennes (2D) :






# Tracé de la frontière de classification

Pour  $C = 5, n = 150, d = 200$

Génération avec des fonctions gaussiennes (3D) :



## 1 Project description

- Project
- Optimization problem
- Implementation

## 2 Results

- Testing the implementation
- Plotting the classification frontier

## 3 Extensions

## 4 Demo

# Extensions

Adding to the project

- **Cross validation** (choice of the best value for  $C$ );

# Extensions

Adding to the project

- **Cross validation** (choice of the best value for  $C$ );
- Implementation of **Coordinate Descent**;

# Extensions

Adding to the project

- **Cross validation** (choice of the best value for  $C$ );
- Implementation of **Coordinate Descent**;
- Implementation of **ACCPM**;

## 1 Project description

- Project
- Optimization problem
- Implementation

## 2 Results

- Testing the implementation
- Plotting the classification frontier

## 3 Extensions

## 4 Demo

## Demo of the SVM