Codes Explorer

Learn Embedded C, ML, Python, C++, 8051, ARM



8051 ARM Verilog C++ Machine Learning Python Java RTOS

Contact Us

July 28, 2017 - 8051

8051 Assembly code to find LCM of two numbers



Hello guys! After lot of optimization and debugging finally found a ALP program to find LCM of two numbers using 8051 micro-controller. Happy share this piece of code with you guys.

Its easy and short. We have been learning to find LCM from our school days. Finding Least common multiple of of two numbers is easy by finding GCD of those two numbers and then dividing of product of those two number by GCD. But in terms of programming its complicated! So, here I

Search	Q

Recent Posts

- Computing the total storage size of the ADLS Gen1 or Gen2 folder in Pyspark
- Run DatabricksNotebooks In Parallel -Python
- Rotate array in the right direction by K steps
- C++ program to demonstrate simple inheritance

have new algorithm to find LCM of two numbers.

ALGORITHM:

- 1. Start
- 2. Store first number(num1) in a register
- 3. Store second number(num2) in another register
- 4. Initialize a counter register(Rd) to 01h
- 5. Compare both the values num1 and num2
 - If num1 = num2 : Store num1 or num2 as result and jump to step 8
 - If num1 < num2 : Swap the register values so that num1 > num2
- 6. Multiply num2 and Rd and divide the product with num1
- 7. Check the reminder
 - If reminder is zero then store product obtained from multiplication in step 6 as result and jump to step 8
 - Else increment Rd and repeat steps 6 and 7

8. Stop

Here is example code to find LCM of 3 and 6

CODE:

ORG 0000h

```
LJMP main
ORG 0040h
main: MOV R0,#03h
MOV R1,#06h
```

MOV R1,#06h ; Ini
MOV R2,#01h ; Ini
MOV A,R0
MOV B,R1

CJNE A,B,label1 ; Com

MOV R4,A SJMP stop

label1: JNC loop ; Comparing a

MOV A,R1 MOV B,R0 Introduction to Python Programming

Categories

- 8051
- ARM
- C++
- databricks
- Java
- Machine Learning
- Python
- RTOS
- Uncategorized
- Verilog

; Ini

MOV RØ,A

MOV R1,B

loop: MOV A,R2; loop to find LCM

MOV B, R0

CJNE A,B,next ; comparing if Rd val

SJMP stop

next: MOV A,R1 ; Finding product of

MOV B,R2 MUL AB

MOV R4,A ; Storing product

INC R2

MOV B, R0

DIV AB ; Dividing by num1 to

MOV R3,B

CJNE R3,#00h,loop; Continue until re

SJMP stop

stop: JMP stop

END

« 8051 Assembly code to find average of all numbers stored in array 8051 code to find a square of first 10 natural numbers and store it in an array. »

Leave a Reply

CodesExplorer

COMPANY

CONTRIBUTE

Learn Code Execute

About Us

Write an Article

Privacy Policy

Careers

29/04/2024, 05:20 Contact Us

Copyright $^{\circledR}$ All rights reserved.

Blog Zone by ProDesigns