

Ground

Digital Pin

Power

Analog Pin

LED

Other Pin

Internal Pin

Microcontroller's Port

SWD Pin

Default

MAXIMUM current per I/O pin is 20mA

MAXIMUM current per +3.3V pin is 50mA

NOTE: CIPO/COPI have previously been referred to as MISO/MOSI

VIN 7-12 V input to the board.


ARDUINO.CC

Last update: 30/06/2021



This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.









MAXIMUM current per +3.3V pin is 50mA

NOTE: CIPO/COPI have previously been referred to as MISO/MOSI

VIN 7-12 V input to the board.


ARDUINO.CC

Last update: 30/06/2021



This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.









VIN 7-12 V input to the board.

MAXIMUM current per +3.3V pin is 50mA

NOTE: CIPO/COPI have previously been referred to as MISO/MOSI

Last update: 30/06/2021



ARDUINO.CC



This work is licensed under the Creative Commons Attribution-ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/ or send a letter to Creative Commons, PO Box 1866, Mountain View, CA 94042, USA.