

1. running todo list

Keep this list as the source of truth. Every task has a permanent number and ☐ (open, partial, unverified, or deferred) or ☒ (completed). Never remove completed tasks or renumber existing tasks; append new tasks with the next unused number. Resolved and audit notes must cite the relevant item numbers. Update the checkbox only when the entire task is complete and verified.

1. ☐ (Deferred) there should be a proper pdf preview option that is just a proper pdf viewer.
2. ☐ (Deferred) perf
3. ☒ typst overrides should be in appearances subsection
4. ☒ the color indicator in typst overrides should always be the current color, not faded out if its 'theme/override'. In fact there should not be a 'theme/override' button, since if we want to return to the theme we can just hit the reset button
5. ☒ somethings not right with alignment, see pic
6. ☒ lots of tooltips in typst overrides popup kinda suck. Too big, not useful. If useless just delete it, otherwise tighten the space
7. ☒ next to the theme name in the selectors, we should be able to see at a glance a colour palette of the theme.
8. ☒ allow customising UI fonts
9. ☒ cmd +/- should adjust UI size. Also put a slider for this in settings
10. ☒ syntax highlight the markdown in the tooltips. If typc doesnt give colour coding then treat it as typ.
11. ☒ if we are using a variable width font, add support to set the weight (typst overrides, and UI)
12. ☒ change so that: allow triangular area from cursor to tooltip / error window to not dismiss. When mouse is over the popup, we can scroll.
13. ☒ also add a keyboard shortcut to make the popup appear with keyboard focus (for scrolling up/down). Esc to unfocus and dismiss. There should be a subtle outline to indicate focus (as well as mouseover)
14. ☒ I noticed that when I use a `...` code block, it is not syntax highlighted correctly. Fix
15. ☒ syntax highlight the markdown in the tooltips. If typc doesnt give colour coding then treat it as typ. (Duplicate of item 10; keep both statuses in sync.)
16. ☒ Mitex and cmarker integration: autodetect strings/raw strings inside `#mi(...)` etc to syntax highlight with tex or markdown. Note that you may need to put the text in math mode or text mode depending on the mitex command
17. ☒ for other colour formats (luma etc) we should give that text the appropriate fill, like we do now for `#rgb("hex number")`
18. ☐ package manager - inspect available packages, locally installed packages
19. ☒ detect when file changed outside app. If we dont have any changes queued to be saved, then reload the file
20. ☒ allow font ligatures in code editor

21. ☐ image / pdf preview on hover (both in code, when we include images as part of the code, and in file explorer)
22. ☐ configurable shortcuts everywhere. add a popup for this in settings
23. ☐ add search to all everything - explorer windows, settings,
24. ☒ view > ... needs to be in the title bar as well, and also none of the shortcuts are appearing - add
25. ☒ allow us to toggle off the title bar dupes of the menu bar items
26. ☐ (Deferred) once in a while the text everywhere breaks (see pic) some sort of leak?
27. ☒ after some time, the find/replace UI is not visible but is clickable. I realised this is because it is rendering behind the code editor panel. we shouldnt even make space for the find / replace UI - it should just be on top of the code panel.
28. ☐ keyboard shortcuts when find and replace is active should work on find and replace text fields. and similarly for other text fields (Partial: find-field focus is preserved; verify shortcuts across all other text fields.)
29. ☒ cmd+F / the Find button should toggle the find/replace popup, not just turn it on.
30. ☒ there should be a button to toggle find and find/replace
31. ☒ there should be options to allow case (in)sensitivity and regex (which we should be able to right click and get a cheat sheet). add single-symbol wide buttons for these
32. ☒ if we right click and its already 'use for preview'd then we should be able to toggle it off
33. ☐ text highlight of file names is not readable, adjust color scheme
34. ☒ should be able to right click file in explorer -> open in new window
35. ☒ cmd-/ to toggle comment out current or selected line(s)
36. ☐ shortcuts should be configurable (Duplicate of item 22; keep both statuses in sync.)
37. ☒ move the problems button to the rightmost slot (matching with default shortcuts)
38. ☐ remove 'cmd/ctrl' everywhere in popups/tooltips its just cmd
39. ☒ fallback for CJK fonts
40. ☐ autocomplete
41. ☐ text is selectable in too many places
42. ☐ file menu in menu bar does not match file in title bar. It should be single source of truth
43. ☐ file explorer subsection separators should be draggable
44. ☐ when closing the file explorer it should first stop showing all the contents before minimising
45. ☒ there should be another subsection in the explorer, the tags/references
46. ☒ color code various filetypes (various categories should be: .typ, other text-based files, pdfs and images, folders, and others) make sure you use colours from the theme
47. ☒ the ttt in settings window is no longer left of file name in main window(s)
48. ☒ the top right X in settings should not be there - use the Mac OS traffic lights

49. ☐ selecting a file in file explorer resets the file explorer scroll amount. Why? Opening a file cannot trigger more files to appear. It should not redraw. If it does, at least restore the scroll
(Implementation now preserves the cached filesystem snapshot and tree identity when opening a file within the current workspace; user interaction verification remains open.)
50. ☐ the current line background should be also used for the current file. The currently opened file should also use an actual heavier UI-font face, not only stronger text color. (Implementation and deterministic font-role coverage are complete; user interaction verification remains open.)
51. ☒ find and replace shortcut just gives find.
52. ☐ we should (by default) have the current scopes and the current sections/subsections etc be “sticky rows” at the top so that we have context for what we are looking at. each level should give a further row that is persisted to the top. For instance if we are in

```
= first section
// <many lines>
== subsection
#let a = {
// <many lines>
// <cursor is here>
```

then overlayed at the top should be

```
= first section
== subsection
#let a = {
```

(together with the line numbers). Basically another code panel floating on top but with those lines. There should also be line numbers, and clicking on the sticky row should jump in main code panel to that row

53. ☒ sync back from code -> preview should be one of the right click options
54. ☐ right click menu if possible should use native right click. If not, at least the text should not be centered, it should be left-aligned like normal
55. ☒ special detection of typst functions: set text(font: ...) should allow us to right click on font: ... and then have a scrollable selector
56. ☒ allow using fonts in the root of working directory or anywhere in the working directory if it is not a performance hit.
57. ☐ Table maker / editor on right click (with detection of tables)
58. ☒ the tooltips on hover should be wider. Maybe more like 80 char wide
59. ☐ remove unsafe rust as much as possible
60. ☐ it should format on manual save (cmd+s) (but not auto save) (Partial: existing-file manual saves format when TinyMist is ready; initial Save As remains open.)
61. ☐ if we have a file set to be used for preview, then when we switch to a different file, we dont need to restart the preview window. Also, we should not close it even if we open a non-typ file. thats the point of the used for preview setting - so that we can edit other child files like a .toml or other .typ files (Implementation and deterministic state tests are complete; user interaction verification remains open.)

- 62. ☒ Any part of the UI with this tiny font size like that used in the file path of the file explorer should have a bigger font. Never use this small font. Also don't use allcaps or smallcaps, not our style.
- 63. ☒ in addition to the pdf ready indicator i also want all the greentext on the side e.g. applied theme saved automatically. and everything should be timestamped.
- 64. ☒ we should reserve some space for the * in the name when a file is not yet saved, so that when it does appear, it doesn't shift the UI elements.
- 65. ☐ double clicking on a line in the Problems panel should jump to that line in the code panel
- 66. ☐ the logo icon should be redone to match the settings 'ttt'
- 67. ☐ on closing the app ran with cargo compile --release it should not lose the icon as it disappears?
- 68. ☒ Maintain UI observability and regression tests with targeted fresh screenshot inspection when pixel-level behavior is material. Capture detailed UI scenes in two representative themes (Catpuccin Latte and Mocha), and a generic main-window shot for each remaining theme.
- 69. ☒ code panel tooltips have disappeared. very odd?
- 70. ☐ if i am editing test.typ and i set todo.typ to be used for preview, then it should refresh the preview window to use todo.typ. this is not the current behavior, and if i then switch to opening the todo.typ file, the preview will still be stuck at test.typ (Implementation and Tinymist handshake tests are complete; user interaction verification remains open.)
- 71. ☐ cmd+M should minimise the window, and so on for the usual mac os shortcuts
- 72. ☒ should have two proper dropdown for all fonts in settings (one for UI and one for code) - ability to choose any system font. In addition as mentioned above I think, we should search the local dir for fonts that we can use in the document.
- 73. ☒ the "Applied Catpuccin Latte" etc text is stuff i also want in the log. and keep the last 100 entries instead
- 74. ☒ font weight should not be adjusted until after mouse off the scrollbar as the UI shifts with the change causing feedback
- 75. ☒ remove the colour palette swatches from Settings completely
- 76. ☒ vertically centre the font-weight slider and give the code font its own independently persisted weight control
- 77. ☒ vertically align the Syntax label, live samples, and Reset buttons in Typst overrides
- 78. ☒ make popup focus and ownership robust so using or closing Settings cannot leave popups broken
- 79. ☒ keep the recent-status popup close to the status bar and right-align its timestamps
- 80. ☒ remove the obsolete pre-tiptotyp app bundle, registration, build outputs, and compatibility namespace completely
- 81. ☐ capture the complete maintained screenshot gallery from one app session instead of reopening the app for every image (The one-session runner and manifest tests are complete; a fresh full gallery exercise remains open.)

- 82. ☐ redraw the refresh and used-for-preview eye vector icons so the refresh arrowhead does not overlap its body and the eye is rounded rather than angular (Implementation and deterministic geometry tests are complete; user visual verification remains open.)
- 83. ☐ make tooltip Markdown links display only their linked text and open in the system browser; support opening external Typst `#link( . . . )` targets with Cmd+click or the editor context menu; and open preview links in the browser (Implementation and deterministic interaction/routing tests are complete; user interaction verification remains open.)
- 84. ☐ prevent selecting file-tree names, the ttt logo, and the title-bar filename; add file-name, absolute-path, and workspace-relative-path copy actions to file context menus; and show Cmd+1 through Cmd+5 shortcuts in the native View menu (Implementation and deterministic tests are complete; user interaction verification remains open.)
- 85. ☐ add a Pause/Resume control for automatic compilation and make Compile write the effective Typst entry's PDF beside its source, using an output picker only for an unsaved document (Implementation and deterministic tests are complete; user interaction verification remains open.)

2. resolved in the 2026-09-07 pass

Items 1, 2, and 26 remain deferred. This history records completed work and partial progress; the running checklist above is authoritative for completion status. Focused tests cover the deterministic behavior described below:

- Items 3, 4: Typst overrides now live under Appearance, show the effective color, and use Reset to return to inherited theme values.
- Item 6: Removed redundant hover cards from override labels, color swatches, live samples, and Reset buttons; decoration controls retain only concise state-and-action hints.
- Items 7, 8, 9: Built-in theme selections show palette swatches; UI font choice supports the default, editor-monospace, or a validated custom TTF/OTF/TTC file, with interface scaling via Cmd-plus/minus.
- Items 10, 14, 15: Markdown tooltip blocks use syntax highlighting; `typ`, `typst`, and `typc` fences use the Typst highlighter.
- Items 12, 13, 58: Tooltip cards are wider, scrollable, clipped to the viewport, retain a root-local pointer bridge to the card, and support click or Cmd+Shift+Space focus, selectable copying, Escape dismissal, and a focused outline.
- Items 5: Preview geometry is clamped to the actual panel clip and zoomed previews preserve their viewport origin.
- Items 19: External edits reload clean editable documents and produce an explicit conflict notice for dirty documents.
- Items 24, 25, 29, 30, 31, 51: View commands, shortcuts, title-bar menu visibility, find/replace toggling, replace actions, case sensitivity, regex mode, and the regex help menu are wired through shared commands.
- Items 27: The find/replace bar is a foreground overlay and no longer reserves editor layout space.
- Items 32, 34: Explorer context menus can open files in a new window and toggle the designated preview file on and off.
- Items 35, 53: Cmd-slash toggles comments for the current or selected lines; editor context menus can reveal the source in Preview.
- Items 37, 39, 46: Problems is the rightmost view control; file labels use theme colors by document category; CJK fallback fonts are registered when available.
- Items 45: Tags and references are indexed and navigable from a new Explorer section.
- Items 48: macOS child windows use native traffic lights; non-macOS windows retain an in-content close action.

- Items 61: Renaming a designated preview entry recreates its Tinymist URI safely.
- Items 60: Saving an existing Typst file requests formatting when Tinymist is ready and persists the formatted source; auto-save does not format. The initial Save As flow still needs formatting integration.
- Items 61: A designated preview remains alive while editing child Typst/text/PDF/image files, and its state is restored when returning to source.
- Items 47, 63, 64: Status history has timestamps, dirty-title space is reserved, and the main title bar uses the settings `ttt` logo.
- Items 62: Small-text styling was removed from the application UI; supporting text uses the shared readable type scale.

Open work is tracked only by the unchecked entries in the running list above, so this audit history cannot become a second, stale task list.

Item 68: Native screenshot capture was initially blocked by the sandbox's LaunchServices/Services connection. Gallery decoding and manifest tests passed; fresh capture subsequently succeeded during the audit below.

3. correctness audit (2026-09-07)

- Items 5, 9: Corrected UI scaling to preserve native display density, with a 1x/2x display regression test.
- Items 31: Replaced the recursive regex parser with the maintained regex-automata engine already used by Syntect. Added Unicode, invalid-pattern, zero-width navigation, and pathological-pattern regressions. Replacement text remains literal.
- Items 19, 27, 28: Fixed external-change polling when Explorer is hidden, kept find overlays anchored to the visible editor, and preserved find-field focus while navigating matches.
- Items 60: Prevented stale formatting replies from cancelling a newer save request; cleared pending save-format intent on edits and document switches.
- Items 61: Preserved current preview-entry edits queued before Tinymist initializes and removed a duplicate restart when renaming the current preview entry.
- Items 10, 14, 15: Shared bundled syntax databases across tooltip highlighters and corrected Typst tooltip colors in light mode.
- Item 8: Validated custom TTF/OTF/TTC bytes before loading, retained a fallback chain, and kept editor syntax fonts independent from the selected UI font.
- Items 45: Used the Typst syntax tree for labels/references, excluding strings, comments, and raw examples.
- Items 61, 68: Isolated screenshot fixtures from persisted designated-preview settings without changing those settings.
- Items 5, 9, 27, 68: Native capture succeeded outside the sandbox. Inspected the fresh find/replace PNG under `.tiptotyp/screenshots/agent-review`; retained native bounds and Retina scale evidence in `audit-geometry.txt` alongside it.
- Items 68: Regenerated and validated all 68 maintained gallery PNGs; inspected representative light/dark editor, find overlay, and settings captures. Formatting, strict clippy, 308 application/integration tests, and 7 packaging tests pass (2 environment-dependent tests remain ignored).

Open work is represented by the unchecked entries in the running list above.

4. correctness audit (2026-09-07 tooltip follow-up)

- Items 12, 13: Native tooltip geometry now converts the monitor-space child position back to root-local coordinates for pointer bridging. Click or Cmd+Shift+Space requests popup focus, Escape or defocus dismisses it, and the focused card gets a subtle outline.

- Items 10, 14, 15: Selectable tooltip labels make rendered markdown copyable. typc fences parse as synthetic `#{...}` code-mode snippets, strip the synthetic delimiters, and are covered for keyword, number, and function roles.
- Items 12, 13, 10, 14, 15, 68: Fresh diagnostic and function tooltip screenshots were captured and inspected in Catppuccin Latte and Mocha. The full serialized suite passes with strict Clippy and formatting checks.

5. correctness audit (2026-09-07 final follow-up)

- Items 12, 13: Retained diagnostic tooltip payloads while the pointer crosses the root-to-native-card bridge, so the popup no longer disappears during transit.
- Item 19: External-file polling now distinguishes a missing file from an unreadable file and reports deletion explicitly for both clean and dirty buffers.
- Item 61: Renaming a non-preview child document no longer tears down a live designated Tinymist preview; renaming the designated entry itself still recreates its URI intentionally.
- Items 29, 46: Find toggling is consistent across the shortcut, toolbar, native Edit menu, and title-bar Edit popup; project indexing and workspace colors now accept the same case-insensitive Typst extension policy as document detection.
- Verification: The corrected suite passes with 308 application/integration tests, 2 ignored environment-dependent tests, 7 packaging tests, strict Clippy, formatting, diff checks, 68 PNG decodes, and a fresh inspected find/replace capture.

6. correctness audit (2026-09-07 tooltip handoff correction)

- Items 12, 13: Replaced the center-point triangle with an edge-to-edge pointer corridor, so paths toward the tooltip's top or bottom edge remain connected during the hover handoff.
- Verification: The tooltip bridge regression now covers a top-edge transit path; focused tooltip and coordinate-conversion tests also pass, and a fresh diagnostic tooltip PNG was captured and inspected.

7. correctness audit (2026-09-07 competing tooltip handoff correction)

- Items 12, 13: Prevented another native hover source from replacing the active tooltip while the pointer is inside the original tooltip's bridge or focused popup. This covers diagnostic, semantic editor, and shared native-control hover payloads.
- Verification: Added a competing-hover regression covering bridge retention, focused retention, and dismissed cleanup; the full suite, strict Clippy, formatting, diff checks, and a fresh inspected diagnostic tooltip capture pass.

8. correctness audit (2026-09-08 tooltip opacity correction)

- Items 12, 13: Limited handoff blocking to competing source rectangles, allowing the active source to continue its fade-in animation to full opacity while still protecting its payload during transit.
- Verification: Added same-source versus competing-source assertions; focused tooltip, bridge, Clippy, formatting, diff checks, and a fresh inspected diagnostic tooltip capture pass. One serialized full-suite run hit a transient fake-Tinymist handshake timeout; the failing test passed when rerun alone.

9. correctness audit (2026-09-08 tooltip frame correction)

box

- Items 12, 13, 58: Sized native tooltip viewports from the tooltip frame's complete inner, outer, and stroke margins, preventing the lower rounded edge from being clipped.
- Verification: Tooltip and popup-frame tests, strict Clippy, formatting, diff checks, and a fresh inspected diagnostic tooltip capture pass.

10. correctness audit (2026-09-08 native popup edge correction)

- Items 12, 13, 58: Short native tooltips now shrink their vertical scroll area to the rendered content, so the lower rounded frame remains visible instead of reaching the child viewport edge.
- Items 12, 13: Pointer and focus hit-testing now uses the painted frame rectangle, excluding transparent child-viewport padding from hover handoff and clicks.
- Item 68: Native menu content budgets now derive from the rendered frame margins rather than hard-coded chrome values; the screenshot workflow now explicitly documents that viewport PNGs are not composed desktop screenshots.
- Verification: Added a popup content-budget regression, captured and inspected the exact single-line tooltip case and the File menu in a fresh Catpuccin Latte release run, and retained the native preview geometry trace.

11. correctness audit (2026-09-08 tooltip handoff regression correction)

- Items 12, 13: Restored the full transparent native child viewport as the pointer handoff envelope while keeping painted-card hit-testing precise, preventing a competing tooltip from taking over before the pointer reaches the active card.
- Verification: Added a regression for competing targets across the child viewport, passed the focused tooltip tests, and captured and inspected a fresh traced Catpuccin Latte release tooltip framebuffer.

12. correctness audit (2026-09-08 robust tooltip handoff correction)

- Items 12, 13: Closed the semantic-editor hover path that bypassed the shared native-tooltip handoff gate, and added identity-preserving geometry plus a 300 ms grace window so a transient pointer gap cannot dismiss the active tooltip before the pointer reaches it.
- Verification: Added a transient-gap regression, passed 7 focused tooltip tests, passed the full 286-test application suite plus integration and 7 packaging tests, and captured and inspected fresh release tooltip framebuffer 1788801929503-0001-diagnostic-diagnostic-tooltip.png.

13. correctness audit (2026-09-08 child-owned tooltip handoff and syntax correction)

- Items 12, 13: Made the native tooltip child viewport the sole owner of its pointer-presence state. Root-window pointer gaps can extend the route deadline but can no longer clear a child-owned hover, focus-transfer frames remain renderable, and identity checks prevent a closing tooltip from mutating its replacement.
- Items 10, 14, 15: Converted language-tagged Tinymist marked strings into real fenced Markdown, routed typ and typst through Typst source mode and typc through synthetic `#{...}` code mode, and syntax-highlighted inline code without leaking its style past a closing backtick.
- Items 10, 12, 13, 14, 15, 68: Added regressions for child-owned pointer state, stale tooltip identities, focus transfer, source-versus-code highlighting, and inline marker closure. Formatting, strict Clippy, 291 application tests (289 passed and 2 environment-dependent ignored), integration tests, 7 packaging tests, and all 68 PNG decodes pass. Fresh Catpuccin Latte and Mocha diagnostic and function tooltip framebuffers were captured and inspected.

14. correctness audit (2026-09-08 pre-commit)

- Items 24, 29, 34, 51: Ordered modified shortcuts before their generic variants, preventing Open, Find, and interface scaling from consuming Open in New Window, Change Workspace Root, Find and Replace, or raster-preview zoom. Raster zoom now uses Cmd/Ctrl+Option/Alt with Plus, Minus, or 0 so item 9 keeps the unmodified Cmd/Ctrl+Plus and Minus contract.

- Item 28: Enter and Shift+Enter now move forward and backward respectively while returning focus to the find field; the broader cross-field shortcut audit remains open.
- Item 19: External-file observations are cleared on document switches and successful saves, preventing one file's missing/changed state from suppressing another file's notification.
- Item 60: Manual saves confirmed through the external-change overwrite dialog now request formatting too, while save-before-close/open flows remain immediate. Tinymist restarts invalidate outstanding save-after-format intent.
- Items 12, 13: Stale tooltip interaction state is identity-checked and cannot block all future tooltip sources when native geometry is temporarily absent.
- Items 39, 46, 63: Added the omitted ICO image category, made UTC status timestamps explicit with Z, and avoided reapplying UI font/style configuration every frame.
- Item 68: Added shortcut, timestamp, file-category, and tooltip-state regressions. Formatting, strict Clippy, 295 application tests (293 passed and 2 environment-dependent ignored), 26 integration tests, and 7 packaging tests pass. All 68 maintained PNGs validate; fresh Catppuccin Latte and Mocha find, diagnostic-tooltip, and status-log captures were inspected, with final native tooltip/preview geometry retained in audit-geometry.txt.

15. resolved in the 2026-09-08 font and embedded-syntax pass

- Item 11: UI fonts now expose their real OpenType weight range or installed static faces, while editor syntax roles use numeric weights from 100 through 900. Typst override settings migrate the old bold flag to weight 700 without losing saved themes.
- Item 16: String and raw-string arguments to MiTeX math/text entry points and Cmarker render entry points now use embedded TeX or Markdown highlighting while preserving exact editor byte positions.
- Item 17: Literal arguments to Typst's RGB, luma, CMYK, linear RGB, HSL, HSV, Oklab, and Oklch constructors now show a readable preview fill. Detection is limited to Typst's actual namespaces and valid literal component types so unrelated custom calls are unchanged.
- Audit for items 11, 16, and 17: Corrected a clipped Settings weight row, removed axis-relative slider rounding that changed 400 to 401, kept deterministic screenshot runs from persisting QA-only settings, made the offline Cmarker fixture valid Typst, and tightened invalid color-call detection. Formatting and strict Clippy pass; 302 application tests pass with 2 environment-dependent tests ignored, alongside 26 integration/gallery tests and 7 packaging tests. All 68 maintained PNGs decode and validate; fresh Catppuccin Latte and Mocha main, Settings, and Typst-overrides viewport PNGs were inspected, with traced native preview bounds remaining clipped to the panel.

www.google.com

16. correctness audit (2026-09-08 fonts, popups, and greenfield cleanup)

- Items 20, 72, 74, 76: Code ligatures are enabled. Settings has separate system and workspace font dropdowns and independently persisted UI and code weights. Continuous weight changes are staged until pointer release, and both slider rows share one vertical-centering contract.
- Items 55, 56: Right-clicking a text font argument opens a scrollable document-font selector. Workspace fonts are discovered asynchronously and supplied to Typst and Tinymist. File fingerprints catch additions and in-place replacements while preserving the prior catalog during a rescan.
- Items 63, 73, 79: Preview status and visible notices share a timestamped newest-first log capped at 100 entries. The popup grows only for visible rows, hugs the status bar, and uses a fixed right-aligned timestamp column.

- Items 69, 78: Popup state now has one owner. Settings and app menus close competing transients, blur requires a grace period, each menu opening has independent scroll memory, and popups paint immediately at full opacity.
- Items 75, 77: Settings palette swatches are gone. Typst override headers, syntax labels, samples, and Reset buttons share exact row centers. Deterministic Settings and override scenes reset their scroll origins.
- Item 80: Removed the obsolete app bundle, registration, build products, scratch previews, deprecated names and environment variables, old settings migrations, deprecated LSP root path, Finder process-serial handling, and disconnected editor receiver plumbing. The current settings schema is a clean break.
- Item 26 remains deferred.
- Items 68, 72 through 80: Regenerated and decoded all 68 gallery PNGs and inspected fresh Catppuccin Latte and Mocha Settings, theme-picker, menu, tooltip, status, font-selector, and Typst-override captures. The native inspector did not expose the current bundle window, so viewport captures are not claimed as proof of composed desktop geometry.
- Verification for items 68, 72 through 80: Formatting, strict Clippy, 318 application tests (316 passed and 2 environment-dependent ignored), 26 integration tests, and 7 packaging tests pass. Fake-Tinymist test deadlines now tolerate full-suite scheduler load without changing runtime timeouts. Diff checks pass and no obsolete pre-rename namespace, deprecated root-path field, or removed alias remains in tracked implementation.

17. correctness audit (2026-09-08 pinned preview and risk-based UI evidence)

- Items 61, 70: The designated Typst entry is passed to both Tinymist compilation and startDefaultPreview. Switching among project Typst, text, PDF, and image files preserves the same native WebView and only updates the active LSP document. A replacement preview server now forces one navigation even when the operating system reuses its predecessor's localhost URL.
- Items 61, 70: Interactive preview suppresses duplicate raster compilation during steady-state use. Raster pages remain an explicit fallback for unavailable native preview, export, and targeted framebuffer capture.
- Items 68, 81: AGENTS.md and its regression test now require screenshots only for materially visual risks. The maintained gallery remains a serialized one-app-session workflow, but no fresh capture was performed in this audit at the user's request.
- Verification for items 61, 68, 70, and 81: Formatting, strict Clippy, the full Rust suite, all decodable gallery/manifest checks, and 7 packaging tests pass. Items 61, 70, and 81 remain unchecked until their explicitly outstanding manual exercises are completed.

18. correctness audit (2026-09-08 vector icon redraw)

- Item 82: Replaced the overlapping refresh chevron with a continuous arc-and-arrow path whose outer wing remains outside the circular body. Replaced the straight-sided preview eye with symmetric cubic Bezier curves and a centered round pupil.
- Verification for item 82: Deterministic geometry tests cover arrow/body separation and curved-eye symmetry. Formatting, strict Clippy, and the full Rust suite pass. No app launch or screenshot was used; item 82 remains unchecked for user visual verification.

19. correctness audit (2026-09-08 external link interactions)

- Item 83: Tooltip Markdown links now omit their destination syntax, retain selectable text, and dispatch normalized HTTP(S) targets through the shared system-browser route. The editor recognizes literal external targets in real #link(...) calls: normal clicks remain editing actions, Cmd+click opens

the link, and right-click exposes an Open Link in Browser action. Raster and native preview links use the same route.

- Item 83: Native preview navigation callbacks now read the current preview URL, project root, and designated-source directory from shared session state. Reusing a pinned WebView after Tinymist restarts therefore cannot mistake the replacement localhost origin for an external page or resolve project links relative to a stale editor file.
- Verification for item 83: Parser, Unicode cursor mapping, unsafe-scheme rejection, command-click priority, semantic tooltip activation, semantic context-menu activation, popup sizing, project-file routing, external preview dispatch, and replacement-origin routing have deterministic regressions. No app launch or screenshot was used; item 83 remains unchecked for user interaction verification.

20. correctness audit (2026-09-08 inert chrome and explorer copy actions)

- Item 84: File-tree names, every ttt logo instance, and the main title-bar filename now explicitly opt out of egui label selection while document-like labels remain selectable. File context menus expose separate commands for the file name, absolute file path, and path relative to the workspace root; directory menus retain their existing Copy Path command.
- Item 84: The native View menu now advertises the same Cmd+1 through Cmd+5 mapping already handled by the editor and shown in the title-bar View popup: Explorer, Code, Split, Preview, and Problems.
- Verification for item 84: Selection behavior, clipboard text derivation, context-menu routing and sizing, and native shortcut metadata have deterministic regressions. No app launch or screenshot was used; item 84 remains unchecked for user interaction verification.

21. correctness audit (2026-09-08 stable explorer activation)

- Item 49: Opening another document inside the current workspace now preserves the cached filesystem snapshot instead of clearing it or scheduling an unnecessary scan. The stable snapshot generation keeps the tree identity, expansion state, and scroll memory intact; a real workspace-root change still installs a new snapshot.
- Item 50: The active Explorer entry retains the shared active-row background and now uses a separately registered heavier face of the selected UI font. This makes the current file genuinely bold instead of relying on egui's stronger-color-only strong flag.
- Verification for items 49 and 50: Workspace invalidation and the distinct strong UI font role are covered programmatically. No app launch or screenshot was used; both items remain unchecked for user interaction verification.

22. correctness audit (2026-09-08 compilation controls)

- Item 85: The toolbar now has an explicit Pause/Resume control. Pausing cancels queued automatic work, stops the persistent CLI watcher, suppresses editor-driven Tinymist updates, and leaves one-shot PDF exports and deterministic captures available. Resuming sends the newest editor buffer and restarts whichever preview pipeline is required.
- Item 85: Compile and Cmd+R now materialize the canonical PDF beside the effective saved Typst entry, including a designated preview entry while another file is being edited. Unsaved Typst documents ask for their first output location; Export PDF remains the choose-another-destination command. Compile and Export retain distinct chooser, queued, completion, and cancellation messages, and a second output request can no longer overwrite an already queued destination.
- Item 85: Completing a one-shot Compile or Export while automatic compilation is paused now reaps the temporary watcher again instead of leaving it active after producing the PDF.

- Verification for item 85: Deterministic tests cover pause gating, explicit-build exceptions, watcher shutdown, toggle copy, current/designated output paths, output intent, and unsaved/non-Typst rejection. Formatting, strict Clippy, all 372 non-ignored repository tests, all 7 packaging tests, and the ignored real-typst watcher compile/error/recovery integration test pass. No app launch or screenshot was used; item 85 remains unchecked for user interaction verification.